

Facility ID: 1677130079 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

[Go to Part II for Emissions Unit P023](#)

[Go to Part II for Emissions Unit P906](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 1677130079 Emissions Unit ID: P023 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P023 (Mild Steel Mixer PM-5) blending laundry detergent dry solid components, 1000 lbs/hr maximum process weight rate, particulate emissions (PE) vented to and controlled by a fabric filter/baghouse (Baghouse #3) serving P011, P012, P023, & P902	OAC rule 3745-31-05(A)(3) (PTI 16-023586)	0.33 lb/hr & 1.4 TPY PE (stack emissions)
	OAC rule 3745-17-07(B)(11)(e) OAC rule 3745-17-08(A)	Visible PE from any stack shall not exceed 5% opacity, as a 6-minute average. There shall be no visible PE from building ventilation (i.e., windows, doors, etc.).
	OAC rule 3745-17-07(B)(11)(e) OAC rule 3745-17-08(A)	This facility is not located within an "Appendix A" area, as identified in OAC rule 3745-17-08. Therefore, pursuant to OAC rule 3745-17-08(A) and OAC rule 3745-17-07(B)(11)(e), this emissions unit is exempt from the requirements of OAC rule 3745-17-08(B) and OAC rule 3745-17-07(B). The emissions limitations specified by these rules are less stringent than the emissions limitations established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- (a) The PE mass emissions limits established pursuant to OAC rule 3745-31-05(A)(3) reflect the potential to emit for this emissions unit. Therefore, no monitoring, record keeping, or reporting requirements are necessary to ensure ongoing compliance with the PE emissions limits.

However, the permittee shall apply for and, if required, obtain a final permit to install prior to equipment replacement or any proposed change such as equipment modification that would increase the potential to emit for any air pollutant.

In order to minimize or eliminate visible emissions of fugitive dust (generated from material transfers, material mixers, and any other fugitive dust-generating stationary plant equipment), the permittee shall properly install (or have properly installed), adjust, operate, and maintain a fabric filter/baghouse system (or comparable air pollution control device), associated air pollution control equipment (i.e., hoods, enclosures, ductwork, and fans, etc.), and any other equipment necessary to adequately enclose, contain, capture (with a collection efficiency sufficient to minimize or eliminate visible emissions of fugitive dust at the point(s) of capture), and vent fugitive dust to the air pollution control device serving this emissions unit, in accordance with the manufacturer's recommendations, instructions, and operating manuals, and to the extent possible with good engineering design.

Scrap process materials shall be properly disposed of, and any spillage of process material from the emissions unit, or cleaning/maintenance of the fabric filter/baghouse system and associated air pollution control equipment shall be promptly cleaned up to reduce the risk of fugitive dust emissions. Also, general housekeeping shall be performed, as needed, to reduce the risk of fugitive dust emissions.

B. Operational Restrictions

1. The permittee shall employ the fabric filter/baghouse system and associated air pollution control equipment serving this emissions unit at all times the emissions unit is in operation.
2. Except for an initial operating period after filter media replacement to attain design filtering efficiency, the pressure

drop across the baghouse serving this emissions unit shall be maintained within the following specified range (while the emissions unit is in operation):

Baghouse #3: 1 - 8 inches of water.

Operation of the baghouse outside of its respective pressure drop range is not necessarily indicative of an emission violation, but rather serves as a trigger level for maintenance and/or repair activities, or further investigations to establish corrective action.

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall document all times the fabric filter/baghouse system and/or associated air pollution control equipment serving this emissions unit were/was not employed when the emissions unit was in operation.
2. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse serving this emissions unit, while the emissions unit is in operation. The monitoring equipment shall be calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a daily basis.
3. The permittee shall perform weekly checks, when the emissions unit is in operation and when weather conditions allow, for any visible particulate emissions from the baghouse serving this emissions unit. The presence or absence of any visible particulate emissions from the baghouse shall be noted weekly in an operations log. If visible particulate emissions are observed from the baghouse, the permittee shall also note the following in an operations log:
 - a. the color of the emissions;
 - b. whether the emissions are representative of normal operations;
 - c. if the emissions are not representative of normal operations, the determined cause of the abnormal emissions if a cause can be determined upon investigation;
 - d. the total duration of the visible emissions incident; and
 - e. any corrective actions taken to eliminate the visible emissions.

The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse serving this emissions unit, while the emissions unit is in operation. The monitoring equipment shall be calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a daily basis.
4. The permittee shall perform weekly checks, when the emissions unit is in operation and when weather conditions allow, for any visible emissions of fugitive dust from building ventilation. The presence or absence of any visible emissions of fugitive dust shall be noted weekly in an operations log. If visible emissions of fugitive dust are observed, the permittee shall also note the following in an operations log:
 - a. the color of the emissions;
 - b. whether the emissions are representative of normal operations;
 - c. if the emissions are not representative of normal operations, the determined cause of the abnormal emissions if a cause can be determined upon investigation;
 - d. the total duration of the visible emissions incident; and
 - e. any corrective actions taken to minimize or eliminate the visible emissions.

D. Reporting Requirements

1. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any record in which the fabric filter/baghouse system and/or associated air pollution control equipment serving this emissions unit were/was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.
2. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse serving this emissions unit did not comply with the allowable range specified above. These reports are due by the dates described in Part 1 - General Terms and Conditions of this permit under section (A)(1).
3. The permittee shall submit on a semiannual basis a report which (a) identifies all days during which any visible particulate emissions were observed from the baghouse and (b) describes the corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted by January 31 and July 31 of each year to the Director (District Office or local air agency).
4. The permittee shall submit on a semiannual basis a report which (a) identifies all days during which any visible emissions of fugitive dust were observed from building ventilation and (b) describes the corrective actions taken to minimize or eliminate the visible emissions of fugitive dust. These reports shall be submitted by January 31 and July 31 of each year to the Director (District Office or local air agency).

E. Testing Requirements

1. Compliance with the emission limitations in Section A.1 of these special terms and conditions shall be determined in accordance with the following methods:
 - a. Emissions Limitation: 5% opacity from any stack, as a 6-minute average

Applicable Compliance Method: If required, compliance shall be determined by visible emission evaluations performed in accordance with the methods and procedures specified in OAC rule 3745-17-03(B)(1).
 - b. Emissions Limitations: 0.33 lb/hr & 1.4 TPY PE (stack emissions)

Applicable Compliance Method: The above PE limitations were established as specified in the equations below:

$$H = VO(60 \text{ minutes/hour})(1 \text{ pound}/7000 \text{ grains});$$

$$Y = H(8760 \text{ hours/year})(1 \text{ ton}/2000 \text{ pounds});$$

Where,

H = 0.33 lb/hr PE [hourly controlled potential stack emissions];
 Y = 1.4 TPY PE [yearly controlled potential stack emissions];
 V = 3800 DSCFM [maximum fabric filter exhaust flow]; and
 O = 0.01 grain of PM/DSCF [assumed maximum outlet loading of fabric filter system].

DSCFM = dry standard cubic feet per minute

If required, compliance shall be determined in accordance with the requirements in 40 CFR Part 60, Appendix A, Method 5 and the methods and procedures specified in OAC rule 3745-17-03(B)(10).

F. Miscellaneous Requirements

1. Modeling to demonstrate compliance with the Ohio EPA's "Air Toxic Policy" was not necessary because the emissions unit's maximum annual emissions for each toxic compound will be less than 1.0 ton. OAC Chapter 3745-31 requires permittees to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that changes in the composition of the materials, or use of new materials, that would cause the emissions of any pollutant that has a listed TLV to increase to above 1.0 ton per year may require the permittee to apply for and obtain a new permit to install.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 1677130079 Emissions Unit ID: P906 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P906 (Pelletizer #2) conversion of powdered final product into tableted final product, 250 lbs/hr maximum process weight rate, particulate emissions (PE) vented to and controlled by a fabric filter/baghouse (Local Bag Filter)	OAC rule 3745-31-05(A)(3) (PTI 16-02386)	0.33 lb/hr & 1.4 TPY PE (stack emissions)
	OAC rule 3745-17-07(B)(11)(e) OAC rule 3745-17-08(A)	Visible PE from any stack shall not exceed 5% opacity, as a 6-minute average. There shall be no visible PE from building ventilation (i.e., windows, doors, etc.).
	OAC rule 3745-17-07(A) OAC rule 3745-17-11(B)	This facility is not located within an "Appendix A" area, as identified in OAC rule 3745-17-08. Therefore, pursuant to OAC rule 3745-17-08(A) and OAC rule 3745-17-07(B)(11)(e), this emissions unit is exempt from the requirements of OAC rule 3745-17-08(B) and OAC rule 3745-17-07(B). The emissions limitations specified by these rules are less stringent than the emissions limitations established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- (a) The PE mass emissions limits established pursuant to OAC rule 3745-31-05(A)(3) reflect the potential to emit for this emissions unit. Therefore, no monitoring, record keeping, or reporting requirements are necessary to ensure ongoing compliance with the PE emissions limits.

However, the permittee shall apply for and, if required, obtain a final permit to install prior to equipment replacement or any proposed change such as equipment modification that would increase the potential to emit for any air pollutant.
In order to minimize or eliminate visible emissions of fugitive dust (generated from material transfers, material mixers, and any other fugitive dust-generating stationary plant equipment), the permittee shall properly install (or have properly installed), adjust, operate, and maintain a fabric filter/baghouse system (or comparable air pollution control device), associated air pollution control equipment (i.e.,

hoods, enclosures, ductwork, and fans, etc.), and any other equipment necessary to adequately enclose, contain, capture (with a collection efficiency sufficient to minimize or eliminate visible emissions of fugitive dust at the point(s) of capture), and vent fugitive dust to the air pollution control device serving this emissions unit, in accordance with the manufacturer's recommendations, instructions, and operating manuals, and to the extent possible with good engineering design.

Scrap process materials shall be properly disposed of, and any spillage of process material from the emissions unit, or cleaning/maintenance of the fabric filter/baghouse system and associated air pollution control equipment shall be promptly cleaned up to reduce the risk of fugitive dust emissions. Also, general housekeeping shall be performed, as needed, to reduce the risk of fugitive dust emissions.

B. Operational Restrictions

1. The permittee shall employ the fabric filter/baghouse system and associated air pollution control equipment serving this emissions unit at all times the emissions unit is in operation.
2. Except for an initial operating period after filter media replacement to attain design filtering efficiency, the pressure drop across the baghouse serving this emissions unit shall be maintained within the following specified range (while the emissions unit is in operation):

Local Bag Filter: 1 - 8 inches of water.

Operation of the baghouse outside of its respective pressure drop range is not necessarily indicative of an emission violation, but rather serves as a trigger level for maintenance and/or repair activities, or further investigations to establish corrective action.

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall document all times the fabric filter/baghouse system and/or associated air pollution control equipment serving this emissions unit were/was not employed when the emissions unit was in operation.
2. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse serving this emissions unit, while the emissions unit is in operation. The monitoring equipment shall be calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a daily basis.
3. The permittee shall perform weekly checks, when the emissions unit is in operation and when weather conditions allow, for any visible particulate emissions from the baghouse serving this emissions unit. The presence or absence of any visible particulate emissions from the baghouse shall be noted weekly in an operations log. If visible particulate emissions are observed from the baghouse, the permittee shall also note the following in an operations log:
 - a. the color of the emissions;
 - b. whether the emissions are representative of normal operations;
 - c. if the emissions are not representative of normal operations, the determined cause of the abnormal emissions if a cause can be determined upon investigation;
 - d. the total duration of the visible emissions incident; and
 - e. any corrective actions taken to eliminate the visible emissions.
4. The permittee shall perform weekly checks, when the emissions unit is in operation and when weather conditions allow, for any visible emissions of fugitive dust from building ventilation. The presence or absence of any visible emissions of fugitive dust shall be noted weekly in an operations log. If visible emissions of fugitive dust are observed, the permittee shall also note the following in an operations log:
 - a. the color of the emissions;
 - b. whether the emissions are representative of normal operations;
 - c. if the emissions are not representative of normal operations, the determined cause of the abnormal emissions if a cause can be determined upon investigation;
 - d. the total duration of the visible emissions incident; and
 - e. any corrective actions taken to minimize or eliminate the visible emissions.

D. Reporting Requirements

1. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any record in which the fabric filter/baghouse system and/or associated air pollution control equipment serving this emissions unit were/was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.
2. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse serving this emissions unit did not comply with the allowable range specified above. These reports are due by the dates described in Part 1 - General Terms and Conditions of this permit under section (A)(1).
3. The permittee shall submit on a semiannual basis a report which (a) identifies all days during which any visible particulate emissions were observed from the baghouse and (b) describes the corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted by January 31 and July 31 of each year to the Director (District Office or local air agency).
4. The permittee shall submit on a semiannual basis a report which (a) identifies all days during which any visible emissions of fugitive dust were observed from building ventilation and (b) describes the corrective actions taken to minimize or eliminate the visible emissions of fugitive dust. These reports shall be submitted by January 31 and July 31 of each year to the Director (District Office or local air agency).

E. Testing Requirements

1. Compliance with the emission limitations in Section A.1 of these special terms and conditions shall be determined in accordance with the following methods:
 - a. Emissions Limitation: 5% opacity from any stack, as a 6-minute average

Applicable Compliance Method: If required, compliance shall be determined by visible emission evaluations performed in accordance with the methods and procedures specified in OAC rule 3745-17-03(B)(1).

b. Emissions Limitations: 0.33 lb/hr & 1.4 TPY PE (stack emissions)

Applicable Compliance Method: The above PE limitations were established as specified in the equations below:

$H = VO(60 \text{ minutes/hour})(1 \text{ pound}/7000 \text{ grains});$
 $Y = H(8760 \text{ hours/year})(1 \text{ ton}/2000 \text{ pounds});$

Where,

$H = 0.33 \text{ lb/hr PE [hourly controlled potential stack emissions];}$
 $Y = 1.4 \text{ TPY PE [yearly controlled potential stack emissions];}$
 $V = 3800 \text{ DSCFM [maximum fabric filter exhaust flow]; and}$
 $O = 0.01 \text{ grain of PM/DSCF [assumed maximum outlet loading of fabric filter system].}$

DSCFM = dry standard cubic feet per minute

If required, compliance shall be determined in accordance with the requirements in 40 CFR Part 60, Appendix A, Method 5 and the methods and procedures specified in OAC rule 3745-17-03(B)(10).

F. Miscellaneous Requirements

1. Modeling to demonstrate compliance with the Ohio EPA's "Air Toxic Policy" was not necessary because the emissions unit's maximum annual emissions for each toxic compound will be less than 1.0 ton. OAC Chapter 3745-31 requires permittees to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that changes in the composition of the materials, or use of new materials, that would cause the emissions of any pollutant that has a listed TLV to increase to above 1.0 ton per year may require the permittee to apply for and obtain a new permit to install.