State of Ohio Environmental Protection Agency

STREET ADDRESS:
Lazarus Government Center
50 W. Town St., Suite 700
Columbus, Ohio 43215

TELE: (614) 644-3020 FAX: (614) 644-3184
www.epa.state.oh.us

MAILING ADDRESS:
P.O. Box 1049
Columbus, OH 43216-1049

9/5/2008

Certified Mail
Facility ID: 0575010106
Permit Number: P0088868
County: Shelby

Michael Wittman
American Trim L.L.C.
1501 West Michigan Street
Sidney, OH 45365-2490

RE: PRELIMINARY PROPOSED AIR POLLUTION TITLE V PERMIT
Permit Type: Initial

Dear Permit Holder:

Enclosed is the Ohio EPA Preliminary Proposed Title V permit that was issued in draft form on 6/11/2008. The comment period for the Draft permit has ended. We are now ready to submit this permit to U.S. EPA for approval.

We are submitting this for your review and comment. If you do not agree with the Preliminary Proposed Title V permit as written, you now have the opportunity to raise your concerns. This permit has been posted to the Division of Air Pollution Control (DAPC) Web page http://www.epa.state.oh.us/dapc in Microsoft Word and Adobe Acrobat format. Comments will be accepted as a marked-up copy of the permit or in narrative format. Any comments must be sent to the following within 14 days of your receipt of this letter:

Andrew Hall
Permit Review/Development Section
Ohio EPA, DAPC
50 West Town Street, Suite 700
Columbus, Ohio 43215

and

Ohio EPA DAPC, Southwest District Office
401 East Fifth Street
Dayton, OH 45402

If you believe that it is necessary to have an informal conference with us, then, as part of your written comments, you should request a conference concerning the written comments.

If comments are not submitted within 14 days of your receipt of this letter, we will forward the proposed permit to U.S. EPA for approval. All comments received will be carefully considered before proceeding with the proposed permit.

Sincerely,

Michael W. Ahern

Michael W. Ahern, Manager
Permit Issuance and Data Management Section, DAPC

Cc: Ohio EPA DAPC, Southwest District Office

State of Ohio Environmental Protection Agency
Division of Air Pollution Control

PRELIMINARY PROPOSED

Air Pollution Title V Permit
for
American Trim L.L.C.

Facility ID: 0575010106
Permit Number: P0088868
Permit Type: Initial
Issued: 9/5/2008
Effective: To be entered upon final issuance
Expiration: To be entered upon final issuance

State of Ohio Environmental Protection Agency
Division of Air Pollution Control

Air Pollution Title V Permit
for
American Trim L.L.C.

Table of Contents

Authorization 1
A. Standard Terms and Conditions 2
1. Federally Enforceable Standard Terms and Conditions 3
2. Monitoring and Related Record Keeping and Reporting Requirements 3
3. Scheduled Maintenance 6
4. Risk Management Plans 6
5. Title IV Provisions 6
6. Severability Clause 7
7. General Requirements 7
8. Fees 8
9. Marketable Permit Programs 8
10. Reasonably Anticipated Operating Scenarios 8
11. Reopening for Cause 8
12. Federal and State Enforceability 9
13. Compliance Requirements 9
14. Permit Shield 10
15. Operational Flexibility 10
16. Emergencies 11
17. Off-Permit Changes 11
18. Compliance Method Requirements 12
19. Insignificant Activities or Emissions Levels 12
20. Permit to Install Requirement 12
21. Air Pollution Nuisance 12
22. Permanent Shutdown of an Emissions Unit 12
23. Title VI Provisions 13
24. Reporting Requirements Related to Monitoring and Record Keeping Requirements Under State Law Only 13
25. Records Retention Requirements Under State Law Only 14
26. Inspections and Information Requests 14
27. Scheduled Maintenance/Malfunction Reporting 14
28. Permit Transfers 14
29. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations 14

B. Facility-Wide Terms and Conditions 16
C. Emissions Unit Terms and Conditions 18
1. B001, Bumper 200 AMU 19
2. K005, Coating/Printing Press C-5 22
3. K006, Coating/Printing Press C-4 29
4. K007, Coating/Printing Press C-3 37
5. K008, Coating/Printing Press C-2 45
6. K009, Coating/Printing Press C-1 53
7. K022, A-Line Screen Presses 61
8. K033, B-Line Screen Presses 69
9. K045, Roll Coater; Department 347 77
10. K046, E-coat Line 85
11. K048, Dept 350 93
12. P081, Stamping Press 1-269 101
13. P082, Stamping Press 1-082 106
14. P085, Stamping Press 1-213 111
15. P086, Stamping Press 1-247 116
16. P087, Stamping Press 1-087 121
17. P088, Stamping Press 1-088 126
18. P089, Stamping Press 1-248 131
19. P090, Stamping Press 1-249 136
20. P091, Stamping Press 1-091 141
21. P092, Stamping Press 1-251 146
22. P093, Stamping Press 1-252 151
23. P094, Stamping Press 1-253 156
24. P095, Stamping Press 1-272 161
25. P096, Stamping Press 1- 276 166
26. P097, Stamping Press 1- 278 171
27. P098, Stamping Press 1-279 176
28. P099, Stamping Press 1-280 181
29. P100, Stamping Press 1-286 186
30. P101, Stamping Press 1-291 191
31. P102, Stamping Press 1-292 196
32. P103, Stamping Press 1-293 201
33. P104, Stamping Press 1-299 206
34. P105, Rollformer 7-141 211

35. P106, Rollformer 7-240 216
36. P107, Stamping Press 1-261 221
37. P108, Stamping Press 1-266 225
38. P109, Stamping Press 1-267 229
39. P110, Stamping Press 1-290 233
40. P111, Stamping Press 1-301 237
41. P112, Stamping Press 1-302 241
42. P113, Stamping Press 1-227 245
43. P114, Stamping Press 1-237 249
44. P115, Screen Washer A 253
45. P116, Screen Washer B 258
46. P117, Stamping Press 1-001 263
47. P118, Stamping Press 1-002 267
48. P119, Stamping Press 1-003 271
49. P120, Stamping Press 1-014 275
50. P121, Stamping Press 1-025 279
51. P122, Stamping Press 1-026 283
52. P123, Stamping Press 1-034 287
53. P124, Stamping Press 1-048 291
54. P125, Stamping Press 1-052 295
55. P126, Stamping Press 1-81 299
56. P127, Stamping Press 1-89 303
57. P128, Stamping Press 1-90 307
58. P129, Stamping Press 1-92 311
59. P130, Stamping Press 1-93 315
60. P131, Stamping Press 1-126 319
61. P132, Stamping Press 1-127 323
62. P133, Stamping Press 1-128 327
63. P134, Stamping Press 1-129 331
64. P135, Stamping Press 1-131 335
65. P136, Stamping Press 1-132 339
66. P137, Stamping Press 1-133 343
67. P138, Stamping Press 1-138 347
68. P139, Stamping Press 1-214 351
69. P140, Stamping Press 1-250 355

Authorization

Facility ID: 0575010106
Facility Description: American Trim, LLC, Sidney facility manufactures decorative and transportation products for appliance and automotive industries.
Application Number(s): A0020083, A0020084, A0020085, A0020086
Permit Number: P0088868
Permit Description: Initial Title V for coating and processes
Permit Type: Initial
Issue Date: 9/5/2008
Effective Date: To be entered upon final issuance
Expiration Date: To be entered upon final issuance
Superseded Permit Number:

This document constitutes issuance of an OAC Chapter 3745-77 Title V permit to:

American Trim L.L.C.
1501 West Michigan Street
Sidney, OH 45365-2490

Ohio EPA District Office or local air agency responsible for processing and administering your permit:

Ohio EPA DAPC, Southwest District Office
401 East Fifth Street
Dayton, OH 45402
(937)285-6357

The above named entity is hereby granted a Title V permit pursuant to Chapter 3745-77 of the Ohio Administrative Code. This permit and the authorization to operate the air contaminant sources (emissions units) at this facility shall expire at midnight on the expiration date shown above. You will be sent a notice approximately 18 months prior to the expiration date regarding the renewal of this permit. If you do not receive a notice, please contact the Ohio EPA DAPC, Southwest District Office. If a renewal permit is not issued prior to the expiration date, the permittee may continue to operate pursuant to OAC rule 3745-77-08(E) and in accordance with the terms of this permit beyond the expiration date, if a timely renewal application is submitted. A renewal application will be considered timely if it is submitted no earlier than 18 months (540 days) and no later than 6 months (180 days) prior to the expiration date.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Chris Korleski
Director

A. Standard Terms and Conditions

1. Federally Enforceable Standard Terms and Conditions

a) All Standard Terms and Conditions are federally enforceable, with the exception of those listed below which are enforceable under State law only:

(1) Standard Term and Condition A. 24., Reporting Requirements Related to Monitoring and Record Keeping Requirements of State-Only Enforceable Permit Terms and Conditions

(2) Standard Term and Condition A. 25., Records Retention Requirements for State-Only Enforceable Permit Terms and Conditions

(3) Standard Term and Condition A. 27., Scheduled Maintenance/Malfunction Reporting

(4) Standard Term and Condition A. 29., Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations
(Authority for term: ORC 3704.036(A))

2. Monitoring and Related Record Keeping and Reporting Requirements

a) Except as may otherwise be provided in the terms and conditions for a specific emissions unit (i.e., in section C. Emissions Unit Terms and Conditions of this Title V permit), the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:

(1) The date, place (as defined in the permit), and time of sampling or measurements.

(2) The date(s) analyses were performed.

(3) The company or entity that performed the analyses.

(4) The analytical techniques or methods used.

(5) The results of such analyses.

(6) The operating conditions existing at the time of sampling or measurement.
(Authority for term: OAC rule 3745-77-07(A)(3)(b)(i))

b) Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.
(Authority for term: OAC rule 3745-77-07(A)(3)(b)(ii))

c) The permittee shall submit required reports in the following manner:

(1) All reporting required in accordance with OAC rule 3745-77-07(A)(3)(c) for deviations caused by malfunctions shall be submitted in the following manner:

Any malfunction, as defined in OAC rule 3745-15-06(B)(1), shall be promptly reported to the Ohio EPA in accordance with OAC rule 3745-15-06. In addition, to fulfill the OAC rule 3745-77-07(A)(3)(c) deviation reporting requirements for malfunctions, written reports that identify each malfunction that occurred during each calendar quarter (including each malfunction reported only verbally in accordance with OAC rule 3745-15-06) shall be submitted (i.e., postmarked) by January 31, April 30, July 31, and October 31 of each year in accordance with Standard Term and Condition A.2.c)(2) below; and each report shall cover the previous calendar quarter. An exceedance of the visible emission limitations specified in OAC rule 3745-17-07(A)(1) that is caused by a malfunction is not a violation and does not need to be reported as a deviation if the owner or operator of the affected air contaminant source or air pollution control equipment complies with the requirements of OAC rule 3745-17-07(A)(3)(c).

In accordance with OAC rule 3745-15-06, a malfunction reportable under OAC rule 3745-15-06(B) constitutes a violation of an emission limitation (or control requirement) and, therefore, is a deviation of the federally enforceable permit requirements. Even though verbal notifications and written reports are required for malfunctions pursuant to OAC rule 3745-15-06, the written reports required pursuant to this term must be submitted quarterly to satisfy the prompt reporting provision of OAC rule 3745-77-07(A)(3)(c).

In identifying each deviation caused by a malfunction, the permittee shall specify the emission limitation(s) (or control requirement(s)) for which the deviation occurred, describe each deviation, and provide the magnitude and duration of each deviation. For a specific malfunction, if this information has been provided in a written report that was submitted in accordance with OAC rule 3745-15-06, the permittee may simply reference that written report to identify the deviation. Nevertheless, all malfunctions, including those reported only verbally in accordance with OAC rule 3745-15-06, must be reported in writing on a quarterly basis.

Any scheduled maintenance, as referenced in OAC rule 3745-15-06(A)(1), that results in a deviation from a federally enforceable emission limitation (or control requirement) shall be reported in the same manner as described above for malfunctions.

(Authority for term: OAC rule 3745-77-07(A)(3)(c))

(2) Except as may otherwise be provided in the terms and conditions for a specific emissions unit (i.e., in section C. Emissions Unit Terms and Conditions of this Title V permit or, in some cases, in section B. Facility-Wide Terms and Conditions of this Title V permit), all reporting required in accordance with OAC rule 3745-77-07(A)(3)(c) for deviations of the emission limitations, operational restrictions, and control device operating parameter limitations shall be submitted in the following manner:

Written reports of (a) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures taken, shall be promptly made to the appropriate Ohio EPA District Office or local air agency. Except as provided below, the written reports shall be submitted (i.e., postmarked) by January 31, April 30, July 31, and October 31 of each year; and each report shall cover the previous calendar quarter.

In identifying each deviation, the permittee shall specify the emission limitation(s), operational restriction(s), and/or control device operating parameter limitation(s) for which the deviation occurred, describe each deviation, and provide the estimated magnitude and duration of each deviation.

These written deviation reports shall satisfy the requirements of OAC rule 3745-77-07(A)(3)(c) pertaining to the submission of monitoring reports every six months and to the prompt reporting of all deviations. Full compliance with OAC rule 3745-77-07(A)(3)(c) requires reporting of all other deviations of the federally enforceable requirements specified in the permit as required by such rule.

If an emissions unit has a deviation reporting requirement for a specific emission limitation, operational restriction, or control device operating parameter limitation that is not on a quarterly basis (e.g., within 30 days following the end of the calendar month, or within 30 or 45 days after the exceedance occurs), that deviation reporting requirement satisfies the reporting requirements specified in this Standard Term and Condition for that specific emission limitation, operational restriction, or control device parameter limitation. Following the provisions of that non-quarterly deviation reporting requirement will also satisfy (for the deviations so reported) the requirements of OAC rule 3745-77-07(A)(3)(c) pertaining to the submission of monitoring reports every six months and to the prompt reporting of all deviations, and additional quarterly deviation reports for that specific emission limitation, operational restriction, or control device parameter limitation are not required pursuant to this Standard Term and Condition.

See A.29 below if no deviations occurred during the quarter.
(Authority for term: OAC rule 3745-77-07(A)(3)(c))

(3) All reporting required in accordance with the OAC rule 3745-77-07(A)(3)(c) for other deviations of the federally enforceable permit requirements which are not reported in accordance with Standard Term and Condition A.2)c)(2) above shall be submitted in the following manner:

Unless otherwise specified by rule, written reports that identify deviations of the following federally enforceable requirements contained in this permit; Standard Terms and Conditions: A.3, A.4, A.5, A.7.e), A.8, A.13, A.15, A.19, A.20, A.21, and A.23 of this Title V permit, as well as any deviations from the requirements in section C. Emissions Unit Terms and Conditions of this Title V permit, and any monitoring, record keeping, and reporting requirements, which are not reported in accordance with Standard Term and Condition A.2.c)(2) above shall be submitted (i.e., postmarked) to the appropriate Ohio EPA District Office or local air agency by January 31 and July 31 of each year; and each report shall cover the previous six calendar months. Unless otherwise specified by rule, all other deviations from federally enforceable requirements identified in this permit shall be submitted annually as part of the annual compliance certification, including deviations of federally enforceable requirements not specifically addressed by permit or rule for the insignificant activities or emissions levels (IEU) identified in section B. Facility-Wide Terms and Conditions of this Title V permit. Annual reporting of deviations is deemed adequate to meet the deviation reporting requirements for IEUs unless otherwise specified by permit or rule.

In identifying each deviation, the permittee shall specify the federally enforceable requirement for which the deviation occurred, describe each deviation, and provide the magnitude and duration of each deviation.

These semi-annual and annual written reports shall satisfy the reporting requirements of OAC rule 3745-77-07(A)(3)(c) for any deviations from the federally enforceable requirements contained in this permit that are not reported in accordance with Standard Term and Condition A.2.c)(2) above.

If no such deviations occurred during a six-month period, the permittee shall submit a semi-annual report which states that no such deviations occurred during that period.
(Authority for term: OAC rules 3745-77-07(A)(3)(c)(i) and (ii) and OAC rule 3745-77-07(A)(13)(b))

(4) Each written report shall be signed by a responsible official certifying that, "based on information and belief formed after reasonable inquiry, the statements and information in the report (including any written malfunction reports required by OAC rule 3745-15-06 that are referenced in the deviation reports) are true, accurate, and complete."
(Authority for term: OAC rule 3745-77-07(A)(3)(c)(iv))

(5) Reports of any required monitoring and/or record keeping information shall be submitted to Ohio EPA DAPC, Southwest District Office.
(Authority for term: OAC rule 3745-77-07(A)(3)(c))

3. Scheduled Maintenance

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. Except as provided in OAC rule 3745-15-06(A)(3), any scheduled maintenance necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s). Any scheduled maintenance, as defined in OAC rule 3745-15-06(A)(1), that results in a deviation from a federally enforceable emission limitation (or control requirement) shall be reported in the same manner as described for malfunctions in Standard Term and Condition A.2.c)(1) above.
(Authority for term: OAC rule 3745-77-07(A)(3)(c))

4. Risk Management Plans

If applicable, the permittee shall develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. § 7401 et seq. ("Act"); and, pursuant to 40 C.F.R. 68.215(a), the permittee shall submit either of the following:

a) a compliance plan for meeting the requirements of 40 C.F.R. Part 68 by the date specified in 40 C.F.R. 68.10(a) and OAC 3745-104-05(A); or

b) as part of the compliance certification submitted under 40 C.F.R. 70.6(c)(5), a certification statement that the source is in compliance with all requirements of 40 C.F.R. Part 68 and OAC Chapter 3745-104, including the registration and submission of the risk management plan.

(Authority for term: OAC rule 3745-77-07(A)(4))

5. Title IV Provisions

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.
(Authority for term: OAC rule 3745-77-07(A)(5))

6. Severability Clause

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition declared invalid.
(Authority for term: OAC rule 3745-77-07(A)(6))

7. General Requirements

a) The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and reissuance, or modification, or for denial of a permit renewal application.

b) It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.

c) This permit may be modified, reopened, revoked, or revoked and reissued, for cause, in accordance with Standard Term and Condition A.11 below. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.

d) This permit does not convey any property rights of any sort, or any exclusive privilege.

e) The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

f) Except as otherwise indicated below, this Title V permit, or permit modification, is effective for five years from the original effective date specified in the permit. In the event that this facility becomes eligible for non-title V permits, this permit shall cease to be enforceable when:

   (1) the permittee submits an approved facility-wide potential to emit analysis supporting a claim that the facility no longer meets the definition of a "major source" as defined in OAC rule 3745-77-01(W) based on the permanent shutdown and removal of one or more emissions units identified in this permit; or

   (2) the permittee no longer meets the definition of a "major source" as defined in OAC rule 3745-77-01(W) based on obtaining restrictions on the facility-wide potential(s) to emit that are federally enforceable or legally and practically enforceable ; or

   (3) a combination of (1) and (2) above.

The permittee shall continue to comply with all applicable OAC Chapter 3745-31 requirements for all regulated air contaminent sources once this permit ceases to be enforceable. The permittee shall comply with any residual requirements, such as quarterly deviation reports, semi-annual deviation reports, and annual compliance certifications covering the period during which this Title V permit was enforceable. All records relating to this permit must be maintained in accordance with law.
(Authority for term: OAC rule 3745-77-01(W), OAC rule 3745-77-07(A)(3)(b)(ii), OAC rule 3745-77(A)(7))

8. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78.
(Authority for term: OAC rule 3745-77-07(A)(8))

9. Marketable Permit Programs

No revision of this permit is required under any approved economic incentive, marketable permits, emissions trading, and other similar programs or processes for changes that are provided for in this permit.
(Authority for term: OAC rule 3745-77-07(A)(9))

10. Reasonably Anticipated Operating Scenarios

The permittee is hereby authorized to make changes among operating scenarios authorized in this permit without notice to the Ohio EPA, but, contemporaneous with making a change from one operating scenario to another, the permittee must record in a log at the permitted facility the scenario under which the permittee is operating. The permit shield provided in these standard terms and conditions shall apply to all operating scenarios authorized in this permit.
(Authority for term: OAC rule 3745-77-07(A)(10))

11. Reopening for Cause

This Title V permit will be reopened prior to its expiration date under the following conditions:

a) Additional applicable requirements under the Act become applicable to one or more emissions units covered by this permit, and this permit has a remaining term of three or more years. Such a reopening shall be completed not later than eighteen (18) months after promulgation of the applicable requirement. No such reopening is required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions has been extended pursuant to paragraph (E)(1) of OAC rule 3745-77-08.

b) This permit is issued to an affected source under the acid rain program and additional requirements (including excess emissions requirements) become applicable. Upon approval by the Administrator, excess emissions offset plans shall be deemed to be incorporated into the permit, and shall not require a reopening of this permit.

c) The Director of the Ohio EPA or the Administrator of the U.S. EPA determines that the federally applicable requirements in this permit are based on a material mistake, or that inaccurate statements were made in establishing the emissions standards or other terms and conditions of this permit related to such federally applicable requirements.

d) The Administrator of the U.S. EPA or the Director of the Ohio EPA determines that this permit must be revised or revoked to assure compliance with the applicable requirements.

(Authority for term: OAC rules 3745-77-07(A)(12) and 3745-77-08(D))

12. Federal and State Enforceability

Only those terms and conditions designated in this permit as federally enforceable, that are required under the Act, or any of its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA, the State, and citizens under the Act. All other terms and conditions of this permit shall not be federally enforceable and shall be enforceable under State law only.
(Authority for term: OAC rule 3745-77-07(B))

13. Compliance Requirements

a) Any document (including reports) required to be submitted and required by a federally applicable requirement in this Title V permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.

b) Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:

(1) At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.

(2) Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with paragraph (E) of OAC rule 3745-77-03.

(3) Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.

(4) As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.

c) The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:

(1) Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.

(2) An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

d) Compliance certifications concerning the terms and conditions contained in this permit that are federally enforceable emission limitations, standards, or work practices, shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) and the Administrator of the U.S. EPA in the following manner and with the following content:

(1) Compliance certifications shall be submitted annually on a calendar year basis. The annual certification shall be submitted (i.e., postmarked) on or before April 30th of each year during the permit term.

(2) Compliance certifications shall include the following:

(a) An identification of each term or condition of this permit that is the basis of the certification.

(b) The permittee's current compliance status.

(c) Whether compliance was continuous or intermittent.

(d) The method(s) used for determining the compliance status of the source currently and over the required reporting period.

(e) Such other facts as the Director of the Ohio EPA may require in the permit to determine the compliance status of the source.

(3) Compliance certifications shall contain such additional requirements as may be specified pursuant to sections 114(a)(3) and 504(b) of the Act.

(Authority for term: OAC rules 3745-77-07(C)(1),(2),(4) and (5) and ORC section 3704.03(L))

14. Permit Shield

a) Compliance with the terms and conditions of this permit (including terms and conditions established for alternate operating scenarios, emissions trading, and emissions averaging, but excluding terms and conditions for which the permit shield is expressly prohibited under OAC rule 3745-77-07) shall be deemed compliance with the applicable requirements identified and addressed in this permit as of the date of permit issuance.

b) This permit shield provision shall apply to any requirement identified in this permit pursuant to OAC rule 3745-77-07(F)(2), as a requirement that does not apply to the source or to one or more emissions units within the source.

(Authority for term: OAC rule 3745-77-07(F))

15. Operational Flexibility

The permittee is authorized to make the changes identified in OAC rule 3745-77-07(H)(1)(a) to (H)(1)(c) within the permitted stationary source without obtaining a permit revision, if such change is not a modification under any provision of Title I of the Act [as defined in OAC rule 3745-77-01(JJ)], and does

not result in an exceedance of the emissions allowed under this permit (whether expressed therein as a rate of emissions or in terms of total emissions), and the permittee provides the Administrator of the U.S. EPA and the appropriate Ohio EPA District Office or local air agency with written notification within a minimum of seven days in advance of the proposed changes, unless the change is associated with, or in response to, emergency conditions. If less than seven days notice is provided because of a need to respond more quickly to such emergency conditions, the permittee shall provide notice to the Administrator of the U.S. EPA and the appropriate District Office of the Ohio EPA or local air agency as soon as possible after learning of the need to make the change. The notification shall contain the items required under OAC rule 3745-77-07(H)(2)(d).
(Authority for term: OAC rules 3745-77-07(H)(1) and (2))

16. Emergencies

The permittee shall have an affirmative defense of emergency to an action brought for noncompliance with technology-based emission limitations if the conditions of OAC rule 3745-77-07(G)(3) are met. This emergency defense provision is in addition to any emergency or upset provision contained in any applicable requirement.
(Authority for term: OAC rule 3745-77-07(G))

17. Off-Permit Changes

The owner or operator of a Title V source may make any change in its operations or emissions at the source that is not specifically addressed or prohibited in the Title V permit, without obtaining an amendment or modification of the permit, provided that the following conditions are met:

a) The change does not result in conditions that violate any applicable requirements or that violate any existing federally enforceable permit term or condition.

b) The permittee provides contemporaneous written notice of the change to the Director and the Administrator of the U.S. EPA, except that no such notice shall be required for changes that qualify as insignificant emissions levels or activities as defined in OAC rule 3745-77-01(U). Such written notice shall describe each such change, the date of such change, any change in emissions or pollutants emitted, and any federally applicable requirement that would apply as a result of the change.

c) The change shall not qualify for the permit shield under OAC rule 3745-77-07(F).

d) The permittee shall keep a record describing all changes made at the source that result in emissions of a regulated air pollutant subject to an applicable requirement, but not otherwise regulated under the permit, and the emissions resulting from those changes.

e) The change is not subject to any applicable requirement under Title IV of the Act or is not a modification under any provision of Title I of the Act.

Paragraph (I) of rule 3745-77-07 of the Administrative Code applies only to modification or amendment of the permittee's Title V permit. The change made may require a permit-to-install under Chapter 3745-31 of the Administrative Code if the change constitutes a modification as defined in that Chapter. Nothing in paragraph (I) of rule 3745-77-07 of the Administrative Code shall affect any applicable obligation under Chapter 3745-31 of the Administrative Code.

(Authority for term: OAC rule 3745-77-07(I))

18. Compliance Method Requirements

Nothing in this permit shall alter or affect the ability of any person to establish compliance with, or a violation of, any applicable requirement through the use of credible evidence to the extent authorized by law. Nothing in this permit shall be construed to waive any defenses otherwise available to the permittee, including but not limited to, any challenge to the Credible Evidence Rule (see 62 Fed. Reg. 8314, Feb. 24, 1997), in the context of any future proceeding.
(This term is provided for informational purposes only.)

19. Insignificant Activities or Emissions Levels

Each IEU that has one or more applicable requirements shall comply with those applicable requirements.
(Authority for term: OAC rule 3745-77-07(A)(1))

20. Permit to Install Requirement

Prior to the "installation" or "modification" of any "air contaminant source," as those terms are defined in OAC rule 3745-31-01, a permit to install must be obtained from the Ohio EPA pursuant to OAC Chapter 3745-31.
(Authority for term: OAC rule 3745-77-07(A)(1))

21. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.
(Authority for term: OAC rule 3745-77-07(A)(1))

22. Permanent Shutdown of an Emissions Unit

The permittee may notify Ohio EPA of any emissions unit that is permanently shut down by submitting a certification from the responsible official that identifies the date on which the emissions unit was permanently shut down. Authorization to operate the affected emissions unit shall cease upon the date certified by the responsible official that the emissions unit was permanently shut down.

After the date on which an emissions unit is permanently shut down (i.e., that has been physically removed from service or has been altered in such a way that it can no longer operate without a subsequent "modification" or "installation" as defined in OAC Chapter 3745-31 and therefore ceases to meet the definition of an "emissions unit" as defined in OAC rule 3745-77-01(O)), rendering existing permit terms and conditions irrelevant, the permittee shall not be required, after the date of the certification and submission to Ohio EPA, to meet any Title V permit requirements applicable to that emissions unit, except for any residual requirements, such as the quarterly deviation reports, semi-annual deviation reports and annual compliance certification covering the period during which the

emissions unit last operated. All records relating to the shutdown emissions unit, generated while the emissions unit was in operation, must be maintained in accordance with law.

No emissions unit certified by the responsible official as being permanently shut down may resume operation without first applying for and obtaining a permit to install pursuant to OAC Chapter 3745-31.
(Authority for term: OAC rule 3745-77-01)

23. Title VI Provisions

If applicable, the permittee shall comply with the standards for recycling and reducing emissions of ozone depleting substances pursuant to 40 CFR Part 82, Subpart F, except as provided for motor vehicle air conditioners in Subpart B of 40 CFR Part 82:

a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices specified in 40 CFR 82.156.

b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment specified in 40 CFR 82.158.

c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

(Authority for term: OAC rule 3745-77-01(H)(11))

24. Reporting Requirements Related to Monitoring and Record Keeping Requirements Under State Law Only

The permittee shall submit required reports in the following manner:

a) Reports of any required monitoring and/or record keeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.

b) Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (i) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and record keeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. In identifying each deviation, the permittee shall specify the applicable requirement for which the deviation occurred, describe each deviation, and provide the magnitude and duration of each deviation. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted (i.e., postmarked) quarterly, by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

25. Records Retention Requirements Under State Law Only

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

26. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.
(Authority for term: OAC rule 3745-77-07(C))

27. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

28. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.
(Authority for term: OAC rule 3745-77-01(C))

29. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations

If no emission limitation (or control requirement), operational restriction and/or control device parameter limitation deviations occurred during a calendar quarter, the permittee shall submit a quarterly report,

which states that no deviations occurred during that quarter. The reports shall be submitted (i.e., postmarked) by January 31, April 30, July 31, and October 31 of each year; and each report shall cover the previous calendar quarter.

The permittee is not required to submit a quarterly report which states that no deviations occurred during that quarter for the following situations:

a) where an emissions unit has deviation reporting requirements for a specific emission limitation, operational restriction, or control device parameter limitation that override the deviation reporting requirements specified in Standard Term and Condition A.2.c)(2); or

b) where an uncontrolled emissions unit has no monitoring, record keeping, or reporting requirements and the emissions unit's applicable emission limitations are established at the potentials to emit; or

c) where the company's responsible official has certified that an emissions unit has been permanently shut down.

B. Facility-Wide Terms and Conditions

1. All the following facility-wide terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only:

   a) None.

C. Emissions Unit Terms and Conditions

1. B001, Bumper 200 AMU

Operations, Property and/or Equipment Description:

Bumper 200 Air Makeup Unit (12.375 mmBtu); air makeup

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) PTI 05-13323	Visible PE shall not exceed 10% opacity as a 6-minute average. The particulate emissions shall not exceed 0.020 pound per million Btu of actual heat input. Emission Limitations: 0.09 lb/hr and 0.4 TPY PE 0.21 lb/hr and 0.91 TPY SO2 2.57 lb/hr and 11.26 TPY NOx 1.02 lb/hr and 4.46 TPY CO 0.13 lb/hr and 0.58 TPY VOC b)(2)a. and b)(2)b, below.
b.	OAC rule 3745-17-07(A)	The emissions limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
c.	OAC rule 3745-17-10(B)(1)	The emissions limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

(2) Additional Terms and Conditions

a. The "Best Available Technology" (BAT) control requirement for this emissions unit has been determined to be compliance with the terms and conditions of this permit.

b. The hourly emission limitations were established for purposes to reflect the emission unit's potential to emit. Therefore, no additional monitoring, record keeping or reporting is required to demonstrate compliance with these emission limitations.

c) Operational Restrictions

(1) The permittee shall burn only natural gas or propane in this emissions unit.

d) Monitoring and/or Recordkeeping Requirements

(1) For each day during which the permittee burns a fuel other than natural gas or propane the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. when a fuel other than natural gas or propane was burned in this emissions unit**.**

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

f) Testing Requirements

(1) Compliance with the emission limitations in the terms and conditions of this permit shall be determined in accordance with the following methods:

Emission Limitations:

0.09 lb/hr and 0.4 TPY PE

0.21 lb/hr and 0.91 TPY SO2

2.57 lb/hr and 11.26 TPY NOx

1.02 lb/hr and 4.46 TPY CO

0.13 lb/hr and 0.58 TPY VOC

Applicable Compliance Method:

The hourly allowable emission limitations above were established by multiplying the maximum natural gas or propane usage rate (12.375 mmBtu/hr) by the higher of the emission factors* for each pollutant, from AP-42, Tables 1.4-1, and 1.4-2, revised 7/98 (for natural gas) and Table 1.5-1, revised October 1996 (for propane).

* for NOx: 0.21 lb NOx/mmBtu; for CO, 0.08 lb CO/mmBtu; for PE, 0.007 lb PE/mmBtu; for VOC, 0.01 lb VOC/mmBtu; and for SO2, 0.017 lb SO2/mmBtu.

If required, compliance with the hourly allowable emission limitations above shall be determined in accordance with the appropriate Methods** of 40 CFR Part 60, Appendix A.

** For NOx, Methods 1 - 4 and 7; for CO, Methods 1 - 4 and 10; for VOC, Methods 1 - 4 and 25 or 25A, as appropriate; for PE, Methods 1 - 5; and for SO2, Methods 1 - 4 and 6.

g) Miscellaneous Requirements

(1) None.

2. K005, Coating/Printing Press C-5

Operations, Property and/or Equipment Description:

Metal Decorative Coating Press

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	3745-31-05(A)(3) PTI 05-14397	The Volatile organic compound (VOC) content of the coatings shall not exceed 5.35 pounds per gallon. The emissions from natural gas and propane combustion in the drying ovens shall not exceed the following: 0.413 lb/hr and 1.809 tons/yr nitrogen oxides (NOx); 0.168 lb/hr and 0.736 ton/yr carbon monoxide (CO); 0.01 lb/hr and 0.057 ton/yr filterable particulate emissions (PE); 0.015 lb/hr and 0.067 ton/yr PM10; 0.001 lb/hr and 0.005 ton/yr sulfur dioxide (SO2); and 0.011 lb/hr and 0.048 ton/yr VOC. Compliance with the requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A) 3745-17-11(B)(1), and 3745-21-09(U)(2)(e)(iii).
b.	OAC rule 3745-21-09(U)(2)(e)(iii)	The coatings usage in this emissions unit shall not exceed 10 gallons per day.
c.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM)	The VOC emissions, for emissions units K005 through K009, combined, shall not exceed 14.87 tons per rolling, 12-month period.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs.
d.	OAC rule 3745-17-11(A)(2)(b)(i)	The Allowable Rate of Particulate Emission shall not exceed 0.551 lbs/hr.
e.	OAC rule 3745-17-07(A) (for the drying ovens)	The Visible PE from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.

(2) Additional Terms and Conditions

a. The emission limitations for PM10, SO2, NOx, CO and VOC from the combustion of natural gas and/or propane in the drying ovens are established to reflect potentials to emit for this emissions unit. Therefore, no additional monitoring, record keeping and/or reporting requirements are necessary to ensure compliance with these limitations.

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The permittee shall burn only natural gas and/or propane as fuel in this emissions unit.

(2) The combined emissions of VOC from emissions units K005 through K009, inclusive, shall not exceed 14.87 tons per rolling, 12-month period, calculated according to the following formula:

SUM of all {[(Pi)(VOCi)]÷ 2000} - {(Rp)(Po)(VOCo) ÷ 2000}

Where:

Pi = usage of each coating, cleanup, or restoration material in gallons;

VOCi = volatile Organic compound content of each coating, cleanup, or restoration material in pounds VOC per gallon;

Rp =ratio of solvent used on emissions units K005 through K009 (total solvent used on all emissions units - the amount of solvent used on emissions unit K045);

Po =total gallons of recovered solvents less the gallons of solvent recovered from emissions unit K045, for the subject time period; and

VOCo = VOC content of recovered solvents in pounds of VOC per gallon.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall collect and record the following information each day this emissions unit is in operation:

a. the name and identification number of each coating employed;

b. the volume, in gallons, of each coating employed;

c. the total volume, in gallons, of all the coatings employed; and

d. the VOC content of each coating employed, in lbs/gallon of coating.

(2) The permittee shall collect and record the following information each month for emissions units K005 through K009, inclusive, combined:

a. the name or identification number for each coating and cleanup/restoration solvent employed;

b. the VOC content of each coating and cleanup/restoration solvent material employed, in pounds per gallon, as applied;

c. the volume, in gallons, of each coating and cleanup/restoration solvent material employed;

d. the VOC emissions, in tons, as determined by the equation in Section A.II.2. of these terms and conditions; and

e. the rolling, 12-month VOC emissions, in tons.

(3) For each day during which the permittee burns fuel other than natural gas or propane in this emissions unit, the permittee shall maintain a record of the type and quantity of fuel burned.

(4) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

*A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. all exceedances of the maximum allowable coatings VOC content of 5.35 pounds per gallon, as applied;

b. all exceedances of the rolling, 12-month VOC emission limitation of 14.87 tons (for emissions units K005 through K009, combined);

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

e. The permittee shall notify the Director (the Ohio EPA, Southwest District Office) of any record showing the use of a fuel other than natural gas or propane in this emissions unit.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)].

(2) The permittee shall notify the Director any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit. A copy of such record shall be sent to the director within forty-five days after the exceedance occurs.

[OAC rule 3745-21-09(B)(3)(e)]

f) Testing Requirements

(1) Compliance with the emission limitation(s) in b)(1) of these terms and conditions shall be determined in accordance with the following method(s):

a. Emission Limitation:

The VOC content of the coatings shall not exceed 5.35 pounds per gallon of coating.

Applicable Compliance Method:

Compliance with the allowable VOC content limitation above shall be demonstrated through the record keeping requirements as established in d)(1) of this permit.

b. Emission Limitation:

The VOC emissions, for emissions units K005 through K009, combined, shall not exceed 14.87 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance with the annual allowable VOC emission limitation above shall be demonstrated through the record keeping requirements established in Section d)(2) of this permit.

c. Emission Limitation:

The VOC emissions shall not exceed 14.87 tons per rolling, 12-month period (for this emissions unit)

Applicable Compliance Method:

As long as compliance with the combined annual VOC emission limitation (for emissions unit K005 though K009, combined) is maintained, compliance with the annual VOC emission limitation for this emission unit shall be assumed.

d. Operational Restriction:

10 gallons of coatings/day

Applicable Compliance Method:

Compliance with the operational restriction above shall be demonstrated through the record keeping requirements as established in d)(1) of this permit.

e. Emission Limitation:

Visible PE from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(1).

f. Emission Limitations:

0.413 lb/hr and 1.809 tons/yr nitrogen oxides (NOx);

0.168 lb/hr and 0.736 ton/yr carbon monoxide (CO);

0.01 lb/hr and 0.057 ton/yr filterable particulate emissions (PE);

0.015 lb/hr and 0.067 ton/yr PM10;

0.001 lb/hr and 0.005 ton/yr sulfur dioxide (SO2); and

0.011 lb/hr and 0.048 ton/yr VOC.

Applicable Compliance Method:

The permittee may demonstrate compliance with the hourly allowable emission limitations above by multiplying the maximum hourly natural gas/propane consumption rate by the appropriate emission factor from USEPA's AP-42.

If required, the permittee shall demonstrate compliance with the hourly allowable emission limitations above based on the results of emission testing conducted in accordance with the following Methods:

i. for NOx, Methods 1 - 4 and 7 of 40 CFR Part 60, Appendix A;

ii. for CO, Methods 1 - 4 and 10 of 40 CFR Part 60, Appendix A;

iii. for PE, Methods 1 - 5 of 40 CFR Part 60, Appendix A;

iv. for PM10, Methods 201 and 202 of 40 CFR Part 60, Appendix A;

v. for SO2, Methods 1 - 4 and 10 of 40 CFR Part 60, Appendix A; and

vi. for VOC, Methods 18, 25, or 25A, as appropriate, of 40 CFR Part 60, Appendix A.

Compliance with the annual allowable emission limitations above shall be ensured as long as compliance with the hourly allowable emission limitations is maintained (the annual allowable limitations were determined by multiplying the hourly allowable limitations by 8760, and them dividing by 2000).

g. Allowable Rate of Particulate Emissions (PE) shall not exceed 0.551 lbs per hour

The Allowable Rate of Particulate Emissions limitations represent the emissions unit’s potential to emit and were established by the following methodology:

If the (P), Process Weight Rate, (P) is > "0", but < or = to 0.05 tons per hour, the Allowable Rate of Particulate Emissions (E) = 0.551.

Only PE is from the combustion of fuel.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/restoration solvent material.

g) Miscellaneous Requirements

(1) None.

3. K006, Coating/Printing Press C-4

Operations, Property and/or Equipment Description:

Metal Decorative Coating Press

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	3745-31-05(A)(3) (PTI 05-14394)	The Volatile organic compound (VOC) content of the coatings shall not exceed 5.35 pounds per gallon. The emissions from natural gas and propane combustion in the drying ovens shall not exceed the following: 0.413 lb/hr and 1.809 tons/yr nitrogen oxides (NOx); 0.168 lb/hr and 0.736 ton/yr carbon monoxide (CO); 0.01 lb/hr and 0.057 ton/yr filterable particulate emissions (PE); 0.015 lb/hr and 0.067 ton/yr PM10; 0.001 lb/hr and 0.005 ton/yr sulfur dioxide (SO2); and 0.011 lb/hr and 0.048 ton/yr VOC. Compliance with the requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A) 3745-17-11(B)(1), and 3745-21-09(U)(2)(e)(iii).
b.	OAC rule 3745-21-09(U)(2)(e)(iii)	The coatings usage in this emissions unit shall not exceed 10 gallons per day.
c.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM)	The VOC emissions, for emissions units K005 through K009, combined, shall not exceed 14.87 tons per rolling, 12-month period.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
d.	OAC rule 3745-17-11(A)(2)(b)(i)	The Allowable Rate of Particulate Emission shall not exceed 0.551 lbs/hr.
e.	OAC rule 3745-17-07(A) (for the drying ovens)	The Visible PE from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.
f.	OAC rule 3745-114-01	Ohio Toxic Policy

(2) Additional Terms and Conditions

a. The emission limitations for PM10, SO2, NOx, CO and VOC from the combustion of natural gas and/or propane in the drying ovens are established to reflect potentials to emit for this emissions unit. Therefore, no additional monitoring, record keeping and/or reporting requirements are necessary to ensure compliance with these limitations.

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The permittee shall burn only natural gas and/or propane as fuel in this emissions unit.

(2) The combined emissions of VOC from emissions units K005 through K009, inclusive, shall not exceed 14.87 tons per rolling, 12-month period, calculated according to the following formula:

SUM of all {[(Pi)(VOCi)]÷ 2000} - {(Rp)(Po)(VOCo) ÷ 2000}

where:

Pi = usage of each coating, cleanup, or restoration material in gallons;

VOCi = volatile Organic compound content of each coating, cleanup, or restoration material in pounds VOC per gallon;

Rp =ratio of solvent used on emissions units K005 through K009 (total solvent used on all emissions units - the amount of solvent used on emissions unit K045);

Po =total gallons of recovered solvents less the gallons of solvent recovered from emissions unit K045, for the subject time period; and

VOCo = VOC content of recovered solvents in pounds of VOC per gallon.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall collect and record the following information each day this emissions unit is in operation:

a. the name and identification number of each coating employed;

b. the volume, in gallons, of each coating employed;

c. the total volume, in gallons, of all the coatings employed; and

d. the VOC content of each coating employed, in lbs/gallon of coating.

(2) The permittee shall collect and record the following information each month for emissions units K005 through K009, inclusive, combined:

a. the name or identification number for each coating and cleanup/restoration solvent employed;

b. the VOC content of each coating and cleanup/restoration solvent material employed, in pounds per gallon, as applied;

c. the volume, in gallons, of each coating and cleanup/restoration solvent material employed;

d. the VOC emissions, in tons, as determined by the equation in Section A.II.2. of these terms and conditions; and

e. the rolling, 12-month VOC emissions, in tons.

(3) For each day during which the permittee burns fuel other than natural gas or propane in this emissions unit, the permittee shall maintain a record of the type and quantity of fuel burned.

(4) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

*A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

(5) The permit to install for this emissions unit was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model. The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Methyl ethyl ketone (MEK)

TLV (mg/m3): 590 mg/m3

Maximum Hourly Emission Rate (g/sec): 0.43

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 1590

MAGLC (ug/m3): 14,000

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters; the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound or chemical with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled, as documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices");

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

(6) If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) meet(s) the definition of a "modification" under other provisions of the rule, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

a. description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of the evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

If the permittee determines that the "Air Toxics Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 (VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii), then the permittee shall obtain a final permit to install prior to the change.

e) Reporting Requirements

(1) The permittee shall submit the following deviation (excursion) reports, in accordance with the specific requirements of this permit, for the following information:

a. all exceedances of the maximum daily coating usage limitation of 10 gallons;

b. all exceedances of the maximum allowable coatings VOC content of 5.35 pounds per gallon, as applied;

c. all exceedances of the rolling, 12-month VOC emission limitation of 14.87 tons (for emissions units K005 through K009, combined);

d. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

e. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

(2) The permittee shall notify the Director (the Ohio EPA, Southwest District Office) of any record showing the use of a fuel other than natural gas or propane in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (the Ohio EPA, Southwest District Office) within 30 days following the end of the calendar month.

f) Testing Requirements

(1) Compliance with the emission limitation(s) in b)(1) of these terms and conditions shall be determined in accordance with the following method(s):

a. Emission Limitation:

The VOC content of the coatings shall not exceed 5.35 pounds per gallon of coating.

Applicable Compliance Method:

Compliance with the allowable VOC content limitation above shall be demonstrated through the record keeping requirements as established in d)(1) of this permit.

b. Emission Limitation:

The VOC emissions, for emissions units K005 through K009, combined, shall not exceed 14.87 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance with the annual allowable VOC emission limitation above shall be demonstrated through the record keeping requirements established in Section d)(2) of this permit.

c. Emission Limitation:

The VOC emissions shall not exceed 14.87 tons per rolling, 12-month period (for this emissions unit)

Applicable Compliance Method:

As long as compliance with the combined annual VOC emission limitation (for emissions unit K005 though K009, combined) is maintained, compliance with the annual VOC emission limitation for this emission unit shall be assumed.

d. Operational Restriction:

10 gallons of coatings/day

Applicable Compliance Method:

Compliance with the operational restriction above shall be demonstrated through the record keeping requirements as established in d)(1) of this permit.

e. Emission Limitation:

Visible PE from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(1).

f. Emission Limitations:

0.413 lb/hr and 1.809 tons/yr nitrogen oxides (NOx);

0.168 lb/hr and 0.736 ton/yr carbon monoxide (CO);

0.01 lb/hr and 0.057 ton/yr filterable particulate emissions (PE);

0.015 lb/hr and 0.067 ton/yr PM10;

0.001 lb/hr and 0.005 ton/yr sulfur dioxide (SO2); and

0.011 lb/hr and 0.048 ton/yr VOC.

Applicable Compliance Method:

The permittee may demonstrate compliance with the hourly allowable emission limitations above by multiplying the maximum hourly natural gas/propane consumption rate by the appropriate emission factor from USEPA's AP-42.

If required, the permittee shall demonstrate compliance with the hourly allowable emission limitations above based on the results of emission testing conducted in accordance with the following Methods:

i. for NOx, Methods 1 - 4 and 7 of 40 CFR Part 60, Appendix A;

ii. for CO, Methods 1 - 4 and 10 of 40 CFR Part 60, Appendix A;

iii. for PE, Methods 1 - 5 of 40 CFR Part 60, Appendix A;

iv. for PM10, Methods 201 and 202 of 40 CFR Part 60, Appendix A;

v. for SO2, Methods 1 - 4 and 10 of 40 CFR Part 60, Appendix A; and

vi. for VOC, Methods 18, 25, or 25A, as appropriate, of 40 CFR Part 60, Appendix A.

Compliance with the annual allowable emission limitations above shall be ensured as long as compliance with the hourly allowable emission limitations is maintained (the annual allowable limitations were determined by multiplying the hourly allowable limitations by 8760, and them dividing by 2000).

g. Allowable Rate of Particulate Emissions (PE) shall not exceed 0.551 lbs per hour

The Allowable Rate of Particulate Emissions limitations represent the emissions unit's potential to emit and were established by the following methodology:

If the (P), Process Weight Rate, (P) is > "0", but < or = to 0.05 tons per hour, the Allowable Rate of Particulate Emissions (E) = 0.551.

Only PE is from the combustion of fuel.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/restoration solvent material.

g) Miscellaneous Requirements

(1) None.

4. K007, Coating/Printing Press C-3

Operations, Property and/or Equipment Description:

Metal Decorative Coating Press

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	3745-31-05(A)(3)	The Volatile organic compound (VOC) content of the coatings shall not exceed 5.35 pounds per gallon. The emissions from natural gas and propane combustion in the drying ovens shall not exceed the following: 0.413 lb/hr and 1.809 tons/yr nitrogen oxides (NOx); 0.168 lb/hr and 0.736 ton/yr carbon monoxide (CO); 0.01 lb/hr and 0.057 ton/yr filterable particulate emissions (PE); 0.015 lb/hr and 0.067 ton/yr PM10; 0.001 lb/hr and 0.005 ton/yr sulfur dioxide (SO2); and 0.011 lb/hr and 0.048 ton/yr VOC. Compliance with the requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A) 3745-17-11(B)(1), and 3745-21-09(U)(2)(e)(iii).
b.	OAC rule 3745-21-09(U)(2)(e)(iii)	The coatings usage in this emissions unit shall not exceed 10 gallons per day.
c.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM)	The VOC emissions, for emissions units K005 through K009, combined, shall not exceed 14.87 tons per rolling, 12-month period.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
d.	OAC rule 3745-17-11(A)(2)(b)(i)	The Allowable Rate of Particulate Emission shall not exceed 0.551 lbs/hr.
e.	OAC rule 3745-17-07(A) (for the drying ovens)	The Visible PE from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.
f.	OAC rule 3745-114-01	Ohio Toxic Policy

(2) Additional Terms and Conditions

a. The emission limitations for PM10, SO2, NOx, CO and VOC from the combustion of natural gas and/or propane in the drying ovens are established to reflect potentials to emit for this emissions unit. Therefore, no additional monitoring, record keeping and/or reporting requirements are necessary to ensure compliance with these limitations.

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The permittee shall burn only natural gas and/or propane as fuel in this emissions unit.

(2) The combined emissions of VOC from emissions units K005 through K009, inclusive, shall not exceed 14.87 tons per rolling, 12-month period, calculated according to the following formula:

SUM of all {[(Pi)(VOCi)]÷ 2000} - {(Rp)(Po)(VOCo) ÷ 2000}

where:

Pi = usage of each coating, cleanup, or restoration material in gallons;

VOCi = volatile Organic compound content of each coating, cleanup, or restoration material in pounds VOC per gallon;

Rp =ratio of solvent used on emissions units K005 through K009 (total solvent used on all emissions units - the amount of solvent used on emissions unit K045);

Po =total gallons of recovered solvents less the gallons of solvent recovered from emissions unit K045, for the subject time period; and

VOCo = VOC content of recovered solvents in pounds of VOC per gallon.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall collect and record the following information each day this emissions unit is in operation:

a. the name and identification number of each coating employed;

b. the volume, in gallons, of each coating employed;

c. the total volume, in gallons, of all the coatings employed; and

d. the VOC content of each coating employed, in lbs/gallon of coating.

(2) The permittee shall collect and record the following information each month for emissions units K005 through K009, inclusive, combined:

a. the name or identification number for each coating and cleanup/restoration solvent employed;

b. the VOC content of each coating and cleanup/restoration solvent material employed, in pounds per gallon, as applied;

c. the volume, in gallons, of each coating and cleanup/restoration solvent material employed;

d. the VOC emissions, in tons, as determined by the equation in Section A.II.2. of these terms and conditions; and

e. the rolling, 12-month VOC emissions, in tons.

(3) For each day during which the permittee burns fuel other than natural gas or propane in this emissions unit, the permittee shall maintain a record of the type and quantity of fuel burned.

(4) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

*A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

(5) The permit to install for this emissions unit was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model. The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Methyl ethyl ketone (MEK)

TLV (mg/m3): 590 mg/m3

Maximum Hourly Emission Rate (g/sec): 0.43

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 1590

MAGLC (ug/m3): 14,000

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters; the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound or chemical with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled, as documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices");

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

(6) If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) meet(s) the definition of a "modification" under other provisions of the rule, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

a. description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of the evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

If the permittee determines that the "Air Toxics Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 (VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii), then the permittee shall obtain a final permit to install prior to the change.

e) Reporting Requirements

(1) The permittee shall submit the following deviation (excursion) reports, in accordance with the specific requirements of this permit, for the following information:

a. all exceedances of the maximum daily coating usage limitation of 10 gallons;

b. all exceedances of the maximum allowable coatings VOC content of 5.35 pounds per gallon, as applied;

c. all exceedances of the rolling, 12-month VOC emission limitation of 14.87 tons (for emissions units K005 through K009, combined);

d. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

e. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

(2) The permittee shall notify the Director (the Ohio EPA, Southwest District Office) of any record showing the use of a fuel other than natural gas or propane in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (the Ohio EPA, Southwest District Office) within 30 days following the end of the calendar month.

f) Testing Requirements

(1) Compliance with the emission limitation(s) in b)(1) of these terms and conditions shall be determined in accordance with the following method(s):

a. Emission Limitation:

The VOC content of the coatings shall not exceed 5.35 pounds per gallon of coating.

Applicable Compliance Method:

Compliance with the allowable VOC content limitation above shall be demonstrated through the record keeping requirements as established in d)(1) of this permit.

b. Emission Limitation:

The VOC emissions, for emissions units K005 through K009, combined, shall not exceed 14.87 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance with the annual allowable VOC emission limitation above shall be demonstrated through the record keeping requirements established in Section d)(2) of this permit.

c. Emission Limitation:

The VOC emissions shall not exceed 14.87 tons per rolling, 12-month period (for this emissions unit)

Applicable Compliance Method:

As long as compliance with the combined annual VOC emission limitation (for emissions unit K005 though K009, combined) is maintained, compliance with the annual VOC emission limitation for this emission unit shall be assumed.

d. Operational Restriction:

10 gallons of coatings/day

Applicable Compliance Method:

Compliance with the operational restriction above shall be demonstrated through the record keeping requirements as established in d)(1) of this permit.

e. Emission Limitation:

Visible PE from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(1).

f. Emission Limitations:

0.413 lb/hr and 1.809 tons/yr nitrogen oxides (NOx);

0.168 lb/hr and 0.736 ton/yr carbon monoxide (CO);

0.01 lb/hr and 0.057 ton/yr filterable particulate emissions (PE);

0.015 lb/hr and 0.067 ton/yr PM10;

0.001 lb/hr and 0.005 ton/yr sulfur dioxide (SO2); and

0.011 lb/hr and 0.048 ton/yr VOC.

Applicable Compliance Method:

The permittee may demonstrate compliance with the hourly allowable emission limitations above by multiplying the maximum hourly natural gas/propane consumption rate by the appropriate emission factor from USEPA's AP-42.

If required, the permittee shall demonstrate compliance with the hourly allowable emission limitations above based on the results of emission testing conducted in accordance with the following Methods:

i. for NOx, Methods 1 - 4 and 7 of 40 CFR Part 60, Appendix A;

ii. for CO, Methods 1 - 4 and 10 of 40 CFR Part 60, Appendix A;

iii. for PE, Methods 1 - 5 of 40 CFR Part 60, Appendix A;

iv. for PM10, Methods 201 and 202 of 40 CFR Part 60, Appendix A;

v. for SO2, Methods 1 - 4 and 10 of 40 CFR Part 60, Appendix A; and

vi. for VOC, Methods 18, 25, or 25A, as appropriate, of 40 CFR Part 60, Appendix A.

Compliance with the annual allowable emission limitations above shall be ensured as long as compliance with the hourly allowable emission limitations is maintained (the annual allowable limitations were determined by multiplying the hourly allowable limitations by 8760, and them dividing by 2000).

g. Allowable Rate of Particulate Emissions (PE) shall not exceed 0.551 lbs per hour

The Allowable Rate of Particulate Emissions limitations represent the emissions unit's potential to emit and were established by the following methodology:

If the (P), Process Weight Rate, (P) is > "0", but < or = to 0.05 tons per hour, the Allowable Rate of Particulate Emissions (E) = 0.551.

Only PE is from the combustion of fuel.

Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/restoration solvent material

5. K008, Coating/Printing Press C-2

Operations, Property and/or Equipment Description:

Metal Decorative Coating Press

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	3745-31-05(A)(3)	The Volatile organic compound (VOC) content of the coatings shall not exceed 5.35 pounds per gallon. The emissions from natural gas and propane combustion in the drying ovens shall not exceed the following: 0.413 lb/hr and 1.809 tons/yr nitrogen oxides (NOx); 0.168 lb/hr and 0.736 ton/yr carbon monoxide (CO); 0.01 lb/hr and 0.057 ton/yr filterable particulate emissions (PE); 0.015 lb/hr and 0.067 ton/yr PM10; 0.001 lb/hr and 0.005 ton/yr sulfur dioxide (SO2); and 0.011 lb/hr and 0.048 ton/yr VOC. Compliance with the requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A) 3745-17-11(B)(1), and 3745-21-09(U)(2)(e)(iii).
b.	OAC rule 3745-21-09(U)(2)(e)(iii)	The coatings usage in this emissions unit shall not exceed 10 gallons per day.
c.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM)	The VOC emissions, for emissions units K005 through K009, combined, shall not exceed 14.87 tons per rolling, 12-month period.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
d.	OAC rule 3745-17-11(A)(2)(b)(i)	The Allowable Rate of Particulate Emission shall not exceed 0.551 lbs/hr.
e.	OAC rule 3745-17-07(A) (for the drying ovens)	The Visible PE from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.
f.	OAC rule 3745-114-01	Ohio Toxic Policy

(2) Additional Terms and Conditions

a. The emission limitations for PM10, SO2, NOx, CO and VOC from the combustion of natural gas and/or propane in the drying ovens are established to reflect potentials to emit for this emissions unit. Therefore, no additional monitoring, record keeping and/or reporting requirements are necessary to ensure compliance with these limitations.

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The permittee shall burn only natural gas and/or propane as fuel in this emissions unit.

(2) The combined emissions of VOC from emissions units K005 through K009, inclusive, shall not exceed 14.87 tons per rolling, 12-month period, calculated according to the following formula:

SUM of all {[(Pi)(VOCi)]÷ 2000} - {(Rp)(Po)(VOCo) ÷ 2000}

where:

Pi = usage of each coating, cleanup, or restoration material in gallons;

VOCi = volatile Organic compound content of each coating, cleanup, or restoration material in pounds VOC per gallon;

Rp =ratio of solvent used on emissions units K005 through K009 (total solvent used on all emissions units - the amount of solvent used on emissions unit K045);

Po =total gallons of recovered solvents less the gallons of solvent recovered from emissions unit K045, for the subject time period; and

VOCo = VOC content of recovered solvents in pounds of VOC per gallon.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall collect and record the following information each day this emissions unit is in operation:

a. the name and identification number of each coating employed;

b. the volume, in gallons, of each coating employed;

c. the total volume, in gallons, of all the coatings employed; and

d. the VOC content of each coating employed, in lbs/gallon of coating.

(2) The permittee shall collect and record the following information each month for emissions units K005 through K009, inclusive, combined:

a. the name or identification number for each coating and cleanup/restoration solvent employed;

b. the VOC content of each coating and cleanup/restoration solvent material employed, in pounds per gallon, as applied;

c. the volume, in gallons, of each coating and cleanup/restoration solvent material employed;

d. the VOC emissions, in tons, as determined by the equation in Section A.II.2. of these terms and conditions; and

e. the rolling, 12-month VOC emissions, in tons.

(3) For each day during which the permittee burns fuel other than natural gas or propane in this emissions unit, the permittee shall maintain a record of the type and quantity of fuel burned.

(4) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

*A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

(5) The permit to install for this emissions unit was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model. The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Methyl ethyl ketone (MEK)

TLV (mg/m3): 590 mg/m3

Maximum Hourly Emission Rate (g/sec): 0.43

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 1590

MAGLC (ug/m3): 14,000

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters; the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound or chemical with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled, as documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices");

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

(6) If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) meet(s) the definition of a "modification" under other provisions of the rule, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

a. description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of the evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

If the permittee determines that the "Air Toxics Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 (VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii), then the permittee shall obtain a final permit to install prior to the change.

e) Reporting Requirements

(1) The permittee shall submit the following deviation (excursion) reports, in accordance with the specific requirements of this permit, for the following information:

a. all exceedances of the maximum daily coating usage limitation of 10 gallons;

b. all exceedances of the maximum allowable coatings VOC content of 5.35 pounds per gallon, as applied;

c. all exceedances of the rolling, 12-month VOC emission limitation of 14.87 tons (for emissions units K005 through K009, combined);

d. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

e. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

(2) The permittee shall notify the Director (the Ohio EPA, Southwest District Office) of any record showing the use of a fuel other than natural gas or propane in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (the Ohio EPA, Southwest District Office) within 30 days following the end of the calendar month.

f) Testing Requirements

(1) Compliance with the emission limitation(s) in b)(1) of these terms and conditions shall be determined in accordance with the following method(s):

a. Emission Limitation:

The VOC content of the coatings shall not exceed 5.35 pounds per gallon of coating.

Applicable Compliance Method:

Compliance with the allowable VOC content limitation above shall be demonstrated through the record keeping requirements as established in d)(1) of this permit.

b. Emission Limitation:

The VOC emissions, for emissions units K005 through K009, combined, shall not exceed 14.87 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance with the annual allowable VOC emission limitation above shall be demonstrated through the record keeping requirements established in Section d)(2) of this permit.

c. Emission Limitation:

The VOC emissions shall not exceed 14.87 tons per rolling, 12-month period (for this emissions unit)

Applicable Compliance Method:

As long as compliance with the combined annual VOC emission limitation (for emissions unit K005 though K009, combined) is maintained, compliance with the annual VOC emission limitation for this emission unit shall be assumed.

d. Operational Restriction:

10 gallons of coatings/day

Applicable Compliance Method:

Compliance with the operational restriction above shall be demonstrated through the record keeping requirements as established in d)(1) of this permit.

e. Emission Limitation:

Visible PE from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(1).

f. Emission Limitations:

0.413 lb/hr and 1.809 tons/yr nitrogen oxides (NOx);

0.168 lb/hr and 0.736 ton/yr carbon monoxide (CO);

0.01 lb/hr and 0.057 ton/yr filterable particulate emissions (PE);

0.015 lb/hr and 0.067 ton/yr PM10;

0.001 lb/hr and 0.005 ton/yr sulfur dioxide (SO2); and

0.011 lb/hr and 0.048 ton/yr VOC.

Applicable Compliance Method:

The permittee may demonstrate compliance with the hourly allowable emission limitations above by multiplying the maximum hourly natural gas/propane consumption rate by the appropriate emission factor from USEPA's AP-42.

If required, the permittee shall demonstrate compliance with the hourly allowable emission limitations above based on the results of emission testing conducted in accordance with the following Methods:

i. for NOx, Methods 1 - 4 and 7 of 40 CFR Part 60, Appendix A;

ii. for CO, Methods 1 - 4 and 10 of 40 CFR Part 60, Appendix A;

iii. for PE, Methods 1 - 5 of 40 CFR Part 60, Appendix A;

iv. for PM10, Methods 201 and 202 of 40 CFR Part 60, Appendix A;

v. for SO2, Methods 1 - 4 and 10 of 40 CFR Part 60, Appendix A; and

vi. for VOC, Methods 18, 25, or 25A, as appropriate, of 40 CFR Part 60, Appendix A.

Compliance with the annual allowable emission limitations above shall be ensured as long as compliance with the hourly allowable emission limitations is maintained (the annual allowable limitations were determined by multiplying the hourly allowable limitations by 8760, and them dividing by 2000).

g. Allowable Rate of Particulate Emissions (PE) shall not exceed 0.551 lbs per hour

The Allowable Rate of Particulate Emissions limitations represent the emissions unit's potential to emit and were established by the following methodology:

If the (P), Process Weight Rate, (P) is > "0", but < or = to 0.05 tons per hour, the Allowable Rate of Particulate Emissions (E) = 0.551.

Only PE is from the combustion of fuel.

Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/restoration solvent material.

6. K009, Coating/Printing Press C-1

Operations, Property and/or Equipment Description:

Metal Decorative Coating Press

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	3745-31-05(A)(3)	The Volatile organic compound (VOC) content of the coatings shall not exceed 5.35 pounds per gallon. The emissions from natural gas and propane combustion in the drying ovens shall not exceed the following: 0.413 lb/hr and 1.809 tons/yr nitrogen oxides (NOx); 0.168 lb/hr and 0.736 ton/yr carbon monoxide (CO); 0.01 lb/hr and 0.057 ton/yr filterable particulate emissions (PE); 0.015 lb/hr and 0.067 ton/yr PM10; 0.001 lb/hr and 0.005 ton/yr sulfur dioxide (SO2); and 0.011 lb/hr and 0.048 ton/yr VOC. Compliance with the requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A) 3745-17-11(B)(1), and 3745-21-09(U)(2)(e)(iii).
b.	OAC rule 3745-21-09(U)(2)(e)(iii)	The coatings usage in this emissions unit shall not exceed 10 gallons per day.
c.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM)	The VOC emissions, for emissions units K005 through K009, combined, shall not exceed 14.87 tons per rolling, 12-month period.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
d.	OAC rule 3745-17-11(A)(2)(b)(i)	The Allowable Rate of Particulate Emission shall not exceed 0.551 lbs/hr.
e.	OAC rule 3745-17-07(A) (for the drying ovens)	The Visible PE from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.
f.	OAC rule 3745-114-01	Ohio Toxic Policy

(2) Additional Terms and Conditions

a. The emission limitations for PM10, SO2, NOx, CO and VOC from the combustion of natural gas and/or propane in the drying ovens are established to reflect potentials to emit for this emissions unit. Therefore, no additional monitoring, record keeping and/or reporting requirements are necessary to ensure compliance with these limitations.

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The permittee shall burn only natural gas and/or propane as fuel in this emissions unit.

(2) The combined emissions of VOC from emissions units K005 through K009, inclusive, shall not exceed 14.87 tons per rolling, 12-month period, calculated according to the following formula:

SUM of all {[(Pi)(VOCi)]÷ 2000} - {(Rp)(Po)(VOCo) ÷ 2000}

where:

Pi = usage of each coating, cleanup, or restoration material in gallons;

VOCi = volatile Organic compound content of each coating, cleanup, or restoration material in pounds VOC per gallon;

Rp =ratio of solvent used on emissions units K005 through K009 (total solvent used on all emissions units - the amount of solvent used on emissions unit K045);

Po =total gallons of recovered solvents less the gallons of solvent recovered from emissions unit K045, for the subject time period; and

VOCo = VOC content of recovered solvents in pounds of VOC per gallon.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall collect and record the following information each day this emissions unit is in operation:

a. the name and identification number of each coating employed;

b. the volume, in gallons, of each coating employed;

c. the total volume, in gallons, of all the coatings employed; and

d. the VOC content of each coating employed, in lbs/gallon of coating.

(2) The permittee shall collect and record the following information each month for emissions units K005 through K009, inclusive, combined:

a. the name or identification number for each coating and cleanup/restoration solvent employed;

b. the VOC content of each coating and cleanup/restoration solvent material employed, in pounds per gallon, as applied;

c. the volume, in gallons, of each coating and cleanup/restoration solvent material employed;

d. the VOC emissions, in tons, as determined by the equation in Section A.II.2. of these terms and conditions; and

e. the rolling, 12-month VOC emissions, in tons.

(3) For each day during which the permittee burns fuel other than natural gas or propane in this emissions unit, the permittee shall maintain a record of the type and quantity of fuel burned.

(4) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

*A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

(5) The permit to install for this emissions unit was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model. The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Methyl ethyl ketone (MEK)

TLV (mg/m3): 590 mg/m3

Maximum Hourly Emission Rate (g/sec): 0.43

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 1590

MAGLC (ug/m3): 14,000

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters; the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound or chemical with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled, as documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices");

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

(6) If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) meet(s) the definition of a "modification" under other provisions of the rule, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

a. description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of the evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

If the permittee determines that the "Air Toxics Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 (VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii), then the permittee shall obtain a final permit to install prior to the change.

e) Reporting Requirements

(1) The permittee shall submit the following deviation (excursion) reports, in accordance with the specific requirements of this permit, for the following information:

a. all exceedances of the maximum daily coating usage limitation of 10 gallons;

b. all exceedances of the maximum allowable coatings VOC content of 5.35 pounds per gallon, as applied;

c. all exceedances of the rolling, 12-month VOC emission limitation of 14.87 tons (for emissions units K005 through K009, combined);

d. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

e. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

(2) The permittee shall notify the Director (the Ohio EPA, Southwest District Office) of any record showing the use of a fuel other than natural gas or propane in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (the Ohio EPA, Southwest District Office) within 30 days following the end of the calendar month.

f) Testing Requirements

(1) Compliance with the emission limitation(s) in b)(1) of these terms and conditions shall be determined in accordance with the following method(s):

a. Emission Limitation:

The VOC content of the coatings shall not exceed 5.35 pounds per gallon of coating.

Applicable Compliance Method:

Compliance with the allowable VOC content limitation above shall be demonstrated through the record keeping requirements as established in d)(1) of this permit.

b. Emission Limitation:

The VOC emissions, for emissions units K005 through K009, combined, shall not exceed 14.87 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance with the annual allowable VOC emission limitation above shall be demonstrated through the record keeping requirements established in Section d)(2) of this permit.

c. Emission Limitation:

The VOC emissions shall not exceed 14.87 tons per rolling, 12-month period (for this emissions unit)

Applicable Compliance Method:

As long as compliance with the combined annual VOC emission limitation (for emissions unit K005 though K009, combined) is maintained, compliance with the annual VOC emission limitation for this emission unit shall be assumed.

d. Operational Restriction:

10 gallons of coatings/day

Applicable Compliance Method:

Compliance with the operational restriction above shall be demonstrated through the record keeping requirements as established in d)(1) of this permit.

e. Emission Limitation:

Visible PE from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(1).

f. Emission Limitations:

0.413 lb/hr and 1.809 tons/yr nitrogen oxides (NOx);

0.168 lb/hr and 0.736 ton/yr carbon monoxide (CO);

0.01 lb/hr and 0.057 ton/yr filterable particulate emissions (PE);

0.015 lb/hr and 0.067 ton/yr PM10;

0.001 lb/hr and 0.005 ton/yr sulfur dioxide (SO2); and

0.011 lb/hr and 0.048 ton/yr VOC.

Applicable Compliance Method:

The permittee may demonstrate compliance with the hourly allowable emission limitations above by multiplying the maximum hourly natural gas/propane consumption rate by the appropriate emission factor from USEPA's AP-42.

If required, the permittee shall demonstrate compliance with the hourly allowable emission limitations above based on the results of emission testing conducted in accordance with the following Methods:

i. for NOx, Methods 1 - 4 and 7 of 40 CFR Part 60, Appendix A;

ii. for CO, Methods 1 - 4 and 10 of 40 CFR Part 60, Appendix A;

iii. for PE, Methods 1 - 5 of 40 CFR Part 60, Appendix A;

iv. for PM10, Methods 201 and 202 of 40 CFR Part 60, Appendix A;

v. for SO2, Methods 1 - 4 and 10 of 40 CFR Part 60, Appendix A; and

vi. for VOC, Methods 18, 25, or 25A, as appropriate, of 40 CFR Part 60, Appendix A.

Compliance with the annual allowable emission limitations above shall be ensured as long as compliance with the hourly allowable emission limitations is maintained (the annual allowable limitations were determined by multiplying the hourly allowable limitations by 8760, and them dividing by 2000).

g. Allowable Rate of Particulate Emissions (PE) shall not exceed 0.551 lbs per hour

The Allowable Rate of Particulate Emissions limitations represent the emissions unit's potential to emit and were established by the following methodology:

If the (P), Process Weight Rate, (P) is > "0", but < or = to 0.05 tons per hour, the Allowable Rate of Particulate Emissions (E) = 0.551.

Only PE is from the combustion of fuel.

Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/restoration solvent material.

7. K022, A-Line Screen Presses

Operations, Property and/or Equipment Description:

Metal Decorative Coating Screen Press Printing Coating Line 172

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3)	VOC content of coatings shall not exceed 5.36 lbs VOC/gallon, minus water and exempt solvents, as applied. Volatile Organic Compound (VOC) emissions from coatings and cleanup/pan solvents materials employed shall not exceed 18.895 tons VOC per rolling 12 month period. The emissions from natural gas and propane combustion in the drying ovens shall not exceed the following: 0.91 lb/hr and 4.0 tons/yr NOx; 0.23 lb/hr and 1.0 tons/yr CO; 0.03 lb/hr and 0.09 ton/yr PE; 0.002 lb/hr and 0.01 ton/yr SO2; and 0.023 lb/hr and 0.10 ton/yr VOC. The requirements of this rule also include compliance with the requirements of OAC rules 3745-21-09(U)(2)(f)(ii), 3745-17-11(B)(1), and 3745-17-07(A).
b.	3745-21-09 (U)(2)(f)(ii)	VOC content of coatings shall not exceed 5.36 lbs VOC/gallon, minus water and exempt solvents, as applied. b)(2)a.
c	OAC rule 3745-31-05(D) Synthetic Minor to avoid	The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
	requirements of 40 CFR Part 63 Subpart MMMM	emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)c, below.
d	OAC rule 3745-17-11(A)(2)(b)(i)	The Allowable Rate of Particulate Emission shall not exceed 0.551 lbs/hr.
e	OAC rule 3745-17-07(A) (for the drying ovens)	The Visible PE from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.

(2) Additional Terms and Conditions

a. Pursuant to OAC rule 3745-21-09(U)(2)(f)(ii), the best available technology has been determined to be extreme performance coatings that have a VOC content greater than the limitations of OAC rules 3745-21-09(U)(1)(c).

b. The emission limitations for PM10, SO2, NOx, CO and VOC from the combustion of natural gas and/or propane in the drying ovens are established to reflect potentials to emit for this emissions unit. Therefore, no additional monitoring, record keeping and/or reporting requirements are necessary to ensure compliance with these limitations.

c. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The permittee shall burn only natural gas and/or propane as fuel in this emissions unit.

(2) The weight of volatile organic materials applied/used for K022 shall not exceed 18.895 tons per rolling 12 months, calculated using the following formula:

[SUM of all materials employed {[(Pi)(VOCi)[1 - (capture*DRE)]]÷ 2000}] - [(Ri)(Po)(VOCo) ÷ 2000]

where:

Pi = usage of each coating, cleanup, or restoration material in gallons

VOCi = volatile Organic compound content of each coating, cleanup, or restoration material in pounds VOC per gallon.

capture = the capture efficiency, assumed to be 0%

DRE = destruction removal efficiency of any control device, 0% without controls

Ri =ratio of solvent used on this specific emission unit/total of material used on all the emission units minus the amount used on K045.

Po = recovered pan/cleanup solvent o recovered from all emission units minus material recovered from K045 in gallons for the last 12-months.

VOCo = VOC content of recovered solvents in pounds of VOC per gallon.

d) Monitoring and/or Recordkeeping Requirements

(1) This facility shall maintain the following monthly records on all coatings and cleanup/pan solvents materials employed in this emissions unit:

a. the name or identification number of material employed, as applied;

b. the VOC content of each coating employed, minus water and exempt solvents, as applied;

c. the VOC content of each cleanup/pan solvent material employed;

d. the volume of each coating employed, in gallons;

e. the volume of each cleanup/pan solvent employed, in gallons;

f. the VOC emissions, in tons, as determined by the equation in Section A.II.2. of these terms and conditions; and

g. the rolling, 12-month VOC emissions, in tons.

(2) If a credit for recovered cleanup/pan solvent material is used to demonstrate compliance and/or used in the calculation of rolling, 12 month emission calculations, the permittee shall maintain the following records for the recovered cleanup/pan solvent material, and the recovery drum or tank serving this emissions unit:

a. the date recovered materials were first added to the recovery tank/drum and the date the materials from the recovery drum or tank were shipped off site;

b. the total amount of material collected and shipped for recycle/recovery and/or disposal at an outside facility, in gallons, on the day it is shipped;

c. record of the VOC content of each cleanup/pan solvent material that is collected for recovery, in pounds per gallon, or a record of the testing results of the VOC content of the material shipped;

d. the mass (lbs) of VOC to be credited to the rolling, 12 month emissions summation, from each shipment of recovered material, calculated using the lowest VOC content of any cleanup/pan solvent material recovered, unless a higher VOC content is established from the testing results of the recovered

material shipped (i.e., b x c), and the date of each such shipment or record of credit; and

e. the record of the total amount of VOC emissions (lbs or tons) that may be applied as a credit, for the materials shipped for recycle/recovery and/or disposal at an outside facility, summed from the records of the VOC emission credits (d), for each shipment recorded during the rolling 12 month period.

(3) For each day during which the permittee burns fuel other than natural gas or propane in this emissions unit, the permittee shall maintain a record of the type and quantity of fuel burned.

(4) This facility shall, on an ongoing basis, evaluate the availability of an alternate coating and coating method that will reduce the emissions from this source and meet the coating specifications of the desired product. Should an alternate coating and/or coating method become available, as based on the Best Available Technology (BAT) for this type of operation, this facility shall submit a schedule for implementation of the alternate coatings and/or coating method within 30 days of the availability.

This facility shall submit quarterly reports that summarize the evaluation of an alternate coating and coating method which details the following information for each coating and/or coating method evaluated:

a. The VOC content, in pounds per gallon;

b. The acceptability;

c. the reason why the alternative coating does not meet specification, for unacceptable coatings;

d. The expected reduction in VOC emissions from the utilization of the acceptable alternate coatings; and

e. The cost of modifying the source to utilize the alternate coatings and/or coating method.

These reports shall be submitted by February 15, May 15, August 15, and November 15 of each year and shall cover the previous calendar quarter (October through December, January through March, April through June, and July through September, respectively).

Once the facility employs coatings in compliance with the requirements of OAC rule 3745-21-09(U)(1) in this source, the evaluation process of alternate coatings and the reporting requirement of this term will be discontinued.

(5) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

*A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall notify the Director (the Ohio EPA, Southwest District Office) in writing of any monthly record showing the use of noncomplying coatings and/or cleanup/pan solvent material. These notifications shall include a copy of such record and shall be sent to the Director (the Ohio EPA, Southwest District Office) within 30 days following the end of the calendar month.

(2) The permittee shall submit the following deviation (excursion) reports, in accordance with the specific requirements of this permit, for the following information:

a. all exceedances of the maximum allowable coatings VOC content of 5.36 pounds per gallon, minus water and exempt solvents, as applied; and

b. all exceedances of the rolling, 12-moth VOC emission limitation of 18.895 tons.

These quarterly deviation (excursion) reports shall be submitted in accordance with Part I- General Terms and Conditions A.1.c.

(3) The permittee shall notify the Director (the Ohio EPA, Southwest District Office) of any record showing the use of a fuel other than natural gas or propane in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (the Ohio EPA, Southwest District Office) within 30 days following the end of the calendar month.

(4) The permittee shall submit the following quarterly deviation (excursion) reports, in accordance with the specific requirements of this permit, for the following information:

a. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

b. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

(5) This facility shall submit quarterly reports that summarize the evaluation of an alternate coating and coating method which details the following information for each coating and/or coating method evaluated:

a. the VOC content, in pounds per gallon;

b. the acceptability;

c. the reason why the alternative coating does not meet specification, for unacceptable coatings;

d. the expected reduction in VOC emissions from the utilization of the acceptable alternate coatings; and

e. the cost of modifying the source to utilize the alternate coatings and/or coating method.

These reports shall be submitted by February 15, May 15, August 15, and November 15 of each year and shall cover the previous calendar quarter (October through December, January through March, April through June, and July through September, respectively).

f) Testing Requirements

(1) Compliance with the emission limitation(s) in b)(1) of these terms and conditions shall be determined in accordance with the following method(s):

a. Emission Limitation:

VOC content of coatings shall not exceed 5.36 lbs VOC/gallon, minus water and exempt solvents, as applied.

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the VOC content of the coatings. The record keeping requirements contained in Section d)(1) shall demonstrate that only materials with these VOC content limitations are applied.

b. Emission Limitation:

Volatile Organic Compound (VOC) emissions from coatings and cleanup/pan solvents materials employed shall not exceed 18.895 tons VOC per rolling 12 month period.

Applicable Compliance Method:

Compliance with the annual allowable VOC emission limitation above shall be determined through the record keeping requirements as established in Section d)(1) of this permit.

c. Emission Limitation:

The emissions from natural gas and propane combustion in the drying ovens shall not exceed the following:

0.91 lb/hr and 4.0 tons/yr NOx;

0.23 lb/hr and 1.0 tons/yr CO;

0.03 lb/hr and 0.09 ton/yr PE;

0.002 lb/hr and 0.01 ton/yr SO2; and

0.023 lb/hr and 0.10 ton/yr VOC.

Applicable Compliance Method:

Compliance with the limits for natural gas combustion within the drying ovens shall be based upon the emission factors from AP-42 "Compilation of Air Pollutant Emission Factors", Tables 1.4-1 and 1.4-2 (7/98). These emission factors (lb pollutant/mmscf) multiplied by the maximum hourly gas burning capacity of the burners (one at 0.78125 mmBtu/hr, two at 1 mmBtu/hr, and four at 0.3125 mmBtu/hr) and times 1 scf/1020 Btu shall be the demonstration of compliance with the hourly limits. Compliance with the ton per year limits are documented by multiplying the calculated hourly limits by 8760 hours in a year and dividing by 2000 pounds.

Compliance with the limits for propane combustion within the drying ovens shall be based upon the emission factors from AP-42 "Compilation of Air Pollutant Emission Factors", Tables 1.5-1 (10/96) These emission factors (lb pollutant/1000 gallons) multiplied by the maximum hourly gas burning capacity of the burners (one at 0.78125 mmBtu/hr, two at 1 mmBtu/hr, and four at 0.3125 mmBtu/hr) and divided by the 91.5 MMBtu/1000 gallons shall be the demonstration of compliance with the hourly limits. Compliance with the ton per year limits are documented by multiplying the calculated hourly limits by 8760 hours in a year and dividing by 2000 pounds.

d. Emission Limitation:

Visible PE from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(1).

e. Allowable Rate of Particulate Emissions (PE) shall not exceed 0.551 lbs per hour

The Allowable Rate of Particulate Emissions limitation represents the emissions unit's potential to emit and was established by the following methodology:

If the (P), Process Weight Rate, (P) is > "0", but < or = to 0.05 tons per hour, the Allowable Rate of Particulate Emissions (E) = 0.551.

Only PE is from the combustion of fuel.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

8. K033, B-Line Screen Presses

Operations, Property and/or Equipment Description:

Metal Decorative Coating Screen Press Printing Coating Line 173

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3)	VOC content of coatings shall not exceed 5.36 lbs VOC/gallon, minus water and exempt solvents, as applied. Volatile Organic Compound (VOC) emissions from coatings and cleanup/pan solvents materials employed shall not exceed 18.895 tons VOC per rolling 12 month period. The emissions from natural gas and propane combustion in the drying ovens shall not exceed the following: 0.91 lb/hr and 4.0 tons/yr NOx; 0.23 lb/hr and 1.0 tons/yr CO; 0.03 lb/hr and 0.09 ton/yr PE; 0.002 lb/hr and 0.01 ton/yr SO2; and 0.023 lb/hr and 0.10 ton/yr VOC. The requirements of this rule also include compliance with the requirements of OAC rules 3745-21-09(U)(2)(f)(ii), 3745-17-11(B)(1), and 3745-17-07(A).
b.	3745-21-09 (U)(2)(f)(ii)	VOC content of coatings shall not exceed 5.36 lbs VOC/gallon, minus water and exempt solvents, as applied. b)(2)a.
c	OAC rule 3745-31-05(D) Synthetic Minor to avoid	The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
	requirements of 40 CFR Part 63 Subpart MMMM	emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)c, below
d	OAC rule 3745-17-11(A)(2)(b)(i)	The Allowable Rate of Particulate Emission shall not exceed 0.551 lbs/hr.
e	OAC rule 3745-17-07(A) (for the drying ovens)	The Visible PE from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.

(2) Additional Terms and Conditions

a. Pursuant to OAC rule 3745-21-09(U)(2)(f)(ii), the best available technology has been determined to be extreme performance coatings that have a VOC content greater than the limitations of OAC rules 3745-21-09(U)(1)(c).

b. The emission limitations for PM10, SO2, NOx, CO and VOC from the combustion of natural gas and/or propane in the drying ovens are established to reflect potentials to emit for this emissions unit. Therefore, no additional monitoring, record keeping and/or reporting requirements are necessary to ensure compliance with these limitations.

c. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The permittee shall burn only natural gas and/or propane as fuel in this emissions unit.

(2) The weight of volatile organic materials applied/used for K022 shall not exceed 18.895 tons per rolling 12 months, calculated using the following formula:

[SUM of all materials employed {[(Pi)(VOCi)[1 - (capture*DRE)]]÷ 2000}] - [(Ri)(Po)(VOCo) ÷ 2000]

where:

Pi = usage of each coating, cleanup, or restoration material in gallons

VOCi = volatile Organic compound content of each coating, cleanup, or restoration material in pounds VOC per gallon.

capture = the capture efficiency, assumed to be 0%

DRE = destruction removal efficiency of any control device, 0% without controls

Ri =ratio of solvent used on this specific emission unit/total of material used on all the emission units minus the amount used on K045.

Po = recovered pan/cleanup solvent o recovered from all emission units minus material recovered from K045 in gallons for the last 12-months.

VOCo = VOC content of recovered solvents in pounds of VOC per gallon.

d) Monitoring and/or Recordkeeping Requirements

(1) This facility shall maintain the following monthly records on all coatings and cleanup/pan solvents materials employed in this emissions unit:

a. the name or identification number of material employed, as applied;

b. the VOC content of each coating employed, minus water and exempt solvents, as applied;

c. the VOC content of each cleanup/pan solvent material employed;

d. the volume of each coating employed, in gallons;

e. the volume of each cleanup/pan solvent employed, in gallons;

f. the VOC emissions, in tons, as determined by the equation in Section A.II.2. of these terms and conditions; and

g. the rolling, 12-month VOC emissions, in tons.

(2) If a credit for recovered cleanup/pan solvent material is used to demonstrate compliance and/or used in the calculation of rolling, 12 month emission calculations, the permittee shall maintain the following records for the recovered cleanup/pan solvent material, and the recovery drum or tank serving this emissions unit:

a. the date recovered materials were first added to the recovery tank/drum and the date the materials from the recovery drum or tank were shipped off site;

b. the total amount of material collected and shipped for recycle/recovery and/or disposal at an outside facility, in gallons, on the day it is shipped;

c. record of the VOC content of each cleanup/pan solvent material that is collected for recovery, in pounds per gallon, or a record of the testing results of the VOC content of the material shipped;

d. the mass (lbs) of VOC to be credited to the rolling, 12 month emissions summation, from each shipment of recovered material, calculated using the lowest VOC content of any cleanup/pan solvent material recovered, unless a higher VOC content is established from the testing results of the recovered

material shipped (i.e., b x c), and the date of each such shipment or record of credit; and

e. the record of the total amount of VOC emissions (lbs or tons) that may be applied as a credit, for the materials shipped for recycle/recovery and/or disposal at an outside facility, summed from the records of the VOC emission credits (d), for each shipment recorded during the rolling 12 month period.

(3) For each day during which the permittee burns fuel other than natural gas or propane in this emissions unit, the permittee shall maintain a record of the type and quantity of fuel burned.

(4) This facility shall, on an ongoing basis, evaluate the availability of an alternate coating and coating method that will reduce the emissions from this source and meet the coating specifications of the desired product. Should an alternate coating and/or coating method become available, as based on the Best Available Technology (BAT) for this type of operation, this facility shall submit a schedule for implementation of the alternate coatings and/or coating method within 30 days of the availability.

This facility shall submit quarterly reports that summarize the evaluation of an alternate coating and coating method which details the following information for each coating and/or coating method evaluated:

a. The VOC content, in pounds per gallon;

b. The acceptability;

c. the reason why the alternative coating does not meet specification, for unacceptable coatings;

d. The expected reduction in VOC emissions from the utilization of the acceptable alternate coatings; and

e. The cost of modifying the source to utilize the alternate coatings and/or coating method.

These reports shall be submitted by February 15, May 15, August 15, and November 15 of each year and shall cover the previous calendar quarter (October through December, January through March, April through June, and July through September, respectively).

Once the facility employs coatings in compliance with the requirements of OAC rule 3745-21-09(U)(1) in this source, the evaluation process of alternate coatings and the reporting requirement of this term will be discontinued.

(5) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

*A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall notify the Director (the Ohio EPA, Southwest District Office) in writing of any monthly record showing the use of noncomplying coatings and/or cleanup/pan solvent material. These notifications shall include a copy of such record and shall be sent to the Director (the Ohio EPA, Southwest District Office) within 30 days following the end of the calendar month.

(2) The permittee shall submit the following deviation (excursion) reports, in accordance with the specific requirements of this permit, for the following information:

a. all exceedances of the maximum allowable coatings VOC content of 5.36 pounds per gallon, minus water and exempt solvents, as applied; and

b. all exceedances of the rolling, 12-moth VOC emission limitation of 18.895 tons.

These quarterly deviation (excursion) reports shall be submitted in accordance with Part I- General Terms and Conditions A.1.c.

(3) The permittee shall notify the Director (the Ohio EPA, Southwest District Office) of any record showing the use of a fuel other than natural gas or propane in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (the Ohio EPA, Southwest District Office) within 30 days following the end of the calendar month.

(4) The permittee shall submit the following quarterly deviation (excursion) reports, in accordance with the specific requirements of this permit, for the following information:

a. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

b. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

(5) This facility shall submit quarterly reports that summarize the evaluation of an alternate coating and coating method which details the following information for each coating and/or coating method evaluated:

a. the VOC content, in pounds per gallon;

b. the acceptability;

c. the reason why the alternative coating does not meet specification, for unacceptable coatings;

d. the expected reduction in VOC emissions from the utilization of the acceptable alternate coatings; and

e. the cost of modifying the source to utilize the alternate coatings and/or coating method.

These reports shall be submitted by February 15, May 15, August 15, and November 15 of each year and shall cover the previous calendar quarter (October through December, January through March, April through June, and July through September, respectively).

f) Testing Requirements

(1) Compliance with the emission limitation(s) in b)(1) of these terms and conditions shall be determined in accordance with the following method(s):

a. Emission Limitation:

VOC content of coatings shall not exceed 5.36 lbs VOC/gallon, minus water and exempt solvents, as applied.

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the VOC content of the coatings. The record keeping requirements contained in Section d)(1) shall demonstrate that only materials with these VOC content limitations are applied.

b. Emission Limitation:

Volatile Organic Compound (VOC) emissions from coatings and cleanup/pan solvents materials employed shall not exceed 18.895 tons VOC per rolling 12 month period.

Applicable Compliance Method:

Compliance with the annual allowable VOC emission limitation above shall be determined through the record keeping requirements as established in Section d)(1) of this permit.

c. Emission Limitation:

The emissions from natural gas and propane combustion in the drying ovens shall not exceed the following:

0.91 lb/hr and 4.0 tons/yr NOx;

0.23 lb/hr and 1.0 tons/yr CO;

0.03 lb/hr and 0.09 ton/yr PE;

0.002 lb/hr and 0.01 ton/yr SO2; and

0.023 lb/hr and 0.10 ton/yr VOC.

Applicable Compliance Method:

Compliance with the limits for natural gas combustion within the drying ovens shall be based upon the emission factors from AP-42 "Compilation of Air Pollutant Emission Factors", Tables 1.4-1 and 1.4-2 (7/98). These emission factors (lb pollutant/mmscf) multiplied by the maximum hourly gas burning capacity of the burners (one at 0.78125 mmBtu/hr, two at 1 mmBtu/hr, and four at 0.3125 mmBtu/hr) and times 1 scf/1020 Btu shall be the demonstration of compliance with the hourly limits. Compliance with the ton per year limits are documented by multiplying the calculated hourly limits by 8760 hours in a year and dividing by 2000 pounds.

Compliance with the limits for propane combustion within the drying ovens shall be based upon the emission factors from AP-42 "Compilation of Air Pollutant Emission Factors", Tables 1.5-1 (10/96) These emission factors (lb pollutant/1000 gallons) multiplied by the maximum hourly gas burning capacity of the burners (one at 0.78125 mmBtu/hr, two at 1 mmBtu/hr, and four at 0.3125 mmBtu/hr) and divided by the 91.5 MMBtu/1000 gallons shall be the demonstration of compliance with the hourly limits. Compliance with the ton per year limits are documented by multiplying the calculated hourly limits by 8760 hours in a year and dividing by 2000 pounds.

d. Emission Limitation:

Visible PE from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(1).

e. Allowable Rate of Particulate Emissions (PE) shall not exceed 0.551 lbs per hour

The Allowable Rate of Particulate Emissions limitation represents the emissions unit's potential to emit and was established by the following methodology:

If the (P), Process Weight Rate, (P) is > "0", but < or = to 0.05 tons per hour, the Allowable Rate of Particulate Emissions (E) = 0.551.

Only PE is from the combustion of fuel.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

9. K045, Roll Coater; Department 347

Operations, Property and/or Equipment Description:

one coating line (dept. 184); coat metal decorated products

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	VOC content of coatings shall not exceed 5.36 lbs VOC/gallon, minus water and exempt solvents, as applied. VOC content of cleanup/pan solvent shall not exceed 7.76 pounds per gallon. The emissions from natural gas and propane combustion in the drying ovens shall not exceed the following: 0.57 lb/hr and 2.51 tons/yr NOx; 0.31 lb/hr and 1.35 tons/yr CO; 0.03 lb/hr and 0.12 ton/yr filterable PM; 0.06 lb/hr and 0.28 ton/yr SO2; and 0.02 lb/hr and 0.09 ton/yr VOC. The requirements of this rule also include compliance with the requirements of OAC rules 3745-21-09(U)(2)(f)(ii), 3745-17-11(B)(1), and 3745-17-07(A).
b.	3745-21-09 (U)(2)(f)(ii)	VOC content of coatings shall not exceed 5.36 lbs VOC/gallon, minus water and exempt solvents, as applied. b)(2)a, below.
	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM)	Volatile Organic Compound (VOC) emissions from coatings, and pan and cleanup materials shall not exceed 22.8 tons VOC per rolling 12 month period.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)c, below.
	OAC rule 3745-17-11(A)(2)(b)(i)	The Allowable Rate of Particulate Emission shall not exceed 0.551 lbs/hr.
	OAC rule 3745-17-07(A) (for the drying ovens)	The Visible PE from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.

(2) Additional Terms and Conditions

a. Pursuant to OAC rule 3745-21-09(U)(2)(f)(ii), the best available technology has been determined to be extreme performance coatings that have a VOC content greater than the limitations of OAC rules 3745-21-09(U)(1)(c).

b. The emission limitations for PM10, SO2, NOx, CO and VOC from the combustion of natural gas and/or propane in the drying ovens are established to reflect potentials to emit for this emissions unit. Therefore, no additional monitoring, record keeping and/or reporting requirements are necessary to ensure compliance with these limitations.

c. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The permittee shall burn only natural gas and/or propane as fuel in this emissions unit.

(2) The weight of volatile organic materials applied/used for K045 shall not exceed 22.8 tons per rolling 12 months, calculated using the following formula:

[SUM of all materials employed {[(Pi)(VOCi)[1 - (capture*DRE)]]÷ 2000}] - [(Po)(VOCo) ÷ 2000]

where:

Pi = usage of coating or pan/cleanup solvent i in gallons for the last 12 months

VOCi = volatile organic compound content of coating i or pan/cleanup solvent i in pounds VOC per gallon.

Po = recovered pan/cleanup solvent o in gallons for the last 12 months

VOCo = volatile Organic compound content of pan/cleanup material o in pounds VOC per gallon.

capture = the capture efficiency, assumed to be 0%

DRE = destruction removal efficiency of any control device, 0% without controls

The permittee has sufficient existing records to demonstrate compliance with this limitation during the first twelve months after issuance of this permit.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall collect and record the following information each month for this emissions unit:

a. the name or identification number of each coating, and cleanup/pan solvent material, as applied;

b. the VOC content of each coating, minus water and exempt solvents, as applied;

c. the VOC content of each cleanup/pan solvent material employed;

d. the volume in gallons of each coating employed;

e. the volume in gallons of each cleanup/pan solvent material employed;

f. the monthly VOC emissions from the coatings, and cleanup/pan solvent materials employed, i.e., multiply the monthly volume, in gallons, of each coating and cleanup/pan solvent material employed by its respective VOC content less water and exempt solvents, and summarize the results;

g. the rolling, 12 month usage summation for coatings, and cleanup/pan solvent materials employed;

h. the rolling, 12 month summation of VOC emissions from the coating, and cleanup/pan solvent material employed, prior to any credit for recovered materials; and

i. if a credit from recovered materials is applied, the rolling, 12 month summation of VOC emissions from the coating, ink, and cleanup/pan solvent material employed, less the total emissions credit from recovered materials shipped during the 12 month period (Section III.1.j - Section III.2.e).

(2) If a credit for recovered cleanup/pan solvent material is used to demonstrate compliance and/or used in the calculation of rolling, 12 month emission calculations, the permittee shall maintain the following records for the recovered cleanup/pan solvent material, and the recovery drum or tank serving this emissions unit:

a. the date recovered materials were first added to the recovery tank/drum and the date the materials from the recovery drum or tank were shipped off site;

b. the total amount of material collected and shipped for recycle/recovery and/or disposal at an outside facility, in gallons, on the day it is shipped;

c. a record of the VOC content of each cleanup/pan solvent material that is collected for recovery, in pounds per gallon, or a record of the testing results of the VOC content of the material shipped;

d. the mass (lbs) of VOC to be credited to the rolling, 12 month emissions summation, from each shipment of recovered material, calculated using the lowest VOC content of any cleanup/pan solvent material recovered, unless a higher VOC content is established from the testing results of the recovered material shipped (i.e., b x c), and the date of each such shipment or record of credit; and

e. the record of the total amount of VOC emissions (lbs or tons) that may be applied as a credit, for the materials shipped for recycle/recovery and/or disposal at an outside facility, summed from the records of the VOC emission credits (d), for each shipment recorded during the rolling 12 month period.

(3) For each day during which the permittee burns fuel other than natural gas or propane in this emissions unit, the permittee shall maintain a record of the type and quantity of fuel burned.

(4) This facility shall, on an ongoing basis, evaluate the availability of an alternate coating and coating method that will reduce the emissions from this source and meet the coating specifications of the desired product. Should an alternate coating and/or coating method become available, as based on the Best Available Technology (BAT) for this type of operation, this facility shall submit a schedule for implementation of the alternate coatings and/or coating method within 30 days of the availability.

This facility shall submit quarterly reports that summarize the evaluation of an alternate coating and coating method which details the following information for each coating and/or coating method evaluated:

a. The VOC content, in pounds per gallon;

b. The acceptability;

c. The reason why the alternative coating does not meet specification, for unacceptable coatings;

d. The expected reduction in VOC emissions from the utilization of the acceptable alternate coatings; and

e. The cost of modifying the source to utilize the alternate coatings and/or coating method.

These reports shall be submitted by February 15, May 15, August 15, and November 15 of each year and shall cover the previous calendar quarter (October through December,

January through March, April through June, and July through September, respectively).

Once the facility employs coatings in compliance with the requirements of OAC rule 3745-21-09(U)(1) in this source, the evaluation process of alternate coatings and the reporting requirement of this term will be discontinued.

(5) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

*A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall notify the Director (the Ohio EPA, Southwest District Office) in writing of any monthly record showing the use of non-complying coatings and/or cleanup/pan solvent material. These notifications shall include a copy of such record and shall be sent to the Director (the Ohio EPA, Southwest District Office) within 30 days following the end of the calendar month.

(2) The permittee shall submit the following quarterly deviation (excursion) reports, in accordance with the General Terms and Conditions of this permit, for the following information:

a. all exceedances of the maximum allowable coatings VOC content of 5.36 pounds per gallon, minus water and exempt solvents, as applied; and

b. all exceedances of the rolling, 12-month VOC emission limitation of 22.8 tons.

These quarterly deviation (excursion) reports shall be submitted in accordance with Part I- General Terms and Conditions A.1.c.

(3) The permittee shall notify the Director (the Ohio EPA, Southwest District Office) of any record showing the use of a fuel other than natural gas or propane in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (the Ohio EPA, Southwest District Office) within 30 days following the end of the calendar month.

(4) The permittee shall submit the following quarterly deviation (excursion) reports, in accordance with the General Terms and Conditions of this permit, for the following information:

a. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

b. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

(5) This facility shall submit quarterly reports that summarize the evaluation of an alternate coating and coating method which details the following information for each coating and/or coating method evaluated:

a. The VOC content, in pounds per gallon;

b. The acceptability;

c. The reason why the alternative coating does not meet specification, for unacceptable coatings;

d. The expected reduction in VOC emissions from the utilization of the acceptable alternate coatings; and

e. The cost of modifying the source to utilize the alternate coatings and/or coating method.

These reports shall be submitted by February 15, May 15, August 15, and November 15 of each year and shall cover the previous calendar quarter (October through December, January through March, April through June, and July through September, respectively).

f) Testing Requirements

(1) Compliance with the emission limitation(s) in Section A.1. of these terms and conditions shall be determined in accordance with the following method(s):

a. Emission Limitation:

VOC content of coatings shall not exceed 5.36 lbs VOC/gallon, minus water and exempt solvents, as applied.

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the VOC content of the coatings. The record keeping requirements contained in Section A.III.1 shall demonstrate that only materials with these VOC content limitations are applied.

b. Emission Limitation:

VOC content of cleanup/pan solvent shall not exceed 7.76 lbs VOC/gallon, as applied

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the VOC content of the coatings. The record keeping requirements contained in Section III.1 shall demonstrate that only materials with these VOC content limitations are applied.

c. Emission Limitation:

Volatile Organic Compound (VOC) emissions from coatings and pan and cleanup materials shall not exceed 22.8 tons VOC per rolling 12 month period.

Applicable Compliance Method:

Compliance with the above term shall be demonstrated through the record keeping requirements in section III of this emission unit.

d. Emission Limitation:

The emissions from natural gas and propane combustion in the direct fired drying ovens shall not exceed the following:

0.57 lb/hr and 2.51 tons/yr NOx;

0.31 lb/hr and 1.35 tons/yr CO;

0.03 lb/hr and 0.12 ton/yr filterable PM;

0.06 lb/hr and 0.28 ton/yr SO2; and

0.02 lb/hr and 0.09 ton/yr VOC.

Applicable Compliance Method:

Compliance with the limits for natural gas combustion within the drying ovens shall be based upon the emission factors from AP-42 "Compilation of Air Pollutant Emission Factors", Tables 1.4-1 and 1.4-2 (7/98). These emission factors (lb pollutant/mmscf) multiplied by the maximum hourly gas burning

capacity of the burners (one at 0.78125 mmBtu/hr, two at 1 mmBtu/hr, and four at 0.3125 mmBtu/hr) and times 1 scf/1020 Btu shall be the demonstration of compliance with the hourly limits. Compliance with the ton per year limits are documented by multiplying the calculated hourly limits by 8760 hours in a year and dividing by 2000 pounds.

Compliance with the limits for propane combustion within the drying ovens shall be based upon the emission factors from AP-42 "Compilation of Air Pollutant Emission Factors", Tables 1.5-1 (10/96) These emission factors (lb pollutant/1000 gallons) multiplied by the maximum hourly gas burning capacity of the burners (one at 0.78125 mmBtu/hr, two at 1 mmBtu/hr, and four at 0.3125 mmBtu/hr) and divided by the 91.5 mmBtu/1000 gallons shall be the demonstration of compliance with the hourly limits. Compliance with the ton per year limits are documented by multiplying the calculated hourly limits by 8760 hours in a year and dividing by 2000 pounds.

e. Emission Limitation:

Visible PE from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(1).

f. Allowable Rate of Particulate Emissions (PE) shall not exceed 0.551 lbs per hour

The Allowable Rate of Particulate Emissions limitation represents the emissions unit's potential to emit and was established by the following methodology:

If the (P), Process Weight Rate, (P) is > "0", but < or = to 0.05 tons per hour, the Allowable Rate of Particulate Emissions (E) = 0.551.

Only PE is from the combustion of fuel.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

10. K046, E-coat Line

Operations, Property and/or Equipment Description:

Electrodeposition surface coating of miscellaneous metal parts

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) b)(1)f, d)(4), d)(5), and d)(6).

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) and PTI 05-14394	The Volatile Organic Compounds (VOC) content of replenishment material used in this emissions unit shall not exceed 0.19 lb/gallon, as applied b)(2)b, below. The VOC content of cleanup materials employed on this emission unit shall not exceed 0.68 lb VOC/lb cleanup material The emissions from natural gas combustion in the drying ovens shall not exceed the following: 0.429 lb/hr and 1.88 tons/yr NOx; 0.36 lb/hr and 1.58 tons/yr CO; 0.033 lb/hr and 0.14 ton/yr filterable PM; 0.003 lb/hr and 0.01 ton/yr SO2; and 0.024 lb/hr and 0.1 ton/yr VOC. b)(2)a, below.
b.	OAC rule 3745-31-05(C) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The maximum replenishment material usage for this emissions unit shall not exceed 100,000 gallons per rolling 12-month period. The maximum cleanup material usage for this emissions unit shall not exceed 150 gallons per rolling 12-month period.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		Emissions of VOC excluding oven emissions shall not exceed 9.93 tons per rolling 12-month period. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)c, below.
c.	OAC rule 3745-17-07(A) (for the drying ovens)	The Visible PE from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.
d.	OAC rule 3745-17-11(A)(2)(b)(i)	The Allowable Rate of Particulate Emission shall not exceed 0.551 lbs/hr.
e.	OAC rule 3745-17-11(B) (for the drying ovens)	The PE limitation specified by this rule is less stringent than the PE limitation established pursuant to OAC rule 3745-31-05(A)(3).
f.	OAC rule 3745-114-01	Ohio Toxic Policy

(2) Additional Terms and Conditions

a. The emission limitations for PM10, SO2, NOx, CO and VOC from the combustion of natural gas and/or propane in the drying ovens are established to reflect potentials to emit for this emissions unit. Therefore, no additional monitoring, record keeping and/or reporting requirements are necessary to ensure compliance with these limitations.

b. This limitation, for the Powerchon 590 Black coating, calculates to 0.64 lb VOC per gallon of coating minus water and exempt solvents, and is more stringent than the limits found in OAC rule 3745-21-09(U).

c. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The permittee shall burn only natural gas in this emissions unit.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall collect and record the following information each month for this emissions unit:

a. the name and identification number of each coating, and cleanup material, as applied;

b. the VOC content of each coating, as applied;

c. the VOC content of each cleanup material employed;

d. the volume in gallons of each coating employed;

e. the volume in gallons of each cleanup material employed;

f. the monthly VOC emissions from the coatings, and cleanup materials employed, i.e., multiply the monthly volume, in gallons, of each coating and cleanup/pan solvent material employed by its respective VOC content, and summarize the results;

g. the rolling, 12 month usage summation for coatings, and cleanup materials employed; and

h. the rolling, 12 month summation of VOC emissions from the coating, and cleanup material employed, prior to any credit for recovered materials.

(2) For each day during which the permittee burns fuel other than natural gas in this emissions unit, the permittee shall maintain a record of the type and quantity of fuel burned.

(3) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

*A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

(4) The permit to install for this emissions unit was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model. The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Carbon Black

TLV (mg/m3): 3.5 mg/m3

Maximum Hourly Emission Rate (g/sec): 0.133

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 40.08

MAGLC (ug/m3): 83.33

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound or chemical with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled, as documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices");

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

(5) If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) meet(s) the definition of a "modification" under other provisions of the rule, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

a. description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of the evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

(6) If the permittee determines that the "Air Toxics Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 (VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii), then the permittee shall obtain a final permit to install prior to the change.

e) Reporting Requirements

(1) The permittee shall notify the Director (the Ohio EPA, Southwest District Office) in writing of any monthly record showing the use of non-complying coatings and/or cleanup/pan solvent material. These notifications shall include a copy of such record and shall be sent to the Director (the Ohio EPA, Southwest District Office) within 30 days following the end of the calendar month.

(2) The permittee shall submit quarterly deviation (excursion) reports which identify all exceedances of the following:

a. the rolling, 12 month usage limitation for coatings replenishment materials of 100,000 gallons;

b. the rolling, 12 month usage limitation for cleanup materials of 150 gallons;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These quarterly deviation (excursion) reports shall be submitted in accordance with Part I - General Terms and Conditions A.1.c.

(3) The permittee shall notify the Director (the Ohio EPA, Southwest District Office) of any record showing the use of a fuel other than natural gas or propane in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (the Ohio EPA, Southwest District Office) within 30 days following the end of the calendar month.

f) Testing Requirements

(1) Compliance with the emission limitation(s) in b)(1) of these terms and conditions shall be determined in accordance with the following method(s):

a. Emission Limitations:

The VOC content of replenishment material used in this emissions unit shall not exceed 0.19 lb/gallon.

The VOC content of cleanup materials employed on this emission unit shall not exceed 0.68 lb VOC/lb of cleanup material

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the VOC content of the coatings and cleanup materials. The record keeping requirements contained in Section III.1 shall demonstrate that only materials with these VOC content limitations are applied. Emission Limitations:

The VOC content of replenishment material used in this emissions unit shall not exceed 0.19 lb/gallon.

The VOC content of cleanup materials employed on this emission unit shall not exceed 0.68 lb VOC/lb of cleanup material

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the VOC content of the coatings and cleanup materials. The record keeping requirements contained in Section III.1 shall demonstrate that only materials with these VOC content limitations are applied.

b. The emissions from natural gas combustion in the drying ovens shall not exceed the following:

0.429 lb/hr and 1.88 tons/yr NOx;

0.36 lb/hr and 1.58 tons/yr CO;

0.033 lb/hr and 0.14 ton/yr filterable PM;

0.003 lb/hr and 0.01 ton/yr SO2; and

0.024 lb/hr and 0.1 ton/yr VOC.

Applicable Compliance Method:

Compliance with the limits for natural gas combustion within the drying ovens shall be based upon the emission factors from AP-42 "Compilation of Air Pollutant Emission Factors", Tables 1.4-1 and 1.4-2 (7/98). These emission factors (lb pollutant/10 mmscf) multiplied by the maximum hourly gas burning capacity of the burners (4.375 mmBtu) and times 1 scf/1020 00 Btu shall be the demonstration of compliance with the hourly limits. Compliance with the ton per year limits are documented by multiplying the calculated hourly limits by 8760 hours in a year and dividing by 2000 pounds.

c. Emission Limitation:

Emissions of VOC excluding oven emissions shall not exceed 9.93 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance shall be assumed so long as the permittee does not exceed the VOC content limitations for both coatings (0.19 lb/gallon) and cleanup materials (0.68 lb/lb of cleanup material), nor the usage limitations for coatings (100,000 gallons) and cleanup materials (150 gallons). Compliance may also be demonstrated through the following calculation:

AER = [SUM of all materials employed {[(Pi)(VOCi)[1 - (capture*DRE)]]÷ 2000}]

where:

AER = Annual emission rate, in tons;

P = usage of each coating or cleanup material in gallons;

VOC = volatile organic compound content of each coating or cleanup material in pounds VOC per gallon;

capture = the capture efficiency, assumed to be 0%; and

DRE = destruction removal efficiency of any control device, 0% without controls.

d. Emission Limitation:

Visible PE from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(1).

e. Allowable Rate of Particulate Emissions (PE) shall not exceed 0.551 lbs per hour

The Allowable Rate of Particulate Emissions limitation represents the emissions unit's potential to emit and was established by the following methodology:

If the (P), Process Weight Rate, (P) is > "0", but < or = to 0.05 tons per hour, the Allowable Rate of Particulate Emissions (E) = 0.551.

Only PE is from the combustion of fuel.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

11. K048, Dept 350

Operations, Property and/or Equipment Description:

Department 350 printing/coating line; coat metal decorated products

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3)	VOC content of non-compliant extreme performance coatings shall not exceed 5.21 lbs VOC/gallon, as applied minus water and exempt solvents The volatile organic content limitation for cleanup/pan solvent shall not exceed 7.76 pounds per gallon. Volatile Organic Compound (VOC) emissions from coatings, pan and cleanup materials shall not exceed 27.8 tons VOC per rolling 12-month period. The emissions from natural gas and propane combustion in the drying ovens and flame treater shall not exceed the following: 2.12 lbs/hr and 9.28 tons/yr NOx; 1.14 lbs/hr and 5.0 tons/yr CO; 0.11 lb/hr and 0.46 ton/yr filterable PM; 0.24 lb/hr and 1.02 ton/yr SO2; and 0.08 lb/hr and 0.34 ton/yr VOC. The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(C), OAC rule 3745-21-09(U)(1), and OAC rule 3745-17-11(B)(1).

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		b)(2)b and b)(2)c, below.
b.	3745-21-09 (U)(2)(f)(ii)	VOC content of non-compliant extreme performance coatings shall not exceed 5.21 lbs VOC/gallon, as applied minus water and exempt solvents. b)(2)a, below
	OAC rule 3745-31-05(C) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)d, below.
	OAC rule 3745-17-07(A) (for the drying ovens)	The Visible PE from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.
	OAC rule 3745-17-11(A)(2)(b)(i)	The Allowable Rate of Particulate Emission shall not exceed 0.551 lbs/hr.
	OAC rule 3745-17-11(B) (for the drying ovens)	The PE limitation specified by this rule is less stringent than the PE limitation established pursuant to OAC rule 3745-31-05(A)(3).

(2) Additional Terms and Conditions

a. Pursuant to OAC rule 3745-21-09(U)(2)(f), the best available technology has been determined to be extreme performance coatings that have a VOC content greater than the limitations of OAC rules 3745-21-09(U)(1)(c).

b. The emission limitations for PM10, SO2, NOx, CO and VOC from the combustion of natural gas and/or propane in the drying ovens are established to reflect potentials to emit for this emissions unit. Therefore, no additional monitoring, record keeping and/or reporting requirements are necessary to ensure compliance with these limitations.

c. Extreme performance coatings are exempted by the BAT determination in this permit and the exemption under OAC rule 3745-21-09(U)(2)(f) in this permit to install from the requirements for extreme performance coatings in OAC rule 3745-21-09(U)(1). If at any time a non-extreme performance coating is used in K048, that coating must comply with the requirements of OAC rule 3745-21-09(U)(1).

For the purposes of discontinuing the coating evaluation in A.2.b, the VOC content of compliant extreme performance coatings shall not exceed 3.5 lbs VOC/gallon, as applied minus water and exempt solvents.

d. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The permittee shall burn only natural gas or propane in this emission unit.

(2) The weight of volatile organic materials applied/used for K048 shall not exceed 27.8 tons of per rolling 12 months, calculated using the following formula:

[SUM of all materials employed {[(Pi)(VOCi)[1 - (capture*DRE)]]÷ 2000}] - [(Ri)(Po)(VOCo) ÷ 2000]

where:

Pi = usage of each coating, cleanup, or restoration material in gallons

VOCi = volatile Organic compound content of each coating, cleanup, or restoration material in pounds VOC per gallon.

Capture = the capture efficiency, assumed to be 0%

DRE = destruction removal efficiency of any control device, 0% without controls

Ri =ratio of solvent used on this specific emission unit/total of material used on all the emission units minus the amount used on K045.

Po = recovered pan/cleanup solvent o recovered from all emission units minus material recovered from K045 in gallons for the last 12-months.

VOCo =VOC content of recovered solvents in pounds of VOC per gallon

The permittee has sufficient existing records to demonstrate compliance with this limitation during the first twelve months after issuance of this permit.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall collect and record the following information each month for this emissions unit:

a. the name or identification number of each coating, and cleanup/pan solvent material, as applied;

b. the VOC content of each coating, minus water and exempt solvents, as applied;

c. the VOC content of each cleanup/pan solvent material employed;

d. the volume in gallons of each coating employed;

e. the volume in gallons of each cleanup/pan solvent material employed;

f. the monthly VOC emissions from the coatings, and cleanup/pan solvent materials employed, i.e., multiply the monthly volume, in gallons, of each coating and cleanup/pan solvent material employed by its respective VOC content less water and exempt solvents, and summarize the results;

g. the rolling, 12 month weight of volatile organic materials applied/used summation for coatings, and cleanup/pan solvent employed as calculated per B.3;

h. the rolling, 12 month summation of VOC emissions from the coating, and cleanup/pan solvent material employed, prior to any credit for recovered materials i.e., the 12 month summation of II.1.f performed at the end each month for the past 12 months; and

i. if a credit from recovered materials is applied, the rolling, 12 month summation of VOC emissions from the coating, ink, and cleanup/pan solvent material employed, less the total emissions credit from recovered materials shipped during the 12 month period (Section III.1.h - Section III.2.e).

(2) If a credit for recovered cleanup/pan solvent material is used to demonstrate compliance and/or used in the calculation of rolling, 12 month emission calculations, the permittee shall maintain the following records for the recovered cleanup/pan solvent material, and the recovery drum or tank serving this emissions unit:

a. the date recovered materials were first added to the recovery tank/drum and the date the materials from the recovery drum or tank were shipped off site;

b. the total amount of material collected and shipped for recycle/recovery and/or disposal at an outside facility, in gallons, on the day it is shipped;

c. a record of the VOC content of each cleanup/pan solvent material that is collected for recovery, in pounds per gallon, or a record of the testing results of the VOC content of the material shipped;

d. the mass (lbs) of VOC to be credited to the rolling, 12 month emissions summation, from each shipment of recovered material, calculated using the lowest VOC content of any cleanup/pan solvent material recovered, unless a higher VOC content is established from the testing results of the recovered material shipped (i.e., b x c), and the date of each such shipment or record of credit; and

e. the record of the total amount of VOC emissions (lbs or tons) that may be applied as a credit, for the materials shipped for recycle/recovery and/or disposal at an outside facility, summed from the records of the VOC emission credits (d), for each shipment recorded during the rolling 12 month period.

(3) For each day during which the permittee burns fuel other than natural gas in this emissions unit, the permittee shall maintain a record of the type and quantity of fuel burned.

(4) This facility shall, on an ongoing basis, evaluate the availability of an alternate coating and coating method that will reduce the emissions from this source and meet the coating specifications of the desired product. Should an alternate coating and/or coating method become available, as based on the Best Available Technology (BAT) for this type of operation, this facility shall submit a schedule for implementation of the alternate coatings and/or coating method within 30 days of the availability.

This facility shall submit quarterly reports that summarize the evaluation of an alternate coating and coating method which details the following information for each coating and/or coating method evaluated:

a. The VOC content, in pounds per gallon;

b. The acceptability;

c. The reason why the alternative coating does not meet specification, for unacceptable coatings;

d. The expected reduction in VOC emissions from the utilization of the acceptable alternate coatings; and

e. The cost of modifying the source to utilize the alternate coatings and/or coating method.

These reports shall be submitted by February 15, May 15, August 15, and November 15 of each year and shall cover the previous calendar quarter (October through December, January through March, April through June, and July through September, respectively).

Once the facility employs coatings in compliance with the requirements of OAC rule 3745-21-09(U)(1) in this source, the evaluation process of alternate coatings and the reporting requirement of this term will be discontinued.

e) Reporting Requirements

(1) The permittee shall notify the Director (the Ohio EPA, Southwest District Office) in writing of any monthly record showing the use of non-complying coatings and/or cleanup/pan solvent material. These notifications shall include a copy of such record and shall be sent to the Director (the Ohio EPA, Southwest District Office) within 30 days following the end of the calendar month.

(2) The permittee shall submit quarterly deviation (excursion) reports which identify all exceedances of the rolling, 12 month emission limitation for volatile organic compounds from coatings and pan/cleanup materials of 27.8 tons.

These deviation (excursion) reports shall be submitted in accordance with the specific requirements in this permit.

(3) The permittee shall notify the Director (the Ohio EPA, Southwest District Office) of any record showing the use of a fuel other than natural gas or propane was burned in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (the Ohio EPA, Southwest District Office) within 30 days following the end of the calendar month.

(4) This facility shall submit quarterly reports that summarize the evaluation of an alternate coating and coating method which details the following information for each coating and/or coating method evaluated:

a. The VOC content, in pounds per gallon;

b. The acceptability;

c. The reason why the alternative coating does not meet specification, for unacceptable coatings;

d. The expected reduction in VOC emissions from the utilization of the acceptable alternate coatings; and

e. The cost of modifying the source to utilize the alternate coatings and/or coating method.

These reports shall be submitted by February 15, May 15, August 15, and November 15 of each year and shall cover the previous calendar quarter (October through December, January through March, April through June, and July through September, respectively).

(5) The permittee shall submit quarterly deviation (excursion) reports which identify all exceedances of the following:

a. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

b. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance with the specific requirements in this permit.

f) Testing Requirements

(1) Compliance with the emission limitation(s) in b)(1) of these terms and conditions shall be determined in accordance with the following method(s):

a. Emission Limitation:

Volatile Organic Compound (VOC) emissions from coatings, and pan and cleanup materials shall not exceed 27.8 tons VOC per rolling 12 month period.

b. Emission Limitation:

VOC content of non-compliant extreme performance coatings shall not exceed 5.21 lbs VOC/gallon, as applied minus water and exempt solvents

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the VOC content of the coatings. The record keeping requirements contained in d)(1) shall demonstrate that only materials with these VOC content limitations are applied.

c. Emission Limitation:

The emissions from natural gas and propane combustion in the drying ovens and flame treater shall not exceed the following:

2.12 lbs/hr and 9.28 tons/yr NOx;

1.14 lbs/hr and 5.0 tons/yr CO;

0.11 lb/hr and 0.46 ton/yr filterable PM;

0.24 lb/hr and 1.02 ton/yr SO2; and

0.08 lb/hr and 0.34 ton/yr VOC.

Applicable Compliance Method:

Compliance with the limits for natural gas combustion within the drying ovens shall be based upon the emission factors from AP-42 "Compilation of Air Pollutant Emission Factors", Tables 1.4-1 and 1.4-2 (7/98). These emission factors (lb pollutant/10 mmscf) multiplied by the maximum hourly gas burning capacity of the burners (one at 2.5 mmBtu/hr, two at 3.75 mmBtu/hr, one at 3.4375 mmBtu/hr, and one at 0.4 mmBtu/hr) and times 1 scf/1020 Btu shall be the demonstration of compliance with the hourly limits. Compliance with the ton per year limits are documented by multiplying the calculated hourly limits by 8760 hours in a year and dividing by 2000 pounds.

Compliance with the limits for propane combustion within the drying ovens shall be based upon the emission factors from AP-42 "Compilation of Air Pollutant Emission Factors", Tables 1.5-1 (10/96) These emission factors (lb pollutant/1000 gallons) multiplied by the maximum hourly gas burning capacity of the burners (one at 2.5 mmBtu/hr, two at 3.75 mmBtu/hr, one at 3.4375 mmBtu/hr, and one at 0.4 mmBtu/hr) and divided by the 91.5 MMBtu/1000 gallons shall be the demonstration of compliance with the hourly limits. Compliance with the ton per year limits are documented by multiplying the calculated hourly limits by 8760 hours in a year and dividing by 2000 pounds.

d. Allowable Rate of Particulate Emissions (PE) shall not exceed 0.551 lbs per hour

The Allowable Rate of Particulate Emissions limitation represents the emissions unit's potential to emit and was established by the following methodology:

If the (P), Process Weight Rate, (P) is > "0", but < or = to 0.05 tons per hour, the Allowable Rate of Particulate Emissions (E) = 0.551.

Only PE is from the combustion of fuel.

e. Emission Limitation:

VOC content of cleanup/pan solvent shall not exceed 7.76 lbs VOC/gallon, as applied

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the VOC content of the coatings. The record keeping requirements contained in d)(1) shall demonstrate that only materials with these VOC content limitations are applied.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

12. P081, Stamping Press 1-269

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

Where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

13. P082, Stamping Press 1-082

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

Where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

14. P085, Stamping Press 1-213

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(1) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None

15. P086, Stamping Press 1-247

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

16. P087, Stamping Press 1-087

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None

17. P088, Stamping Press 1-088

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
.a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

18. P089, Stamping Press 1-248

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

19. P090, Stamping Press 1-249

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

20. P091, Stamping Press 1-091

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

21. P092, Stamping Press 1-251

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

22. P093, Stamping Press 1-252

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

23. P094, Stamping Press 1-253

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

24. P095, Stamping Press 1-272

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

25. P096, Stamping Press 1- 276

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

26. P097, Stamping Press 1- 278

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

27. P098, Stamping Press 1-279

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

28. P099, Stamping Press 1-280

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

29. P100, Stamping Press 1-286

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

30. P101, Stamping Press 1-291

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

31. P102, Stamping Press 1-292

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

32. P103, Stamping Press 1-293

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None

33. P104, Stamping Press 1-299

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

b. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon; and

c. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined.

(2) The permittee shall submit quarterly deviation (excursion) reports which identify all exceedances of the following:

a. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

b. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

(3) These deviation (excursion) reports shall be submitted in accordance the specific requirements of this permit.

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

34. P105, Rollformer 7-141

Operations, Property and/or Equipment Description:

Rollformer 7-141

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

(2) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(3) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

f) Miscellaneous Requirements

(1) None.

35. P106, Rollformer 7-240

Operations, Property and/or Equipment Description:

Rollformer 7-240

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content lubricating oils shall not exceed 6.76 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. b)(2)b, below.
c.	OAC 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at

this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) VOC emissions from emissions units P081 through P106 combined shall not exceed 48.02 tons per rolling 12-month period. Emissions shall be calculated according to the following formula:

Sum of all (Gi)(Vi) ÷ 2000 lbs/ton

where:

Gi = usage of lubricant i in gallons for the rolling 12-month period

Vi = VOC content of lubricant i in pounds of VOC per gallon, subject to the following limitation: Vi 6.76 lbs VOC/gallon

i = total number of unique lubricants used on emission units P081 through P106 combined.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P081 through P106, combined:

a. the company name and or identification, for each lubricating oil with a VOC content greater than zero (0) employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed per rolling, 12-month summation;

d. the VOC content of each lubricating oil solvent employed, in pounds per gallon;

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calender months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for Type 1 lubricating oils of 6.76 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 48.02 tons for emissions units P081 through P106, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average; and

e. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. Emission Limitation:

The combined volatile organic compound (VOC) emissions shall not exceed 48.02 tons as a rolling, 12-month summation for emissions units P081 through P106, inclusive.

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 48.02 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P081 through P106.

The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

i. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

ii. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

These deviation (excursion) reports shall be submitted in accordance as specified in this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

36. P107, Stamping Press 1-261

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content of lubricating oils shall not exceed 5.75 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
c.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

37. P108, Stamping Press 1-266

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content of lubricating oils shall not exceed 5.75 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
c.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements

(1) None.

38. P109, Stamping Press 1-267

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content of lubricating oils shall not exceed 5.75 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
c.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

39. P110, Stamping Press 1-290

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content of lubricating oils shall not exceed 5.75 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
c.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

40. P111, Stamping Press 1-301

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content of lubricating oils shall not exceed 5.75 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
c.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

41. P112, Stamping Press 1-302

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content of lubricating oils shall not exceed 5.75 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
c.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

42. P113, Stamping Press 1-227

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content of lubricating oils shall not exceed 5.75 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
c.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

43. P114, Stamping Press 1-237

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content of lubricating oils shall not exceed 5.75 pounds per gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
c.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

44. P115, Screen Washer A

Operations, Property and/or Equipment Description:

Screen Washer using solvent cleaner

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content of the cleaning solution shall not exceed 8.5 lbs VOC/gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	VOC emissions from emission units P115 and P116 combined shall not exceed 40.0 tons per rolling 12-month period. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)a, below.

(2) Additional Terms and Conditions

a. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate..

c) Operational Restrictions

(1) The VOC in raw materials usage shall not cause VOC emissions from emission units P115 and P116 combined to exceed 40.0 tons per rolling 12-month period based on the following equation:

AER= ([Sum of all (Vi)(Gi)] ÷ 2000 lbs/Ton) - [(Rw)(Po)(VOCo)÷ 2000 lbs/Ton]

where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi =VOC content in pounds per gallon of each cleaning solution; subject to the following limitation: Vi 8.5 lbs VOC/gallon;

Gi = Gallons used of each cleaning solution for the rolling 12 month period;

Rw = ratio of solvent used on Emission units P115 and P116 to (total solvent used on all Emission units - the amount of solvent used on Emission unit K045);

Po = total gallons of recovered solvents less the gallons of solvent recovered from Emission unit K045, for the subject time period; and

VOCo =VOC content of recovered solvents in pounds of VOC per gallon.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P115 and P116, combined:

a. the company name or identification for each cleaning solution employed;

b. the volume, in gallons, of each cleaning solution employed;

c. the VOC content of each cleaning solution employed, in pounds per gallon;

d. the rolling 12-month summation of VOC emissions from the cleaning solution employed, prior to any credit claimed for solvent recycling i.e., the sum of the usage of each cleaning solution employed multiplied by its respective VOC content.

(2) If a credit for recovered cleaning solution is used to demonstrate compliance and/or used in the calculation of rolling, 12 month emission calculations, the permittee shall maintain the following records for the recovered cleaning solution, and the recovery drum or tank serving this emissions unit:

a. the date recovered materials were first added to the recovery tank/drum and the date the materials from the recovery drum or tank were shipped off site;

b. the total amount of material collected and shipped for recycle/recovery and/or disposal at an outside facility, in gallons, on the day it is shipped;

c. a record of the VOC content of each cleanup/pan solvent material that is collected for recovery, in pounds per gallon, or a record of the testing results of the VOC content of the material shipped;

d. the mass (lbs) of VOC to be credited to the rolling, 12 month emissions summation, from each shipment of recovered material, calculated using the lowest VOC content of any cleanup/pan solvent material recovered, unless a higher VOC content is established from the testing results of the recovered material shipped (i.e., b x c), and the date of each such shipment or record of credit; and

e. the record of the total amount of VOC emissions (lbs or tons) that may be applied as a credit, for the materials shipped for recycle/recovery and/or disposal at an outside facility, summed from the records of the VOC emission credits (d), for each shipment recorded during the rolling 12 month period.

(3) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. The permittee shall submit deviation (excursion) reports which identify all exceedances of the rolling, 12-month limitation upon VOC emissions for emission units P115 and P116 combined of 40 tons;

b. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

c. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall notify the Director (the Ohio EPA, Southwest District Office) in writing of any monthly record showing the use of non-complying cleaning solution. These notifications shall include a copy of such record and shall be sent to the Director (the Ohio EPA, Southwest District Office) within 30 days following the end of the calendar month.

f) Testing Requirements

(1) Compliance with the emission limitations in Section b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. Emission Limitation:

The volatile organic compound (VOC) content of the cleaning solution shall not exceed 8.5 lbs VOC/gallon.

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the VOC content of the cleaning solutions. The record keeping requirements contained in d)(1). shall demonstrate that only materials with these VOC content limitations are applied.

b. Emission Limitation:

VOC emissions from emission units P115 and P116 combined shall not exceed 40.0 tons per rolling 12-month period.

Equation:

[Sum of all (Vi)(Gi)] ÷ 2000 lbs/Ton] - [(Rw)(Po)(VOCo)÷ 2000 lbs/Ton]

where

Vi = VOC content in pounds per gallon of each cleaning solution, subject to the following limitation: Vi 8.5 lbs VOC/gallon;

Gi = Gallons used of each cleaning solution for the rolling 12 month period;

Rw = ratio of solvent used on Emission units P115 and P116 to (total solvent used on all Emission units - the amount of solvent used on Emission unit K045);

Po = total gallons of recovered solvents less the gallons of solvent recovered from Emission unit K045, for the subject time period; and

VOCo = VOC content of recovered solvents in pounds of VOC per gallon

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 10.5 tons as a rolling, 12-month summation.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P107 through P114 and P117 through P140, combined.

d. Emission Limitation:

VOC emissions from these emissions units shall not exceed 40.0 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P115 and P116.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each solvent containing material.

g) Miscellaneous Requirements

(1) None.

45. P116, Screen Washer B

Operations, Property and/or Equipment Description:

Screen Washer using solvent cleaner

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC Rule 3745-31-05(A)(3)	The volatile organic compound (VOC) content of the cleaning solution shall not exceed 8.5 lbs VOC/gallon.
b.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	VOC emissions from emission units P115 and P116 combined shall not exceed 40.0 tons per rolling 12-month period. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)a, below.

(2) Additional Terms and Conditions

a. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The VOC in raw materials usage shall not cause VOC emissions from emission units P115 and P116 combined to exceed 40.0 tons per rolling 12-month period based on the following equation:

AER= ([Sum of all (Vi)(Gi)] ÷ 2000 lbs/Ton) - [(Rw)(Po)(VOCo)÷ 2000 lbs/Ton]

where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi =VOC content in pounds per gallon of each cleaning solution; subject to the following limitation: Vi 8.5 lbs VOC/gallon;

Gi = Gallons used of each cleaning solution for the rolling 12 month period;

Rw = ratio of solvent used on Emission units P115 and P116 to (total solvent used on all Emission units - the amount of solvent used on Emission unit K045);

Po = total gallons of recovered solvents less the gallons of solvent recovered from Emission unit K045, for the subject time period; and

VOCo =VOC content of recovered solvents in pounds of VOC per gallon.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P115 and P116, combined:

a. the company name or identification for each cleaning solution employed;

b. the volume, in gallons, of each cleaning solution employed;

c. the VOC content of each cleaning solution employed, in pounds per gallon;

d. the rolling 12-month summation of VOC emissions from the cleaning solution employed, prior to any credit claimed for solvent recycling i.e., the sum of the usage of each cleaning solution employed multiplied by its respective VOC content.

(2) If a credit for recovered cleaning solution is used to demonstrate compliance and/or used in the calculation of rolling, 12 month emission calculations, the permittee shall maintain the following records for the recovered cleaning solution, and the recovery drum or tank serving this emissions unit:

a. the date recovered materials were first added to the recovery tank/drum and the date the materials from the recovery drum or tank were shipped off site;

b. the total amount of material collected and shipped for recycle/recovery and/or disposal at an outside facility, in gallons, on the day it is shipped;

c. a record of the VOC content of each cleanup/pan solvent material that is collected for recovery, in pounds per gallon, or a record of the testing results of the VOC content of the material shipped;

d. the mass (lbs) of VOC to be credited to the rolling, 12 month emissions summation, from each shipment of recovered material, calculated using the lowest VOC content of any cleanup/pan solvent material recovered, unless a higher VOC content is established from the testing results of the recovered material shipped (i.e., b x c), and the date of each such shipment or record of credit; and

e. the record of the total amount of VOC emissions (lbs or tons) that may be applied as a credit, for the materials shipped for recycle/recovery and/or disposal at an outside facility, summed from the records of the VOC emission credits (d), for each shipment recorded during the rolling 12 month period.

(3) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. The permittee shall submit deviation (excursion) reports which identify all exceedances of the rolling, 12-month limitation upon VOC emissions for emission units P115 and P116 combined of 40 tons;

b. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

c. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the rolling, 12-month limitation upon VOC emissions for emission units P115 and P116 combined of 40 tons.

f) Testing Requirements

(1) Compliance with the emission limitations in Section b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. Emission Limitation:

The volatile organic compound (VOC) content of the cleaning solution shall not exceed 8.5 lbs VOC/gallon.

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the VOC content of the cleaning solutions. The record keeping requirements contained in d)(1). shall demonstrate that only materials with these VOC content limitations are applied.

b. Emission Limitation:

VOC emissions from emission units P115 and P116 combined shall not exceed 40.0 tons per rolling 12-month period.

Equation:

[Sum of all (Vi)(Gi)] ÷ 2000 lbs/Ton] - [(Rw)(Po)(VOCo)÷ 2000 lbs/Ton]

where

Vi = VOC content in pounds per gallon of each cleaning solution, subject to the following limitation: Vi 8.5 lbs VOC/gallon;

Gi = Gallons used of each cleaning solution for the rolling 12 month period;

Rw = ratio of solvent used on Emission units P115 and P116 to (total solvent used on all Emission units - the amount of solvent used on Emission unit K045);

Po = total gallons of recovered solvents less the gallons of solvent recovered from Emission unit K045, for the subject time period; and

VOCo = VOC content of recovered solvents in pounds of VOC per gallon

Applicable Compliance Method:

Compliance with the rolling, 12-month VOC emissions limitation shall be determined through the record keeping requirements established in d) of this permit.

c. Emission Limitation:

VOC emissions from this emissions unit shall not exceed 10.5 tons as a rolling, 12-month summation.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P107 through P114 and P117 through P140, combined.

d. Emission Limitation:

VOC emissions from these emissions units shall not exceed 40.0 tons per rolling 12-month period.

Applicable Compliance Method:

Compliance with this limitation shall be based upon compliance with the grouped annual limit for P115 and P116.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each solvent containing material.

g) Miscellaneous Requirements

(1) None.

46. P117, Stamping Press 1-001

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

47. P118, Stamping Press 1-002

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

48. P119, Stamping Press 1-003

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

49. P120, Stamping Press 1-014

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None

50. P121, Stamping Press 1-025

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

51. P122, Stamping Press 1-026

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

52. P123, Stamping Press 1-034

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

53. P124, Stamping Press 1-048

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

54. P125, Stamping Press 1-052

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

55. P126, Stamping Press 1-81

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

56. P127, Stamping Press 1-89

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

57. P128, Stamping Press 1-90

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

58. P129, Stamping Press 1-92

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

59. P130, Stamping Press 1-93

Operations, Property and/or Equipment Description:

fStamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

60. P131, Stamping Press 1-126

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

61. P132, Stamping Press 1-127

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

62. P133, Stamping Press 1-128

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

63. P134, Stamping Press 1-129

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

64. P135, Stamping Press 1-131

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

65. P136, Stamping Press 1-132

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

66. P137, Stamping Press 1-133

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

67. P138, Stamping Press 1-138

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

68. P139, Stamping Press 1-214

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.

69. P140, Stamping Press 1-250

Operations, Property and/or Equipment Description:

Stamping Press to form metal products using lubricating oil; installed prior to 1970.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (Synthetic Minor to avoid requirements of 40 CFR Part 63 Subpart MMMM and PSD Applicability Threshold)	The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive. The Hazardous Air Pollutants (HAPs), emissions from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any combination of HAPs. as based on a rolling, 12-month summation. b)(2)b, below
b.	OAC rule 3745-21-07(G)	b)(2)a, below.

(2) Additional Terms and Conditions

a. The liquid organic materials employed by this emissions unit shall not be exposed to temperatures exceeding 220 degrees Fahrenheit, and the boiling points shall exceed 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure. Pursuant to OAC rule 3745-21-07(G)(9)(e), liquid organic materials which exhibit the aforementioned physical properties and are not exposed to temperatures exceeding 220 degrees Fahrenheit are not subject to the requirements of OAC rule 3745-21-07(G).

b. The actual usage of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from all non-insignificant emissions units at this facility shall not exceed 9.0 TPY* for any single HAP and 22.5 TPY* for any

combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

*This assumes the HAPs emitted are the same as the amount of HAPs used since all HAPs used evaporate.

c) Operational Restrictions

(1) The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

VOC emissions shall be calculated according to the following equation:

AER = [Sum of all(Vi)(Gi)] ÷ 2000 lbs/Ton

Where:

AER= Annual Emission Rate, in tons per 12-month rolling period;

Vi = VOC content in pounds per gallon of each lubricating oil, subject to the following limitation: Vi 5.75 lbs VOC/gallon; and

Gi = Gallons used of each lubricating oil for the rolling 12 month period.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain monthly records of the following information for emissions units P107 through P114 and P117 through P140, combined:

a. the company name and identification for each lubricating oil employed;

b. whether or not each liquid organic materials employed have boiling points exceeding 200 degrees Fahrenheit at 0.5 millimeter mercury absolute pressure or the materials have been exposed to temperatures exceeding 220 degrees Fahrenheit;

c. the volume, in gallons, of each lubricating oil employed;

d. the VOC content of each lubricating oil employed, in pounds per gallon; and

e. the rolling 12-month summation of VOC emissions from the lubricating oils employed, i.e., the sum of the usage of each lubricating oil employed multiplied by its respective VOC content.

(2) The permittee shall collect and record the following information each month for the HAP(s) employed in all non-insignificant emissions units at this facility:

a. the emission unit's source identification and description that Hazardous Air Pollutant (HAP) containing materials were employed;

b. the name and identification number of each HAP containing material employed;

c. the individual HAP* content for each HAP containing material employed, in pounds of individual HAP per gallon, as employed;

d. the amount of each HAP containing material employed, in gallons;

e. the total individual HAP usage for each HAP from the above listed materials employed, in pounds or tons per month [for each HAP the sum of (c) times (d)];

f. the total combined HAP usage from all above listed materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating];

g. the updated rolling, 12-month summation of usage for each individual HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

h. the updated rolling, 12-month summation of usage for total combined HAP**, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA, Southwest District Office contact. This information does not have to be kept on a line-by-line basis.

** This assumes the HAP(s) emitted are the same as the amounts of HAP(s) used since all HAP(s) used evaporate.

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. any monthly record showing noncompliance with the VOC content limit for lubricating oils of 5.75 lbs/gallon;

b. any monthly record showing noncompliance with the rolling, 12-month VOC emissions limit of 10.5 tons for emissions units P107 through P114, and P117 through P140, combined;

c. an identification of each month during which the individual HAP emissions from all non-insignificant emissions units at this facility exceeded 9.0 tons per year, based on a 12-month rolling average; and

d. an identification of each month during which the combined HAP emissions all non-insignificant emissions units at this facility exceeded 22.5 tons per year, based on a 12-month rolling average.

The quarterly deviation (excursion) reports shall be submitted in accordance with the reporting requirements of the Standard Terms and Conditions of this permit.

[OAC rule 3745-15-03(B)(1)(a)] and [OAC rule 3745-15-03(C)] and [OAC rule 3745-77-07(C)(1)]

(2) The permittee shall submit deviation (excursion) reports which identify all exceedances of the following:

a. any monthly record showing noncompliance with the liquid organic material usage limitation for this emissions unit, i.e., liquid organic materials must not be exposed to temperatures exceeding 220 degrees Fahrenheit and the boiling points must exceed 200 degrees at 0.5 millimeter mercury absolute pressure per OAC rule 3745-21-07(G)(9)(e);

f) Testing Requirements

(1) Compliance with the emission limitations in b)(1). of these terms and conditions shall be determined in accordance with the following methods:

a. VOC Content Limitation:

5.75 lbs VOC/gallon of lubricating oil

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

b. 6.76 lbs VOC/gallon of lubricating oils

Applicable Compliance Method:

Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound content of materials added to this emissions unit.

c. Emission Limitation:

The combined VOC emissions shall not exceed 10.5 tons as a rolling, 12-month summation for emissions units P107 through P114, inclusive, and P117 through P140, inclusive.

Applicable Compliance Method:

Compliance with this limitation shall be based the records keeping requirement of d)(1) of this permit.

(2) Formulation data of USEPA Method 24 shall be used to determine the VOC content of each coating and cleanup/pan solvent material.

g) Miscellaneous Requirements.

(1) None.