



State of Ohio Environmental Protection Agency

STREET ADDRESS:

Lazarus Government Center
50 W. Town St., Suite 700
Columbus, Ohio 43215

TELE: (614) 644-3020 FAX: (614) 644-3184
www.epa.state.oh.us

MAILING ADDRESS:

P.O. Box 1049
Columbus, OH 43216-1049

9/29/2008

John B. Kauffman
T-Road Finishing, LLC
2631 S. Carr Rd.
Apple Creek, OH 44606

RE: FINAL AIR POLLUTION PERMIT-TO-INSTALL AND OPERATE
Facility ID: 0285000483
Permit Number: 02-23004
Permit Type: Initial Installation
County: Wayne

Certified Mail

Yes	TOXIC REVIEW
No	PSD
No	SYNTHETIC MINOR
No	CEMS
No	MACT
No	NSPS
No	NESHAPS
No	NETTING
No	MAJOR NON-ATTAINMENT
Yes	MODELING SUBMITTED

Dear Permit Holder:

Enclosed please find a final Air Pollution Permit-to-Install and Operate ("PTIO") which will allow you to install, modify, and/or operate the described emissions unit(s) in the manner indicated in the permit. Because this permit contains conditions and restrictions, please read it very carefully.

Ohio EPA maintains a document entitled "Frequently Asked Questions about the PTIO". The document can be downloaded from the DAPC Web page, www.epa.state.oh.us/dapc, from the "Permits" link. This document contains additional information related to your permit, such as what activities are covered under the PTIO, who has enforcement authority over the permit and Ohio EPA's authorization to inspect your facility and records. Please contact the Office of Compliance Assistance and Pollution Prevention at (614) 644-3469 if you need assistance.

The issuance of this PTIO is a final action of the Director and may be appealed to the Environmental Review Appeals Commission ("ERAC") under Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and describe the action complained of and the grounds for the appeal. The appeal must be filed with the ERAC within thirty (30) days after notice of the Director's action. A filing fee of \$70.00 must be submitted to the ERAC with the appeal, although the ERAC, has discretion to reduce the amount of the filing fee if you can demonstrate (by affidavit) that payment of the full amount of the fee would cause extreme hardship. If you file an appeal of this action, you must notify Ohio EPA of the filing of the appeal (by providing a copy to the Director) within three (3) days of filing your appeal with the ERAC. Ohio EPA requests that a copy of the appeal also be provided to the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the ERAC at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, OH 43215

If you have any questions regarding this permit, please contact the Ohio EPA DAPC, Northeast District Office. This permit has been posted to the Division of Air Pollution Control (DAPC) Web page www.epa.state.oh.us/dapc.

Sincerely,

Michael W. Ahern
Michael W. Ahern, Manager
Permit Issuance and Data Management Section, DAPC

Cc: Ohio EPA-NEDO

Ted Strickland, Governor
Lee Fisher, Lieutenant Governor
Chris Korleski, Director



**State of Ohio Environmental Protection Agency
Division of Air Pollution Control**

FINAL

**Air Pollution Permit-to-Install and Operate
for
T-Road Finishing, LLC**

Facility ID: 0285000483
Permit Number: 02-23004
Permit Type: Initial Installation
Issued: 9/29/2008
Effective: 9/29/2008
Expiration: 9/29/2013



Air Pollution Permit-to-Install and Operate
for
T-Road Finishing, LLC

Table of Contents

- Authorization 1
- A. Standard Terms and Conditions 3
 - 1. What does this permit-to-install and operate ("PTIO") allow me to do?..... 4
 - 2. Who is responsible for complying with this permit? 4
 - 3. What records must I keep under this permit? 4
 - 4. What are my permit fees and when do I pay them?..... 4
 - 5. When does my PTIO expire, and when do I need to submit my renewal application? 4
 - 6. What happens to this permit if my project is delayed or I do not install or modify my source? 5
 - 7. What reports must I submit under this permit? 5
 - 8. If I am required to obtain a Title V operating permit in the future, what happens to the operating provisions and PER obligations under this permit? 5
 - 9. What are my obligations when I perform scheduled maintenance on air pollution control equipment?... 5
 - 10. Do I have to report malfunctions of emissions units or air pollution control equipment? If so, how must I report? 6
 - 11. Can Ohio EPA or my local air agency inspect the facility where the emission unit(s) is/are located? 6
 - 12. What happens if one or more emissions units operated under this permit is/are shut down permanently? 6
 - 13. Can I transfer this permit to a new owner or operator? 6
 - 14. Does compliance with this permit constitute compliance with OAC rule 3745-15-07, "air pollution nuisance"? 7
 - 15. What happens if a portion of this permit is determined to be invalid? 7
- B. Facility-Wide Terms and Conditions 8
- C. Emissions Unit Terms and Conditions 10
 - 1. P001, Diesel Engine #1 11
 - 2. R001, Booth#1 15
 - 3. R002, Booth #2 25



State of Ohio Environmental Protection Agency
Division of Air Pollution Control

Final Permit-to-Install and Operate
Permit Number: 02-23004
Facility ID: 0285000483
Effective Date: 9/29/2008

Authorization

Facility ID: 0285000483
Application Number(s): A0003178, A0035565
Permit Number: 02-23004
Permit Description: 2 coating booths, 1 diesel engine.
Permit Type: Initial Installation
Permit Fee: \$0.00
Issue Date: 9/29/2008
Effective Date: 9/29/2008
Expiration Date: 9/29/2013
Permit Evaluation Report (PER) Annual Date: July 1 - June 30, Due Aug 15
This document constitutes issuance to:

T-Road Finishing, LLC
2631 S. Carr Ed.
Apple Creek, OH 44606

of a Permit-to-Install and Operate for the emissions unit(s) identified on the following page.

Ohio EPA District Office or local air agency responsible for processing and administering your permit:

Ohio EPA DAPC, Northeast District Office
2110 East Aurora Road
Twinsburg, OH 43087
(330)425-9171

The above named entity is hereby granted this Permit-to-Install and Operate for the air contaminant source(s) (emissions unit(s)) listed in this section pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the described emissions unit(s) will operate in compliance with applicable State and federal laws and regulations.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Chris Korleski
Director



Authorization (continued)

Permit Number: 02-23004
Permit Description: 2 coating booths, 1 diesel engine.

Permits for the following emissions unit(s) or groups of emissions units are in this document as indicated below:

Emissions Unit ID:	P001
Company Equipment ID:	Diesel Engine #1
Superseded Permit Number:	
General Permit Category and Type:	Not Applicable
Emissions Unit ID:	R001
Company Equipment ID:	Booth#1
Superseded Permit Number:	
General Permit Category and Type:	Not Applicable
Emissions Unit ID:	R002
Company Equipment ID:	Booth #2
Superseded Permit Number:	
General Permit Category and Type:	Not Applicable



State of Ohio Environmental Protection Agency
Division of Air Pollution Control

Final Permit-to-Install and Operate

Permit Number: 02-23004

Facility ID: 0285000483

Effective Date: 9/29/2008

A. Standard Terms and Conditions



1. What does this permit-to-install and operate ("PTIO") allow me to do?

This permit allows you to install and operate the emissions unit(s) identified in this PTIO. You must install and operate the unit(s) in accordance with the application you submitted and all the terms and conditions contained in this PTIO, including emission limits and those terms that ensure compliance with the emission limits (for example, operating, recordkeeping and monitoring requirements).

2. Who is responsible for complying with this permit?

The person identified on the "Authorization" page, above, is responsible for complying with this permit until the permit is revoked, terminated, or transferred. "Person" means a person, firm, corporation, association, or partnership. The words "you," "your," or "permittee" refer to the "person" identified on the "Authorization" page above.

The permit applies only to the emissions unit(s) identified in the permit. If you install or modify any other equipment that requires an air permit, you must apply for an additional PTIO(s) for these sources.

3. What records must I keep under this permit?

You must keep all records required by this permit, including monitoring data, test results, strip-chart recordings, calibration data, maintenance records, and any other record required by this permit for five years from the date the record was created. You can keep these records electronically, provided they can be made available to Ohio EPA during an inspection at the facility. Failure to make requested records available to Ohio EPA upon request is a violation of this permit requirement.

4. What are my permit fees and when do I pay them?

There are two fees associated with permitted air contaminant sources in Ohio:

- PTIO fee. This one-time fee is based on a fee schedule in accordance with Ohio Revised Code (ORC) section 3745.11, or based on a time and materials charge for permit application review and permit processing if required by the Director.

You will be sent an invoice for this fee after you receive this PTIO and payment is due within 30 days of the invoice date. You are required to pay the fee for this PTIO even if you do not install or modify your operations as authorized by this permit.

- Annual emissions fee. Ohio EPA will assess a separate fee based on the total annual emissions from your facility. You self-report your emissions in accordance with Ohio Administrative Code (OAC) Chapter 3745-78. This fee assessed is based on a fee schedule in ORC section 3745.11 and funds Ohio EPA's permit compliance oversight activities. For facilities that are permitted as synthetic minor sources, the fee schedule is adjusted annually for inflation. Ohio EPA will notify you when it is time to report your emissions and to pay your annual emission fees.

5. When does my PTIO expire, and when do I need to submit my renewal application?

This permit expires on the date identified at the beginning of this permit document (see "Authorization" page above) and you must submit a renewal application to renew the permit. Ohio EPA will send a renewal notice to you approximately six months prior to the expiration date of this permit. However, it is very important that you submit a complete renewal permit application (postmarked prior to expiration of this permit) even if you do not receive the renewal notice.



If a complete renewal application is submitted before the expiration date, Ohio EPA considers this a timely application for purposes of ORC section 119.06, and you are authorized to continue operating the emissions unit(s) covered by this permit beyond the expiration date of this permit until final action is taken by Ohio EPA on the renewal application.

6. What happens to this permit if my project is delayed or I do not install or modify my source?

This PTIO expires 18 months after the issue date identified on the "Authorization" page above unless otherwise specified if you have not (1) started constructing the new or modified emission sources identified in this permit, or (2) entered into a binding contract to undertake such construction. This deadline can be extended by up to 12 months, provided you apply to Ohio EPA for this extension within a reasonable time before the 18-month period has ended and you can show good cause for any such extension.

7. What reports must I submit under this permit?

An annual permit evaluation report (PER) is required in addition to any malfunction reporting required by OAC rule 3745-15-06 or other specific rule-based reporting requirement identified in this permit. Your PER due date is identified in the Authorization section of this permit.

8. If I am required to obtain a Title V operating permit in the future, what happens to the operating provisions and PER obligations under this permit?

If you are required to obtain a Title V permit under OAC Chapter 3745-77 in the future, the permit-to-operate portion of this permit will be superseded by the issued Title V permit. From the effective date of the Title V permit forward, this PTIO will effectively become a PTI (permit-to-install) in accordance with OAC rule 3745-31-02(B). The following terms and conditions will no longer be applicable after issuance of the Title V permit: Section B, Term 1.b) and Section C, for each emissions unit, Term a)(2).

The PER requirements in this permit remain effective until the date the Title V permit is issued and is effective, and cease to apply after the effective date of the Title V permit. The final PER obligation will cover operations up to the effective date of the Title V permit and must be submitted on or before the submission deadline identified in this permit on the last day prior to the effective date of the Title V permit.

9. What are my obligations when I perform scheduled maintenance on air pollution control equipment?

You must perform scheduled maintenance of air pollution control equipment in accordance with OAC rule 3745-15-06(A). If scheduled maintenance requires shutting down or bypassing any air pollution control equipment, you must also shut down the emissions unit(s) served by the air pollution control equipment during maintenance, unless the conditions of OAC rule 3745-15-06(A)(3) are met. Any emissions that exceed permitted amount(s) under this permit (unless specifically exempted by rule) must be reported as deviations in the annual permit evaluation report (PER), including nonexempt excess emissions that occur during approved scheduled maintenance.



10. Do I have to report malfunctions of emissions units or air pollution control equipment? If so, how must I report?

If you have a reportable malfunction of any emissions unit(s) or any associated air pollution control system, you must report this to the Ohio EPA DAPC, Northeast District Office in accordance with OAC rule 3745-15-06(B). Malfunctions that must be reported are those that result in emissions that exceed permitted emission levels. It is your responsibility to evaluate control equipment breakdowns and operational upsets to determine if a reportable malfunction has occurred.

If you have a malfunction, but determine that it is not a reportable malfunction under OAC rule 3745-15-06(B), it is recommended that you maintain records associated with control equipment breakdown or process upsets. Although it is not a requirement of this permit, Ohio EPA recommends that you maintain records for non-reportable malfunctions.

11. Can Ohio EPA or my local air agency inspect the facility where the emission unit(s) is/are located?

Yes. Under Ohio law, the Director or his authorized representative may inspect the facility, conduct tests, examine records or reports to determine compliance with air pollution laws and regulations and the terms and conditions of this permit. You must provide, within a reasonable time, any information Ohio EPA requests either verbally or in writing.

12. What happens if one or more emissions units operated under this permit is/are shut down permanently?

Ohio EPA can terminate the permit terms associated with any permanently shut down emissions unit. "Shut down" means the emissions unit has been physically removed from service or has been altered in such a way that it can no longer operate without a subsequent "modification" or "installation" as defined in OAC Chapter 3745-31.

You should notify Ohio EPA of any emissions unit that is permanently shut down by submitting a certification that identifies the date on which the emissions unit was permanently shut down. The certification must be submitted by an authorized official from the facility. You cannot continue to operate an emission unit once the certification has been submitted to Ohio EPA by the authorized official.

You must comply with all recordkeeping and reporting for any permanently shut down emissions unit in accordance with the provisions of the permit, regulations or laws that were enforceable during the period of operation, such as the requirement to submit a PER, air fee emission report, or malfunction report. You must also keep all records relating to any permanently shutdown emissions unit, generated while the emissions unit was in operation, for at least five years from the date the record was generated.

Again, you cannot resume operation of any emissions unit certified by the authorized official as being permanently shut down without first applying for and obtaining a permit pursuant to OAC Chapter 3745-31.

13. Can I transfer this permit to a new owner or operator?

You can transfer this permit to a new owner or operator. If you transfer the permit, you must follow the procedures in OAC Chapter 3745-31, including notifying Ohio EPA or the local air agency of the



State of Ohio Environmental Protection Agency
Division of Air Pollution Control

Final Permit-to-Install and Operate

Permit Number: 02-23004

Facility ID: 0285000483

Effective Date: 9/29/2008

change in ownership or operator. Any transferee of this permit must assume the responsibilities of the transferor permit holder.

14. Does compliance with this permit constitute compliance with OAC rule 3745-15-07, "air pollution nuisance"?

This permit and OAC rule 3745-15-07 prohibit operation of the air contaminant source(s) regulated under this permit in a manner that causes a nuisance. Ohio EPA can require additional controls or modification of the requirements of this permit through enforcement orders or judicial enforcement action if, upon investigation, Ohio EPA determines existing operations are causing a nuisance.

15. What happens if a portion of this permit is determined to be invalid?

If a portion of this permit is determined to be invalid, the remainder of the terms and conditions remain valid and enforceable. The exception is where the enforceability of terms and conditions are dependent on the term or condition that was declared invalid.



State of Ohio Environmental Protection Agency
Division of Air Pollution Control

Final Permit-to-Install and Operate

Permit Number: 02-23004

Facility ID: 0285000483

Effective Date: 9/29/2008

B. Facility-Wide Terms and Conditions



State of Ohio Environmental Protection Agency
Division of Air Pollution Control

Final Permit-to-Install and Operate

Permit Number: 02-23004

Facility ID: 0285000483

Effective Date: 9/29/2008

1. This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).
 - a) For the purpose of a permit-to-install document, the facility-wide terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (1) None.
 - b) For the purpose of a permit-to-operate document, the facility-wide terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (1) None.



State of Ohio Environmental Protection Agency
Division of Air Pollution Control

Final Permit-to-Install and Operate

Permit Number: 02-23004

Facility ID: 0285000483

Effective Date: 9/29/2008

C. Emissions Unit Terms and Conditions



1. P001, Diesel Engine #1

Operations, Property and/or Equipment Description:

81 HP Perkins Model No. 4236 Diesel Engine

a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

(1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. None.

(2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

a. None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3)	0.18 lb/hr and 0.78 TPY of particulate emissions (PE)/PM less than 10 micron in diameter (PM-10) 0.17 lb/hr and 0.73 TPY of Sulfur Dioxide (SO ₂). 2.51 lbs/hr and 11.00 TPY of Nitrogen Dioxide (NO _x). 0.20 lb/hr and 0.89 TPY of organic compounds (OC). 0.54 lb/hr and 2.37 TPY of Carbon Monoxide (CO). Visible particulate emissions from the stack serving this emissions unit shall not exceed 10% opacity, as a six-minute average.



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-11(B)(5)(a).
b.	OAC rule 37-45-17-11(B)(5)(a)	0.310 lb/mmBTU of particulate emissions.
c.	OAC rule 3745-17-07(A)(1)	The opacity limitation specified in this rule is less stringent than the limit established pursuant to OAC rule 3745-31-05(A)(3).
d.	OAC rule 3745-18-06(G)	This emissions unit is exempt from the requirements of OAC rule 3745-18-06 pursuant to OAC rule 3745-18-06(B).

(2) Additional Terms and Conditions

- a. In accordance with OAC rule 3745-31-05(A)(3), best available technology for this emissions unit includes the emissions limitations and fuel sulfur content restriction.
- b. The permittee shall use only diesel fuel/number 2 fuel oil with a maximum sulfur content of 0.5 percent by weight for combustion in this emissions unit.

c) Operational Restrictions

- (1) None.

d) Monitoring and/or Recordkeeping Requirements

- (1) For each day during which the permittee burns a fuel other than diesel fuel, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.
- (2) The permittee shall maintain documentation of the sulfur content of all fuels received.

e) Reporting Requirements

- (1) The permittee shall submit deviation (excursion) reports that identify each day during which a fuel other than diesel fuel with a maximum sulfur content of 0.5 percent by weight was burned in this emissions unit. Each report shall be submitted within 30 days of the deviation.
- (2) The reports shall include what corrective action was taken and shall be sent to the Director (Ohio EPA Northeast District Office) within 30 days following the exceedance.
- (3) Annual Permit Evaluation Report (PER) forms will be mailed to the permittee at the end of the reporting period specified in the Authorization section of this permit. The permittee shall submit the PER in the form and manner provided by the Director by the due date identified in the Authorization section of this permit. The permit evaluation report shall cover a reporting period of no more than twelve-months for each air contaminant source identified in this permit.



f) Testing Requirements

(1) Compliance with the emission limitations specified in b)(1) of these terms and conditions shall be determined in accordance with the following methods:

a. Emission Limitations:

0.18 lb/hr and 0.78 TPY of particulate emissions/PM-10

Applicable Compliance Method:

Compliance with the hourly emission limitation above shall be determined by multiplying 0.0022 lb/hp-hr, the emission factor from AP-42 Table 3.3-1 (10/96), by 81 HP, the power output rating of this unit.

Compliance with the annual emission limitations shall be determined by multiplying the hourly emission rate determined above by 8760, the maximum hours of operation, and dividing by 2000 lbs/ton.

b. Emission Limitations:

0.17 lb/hr and 0.73 TPY of Sulfur Dioxide

Applicable Compliance Method:

Compliance with the hourly emission limitation above shall be determined by multiplying 0.00205 lb/hp-hr, the emission factor from AP-42 Table 3.3-1 (10/96), by 81 HP, the power output rating of this unit.

Compliance with the annual emission limitations shall be determined by multiplying the hourly emission rate determined above by 8760, the maximum hours of operation, and dividing by 2000 lbs/ton.

c. Emission Limitations:

2.51 lbs/hr and 11.00 TPY of Nitrogen Oxide

Applicable Compliance Method:

Compliance with the hourly emission limitation above shall be determined by multiplying 0.031 lb/hp-hr, the emission factor from AP-42 Table 3.3-1 (10/96), by 81 HP, the power output rating of this unit.

Compliance with the annual emission limitations shall be determined by multiplying the hourly emission rate determined above by 8760, the maximum hours of operation, and dividing by 2000 lbs/ton.

d. Emission Limitations:

0.20 lb/hr and 0.89 TPY of organic compounds



Applicable Compliance Method:

Compliance with the hourly emission limitation above shall be determined by multiplying 0.0022 lb/hp-hr, the emission factor from AP-42 Table 3.3-1 (10/96), by 81 HP, the power output rating of this unit.

Compliance with the annual emission limitations shall be determined by multiplying the hourly emission rate determined above by 8760, the maximum hours of operation, and dividing by 2000 lbs/ton.

e. Emission Limitations:

0.54 lb/hr and 2.37 TPY of Carbon Monoxide

Applicable Compliance Method:

Compliance with the hourly emission limitation above shall be determined by multiplying 0.00668 lb/hp-hr, the emission factor from AP-42 Table 3.3-1 (10/96), by 81 HP, the power output rating of this unit.

Compliance with the annual emission limitations shall be determined by multiplying the hourly emission rate determined above by 8760, the maximum hours of operation, and dividing by 2000 lbs/ton.

f. Emission Limitation:

Visible particulate emissions from the stack serving this emissions unit shall not exceed 10 percent opacity, as a six-minute average.

Applicable Compliance Method:

If required, compliance with the opacity limitation shall be determined using Method 9 of 40 CFR, Part 60, Appendix A.

Emission Limitation

0.310 lb/mmBTU of particulate emissions

Applicable Compliance Method:

If required, compliance shall be determined according to OAC rule 3745-17-03(B)(10), Method 5, 40 CFR 60, Appendix A.

g) Miscellaneous Requirements

(1) None.



2. R001, Booth#1

Operations, Property and/or Equipment Description:

Coating Booth No. 1 with exhaust fan and airless/HVLP spray pumps/guns

- a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).
 - (1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - a. d)(6), d)(7), d)(8), d)(9), e)(4)
 - (2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - a. None.
- b) Applicable Emissions Limitations and/or Control Requirements
 - (1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3)	See b)(2)(b), b)(2)(c) and c)(1) below. The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(C) and OAC rule 3745-17-11(C).
b.	OAC rule 3745-31-05(D)	See b)(2)(d) and c)(2) below.
c.	OAC rule 3745-17-11(C)	See c)(1) below.
d.	OAC rule 3745-21-07(G)	See b)(2)(a) below.
e.	OAC rule 3745-114-01	See d)(6), d)(7), d)(8), d)(9) and e)(4) below.
f.	ORC 3704.03(F)(4)(c)	See c)(3) below.



(2) Additional Terms and Conditions

- a. Each day that a photochemically reactive material [as defined in OAC 3745-21-01(C)(5)] is employed, the organic compound (OC) emissions from all coatings and photochemically reactive cleanup material shall not exceed 8 pounds per hour and 40 pounds per day. OC emissions from cleanup material that is not a photochemically reactive material shall not be included in showing compliance with these emission limitations.

The OC emission limitations of 8 pounds per hour and 40 pounds per day when photochemically reactive coatings or clean up materials are employed shall cease to be effective and federally enforceable on the date the U.S. EPA approves the revisions to OAC rule 3745-21-07(G) as a revision to the Ohio SIP for organic compounds. After the rule is added to the Ohio SIP, the emission limitations, monitoring, record keeping, reporting and testing requirements related to these hourly and daily limitations included in sections d)(2), d)(3)(b), e)(2)(a), f)(1)(a) and f)(1)(b) shall be void.

- b. Each day that photochemically reactive materials [as defined in OAC rule 3745-21-01(C)(5)] are not employed, the volatile organic compound (VOC) emissions from coatings shall not exceed 39.20 pounds per hour. This emission limitation is based upon the maximum coating application rate of 7.00 gallons per hour.

The requirement to comply with this emission limitation only on days when photochemically reactive coating or clean up material are not employed shall cease on the date the U.S. EPA approves revisions to OAC rule 3745-21-07(G) as a revision to the Ohio SIP for organic compounds. After the revised rule is added to the Ohio SIP, this emission limitation shall be effective every day the emissions unit is in operation.

- c. The VOC emissions from all coatings and cleanup materials from this emissions unit, and from emissions units R001 and R002, combined, shall not exceed 24.9 tons per year, as a rolling, 12-month summation.
- d. The VOC content of coatings shall not exceed 6.357 pounds per gallon, as applied.

c) Operational Restrictions

- (1) All exhaust from the spray booth shall pass through the dry filters whenever this emissions unit is in operation.
- (2) The maximum emissions from coating and cleanup material usage for this emissions unit and for emissions units R001 and R002, combined, shall not exceed 24.9 tons of VOC per rolling, 12-month period.
- (3) The hours of operation of this emissions unit shall not exceed 71.25 hours per week.

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall maintain daily records that document all time periods when the dry filters were not in service when the emissions unit was in operation.



- (2) The permittee shall collect and record the following information for each day that photochemically reactive coatings or cleanup material are employed in this emissions unit:
- a. the company identification for each coating and photochemically reactive cleanup material employed;
 - b. the number of gallons of each coating and photochemically reactive cleanup material employed minus the number of gallons of coating and/or cleanup material recovered for disposal;
 - c. the OC content of each coating and photochemically reactive cleanup material, in pounds OC per gallon;
 - d. the total emissions rate for all coatings and photochemically reactive cleanup materials, in pounds OC per day;
 - e. the total number of hours the emissions unit was in operation;
 - f. the average hourly OC emission rate for all coatings and photochemically reactive cleanup materials, i.e., (d)/(e), in pounds per hour (average);
 - g. the VOC content of each coating and photochemically reactive cleanup material, in pounds VOC per gallon; and
 - h. the total emissions rate for all coatings and photochemically reactive cleanup materials, in pounds VOC per day.

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit. Also, the definition of "photochemically reactive material" is based upon OAC rule 3745-21-01(C)(5).]

[Note: After the revision to OAC rule 3745-21-07(G) is approved into the Ohio SIP, section d)(2) will be voided entirely.]

- (3) The permittee shall collect and record the following information for each day that photochemically reactive coatings or cleanup materials are not employed in this emissions unit:
- a. the company identification for each coating or cleanup material employed;
 - b. documentation that photochemically reactive material as defined in OAC rule 3745-21-01(C)(5) was not used;
 - c. the VOC content of each coating, in lbs/gallon as applied;
 - d. the number of gallons of each coating employed minus the number of gallons of coating recovered for disposal;
 - e. the total VOC emissions from all coatings employed, in lbs/day, i.e., sum of (c) times (d);
 - f. the total number of hours the emissions unit was in operation; and



- g. the average hourly VOC emission rate for all coatings, i.e., (e)/(f), in lbs/hr.

[Note: After the revision to OAC rule 3745-21-07(G) is approved into the Ohio SIP, the records required by this section shall be kept on a daily basis with no reference to photochemically reactive materials. Section d)(3)(b) will be voided entirely.]

- (4) The permittee shall record each week the total number of hours the emissions unit was in operation; [i.e., the sum of d)(2)(e) and d)(3)(f)]

[Note: After the revision to OAC rule 3745-21-07(G) is approved into the Ohio SIP, the reference to d)(2)(e) shall be voided.]

- (5) The permittee shall collect and record the following information for each month for the emissions unit:

- a. the number of gallons of each nonphotochemically reactive cleanup material employed minus the number of gallons of cleanup material recovered for disposal;
- b. the VOC content of each nonphotochemically cleanup material, in lbs/gallon;
- c. the total VOC emissions from all nonphotochemically reactive cleanup materials employed, in lbs/month, i.e., sum of (b) times (a);
- d. the actual VOC emissions from all coatings and cleanup materials for the previous, 12-month period [i.e., sum of the daily VOC emissions (sections d)(2)(h) and d)(3)(e) and the monthly nonphotochemically reactive cleanup material VOC emission (term d)(6)(c) for the previous, 12-month period]; and
- e. the actual VOC emissions from emissions units R001 and R002, combined, for the previous, 12-month period.

[Note: Records of nonphotochemically reactive cleanup material shall be recorded monthly according to section d)(4) above. After the revision to OAC rule 3745-21-07(G) is approved into the Ohio SIP, any reference to "nonphotochemically reactive" and "section d)(2)(h)" shall be voided.]

- (6) The permit to install for the emissions units in this PTI was evaluated based on the actual materials and the design parameters of the emissions unit's(s') exhaust system, as specified by the permittee in the permit application. The "Toxic Air Contaminant Statute", ORC 3704.03(F), was applied to this/these emissions unit(s) for each toxic air contaminant listed in OAC rule 3745-114-01, using data from the permit application; and modeling was performed for each toxic air contaminant(s) emitted at over one ton per year using an air dispersion model such as SCREEN 3.0, AERMOD, or ISCST3, or other Ohio EPA approved model. The predicted 1-hour maximum ground_level concentration result(s) from the approved air dispersion model, was compared to the Maximum Acceptable Ground_Level Concentration (MAGLC), calculated as described in the Ohio EPA guidance document entitled "Review of New Sources of Air Toxic Emissions, Option A", as follows:



- a. the exposure limit, expressed as a time-weighted average concentration for a conventional 8-hour workday and a 40-hour workweek, for each toxic compound(s) emitted from the emissions unit(s), (as determined from the raw materials processed and/or coatings or other materials applied) has been documented from one of the following sources and in the following order of preference (TLV was and shall be used, if the chemical is listed):
 - i. threshold limit value (TLV) from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices"; or
 - ii. STEL (short term exposure limit) or the ceiling value from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices"; the STEL or ceiling value is multiplied by 0.737 to convert the 15-minute exposure limit to an equivalent 8-hour TLV.

- b. The TLV is divided by ten to adjust the standard from the working population to the general public (TLV/10).
- c. This standard is/was then adjusted to account for the duration of the exposure or the operating hours of the emissions unit(s), i.e., "X" hours per day and "Y" days per week, from that of 8 hours per day and 5 days per week. The resulting calculation was (and shall be) used to determine the Maximum Acceptable Ground-Level Concentration (MAGLC):

$$TLV/10 \times 8/X \times 5/Y = 4 TLV/XY = MAGLC$$

- d. The following summarizes the results of dispersion modeling for the significant toxic contaminants (emitted at 1 or more tons/year) or "worst case" toxic contaminant(s):

Toxic Contaminant: Toluene

TLV (mg/m3): 453.6

Maximum Hourly Emission Rate (lbs/hr): 2.45

Predicted 1-Hour Maximum Ground Level Concentration (ug/m3): 3357

Adjusted MAGLC (ug/m3): 4231 (adjusted for 71.25 hrs/wk)

The permittee, has demonstrated that emissions of xylene and toluene from emissions units R001 and R002 are calculated to be less than eighty per cent of the maximum acceptable ground level concentration (MAGLC); any new raw material or processing agent shall not be applied without evaluating each component toxic air contaminant in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F).

- (7) Prior to making any physical changes to or changes in the method of operation of the emissions unit(s), that could impact the parameters or values that were used in the



predicted 1-hour maximum ground level concentration”, the permittee shall re-model the change(s) to demonstrate that the MAGLC has not been exceeded. Changes that can affect the parameters/values used in determining the 1-hour maximum ground-level concentration include, but are not limited to, the following:

- a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a new toxic air contaminant with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any toxic air contaminant listed in OAC rule 3745-114-01, that was modeled from the initial (or last) application; and
- c. physical changes to the emissions unit(s) or its/their exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the “Toxic Air Contaminant Statute” will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a “modification” under OAC rule 3745_31_01 solely due to a non-restrictive change to a parameter or process operation, where compliance with the “Toxic Air Contaminant Statute”, ORC 3704.03(F), has been documented. If the change(s) meet(s) the definition of a “modification” or if a new toxic is emitted, or the modeled toxic(s) is/are expected to exceed the previous modeled level(s), then the permittee shall apply for and obtain a final permit-to-install prior to the change. The Director may consider any significant departure from the operations of the emissions unit, described in the permit-to-install application, as a modification that results in greater emissions than the emissions rate modeled to determine the ground level concentration; and may require the permittee to submit a permit-to-install application for the increased emissions.

- (8) The permittee shall collect, record, and retain the following information for each toxic evaluation conducted to determine compliance with the “Toxic Air Contaminant Statute”, ORC 3704.03(F):
 - a. a description of the parameters/values used in each compliance demonstration and the parameters or values changed for any re-evaluation of the toxic(s) modeled (the composition of materials, new toxic contaminants emitted, change in stack/exhaust parameters, etc.);
 - b. the Maximum Acceptable Ground Level Concentration (MAGLC) for each significant toxic contaminant or worst-case contaminant, calculated in accordance with the “Toxic Air Contaminant Statute”, ORC 3704.03(F);
 - c. a copy of the computer model run(s), that established the predicted 1-hour maximum ground level concentration that demonstrated the emissions unit(s) to be in compliance with the “Toxic Air Contaminant Statute”, ORC 3704.03(F), initially and for each change that requires re-evaluation of the toxic air contaminant emissions; and
 - d. the documentation of the initial evaluation of compliance with the “Toxic Air Contaminant Statute”, ORC 3704.03(F), and documentation of any determination



that was conducted to re-evaluate compliance due to a change made to the emissions unit(s) or the materials applied.

(9) The permittee shall maintain a record of any change made to a parameter or value used in the dispersion model, used to demonstrate compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground level concentration. The record shall include the date and reason(s) for the change and if the change would increase the ground-level concentration.

(10) The permittee shall maintain documentation of the manufacturer's recommendations, instructions, or operating manuals for the control devices with any modifications deemed necessary by the permittee during the time period in which the control devices are utilized.

The permittee shall operate the control devices in accordance with the manufacturer's recommendations, instructions, or operating manuals with any modifications deemed necessary by the permittee.

(11) The permittee shall conduct periodic inspections of the control devices to determine whether the devices are operating in accordance with the manufacturer's recommendations, instructions, or operating manuals with any modifications deemed necessary by the permittee. The periodic inspections of each control device shall be performed at a frequency that is based upon the recommendation of the manufacturer of the control device, and the permittee shall maintain a copy of the manufacturer's recommended inspection frequency. In addition to these periodic inspections, not less than once each calendar year the permittee shall conduct a comprehensive inspection of the control device while the emissions unit is shut down and perform any needed maintenance and repair for the control device to ensure that it is able to routinely operate in accordance with the manufacturer's recommendations.

(12) The permittee shall document each inspection of a control device by maintaining a record that includes the date of the inspection, a description of each problem identified and the date it was corrected, a description of the maintenance and repairs performed, and the name of the person who performed the inspection.

(13) In the event that the control devices are not operating in accordance with the manufacturer's recommendations, instructions, or operating manuals with any modifications deemed necessary by the permittee, the control devices shall be expeditiously repaired or otherwise returned to operation in accordance with such requirements. The permittee shall maintain documentation of those periods when the control devices are not operating in accordance with such requirements.

e) Reporting Requirements

(1) The permittee shall notify the Director (Ohio EPA, Northeast District Office) in writing of any daily record showing that the dry filters were not in service or not operated in accordance with the manufacturer's recommendations, instructions, or operating manuals with any modifications deemed necessary by the permittee when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (Ohio EPA, Northeast District Office) within 30 days after the event occurs.



- (2) The permittee submit quarterly deviation (excursion) reports that identify:
- a. for the days during which a photochemically reactive material was employed, each day during which the OC emissions from the coatings and photochemically reactive cleanup materials exceeded 8 pounds per hour and/or 40 pounds per day, and the actual OC emissions for each such incidence;
 - b. for the days during which a photochemically reactive material was not employed, each day during which the average VOC emissions from the coatings exceeded the pounds per hour limitation specified above, and the actual average VOC emissions for each such day;
 - c. each day during which the VOC content of any coating exceeded the pounds per gallon limitation specified above and the actual VOC content of each such coating employed; and
 - d. any exceedence of the annual VOC* emission limitation of 24.9 tons per year, as a rolling, 12-month summation from emissions units R001 and R002, combined, and the actual VOC emissions during each such period.

*based upon the premise that 100% of the solvent in the coating and clean up material employed is emitted.

The reports contained in this permit shall be submitted in accordance with the reporting requirements specified in Part B - General Terms and Conditions, Section 1 of this permit.

[Note: After the revision to OAC rule 3745-21-07(G) is approved into the Ohio SIP, section e)(2)(a) and the opening phrase of section e)(2)(b) that references photochemically reactive material shall be voided.

- (3) The permittee shall also submit annual reports that summarize the emissions of VOC from this emissions unit and from emissions units R001 and R002, combined.

The reports shall include the emissions calculations, shall be submitted by January 31 of each year, and shall cover the previous calendar year.

- (4) The permittee shall submit annual reports to the Ohio EPA, Northeast District Office, documenting any changes made to a parameter or value used in the dispersion model (including the air toxic compounds emitted and the emission rate), that was used to demonstrate compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground level concentration. If no changes to the emissions unit(s) or the exhaust stack have been made, then the report shall include a statement to this effect. This report shall be postmarked or delivered no later than January 31 following the end of each calendar year.

- (5) Annual Permit Evaluation Report (PER) forms will be mailed to the permittee at the end of the reporting period specified in the Authorization section of this permit. The permittee shall submit the PER in the form and manner provided by the Director by the due date identified in the Authorization section of this permit. The permit evaluation report shall cover a reporting period of no more than twelve-months for each air contaminant source identified in this permit.



f) Testing Requirements

(1) Compliance with the allowable emission limitations in sections b)(1) and b)(2) of these terms and conditions shall be determined in accordance with the following methods:

a. Emission Limitation:

8 pounds per hour of OC emissions for each day that photochemically reactive materials are employed

Applicable Compliance Method:

Compliance shall be demonstrated by the daily values calculated in section d)(2)(f) based upon the record keeping requirements specified in section d)(2).

b. Emission Limitation:

40 pounds per day of OC emissions for each day that photochemically reactive materials are employed

Applicable Compliance Method:

Compliance shall be demonstrated by the daily values calculated in section d)(2)(d) based upon the record keeping requirements specified in section d)(2).

c. Emission Limitation:

39.20 pounds VOC emissions per hour for each day that photochemically reactive materials are not employed

Applicable Compliance Method:

Compliance shall be demonstrated by the daily values calculated in section d)(3)(g) based on the record keeping requirements specified in section d)(3).

d. Emission Limitation:

24.9 tons of VOC emissions per year from all coatings and cleanup material from R001 and from R001 and R002, combined

Applicable Compliance Method:

Compliance shall be demonstrated by the values recorded in sections d)(5)(d) and d)(5)(e) based on the record keeping requirements specified in sections d)(2), d)(3) and d)(4).

e. Emission Limitation:

6.357 pounds of VOC per gallon coating, as applied

Applicable Compliance Method:

Any determination of VOC content, solids contents, or density of coating material shall be based on the coating materials as employed (as applied), including the



addition of any thinner or viscosity reducer to the coatings. In accordance with OAC rule 3745-21-04(B)(5), the permittee shall determine the composition of the coatings by formulation data supplied by the manufacturer of the coating materials, or from data determined by an analysis of each coating, as applied, by Reference Method 24 or Method 24A. If, pursuant to section 11.4 of Method 24, 40 CFR Part 60, Appendix A (revised as of July 1, 2001), an owner or operator determines that Method 24 or Method 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating or ink to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 and/or Method 24A.

[Note: After the revision to OAC rule 3745-21-07(G) is approved into the Ohio SIP, sections f)(1)(a) and f)(1)(b), the reference to photochemically reactive materials in section f)(1)(c) and the reference to section d)(2) in section f)(1)(d) shall be voided.]

- g) Miscellaneous Requirements
 - (1) None



3. R002, Booth #2

Operations, Property and/or Equipment Description:

Coating Booth No. 2 with exhaust fan and air assisted airless spray pumps/guns

- a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).
 - (1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - a. d)(6), d)(7), d)(8), d)(9), e)(4)
 - (2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - a. None.
- b) Applicable Emissions Limitations and/or Control Requirements
 - (1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3)	See b)(2)(b), b)(2)(c) and c)(1) below. The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(C) and OAC rule 3745-17-11(C).
b.	OAC rule 3745-31-05(D)	See b)(2)(d) and c)(2) below.
c.	OAC rule 3745-17-11(C)	See c)(1) below.
d.	OAC rule 3745-21-07(G)	See b)(2)(a) below.
e.	OAC rule 3745-114-01	See d)(6), d)(7), d)(8), d)(9) and e)(4) below.
f.	ORC 3704.03(F)(4)(c)	See c)(3) below.



(2) Additional Terms and Conditions

- a. Each day that a photochemically reactive material [as defined in OAC 3745-21-01(C)(5)] is employed, the organic compound (OC) emissions from all coatings and photochemically reactive cleanup material shall not exceed 8 pounds per hour and 40 pounds per day. OC emissions from cleanup material that is not a photochemically reactive material shall not be included in showing compliance with these emission limitations.

The OC emission limitations of 8 pounds per hour and 40 pounds per day when photochemically reactive coatings or clean up materials are employed shall cease to be effective and federally enforceable on the date the U.S. EPA approves the revisions to OAC rule 3745-21-07(G) as a revision to the Ohio SIP for organic compounds. After the rule is added to the Ohio SIP, the emission limitations, monitoring, record keeping, reporting and testing requirements related to these hourly and daily limitations included in sections d)(2), d)(3)(b), e)(2)(a), f)(1)(a) and f)(1)(b) shall be void.

- b. Each day that photochemically reactive materials [as defined in OAC rule 3745-21-01(C)(5)] are not employed, the volatile organic compound (VOC) emissions from coatings shall not exceed 19.07 pounds per hour. This emission limitation is based upon the maximum coating application rate of 3.00 gallons per hour.

The requirement to comply with this emission limitation only on days when photochemically reactive coating or clean up material are not employed shall cease on the date the U.S. EPA approves revisions to OAC rule 3745-21-07(G) as a revision to the Ohio SIP for organic compounds. After the revised rule is added to the Ohio SIP, this emission limitation shall be effective every day the emissions unit is in operation.

- c. The VOC emissions from all coatings and cleanup materials from this emissions unit, and from emissions units R001 and R002, combined, shall not exceed 24.9 tons per year, as a rolling, 12-month summation.
- d. The VOC content of coatings shall not exceed 6.357 pounds per gallon, as applied.

c) Operational Restrictions

- (1) All exhaust from the spray booth shall pass through the dry filters whenever this emissions unit is in operation.
- (2) The maximum emissions from coating and cleanup material usage for this emissions unit and for emissions units R001 and R002, combined, shall not exceed 24.9 tons of VOC per rolling, 12-month period.
- (3) The hours of operation of this emissions unit shall not exceed 71.25 hours per week

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall maintain daily records that document all time periods when the dry filters were not in service when the emissions unit was in operation.



- (2) The permittee shall collect and record the following information for each day that photochemically reactive coatings or cleanup material are employed in this emissions unit:
- a. the company identification for each coating and photochemically reactive cleanup material employed;
 - b. the number of gallons of each coating and photochemically reactive cleanup material employed minus the number of gallons of coating and/or cleanup material recovered for disposal;
 - c. the OC content of each coating and photochemically reactive cleanup material, in pounds OC per gallon;
 - d. the total emissions rate for all coatings and photochemically reactive cleanup materials, in pounds OC per day;
 - e. the total number of hours the emissions unit was in operation;
 - f. the average hourly OC emission rate for all coatings and photochemically reactive cleanup materials, i.e., (d)/(e), in pounds per hour (average);
 - g. the VOC content of each coating and photochemically reactive cleanup material, in pounds VOC per gallon; and
 - h. the total emissions rate for all coatings and photochemically reactive cleanup materials, in pounds VOC per day.

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit. Also, the definition of "photochemically reactive material" is based upon OAC rule 3745-21-01(C)(5).]

[Note: After the revision to OAC rule 3745-21-07(G) is approved into the Ohio SIP, section d)(2) will be voided entirely.]

- (3) The permittee shall collect and record the following information for each day that photochemically reactive coatings or cleanup materials are not employed in this emissions unit:
- a. the company identification for each coating or cleanup material employed;
 - b. documentation that photochemically reactive material as defined in OAC rule 3745-21-01(C)(5) was not used;
 - c. the VOC content of each coating, in lbs/gallon as applied;
 - d. the number of gallons of each coating employed minus the number of gallons of coating recovered for disposal;
 - e. the total VOC emissions from all coatings employed, in lbs/day, i.e., sum of (c) times (d);
 - f. the total number of hours the emissions unit was in operation; and



- g. the average hourly VOC emission rate for all coatings, i.e., (e)/(f), in lbs/hr.

[Note: After the revision to OAC rule 3745-21-07(G) is approved into the Ohio SIP, the records required by this section shall be kept on a daily basis with no reference to photochemically reactive materials. Section d)(3)(b) will be voided entirely.]

- (4) The permittee shall record each week the total number of hours the emissions unit was in operation; [i.e., the sum of d)(2)(e) and d)(3)(f)]

[Note: After the revision to OAC rule 3745-21-07(G) is approved into the Ohio SIP, the reference to d)(2)(e) shall be voided.]

- (5) The permittee shall collect and record the following information for each month for the emissions unit:

- a. the number of gallons of each nonphotochemically reactive cleanup material employed minus the number of gallons of cleanup material recovered for disposal;
- b. the VOC content of each nonphotochemically cleanup material, in lbs/gallon;
- c. the total VOC emissions from all nonphotochemically reactive cleanup materials employed, in lbs/month, i.e., sum of (b) times (a);
- d. the actual VOC emissions from all coatings and cleanup materials for the previous, 12-month period [i.e., sum of the daily VOC emissions (sections d)(2)(h) and d)(3)(e) and the monthly nonphotochemically reactive cleanup material VOC emission (term d)(6)(c) for the previous, 12-month period]; and
- e. the actual VOC emissions from emissions units R001 and R002, combined, for the previous, 12-month period.

[Note: Records of nonphotochemically reactive cleanup material shall be recorded monthly according to section d)(4) above. After the revision to OAC rule 3745-21-07(G) is approved into the Ohio SIP, any reference to "nonphotochemically reactive" and "section d)(2)(h)" shall be voided.]

- (6) The permit to install for the emissions units in this PTI was evaluated based on the actual materials and the design parameters of the emissions unit's(s') exhaust system, as specified by the permittee in the permit application. The "Toxic Air Contaminant Statute", ORC 3704.03(F), was applied to this/these emissions unit(s) for each toxic air contaminant listed in OAC rule 3745-114-01, using data from the permit application; and modeling was performed for each toxic air contaminant(s) emitted at over one ton per year using an air dispersion model such as SCREEN 3.0, AERMOD, or ISCST3, or other Ohio EPA approved model. The predicted 1-hour maximum ground_level concentration result(s) from the approved air dispersion model, was compared to the Maximum Acceptable Ground_Level Concentration (MAGLC), calculated as described in the Ohio EPA guidance document entitled "Review of New Sources of Air Toxic Emissions, Option A", as follows:



- a. the exposure limit, expressed as a time-weighted average concentration for a conventional 8-hour workday and a 40-hour workweek, for each toxic compound(s) emitted from the emissions unit(s), (as determined from the raw materials processed and/or coatings or other materials applied) has been documented from one of the following sources and in the following order of preference (TLV was and shall be used, if the chemical is listed):
 - i. threshold limit value (TLV) from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices"; or
 - ii. STEL (short term exposure limit) or the ceiling value from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices"; the STEL or ceiling value is multiplied by 0.737 to convert the 15-minute exposure limit to an equivalent 8-hour TLV.
- b. The TLV is divided by ten to adjust the standard from the working population to the general public (TLV/10).
- c. This standard is/was then adjusted to account for the duration of the exposure or the operating hours of the emissions unit(s), i.e., "X" hours per day and "Y" days per week, from that of 8 hours per day and 5 days per week. The resulting calculation was (and shall be) used to determine the Maximum Acceptable Ground-Level Concentration (MAGLC):

$$TLV/10 \times 8/X \times 5/Y = 4 TLV/XY = MAGLC$$

- d. The following summarizes the results of dispersion modeling for the significant toxic contaminants (emitted at 1 or more tons/year) or "worst case" toxic contaminant(s):

Toxic Contaminant: Toluene

TLV (mg/m³): 453.6

Maximum Hourly Emission Rate (lbs/hr): 2.45

Predicted 1-Hour Maximum Ground Level Concentration (ug/m³): 3357

Adjusted MAGLC (ug/m³): 4231 (adjusted for 71.25 hrs/wk)

The permittee, has demonstrated that emissions of xylene and toluene from emissions units R001 and R002 are calculated to be less than eighty per cent of the maximum acceptable ground level concentration (MAGLC); any new raw material or processing agent shall not be applied without evaluating each component toxic air contaminant in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F).

- (7) Prior to making any physical changes to or changes in the method of operation of the emissions unit(s), that could impact the parameters or values that were used in the



predicted 1-hour maximum ground level concentration”, the permittee shall re-model the change(s) to demonstrate that the MAGLC has not been exceeded. Changes that can affect the parameters/values used in determining the 1-hour maximum ground-level concentration include, but are not limited to, the following:

- a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a new toxic air contaminant with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any toxic air contaminant listed in OAC rule 3745-114-01, that was modeled from the initial (or last) application; and
- c. physical changes to the emissions unit(s) or its/their exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the “Toxic Air Contaminant Statute” will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a “modification” under OAC rule 3745_31_01 solely due to a non-restrictive change to a parameter or process operation, where compliance with the “Toxic Air Contaminant Statute”, ORC 3704.03(F), has been documented. If the change(s) meet(s) the definition of a “modification” or if a new toxic is emitted, or the modeled toxic(s) is/are expected to exceed the previous modeled level(s), then the permittee shall apply for and obtain a final permit-to-install prior to the change. The Director may consider any significant departure from the operations of the emissions unit, described in the permit-to-install application, as a modification that results in greater emissions than the emissions rate modeled to determine the ground level concentration; and may require the permittee to submit a permit-to-install application for the increased emissions.

- (8) The permittee shall collect, record, and retain the following information for each toxic evaluation conducted to determine compliance with the “Toxic Air Contaminant Statute”, ORC 3704.03(F):
 - a. a description of the parameters/values used in each compliance demonstration and the parameters or values changed for any re-evaluation of the toxic(s) modeled (the composition of materials, new toxic contaminants emitted, change in stack/exhaust parameters, etc.);
 - b. the Maximum Acceptable Ground Level Concentration (MAGLC) for each significant toxic contaminant or worst-case contaminant, calculated in accordance with the “Toxic Air Contaminant Statute”, ORC 3704.03(F);
 - c. a copy of the computer model run(s), that established the predicted 1-hour maximum ground level concentration that demonstrated the emissions unit(s) to be in compliance with the “Toxic Air Contaminant Statute”, ORC 3704.03(F), initially and for each change that requires re-evaluation of the toxic air contaminant emissions; and
 - d. the documentation of the initial evaluation of compliance with the “Toxic Air Contaminant Statute”, ORC 3704.03(F), and documentation of any determination



that was conducted to re-evaluate compliance due to a change made to the emissions unit(s) or the materials applied.

(9) The permittee shall maintain a record of any change made to a parameter or value used in the dispersion model, used to demonstrate compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground level concentration. The record shall include the date and reason(s) for the change and if the change would increase the ground-level concentration.

(10) The permittee shall maintain documentation of the manufacturer's recommendations, instructions, or operating manuals for the control devices with any modifications deemed necessary by the permittee during the time period in which the control devices are utilized.

The permittee shall operate the control devices in accordance with the manufacturer's recommendations, instructions, or operating manuals with any modifications deemed necessary by the permittee.

(11) The permittee shall conduct periodic inspections of the control devices to determine whether the devices are operating in accordance with the manufacturer's recommendations, instructions, or operating manuals with any modifications deemed necessary by the permittee. The periodic inspections of each control device shall be performed at a frequency that is based upon the recommendation of the manufacturer of the control device, and the permittee shall maintain a copy of the manufacturer's recommended inspection frequency. In addition to these periodic inspections, not less than once each calendar year the permittee shall conduct a comprehensive inspection of the control device while the emissions unit is shut down and perform any needed maintenance and repair for the control device to ensure that it is able to routinely operate in accordance with the manufacturer's recommendations.

(12) The permittee shall document each inspection of a control device by maintaining a record that includes the date of the inspection, a description of each problem identified and the date it was corrected, a description of the maintenance and repairs performed, and the name of the person who performed the inspection.

(13) In the event that the control devices are not operating in accordance with the manufacturer's recommendations, instructions, or operating manuals with any modifications deemed necessary by the permittee, the control devices shall be expeditiously repaired or otherwise returned to operation in accordance with such requirements. The permittee shall maintain documentation of those periods when the control devices are not operating in accordance with such requirements.

e) Reporting Requirements

(1) The permittee shall notify the Director (Ohio EPA, Northeast District Office) in writing of any daily record showing that the dry filters were not in service or not operated in accordance with the manufacturer's recommendations, instructions, or operating manuals with any modifications deemed necessary by the permittee when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (Ohio EPA, Northeast District Office) within 30 days after the event occurs.



- (2) The permittee submit quarterly deviation (excursion) reports that identify:
- a. for the days during which a photochemically reactive material was employed, each day during which the OC emissions from the coatings and photochemically reactive cleanup materials exceeded 8 pounds per hour and/or 40 pounds per day, and the actual OC emissions for each such incidence;
 - b. for the days during which a photochemically reactive material was not employed, each day during which the average VOC emissions from the coatings exceeded the pounds per hour limitation specified above, and the actual average VOC emissions for each such day;
 - c. each day during which the VOC content of any coating exceeded the pounds per gallon limitation specified above and the actual VOC content of each such coating employed; and
 - d. any exceedence of the annual VOC* emission limitation of 24.9 tons per year, as a rolling, 12-month summation from emissions units R001 and R002, combined, and the actual VOC emissions during each such period.

*based upon the premise that 100% of the solvent in the coating and clean up material employed is emitted.

The reports contained in this permit shall be submitted in accordance with the reporting requirements specified in Part B - General Terms and Conditions, Section 1 of this permit.

[Note: After the revision to OAC rule 3745-21-07(G) is approved into the Ohio SIP, section e)(2)(a) and the opening phrase of section e)(2)(b) that references photochemically reactive material shall be voided.

- (3) The permittee shall also submit annual reports that summarize the emissions of VOC from this emissions unit and from emissions units R001 and R002, combined.

The reports shall include the emissions calculations, shall be submitted by January 31 of each year, and shall cover the previous calendar year.

- (4) The permittee shall submit annual reports to the Ohio EPA, Northeast District Office, documenting any changes made to a parameter or value used in the dispersion model (including the air toxic compounds emitted and the emission rate), that was used to demonstrate compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground level concentration. If no changes to the emissions unit(s) or the exhaust stack have been made, then the report shall include a statement to this effect. This report shall be postmarked or delivered no later than January 31 following the end of each calendar year.

- (5) Annual Permit Evaluation Report (PER) forms will be mailed to the permittee at the end of the reporting period specified in the Authorization section of this permit. The permittee shall submit the PER in the form and manner provided by the Director by the due date identified in the Authorization section of this permit. The permit evaluation report shall cover a reporting period of no more than twelve-months for each air contaminant source identified in this permit.



f) Testing Requirements

(1) Compliance with the allowable emission limitations in sections b)(1) and b)(2) of these terms and conditions shall be determined in accordance with the following methods:

a. Emission Limitation:

8 pounds per hour of OC emissions for each day that photochemically reactive materials are employed

Applicable Compliance Method:

Compliance shall be demonstrated by the daily values calculated in section d)(2)(f) based upon the record keeping requirements specified in section d)(2).

b. Emission Limitation:

40 pounds per day of OC emissions for each day that photochemically reactive materials are employed

Applicable Compliance Method:

Compliance shall be demonstrated by the daily values calculated in section d)(2)(d) based upon the record keeping requirements specified in section d)(2).

c. Emission Limitation:

19.07 pounds VOC emissions per hour for each day that photochemically reactive materials are not employed

Applicable Compliance Method:

Compliance shall be demonstrated by the daily values calculated in section d)(3)(g) based on the record keeping requirements specified in section d)(3).

d. Emission Limitation:

24.9 tons of VOC emissions per year from all coatings and cleanup material from R001 and from R001 and R002, combined

Applicable Compliance Method:

Compliance shall be demonstrated by the values recorded in sections d)(5)(d) and d)(5)(e) based on the record keeping requirements specified in sections d)(2), d)(3) and d)(4).

e. Emission Limitation:

6.357 pounds of VOC per gallon coating, as applied

Applicable Compliance Method:

Any determination of VOC content, solids contents, or density of coating material shall be based on the coating materials as employed (as applied), including the



addition of any thinner or viscosity reducer to the coatings. In accordance with OAC rule 3745-21-04(B)(5), the permittee shall determine the composition of the coatings by formulation data supplied by the manufacturer of the coating materials, or from data determined by an analysis of each coating, as applied, by Reference Method 24 or Method 24A. If, pursuant to section 11.4 of Method 24, 40 CFR Part 60, Appendix A (revised as of July 1, 2001), an owner or operator determines that Method 24 or Method 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating or ink to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 and/or Method 24A.

[Note: After the revision to OAC rule 3745-21-07(G) is approved into the Ohio SIP, sections f)(1)(a) and f)(1)(b), the reference to photochemically reactive materials in section f)(1)(c) and the reference to section d)(2) in section f)(1)(d) shall be voided.]

- g) Miscellaneous Requirements
 - (1) None