

Facility ID: 0125230902 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

[Go to Part II for Emissions Unit F001](#)

[Go to Part II for Emissions Unit F002](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0125230902 Emissions Unit ID: F001 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Paved roadways and parking areas (see Section A.2.a)	OAC rule 3745-31-05 PTI 01-8024	Allowable annual particulate emissions from this emissions unit shall not exceed 23.48 tons PM per year.
		No visible particulate emissions except for one minute during any 60-minute period
Unpaved roadways (see Section A.2.b)	OAC rule 3745-17-07 (B)(4)	Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see Sections A.2.c, and A.2.e through A.2.i)
	OAC rule 3745-17-08 (B), (B)(8), (B)(9)	Less stringent than the above-mentioned visible emission limitation
	OAC rule 3745-31-05	Less stringent than the above-mentioned control measure requirements
		Allowable annual particulate emissions from this emissions unit shall not exceed 20.3 tons PM per year.
		No visible particulate emissions except for 3 minutes during any 60-minute period
		Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see Sections A.2.d through A.2.i)
	OAC rule 3745-17-07 (B)(5)	Less stringent than the above-mentioned visible emission limitation
	OAC rule 3745-17-08 (B), (B)(2)	Less stringent than the above-mentioned control measure requirements

2. Additional Terms and Conditions

- (a) The paved roadways that are covered by this permit and subject to the above-mentioned requirements are listed below:
 - paved roadways:
 - Entrance roadway
 - Mixer and cement tanker loop
 The unpaved roadways that are covered by this permit and subject to the above-mentioned requirements are listed below:
 - unpaved roadways:
 - Aggregate delivery trucks loop
 - Rubber tired loader area

The permittee shall employ best available control measures on all paved roadways for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to treat the paved roadways by sweeping at sufficient treatment frequencies to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

The permittee shall employ best available control measures on all unpaved roadways for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to treat the unpaved roadways with water and/or other suitable dust suppression chemicals at sufficient treatment frequencies to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

The needed frequencies of implementation of the control measures shall be determined by the permittee's inspections pursuant to the monitoring section of this permit. Implementation of the control measures shall not be necessary for a paved or unpaved roadway that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Implementation of any control measure may be suspended if unsafe or hazardous driving conditions would be created by its use.

Any unpaved roadway, which during the term of this permit is paved or takes the characteristics of a paved surface due to the application of certain types of dust suppressants, may be controlled with the control measure(s) specified above for paved surfaces. Any unpaved roadway or parking area that takes the characteristics of a paved roadway or parking area due to the application of certain types of dust suppressants shall remain subject to the visible emission limitation for unpaved roadways and parking areas. Any unpaved roadway or parking area that is paved shall be subject to the visible emission limitation for paved roadways and parking areas.

The permittee shall promptly remove, in such a manner as to minimize or prevent resuspension, earth and/or other material from paved streets onto which such material has been deposited by trucking or earth moving equipment or erosion by water or other means.

Open-bodied vehicles transporting materials likely to become airborne shall have such materials covered at all times if the control measure is necessary for the materials being transported.

Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the best available technology requirements of OAC rule 3745-31-05.

B. Operational Restrictions

1. None

C. Monitoring and/or Record Keeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform inspections of the roadways and parking areas in accordance with the following frequencies:

paved roadways:
all

minimum inspection frequency:
daily

unpaved roadways:
all

minimum inspection frequency:
daily

2. The purpose of the inspections is to determine the need for implementing the above-mentioned control measures. The inspections shall be performed during representative, normal traffic conditions. No inspection shall be necessary for a roadway that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above-identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.
3. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.
4. The permittee shall maintain records of the following information:
 - a. the date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;
 - b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;
 - c. the dates the control measures were implemented; and
 - d. on a calendar quarter basis, the total number of days the control measures were implemented and the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measures.

The information required in 4.d. shall be kept separately for (i) the paved roadways and (ii) the unpaved roadways, and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:
 - a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and

- b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.
2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.
- E. Testing Requirements**
1. Emissions Limitation (paved roadways):
- Allowable annual particulate emissions from this emissions unit shall not exceed 23.48 tons PM per year.
- Applicable Compliance Method:
- Compliance with the emission limitation for the paved roadways identified above shall be determined by using the emission factor for paved roadways as stated in AP-42, 5th Edition, October 1997, Chapter 13.2.1, Equation (1). This equation will provide the emission factor for particulate matter in pounds per vehicle mile traveled. This emission factor is then multiplied by the total annual vehicle miles traveled and divided by 2000 pounds to obtain the total annual uncontrolled PM emissions (in tons per year). The uncontrolled PM emissions are then multiplied by a control efficiency of 70 percent (from sweeping) to obtain the total annual controlled PM emissions.
2. Emissions Limitation (unpaved roadways):
- Allowable annual particulate emissions from this emissions unit shall not exceed 20.3 tons PM per year.
- Applicable Compliance Method:
- Compliance with the emission limitation for the unpaved roadways identified above shall be determined by using the emission factor for unpaved roadways as stated in AP-42, 5th Edition, September 1998, Chapter 13.2.2, Equation (2). The correction factor listed in AP-42 for situations in which the average vehicle speed is less than 15 miles per hour also should be used with this equation. This equation will provide the emission factor for particulate matter in pounds per vehicle mile traveled. This emission factor is then multiplied by the total annual vehicle miles traveled and divided by 2000 pounds to obtain the total annual uncontrolled PM emissions (in tons per year). The uncontrolled PM emissions are then multiplied by a control efficiency of 60 percent (from watering and/or use of chemical dust suppressants) to obtain the total annual controlled PM emissions.
3. Emissions Limitation (paved roadways):
- No visible particulate emissions except for one minute during any 60-minute period.
- Applicable Compliance Method:
- Compliance with the emission limitation for the unpaved roadways and parking areas identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources," as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(d) of OAC rule 3745-17-03.
4. Emissions Limitation (unpaved roadways):
- No visible particulate emissions except for 3 minutes during any 60-minute period.
- Applicable Compliance Method:
- Compliance with the emission limitation for the unpaved roadways and parking areas identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources," as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(d) of OAC rule 3745-17-03.
- F. Miscellaneous Requirements**
1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0125230902 Emissions Unit ID: F002 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
- (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
- (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Load-in and load-out of storage piles and wind erosion from storage piles (see Section A.2.a for identification of storage piles).	OAC rule 3745-31-05 PTI 01-8024	2.13 tons per year particulate emissions. No visible emissions except for one minute in any hour. Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see Sections A.2.b, A.2.c, A.2.d, A.2.e and A.2.f).
Load-in and load-out of storage piles, and wind erosion from storage piles	OAC rule 3745-17-07 (B)(6) OAC rule 3745-17-08 (B)(6)	Less stringent than the above-mentioned visible emission limitation. Less stringent than the above-mentioned visible emission limitation.

2. Additional Terms and Conditions

- (a) The storage piles that are covered by this permit and subject to the above-mentioned requirements are listed below:

- (1) Fine Aggregate (sand) pile
- (6) Coarse Aggregate (stone) piles

The permittee shall employ best available control measures on all load-in and load-out operations associated with the storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to maintaining the load-in and load-out material(s) with sufficient moisture to ensure compliance. The permittee also will reduce the drop height of front-end loader buckets to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

The above-mentioned control measure(s) shall be employed for each load-in and load-out operation of each storage pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) are necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measure(s) shall continue during any such operation until further observation confirms that use of the measure(s) is unnecessary.

The permittee shall employ best available control measures for wind erosion from the surfaces of all storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to maintaining the storage piles with sufficient moisture to ensure compliance. The permittee also will maintain as low a pile(s) height as possible to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

The above-mentioned control measure(s) shall be employed for wind erosion from each pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) are necessary to ensure compliance with the above-mentioned applicable requirements. Implementation of the control measure(s) shall not be necessary for a storage pile that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements.

Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the requirements of OAC rules 3745-17-08 and 3745-31-05.

B. Operational Restrictions

1. None

C. Monitoring and/or Record Keeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform inspections of each load-in operation at each storage pile in accordance with the following frequencies:

Storage pile identification:
all

Minimum load-in inspection frequency:
daily

2. Except as otherwise provided in this section, the permittee shall perform inspections of each load-out operation at each storage pile in accordance with the following frequencies:

Storage pile identification:
all

Minimum load-out inspection frequency:
daily

3. Except as otherwise provided in this section, the permittee shall perform inspections of the wind erosion from pile surfaces associated with each storage pile in accordance with the following frequencies:

Storage pile identification:

all

Minimum wind erosion inspection frequency:

daily

4. No inspection shall be necessary for wind erosion from the surface of a storage pile when the pile is covered with snow and/or ice and for any storage pile activity if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.
5. The purpose of the inspections is to determine the need for implementing the control measures specified in this permit for load-in and load-out of a storage pile, and wind erosion from the surface of a storage pile. The inspections shall be performed during representative, normal storage pile operating conditions.
6. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.
7. The permittee shall maintain records of the following information:
 - a. the date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;
 - b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;
 - c. the dates the control measures were implemented; and
 - d. on a calendar quarter basis, the total number of days the control measures were implemented and, for wind erosion from pile surfaces, the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measure(s).

The information required in 7.d. shall be kept separately for (i) the load-in operations, (ii) the load-out operations, and (iii) the pile surfaces (wind erosion), and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:
 - a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and
 - b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.
2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Emissions Limitation:

Allowable annual particulate emissions from this emissions unit shall not exceed 2.13 tons PM per year.

Applicable Compliance Method:

Compliance with the emission limitation for the storage piles identified above shall be determined by using the emission factor for storage piles as stated in AP-42, 5th Edition, January 1995, Chapter 13.2.4, Equation (1). This equation will provide the particulate emission factor for the load-in and load-out operations in pounds per ton. The emission factor for wind erosion from the storage piles shall be determined by using the emission factor equation stated in "Control of Open Fugitive Dust Sources," U.S. EPA, September 1988, Chapter 4.1.3, Equation (4-9). The associated emission factors shall be multiplied by the appropriate production capacities to obtain the emission rates. The emissions from all load-in and load-out operations and wind erosion shall be summed to obtain the total annual PM emissions.
2. Emissions Limitation

No visible emissions except for one minute in any hour.

Applicable Compliance Method:

Compliance with the visible emission limitations for the storage piles identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

1. None