



State of Ohio Environmental Protection Agency

**STREET ADDRESS:**

Lazarus Government Center  
50 W. Town St., Suite 700  
Columbus, Ohio 43215

TELE: (614) 644-3020 FAX: (614) 644-3184  
www.epa.state.oh.us

**MAILING ADDRESS:**

P.O. Box 1049  
Columbus, OH 43216-1049

5/18/2009

**Certified Mail**

Mr. Mike Jones  
REXAM Beverage Can Co  
10444 Waterville Swanton Rd.  
Whitehouse, OH 43571

RE: FINAL AIR POLLUTION PERMIT-TO-INSTALL  
Facility ID: 0448002007  
Permit Number: P0104686  
Permit Type: Administrative Modification  
County: Lucas

No	TOXIC REVIEW
No	PSD
Yes	SYNTHETIC MINOR
No	CEMS
No	MACT
Yes	NSPS
No	NESHAPS
No	NETTING
No	MAJOR NON-ATTAINMENT
No	MODELING SUBMITTED

Dear Permit Holder:

Enclosed please find a final Air Pollution Permit-to-Install (PTI) which will allow you to install or modify the described emissions unit(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, we urge you to read it carefully.

The issuance of this PTI is a final action of the Director and may be appealed to the Environmental Review Appeals Commission ("ERAC") under Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and describe the action complained of and the grounds for the appeal. The appeal must be filed with the ERAC within thirty (30) days after notice of the Director's action. A filing fee of \$70.00 must be submitted to the ERAC with the appeal, although the ERAC, has discretion to reduce the amount of the filing fee if you can demonstrate (by affidavit) that payment of the full amount of the fee would cause extreme hardship. If you file an appeal of this action, you must notify Ohio EPA of the filing of the appeal (by providing a copy to the Director) within three (3) days of filing your appeal with the ERAC. Ohio EPA requests that a copy of the appeal also be provided to the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the ERAC at the following address:

Environmental Review Appeals Commission  
309 South Fourth Street, Room 222  
Columbus, OH 43215

The Ohio EPA is encouraging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Compliance Assistance and Pollution Prevention at (614) 644-3469. If you have any questions regarding this permit, please contact the Toledo Department of Environmental Services. This permit has been posted to the Division of Air Pollution Control (DAPC) Web page <http://www.epa.state.oh.us/dapc>.

Sincerely,

Michael W. Ahern, Manager  
Permit Issuance and Data Management Section, DAPC

Cc: U.S. EPA Region 5 *Via E-Mail Notification*  
Toledo Department of Environmental Services

Ted Strickland, Governor  
Lee Fisher, Lieutenant Governor  
Chris Korleski, Director





**State of Ohio Environmental Protection Agency  
Division of Air Pollution Control**

**FINAL**

**Air Pollution Permit-to-Install  
for  
REXAM Beverage Can Co**

Facility ID: 0448002007  
Permit Number: P0104686  
Permit Type: Administrative Modification  
Issued: 5/18/2009  
Effective: 5/18/2009





**Air Pollution Permit-to-Install**  
for  
REXAM Beverage Can Co

**Table of Contents**

Authorization ..... 1

A. Standard Terms and Conditions ..... 3

    1. Federally Enforceable Standard Terms and Conditions ..... 4

    2. Severability Clause ..... 4

    3. General Requirements ..... 4

    4. Monitoring and Related Record Keeping and Reporting Requirements ..... 5

    5. Scheduled Maintenance/Malfunction Reporting ..... 6

    6. Compliance Requirements ..... 6

    7. Best Available Technology ..... 7

    8. Air Pollution Nuisance ..... 7

    9. Reporting Requirements ..... 7

    10. Applicability ..... 8

    11. Construction of New Sources(s) and Authorization to Install ..... 8

    12. Permit-To-Operate Application ..... 9

    13. Construction Compliance Certification ..... 9

    14. Public Disclosure ..... 9

    15. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations ..... 9

    16. Fees ..... 9

    17. Permit Transfers ..... 10

    18. Risk Management Plans ..... 10

    19. Title IV Provisions ..... 10

B. Facility-Wide Terms and Conditions ..... 11

C. Emissions Unit Terms and Conditions ..... 13

    1. K010, Modified Can Manufacturing Line 2 ..... 14

    2. K011, Modified Can Manufacturing Line 3 ..... 29





State of Ohio Environmental Protection Agency  
Division of Air Pollution Control

**Final Permit-to-Install**  
**Permit Number:** P0104686  
**Facility ID:** 0448002007  
**Effective Date:** 5/18/2009

## Authorization

Facility ID: 0448002007  
Facility Description: Metal beverage can manufacturing facility  
Application Number(s): M0000426  
Permit Number: P0104686  
Permit Description: Rexam is an aluminum can coating facility.  
Permit Type: Administrative Modification  
Permit Fee: \$0.00  
Issue Date: 5/18/2009  
Effective Date: 5/18/2009

This document constitutes issuance to:

REXAM Beverage Can Co  
10444 Waterville Swanton Rd.  
Whitehouse, OH 43571

Of a Permit-to-Install for the emissions unit(s) identified on the following page.

Ohio EPA District Office or local air agency responsible for processing and administering your permit:

Toledo Department of Environmental Services  
348 South Erie Street  
Toledo, OH 43604  
(419)936-3015

The above named entity is hereby granted a Permit-to-Install for the emissions unit(s) listed in this section pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Chris Korleski  
Director



State of Ohio Environmental Protection Agency  
 Division of Air Pollution Control

**Final Permit-to-Install**  
**Permit Number:** P0104686  
**Facility ID:** 0448002007  
**Effective Date:** 5/18/2009

## Authorization (continued)

Permit Number: P0104686  
 Permit Description: Rexam is an aluminum can coating facility.

Permits for the following Emissions Unit(s) or groups of Emissions Units are in this document as indicated below:

<b>Emissions Unit ID:</b>	<b>K010</b>
Company Equipment ID:	Modified Can Manufacturing Line 2
Superseded Permit Number:	04-01465
General Permit Category and Type:	Not Applicable
<b>Emissions Unit ID:</b>	<b>K011</b>
Company Equipment ID:	Modified Can Manufacturing Line 3
Superseded Permit Number:	04-01465
General Permit Category and Type:	Not Applicable



State of Ohio Environmental Protection Agency  
Division of Air Pollution Control

**Final Permit-to-Install**  
**Permit Number:** P0104686  
**Facility ID:** 0448002007  
**Effective Date:** 5/18/2009

## **A. Standard Terms and Conditions**



**1. Federally Enforceable Standard Terms and Conditions**

- a) All Standard Terms and Conditions are federally enforceable, with the exception of those listed below which are enforceable under State law only:
  - (1) Standard Term and Condition A. 2.a), Severability Clause
  - (2) Standard Term and Condition A. 3.c) through A. 3.e) General Requirements
  - (3) Standard Term and Condition A. 6.c) and A. 6.d), Compliance Requirements
  - (4) Standard Term and Condition A. 9., Reporting Requirements
  - (5) Standard Term and Condition A. 10., Applicability
  - (6) Standard Term and Condition A. 11.b) through A. 11.e), Construction of New Source(s) and Authorization to Install
  - (7) Standard Term and Condition A. 14., Public Disclosure
  - (8) Standard Term and Condition A. 15., Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations
  - (9) Standard Term and Condition A. 16., Fees
  - (10) Standard Term and Condition A. 17., Permit Transfers

**2. Severability Clause**

- a) A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition declared invalid.
- b) All terms and conditions designated in parts B and C of this permit are federally enforceable as a practical matter, if they are required under the Act, or any its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA and the State and by citizens (to the extent allowed by section 304 of the Act) under the Act. Terms and conditions in parts B and C of this permit shall not be federally enforceable and shall be enforceable under State law only, only if specifically identified in this permit as such.

**3. General Requirements**

- a) The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and re-issuance, or modification.



- b) It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.
- c) This permit may be modified, revoked, or revoked and reissued, for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.
- d) This permit does not convey any property rights of any sort, or any exclusive privilege.
- e) The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

**4. Monitoring and Related Record Keeping and Reporting Requirements**

- a) Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:
  - (1) The date, place (as defined in the permit), and time of sampling or measurements.
  - (2) The date(s) analyses were performed.
  - (3) The company or entity that performed the analyses.
  - (4) The analytical techniques or methods used.
  - (5) The results of such analyses.
  - (6) The operating conditions existing at the time of sampling or measurement.
- b) Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.
- c) Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall submit required reports in the following manner:
  - (1) Reports of any required monitoring and/or recordkeeping of federally enforceable information shall be submitted to the Toledo Department of Environmental Services.



- (2) Quarterly written reports of (i) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, excluding deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06, that have been detected by the testing, monitoring and recordkeeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures taken, shall be made to the Toledo Department of Environmental Services. The written reports shall be submitted (i.e., postmarked) quarterly, by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. See A.15. below if no deviations occurred during the quarter.
- (3) Written reports, which identify any deviations from the federally enforceable monitoring, recordkeeping, and reporting requirements contained in this permit shall be submitted (i.e., postmarked) to the Toledo Department of Environmental Services every six months, by January 31 and July 31 of each year for the previous six calendar months. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report, which states that no deviations occurred during that period.
- (4) This permit is for an emissions unit located at a Title V facility. Each written report shall be signed by a responsible official certifying that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.

d) The permittee shall report actual emissions pursuant to OAC Chapter 3745-78 for the purpose of collecting Air Pollution Control Fees.

## 5. **Scheduled Maintenance/Malfunction Reporting**

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction, i.e., upset, of any emissions units or any associated air pollution control system(s) shall be reported to the Toledo Department of Environmental Services in accordance with paragraph (B) of OAC rule 3745-15-06. (The definition of an upset condition shall be the same as that used in OAC rule 3745-15-06(B)(1) for a malfunction.) The verbal and written reports shall be submitted pursuant to OAC rule 3745-15-06.

Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emission unit(s) that is (are) served by such control system(s).

## 6. **Compliance Requirements**

- a) The emissions unit(s) identified in this Permit shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.
- b) Any document (including reports) required to be submitted and required by a federally applicable requirement in this permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.
- c) Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:



- (1) At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.
  - (2) Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with ORC section 3704.08.
  - (3) Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.
  - (4) As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.
- d) The permittee shall submit progress reports to the Toledo Department of Environmental Services concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:
- (1) Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
  - (2) An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

## **7. Best Available Technology**

As specified in OAC Rule 3745-31-05, new sources that must employ Best Available Technology (BAT) shall comply with the Applicable Emission Limitations/Control Measures identified as BAT for each subject emissions unit.

## **8. Air Pollution Nuisance**

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

## **9. Reporting Requirements**

The permittee shall submit required reports in the following manner:

- a) Reports of any required monitoring and/or recordkeeping of state-only enforceable information shall be submitted to the Toledo Department of Environmental Services.
- b) Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from state-only required emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the Toledo Department of Environmental Services. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted



(i.e., postmarked) quarterly, by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

## **10. Applicability**

This Permit-to-Install is applicable only to the emissions unit(s) identified in the Permit-to-Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

## **11. Construction of New Sources(s) and Authorization to Install**

- a) This permit does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. This permit does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the application and terms and conditions of this permit. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of this permit does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Issuance of this permit is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.
- b) If applicable, authorization to install any new emissions unit included in this permit shall terminate within eighteen months of the effective date of the permit if the owner or operator has not undertaken a continuing program of installation or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.
- c) The permittee may notify Ohio EPA of any emissions unit that is permanently shut down (i.e., the emissions unit has been physically removed from service or has been altered in such a way that it can no longer operate without a subsequent "modification" or "installation" as defined in OAC Chapter 3745-31) by submitting a certification from the authorized official that identifies the date on which the emissions unit was permanently shut down. Authorization to operate the affected emissions unit shall cease upon the date certified by the authorized official that the emissions unit was permanently shut down. At a minimum, notification of permanent shut down shall be made or confirmed through completion of the annual PER covering the last period of operation of the affected emissions unit(s).
- d) The provisions of this permit shall cease to be enforceable for each affected emissions unit after the date on which an emissions unit is permanently shut down (i.e., emissions unit has been physically removed from service or has been altered in such a way that it can no longer operate without a subsequent "modification" or "installation" as defined in OAC Chapter 3745-31). All records relating to any permanently shutdown emissions unit, generated while the emissions unit was in operation, must be maintained in accordance with law. All reports required by this permit must be submitted for any period an affected emissions unit operated prior to permanent shut down. At a minimum, the permit requirements must be evaluated as part of the PER covering the last period the emissions unit operated.



No emissions unit certified by the authorized official as being permanently shut down may resume operation without first applying for and obtaining a permit pursuant to OAC Chapter 3745-31.

- e) The permittee shall comply with any residual requirements related to this permit, such as the requirement to submit a PER, air fee emission report, or other any reporting required by this permit for the period the operating provisions of this permit were enforceable, or as required by regulation or law. All reports shall be submitted in a form and manner prescribed by the Director. All records relating to this permit must be maintained in accordance with law.

## **12. Permit-To-Operate Application**

The permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77. The permittee shall submit a complete Title V permit application or a complete Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).

## **13. Construction Compliance Certification**

The applicant shall identify the following dates in the online facility profile for each new emissions unit identified in this permit.

- a) Completion of initial installation date shall be entered upon completion of construction and prior to start-up.
- b) Commence operation after installation or latest modification date shall be entered within 90 days after commencing operation of the applicable emissions unit.

## **14. Public Disclosure**

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

## **15. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations**

If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly (i.e., postmarked), by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.

## **16. Fees**

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable permit-to-install fees within 30 days after the issuance of any permit-to-install. The permittee shall pay all applicable permit-to-operate fees within thirty days of the issuance of the invoice.



State of Ohio Environmental Protection Agency  
Division of Air Pollution Control

**Final Permit-to-Install**  
**Permit Number:** P0104686  
**Facility ID:** 0448002007  
**Effective Date:** 5/18/2009

**17. Permit Transfers**

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The Toledo Department of Environmental Services must be notified in writing of any transfer of this permit.

**18. Risk Management Plans**

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. 7401 et seq. ("Act"), the permittee shall comply with the requirement to register such a plan.

**19. Title IV Provisions**

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.



State of Ohio Environmental Protection Agency  
Division of Air Pollution Control

**Final Permit-to-Install**  
**Permit Number:** P0104686  
**Facility ID:** 0448002007  
**Effective Date:** 5/18/2009

## **B. Facility-Wide Terms and Conditions**



State of Ohio Environmental Protection Agency  
Division of Air Pollution Control

**Final Permit-to-Install**  
**Permit Number:** P0104686  
**Facility ID:** 0448002007  
**Effective Date:** 5/18/2009

1. All the following facility-wide terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only:
  - a) None.



State of Ohio Environmental Protection Agency  
Division of Air Pollution Control

**Final Permit-to-Install**  
**Permit Number:** P0104686  
**Facility ID:** 0448002007  
**Effective Date:** 5/18/2009

## **C. Emissions Unit Terms and Conditions**



**1. K010, Modified Can Manufacturing Line 2**

**Operations, Property and/or Equipment Description:**

K010 - Beverage can coating line #2- comprised of a continuous motion printer with a 3.00 mmBtu/hr oven, an interior body sprayer with 3.55 mmBtu/hr oven and a continuous motion coater with 3.00 mmBtu/hr oven; both the continuous motion printer oven and the inside sprayer oven are controlled with a 7.3 mm Btu.hr regenerative thermal oxidizer (RTO).

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D) (PTI 04-01465 issued on 5/22/07)	See b)(2)a.  Volatile Organic Compound (VOC) emissions shall not exceed 57.26 tons per rolling, 12-month period.  See b)(2)i., (2)j. and c)(3)
b.	OAC rule 3745-31-05(A)(3) (PTI 04-01465 issued on 5/22/07)	VOC emissions shall not exceed 20.13 pounds per hour.  See b)(2)c. (2)i. and (2)j.
c.	OAC rule 3745-31-05(A)(3)(a)(ii)	See b)(2)h.
d.	OAC rule 3745-17-07(A)(1)	Visible emissions from stacks this emissions unit shall not exceed 20% opacity as a 6-minute average, unless otherwise specified by the rule.
e.	OAC rule 3745-17-11(B)(1)	PE shall not exceed 0.551 pounds per hour.  See b)(2)k.
f.	OAC rule 3745-18-06(A)	See b)(2)c. and (2)e.
g.	40 CFR Part 60, Subpart WW	See b)(2)d. and (2)f..



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
h.	OAC rule 3745-21-09(D)(1)	See b)(2)d.
i.	OAC rule 3745-21-08(B)	See b)(2)g.

(2) Additional Terms and Conditions

- a. The emissions of hazardous air pollutants (HAPs) from this facility, as identified in Section 112(b) of Title III of the Clean Air Act, shall not exceed 9.9 tons per year for any single HAP and 24.9 tons per year for any combination of HAPs.
- b. The requirement of this rule also include compliance with the requirements of 40 CFR Part 60, Subpart WW.
- c. The hourly and annual emission limitations for the bake ovens and the RTO were established for PTI purposes to reflect the potential to emit for the combustion of natural gas in this emissions unit at the maximum burner heat input capacity of 3.0 mmBtu per hour for the continuous motion base coat oven, 3.00 mmBtu per hour for the continuous motion printer oven, 3.55 mmBtu per hour for the inside spray bake oven, and 7.30 mmBtu per hour for the RTO. Therefore, it is not necessary to develop monitoring, record keeping, and/or reporting requirements to ensure compliance with these limitations.
- d. The emission limitation established by this rule is less stringent than the emission limitation established by OAC rule 3745-31-05(A)(3).
- e. OAC rule 3745-18-06(A) does not establish SO<sub>2</sub> emission limitations for the fuel burning equipment associated with this emissions unit because the emissions unit only employs natural gas as fuel. However, OAC rule 3745-18-06(A) requires that the natural gas being combusted meet certain fuel quality restrictions (a heat content greater than 950 Btu per standard cubic foot and a sulfur content less than 0.6 pound per million standard cubic feet). Because the natural gas being burned in this emission unit is the standard, pipeline quality natural gas supplied to industrial, commercial, and residential users throughout the State, it is assumed that it meets the fuel quality restrictions; and no monitoring, record keeping or reporting requirements are necessary to ensure ongoing compliance with OAC rule 3745-18-06(A).
- f. This emissions unit is subject to the applicable provisions of Subpart WW of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60. The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.
- g. On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the



requirement to satisfy the "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

h. The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the SO<sub>2</sub>, NO<sub>x</sub>, PE, PM<sub>10</sub>, and CO emissions from this air contaminant source since the uncontrolled potential to emit for SO<sub>2</sub>, NO<sub>x</sub>, PE, PM<sub>10</sub> and CO is less than 10 tons per year.

i. Volatile organic compound (VOC) emissions from individual coatings shall not exceed the following:

- inks: 1.81 pounds per gallon of coating excluding water and exempt solvents;
- basecoat: 1.8 pounds per gallon of coating excluding water and exempt solvents;
- basecoat: 2.4 pounds per gallon of coating solids;
- over varnish: 2.1 pounds per gallon of coating excluding water and exempt solvents;
- over varnish: 2.9 pounds per gallon of coating solids;
- exterior bottom end varnish: 2.1 pounds per gallon of coating excluding water and exempt solvents;
- exterior bottom end varnish: 2.9 pounds per gallon of coating solids;
- inside spray: 3.5 pounds per gallon of coating excluding water and exempt solvents;
- inside spray: 6.8 pounds per gallon of coating solids; and
- clean-up solvent: 6.55 pounds of VOC per gallon.

j. For the regenerative thermal oxidizer (RTO), the capture efficiency shall be a minimum of 72% and the destructive efficiency shall be a minimum of 95% for VOC emissions from the continuous motion printer oven and inside body spray oven.

k. The inside body coating is the only coating sprayed and therefore is the only coating producing particulate emissions.

c) Operational Restrictions

- (1) The permittee shall burn only natural gas in the 3.0 mmBtu direct fired natural gas continuous motion base coater oven, 3.00 mmBtu per hour for the continuous motion printer oven, 3.55 mmBtu per hour for the interior body coating oven emissions units, and the 7.3 mmBtu per hour Regenerative Thermal Oxidizer (RTO).
- (2) The individual HAP and total HAP, combined, emission rates for all emissions units at the facility shall not exceed 9.9 and 24.9 tons per year, respectively, based upon a rolling, 12-month summation of emission rates. .
- (3) Coating and clean-up material usage shall not exceed the following levels based upon a rolling, 12-month summation of the usage rates:



Base coat: 9,600 gallons per rolling 12-month period;  
Over varnish: 74,435 gallons per rolling 12-month period;  
Bottom varnish: 4,120 gallons per rolling 12-month period;  
Inside spray: 186,095 gallons per rolling 12-month period;  
Inks: 7,188 gallons per rolling 12-month period; and  
Clean-up solvent: 700 gallons per rolling 12-month period..

d) Monitoring and/or Recordkeeping Requirements

- (1) For each day during which the permittee burns a fuel other than natural gas in the basecoater pin oven, printer oven, the interior body coating oven, or the RTO, the permittee shall maintain a record of the type and quantity of fuel burned in the respective oven.
- (2) The permittee shall collect and record the following information each month for the line:
  - a. For the coatings:
    - i. the name and identification number of each coating (i.e., over varnish, bottom varnish, inside spray coating, or basecoat coating), as applied;
    - ii. the volume of each coating employed, in gallons;
    - iii. the VOC content of each coating, in pounds of VOC per gallon of coating;
    - iv. the VOC content of each coating, in pounds of VOC per gallon of coating excluding water and exempt solvents;
    - v. the VOC content of each coating, in pounds of VOC per gallon of solids, as applied; and
    - vi. the monthly total VOC emissions from all coatings employed,  $[(ii) \times (iii) \times (1-TCE)] \div 2000$ , in tons; (TCE = overall percentage total control efficiency of the RTO as determined during the most recent emissions test that demonstrated compliance. Prior to the initial compliance test of the RTO, the permittee shall use the estimated overall percentage total control based on testing of a similar source  $((72\%)(95\%))=0.684$  (TCE = 0 for base coat at all times).
  - b. For the inks:
    - i. the name and identification number of each ink, as applied;
    - ii. the volume (or mass) of each ink employed, in gallons (or pounds);
    - iii. the VOC content of each ink, in pounds of VOC per gallon (or pounds) of ink;
    - iv. the VOC content of each ink, in pounds of VOC per gallon of ink excluding water and exempt solvents;



- v. the monthly total VOC emissions from all inks employed, calculated on a volume (or mass) basis,  $[(ii) \times (iii) \times (1-TCE)] \div 2000$ , in tons; (TCE = overall percentage total control efficiency of the RTO as determined during the most recent emissions test that demonstrated compliance. Prior to the initial compliance test of the RTO, the permittee shall use the estimated overall percentage total control based on testing of a similar source  $((72\%)(95\%))=0.684$  (TCE = 0 for base coat at all times).
  - c. For the clean-up materials:
    - i. the name and identification number of each clean-up material employed,
    - ii. the volume of each clean-up material employed, in gallons,
    - iii. the VOC content of each clean-up material employed, in pounds of VOC per gallon,
    - iv. the monthly total VOC emissions from all clean-up materials employed,  $(ii) \times (iii) \div 2000$ , in tons;
  - d. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation of VOC emissions from all coatings, inks and clean-up materials employed, in tons.
  - e. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation, of each type of coating employed in gallons.
  - f. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation, of all the types of ink employed in gallons (or pounds).
  - g. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation, of each type of clean-up solvent employed, in gallons.
- (3) The permittee shall install, operate, and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the thermal incinerator when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The accuracy for each thermocouple, monitor, and recorder shall be guaranteed by the manufacturer to be within  $\pm 0.75$  percent of the temperature being measured or  $\pm 4.5$  degrees Fahrenheit ( $\pm 2.5$  degrees Celcius), whichever is greater. The temperature monitor and recorder shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and the operating manuals, with any modifications deemed necessary by the permittee. The permittee shall collect and calculate the average combustion temperature within the thermal incinerator, each of the eight, 3-hour blocks of time during each day of operation, and shall record and maintain the following information each day:
- a. all 3-hour blocks of time, when the emissions unit was in operation, during which the average combustion temperature within the thermal incinerator was more than 50 degrees Fahrenheit below the average temperature maintained during



the most recent emissions test (1616° F based on the emissions test performed on 7/8/09 for EU# K010 and K011) that demonstrated the emissions unit to be in compliance;

- b. a log or record of the operating time for the capture (collection) system, thermal incinerator, monitoring equipment, and the associated emissions unit;
  - c. whenever the monitored value for the combustion temperature deviates from the range specified above, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation: the date(s) the investigation was conducted, the names of the personnel who conducted the investigation, and the findings and recommendations; and
  - d. in response to each required investigation to determine the cause of the deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable combustion temperature specified above, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken: a description of the corrective action, the date it was completed, the date and time of the deviation, the total period of time during which there was a deviation, the combustion temperature immediately after the corrective action, and the names of the personnel who performed the work. Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.
- (4) The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack and for any visible emissions of fugitive dust from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
- a. the location and color of the emissions;
  - b. whether the emissions are representative of normal operations;
  - c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;
  - d. the total duration of any visible emission incident; and
  - e. any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item (d) above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that



no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

- (5) The permittee shall collect and record the following information each month for the line:
- a. the name and identification number of each coating, and each cleanup material employed;
  - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
  - c. the total HAP content of each coating, and cleanup material, in pounds per gallon;
  - d. the individual HAP content of each coating, and cleanup material, in pounds per gallon;
  - e. the number of gallons of each coating, and cleanup material employed;
  - f. the total VOC emissions (VOC applied) from all coatings, and cleanup materials employed [the sum of (5)b. times (5)e. divided by 2000 lbs/ton) for all coatings and cleanup materials], in tons;
  - g. the total HAP emissions (HAP applied) from all coatings and cleanup materials employed, in tons;
  - h. the individual HAP emissions (HAP applied) from all coatings and cleanup materials employed, in tons;
  - i. the rolling, 12-month summation of total HAP emissions, in tons; and
  - j. the rolling, 12-month summation of individual HAP emissions, in tons.
- (6) The permittee shall maintain records of the facility's potential to emit for each individual hazardous air pollutant and the total of all hazardous air pollutants combined by maintaining a formal up-to-date HAP emissions inventory from all HAP emissions units at the facility. The permittee shall maintain a record including methods, procedures, and assumptions supporting the calculations.

e) Reporting Requirements

- (1) The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than natural gas was burned in any oven or the RTO comprising this emission unit, as fuel. Each report shall be submitted to the Toledo Division of Environmental Services within 30 days after the deviation occurs.
- (2) The permittee shall notify the Toledo Division of Environmental Services in writing of any monthly record showing the use of non-complying coatings. The notification shall include a copy of such record and shall be sent to the Toledo Division of Environmental Services within 30 days following the end of the calendar month.



- (3) The permittee shall submit quarterly deviation (excursion) reports that identify:
- a. all exceedances of the rolling, 12-month usage rate limitations for coatings and clean-up materials specified under c)(3);
  - b. all exceedances of the rolling, 12-month emission limitation for VOC and, for the first 12 calendar months of operation or the first 12 calendar months following the issuance of this permit, all exceedances of the maximum allowable cumulative emission levels;
  - c. all exceedances of the rolling, 12-month emission limitations for individual HAP or any combination of HAP and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative total HAP emission limitation set forth in c)(2) of this permit;and
  - d. identify all days during which any visible particulate emissions were observed from any stack serving this emissions unit and describe any corrective actions taken to eliminate the visible particulate emissions. If no visible emissions observed, then state no visible emissions occurred during that period.

These reports shall be submitted by January 31, April 30, July 31, and October 31 of each year to the Toledo Division of Environmental Services and shall address the data obtained during the previous calendar period. If no deviations (excursions) have occurred, the permittee shall submit a quarterly report which states that no deviations (excursions) have occurred during the previous quarter.

- (4) The permittee shall submit quarterly reports that identify the following information concerning the operation of the RTO during the operation of the emissions unit:
- a. each period of time when the combustion temperature was outside the acceptable range;
  - b. an identification of each incident of deviation described in (4)a. where a prompt investigation was not conducted;
  - c. an identification of each incident of deviation described in (4)a. where prompt corrective action, that would bring the temperature into compliance with the acceptable range, was determined to be necessary and was not taken; and
  - d. an identification of each incident of deviation described in (4)a. where proper records were not maintained for the investigation and/or the corrective action.
- f) Testing Requirements
- (1) Compliance with b)(1) and b)(2) of these terms and conditions shall be determined in accordance with the following methods:
- a. Emission Limitation:  
  
Emissions from all emissions units at the facility shall not exceed 9.9 tons per year for any single HAP and 24.9 tons per year for any combination of HAPs.



Applicable Compliance Method:

The monitoring and record keeping requirements of c) will be used to demonstrate compliance.

b. Emission Limitation:

57.26 tons of VOC per rolling, 12-month period for Line 2.

Applicable Compliance Method:

Compliance with this emissions limitation shall be demonstrated as the summation of the VOC emissions for the combustion of natural gas and the VOC emissions from all coatings and clean-up materials. Compliance with this emission limitation will be demonstrated by the monitoring and record keeping requirements of d)(2).

c. Emission Limitation:

20.13 pounds of VOC per hour.

Applicable Compliance Method:

A one-time calculation of the hourly potential to emit, based upon the worst case operating scenario, shall be used to demonstrate compliance with this limitation.

This emissions limitation shall be demonstrated as the summation of the VOC emissions for the combustion of natural gas and the VOC emissions from all coatings and clean-up materials:

Sum of [Gallons of coating applied per hour\*weight % of solvent\*density of coating\*(1-CE)] + sum of [(fuel usage rating\*5.5 lb/mmscf\*(1-CE))/1020 mmBtu/mmscf] CE=0 for basecoat and basecoat oven at all times

CE = overall percentage control efficiency of the RTO, as determined during the most recent emissions test that demonstrated compliance. Prior to the initial compliance test of the RTO, the permittee shall use the estimated overall percentage control based on testing of a similar source ((72%)(95%))=0.684

d. Emission limitation:

1.8 pounds of VOC per gallon of coating (minus water and exempt solvents) for the continuous motion base coat coating line.

Applicable Compliance Method:

The monitoring and record keeping requirement in d) will be used to demonstrate compliance. If required, compliance shall be demonstrated by an evaluation performed in accordance with OAC rule(s) 3745-21-09(B)(3)(f) and 3745-21-10(B) using the methods and procedures specified in US EPA Reference Method 24 of 40 CFR Part 60, Appendix A. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method



24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the US EPA and shall use formulation data for that coating to demonstrate compliance until the US EPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

e. Emission limitation:

2.40 pound of VOC per gallon of coating solids for the continuous motion base coat coating line.

Applicable Compliance Method:

The monitoring and record keeping requirement A.III will be used to demonstrate compliance. If required, compliance shall be demonstrated by an evaluation performed in accordance with OAC rule(s) 3745-21-09(B)(3)(f) and 3745-21-10(B) using the methods and procedures specified in US EPA Reference Method 24 of 40 CFR Part 60, Appendix A. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the US EPA and shall use formulation data for that coating to demonstrate compliance until the US EPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

f. Emission Limitation:

CO emissions shall be less than 10 tons per year from line 2 (ie. the continuous motion base coater oven, the continuous motion printer oven, the inside bake oven, and the RTO).

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner heat input capacity (3.0 mmBtu/hr + 3.0 mmBtu/hr + 3.55 mmBtu/hr + 7.33 mmBtu/hr = 16.88 mmBtu/hr) by an emission factor of 84 pounds of CO per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98. The resulting value shall be multiplied by 8760 hours per year and divided by 2000 pounds per ton.

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Methods 1 thru 4 and 10 of 40 CFR Part 60 Appendix A. Alternative U.S. EPA approved test methods may be used with prior approval from Ohio EPA.

g. Emission Limitation:

NOx emissions shall be less than 10 tons per year from line 2 (ie. the continuous motion base coater oven, the continuous motion printer oven, the inside bake oven, and the RTO).



Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner heat input capacity (3.0 mmBtu/hr + 2.75 mmBtu/hr + 3.55 mmBtu/hr + 7.33 mmBtu/hr = 16.63 mmBtu/hr) by an emission factor of 100 pounds of NOx per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98. The resulting value shall be multiplied by 8760 hours per year and divided by 2000 pounds per ton.

If required, the permittee shall demonstrate compliance using Methods 1 through 4 and 7E of 40 CFR Part 60, Appendix A. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

h. Emission Limitation:

VE shall not exceed 20% opacity of visible PE, as a 6-minute average.

Applicable Compliance Method:

If required, compliance shall be determined through visible emissions observations performed in accordance with Method 9 of 40 CFR Part 60, Appendix A and the procedures specified in OAC rule 3745-17-03(B)(1).

i. Emission Limitation:

PE emissions shall be less than 10 tons per year from line 2 (ie. the continuous motion base coater oven, the continuous motion printer oven, the inside bake oven, and the RTO).

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner heat input capacity (3.0 mmBtu/hr + 2.75 mmBtu/hr + 3.55 mmBtu/hr + 7.33 mmBtu/hr = 16.63 mmBtu/hr) by an emission factor of 1.9 pounds of PE per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98. The resulting value shall be multiplied by 8760 hours per year and divided by 2000 pounds per ton.

To this amount shall be added the emissions from the from the inside spray operation. Annual allowable emissions are based on the hourly allowable emission rate (0.55 pound per hour) multiplied by the maximum annual operating hours (8760 hours per year), divided by 2000 pounds/ton.

If required, the permittee shall demonstrate compliance using Methods 1 thru 5 of 40 CFR part 60, Appendix A. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.



j. Emission Limitation:

PM<sub>10</sub> emissions shall be less than 10 tons per year from line 2 (ie. the continuous motion base coater oven, the continuous motion printer oven, the inside bake oven, and the RTO).

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner heat input capacity (3.0 mmBtu/hr + 2.75 mmBtu/hr + 3.55 mmBtu/hr + 7.33 mmBtu/hr = 16.63 mmBtu/hr) by an emission factor of 7.6 pounds of PM<sub>10</sub> per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98. The resulting value shall be multiplied by 8760 hours per year and divided by 2000 pounds per ton.

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

k. Emission Limitation:

SO<sub>2</sub> emissions shall be less than 10 tons per year from line 2 (ie. the continuous motion base coater oven, the continuous motion printer oven, the inside bake oven, and the RTO).

Applicable Compliance Method

Compliance shall be demonstrated by multiplying the maximum burner heat input capacity (3.0 mmBtu/hr + 2.75 mmBtu/hr + 3.55 mmBtu/hr + 7.33 mmBtu/hr = 16.63 mmBtu/hr) by an emission factor of 0.6 pound of SO<sub>2</sub> per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98. The resulting value shall be multiplied by 8760 hours per year and divided by 2000 pounds per ton.

If required, the permittee shall demonstrate compliance using Methods 1 through 4 and 6 of 40 CFR part 60, Appendix A. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

l. Emission Limitation:

2.1 pounds of VOC per gallon of coating (excluding water and exempt solvents) for over varnish and exterior bottom end varnish.

Applicable Compliance Method:

The monitoring and record keeping requirement in d) will be used to demonstrate compliance. If required, compliance shall be demonstrated by an evaluation performed in accordance with OAC rule(s) 3745-21-09(B)(3)(f) and 3745-21-10(B) using the methods and procedures specified in US EPA Reference Method



24 of 40 CFR Part 60, Appendix A. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the US EPA and shall use formulation data for that coating to demonstrate compliance until the US EPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

m. Emission Limitation:

2.9 pounds of VOC per gallon of coating solids for over varnish and exterior bottom end varnish.

Applicable Compliance Method:

The monitoring and record keeping requirement in d) will be used to demonstrate compliance. If required, compliance shall be demonstrated by an evaluation performed in accordance with OAC rule(s) 3745-21-09(B)(3)(f) and 3745-21-10(B) using the methods and procedures specified in US EPA Reference Method 24 of 40 CFR Part 60, Appendix A. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the US EPA and shall use formulation data for that coating to demonstrate compliance until the US EPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

n. Emission limitation:

1.81 pounds of VOC per gallon of coating (excluding water and exempt solvents) for inks.

Applicable Compliance Method:

Compliance shall be determined through the monitoring and record keeping requirements of c). If required, compliance shall be demonstrated by an evaluation performed in accordance with OAC rule(s) 3745-21-09(B)(3)(f) and 3745-21-10(B) using the methods and procedures specified in US EPA Reference Method 24 of 40 CFR Part 60, Appendix A. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the US EPA and shall use formulation data for that coating to demonstrate compliance until the US EPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

o. Emission Limitation:

3.5 pounds of VOC per gallon of coating (excluding water and exempt solvents) for the interior body coating line, line 2 can body sprayers.



Applicable Compliance Method:

The monitoring and record keeping requirement in d) will be used to demonstrate compliance. If required, compliance shall be demonstrated by an evaluation performed in accordance with OAC rule 3745-21-10(B) and OAC rule 3745-21-04(B)(5) using the methods and procedures specified in US EPA Reference Method 24 of 40 CFR Part 60, Appendix A. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If the permittee determines that Method 24 has not been used for a particular coating, the permittee shall request that the coating supplier perform Method 24 on the coating in question. If the supplier determines that Method 24 cannot be used, the permittee shall so notify the Administrator of the US EPA and pursuant to section 4.3 of Method 24, 40 CFR Part 60, Appendix A, will request that the supplier use formulation data to demonstrate compliance until the US EPA provides alternative analytical procedures or alternative precision statements for Method 24.

p. Emission Limitation:

6.8 pounds of VOC per gallon of coating solids for the Interior Body Coating, line 2 can body sprayers.

Applicable Compliance Method:

The monitoring and record keeping requirement in d) will be used to demonstrate compliance. If required, compliance shall be demonstrated by an evaluation performed in accordance with OAC rule 3745-21-10(B) and OAC rule 3745-21-04(B)(5) using the methods and procedures specified in US EPA Reference Method 24 of 40 CFR Part 60, Appendix A. Alternate, equivalent methods may be based upon approval by the Toledo Division of Environmental Services. If the permittee determines that Method 24 has not been used for a particular coating, the permittee shall request that the coating supplier perform Method 24 on the coating in question. If the supplier determines that Method 24 cannot be used, the permittee shall so notify the Administrator of the US EPA and pursuant to section 4.3 of Method 24, 40 CFR Part 60, Appendix A, will request that the supplier use formulation data to demonstrate compliance until the US EPA provides alternative analytical procedures or alternative precision statements for Method 24.

q. Emission limitation:

clean-up solvent: 6.55 pounds of VOC per gallon.

Applicable Compliance Method:

The permittee shall determine the VOC content of the clean-up solvent from manufacturer's formulation data.

r. Emission Limitation:

0.551 pound per hour PE from the inside body spray



Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum coating usage (26.08 gal/hr) by the coating density (8.43 lb coating/gal coating), the solid concentration (0.211 lb PE/lb coating) and the transfer efficiency multiplied by the control efficiency  $((1-0.94)(1-0.090)=0.006)$ .

If required, the permittee shall demonstrate compliance using Methods 1 thru 5 of 40 CFR part 60, Appendix A. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

s. Emission Limitation:

95% destructive efficiency and a minimum 72% capture efficiency for VOC emissions from the continuous motion printer and inside body spray.

Applicable Compliance Method:

The permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Method 25 or 25A of 40 CFR Part 60 Appendix A and Method 204 through 204F of 40 CFR Part 51, Appendix M, using the methods and procedures specified in OAC rule 3745-21-10. The permittee may request to use an alternate method or procedure for the determination of capture efficiency in accordance with the US EPA's "Guidelines for Determining Capture Efficiency", dated January 9, 1995. (The Ohio EPA will consider the request, including an evaluation of the applicability, necessity and validity of the alternative, and may approve the use of the alternate if such approval does not contravene any other applicable requirement.)

g) Miscellaneous Requirements

- (1) The terms and conditions contained in this permit to install for emissions unit K010 shall supercede all requirements for emissions unit K010 contained in Permit to Install 04-01439 (issued 6/13/2006) and PTI 04-01465 (issued 5/22/07).



**2. K011, Modified Can Manufacturing Line 3**

**Operations, Property and/or Equipment Description:**

K011 - Beverage can manufacturing and coating line 3 comprised of a cupper and series of trimmers (no control), 1.925 mmBtu/hr natural gas washer, continuous motion printer and a 2.75 mmBtu/hr oven and an interior body spray coater and 5.2 mmBtu/hr oven controlled by a 7.3 mmBtu/hr regenerative thermal oxidizer (RTO).

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(D)  (PTI 04-01465 issued 5/22/07)	See b)(2)a.  Volatile Organic Compound (VOC) emissions shall not exceed 72.80 tons per rolling, 12-month period from line 3.  See b)(2)e., (2)h. and c)(2).
b.	OAC rule 3745-31-05(A)(3)  (PTI 04-01465 issued 5/22/07)	VOC emissions shall not exceed 22.52 pounds per hour.  See b)(2)c., (2)e. and (2)h.
c.	OAC rule 3745-31-05(A)(3)(a)(ii)	See b)(2)c. and (2)g.
d.	OAC rule 3745-17-07(A)(1)	Visible Emissions (VE) from this emissions unit shall not exceed 20% opacity as a six minute average.
e.	OAC rule 3745-17-11(B)(1)	Particulate emissions (PE) shall not exceed 0.551 pounds per hour.  See b)(2)j.
f.	OAC rule 3745-18-06(A)	See b)(2)c. and (2)i.
g.	OAC rule 3745-21-08(B)	See b)(2)d.



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
h.	40 CFR Part 60, Subpart WW	See b)(2)b. and (2)f.
I	OAC rule 3745-21-09(D)	See b)(2)b.

(2) Additional Terms and Conditions

- a. The emissions of hazardous air pollutants (HAPs) from this facility, as identified in Section 112(b) of Title III of the Clean Air Act, shall not exceed 9.9 tons per year for any single HAP and 24.9 tons per year for any combination of HAPs.
- b. The emission limitation established by this rule is less stringent than the emission limitation established by OAC rule 3745-31-05(A)(3).
- c. The hourly and annual emission limitations for the bake ovens and the RTO were established for PTI purposes to reflect the potential to emit for the combustion of natural gas in this emissions unit at the maximum burner heat input capacity. Therefore, it is not necessary to develop monitoring, record keeping and/or reporting requirements to ensure compliance with these limitations.
- d. On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the requirement to satisfy the "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.
- e. Volatile organic compound (VOC) emissions from individual coatings shall not exceed the following:
  - inks: 1.81 pounds per gallon of coating excluding water and exempt solvents;
  - over varnish: 2.1 pounds per gallon of coating excluding water and exempt solvents;
  - over varnish: 2.9 pounds per gallon of coating solids;
  - exterior bottom end varnish: 2.1 pounds per gallon of coating excluding water and exempt solvents;
  - exterior bottom end varnish: 2.9 pounds per gallon of coating solids;
  - clean-up solvent: 6.55 pounds of VOC per gallon;
  - inside spray: 3.5 pounds per gallon of coating excluding water and exempt solvents; and
  - inside spray: 6.8 pounds per gallon of coating solids.



- f. This emissions unit is subject to the applicable provisions of Subpart WW of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60. The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.
- g. The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the CO, NOx, SO<sub>2</sub>, PE, and PM<sub>10</sub> emissions from this air contaminant source since the uncontrolled potential to emit for CO, NOx, SO<sub>2</sub>, PE, and PM<sub>10</sub> emissions are less than 10 tons per year.
- h. For the regenerative thermal oxidizer (RTO), the capture efficiency shall be a minimum of 72% and the destructive efficiency shall be a minimum of 95% for VOC emissions from the inside body spray oven.
- i. OAC rule 3745-18-06(A) does not establish SO<sub>2</sub> emission limitations for the fuel burning equipment associated with this emissions unit because the emissions unit only employs natural gas as fuel. However, OAC rule 3745-18-06(A) requires that the natural gas being combusted meet certain fuel quality restrictions (a heat content greater than 950 BTU per standard cubic feet). Because the natural gas being burned in this emission unit is the standard, pipeline quality natural gas supplied to industrial, commercial, and residential users throughout the State, it is assumed that it meets the fuel quality restrictions; and no monitoring, record keeping or reporting requirements are necessary to ensure ongoing compliance with OAC rule 3745-18-06(A).
- j. The inside body coating is the only coating sprayed and therefore is the only coating producing particulate emissions.

c) Operational Restrictions

- (1) The permittee shall burn only natural gas as fuel in these emissions units.
- (2) Coating and clean-up material usage shall not exceed the following levels based upon a rolling, 12-month summation of the usage rates:
  - Inside spray: 165,812 gallons per rolling 12-month period;
  - Over varnish: 64,088 gallons per rolling 12-month period;
  - Bottom varnish: 3,671 gallons per rolling 12-month period;
  - Inks: 6,404 gallons per rolling 12-month period; and
  - Clean-up solvent: 360 gallons per rolling 12-month period.
- (3) The individual HAP and total HAP, combined, emission rates for all emissions units at the facility shall not exceed 9.9 and 24.9 tons per year, respectively, based upon a rolling, 12-month summation of emission rates.

After the first 12 calendar months of operation following the issuance of this permit, compliance with the individual HAP and total HAP, combined, emission limitations for all



emissions units at the facility shall be based upon a rolling, 12-month summation of the monthly usage emission figures.

- (4) The permittee shall not operate the body making equipment when the oil mist collection system is not in operation.

d) Monitoring and/or Recordkeeping Requirements

- (1) For each day during which the permittee burns a fuel other than natural gas, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.

- (2) The permittee shall maintain daily records that document any time periods when the oil mist collection system was not in service when the body making equipment was in operation.

- (3) The permittee shall collect and record the following information each month for the line:

a. For the coatings:

- i. the name and identification number of each coating (i.e., over varnish, bottom varnish or inside spray coating), as applied,
- ii. the total volume of each coating for the month, in gallons;
- iii. the VOC content of each coating, in pounds of VOC per gallon of coating,
- iv. the VOC content of each coating, in pounds of VOC per gallon of coating excluding water and exempt solvents,
- v. the VOC content of each coating, in pounds of VOC per gallon of solids, as applied,
- vi. the monthly total VOC emissions from all coatings employed (excluding interior spray coating),  $(ii) \times (v) \div 2000$ , in tons;
- vii. the monthly total VOC emissions from interior spray coating,  $[(ii) \times (iii) \times (1-TCE)] \div 2000$ , in tons; (TCE = overall percentage total control efficiency of the RTO, as determined during the most recent emissions test that demonstrated compliance. Prior to the initial compliance test of the RTO, the permittee shall use the estimated overall percentage total control based on testing of a similar source  $((72\%)(95\%))=0.684$ );

b. For the inks:

- i. the name and identification number of each ink, as applied,
- ii. the volume (and mass) of each ink, in gallons (and pounds),
- iii. the VOC content of each ink, in pounds of VOC per gallon (or pound) of ink,



- iv. the VOC content of each ink, in pounds of VOC per gallon of coating excluding water and exempt solvents,
    - v. the monthly total VOC emissions from all inks employed, calculated on a volume (or mass) basis,  $(ii) \times (iii) \div 2000$ , in tons;
  - c. For the clean-up materials:
    - i. the name and identification number of each clean-up material employed,
    - ii. the volume of each clean-up material employed, in gallons,
    - iii. the VOC content of each clean-up material employed, in pounds of VOC per gallon,
    - iv. the monthly total VOC emissions from all clean-up materials employed,  $(ii) \times (iii) \div 2000$ , in tons;
  - d. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation of VOC emissions from all coatings, inks and clean-up materials employed, in tons.
  - e. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation, of each type of coating employed in gallons.
  - f. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation, of all the types of ink employed in gallons.
  - g. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation, of each type of clean-up solvent employed, in gallons.
- (4) The permittee shall install, operate, and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the thermal incinerator when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The accuracy for each thermocouple, monitor, and recorder shall be guaranteed by the manufacturer to be within  $\pm 0.75$  percent of the temperature being measured or  $\pm 4.5$  degrees Fahrenheit ( $\pm 2.5$  degrees Celcius), whichever is greater. The temperature monitor and recorder shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and the operating manuals, with any modifications deemed necessary by the permittee. The permittee shall collect and calculate the average combustion temperature within the thermal incinerator, each of the eight, 3-hour blocks of time during each day of operation, and shall record and maintain the following information each day:
  - a. all 3-hour blocks of time, when the emissions unit was in operation, during which the average combustion temperature within the thermal incinerator was more than 50 degrees Fahrenheit below the average temperature maintained during the most recent emissions test (1616° F based on the emissions test performed



- on 7/8/08 for EU # K010 and K011) that demonstrated the emissions unit to be in compliance;
- b. a log or record of the operating time for the capture (collection) system, thermal incinerator, monitoring equipment, and the associated emissions unit;
  - c. whenever the monitored value for the combustion temperature deviates from the range specified above, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation: the date(s) the investigation was conducted, the names of the personnel who conducted the investigation, and the findings and recommendations; and
  - d. in response to each required investigation to determine the cause of the deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable combustion temperature specified above, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken: a description of the corrective action, the date it was completed, the date and time of the deviation, the total period of time during which there was a deviation, the combustion temperature immediately after the corrective action, and the names of the personnel who performed the work. Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.
- (5) The permittee shall collect and record the following information each month for the line:
- a. the name and identification number of each coating, and each cleanup material employed;
  - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
  - c. the total HAP content of each coating, and cleanup material, in pounds per gallon;
  - d. the individual HAP content of each coating, and cleanup material, in pounds per gallon;
  - e. the number of gallons of each coating, and cleanup material employed;
  - f. the total VOC emissions (VOC applied) from all coatings, and cleanup materials employed [the sum of (5)b. times (5)e. divided by 2000 lbs/ton) for all coatings and cleanup materials], in tons;
  - g. the total HAP emissions (HAP applied) from all coatings and cleanup materials employed, in tons;
  - h. the individual HAP emissions (HAP applied) from all coatings and cleanup materials employed, in tons



- i. the rolling, 12-month summation of total HAP emissions, in tons, and
  - j. the rolling, 12-month summation of individual HAP emissions, in tons.
- (6) The permittee shall maintain records of the facility's potential to emit for each individual hazardous air pollutant and the total of all hazardous air pollutants combined by maintaining a formal up-to-date HAP emissions inventory from all HAP emissions units at the facility. The permittee shall maintain a record including methods, procedures, and assumptions supporting the calculations.
- (7) The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack and for any visible emissions of fugitive dust from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
- a. the location and color of the emissions;
  - b. whether the emissions are representative of normal operations;
  - c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;
  - d. the total duration of any visible emission incident; and
  - e. any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item (d) above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

e) Reporting Requirements

- (1) The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than natural gas was burned in this emissions unit as fuel. Each report shall be submitted within 30 days after the deviation occurs to the Toledo Division of Environmental Services.
- (2) The permittee shall notify the Toledo Division of Environmental Services in writing of any daily record showing that the oil mist collector was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.



- (3) The permittee shall notify the Toledo Division of Environmental Services in writing of any monthly record showing the use of non-complying coatings, inks, or clean-up solvent. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.
- (4) The permittee shall submit quarterly deviation (excursion) reports that identify:
  - a. all exceedances of the rolling, 12-month usage rate limitations for coatings, inks and clean-up materials specified under c)(2);
  - b. all exceedances of the rolling, 12-month emission limitation for VOC;
  - c. all exceedances of the rolling, 12-month emission limitations for individual HAP or any combination of HAPs;
  - d. identify all days during which any visible particulate emissions were observed from any stack serving this emissions unit and describe any corrective actions taken to eliminate the visible particulate emissions. If no visible emissions observed, then state no visible emissions occurred during that period.

These reports shall be submitted by January 31, April 30, July 31, and October 31 of each year to the Toledo Division of Environmental Services and shall address the data obtained during the previous calendar period. If no deviations (excursions) have occurred, the permittee shall submit a quarterly report which states that no deviations (excursions) have occurred during the previous quarter.

- (5) The permittee shall submit quarterly reports that identify the following information concerning the operation of the RTO during the operation of the emissions unit:
  - a. each period of time when the combustion temperature was outside the acceptable range;
  - b. an identification of each incident of deviation described in (11)a. where a prompt investigation was not conducted;
  - c. an identification of each incident of deviation described in (11)a. where prompt corrective action, that would bring the temperature into compliance with the acceptable range, was determined to be necessary and was not taken; and
  - d. an identification of each incident of deviation described in (11)a. where proper records were not maintained for the investigation and/or the corrective action.
- f) Testing Requirements
  - (1) Compliance with b)(1) and (b)(2) of these terms and conditions shall be determined in accordance with the following methods:
    - a. Emission Limitation:

Emissions from all emissions units at the facility shall not exceed 9.9 tons per year for any single HAP and 24.9 tons per year for any combination of HAPs.



Applicable Compliance Method:

The monitoring and record keeping requirement of c) will be used to demonstrate compliance.

b. Emission Limitation:

72.80 tons of VOC per rolling, 12-month period for line 3.

Applicable Compliance Method:

Compliance with this emissions limitation shall be demonstrated as the summation of the VOC emissions for the combustion of natural gas and the VOC emissions from all coatings, inks and clean-up materials. Compliance with this emission limitation will be demonstrated by the monitoring and record keeping requirements of c).

c. Emission Limitation:

22.52 pounds per hour of VOC.

Applicable Compliance Method:

A one-time calculation of the hourly potential to emit, based upon the worst case operating scenario, shall be used to demonstrate compliance with this limitation.

This emissions limitation shall be demonstrated as the summation of the VOC emissions for the combustion of natural gas and the VOC emissions from all coatings and clean-up materials with the inside spray operation controlled by the RTO:

Sum of [Gallons of coating applied per hour\*weight % of solvent\*density of coating\*(1-CE)] + sum of [(fuel usage rating\*5.5 lb/mmscf\*(1-CE))/1020 mmBtu/mmscf] CE=0 for all coatings, inks, and other materials except inside spray and inside spray oven.

CE = overall percentage control efficiency of the RTO, as determined during the most recent emissions test that demonstrated compliance. Prior to the initial compliance test of the RTO, the permittee shall use the estimated overall percentage control based on testing of a similar source ((72%)(95%))=0.684.

d. Emission Limitation:

VE shall not exceed 20% opacity of visible PE, as a 6-minute average.

Applicable Compliance Method:

If required, compliance shall be demonstrated through visible emissions readings taken in accordance with Method 9 of 40 CFR Part 60, Appendix A.

e. Emission Limitation:

0.551 pound per hour PE



Applicable Compliance Method:

Compliance for the body making process shall be demonstrated by multiplying the maximum coolant usage (1.25 gal/hr) by the coolant density (8.55 lb coating/gal coating), the solid concentration (0.55 lb PE/lb coating) and the estimated oil mist collector efficiency (1-0.95).

To this amount will be added the inside spray particulate emissions, whose compliance shall be demonstrated by multiplying the maximum coating usage (26.08 gal/hr) by the coating density (8.43 lb coating/gal coating), the solid concentration (0.211 lb PE/lb coating) and the transfer efficiency multiplied by the control efficiency  $((1-0.94)(1-0.090)=0.006)$ .

If required, the permittee shall demonstrate compliance using Methods 1 thru 5 of 40 CFR part 60, Appendix A. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

f. Emission Limitation:

CO emissions shall be less than 10 tons per year from Line 3.

Applicable Compliance Method

Compliance shall be demonstrated by multiplying the maximum burner capacity (1.925 mmBtu/hr + 2.75 mmBtu/hr + 5.20 mmBtu/hr = 9.875 mmBtu/hr) by an emission factor of 84 pounds of CO per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98. The resulting value shall be multiplied by 8760 hours per year and divided by 2000 pounds per ton.

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Methods 1 thru 4 and 10 of 40 CFR Part 60 Appendix A. Alternative U.S. EPA approved test methods may be used with prior approval from Ohio EPA.

g. Emission Limitation:

NOx emissions shall be less than 10 tons per year from Line 3.

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner capacity (1.925 mmBtu/hr + 2.75 mmBtu/hr + 5.20 mmBtu/hr = 9.875 mmBtu/hr) by an emission factor of 100 pounds of NOx per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98. The resulting value shall be multiplied by 8760 hours per year and divided by 2000 pounds per ton.



If required, the permittee shall demonstrate compliance using Methods 1 through 4 and 7E of 40 CFR Part 60, Appendix A. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

h. Emission Limitation:

PE shall be less than 10 tons per year from Line 3.

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner capacity (1.925 mmBtu/hr + 2.75 mmBtu/hr + 5.20 mmBtu/hr = 9.875 mmBtu/hr) by an emission factor of 1.9 pounds of PE per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98. The resulting value shall be multiplied by 8760 hours per year and divided by 2000 pounds per ton.

To this amount shall be added the emissions from the body making process. Annual allowable emissions are based on the hourly allowable emission rate (0.55 pound per hour) multiplied by the maximum annual operating hours (8760 hours per year), divided by 2000 pounds/ton.

Also, to this amount shall be added the emissions from the inside spray operation. Annual allowable emissions are based on the hourly allowable emission rate (0.55 pound per hour) multiplied by the maximum annual operating hours (8760 hours per year), divided by 2000 pounds/ton.

If required, the permittee shall demonstrate compliance using Method 5 of 40 CFR part 60, Appendix A. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

i. Emission Limitation:

PM<sub>10</sub> shall be less than 10 tons per year from Line 3.

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner capacity (1.925 mmBtu/hr + 2.75 mmBtu/hr + 5.20 mmBtu/hr = 9.875 mmBtu/hr) by an emission factor of 7.6 pounds of PM<sub>10</sub> per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98. The resulting value shall be multiplied by 8760 hours per year and divided by 2000 pounds per ton.

To this amount shall be added the emissions from the body making process. Emissions shall be calculated by multiplying the maximum coolant usage (1.25 gal/hr) by the coolant density (8.55 lb coating/gal coating), the solid concentration (0.55 lb PM10/lb coating) and the estimated oil mist collector efficiency (1-0.95). The resulting value shall be multiplied by 8760 hours per year and divided by 2000 pounds per ton.



If required, the permittee shall demonstrate compliance with this emission limitation in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

j. Emission Limitation:

SO<sub>2</sub> emissions shall be less than 10 tons per year from Line 3.

Applicable Compliance Method

Compliance shall be demonstrated by multiplying the maximum burner capacity (1.925 mmBtu/hr + 2.75 mmBtu/hr + 5.20 mmBtu/hr = 9.875 mmBtu/hr) by an emission factor of 0.6 pound of SO<sub>2</sub> per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98. The resulting value shall be multiplied by 8760 hours per year and divided by 2000 pounds per ton.

If required, the permittee shall demonstrate compliance using Methods 1 through 4 and 6 of 40 CFR part 60, Appendix A. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

k. Emission limitation:

inks: 1.81 pounds of VOC per gallon of coating excluding water and exempt solvents

Applicable Compliance Method:

Compliance shall be determined through the monitoring and record keeping requirements of d). If required, compliance shall be demonstrated by an evaluation performed in accordance with OAC rule(s) 3745-21-09(B)(3)(f) and 3745-21-10(B) using the methods and procedures specified in US EPA Reference Method 24 of 40 CFR Part 60, Appendix A.

Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the US EPA and shall use formulation data for that coating to demonstrate compliance until the US EPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

l. Emission limitation:

over varnish: 2.1 pounds of VOC per gallon of coating, excluding water and exempt solvents

Applicable Compliance Method:

Compliance shall be determined through the monitoring and record keeping requirements d). If required, compliance shall be demonstrated by an evaluation



performed in accordance with OAC rule(s) 3745-21-09(B)(3)(f) and 3745-21-10(B) using the methods and procedures specified in US EPA Reference Method 24 of 40 CFR Part 60, Appendix A.

Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the US EPA and shall use formulation data for that coating to demonstrate compliance until the US EPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

m. Emission limitation:

over varnish: 2.9 pounds of VOC per gallon of coating solids

Applicable Compliance Method:

Compliance shall be determined through the monitoring and record keeping requirements of d). If required, compliance shall be demonstrated by an evaluation performed in accordance with OAC rule 3745-21-10(B) and 40 CFR 60.496 using the methods and procedures specified in US EPA Reference Method 24 of 40 CFR Part 60, Appendix A.

Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the US EPA and shall use formulation data for that coating to demonstrate compliance until the US EPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

n. Emission limitation:

bottom varnish (exterior bottom end coating): 2.1 pounds of VOC per gallon of coating excluding water and exempt solvents

Applicable Compliance Method:

Compliance shall be determined through the monitoring and record keeping requirements of d). If required, compliance shall be demonstrated by an evaluation performed in accordance with OAC rule(s) 3745-21-09(B)(3)(f) and 3745-21-10(B) using the methods and procedures specified in US EPA Reference Method 24 of 40 CFR Part 60, Appendix A.

Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the US EPA and shall use formulation data for that coating to demonstrate compliance until the US EPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.



o. Emission limitation:

bottom varnish (exterior bottom end coating): 2.9 pounds of VOC per gallon of coating solids.

Applicable Compliance Method:

Compliance shall be determined through the monitoring and record keeping requirements of d). If required, compliance shall be demonstrated by an evaluation performed in accordance with OAC rule 3745-21-10(B) and 40 CFR 60.496 using the methods and procedures specified in US EPA Reference Method 24 of 40 CFR Part 60, Appendix A.

Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the US EPA and shall use formulation data for that coating to demonstrate compliance until the US EPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

p. Emission limitation:

clean-up solvent: 6.55 pounds of VOC per gallon.

Applicable Compliance Method:

The permittee shall determine the VOC-content of the clean-up solvent from manufacturer's formulation data.

q. Emission limitation:

inside spray: 3.5 pounds of VOC per gallon of coating excluding water and exempt solvents

Applicable Compliance Method:

Compliance shall be determined through the monitoring and record keeping requirements of d). If required, compliance shall be demonstrated by an evaluation performed in accordance with OAC rule(s) 3745-21-09(B)(3)(f) and 3745-21-10(B) using the methods and procedures specified in US EPA Reference Method 24 of 40 CFR Part 60, Appendix A.

Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the US EPA and shall use formulation data for that coating to demonstrate compliance until the US EPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.



r. Emission limitation:

inside spray: 6.8 pounds of VOC per gallon of coating solids

Applicable Compliance Method:

Compliance shall be determined through the monitoring and record keeping requirements of d). If required, compliance shall be demonstrated by an evaluation performed in accordance with 3745-21-10(B) and 40 CFR 60.496 using the methods and procedures specified in US EPA Reference Method 24 of 40 CFR Part 60, Appendix A.

Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the US EPA and shall use formulation data for that coating to demonstrate compliance until the US EPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

g) Miscellaneous Requirements

- (1) The terms and conditions contained in this permit to install for emissions unit K011 shall supercede all requirements for emissions unit K011 contained in Permit to Install 04-01429 (issued 10/19/2006) and PTI 04-01465 (issued 5/22/07).