



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL  
FAIRFIELD COUNTY**

**CERTIFIED MAIL**

Street Address:

50 West Town Street, Suite 700

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center  
P.O. Box 1049

**Application No: 01-12091**

**Fac ID: 0123000234**

**DATE: 6/26/2007**

Westerman Companies

Barry Keller

Post Office Box 125 245 N Broad St

Bremen, OH 43107

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action of the Director is final and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. The appeal must be filed with the Commission within thirty (30) days after notice of the Director's action. The appeal must be accompanied by a filing fee of \$70.00 which the Commission, in its discretion, may reduce if by affidavit you demonstrate that payment of the full amount of the fee would cause extreme hardship. Notice of the filing of the appeal shall be filed with the Director within three (3) days of filing with the Commission. Ohio EPA requests that a copy of the appeal be served upon the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission  
309 South Fourth Street, Room 222  
Columbus, OH 43215

Sincerely,

Michael W. Ahern, Manager

Permit Issuance and Data Management Section

Division of Air Pollution Control

CC: USEPA

CDO



---

**Permit To Install  
Terms and Conditions**

**Issue Date: 6/26/2007  
Effective Date: 6/26/2007**

---

**FINAL PERMIT TO INSTALL 01-12091**

Application Number: 01-12091  
Facility ID: 0123000234  
Permit Fee: **\$400**  
Name of Facility: Westerman Companies  
Person to Contact: Barry Keller  
Address: Post Office Box 125 245 N Broad St  
Bremen, OH 43107

Location of proposed air contaminant source(s) [emissions unit(s)]:  
**245 N Broad St  
Bremen, Ohio**

Description of proposed emissions unit(s):  
**Drowndraft spray paint booth, Building 18.**

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

---

Chris Korleski  
Director

## Part I - GENERAL TERMS AND CONDITIONS

### A. Permit to Install General Terms and Conditions

#### 1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

#### 2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted (i.e., postmarked) quarterly by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

#### 3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

#### 4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon

the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

**5. Scheduled Maintenance/Malfunction Reporting**

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

**6. Permit Transfers**

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

**7. Air Pollution Nuisance**

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

**8. Termination of Permit to Install**

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

**9. Construction of New Sources(s)**

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

#### **10. Public Disclosure**

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

#### **11. Applicability**

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

#### **12. Best Available Technology**

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

Westerman Companies  
 PTI Application: 01-12091  
 Issued: 6/26/2007

Facility ID: 0123000234

**13. Source Operation and Operating Permit Requirements After Completion of Construction**

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

**14. Construction Compliance Certification**

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

**15. Fees**

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

**B. Permit to Install Summary of Allowable Emissions**

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)	
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS	
<u>Pollutant</u>	<u>Tons Per Year</u>
VOC	82.3
PE	17.5
Combined HAPs	24.9
Individual HAP	9.9

7

**Westerman Companies**  
**PTI Application: 01-12091**  
**Issued: 6/26/2007**

**Facility ID: 0123000234**

Issued: 6/26/2007

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)****A. Applicable Emissions Limitations and/or Control Requirements**

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

**Operations, Property, and/or Equipment - (K009) - Building No. 17 - Shop Floor Painting. The terms of this permit supercede those identified in PTI No. 01-08944 issued August 9, 2005.**

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(A)(3)	<p>Emissions shall not exceed:</p> <p>16.0 lbs/hr of VOC from coating operations. See Section B.2 below.</p> <p>22.0 lbs/hr of VOC from cleanup operations. See Section B.4 below.</p> <p>Particulate emissions (PE) shall not exceed 0.13 lb/hr and 0.6 ton per year from coating operations.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rules 3745-35-07(B), 3745-31-05(C) and 3745-21-09(U)(2)(e)(iii).</p> <p>See Section A.2.a below.</p>
<p>OAC rule 3745-31-05(C) (synthetic minor to avoid NSR)</p> <p>OAC rule 3745-35-07(B) (synthetic minor to avoid Title V)</p>	<p>Emissions shall not exceed, as a 12-month rolling summation:</p> <p>3.2 tons of VOC from coating material usage.</p> <p>See Section B.1 below.</p> <p>VOC emissions from cleanup material usage in emissions units K009, K010, K011, K012, K013, K014, and K015 combined shall not exceed 5.88 tons per rolling, 12-month summation.</p> <p>See Section B.3 below.</p>

**Issued: 6/26/2007**

OAC rule 3745-35-07(B) (synthetic minor to avoid Title V)	The combined total hazardous air pollutants (HAP) emissions shall not exceed 9.9 tons per rolling 12-month period for any single HAP and 24.9 tons per rolling 12-month period for all HAPs from all coating and cleanup materials used in units K009, K010, K011, K012, K013, K014, and K015 combined.
OAC rule 3745-17-07(A)(1)	Visible PE from any stack serving this emissions unit shall not exceed 20 % opacity, as a six-minute average, except as specified by rule.
OAC rule 3745-17-11(A)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to the requirement specified in OAC rule 3745-31-05(A)(3).
OAC rule 3745-21-09(U)(2)(e)(iii)	This emissions unit shall not employ more than 10 gallons of coating on metal parts in any given day.

## 2. Additional Terms and Conditions

- 2.a** The hourly VOC emission limitation and the hourly and annual PE emission limitations were established to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to develop monitoring, record keeping and/or reporting requirements to ensure compliance with these limits.

## B. Operational Restrictions

1. The maximum annual coating usage for K009 shall not exceed 1600 gallons applied based upon a rolling, 12-month summation of the coating usage figures.

To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed the coating usage levels specified in the following table:

<u>Month(s)</u>	<u>Maximum Allowable Cumulative Coating Usage</u>
1	134
1-2	268
1-3	402
1-4	536
1-5	670
1-6	804
1-7	938

Emissions Unit ID: K009

1-8	1072
1-9	1206
1-10	1340
1-11	1474
1-12	1600

After the first 12 calendar months of operation following the issuance of this permit, compliance with the annual coating usage limitation shall be based upon a rolling, 12-month summation of the coating usage figures.

- The maximum coating content shall not exceed 4.0 lbs VOC per gallon, excluding water and exempt solvents.
- The maximum annual cleanup material usage for emission units K009, K010, K011, K012, K013, K014, and K015 combined shall not exceed 1,623 gallons, based upon a rolling, 12-month summation of the cleanup material usage.

To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed the cleanup material usage levels specified in the following table:

<u>Month(s)</u>	<u>Maximum Allowable Cumulative Cleanup Material Usage</u>
1	136
1-2	272
1-3	408
1-4	544
1-5	680
1-6	816
1-7	952
1-8	1,088
1-9	1,224
1-10	1,360
1-11	1,496
1-12	1,623

After the first 12 calendar months of operation following the issuance of this permit, compliance with the annual cleanup material usage limitation shall be based upon a rolling, 12-month summation of the cleanup material usage figures.

**Issued: 6/26/2007**

4. The maximum cleanup material content shall not exceed 7.25 lbs VOC per gallon, excluding water and exempt solvents.
5. The permittee shall operate the dry filtration system whenever this emissions unit is in operation, to control particulate emissions.

Issued: 6/26/2007

**C. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information each day for emissions unit K009:
  - a. the name and identification number of each coating applied;
  - b. the volume, in gallons, of each coating applied; and
  - c. the total volume, in gallons, of all of the coatings applied.
  
2. The permittee shall collect and record the following information each month for emissions unit K009:
  - a. the name and identification of each coating material, as applied;
  - b. the VOC content for each coating material in pounds of VOC per gallon of coating material, excluding water and exempt solvents, as applied;
  - c. the number of gallons applied, of each coating material, excluding water and exempt solvents, as applied;
  - d. the rolling, 12-month summation of the coating usage, in gallons, excluding water and exempt solvents;
  - e. the total VOC emissions rate for all coating materials, in pounds per month (b x c); and
  - f. the total VOC emissions rate for all coating materials, in pounds per rolling, 12-month summation (b x d).
  
3. The permittee shall collect and record the following information each month for emissions units K009, K010, K011, K012, K013, K014, and K015:
  - a. the name and identification of each cleanup material, as applied;
  - b. the VOC content for each cleanup material in pounds of VOC per gallon of cleanup material, excluding water and exempt solvents, as applied;
  - c. the number of gallons applied, of each cleanup material, excluding water and

**Issued: 6/26/2007**

- exempt solvents, as applied;
  - d. the rolling, 12-month summation of the cleanup material usage, in gallons, excluding water and exempt solvents;
  - e. the total VOC emission rate for all cleanup materials, in pounds per month (b x c); and
  - f. the total VOC emissions rate for all cleanup materials, in pounds per rolling, 12-month rolling summation for K009, K010, K011, K012, K013, K014, and K015 combined.
4. The permittee shall collect and record the following information each month for emissions units K009, K010, K011, K012, K013, K014, and K015:
- a. the name and identification number of each coating, as applied;
  - b. the individual HAP<sup>1</sup> content for each HAP of each coating in pounds of individual HAP per gallon of coating, as applied;
  - c. the total combined HAP content for each HAP of each coating in pounds of combined HAPs per gallon of coating, as applied (sum of all individual HAP contents from b);
  - d. the number of gallons of each coating employed;
  - e. the name and identification of each cleanup material employed;
  - f. the individual HAP content for each HAP of each cleanup material in pounds of individual HAP per gallon cleanup material, as applied;
  - g. the total combined HAP content of each cleanup material in pounds of combined HAPs per gallon of cleanup material, as applied (sum of all individual HAP contents from f);
  - h. the number of gallons of each cleanup material employed;
  - i. the total individual HAP emissions for each HAP from all coating and cleanup material in pounds or tons per rolling, 12-month period (for each HAP the sum of b times d for each coating and the sum of f times h for each cleanup material);

Emissions Unit ID: **K009**

- j. the total combined HAPs emissions from all coating and cleanup materials employed, in pounds or tons per month and pounds or tons per rolling, 12-month period (the sum of c times d for each coating plus the sum of g times h for each cleanup material);
- k. the updated rolling, 12-month summation of emissions for each individual HAP in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and
- l. the updated rolling, 12-month summation of emissions for total combined HAPs in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

<sup>1</sup> A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA field office or local air agency contact. Material Safety Data Sheets typically include a listing of the solvents contained in the coatings or clean materials. This information does not have to be kept on a line-by-line basis.

- 5. The permit to install for this emissions unit (K009) was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the ISCST3 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the ISCST3 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: xylene

TLV (mg/m<sup>3</sup>): 434.19

Maximum Hourly Emission Rate (g/s): 2.04

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m<sup>3</sup>): 507.8

MAGLC (ug/m<sup>3</sup>): 10,337.91

Pollutant: toluene

TLV (mg/m<sup>3</sup>): 188.40

Maximum Hourly Emission Rate (g/s): 2.04

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m<sup>3</sup>): 507.8

MAGLC (ug/m<sup>3</sup>): 4,485.83

**Issued: 6/26/2007**

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

Emissions Unit ID: **K009**

- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

#### **D. Reporting Requirements**

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.
2. The permittee shall notify Ohio EPA, Central District Office in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to Ohio EPA, Central District Office within 45 days after the exceedance occurs.
3. The permittee shall submit quarterly deviation (excursion) reports which identify all exceedances of the following:
  - a. the VOC content limit for coating materials;
  - b. the VOC content limit for cleanup materials;
  - c. the rolling, 12-month coating usage limitation for K009;
  - d. the rolling, 12-month VOC emission limitation for K009;
  - e. the rolling, 12-month cleanup usage limitation for K009, K010, K011, K012, K013, K014, and K015 combined;
  - f. the rolling, 12-month VOC emission limitation, from cleanup material, for K009, K010, K011, K012, K013, K014, and K015 combined;
  - g. the rolling, 12-month total individual HAP emission limitation for K009, K010, K011, K012, K013, K014, and K015 combined; and
  - h. the rolling, 12-month total combined HAPs emissions limitation for K009, K010, K011, K012, K013, K014, and K015 combined.
4. These quarterly deviation (excursion) reports shall be submitted to the Ohio EPA Central District Office by January 31, April 30, July 31 and October 31 of each year and shall cover the previous calendar quarter. If no deviations occurred during a calendar quarter, the permittee shall submit a report which states that no deviations occurred

**Issued: 6/26/2007**

during the calendar quarter.

5. The permittee shall submit annual reports which specify the VOC and individual and combined HAP emissions from this emissions unit for the previous calendar year. The reports shall be submitted by April 15 of each year. This reporting requirement may be satisfied by including and identifying the specific emission data from this emissions unit in the annual Fee Emission Report.

## **E. Testing Requirements**

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following methods:
  - a. Emissions Limitation:  
16.0 lbs/hr of VOC from coating operations.  
  
Applicable Compliance Method:  
Compliance has been demonstrated by multiplying the maximum hourly coating usage rate of 4.0 gallons/hour by the maximum VOC content of 4.0 lbs/gallon.
  - b. Emissions Limitation:  
22.0 lbs/hr of VOC from cleanup operations.  
  
Applicable Compliance Method:  
Compliance has been demonstrated by multiplying the maximum hourly cleanup usage rate of 3.0 gallons/hour by the maximum VOC content of 7.25 lbs/gallon.
  - c. Emission Limitation:  
VOC emissions from coatings shall not exceed 3.2 tons, as a 12-month rolling summation.  
  
Applicable Compliance Method:  
Compliance shall be based upon the record keeping requirements as specified in Section C.2.
  - d. Emissions Limitation:  
4.0 pounds of VOC per gallon of coating, excluding water and exempt solvents.  
  
Applicable Compliance Method:  
Compliance with the VOC content of the coatings applied in this emissions unit

Emissions Unit ID: **K009**

shall be determined through monthly record keeping, as specified in Sections C.2. Formulation data from the coating manufacturer and/or, if required, USEPA Method 24 (or an alternative approved method) shall be used to determine the volatile organic compound content of the coatings, to be used in the calculation of emissions.

- e. Emissions Limitation:  
7.25 pounds of VOC per gallon of cleanup material, excluding water and exempt solvents.

Applicable Compliance Method:

Compliance with the VOC content of the cleanup material applied in this emissions unit shall be determined through monthly record keeping, as specified in Sections C.3. Formulation data from the cleanup material manufacturer and/or, if required, USEPA Method 24 (or an alternative approved method) shall be used to determine the volatile organic compound content of the cleanup materials, to be used in the calculation of emissions.

- f. Emission Limitation:  
PE shall not exceed 0.13 lb/hr.

Applicable Compliance Method:

To determine the annual worst case emissions for particulate matter, the following equation shall be used:

$$E = CS_a (\text{pounds per hour}) \times (1 - TE) \times (1 - CE).$$

$$CS_a = \text{maximum coating solids usage rate is calculated by multiplying the paint density (lbs/gal), by the solids percent by weight and by the maximum hourly gallon used..}$$

$$TE = \text{transfer efficiency, which is the ratio of the amount of coatings solids deposited on the coated part to the amount of coating solids used (75% for air spray gun).}$$

$$CE = \text{control efficiency of the control equipment (95% for panel filters).}$$

Note: The values cited for M, TE, and CE are based on manufacturer's data.

- g. Emission Limitation:  
PE shall not exceed 0.6 ton per year.

**Issued: 6/26/2007**

Applicable Compliance Method:

The annual emission limitation was established by multiplying the hourly limitation by 8,760 hours/year and then dividing by 2,000 pounds/ton. Compliance with the annual emission limitation may be assumed as long as compliance with the hourly emission limitation is maintained.

h. Emission Limitation:

VOC emissions from cleanup materials applied in emissions units K009, K010, K011, K012, K013, K014, and K015 combined shall not exceed 5.88 tons per rolling 12-month summation.

Applicable Compliance Method:

Compliance with the rolling 12-month limitation shall be established by the record keeping found in Section C.3.

i. Emission Limitation:

The individual HAP emissions shall not exceed 9.9 tons per rolling 12-month period for all single HAP from all coatings and cleanup materials used in units K009, K010, K011, K012, K013, K014, and K015 combined.

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements specified in Section C.4 of this permit.

j. Emission Limitation:

The combined total HAPs emissions shall not exceed 24.9 tons per rolling 12-month period for all HAP from all coatings and cleanup materials used in units K009, K010, K011, K012, K013, K014, and K015 combined.

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements specified in Section C.4 of this permit.

**Issued: 6/26/2007**

**F. Miscellaneous Requirements**

None

Issued: 6/26/2007

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)****A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

**Operations, Property, and/or Equipment - (K010) - Building No. 11 - Shop Floor Painting. The terms of this permit supercede those identified in PTI No. 01-08944 issued August 9, 2005.**

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(A)(3)	<p>Emissions shall not exceed:</p> <p>16.0 lbs/hr of VOC from coating operations. See Section B.2 below.</p> <p>22.0 lbs/hr of VOC from cleanup operations. See Section B.4 below.</p> <p>Particulate emissions (PE) shall not exceed 0.13 lb/hr and 0.6 tons per year from coating operations.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rules 3745-35-07(B), 3745-31-05(C) and 3745-21-09(U)(2)(e)(iii).</p> <p>See Section A.2.a below.</p>
<p>OAC rule 3745-31-05(C) (synthetic minor to avoid NSR)</p> <p>OAC rule 3745-35-07(B) (synthetic minor to avoid Title V)</p>	<p>Emissions shall not exceed, as a 12-month rolling summation:</p> <p>3.2 tons of VOC from coating material usage.</p> <p>See Section B.1 below.</p> <p>VOC emissions from cleanup material usage in emissions units K009, K010, K011, K012, K013, K014, and K015 combined shall not exceed 5.88 tons per rolling, 12-month summation.</p> <p>See Section B.3 below.</p>

Emissions Unit ID: **K010**

OAC rule 3745-35-07(B) (synthetic minor to avoid Title V)	The combined total hazardous air pollutants (HAP) emissions shall not exceed 9.9 tons per rolling 12-month period for any single HAP and 24.9 tons per rolling 12-month period for all HAPs from all coating and cleanup materials used in units K009, K010, K011, K012, K013, K014, and K015 combined.
OAC rule 3745-17-07(A)(1)	Visible PE from any stack serving this emissions unit shall not exceed 20 % opacity, as a six-minute average, except as specified by rule.
OAC rule 3745-17-11(A)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to the requirement specified in OAC rule 3745-31-05(A)(3).
OAC rule 3745-21-09(U)(2)(e)(iii)	This emissions unit shall not employ more than 10 gallons of coating on metal parts in any given day.

## 2. Additional Terms and Conditions

- 2.a** The hourly VOC emission limitation and the hourly and annual PE emission limitations were established to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to develop monitoring, record keeping and/or reporting requirements to ensure compliance with these limits.

## B. Operational Restrictions

1. The maximum annual coating usage for K010 shall not exceed 1600 gallons applied based upon a rolling, 12-month summation of the coating usage figures.

To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed the coating usage levels specified in the following table:

<u>Month(s)</u>	<u>Maximum Allowable Cumulative Coating Usage</u>
1	134
1-2	268
1-3	402
1-4	536
1-5	670
1-6	804
1-7	938
1-8	1072

**Issued: 6/26/2007**

1-9	1206
1-10	1340
1-11	1474
1-12	1600

After the first 12 calendar months of operation following the issuance of this permit, compliance with the annual coating usage limitation shall be based upon a rolling, 12-month summation of the coating usage figures.

2. The maximum coating content shall not exceed 4.0 lbs VOC per gallon, excluding water and exempt solvents.
3. The maximum annual cleanup material usage for emission units K009, K010, K011, K012, K013, K014, and K015 combined shall not exceed 1,623 gallons, based upon a rolling, 12-month summation of the cleanup material usage.

To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed the cleanup material usage levels specified in the following table:

<u>Month(s)</u>	<u>Maximum Allowable Cumulative Coating Usage</u>
1	136
1-2	272
1-3	408
1-4	544
1-5	680
1-6	816
1-7	952
1-8	1,088
1-9	1,224
1-10	1,360
1-11	1,496
1-12	1,623

After the first 12 calendar months of operation following the issuance of this permit, compliance with the annual cleanup material usage limitation shall be based upon a rolling, 12-month summation of the cleanup material usage figures.

**Westerman Companies**

**DTI Application: 01-12001**

**Facility ID: 0123000234**

**Emissions Unit ID: K010**

4. The maximum cleanup material content shall not exceed 7.25 lbs VOC per gallon, excluding water and exempt solvents.
5. The permittee shall operate the dry filtration system whenever this emissions unit is in operation, to control particulate emissions.

Issued: 6/26/2007

**C. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information each day for emissions unit K010:
  - a. the name and identification number of each coating applied;
  - b. the volume, in gallons, of each coating applied; and
  - c. the total volume, in gallons, of all of the coatings applied.
  
2. The permittee shall collect and record the following information each month for emissions unit K010:
  - a. the name and identification of each coating material, as applied;
  - b. the VOC content for each coating material in pounds of VOC per gallon of coating material, excluding water and exempt solvents, as applied;
  - c. the number of gallons applied, of each coating material, excluding water and exempt solvents, as applied;
  - d. the rolling, 12-month summation of the coating usage, in gallons, excluding water and exempt solvents;
  - e. the total VOC emissions rate for all coating materials, in pounds per month (b x c); and
  - f. the total VOC emissions rate for all coating materials, in pounds per rolling, 12-month summation (b x d).
  
3. The permittee shall collect and record the following information each month for emissions units K009, K010, K011, K012, K013, K014, and K015:
  - a. the name and identification of each cleanup material, as applied;
  - b. the VOC content for each cleanup material in pounds of VOC per gallon of cleanup material, excluding water and exempt solvents, as applied;
  - c. the number of gallons applied, of each cleanup material, excluding water and

**Issued: 6/26/2007**

- exempt solvents, as applied;
  - d. the rolling, 12-month summation of the cleanup material usage, in gallons, excluding water and exempt solvents;
  - e. the total VOC emission rate for all cleanup materials, in pounds per month (b x c); and
  - f. the total VOC emissions rate for all cleanup materials, in pounds per rolling, 12-month rolling summation for K009, K010, K011, K012, K013, K014, and K015 combined.
4. The permittee shall collect and record the following information each month for emissions units K009, K010, K011, K012, K013, K014, and K015:
- a. the name and identification number of each coating, as applied;
  - b. the individual HAP<sup>1</sup> content for each HAP of each coating in pounds of individual HAP per gallon of coating, as applied;
  - c. the total combined HAP content for each HAP of each coating in pounds of combined HAPs per gallon of coating, as applied (sum of all individual HAP contents from b);
  - d. the number of gallons of each coating employed;
  - e. the name and identification of each cleanup material employed;
  - f. the individual HAP content for each HAP of each cleanup material in pounds of individual HAP per gallon cleanup material, as applied;
  - g. the total combined HAP content of each cleanup material in pounds of combined HAPs per gallon of cleanup material, as applied (sum of all individual HAP contents from f);
  - h. the number of gallons of each cleanup material employed;
  - i. the total individual HAP emissions for each HAP from all coating and cleanup material in pounds or tons per rolling, 12-month period (for each HAP the sum of b times d for each coating and the sum of f times h for each cleanup material);

**Issued: 6/26/2007**

- j. the total combined HAPs emissions from all coating and cleanup materials employed, in pounds or tons per month and pounds or tons per rolling, 12-month period (the sum of c times d for each coating plus the sum of g times h for each cleanup material);
- k. the updated rolling, 12-month summation of emissions for each individual HAP in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and
- l. the updated rolling, 12-month summation of emissions for total combined HAPs in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

<sup>1</sup> A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA field office or local air agency contact. Material Safety Data Sheets typically include a listing of the solvents contained in the coatings or clean materials. This information does not have to be kept on a line-by-line basis.

- 5. The permit to install for this emissions unit (K010) was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the ISCST3 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the ISCST3 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: xylene

TLV (mg/m<sup>3</sup>): 434.19

Maximum Hourly Emission Rate (g/s): 2.04

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m<sup>3</sup>): 507.8

MAGLC (ug/m<sup>3</sup>): 10,337.91

Pollutant: toluene

TLV (mg/m<sup>3</sup>): 188.40

Maximum Hourly Emission Rate (g/s): 2.04

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m<sup>3</sup>): 507.8

Emissions Unit ID: **K010**MAGLC (ug/m<sup>3</sup>):4,485.83

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

**Issued: 6/26/2007**

- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

**D. Reporting Requirements**

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.
2. The permittee shall notify Ohio EPA, Central District Office in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to Ohio EPA, Central District Office within 45 days after the exceedance occurs.
3. The permittee shall submit quarterly deviation (excursion) reports which identify all exceedances of the following:
  - a. the VOC content limit for coating materials;
  - b. the VOC content limit for cleanup materials;
  - c. the rolling, 12-month coating usage limitation for K010;
  - d. the rolling, 12-month VOC emission limitation for K010;
  - e. the rolling, 12-month cleanup usage limitation for K009, K010, K011, K012, K013, K014, and K015 combined;
  - f. the rolling, 12-month VOC emission limitation, from cleanup material, for K009, K010, K011, K012, K013, K014, and K015 combined;
  - g. the rolling, 12-month total individual HAP emission limitation for K009, K010, K011, K012, K013, K014, and K015 combined; and
  - h. the rolling, 12-month total combined HAPs emissions limitation for K009, K010, K011, K012, K013, K014, and K015 combined.
4. These quarterly deviation (excursion) reports shall be submitted to the Ohio EPA Central District Office by January 31, April 30, July 31 and October 31 of each year and shall cover the previous calendar quarter. If no deviations occurred during a calendar

Emissions Unit ID: K010

quarter, the permittee shall submit a report which states that no deviations occurred during the calendar quarter.

5. The permittee shall submit annual reports which specify the VOC and individual and combined HAP emissions from this emissions unit for the previous calendar year. The reports shall be submitted by April 15 of each year. This reporting requirement may be satisfied by including and identifying the specific emission data from this emissions unit in the annual Fee Emission Report.

## E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following methods:
  - a. Emissions Limitation:  
16.0 lbs/hr of VOC from coating operations.  
  
Applicable Compliance Method:  
Compliance has been demonstrated by multiplying the maximum hourly coating usage rate of 4.0 gallons/hour by the maximum VOC content of 4.0 lbs/gallon.
  - b. Emissions Limitation:  
22.0 lbs/hr of VOC from cleanup operations.  
  
Applicable Compliance Method:  
Compliance has been demonstrated by multiplying the maximum hourly cleanup usage rate of 3.0 gallons/hour by the maximum VOC content of 7.25 lbs/gallon.
  - c. Emission Limitation:  
VOC emissions from coatings shall not exceed 3.2 tons, as a 12-month rolling summation.  
  
Applicable Compliance Method:  
Compliance shall be based upon the record keeping requirements as specified in Section C.2.
  - d. Emissions Limitation:  
4.0 pounds of VOC per gallon of coating, excluding water and exempt solvents.  
  
Applicable Compliance Method:  
Compliance with the VOC content of the coatings applied in this emissions unit

**Issued: 6/26/2007**

shall be determined through monthly record keeping, as specified in Sections C.2. Formulation data from the coating manufacturer and/or, if required, USEPA Method 24 (or an alternative approved method) shall be used to determine the volatile organic compound content of the coatings, to be used in the calculation of emissions.

- e. Emissions Limitation:  
7.25 pounds of VOC per gallon of cleanup material, excluding water and exempt solvents.

Applicable Compliance Method:

Compliance with the VOC content of the cleanup material applied in this emissions unit shall be determined through monthly record keeping, as specified in Sections C.3. Formulation data from the cleanup material manufacturer and/or, if required, USEPA Method 24 (or an alternative approved method) shall be used to determine the volatile organic compound content of the cleanup materials, to be used in the calculation of emissions.

- f. Emissions Limitation:  
This emissions unit shall not employ more than 10 gallons of coating on metal parts in any given day.

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements as specified in Section C.1.

- g. Emission Limitation:  
PE shall not exceed 0.13 lb/hr.

Applicable Compliance Method:

To determine the annual worst case emissions for particulate matter, the following equation shall be used:

$$E = CS_a (\text{pounds per hour}) \times (1 - TE) \times (1 - CE).$$

$CS_a$  = maximum coating solids usage rate is calculated by multiplying the paint density (lbs/gal), by the solids percent by weight, and by the maximum hourly gallon used.

TE = transfer efficiency, which is the ratio of the amount of coatings

Emissions Unit ID: **K010**

solids deposited on the coated part to the amount of coating solids used (75% for air spray gun).

CE = control efficiency of the control equipment (95% for panel filters).

Note: The values cited for M, TE, and CE are based on manufacturer's data.

- h. Emission Limitation:  
 PE shall not exceed 0.6 ton per year.

Applicable Compliance Method:

The annual emission limitation was established by multiplying the hourly limitation by 8,760 hours/year and then dividing by 2,000 pounds/ton. Compliance with the annual emission limitation may be assumed as long as compliance with the hourly emission limitation is maintained.

- i. Emission Limitation:  
 VOC emissions from cleanup materials applied in emissions units K009, K010, K011, K012, K013, K014, and K015 combined shall not exceed 5.88 tons per rolling 12-month summation.

Applicable Compliance Method:

Compliance with the rolling 12-month limitation shall be established by the record keeping found in Section C.3.

- j. Emission Limitation:  
 The individual HAP emissions shall not exceed 9.9 tons per rolling 12-month period for all single HAP from all coatings and cleanup materials used in units K009, K010, K011, K012, K013, K014, and K015 combined.

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements specified in Section C.4 of this permit.

- k. Emission Limitation:  
 The combined total HAPs emissions shall not exceed 24.9 tons per rolling 12-month period for all HAP from all coatings and cleanup materials used in units K009, K010, K011, K012, K013, K014, and K015 combined.

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements specified in

**Issued: 6/26/2007**

Section C.4 of this permit.

**F. Miscellaneous Requirements**

None

Issued: 6/26/2007

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)****A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

**Operations, Property, and/or Equipment - (K011) - Building No. 11 - Primer Paint Booth. The terms of this permit supercede those identified in PTI No. 01-08944 issued August 9, 2005.**

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(A)(3)	<p>Emissions shall not exceed:</p> <p>7.0 lbs/hr of volatile organic compounds (VOC) from coating operations.</p> <p>22.0 lbs/hr of VOC from cleanup operations. See Section B.4 below.</p> <p>Particulate emissions (PE) shall not exceed 0.2 lb/hr and 0.9 ton per year from coating operations.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(C), 3745-35-07(B) and 3745-21-09(U)(1)(d).</p> <p>See Section A.2.a below.</p>
<p>OAC rule 3745-31-05(C) (synthetic minor to avoid NSR)</p> <p>OAC rule 3745-35-07(B) (synthetic minor to avoid Title V)</p>	<p>Emissions shall not exceed, as a 12-month rolling summation:</p> <p>15.7 tons of VOC from coating material usage.</p> <p>See Section B.1 below.</p> <p>VOC emissions from cleanup material usage in emissions units K009, K010, K011, K012, K013, K014, and K015 combined shall not exceed 5.88 tons per rolling, 12-month summation.</p> <p>See Section B.3 below.</p>

Emissions Unit ID: **K011**

OAC rule 3745-35-07(B) (synthetic minor to avoid Title V)	The combined total hazardous air pollutants (HAP) emissions shall not exceed 9.9 tons per rolling 12-month period for any single HAP and 24.9 tons per rolling 12-month period for all HAPs from all coating and cleanup materials used in units K009, K010, K011, K012, K013, K014, and K015 combined.
OAC rule 3745-17-07(A)(1)	Visible PE from any stack serving this emissions unit shall not exceed 20 % opacity, as a six-minute average, except as specified by rule.
OAC rule 3745-17-11(A)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to the requirement specified in OAC rule 3745-31-05(A)(3).
OAC rule 3745-21-09(U)(1)(d)	See Section B.2 below.

## 2. Additional Terms and Conditions

- 2.a** The hourly VOC emission limitation and the hourly and annual PE emission limitations were established to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to develop monitoring, record keeping and/or reporting requirements to ensure compliance with these limits.

## B. Operational Restrictions

1. The maximum annual coating usage for K011 shall not exceed 8,976 gallons applied based upon a rolling, 12-month summation of the coating usage figures.

To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed the coating usage levels specified in the following table:

<u>Month(s)</u>	<u>Maximum Allowable Cumulative Coating Usage</u>
1	748
1-2	1,496
1-3	2,244
1-4	2,992
1-5	3,740
1-6	4,488
1-7	5,234
1-8	5,982

Emissions Unit ID: **K011**

1-9	6,730
1-10	7,478
1-11	8,226
1-12	8,976

After the first 12 calendar months of operation following the issuance of this permit, compliance with the annual coating usage limitation shall be based upon a rolling, 12-month summation of the coating usage figures.

- The maximum coating content shall not exceed 3.5 lbs VOC per gallon, excluding water and exempt solvents.
- The maximum annual cleanup material usage for emission units K009, K010, K011, K012, K013, K014, and K015 combined shall not exceed 1,623 gallons, based upon a rolling, 12-month summation of the cleanup material usage.

To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed the cleanup material usage levels specified in the following table:

<u>Month(s)</u>	<u>Maximum Allowable Cumulative Cleanup Material Usage</u>
1	136
1-2	272
1-3	408
1-4	544
1-5	680
1-6	816
1-7	952
1-8	1,088
1-9	1,224
1-10	1,360
1-11	1,496
1-12	1,623

After the first 12 calendar months of operation following the issuance of this permit, compliance with the annual cleanup material usage limitation shall be based upon a rolling, 12-month summation of the cleanup material usage figures.

- The maximum cleanup content shall not exceed 7.25 lbs VOC per gallon, excluding

**Issued: 6/26/2007**

water and exempt solvents.

5. The permittee shall operate the dry filtration system whenever this emissions unit is in operation, to control particulate emissions.

Issued: 6/26/2007

**C. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information each month for emissions unit K011:
  - a. the name and identification of each coating material, as applied;
  - b. the VOC content for each coating material in pounds of VOC per gallon of coating material, excluding water and exempt solvents, as applied;
  - c. the number of gallons applied, of each coating material, excluding water and exempt solvents, as applied;
  - d. the rolling, 12-month summation of the coating usage, in gallons, excluding water and exempt solvents;
  - e. the total VOC emissions rate for all coating materials, in pounds per month (b x c); and
  - f. the total VOC emissions rate for all coating materials, in pounds per rolling, 12-month summation (b x d).
  
2. The permittee shall collect and record the following information each month for emissions units K009, K010, K011, K012, K013, K014, and K015:
  - a. the name and identification of each cleanup material, as applied;
  - b. the VOC content for each cleanup material in pounds of VOC per gallon of cleanup material, excluding water and exempt solvents, as applied;
  - c. the number of gallons applied, of each cleanup material, excluding water and exempt solvents, as applied;
  - d. the rolling, 12-month summation of the cleanup material usage, in gallons, excluding water and exempt solvents;
  - e. the total VOC emission rate for all cleanup materials, in pounds per month (b x c); and
  - f. the total VOC emissions rate for all cleanup materials, in pounds per rolling,

Emissions Unit ID: **K011**

12-month rolling summation for K009, K010, K011, K012, K013, K014, and K015 combined.

3. The permittee shall collect and record the following information each month for emissions units K009, K010, K011, K012, K013, K014, and K015:
  - a. the name and identification number of each coating, as applied;
  - b. the individual HAP<sup>1</sup> content for each HAP of each coating in pounds of individual HAP per gallon of coating, as applied;
  - c. the total combined HAP content for each HAP of each coating in pounds of combined HAPs per gallon of coating, as applied (sum of all individual HAP contents from b);
  - d. the number of gallons of each coating employed;
  - e. the name and identification of each cleanup material employed;
  - f. the individual HAP content for each HAP of each cleanup material in pounds of individual HAP per gallon cleanup material, as applied;
  - g. the total combined HAP content of each cleanup material in pounds of combined HAPs per gallon of cleanup material, as applied (sum of all individual HAP contents from f);
  - h. the number of gallons of each cleanup material employed;
  - i. the total individual HAP emissions for each HAP from all coating and cleanup material in pounds or tons per rolling, 12-month period (for each HAP the sum of b times d for each coating and the sum of f times h for each cleanup material);
  - j. the total combined HAPs emissions from all coating and cleanup materials employed, in pounds or tons per month and pounds or tons per rolling, 12-month period (the sum of c times d for each coating plus the sum of g times h for each cleanup material);
  - k. the updated rolling, 12-month summation of emissions for each individual HAP in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

**Issued: 6/26/2007**

- I. the updated rolling, 12-month summation of emissions for total combined HAPs in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

<sup>1</sup>A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA field office or local air agency contact. Material Safety Data Sheets typically include a listing of the solvents contained in the coatings or clean materials. This information does not have to be kept on a line-by-line basis.

4. The permit to install for this emissions unit (K011) was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the ISCST3 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the ISCST3 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: xylene

TLV (mg/m<sup>3</sup>): 434.19

Maximum Hourly Emission Rate (g/s): 2.04

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m<sup>3</sup>): 507.8

MAGLC (ug/m<sup>3</sup>): 10,337.91

Pollutant: toluene

TLV (mg/m<sup>3</sup>): 188.40

Maximum Hourly Emission Rate (g/s): 2.04

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m<sup>3</sup>): 507.8

MAGLC (ug/m<sup>3</sup>): 4,485.83

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

Emissions Unit ID: **K011**

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

#### **D. Reporting Requirements**

**Issued: 6/26/2007**

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.
2. The permittee shall notify Ohio EPA, Central District Office in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to Ohio EPA, Central District Office within 45 days after the exceedance occurs.
3. The permittee shall submit quarterly deviation (excursion) reports which identify all exceedances of the following:
  - a. the VOC content limit for coating materials;
  - b. the VOC content limit for cleanup materials;
  - c. the rolling, 12-month coating usage limitation for K011;
  - d. the rolling, 12-month VOC emission limitation for K011;
  - e. the rolling, 12-month cleanup usage limitation for K009, K010, K011, K012, K013, K014, and K015 combined;
  - f. the rolling, 12-month VOC emission limitation, from cleanup material, for K009, K010, K011, K012, K013, K014, and K015 combined;
  - g. the rolling, 12-month total individual HAP emission limitation for K009, K010, K011, K012, K013, K014, and K015 combined; and
  - h. the rolling, 12-month total combined HAPs emissions limitation for K009, K010, K011, K012, K013, K014, and K015 combined.
4. These quarterly deviation (excursion) reports shall be submitted to the Ohio EPA Central District Office by January 31, April 30, July 31 and October 31 of each year and shall cover the previous calendar quarter. If no deviations occurred during a calendar quarter, the permittee shall submit a report which states that no deviations occurred during the calendar quarter.
5. The permittee shall submit annual reports which specify the VOC and individual and combined HAP emissions from this emissions unit for the previous calendar year. The reports shall be submitted by April 15 of each year. This reporting requirement may be satisfied by including and identifying the specific emission data from this emissions unit in the annual Fee Emission Report.

**E. Testing Requirements**

Emissions Unit ID: **K011**

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following methods:
  - a. Emissions Limitation:  
7.0 lbs/hr of VOC from coating operations.  
  
Applicable Compliance Method:  
Compliance has been demonstrated by multiplying the maximum hourly coating usage rate of 2.0 gallons/hour by the maximum VOC content of 3.5 lbs/gallon.
  - b. Emissions Limitation:  
22.0 lbs/hr of VOC from cleanup operations.  
  
Applicable Compliance Method:  
Compliance has been demonstrated by multiplying the maximum hourly cleanup usage rate of 3.0 gallons/hour by the maximum VOC content of 7.25 lbs/gallon.
  - c. Emission Limitation:  
VOC emissions from coatings shall not exceed 15.7 tons, as a 12-month rolling summation.  
  
Applicable Compliance Method:  
Compliance shall be based upon the record keeping requirements as specified in Section C.1.

Issued: 6/26/2007

- d. Emissions Limitation:  
3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents.

Applicable Compliance Method:

Compliance with the VOC content of the coatings applied in this emissions unit shall be determined through monthly record keeping, as specified in Sections C.1. Formulation data from the coating manufacturer and/or, if required, USEPA Method 24 (or an alternative approved method) shall be used to determine the volatile organic compound content of the coatings, to be used in the calculation of emissions.

- e. Emissions Limitation:  
7.25 pounds of VOC per gallon of cleanup material, excluding water and exempt solvents.

Applicable Compliance Method:

Compliance with the VOC content of the cleanup material applied in this emissions unit shall be determined through monthly record keeping, as specified in Sections C.2. Formulation data from the cleanup material manufacturer and/or, if required, USEPA Method 24 (or an alternative approved method) shall be used to determine the volatile organic compound content of the cleanup materials, to be used in the calculation of emissions.

- f. Emission Limitation:  
PE shall not exceed 0.2 lb/hr.

Applicable Compliance Method:

To determine the annual worst case emissions for particulate matter, the following equation shall be used:

$$E = CS_a (\text{pounds per hour}) \times (1 - TE) \times (1 - CE).$$

$CS_a$  = maximum coating solids usage rate is calculated by multiplying the paint density (lbs/gal), by the solids percent by weight, and by the maximum hourly gallon used.

$TE$  = transfer efficiency, which is the ratio of the amount of coatings solids deposited on the coated part to the amount of coating solids used (75% for air spray gun)

Issued: 6/26/2007

CE = control efficiency of the control equipment (95% for panel filters)

Note: The values cited for M, TE, and CE are based on manufacturer's data.

- g. Emission Limitation:  
PE shall not exceed 0.9 ton per year.

Applicable Compliance Method:

The annual emission limitation was established by multiplying the hourly limitation by 8,760 hours/year and then dividing by 2,000 pounds/ton. Compliance with the annual emission limitation may be assumed as long as compliance with the hourly emission limitation is maintained.

- h. Emission Limitation:  
VOC emissions from cleanup materials applied in emissions units K009, K010, K011, K012, K013, K014, and K015 combined shall not exceed 5.88 tons per rolling 12-month summation.

Applicable Compliance Method:

Compliance with the rolling 12-month limitation shall be established by the record keeping found in Section C.2.

- i. Emission Limitation:  
The individual HAP emissions shall not exceed 9.9 tons per rolling 12-month period for all single HAP from all coatings and cleanup materials used in units K009, K010, K011, K012, K013, K014, and K015 combined.

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements specified in Section C.3 of this permit.

- j. Emission Limitation:  
The combined total HAPs emissions shall not exceed 24.9 tons per rolling 12-month period for all HAP from all coatings and cleanup materials used in units K009, K010, K011, K012, K013, K014, and K015 combined.

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements specified in Section C.3 of this permit.

**F. Miscellaneous Requirements**

None

Issued: 6/26/2007

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)****A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

**Operations, Property, and/or Equipment - (K012) - Building No. 11 - Finishing Paint Booth.  
The terms of this permit supercede those identified in PTI No. 01-08944 issued August 9, 2005.**

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(A)(3)	<p>Emissions shall not exceed:</p> <p>7.0 lbs/hr of volatile organic compounds (VOC) from coating operations.</p> <p>22.0 lbs/hr of VOC from cleanup operations. See Section B.4 below.</p> <p>Particulate emissions (PE) shall not exceed 0.2 lb/hr and 0.8 ton per year from coating operations.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(C), 3745-35-07(B) and 3745-21-09(U)(1)(d).</p> <p>See Section A.2.a below.</p>
<p>OAC rule 3745-31-05(C) (synthetic minor to avoid NSR)</p> <p>OAC rule 3745-35-07(B) (synthetic minor to avoid Title V)</p>	<p>Emissions shall not exceed, as a 12-month rolling summation:</p> <p>15.7 tons of VOC from coating material usage.</p> <p>See Section B.1 below.</p> <p>VOC emissions from cleanup material usage in emissions units K009, K010, K011, K012, K013, K014, and K015 combined shall not exceed 5.88 tons per rolling, 12-month summation.</p> <p>See Section B.3 below.</p>

**Issued: 6/26/2007**

OAC rule 3745-35-07(B) (synthetic minor to avoid Title V)	The combined total hazardous air pollutants (HAP) emissions shall not exceed 9.9 tons per rolling 12-month period for any single HAP and 24.9 tons per rolling 12-month period for all HAPs from all coating and cleanup materials used in units K009, K010, K011, K012, K013, K014, and K015 combined.
OAC rule 3745-17-07(A)(1)	Visible PE from any stack serving this emissions unit shall not exceed 20 % opacity, as a six-minute average, except as specified by rule.
OAC rule 3745-17-11(A)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to the requirement specified in OAC rule 3745-31-05(A)(3).
OAC rule 3745-21-09(U)(1)(d)	See Section B.2 below.

## 2. Additional Terms and Conditions

- 2.a** The hourly VOC emission limitation and the hourly and annual PE emission limitations were established to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to develop monitoring, record keeping and/or reporting requirements to ensure compliance with these limits.

## B. Operational Restrictions

1. The maximum annual coating usage for K012 shall not exceed 8,976 gallons applied based upon a rolling, 12-month summation of the coating usage figures.

To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed the coating usage levels specified in the following table:

<u>Month(s)</u>	<u>Maximum Allowable Cumulative Coating Usage</u>
1	748
1-2	1,496
1-3	2,244
1-4	2,992
1-5	3,740
1-6	4,488
1-7	5,234

Emissions Unit ID: **K012**

1-8	5,982
1-9	6,730
1-10	7,478
1-11	8,226
1-12	8,976

After the first 12 calendar months of operation following the issuance of this permit, compliance with the annual coating usage limitation shall be based upon a rolling, 12-month summation of the coating usage figures.

- The maximum coating content shall not exceed 3.5 lbs VOC per gallon, excluding water and exempt solvents.
- The maximum annual cleanup material usage for emission units K006, K009, K010, K011, K012, K013, and K014 combined shall not exceed 1,623 gallons, based upon a rolling, 12-month summation of the cleanup material usage.

To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed the cleanup material usage levels specified in the following table:

<u>Month(s)</u>	<u>Maximum Allowable Cumulative Cleanup Material Usage</u>
1	136
1-2	272
1-3	408
1-4	544
1-5	680
1-6	816
1-7	952
1-8	1,088
1-9	1,224
1-10	1,360
1-11	1,496
1-12	1,623

After the first 12 calendar months of operation following the issuance of this permit, compliance with the annual cleanup material usage limitation shall be based upon a rolling, 12-month summation of the cleanup material usage figures.

**Issued: 6/26/2007**

4. The maximum cleanup material content shall not exceed 7.25 lbs VOC per gallon, excluding water and exempt solvents.
5. The permittee shall operate the dry filtration system whenever this emissions unit is in operation, to control particulate emissions.

Issued: 6/26/2007

**C. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information each month for emissions unit K012:
  - a. the name and identification of each coating material, as applied;
  - b. the VOC content for each coating material in pounds of VOC per gallon of coating material, excluding water and exempt solvents, as applied;
  - c. the number of gallons applied, of each coating material, excluding water and exempt solvents, as applied;
  - d. the rolling, 12-month summation of the coating usage, in gallons, excluding water and exempt solvents;
  - e. the total VOC emissions rate for all coating materials, in pounds per month (b x c); and
  - f. the total VOC emissions rate for all coating materials, in pounds per rolling, 12-month summation (b x d).
  
2. The permittee shall collect and record the following information each month for emissions units K009, K010, K011, K012, K013, K014, and K015:
  - a. the name and identification of each cleanup material, as applied;
  - b. the VOC content for each cleanup material in pounds of VOC per gallon of cleanup material, excluding water and exempt solvents, as applied;
  - c. the number of gallons applied, of each cleanup material, excluding water and exempt solvents, as applied;
  - d. the rolling, 12-month summation of the cleanup material usage, in gallons, excluding water and exempt solvents;
  - e. the total VOC emission rate for all cleanup materials, in pounds per month (b x c); and
  - f. the total VOC emissions rate for all cleanup materials, in pounds per rolling,

**Issued: 6/26/2007**

12-month rolling summation for K009, K010, K011, K012, K013, K014, and K015 combined.

3. The permittee shall collect and record the following information each month for emissions units K009, K010, K011, K012, K013, K014, and K015:
  - a. the name and identification number of each coating, as applied;
  - b. the individual HAP<sup>1</sup> content for each HAP of each coating in pounds of individual HAP per gallon of coating, as applied;
  - c. the total combined HAP content for each HAP of each coating in pounds of combined HAPs per gallon of coating, as applied (sum of all individual HAP contents from b);
  - d. the number of gallons of each coating employed;
  - e. the name and identification of each cleanup material employed;
  - f. the individual HAP content for each HAP of each cleanup material in pounds of individual HAP per gallon cleanup material, as applied;
  - g. the total combined HAP content of each cleanup material in pounds of combined HAPs per gallon of cleanup material, as applied (sum of all individual HAP contents from f);
  - h. the number of gallons of each cleanup material employed;
  - i. the total individual HAP emissions for each HAP from all coating and cleanup material in pounds or tons per rolling, 12-month period (for each HAP the sum of b times d for each coating and the sum of f times h for each cleanup material);
  - j. the total combined HAPs emissions from all coating and cleanup materials employed, in pounds or tons per month and pounds or tons per rolling, 12-month period (the sum of c times d for each coating plus the sum of g times h for each cleanup material);
  - k. the updated rolling, 12-month summation of emissions for each individual HAP in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

- I. the updated rolling, 12-month summation of emissions for total combined HAPs in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

<sup>1</sup> A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA field office or local air agency contact. Material Safety Data Sheets typically include a listing of the solvents contained in the coatings or clean materials. This information does not have to be kept on a line-by-line basis.

4. The permit to install for this emissions unit (K012) was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the ISCST3 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the ISCST3 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: xylene

TLV (mg/m<sup>3</sup>): 434.19

Maximum Hourly Emission Rate (g/s): 2.04

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m<sup>3</sup>): 507.8

MAGLC (ug/m<sup>3</sup>): 10,337.91

Pollutant: toluene

TLV (mg/m<sup>3</sup>): 188.40

Maximum Hourly Emission Rate (g/s): 2.04

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m<sup>3</sup>): 507.8

MAGLC (ug/m<sup>3</sup>): 4,485.83

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

**Issued: 6/26/2007**

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

#### **D. Reporting Requirements**

Emissions Unit ID: **K012**

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.
2. The permittee shall notify Ohio EPA, Central District Office in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to Ohio EPA, Central District Office within 45 days after the exceedance occurs.
3. The permittee shall submit quarterly deviation (excursion) reports which identify all exceedances of the following:
  - a. the VOC content limit for coating materials;
  - b. the VOC content limit for cleanup materials;
  - c. the rolling, 12-month coating usage limitation for K012;
  - d. the rolling, 12-month VOC emission limitation for K012;
  - e. the rolling, 12-month cleanup usage limitation for K009, K010, K011, K012, K013, K014, and K015 combined;
  - f. the rolling, 12-month VOC emission limitation, from cleanup material, for K009, K010, K011, K012, K013, K014, and K015 combined;
  - g. the rolling, 12-month total individual HAP emission limitation for K009, K010, K011, K012, K013, K014, and K015 combined; and
  - h. the rolling, 12-month total combined HAPs emissions limitation for K009, K010, K011, K012, K013, K014, and K015 combined.
4. These quarterly deviation (excursion) reports shall be submitted to the Ohio EPA Central District Office by January 31, April 30, July 31 and October 31 of each year and shall cover the previous calendar quarter. If no deviations occurred during a calendar quarter, the permittee shall submit a report which states that no deviations occurred during the calendar quarter.
5. The permittee shall submit annual reports which specify the VOC and individual and combined HAP emissions from this emissions unit for the previous calendar year. The reports shall be submitted by April 15 of each year. This reporting requirement may be satisfied by including and identifying the specific emission data from this emissions unit in the annual Fee Emission Report.

## **E. Testing Requirements**

**Issued: 6/26/2007**

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following methods:

a. Emissions Limitation:  
7.0 lbs/hr of VOC from coating operations.

Applicable Compliance Method:  
Compliance has been demonstrated by multiplying the maximum hourly coating usage rate of 2.0 gallons/hour by the maximum VOC content of 3.5 lbs/gallon.

b. Emissions Limitation:  
22.0 lbs/hr of VOC from cleanup operations.

Applicable Compliance Method:  
Compliance has been demonstrated by multiplying the maximum hourly cleanup usage rate of 3.0 gallons/hour by the maximum VOC content of 7.25 lbs/gallon.

c. Emission Limitation:  
VOC emissions from coatings shall not exceed 15.7 tons, as a 12-month rolling summation.

Applicable Compliance Method:  
Compliance shall be based upon the record keeping requirements as specified in Section C.1.

d. Emissions Limitation:  
3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents.

Applicable Compliance Method:  
Compliance with the VOC content of the coatings applied in this emissions unit shall be determined through monthly record keeping, as specified in Sections C.1. Formulation data from the coating manufacturer and/or, if required, USEPA Method 24 (or an alternative approved method) shall be used to determine the volatile organic compound content of the coatings, to be used in the calculation of emissions.

e. Emissions Limitation:  
7.25 pounds of VOC per gallon of cleanup material, excluding water and exempt solvents.

Emissions Unit ID: K012

Applicable Compliance Method:

Compliance with the VOC content of the cleanup material applied in this emissions unit shall be determined through monthly record keeping, as specified in Sections C.2. Formulation data from the cleanup material manufacturer and/or, if required, USEPA Method 24 (or an alternative approved method) shall be used to determine the volatile organic compound content of the cleanup materials, to be used in the calculation of emissions.

- f. Emission Limitation:  
PE shall not exceed 0.2 lb/hr.

Applicable Compliance Method:

To determine the annual worst case emissions for particulate matter, the following equation shall be used:

$$E = CS_a (\text{pounds per hour}) \times (1 - TE) \times (1 - CE)$$

$CS_a$  = maximum coating solids usage rate is calculated by multiplying the paint density (lbs/gal), by the solids percent by weight, and by the maximum hourly gallon used.

TE = transfer efficiency, which is the ratio of the amount of coatings solids deposited on the coated part to the amount of coating solids used (75% for air spray gun)

CE = control efficiency of the control equipment (95% for panel filters)

Note: The values cited for M, TE, and CE are based on manufacturer's data.

- g. Emission Limitation:  
PE shall not exceed 0.8 ton per year.

Applicable Compliance Method:

The annual emission limitation was established by multiplying the hourly limitation by 8,760 hours/year and then dividing by 2,000 pounds/ton. Compliance with the annual emission limitation may be assumed as long as compliance with the hourly emission limitation is maintained.

- h. Emission Limitation:  
VOC emissions from cleanup materials applied in emissions units K009, K010, K011, K012, K013, K014, and K015 combined shall not exceed 5.88 tons per

**Issued: 6/26/2007**

rolling 12-month summation.

Applicable Compliance Method:

Compliance with the rolling 12-month limitation shall be established by the record keeping found in Section C.2.

i. Emission Limitation:

The individual HAP emissions shall not exceed 9.9 tons per rolling 12-month period for all single HAP from all coatings and cleanup materials used in units K009, K010, K011, K012, K013, K014, and K015 combined.

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements specified in Section C.3 of this permit.

j. Emission Limitation:

The combined total HAPs emissions shall not exceed 24.9 tons per rolling 12-month period for all HAP from all coatings and cleanup materials used in units K009, K010, K011, K012, K013, K014, and K015 combined.

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements specified in Section C.3 of this permit.

**F. Miscellaneous Requirements**

None

Issued: 6/26/2007

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)****A. Applicable Emissions Limitations and/or Control Requirements**

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

**Operations, Property, and/or Equipment - (K013) - Building No. 15 - Paint Booth. The terms of this permit supercede those identified in PTI No. 01-08944 issued August 9, 2005.**

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(A)(3)	<p>Emissions shall not exceed:</p> <p>8.8 lbs/hr of volatile organic compounds (VOC) from coating operations.</p> <p>22.0 lbs/hr of VOC from cleanup operations. See Section B.4 below.</p> <p>Particulate emissions (PE) shall not exceed 0.3 lb/hr and 1.5 tons per year from coating operations.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(C), 3745-35-07(B) and 3745-21-09(U)(1)(d).</p> <p>See Section A.2.a below</p>
<p>OAC rule 3745-31-05(C) (synthetic minor to avoid NSR)</p> <p>OAC rule 3745-35-07(B) (synthetic minor to avoid Title V)</p>	<p>Emissions shall not exceed, as a 12-month rolling summation:</p> <p>19.6 tons of VOC from coating material usage.</p> <p>See Section B.1 below.</p> <p>VOC emissions from cleanup material usage in emissions units K009, K010, K011, K012, K013, K014, and K015 combined shall not exceed 5.88 tons per rolling, 12-month summation.</p> <p>See Section B.3 below.</p>

Emissions Unit ID: **K013**

OAC rule 3745-35-07(B) (synthetic minor to avoid Title V)	The combined total hazardous air pollutants (HAP) emissions shall not exceed 9.9 tons per rolling 12-month period for any single HAP and 24.9 tons per rolling 12-month period for all HAPs from all coating and cleanup materials used in units K009, K010, K011, K012, K013, K014, and K015 combined.
OAC rule 3745-17-07(A)(1)	Visible PE from any stack serving this emissions unit shall not exceed 20 % opacity, as a six-minute average, except as specified by rule.
OAC rule 3745-17-11(A)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to the requirement specified in OAC rule 3745-31-05(A)(3).
OAC rule 3745-21-09(U)(1)(d)	See Section B.2 below.

## 2. Additional Terms and Conditions

- 2.a** The hourly VOC emission limitation and the hourly and annual PE emission limitations were established to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to develop monitoring, record keeping and/or reporting requirements to ensure compliance with these limits.

## B. Operational Restrictions

1. The maximum annual coating usage for K013 shall not exceed 11,220 gallons applied based upon a rolling, 12-month summation of the coating usage figures.

To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed the coating usage levels specified in the following table:

<u>Month(s)</u>	<u>Maximum Allowable Cumulative Coating Usage</u>
1	935
1-2	1,870
1-3	2,805
1-4	3,740
1-5	4,675
1-6	5,610
1-7	6,545
1-8	7,480

**Issued: 6/26/2007**

1-9	8,415
1-10	9,350
1-11	10,285
1-12	11,220

After the first 12 calendar months of operation following the issuance of this permit, compliance with the annual coating usage limitation shall be based upon a rolling, 12-month summation of the coating usage figures.

2. The maximum coating content shall not exceed 3.5 lbs VOC per gallon, excluding water and exempt solvents.
3. The maximum annual cleanup material usage for emission units K009, K010, K011, K012, K013, K014, and K015 combined shall not exceed 1,623 gallons, based upon a rolling, 12-month summation of the cleanup material usage.

To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed the cleanup material usage levels specified in the following table:

<u>Month(s)</u>	<u>Maximum Allowable Cumulative Cleanup Material Usage</u>
1	136
1-2	272
1-3	408
1-4	544
1-5	680
1-6	816
1-7	952
1-8	1,088
1-9	1,224
1-10	1,360
1-11	1,496
1-12	1,623

After the first 12 calendar months of operation following the issuance of this permit, compliance with the annual cleanup material usage limitation shall be based upon a rolling, 12-month summation of the cleanup material usage figures.

**Issued: 6/26/2007**

4. The maximum cleanup material content shall not exceed 7.25 lbs VOC per gallon, excluding water and exempt solvents.
5. The permittee shall operate the dry filtration system whenever this emissions unit is in operation, to control particulate emissions.

Issued: 6/26/2007

**C. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information each month for emissions unit K013:
  - a. the name and identification of each coating material, as applied;
  - b. the VOC content for each coating material in pounds of VOC per gallon of coating material, excluding water and exempt solvents, as applied;
  - c. the number of gallons applied, of each coating material, excluding water and exempt solvents, as applied;
  - d. the rolling, 12-month summation of the coating usage, in gallons, excluding water and exempt solvents;
  - e. the total VOC emissions rate for all coating materials, in pounds per month (b x c); and
  - f. the total VOC emissions rate for all coating materials, in pounds per rolling, 12-month summation (b x d).
  
2. The permittee shall collect and record the following information each month for emissions units K009, K010, K011, K012, K013, K014, and K015:
  - a. the name and identification of each cleanup material, as applied;
  - b. the VOC content for each cleanup material in pounds of VOC per gallon of cleanup material, excluding water and exempt solvents, as applied;
  - c. the number of gallons applied, of each cleanup material, excluding water and exempt solvents, as applied;
  - d. the rolling, 12-month summation of the cleanup material usage, in gallons, excluding water and exempt solvents;
  - e. the total VOC emission rate for all cleanup materials, in pounds per month (b x c); and
  - f. the total VOC emissions rate for all cleanup materials, in pounds per rolling,

Emissions Unit ID: **K013**

12-month rolling summation for K009, K010, K011, K012, K013, K014, and K015 combined.

3. The permittee shall collect and record the following information each month for emissions units K009, K010, K011, K012, K013, K014, and K015:
  - a. the name and identification number of each coating, as applied;
  - b. the individual HAP<sup>1</sup> content for each HAP of each coating in pounds of individual HAP per gallon of coating, as applied;
  - c. the total combined HAP content for each HAP of each coating in pounds of combined HAPs per gallon of coating, as applied (sum of all individual HAP contents from b);
  - d. the number of gallons of each coating employed;
  - e. the name and identification of each cleanup material employed;
  - f. the individual HAP content for each HAP of each cleanup material in pounds of individual HAP per gallon cleanup material, as applied;
  - g. the total combined HAP content of each cleanup material in pounds of combined HAPs per gallon of cleanup material, as applied (sum of all individual HAP contents from f);
  - h. the number of gallons of each cleanup material employed;
  - i. the total individual HAP emissions for each HAP from all coating and cleanup material in pounds or tons per rolling, 12-month period (for each HAP the sum of b times d for each coating and the sum of f times h for each cleanup material);
  - j. the total combined HAPs emissions from all coating and cleanup materials employed, in pounds or tons per month and pounds or tons per rolling, 12-month period (the sum of c times d for each coating plus the sum of g times h for each cleanup material);
  - k. the updated rolling, 12-month summation of emissions for each individual HAP in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and

**Issued: 6/26/2007**

- I. the updated rolling, 12-month summation of emissions for total combined HAPs in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

<sup>1</sup>A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA field office or local air agency contact. Material Safety Data Sheets typically include a listing of the solvents contained in the coatings or clean materials. This information does not have to be kept on a line-by-line basis.

4. The permit to install for this emissions unit (K013) was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the ISCST3 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the ISCST3 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: xylene

TLV (mg/m<sup>3</sup>): 434.19

Maximum Hourly Emission Rate (g/s): 2.04

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m<sup>3</sup>): 507.8

MAGLC (ug/m<sup>3</sup>): 10,337.91

Pollutant: toluene

TLV (mg/m<sup>3</sup>): 188.40

Maximum Hourly Emission Rate (g/s): 2.04

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m<sup>3</sup>): 507.8

MAGLC (ug/m<sup>3</sup>): 4,485.83

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

Emissions Unit ID: **K013**

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

#### **D. Reporting Requirements**

**Issued: 6/26/2007**

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.
2. The permittee shall notify Ohio EPA, Central District Office in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to Ohio EPA, Central District Office within 45 days after the exceedance occurs.
3. The permittee shall submit quarterly deviation (excursion) reports which identify all exceedances of the following:
  - a. the VOC content limit for coating materials;
  - b. the VOC content limit for cleanup materials;
  - c. the rolling, 12-month coating usage limitation for K013;
  - d. the rolling, 12-month VOC emission limitation for K013;
  - e. the rolling, 12-month cleanup usage limitation for K009, K010, K011, K012, K013, K014, and K015 combined;
  - f. the rolling, 12-month VOC emission limitation, from cleanup material, for K009, K010, K011, K012, K013, K014, and K015 combined;
  - g. the rolling, 12-month total individual HAP emission limitation for K009, K010, K011, K012, K013, K014, and K015 combined; and
  - h. the rolling, 12-month total combined HAPs emissions limitation for K009, K010, K011, K012, K013, K014, and K015 combined.
4. These quarterly deviation (excursion) reports shall be submitted to the Ohio EPA Central District Office by January 31, April 30, July 31 and October 31 of each year and shall cover the previous calendar quarter. If no deviations occurred during a calendar quarter, the permittee shall submit a report which states that no deviations occurred during the calendar quarter.
5. The permittee shall submit annual reports which specify the VOC and individual and combined HAP emissions from this emissions unit for the previous calendar year. The reports shall be submitted by April 15 of each year. This reporting requirement may be satisfied by including and identifying the specific emission data from this emissions unit in the annual Fee Emission Report.

**E. Testing Requirements**

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following methods:
  - a. Emissions Limitation:  
8.8 lbs/hr of VOC from coating operations.  
  
Applicable Compliance Method:  
Compliance has been demonstrated by multiplying the maximum hourly cleanup usage rate of 2.5 gallons/hour by the maximum VOC content of 3.5 lbs/gallon.
  - b. Emissions Limitation:  
22.0 lbs/hr of VOC from cleanup operations.  
  
Applicable Compliance Method:  
Compliance has been demonstrated by multiplying the maximum hourly coating usage rate of 3.0 gallons/hour by the maximum VOC content of 7.25 lbs/gallon.
  - c. Emission Limitation:  
VOC emissions from coatings shall not exceed 19.6 tons, as a 12-month rolling summation.  
  
Applicable Compliance Method:  
Compliance shall be based upon the record keeping requirements as specified in Section C.1.
  - d. Emissions Limitation:  
3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents.  
  
Applicable Compliance Method:  
Compliance with the VOC content of the coatings applied in this emissions unit shall be determined through monthly record keeping, as specified in Sections C.1. Formulation data from the coating manufacturer and/or, if required, USEPA Method 24 (or an alternative approved method) shall be used to determine the volatile organic compound content of the coatings, to be used in the calculation of emissions.
  - e. Emissions Limitation:  
7.25 pounds of VOC per gallon of cleanup material, excluding water and exempt solvents.

**Issued: 6/26/2007**Applicable Compliance Method:

Compliance with the VOC content of the cleanup material applied in this emissions unit shall be determined through monthly record keeping, as specified in Sections C.2. Formulation data from the cleanup material manufacturer and/or, if required, USEPA Method 24 (or an alternative approved method) shall be used to determine the volatile organic compound content of the cleanup materials, to be used in the calculation of emissions.

f. Emission Limitation:

PE shall not exceed 0.3 lb/hr.

Applicable Compliance Method:

To determine the annual worst case emissions for particulate matter, the following equation shall be used:

$$E = CS_a (\text{pounds per hour}) \times (1 - TE) \times (1 - CE).$$

$CS_a$  = maximum coating solids usage rate is calculated by multiplying the paint density (lbs/gal), by the solids percent by weight, and by the maximum hourly gallon used.

TE = transfer efficiency, which is the ratio of the amount of coatings solids deposited on the coated part to the amount of coating solids used (75% for air spray gun).

CE = control efficiency of the control equipment (95% for panel filters).

Note: The values cited for M, TE, and CE are based on manufacturer's data.

g. Emission Limitation:

PE shall not exceed 1.5 ton per year.

Applicable Compliance Method:

The annual emission limitation was established by multiplying the hourly limitation by 8,760 hours/year and then dividing by 2,000 pounds/ton. Compliance with the annual emission limitation may be assumed as long as compliance with the hourly emission limitation is maintained.

h. Emission Limitation:

VOC emissions from cleanup materials applied in emissions units K009, K010,

Emissions Unit ID: **K013**

K011, K012, K013, K014, and K015 combined shall not exceed 5.88 tons per rolling 12-month summation.

Applicable Compliance Method:

Compliance with the rolling 12-month limitation shall be established by the record keeping found in Section C.2.

i. Emission Limitation:

The individual HAP emissions shall not exceed 9.9 tons per rolling 12-month period for all single HAP from all coatings and cleanup materials used in units K009, K010, K011, K012, K013, K014, and K015 combined.

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements specified in Section C.3 of this permit.

j. Emission Limitation:

The combined total HAPs emissions shall not exceed 24.9 tons per rolling 12-month period for all HAP from all coatings and cleanup materials used in units K009, K010, K011, K012, K013, K014, and K015 combined.

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements specified in Section C.3 of this permit.

**F. Miscellaneous Requirements**

None

Issued: 6/26/2007

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)****A. Applicable Emissions Limitations and/or Control Requirements**

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

**Operations, Property, and/or Equipment - (K014) - Building No. 15 - Shop Floor Painting. The terms of this permit supercede those identified in PTI No. 01-08944 issued August 9, 2005.**

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(A)(3)	<p>Emissions shall not exceed:</p> <p>16.0 lbs/hr of volatile organic compounds (VOC) from coating operations.</p> <p>22.0 lbs/hr of VOC from cleanup operations. See Section B.4 below.</p> <p>Particulate emissions (PE) shall not exceed 2.7 lbs/hr and 11.8 tons per year from coating operations.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(C), 3745-35-07(B) and 3745-21-09(U)(1)(d).</p> <p>See Section A.2.a below.</p>
OAC rule 3745-31-05(C) (synthetic minor to avoid NSR) OAC rule 3745-35-07(B) (synthetic minor to avoid Title V)	<p>Emissions shall not exceed, as a 12-month rolling summation:</p> <p>3.2 tons of VOC from coating material usage.</p> <p>See Section B.1 below.</p> <p>VOC emissions from cleanup material usage in emissions units K009, K010, K011, K012, K013, K014, and K015 combined shall not exceed 5.88 tons per rolling, 12-month summation.</p> <p>See Section B.3 below.</p>

Issued: 6/26/2007

OAC rule 3745-35-07(B) (synthetic minor to avoid Title V)	The combined total hazardous air pollutants (HAP) emissions shall not exceed 9.9 tons per rolling 12-month period for any single HAP and 24.9 tons per rolling 12-month period for all HAPs from all coating and cleanup materials used in units K009, K010, K011, K012, K013, K014, and K015 combined.
OAC rule 3745-17-07(A)(1)	Visible PE from any stack serving this emissions unit shall not exceed 20 % opacity, as a six-minute average, except as specified by rule.
OAC rule 3745-17-11(A)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to the requirement specified in OAC rule 3745-31-05(A)(3).
OAC rule 3745-21-09(U)(2)(e)(iii)	This emissions unit shall not employ more than 10 gallons of coating on metal parts in any given day.

## 2. Additional Terms and Conditions

- 2.a** The hourly VOC emission limitation and the hourly and annual PE emission limitations were established to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to develop monitoring, record keeping and/or reporting requirements to ensure compliance with these limits.

## B. Operational Restrictions

1. The maximum annual coating usage for K014 shall not exceed 1600 gallons applied based upon a rolling, 12-month summation of the coating usage figures.

To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed the coating usage levels specified in the following table:

<u>Month(s)</u>	<u>Maximum Allowable Cumulative Coating Usage</u>
1	134
1-2	268
1-3	402
1-4	536
1-5	670
1-6	804
1-7	938

Emissions Unit ID: **K014**

1-8	1072
1-9	1206
1-10	1340
1-11	1474
1-12	1600

After the first 12 calendar months of operation following the issuance of this permit, compliance with the annual coating usage limitation shall be based upon a rolling, 12-month summation of the coating usage figures.

- The maximum coating content shall not exceed 4.0 lbs VOC per gallon, excluding water and exempt solvents.
- The maximum annual cleanup material usage for emission units K009, K010, K011, K012, K013, K014, and K015 combined shall not exceed 1,623 gallons, based upon a rolling, 12-month summation of the cleanup material usage.

To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed the cleanup material usage levels specified in the following table:

<u>Month(s)</u>	<u>Maximum Allowable Cumulative Cleanup Material Usage</u>
1	136
1-2	272
1-3	408
1-4	544
1-5	680
1-6	816
1-7	952
1-8	1,088
1-9	1,224
1-10	1,360
1-11	1,496
1-12	1,623

After the first 12 calendar months of operation following the issuance of this permit, compliance with the annual cleanup material usage limitation shall be based upon a rolling, 12-month summation of the cleanup material usage figures.

**Issued: 6/26/2007**

4. The maximum cleanup content shall not exceed 7.25 lbs VOC per gallon, excluding water and exempt solvents.
5. The permittee shall operate the dry filtration system whenever this emissions unit is in operation, to control particulate emissions.

Issued: 6/26/2007

**C. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information each day for emissions unit K014:
  - a. the name and identification number of each coating applied;
  - b. the volume, in gallons, of each coating applied; and
  - c. the total volume, in gallons, of all of the coatings applied.
  
2. The permittee shall collect and record the following information each month for emissions unit K014:
  - a. the name and identification of each coating material, as applied;
  - b. the VOC content for each coating material in pounds of VOC per gallon of coating material, excluding water and exempt solvents, as applied;
  - c. the number of gallons applied, of each coating material, excluding water and exempt solvents, as applied;
  - d. the rolling, 12-month summation of the coating usage, in gallons, excluding water and exempt solvents;
  - e. the total VOC emissions rate for all coating materials, in pounds per month (b x c); and
  - f. the total VOC emissions rate for all coating materials, in pounds per rolling, 12-month summation (b x d).
  
3. The permittee shall collect and record the following information each month for emissions units K009, K010, K011, K012, K013, K014, and K015:
  - a. the name and identification of each cleanup material, as applied;
  - b. the VOC content for each cleanup material in pounds of VOC per gallon of cleanup material, excluding water and exempt solvents, as applied;
  - c. the number of gallons applied, of each cleanup material, excluding water and

**Issued: 6/26/2007**

- exempt solvents, as applied;
  - d. the rolling, 12-month summation of the cleanup material usage, in gallons, excluding water and exempt solvents;
  - e. the total VOC emission rate for all cleanup materials, in pounds per month (b x c); and
  - f. the total VOC emissions rate for all cleanup materials, in pounds per rolling, 12-month rolling summation for K009, K010, K011, K012, K013, K014, and K015 combined.
4. The permittee shall collect and record the following information each month for emissions units K009, K010, K011, K012, K013, K014, and K015:
- a. the name and identification number of each coating, as applied;
  - b. the individual HAP<sup>1</sup> content for each HAP of each coating in pounds of individual HAP per gallon of coating, as applied;
  - c. the total combined HAP content for each HAP of each coating in pounds of combined HAPs per gallon of coating, as applied (sum of all individual HAP contents from b);
  - d. the number of gallons of each coating employed;
  - e. the name and identification of each cleanup material employed;
  - f. the individual HAP content for each HAP of each cleanup material in pounds of individual HAP per gallon cleanup material, as applied;
  - g. the total combined HAP content of each cleanup material in pounds of combined HAPs per gallon of cleanup material, as applied (sum of all individual HAP contents from f);
  - h. the number of gallons of each cleanup material employed;
  - i. the total individual HAP emissions for each HAP from all coating and cleanup material in pounds or tons per rolling, 12-month period (for each HAP the sum of b times d for each coating and the sum of f times h for each cleanup material);

Emissions Unit ID: **K014**

- j. the total combined HAPs emissions from all coating and cleanup materials employed, in pounds or tons per month and pounds or tons per rolling, 12-month period (the sum of c times d for each coating plus the sum of g times h for each cleanup material);
- k. the updated rolling, 12-month summation of emissions for each individual HAP in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and
- l. the updated rolling, 12-month summation of emissions for total combined HAPs in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

<sup>1</sup> A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA field office or local air agency contact. Material Safety Data Sheets typically include a listing of the solvents contained in the coatings or clean materials. This information does not have to be kept on a line-by-line basis.

5. The permit to install for this emissions unit (K014) was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the ISCST3 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the ISCST3 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: xylene

TLV (mg/m<sup>3</sup>): 434.19

Maximum Hourly Emission Rate (g/s): 2.04

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m<sup>3</sup>): 507.8

MAGLC (ug/m<sup>3</sup>): 10,337.91

Pollutant: toluene

TLV (mg/m<sup>3</sup>): 188.40

Maximum Hourly Emission Rate (g/s): 2.04

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m<sup>3</sup>): 507.8

MAGLC (ug/m<sup>3</sup>): 4,485.83

**Issued: 6/26/2007**

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

#### **D. Reporting Requirements**

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.
2. The permittee shall notify Ohio EPA, Central District Office in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to Ohio EPA, Central District Office within 45 days after the exceedance occurs.
3. The permittee shall submit quarterly deviation (excursion) reports which identify all exceedances of the following:
  - a. the VOC content limit for coating materials;
  - b. the VOC content limit for cleanup materials;
  - c. the rolling, 12-month coating usage limitation for K014;
  - d. the rolling, 12-month VOC emission limitation for K014;
  - e. the rolling, 12-month cleanup usage limitation for K009, K010, K011, K012, K013, K014, and K015 combined;
  - f. the rolling, 12-month VOC emission limitation, from cleanup material, for K009, K010, K011, K012, K013, K014, and K015 combined;
  - g. the rolling, 12-month total individual HAP emission limitation for K009, K010, K011, K012, K013, K014, and K015 combined; and
  - h. the rolling, 12-month total combined HAPs emissions limitation for K009, K010, K011, K012, K013, K014, and K015 combined.
4. These quarterly deviation (excursion) reports shall be submitted to the Ohio EPA Central District Office by January 31, April 30, July 31 and October 31 of each year and shall cover the previous calendar quarter. If no deviations occurred during a calendar

**Issued: 6/26/2007**

quarter, the permittee shall submit a report which states that no deviations occurred during the calendar quarter.

5. The permittee shall submit annual reports which specify the VOC and individual and combined HAP emissions from this emissions unit for the previous calendar year. The reports shall be submitted by April 15 of each year. This reporting requirement may be satisfied by including and identifying the specific emission data from this emissions unit in the annual Fee Emission Report.

## **E. Testing Requirements**

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following methods:

- a. Emissions Limitation:  
16.0 lbs/hr of VOC from coating operations.

Applicable Compliance Method:  
Compliance has been demonstrated by multiplying the maximum hourly coating usage rate of 4.0 gallons/hour by the maximum VOC content of 4.0 lbs/gallon.

- b. Emissions Limitation:  
22.0 lbs/hr of VOC from cleanup operations.

Applicable Compliance Method:  
Compliance has been demonstrated by multiplying the maximum hourly cleanup usage rate of 3.0 gallons/hour by the maximum VOC content of 7.25 lbs/gallon.

- c. Emission Limitation:  
VOC emissions from coatings shall not exceed 3.2 tons, as a 12-month rolling summation.

Applicable Compliance Method:  
Compliance shall be based upon the record keeping requirements as specified in Section C.1.

- d. Emissions Limitation:  
3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents.

Applicable Compliance Method:

Emissions Unit ID: **K014**

Compliance with the VOC content of the coatings applied in this emissions unit shall be determined through monthly record keeping, as specified in Sections C.1. Formulation data from the coating manufacturer and/or, if required, USEPA Method 24 (or an alternative approved method) shall be used to determine the volatile organic compound content of the coatings, to be used in the calculation of emissions.

- e. Emissions Limitation:  
 7.25 pounds of VOC per gallon of cleanup material, excluding water and exempt solvents.

Applicable Compliance Method:

Compliance with the VOC content of the cleanup material applied in this emissions unit shall be determined through monthly record keeping, as specified in Sections C.2. Formulation data from the cleanup material manufacturer and/or, if required, USEPA Method 24 (or an alternative approved method) shall be used to determine the volatile organic compound content of the cleanup materials, to be used in the calculation of emissions.

- f. Emission Limitation:  
 PE shall not exceed 2.7 lb/hr.

Applicable Compliance Method:

To determine the annual worst case emissions for particulate matter, the following equation shall be used:

$$E = CS_a (\text{pounds per hour}) \times (1 - TE)$$

$$CS_a = \text{maximum coating solids usage rate is calculated by multiplying the paint density (lbs/gal), by the solids percent by weight, and by the maximum hourly gallon used.}$$

$$TE = \text{transfer efficiency, which is the ratio of the amount of coatings solids deposited on the coated part to the amount of coating solids used (75% for air spray gun)}$$

Note: The values cited for M and TE are based on manufacturer's data.

- g. Emission Limitation:  
 PE shall not exceed 11.8 ton per year.

Applicable Compliance Method:

**Issued: 6/26/2007**

The annual emission limitation was established by multiplying the hourly limitation by 8,760 hours/year and then dividing by 2,000 pounds/ton. Compliance with the annual emission limitation may be assumed as long as compliance with the hourly emission limitation is maintained.

- h. Emission Limitation:  
VOC emissions from cleanup materials applied in emissions units K009, K010, K011, K012, K013, K014, and K015 combined shall not exceed 5.88 tons per rolling 12-month summation.

Applicable Compliance Method:

Compliance with the rolling 12-month limitation shall be established by the record keeping found in Section C.2.

- i. Emission Limitation:  
The individual HAP emissions shall not exceed 9.9 tons per rolling 12-month period for all single HAP from all coatings and cleanup materials used in units K009, K010, K011, K012, K013, K014, and K015 combined.

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements specified in Section C.3 of this permit.

- j. Emission Limitation:  
The combined total HAPs emissions shall not exceed 24.9 tons per rolling 12-month period for all HAP from all coatings and cleanup materials used in units K009, K010, K011, K012, K013, K014, and K015 combined.

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements specified in Section C.3 of this permit.

**F. Miscellaneous Requirements**

None

Issued: 6/26/2007

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)****A. Applicable Emissions Limitations and/or Control Requirements**

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

**Operations, Property, and/or Equipment - (K015) - Building 18 - Paint Booth.**

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(A)(3)	<p>Emissions shall not exceed:</p> <p>17.5 lbs/hr of volatile organic compounds (VOC) from coating operations.</p> <p>22.0 lbs/hr of VOC from cleanup operations. See Section B.4 below.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(C), 3745-35-07(B) and 3745-21-09(U)(1)(d).</p> <p>See Section A.2.a below.</p>
OAC rule 3745-31-05(C) (synthetic minor to avoid NSR) OAC rule 3745-35-07(B) (synthetic minor to avoid Title V)	<p>Emissions shall not exceed, as a 12-month rolling summation:</p> <p>15.75 tons of VOC from coating material usage.</p> <p>See Section B.1 below.</p> <p>VOC emissions from cleanup material usage in emissions units K009, K010, K011, K012, K013, K014, and K015 combined shall not exceed 5.88 tons per rolling, 12-month summation.</p> <p>See Section B.3 below.</p>
OAC rule 3745-31-05(C) (synthetic minor to avoid Title BAT)	<p>Particulate emissions (PE) emissions shall not exceed 2.31 tons per year from coating operations.</p> <p>See Section A.2.c below.</p>

**Issued: 6/26/2007**

OAC rule 3745-35-07(B) (synthetic minor to avoid Title V)	The combined total hazardous air pollutants (HAP) emissions shall not exceed 9.9 tons per rolling 12-month period for any single HAP and 24.9 tons per rolling 12-month period for all HAPs from all coating and cleanup materials used in units K009, K010, K011, K012, K013, K014, and K015 combined.
OAC rule 3745-17-07(A)(1)	Visible PE from any stack serving this emissions unit shall not exceed 20 % opacity, as a six-minute average, except as specified by rule.
OAC rule 3745-17-11(A)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to the requirement specified in OAC rule 3745-31-05(C).
OAC rule 3745-21-09(U)(1)(d)	See Section B.2 below.

## 2. Additional Terms and Conditions

- 2.a** The hourly VOC emission limitation is established to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to develop monitoring, record keeping and/or reporting requirements to ensure compliance with these limits.
- 2.b** Per the rule, the allowable hourly emissions limitation for PE is greater than the potential to emit for this emissions unit without control. Therefore, no additional monitoring, recordkeeping and/or reporting is necessary to ensure compliance with this limit.
- 2.c** Permit to Install 01-12091 for this air contaminant source takes into account the following voluntary restrictions (including the use of any applicable air pollution control equipment) as proposed by the permittee for the purpose of avoiding Best Available Technology (BAT) requirements under rule 3745-31-05(A)(3):

Fabric filter for particulate emissions.

## B. Operational Restrictions

1. The maximum annual coating usage for K015 shall not exceed 9000 gallons applied based upon a rolling, 12-month summation of the coating usage figures.

To ensure enforceability during the first 12 calendar months of operation following the

**Issued: 6/26/2007**

issuance of this permit, the permittee shall not exceed the coating usage levels specified in the following table:

<u>Month(s)</u>	<u>Maximum Allowable Cumulative Coating Usage</u>
1	750
1-2	1500
1-3	2250
1-4	3000
1-5	3750
1-6	4500
1-7	5250
1-8	6000
1-9	6750
1-10	7500
1-11	8250
1-12	9000

After the first 12 calendar months of operation following the issuance of this permit, compliance with the annual coating usage limitation shall be based upon a rolling, 12-month summation of the coating usage figures.

2. The maximum coating content shall not exceed 3.5 lbs VOC per gallon, excluding water and exempt solvents.
3. The maximum annual cleanup material usage for emission units K009, K010, K011, K012, K013, K014, and K015 combined shall not exceed 1,623 gallons, based upon a rolling, 12-month summation of the cleanup material usage.

To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed the cleanup material usage levels specified in the following table:

<u>Month(s)</u>	<u>Maximum Allowable Cumulative Cleanup Material Usage</u>
1	136
1-2	272
1-3	408

Emissions Unit ID: **K015**

1-4	544
1-5	680
1-6	816
1-7	952
1-8	1,088
1-9	1,224
1-10	1,360
1-11	1,496
1-12	1,623

After the first 12 calendar months of operation following the issuance of this permit, compliance with the annual cleanup material usage limitation shall be based upon a rolling, 12-month summation of the cleanup material usage figures.

4. The maximum cleanup content shall not exceed 7.25 lbs VOC per gallon, excluding water and exempt solvents.
5. The permittee shall operate the dry filtration system whenever this emissions unit is in operation, to control particulate emissions.

### **C. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information each day for emissions unit K015:
  - a. the name and identification number of each coating applied;
  - b. the volume, in gallons, of each coating applied; and
  - c. the total volume, in gallons, of all of the coatings applied.
2. The permittee shall collect and record the following information each month for emissions unit K015:
  - a. the name and identification of each coating material, as applied;
  - b. the VOC content for each coating material in pounds of VOC per gallon of coating material, excluding water and exempt solvents, as applied;
  - c. the number of gallons applied, of each coating material, excluding water and exempt solvents, as applied;

**Issued: 6/26/2007**

- d. the rolling, 12-month summation of the coating usage, in gallons, excluding water and exempt solvents;
  - e. the total VOC emissions rate for all coating materials, in pounds per month (b x c); and
  - f. the total VOC emissions rate for all coating materials, in pounds per rolling, 12-month summation (b x d).
3. The permittee shall collect and record the following information each month for emissions units K009, K010, K011, K012, K013, K014, and K015:
- a. the name and identification of each cleanup material, as applied;
  - b. the VOC content for each cleanup material in pounds of VOC per gallon of cleanup material, excluding water and exempt solvents, as applied;
  - c. the number of gallons applied, of each cleanup material, excluding water and exempt solvents, as applied;
  - d. the rolling, 12-month summation of the cleanup material usage, in gallons, excluding water and exempt solvents;
  - e. the total VOC emission rate for all cleanup materials, in pounds per month (b x c); and
  - f. the total VOC emissions rate for all cleanup materials, in pounds per rolling, 12-month rolling summation for K009, K010, K011, K012, K013, K014, and K015 combined.
4. The permittee shall collect and record the following information each month for emissions units K009, K010, K011, K012, K013, K014, and K015:
- a. the name and identification number of each coating, as applied;
  - b. the individual HAP<sup>1</sup> content for each HAP of each coating in pounds of individual HAP per gallon of coating, as applied;
  - c. the total combined HAP content for each HAP of each coating in pounds of

**Issued: 6/26/2007**

- combined HAPs per gallon of coating, as applied (sum of all individual HAP contents from b);
- d. the number of gallons of each coating employed;
  - e. the name and identification of each cleanup material employed;
  - f. the individual HAP content for each HAP of each cleanup material in pounds of individual HAP per gallon cleanup material, as applied;
  - g. the total combined HAP content of each cleanup material in pounds of combined HAPs per gallon of cleanup material, as applied (sum of all individual HAP contents from f);
  - h. the number of gallons of each cleanup material employed;
  - i. the total individual HAP emissions for each HAP from all coating and cleanup material in pounds or tons per rolling, 12-month period (for each HAP the sum of b times d for each coating and the sum of f times h for each cleanup material);
  - j. the total combined HAPs emissions from all coating and cleanup materials employed, in pounds or tons per month and pounds or tons per rolling, 12-month period (the sum of c times d for each coating plus the sum of g times h for each cleanup material);
  - k. the updated rolling, 12-month summation of emissions for each individual HAP in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and
  - l. the updated rolling, 12-month summation of emissions for total combined HAPs in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

<sup>1</sup>A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA field office or local air agency contact. Material Safety Data Sheets typically include a listing of the solvents contained in the coatings or clean materials. This information does not have to be kept on a line-by-line basis.

- 5. The permit to install for this emissions unit (K015) was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the

Emissions Unit ID: **K015**

emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the ISCST3 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the ISCST3 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: n-butanol

TLV (mg/m<sup>3</sup>): 63.63

Maximum Hourly Emission Rate (g/s): 0.33

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m<sup>3</sup>): 467MAGLC (ug/m<sup>3</sup>): 1,443

Pollutant: toluene

TLV (mg/m<sup>3</sup>): 188.40

Maximum Hourly Emission Rate (g/s): 1.31

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m<sup>3</sup>): 1,853MAGLC (ug/m<sup>3</sup>): 4,485

Pollutant: methyl ethyl ketone

TLV (mg/m<sup>3</sup>): 589.77

Maximum Hourly Emission Rate (g/s): 2.61

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m<sup>3</sup>): 2,998MAGLC (ug/m<sup>3</sup>): 14,042

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value

**Issued: 6/26/2007**

previously modeled;

- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

#### **D. Reporting Requirements**

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.

Emissions Unit ID: **K015**

2. The permittee shall notify Ohio EPA, Central District Office in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to Ohio EPA, Central District Office within 45 days after the exceedance occurs.
3. The permittee shall submit quarterly deviation (excursion) reports which identify all exceedances of the following:
  - a. the VOC content limit for coating materials;
  - b. the VOC content limit for cleanup materials;
  - c. the rolling, 12-month coating usage limitation for K015;
  - d. the rolling, 12-month VOC emission limitation for K015;
  - e. the rolling, 12-month cleanup usage limitation for K009, K010, K011, K012, K013, K014, and K015 combined;
  - f. the rolling, 12-month VOC emission limitation, from cleanup material, for K009, K010, K011, K012, K013, K014, and K015 combined;
  - g. the rolling, 12-month total individual HAP emission limitation for K009, K010, K011, K012, K013, K014, and K015 combined; and
  - h. the rolling, 12-month total combined HAPs emissions limitation for K009, K010, K011, K012, K013, K014, and K015 combined.
4. These quarterly deviation (excursion) reports shall be submitted to the Ohio EPA Central District Office by January 31, April 30, July 31 and October 31 of each year and shall cover the previous calendar quarter. If no deviations occurred during a calendar quarter, the permittee shall submit a report which states that no deviations occurred during the calendar quarter.
5. The permittee shall submit annual reports which specify the VOC and individual and combined HAP emissions from this emissions unit for the previous calendar year. The reports shall be submitted by April 15 of each year. This reporting requirement may be satisfied by including and identifying the specific emission data from this emissions unit in the annual Fee Emission Report.

Issued: 6/26/2007

**E. Testing Requirements**

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following methods:

- a. Emissions Limitation:  
17.5 lbs/hr of VOC from coating operations.

Applicable Compliance Method:

Compliance has been demonstrated by multiplying the maximum hourly coating usage rate of 5.0 gallons/hour by the maximum VOC content of 3.5 lbs/gallon.

- b. Emissions Limitation:  
22.0 lbs/hr of VOC from cleanup operations.

Applicable Compliance Method:

Compliance has been demonstrated by multiplying the maximum hourly cleanup usage rate of 3.0 gallons/hour by the maximum VOC content of 7.25 lbs/gallon.

- c. Emission Limitation:  
VOC emissions from coatings shall not exceed 15.75 tons, as a 12-month rolling summation.

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements as specified in Section C.1.

- d. Emissions Limitation:  
3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents.

Applicable Compliance Method:

Compliance with the VOC content of the coatings applied in this emissions unit shall be determined through monthly record keeping, as specified in Sections C.1. Formulation data from the coating manufacturer and/or, if required, USEPA Method 24 (or an alternative approved method) shall be used to determine the volatile organic compound content of the coatings, to be used in the calculation of emissions.

- e. Emissions Limitation:  
7.25 pounds of VOC per gallon of cleanup material, excluding water and exempt

Emissions Unit ID: **K015**

solvents.

Applicable Compliance Method:

Compliance with the VOC content of the cleanup material applied in this emissions unit shall be determined through monthly record keeping, as specified in Sections C.2. Formulation data from the cleanup material manufacturer and/or, if required, USEPA Method 24 (or an alternative approved method) shall be used to determine the volatile organic compound content of the cleanup materials, to be used in the calculation of emissions.

- f. Emission Limitation:  
PE shall not exceed 2.31 ton per year.

Applicable Compliance Method:

The annual emission limitation was established by multiplying the hourly limitation by 8,760 hours/year and then dividing by 2,000 pounds/ton. Compliance with the annual emission limitation may be assumed as long as compliance with the hourly emission limitation is maintained.

- g. Emission Limitation:  
VOC emissions from cleanup materials applied in emissions units K009, K010, K011, K012, K013, K014, and K015 combined shall not exceed 5.88 tons per rolling 12-month summation.

Applicable Compliance Method:

Compliance with the rolling 12-month limitation shall be established by the record keeping found in Section C.2.

- h. Emission Limitation:  
The individual HAP emissions shall not exceed 9.9 tons per rolling 12-month period for all single HAP from all coatings and cleanup materials used in units K009, K010, K011, K012, K013, K014, and K015 combined.

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements specified in Section C.3 of this permit.

- i. Emission Limitation:  
The combined total HAPs emissions shall not exceed 24.9 tons per rolling 12-month period for all HAP from all coatings and cleanup materials used in units K009, K010, K011, K012, K013, K014, and K015 combined.

**Issued: 6/26/2007**

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements specified in Section C.3 of this permit.

**F. Miscellaneous Requirements**

1. The permittee shall permanently shut down emission unit K006, previously permitted in PTI 01-08944, prior to the installation of emission unit K015 which is contained in this permit to install.

Issued: 6/26/2007

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)****A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

**Operations, Property, and/or Equipment - (P004) - Building No. 11 - Blast Booth. The terms of this permit supercede those identified in PTI No. 01-08944 issued August 9, 2005.**

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(A)(3)	Particulate emissions (PE) shall not exceed 0.02 lb/hr and 0.1 ton PE/yr.  Visible PE shall not exceed 5% opacity as a 6-minute average.  See A.2.a
OAC rule 3745-17-07(A)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
OAC rule 3745-17-11(B)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

**2. Additional Terms and Conditions**

- 2.a The hourly and annual PE emission limitations were established to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to develop monitoring, record keeping and/or reporting requirements to ensure compliance with these limits.

**B. Operational Restrictions**

1. The pressure drop across the cartridge filter shall be maintained within the range of 2-4 inches of water while the emissions unit is in operation.

**C. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the cartridge filter while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on weekly basis.

#### D. Reporting Requirements

1. The permittee shall submit pressure drop deviation (excursion) reports that identify that all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above. These reports shall be submitted to Ohio EPA Central District Office within 30 days after the deviation occurs.

#### E. Testing Requirements

1. Compliance with the emission limitations in Section A.1 of the terms and conditions of this permit shall be determined in accordance with the following methods:

- a. Emission Limitation:  
0.02 lb PE/hr and 0.1 TPY PE

Applicable Compliance Method:

If required, compliance may be demonstrated by calculation using an emission factor of 0.69 lb PE / 1000 lbs of abrasive \* multiplied by the maximum abrasive usage of 3000 lbs / hr multiplied by the control efficiency (1 - 0.99).

The annual limitation was developed by multiplying the lb/hr limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

\* Emission factor, 0.69 lb PE / 1000 lbs of abrasive, is obtained from USEPA's AP-42, Volume I, Fifth Edition, Section 13.2.6, "Abrasive Blasting", Table 13.2.6-1, September 1997.

- b. Emission Limitation:  
Visible PE shall not exceed 5% opacity as a 6-minute average

Applicable Compliance Method:

If required, compliance shall be determined in accordance with the test method

**Issued: 6/26/2007**

and procedures in Method 9 of 40 CFR Part 60, Appendix A.

**F. Miscellaneous Requirements**

None

Emissions Unit ID: P004

SIC CODE 3443 SCC CODE 40200110 EMISSIONS UNIT ID K009

EMISSIONS UNIT DESCRIPTION Building No. 17 - Shop Floor Painting. The terms of this permit supercede those identified in PTI No. 01-08944 issued August 9, 2005.

DATE INSTALLED July 2005

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			0.13 lb/hr	0.6
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds	non-attainment			16.0 lbs/hr	3.2
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? No. NESHAP? No. PSD? No. OFFSET POLICY? No.

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

**Enter Determination:** BAT is compliance with emissions limitations, and the rolling 12-month HAPs limit. Monitoring and record keeping is required to demonstrate ongoing compliance with limits. The basis for the determination is OAC rules 3745-31-05 (A)(3), 3745-21-09 (U)(1)(d), 3745-35-07 (B), and 3745-31-05 (C).

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? Yes.

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ N/A

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? X YES      NO

IDENTIFY THE AIR CONTAMINANTS: xylene and toluene

Emissions Unit ID: P004

SIC CODE 3443 SCC CODE 40200110 EMISSIONS UNIT ID K010

EMISSIONS UNIT DESCRIPTION Building No. 11 - Shop Floor Painting. The terms of this permit supercede those identified in PTI No. 01-08944 issued August 9, 2005.

DATE INSTALLED July 2005

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			0.13 lb/hr	0.6
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds	non-attainment			10.0 lbs/hr	3.2
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? No. NESHAP? No. PSD? No. OFFSET POLICY? No.

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

**Enter Determination:** BAT is compliance with emissions limitations, and the rolling 12-month HAPs limit. Monitoring and record keeping is required to demonstrate ongoing compliance with limits. The basis for the determination is OAC rules 3745-31-05 (A)(3), 3745-21-09 (U)(1)(d), 3745-35-07 (B), and 3745-31-05 (C).

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? Yes.

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ N/A

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? X YES      NO

IDENTIFY THE AIR CONTAMINANTS: xylene and toluene

Emissions Unit ID: **P004**

Issued: 6/26/2007

SIC CODE 3443 SCC CODE 40200110 EMISSIONS UNIT ID K011  
 EMISSIONS UNIT DESCRIPTION Building No. 11 - Primer Paint Booth. The terms of this permit supercede those identified in PTI No. 01-08944 issued August 9, 2005.  
 DATE INSTALLED July 2005

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			0.2 lb/hr	0.9
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds	non-attainment			7.0 lbs/hr	15.7
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? No. NESHAP? No. PSD? No. OFFSET POLICY? No.

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

**Enter Determination:** BAT is compliance with emissions limitations, and the rolling 12-month HAPs limit. Monitoring and record keeping is required to demonstrate ongoing compliance with limits. The basis for the determination is OAC rules 3745-31-05 (A)(3), 3745-21-09 (U)(1)(d), 3745-35-07 (B), and 3745-31-05 (C).

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? Yes.

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ N/A

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? X YES      NO

IDENTIFY THE AIR CONTAMINANTS: xylene and toluene

Emissions Unit ID: P004

SIC CODE 3443 SCC CODE 40200110 EMISSIONS UNIT ID K012

EMISSIONS UNIT DESCRIPTION Building No. 11 - Finishing Paint Booth. The terms of this permit supercede those identified in PTI No. 01-08944 issued August 9, 2005.

DATE INSTALLED July 2005

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			0.2 lb/hr	0.8
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds	non-attainment			7.0 lb/hr	15.7
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? No. NESHAP? No. PSD? No. OFFSET POLICY? No.

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

**Enter Determination:** BAT is compliance with emissions limitations, and the rolling 12-month HAPs limit. Monitoring and record keeping is required to demonstrate ongoing compliance with limits. The basis for the determination is OAC rules 3745-31-05 (A)(3), 3745-21-09 (U)(1)(d), 3745-35-07 (B), and 3745-31-05 (C).

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? Yes.

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ N/A

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? X YES      NO

IDENTIFY THE AIR CONTAMINANTS: xylene and toluene

Emissions Unit ID: P004

SIC CODE 3443 SCC CODE 40200110 EMISSIONS UNIT ID K013

EMISSIONS UNIT DESCRIPTION Building No. 15 - Paint Booth. The terms of this permit supercede those identified in PTI No. 01-08944 issued August 9, 2005.

DATE INSTALLED July 2005

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			0.3 lb/hr	1.5
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds	non-attainment			8.8 lb/hr	19.6
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? No. NESHAP? No. PSD? No. OFFSET POLICY? No.

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

**Enter Determination:** BAT is compliance with emissions limitations, and the rolling 12-month HAPs limit. Monitoring and record keeping is required to demonstrate ongoing compliance with limits. The basis for the determination is OAC rules 3745-31-05 (A)(3), 3745-21-09 (U)(1)(d), 3745-35-07 (B), and 3745-31-05 (C).

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? Yes.

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ N/A

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? X YES      NO

IDENTIFY THE AIR CONTAMINANTS: xylene and toluene

Emissions Unit ID: **P004**

Issued: 6/26/2007

SIC CODE 3443 SCC CODE 40200110 EMISSIONS UNIT ID K014  
 EMISSIONS UNIT DESCRIPTION Building No. 15 - Shop Floor Painting. The terms of this permit supercede those identified in PTI No. 01-08944 issued August 9, 2005.  
 DATE INSTALLED July 2005

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			2.7 lb/hr	11.8
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds	non-attainment			16.0 lb/hr	3.2
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? No. NESHAP? No. PSD? No. OFFSET POLICY? No.

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

**Enter Determination:** BAT is compliance with emissions limitations, and the rolling 12-month HAPs limit. Monitoring and record keeping is required to demonstrate ongoing compliance with limits. The basis for the determination is OAC rules 3745-31-05 (A)(3), 3745-21-09 (U)(1)(d), 3745-35-07 (B), and 3745-31-05 (C).

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? Yes.  
 OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ N/A

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? X YES      NO

IDENTIFY THE AIR CONTAMINANTS: xylene and toluene

Emissions Unit ID: P004

SIC CODE 3443 SCC CODE 40200110 EMISSIONS UNIT ID K015  
 EMISSIONS UNIT DESCRIPTION Building 18 - Paint Booth.  
 DATE INSTALLED August 2006

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			N/A	less than 10
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds	non-attainment			17.5 lb/hr	15.8
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? No. NESHAP? No. PSD? No. OFFSET POLICY? No.

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

**Enter Determination:** BAT is compliance with emissions limitations, and the rolling 12-month HAPs limit. Monitoring and record keeping is required to demonstrate ongoing compliance with limits. The basis for the determination is OAC rules 3745-31-05 (A)(3), 3745-21-09 (U)(1)(d), 3745-35-07 (B), and 3745-31-05 (C).

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? Yes.

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ N/A

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? X YES      NO

IDENTIFY THE AIR CONTAMINANTS: xylene and toluene

Emissions Unit ID: **P004****Issued: 6/26/2007**

SIC CODE 3443 SCC CODE 40200110 EMISSIONS UNIT ID P004  
 EMISSIONS UNIT DESCRIPTION Building No. 11 - Blast Booth. The terms of this permit supercede those identified in PTI No. 01-08944 issued August 9, 2005.  
 DATE INSTALLED July 2005

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			0.02 lb/hr	0.1
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? No.

NESHAP? No.

PSD? No.

OFFSET POLICY? No.

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

**Enter Determination:** BAT is compliance with emissions limitations, and the rolling 12-month HAPs limit. Monitoring and record keeping is required to demonstrate ongoing compliance with limits. The basis for the determination is OAC rules 3745-31-05 (A)(3), 3745-21-09 (U)(1)(d), 3745-35-07 (B), and 3745-31-05 (C).

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? No.OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ N/A**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? \_\_\_\_\_ YES \_\_\_\_\_ NO

IDENTIFY THE AIR CONTAMINANTS: \_\_\_\_\_