



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL  
FRANKLIN COUNTY**

**CERTIFIED MAIL**

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center  
P.O. Box 1049

**Application No: 01-08455**

**DATE: 9/27/2001**

Genpak LLC  
Cathy Hager  
4495 Hampton Woods Ct  
Columbus, OH 43230

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission  
236 East Town Street, Room 300  
Columbus, Ohio 43215

Very truly yours,

Thomas G. Rigo, Manager  
Field Operations and Permit Section  
Division of Air Pollution Control

cc: USEPA

CDO



STATE OF OHIO ENVIRONMENTAL PROTECTION AGENCY

---

**Permit To Install  
Terms and Conditions**

**Issue Date: 9/27/2001  
Effective Date: 9/27/2001**

---

**FINAL PERMIT TO INSTALL 01-08455**

Application Number: 01-08455  
APS Premise Number: 0125042477  
Permit Fee: **\$2000**  
Name of Facility: Genpak LLC  
Person to Contact: Cathy Hager  
Address: 4495 Hampton Woods Ct  
Columbus, OH 43230

Location of proposed air contaminant source(s) [emissions unit(s)]:

**800 Kaderly Dr  
Columbus, Ohio**

Description of proposed emissions unit(s):

**Silo.**

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

## Part I - GENERAL TERMS AND CONDITIONS

### A. Permit to Install General Terms and Conditions

#### 1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

#### 2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

#### 3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

#### 4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized

Genpak LLC

PTI Application: 01-08455

Issued: 9/27/2001

Facility ID: 0125042477

representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

**5. Scheduled Maintenance/Malfunction Reporting**

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

**6. Permit Transfers**

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

**7. Air Pollution Nuisance**

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

**8. Termination of Permit to Install**

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

**9. Construction of New Sources(s)**

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio

Genpak LLC

PTI Application: 01-08455

Issued: 9/27/2001

Facility ID: 0125042477

Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

**10. Public Disclosure**

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

**11. Applicability**

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit to Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

**12. Best Available Technology**

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

**13. Source Operation and Operating Permit Requirements After Completion of Construction**

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within thirty (30) days after commencing operation of the emissions unit(s) covered by this permit.

Genpak LLC  
 PTI Application: 01-08455  
 Issued: 9/27/2001

Facility ID: 0125042477

#### 14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

#### 15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

### B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)**  
**TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
Particulate	12.12

## PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

### A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P001 - CPET virgin material silo number one	OAC rule 3745-31-05(A)(3)	Particulate emissions shall not exceed 0.74 pound per hour and 3.3 tons per year.
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by rule.
	OAC rule 3745-17-11(B)	The emissions limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

### 2. Additional Terms and Conditions

- 2.a The 0.74 pound per hour particulate limitation for this emissions unit was established to reflect the maximum hourly potential to emit. Therefore, it is not necessary to develop recordkeeping and/or reporting requirements to ensure compliance with this limit.

### B. Operational Restrictions

8

**Genpa**

**PTI A**

**Issued: 9/27/2001**

Emissions Unit ID: **P001**

None

**C. Monitoring and/or Recordkeeping Requirements**

a. The permittee shall collect and record the following information on a monthly basis:

i. amount of virgin material processed in this emissions unit;

- ii. the total monthly particulate emissions determined by the following equation:

(monthly virgin material processed in pounds) x (0.1% particulate material\*)

\* Based on particulate analysis performed on August 1, 2001 and submitted with Genpak LLC's permit to install application; and

- iii. the cumulative annual particulate emissions determined by summing the monthly emissions recorded in Section C.1.b. above.

#### **D. Reporting Requirements**

1. The permittee shall submit annual deviation reports if the annual emission limit of 3.3 tons per year of particulate (as recorded in Section C.1.c. above) is exceeded for this emissions unit. These reports shall be submitted by January 31 of each year.

#### **E. Testing Requirements**

1. Compliance with the emission limitations in Section A.I. of these terms and conditions shall be determined in accordance with the following methods:
  - a. Emissions Limitation:  
Particulate emissions from the stack shall not exceed 0.74 pound per hour and 3.3 tons per year.

Applicable Compliance Method:

Compliance with the hourly emission limitation for particulate shall be demonstrated by multiplying the maximum amount of virgin material processed per hour of 744.5 pounds by the percentage of particulate of 0.1%. Compliance with the annual emission limitation shall be demonstrated by the recordkeeping required in Section C.1.b. above.

If required, the permittee shall demonstrate compliance with these emission limitations through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1-4 and Method 5 for particulate emissions. Alternative EPA approved test methods may be used with prior approval from the Ohio EPA.

- li>a. Emission Limitation:  
Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by rule.

10

**Genpa**

**PTI A**

**Issued: 9/27/2001**

Emissions Unit ID: **P001**

Applicable Compliance Method:

If required, compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such appendix existed on July 1, 1996.

**F. Miscellaneous Requirements**

None

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P002 - APET virgin material silo number two	OAC rule 3745-31-05(A)(3)	Particulate emissions shall not exceed 1.51 pounds per hour and 6.6 tons per year.
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by rule.
	OAC rule 3745-17-11(B)	The emissions limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

**2. Additional Terms and Conditions**

- 2.a The 1.51 pounds per hour particulate limitation for this emissions unit was established to reflect the maximum hourly potential to emit. Therefore, it is not necessary to develop recordkeeping and/or reporting requirements to ensure compliance with this limit.

**B. Operational Restrictions**

None

**C. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information on a monthly basis:

- a. amount of virgin material processed in this emissions unit; and
- b. the total monthly particulate emissions determined by the following equation:

(monthly virgin material processed in pounds) x (0.1% particulate material\*)

\* Based on particulate analysis performed on August 1, 2001 and submitted with Genpak LLC's permit to install application; and

- c. the cumulative annual particulate emissions determined by summing the monthly emissions recorded in Section C.1.b. above.

#### **D. Reporting Requirements**

1. The permittee shall submit annual deviation reports if the annual emission limit of 6.6 tons per year of particulate (as recorded in Section C.1.c. above) is exceeded for this emissions unit. These reports shall be submitted by January 31 of each year.

#### **E. Testing Requirements**

1. Compliance with the emission limitations in Section A.I. of these terms and conditions shall be determined in accordance with the following methods:

- a. Emissions Limitation:

Particulate emissions from the stack shall not exceed 1.51 pounds per hour and 6.6 tons per year.

Applicable Compliance Method:

Compliance with the hourly emission limitation for particulate shall be demonstrated by multiplying the maximum amount of virgin material processed per hour of 1510.8 pounds by the percentage of particulate of 0.1%. Compliance with the annual emission limitation shall be demonstrated by the recordkeeping required in Section C.1.b. above.

If required, the permittee shall demonstrate compliance with these emission limitations through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1-4 and Method 5 for particulate emissions. Alternative EPA approved test methods may be used with prior approval from the Ohio EPA.

- b. Emission Limitation:

Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by rule.

**Applicable Compliance Method:**

If required, compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such appendix existed on July 1, 1996.

14

**Genpa**

**PTI A**

**Issued: 9/27/2001**

Emissions Unit ID: **P002**

**F. Miscellaneous Requirements**

None

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P003 - regrind material silo number three with cyclone	OAC rule 3745-31-05(A)(3)	Particulate emissions shall not exceed 0.11 pound per hour and 0.5 ton per year.
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by rule.
	OAC rule 3745-17-11(B)	The emissions limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

**2. Additional Terms and Conditions**

- 2.a The 0.11 pound per hour particulate limitation for this emissions unit was established to reflect the maximum hourly potential to emit. Therefore, it is not necessary to develop recordkeeping and/or reporting requirements to ensure compliance with this limit.

**B. Operational Restrictions**

1. The permittee shall operate the cyclone whenever this emissions unit is in operation.

**C. Monitoring and/or Recordkeeping Requirements**

Emissions Unit ID: P003

1. The permittee shall collect and record the following information on a monthly basis:
  - a. amount of regrind material processed in this emissions unit; and
  - b. the total monthly particulate emissions determined by the following equation:
 

(monthly regrind material processed in pounds) x (0.1% particulate material\*) x (1-.90,  
the control efficiency of the cyclone)

\* Based on particulate analysis performed on August 1, 2001 and submitted with Genpak LLC's permit to install application; and
  - c. the cumulative annual particulate emissions determined by summing the monthly emissions recorded in Section C.1.b. above.

#### D. Reporting Requirements

1. The permittee shall submit annual deviation reports if the annual emission limit of 0.5 ton per year of particulate (as recorded in Section C.1.c. above) is exceeded for this emissions unit. These reports shall be submitted by January 31 of each year.

#### E. Testing Requirements

1. Compliance with the emission limitations in Section A.I. of these terms and conditions shall be determined in accordance with the following methods:
  - a. Emissions Limitation:  
Particulate emissions from the stack shall not exceed 0.11 pound per hour and 0.5 ton per year.

##### Applicable Compliance Method:

Compliance with the hourly emission limitation for particulate shall be demonstrated by multiplying the maximum amount of regrind material processed per hour of 1,055.5 pounds by the percentage of particulate of 0.1%. The resulting uncontrolled emission rate shall multiplied by the control efficiency of the cyclone of 90% (1-.9). Compliance with the annual emission limitation shall be demonstrated by the recordkeeping required in Section C.1.b. above.

If required, the permittee shall demonstrate compliance with these emission limitations through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1-4 and Method 5 for particulate emissions. Alternative EPA approved test

methods may be used with prior approval from the Ohio EPA.

- b. Emission Limitation:  
Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by rule.

Applicable Compliance Method:

If required, compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such appendix existed on July 1, 1996.

**F. Miscellaneous Requirements**

None

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P004 - regrind material silo number four with baghouse	OAC rule 3745-31-05(A)(3)	Particulate emissions shall not exceed 0.01 pound per hour and 0.05 ton per year.
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by rule.
	OAC rule 3745-17-11(B)	The emissions limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

**2. Additional Terms and Conditions**

- 2.a The 0.01 pound per hour particulate limitation was established to reflect the potential to emit for this emissions unit as vented to a baghouse. Therefore, the parametric monitoring of the baghouse as established in the following terms and conditions will ensure compliance with these limits.

**B. Operational Restrictions**

1. The permittee shall operate the baghouse whenever this emissions unit is in operation.
2. The pressure drop across the baghouse shall be maintained within the range of 1.0 to 6.0 inches of

**Genpak LLC**  
**PTI Application: 01 09455**  
**Issued**

**Facility ID: 0125042477**

**Emissions Unit ID: P004**

water while the emissions unit is in operation.

### C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual (s). The permittee shall monitor and record the pressure drop across the baghouse on a biweekly basis while the emissions unit is in operation.
2. The permittee shall collect and record the following information on a monthly basis:
  - a. amount of regrind material processed in this emissions unit; and
  - b. the total monthly particulate emissions determined by the following equation:  
  
(monthly regrind material processed in pounds) x (0.1% particulate material\*) x (1-.99,  
the control efficiency of the baghouse)  
  
\* Based on particulate analysis performed on August 1, 2001 and submitted with Genpak LLC's permit to install application; and
  - c. the cumulative annual particulate emissions determined by summing the monthly emissions recorded in Section C.1.b. above.

### D. Reporting Requirements

1. The permittee shall submit annual deviation (excursion) reports for all exceedances during which the pressure drop across the baghouse did not comply with the allowable range specified in Section II.B.2. above, and any actions taken to return the pressure drop to a compliant operating range. These reports shall be submitted by January 31 of each year.
2. The permittee shall submit annual deviation reports if the annual emission limit of 0.05 ton per year of particulate (as recorded in Section C.1.c. above) is exceeded for this emissions unit. These reports shall be submitted by January 31 of each year.

### E. Testing Requirements

1. Compliance with the emission limitations in Section A.I. of these terms and conditions shall be determined in accordance with the following methods:
  - a. Emissions Limitation:

Particulate emissions from the stack shall not exceed 0.01 pound per hour and 0.05 ton per year.

**Applicable Compliance Method:**

Compliance with the hourly emission limitation for particulate shall be demonstrated by multiplying the maximum amount of regrind material processed per hour of 1,055.5 pounds by the percentage of particulate of 0.1%. The resulting uncontrolled emission rate shall multiplied by the control efficiency of the baghouse of 99% (1-.9). Compliance with the annual emission limitation shall be demonstrated by the recordkeeping required in Section C.1.b. above.

If required, the permittee shall demonstrate compliance with these emission limitations through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1-4 and Method 5 for particulate emissions. Alternative EPA approved test methods may be used with prior approval from the Ohio EPA.

- b. **Emission Limitation:**  
Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by rule.

**Applicable Compliance Method:**

If required, compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such appendix existed on July 1, 1996.

**F. Miscellaneous Requirements**

None

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P005 - regrind material silo number five with cyclone	OAC rule 3745-31-05(A)(3)	Particulate emissions shall not exceed 0.11 pound per hour and 0.5 ton per year.
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by rule.
	OAC rule 3745-17-11(B)	The emissions limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

**2. Additional Terms and Conditions**

- 2.a The 0.11 pound per hour particulate limitation for this emissions unit was established to reflect the maximum hourly potential to emit. Therefore, it is not necessary to develop recordkeeping and/or reporting requirements to ensure compliance with this limit.

**B. Operational Restrictions**

- 1. The permittee shall operate the cyclone whenever this emissions unit is in operation.

**C. Monitoring and/or Recordkeeping Requirements**

- 1. The permittee shall collect and record the following information on a monthly basis:

- a. amount of regrind material processed in this emissions unit; and
- b. the total monthly particulate emissions determined by the following equation:  
  
(monthly regrind material processed in pounds) x (0.1% particulate material\*) x (1-.90,  
the control efficiency of the cyclone)  
  
\* Based on particulate analysis performed on August 1, 2001 and submitted with Genpak  
LLC's permit to install application; and
- c. the cumulative annual particulate emissions determined by summing the monthly emissions  
recorded in Section C.1.b. above.

#### **D. Reporting Requirements**

1. The permittee shall submit annual deviation reports if the annual emission limit of 0.5 ton per year of particulate (as recorded in Section C.1.c. above) is exceeded for this emissions unit. These reports shall be submitted by January 31 of each year.

#### **E. Testing Requirements**

1. Compliance with the emission limitations in Section A.I. of these terms and conditions shall be determined in accordance with the following methods:
  - a. Emissions Limitation:  
Particulate emissions from the stack shall not exceed 0.11 pound per hour and 0.5 ton per year.

##### Applicable Compliance Method:

Compliance with the hourly emission limitation for particulate shall be demonstrated by multiplying the maximum amount of regrind material processed per hour of 1,055.5 pounds by the percentage of particulate of 0.1%. The resulting uncontrolled emission rate shall multiplied by the control efficiency of the cyclone of 90% (1-.9). Compliance with the annual emission limitation shall be demonstrated by the recordkeeping required in Section C.1.b. above.

If required, the permittee shall demonstrate compliance with these emission limitations through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1-4 and Method 5 for particulate emissions. Alternative EPA approved test

methods may be used with prior approval from the Ohio EPA.

- b. Emission Limitation:  
Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by rule.

Applicable Compliance Method:

If required, compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such appendix existed on July 1, 1996.

**F. Miscellaneous Requirements**

None

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P006 - overflow material silo number six with cyclone	OAC rule 3745-31-05(A)(3)	Particulate emissions shall not exceed 0.11 pound per hour and 0.5 ton per year.
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by rule.
	OAC rule 3745-17-11(B)	The emissions limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

**2. Additional Terms and Conditions**

- 2.a The 0.11 pound per hour particulate limitation for this emissions unit was established to reflect the maximum hourly potential to emit. Therefore, it is not necessary to develop recordkeeping and/or reporting requirements to ensure compliance with this limit.

**B. Operational Restrictions**

1. The permittee shall operate the cyclone whenever this emissions unit is in operation.

**C. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information on a monthly basis:

- a. amount of overflow material processed in this emissions unit; and
- b. the total monthly particulate emissions determined by the following equation:  
  
(monthly overflow material processed in pounds) x (0.1% particulate material\*) x (1-.90,  
the control efficiency of the cyclone)  
  
\* Based on particulate analysis performed on August 1, 2001 and submitted with Genpak  
LLC's permit to install application; and
- c. the cumulative annual particulate emissions determined by summing the monthly emissions  
recorded in Section C.1.b. above.

#### **D. Reporting Requirements**

1. The permittee shall submit annual deviation reports if the annual emission limit of 0.5 ton per year of particulate (as recorded in Section C.1.c. above) is exceeded for this emissions unit. These reports shall be submitted by January 31 of each year.

#### **E. Testing Requirements**

1. Compliance with the emission limitations in Section A.I. of these terms and conditions shall be determined in accordance with the following methods:
  - a. Emissions Limitation:  
Particulate emissions from the stack shall not exceed 0.11 pound per hour and 0.5 ton per year.

##### Applicable Compliance Method:

Compliance with the hourly emission limitation for particulate shall be demonstrated by multiplying the maximum amount of overflow material processed per hour of 1,055.5 pounds by the percentage of particulate of 0.1%. The resulting uncontrolled emission rate shall multiplied by the control efficiency of the cyclone of 90% (1-.9). Compliance with the annual emission limitation shall be demonstrated by the recordkeeping required in Section C.1.b. above.

If required, the permittee shall demonstrate compliance with these emission limitations through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1-4 and Method 5 for particulate emissions. Alternative EPA approved test

methods may be used with prior approval from the Ohio EPA.

- b. Emission Limitation:  
Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by rule.

Applicable Compliance Method:

If required, compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such appendix existed on July 1, 1996.

**F. Miscellaneous Requirements**

None

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P007 - regrind silo number seven with cyclone	OAC rule 3745-31-05(A)(3)	Particulate emissions shall not exceed 0.11 pound per hour and 0.5 ton per year.
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by rule.
	OAC rule 3745-17-11(B)	The emissions limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

**2. Additional Terms and Conditions**

- 2.a The 0.11 pound per hour particulate limitation for this emissions unit was established to reflect the maximum hourly potential to emit. Therefore, it is not necessary to develop recordkeeping and/or reporting requirements to ensure compliance with this limit.

**B. Operational Restrictions**

1. The permittee shall operate the cyclone whenever this emissions unit is in operation.

**C. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information on a monthly basis:

- a. amount of regrind material processed in this emissions unit;
- b. the total monthly particulate emissions determined by the following equation:  
  
(monthly regrind material processed in pounds) x (0.1% particulate material\*) x (1-.90,  
the control efficiency of the cyclone)  
  
\* Based on particulate analysis performed on August 1, 2001 and submitted with Genpak  
LLC's permit to install application; and
- c. the cumulative annual particulate emissions determined by summing the monthly emissions  
recorded in Section C.1.b. above.

#### **D. Reporting Requirements**

1. The permittee shall submit annual deviation reports if the annual emission limit of 0.5 ton per year of particulate (as recorded in Section C.1.c. above) is exceeded for this emissions unit. These reports shall be submitted by January 31 of each year.

#### **E. Testing Requirements**

1. Compliance with the emission limitations in Section A.I. of these terms and conditions shall be determined in accordance with the following methods:
  - a. Emissions Limitation:  
Particulate emissions from the stack shall not exceed 0.11 pound per hour and 0.5 ton per year.

##### Applicable Compliance Method:

Compliance with the hourly emission limitation for particulate shall be demonstrated by multiplying the maximum amount of regrind material processed per hour of 1,055.5 pounds by the percentage of particulate of 0.1%. The resulting uncontrolled emission rate shall multiplied by the control efficiency of the cyclone of 90% (1-.9). Compliance with the annual emission limitation shall be demonstrated by the recordkeeping required in Section C.1.b. above.

If required, the permittee shall demonstrate compliance with these emission limitations through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1-4 and Method 5 for particulate emissions. Alternative EPA approved test

methods may be used with prior approval from the Ohio EPA.

- b. Emission Limitation:  
Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by rule.

Applicable Compliance Method:

If required, compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such appendix existed on July 1, 1996.

**F. Miscellaneous Requirements**

None

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P008 - APET regrind material silo number eight with baghouse	OAC rule 3745-31-05(A)(3)	Particulate emissions shall not exceed 0.01 pound per hour and 0.06 ton per year.
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by rule.
	OAC rule 3745-17-11(B)	The emissions limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

**2. Additional Terms and Conditions**

- 2.a The 0.01 pound per hour particulate limitation was established to reflect the potential to emit for this emissions unit as vented to a baghouse. Therefore, the parametric monitoring of the baghouse as established in the following terms and conditions will ensure compliance with these limits.

**B. Operational Restrictions**

1. The permittee shall operate the baghouse whenever this emissions unit is in operation.
2. The pressure drop across the baghouse shall be maintained within the range of 1.0 to 6.0 inches of water while the emissions unit is in operation.

32

**Genpa**

**PTI A**

**Issued: 9/27/2001**

Emissions Unit ID: **P008**

### C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual (s). The permittee shall monitor and record the pressure drop across the baghouse on a biweekly basis while the emissions unit is in operation.
2. The permittee shall collect and record the following information on a monthly basis:
  - a. amount of regrind material processed in this emissions unit; and
  - b. the total monthly particulate emissions determined by the following equation:  
  
(monthly regrind material processed in pounds) x (0.1% particulate material\*) x (1-.99,  
the control efficiency of the baghouse)  
  
\* Based on particulate analysis performed on August 1, 2001 and submitted with Genpak LLC's permit to install application; and
  - c. the cumulative annual particulate emissions determined by summing the monthly emissions recorded in Section C.1.b. above.

### D. Reporting Requirements

1. The permittee shall submit annual deviation (excursion) reports for all exceedances during which the pressure drop across the baghouse did not comply with the allowable range specified in Section II.B.2. above, and any actions taken to return the pressure drop to a compliant operating range. These reports shall be submitted by January 31 of each year.
2. The permittee shall submit annual deviation reports if the annual emission limit of 0.06 ton per year of particulate (as recorded in Section C.1.c. above) is exceeded for this emissions unit. These reports shall be submitted by January 31 of each year.

### E. Testing Requirements

1. Compliance with the emission limitations in Section A.I. of these terms and conditions shall be determined in accordance with the following methods:
  - a. Emissions Limitation:

Particulate emissions from the stack shall not exceed 0.01 pound per hour and 0.06 ton per year.

**Applicable Compliance Method:**

Compliance with the hourly emission limitation for particulate shall be demonstrated by multiplying the maximum amount of regrind material processed per hour of 1,289.2 pounds by the percentage of particulate of 0.1%. The resulting uncontrolled emission rate shall multiplied by the control efficiency of the baghouse of 99% (1-.9). Compliance with the annual emission limitation shall be demonstrated by the recordkeeping required in Section C.1.b. above.

If required, the permittee shall demonstrate compliance with these emission limitations through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1-4 and Method 5 for particulate emissions. Alternative EPA approved test methods may be used with prior approval from the Ohio EPA.

- b. **Emission Limitation:**  
Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by rule.

**Applicable Compliance Method:**

If required, compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such appendix existed on July 1, 1996.

**F. Miscellaneous Requirements**

None

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P009 - regrind material silo with baghouse	OAC rule 3745-31-05(A)(3)	Particulate emissions shall not exceed 0.01 pound per hour and 0.05 ton per year.
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by rule.
	OAC rule 3745-17-11(B)	The emissions limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

**2. Additional Terms and Conditions**

- 2.a The 0.01 pound per hour particulate limitation was established to reflect the potential to emit for this emissions unit as vented to a baghouse. Therefore, the parametric monitoring of the baghouse as established in the following terms and conditions will ensure compliance with these limits.

**B. Operational Restrictions**

- 1. The permittee shall operate the baghouse whenever this emissions unit is in operation.
- 2. The pressure drop across the baghouse shall be maintained within the range of 1.0 to 6.0 inches of water while the emissions unit is in operation.

36

**Genpa**

**PTI A**

**Issued: 9/27/2001**

Emissions Unit ID: **P009**

### C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual (s). The permittee shall monitor and record the pressure drop across the baghouse on a biweekly basis while the emissions unit is in operation.
2. The permittee shall collect and record the following information on a monthly basis:
  - a. amount of regrind material processed in this emissions unit; and
  - b. the total monthly particulate emissions determined by the following equation:  
  
(monthly regrind material processed in pounds) x (0.1% particulate material\*) x (1-.99,  
the control efficiency of the baghouse)  
  
\* Based on particulate analysis performed on August 1, 2001 and submitted with Genpak LLC's permit to install application; and
  - c. the cumulative annual particulate emissions determined by summing the monthly emissions recorded in Section C.1.b. above.

### D. Reporting Requirements

1. The permittee shall submit annual deviation (excursion) reports for all exceedances during which the pressure drop across the baghouse did not comply with the allowable range specified in Section II.B.2. above, and any actions taken to return the pressure drop to a compliant operating range. These reports shall be submitted by January 31 of each year.
2. The permittee shall submit annual deviation reports if the annual emission limit of 0.05 ton per year of particulate (as recorded in Section C.1.c. above) is exceeded for this emissions unit. These reports shall be submitted by January 31 of each year.

### E. Testing Requirements

1. Compliance with the emission limitations in Section A.I. of these terms and conditions shall be determined in accordance with the following methods:
  - a. Emissions Limitation:

Genpak LLC  
PTI Application: 01 09155  
Issued

Facility ID: 0125042477

Emissions Unit ID: P009

Particulate emissions from the stack shall not exceed 0.01 pound per hour and 0.05 ton per year.

Applicable Compliance Method:

Compliance with the hourly emission limitation for particulate shall be demonstrated by multiplying the maximum amount of regrind material processed per hour of 1,055.5 pounds by the percentage of particulate of 0.1%. The resulting uncontrolled emission rate shall multiplied by the control efficiency of the baghouse of 99% (1-.9). Compliance with the annual emission limitation shall be demonstrated by the recordkeeping required in Section C.1.b. above.

If required, the permittee shall demonstrate compliance with these emission limitations through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1-4 and Method 5 for particulate emissions. Alternative EPA approved test methods may be used with prior approval from the Ohio EPA.

- b. Emission Limitation:  
Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by rule.

Applicable Compliance Method:

If required, compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such appendix existed on July 1, 1996.

#### F. Miscellaneous Requirements

None

## PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

### A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P010 - APET regrind material silo number ten with baghouse	OAC rule 3745-31-05(A)(3)	Particulate emissions shall not exceed 0.01 pound per hour and 0.06 ton per year.
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by rule.
	OAC rule 3745-17-11(B)	The emissions limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

### 2. Additional Terms and Conditions

- 2.a The 0.01 pound per hour particulate limitation was established to reflect the potential to emit for this emissions unit as vented to a baghouse. Therefore, the parametric monitoring of the baghouse as established in the following terms and conditions will ensure compliance with these limits.

### B. Operational Restrictions

1. The permittee shall operate the baghouse whenever this emissions unit is in operation.
2. The pressure drop across the baghouse shall be maintained within the range of 1.0 to 6.0 inches of

40

**Genpa**

**PTI A**

**Issued: 9/27/2001**

Emissions Unit ID: **P010**

water while the emissions unit is in operation.

### C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual (s). The permittee shall monitor and record the pressure drop across the baghouse on a biweekly basis while the emissions unit is in operation.
2. The permittee shall collect and record the following information on a monthly basis:
  - a. amount of regrind material processed in this emissions unit; and
  - b. the total monthly particulate emissions determined by the following equation:  
  
(monthly regrind material processed in pounds) x (0.1% particulate material\*) x (1-.99,  
the control efficiency of the baghouse)  
  
\* Based on particulate analysis performed on August 1, 2001 and submitted with Genpak LLC's permit to install application; and
  - c. the cumulative annual particulate emissions determined by summing the monthly emissions recorded in Section C.1.b. above.

### D. Reporting Requirements

1. The permittee shall submit annual deviation (excursion) reports for all exceedances during which the pressure drop across the baghouse did not comply with the allowable range specified in Section II.B.2. above, and any actions taken to return the pressure drop to a compliant operating range. These reports shall be submitted by January 31 of each year.
2. The permittee shall submit annual deviation reports if the annual emission limit of 0.06 ton per year of particulate (as recorded in Section C.1.c. above) is exceeded for this emissions unit. These reports shall be submitted by January 31 of each year.

### E. Testing Requirements

1. Compliance with the emission limitations in Section A.I. of these terms and conditions shall be determined in accordance with the following methods:
  - a. Emissions Limitation:

Genpak LLC  
PTI Application: 01 09155  
Issued

Facility ID: 0125042477

Emissions Unit ID: P010

Particulate emissions from the stack shall not exceed 0.01 pound per hour and 0.06 ton per year.

Applicable Compliance Method:

Compliance with the hourly emission limitation for particulate shall be demonstrated by multiplying the maximum amount of regrind material processed per hour of 1,289.2 pounds by the percentage of particulate of 0.1%. The resulting uncontrolled emission rate shall multiplied by the control efficiency of the baghouse of 99% (1-.9). Compliance with the annual emission limitation shall be demonstrated by the recordkeeping required in Section C.1.b. above.

If required, the permittee shall demonstrate compliance with these emission limitations through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1-4 and Method 5 for particulate emissions. Alternative EPA approved test methods may be used with prior approval from the Ohio EPA.

- b. Emission Limitation:  
Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by rule.

Applicable Compliance Method:

If required, compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such appendix existed on July 1, 1996.

## F. Miscellaneous Requirements

None