

Facility ID: 0204010284 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

[Go to Part II for Emissions Unit P001](#)
[Go to Part II for Emissions Unit P002](#)
[Go to Part II for Emissions Unit P003](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0204010284 Emissions Unit ID: P001 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
One hard chromium electroplating tank with a composite mesh-pad system for controlling chromic acid emissions.	40 CFR Part 63 Subpart N OAC 3745-17-07 OAC 3745-17-11 OAC 3745-31-05 PTI 02-12402	The permittee shall not allow the concentration of total chromium in the exhaust gases discharged to the atmosphere to exceed 0.03 mg/dscm. Visible emissions from control system stack not to exceed 20 percent opacity as a six minute average except as provided by rule. Less stringent than limit from OAC 3745-31-05. Less stringent than 40 CFR Part 63 Subpart N.

2. **Additional Terms and Conditions**
 - (a) None

B. Operational Restrictions

1. At all times, including periods of startup, shutdown, and malfunction, the permittee shall operate and maintain any chromium electroplating or anodizing tank, including associated air pollution control devices and monitoring equipment, in a manner consistent with the operation and maintenance plan required by these terms and conditions.
2. Malfunctions shall be corrected as soon as practicable after their occurrence in accordance with the operation and maintenance plan.
3. Determination of whether acceptable operation and maintenance procedures are being used will be based on information available to the appropriate Ohio EPA District Office or local air agency, which may include, but is not limited to, monitoring results; review of the operation and maintenance plan, procedures, and records; and inspection of the emission unit. Based on this information, the appropriate Ohio EPA District Office or local air agency may require that the permittee make changes to the operation and maintenance plan if that plan:
 - a. does not address a malfunction that has occurred;
 - b. fails to provide for the operation of the emission units, the air pollution control techniques, or the control system and process monitoring equipment during a malfunction in a manner consistent with good air pollution practices; or
 - c. does not provide adequate procedures for correcting malfunctioning process equipment, air pollution control techniques, or monitoring equipment as quickly as practicable.
4. The operation and maintenance plan shall be implemented and shall include the following elements:
 - a. The plan shall specify the operation and maintenance criteria for the affected source, the add-on air pollution control device (if such a device is used to comply with the emissions limits), and the process and control system monitoring equipment, and shall include a standardized checklist to document the operation and maintenance of the equipment.
 - b. The O/M plan shall incorporate the following work practice standards for composite mesh pad systems:

- i. Visually inspect the device at least once per quarter to ensure there is proper drainage, no chromic acid buildup on the pads, and no evidence of chemical attack on the structural integrity of the device.
- ii. Visually inspect at least once per quarter the back portion of the mesh pad closest to the fan to ensure there is no breakthrough of chromic acid mist.
- iii. Visually inspect at least once per quarter the ductwork from the tank to the control device to ensure there are no leaks.
- iv. Perform washdown of the composite mesh-pads in accordance with the manufacturer's recommendations.

c. The plan shall specify procedures to be followed to ensure that equipment or process malfunctions due to poor maintenance or other preventable conditions do not occur.

- d. The plan shall include a systematic procedure for identifying malfunctions of process equipment, add-on air pollution control devices, and process and control system monitoring equipment, and for implementing corrective actions to address such malfunctions.
- e. If the operation and maintenance plan fails to address or inadequately addresses an event that meets the characteristics of a malfunction at the time the plan is initially developed, the permittee shall revise the operation and maintenance plan within 45 days after such an event occurs.
- f. If actions taken by the permittee during periods of malfunction are inconsistent with the procedures specified in the operation and maintenance plan, the permittee shall record the actions taken for that event and shall report such actions within 2 working days after commencing actions inconsistent with the plan. This report shall be followed by a letter within 7 working days after the end of the event, unless the permittee makes alternative reporting arrangements, in advance, with the appropriate Ohio EPA District Office or local air agency.

g. The permittee shall keep the written operation and maintenance plan on record after it is developed to be made available for inspection, upon request, by the appropriate Ohio EPA District Office or local air agency for the life of the emission unit. If the operation and maintenance plan is revised, the permittee shall keep previous versions of the plan on record to be made available for inspection, upon request, by the appropriate Ohio EPA District Office or local air agency for a period of five years after each revision to the plan.

- h. The permittee may use applicable standard operating procedure (SOP) manuals, Occupational Safety and Health Administration (OSHA) plans, or other existing plans to meet the operation and maintenance plan requirements as long as the alternative plans meet the requirements.

- 5. The composite mesh-pad system shall be operated within +/- 1 inch of water column of the pressure drop value of 3.03 inches of water column established during the initial performance test.

C. Monitoring and/or Record Keeping Requirements

- 1. Composite mesh-pad (CMP) system monitoring requirements to demonstrate continuous compliance:
 - a. The permittee may conduct multiple performance tests to establish a range of compliant pressure drop values, or may set as the compliance value the average pressure drop measured over the three test runs of one performance test and accept +/- 1 inch of water column from this value as the compliant range.
 - b. The permittee shall monitor and record the pressure drop across the composite mesh-pad system once each day that the emission unit is operating. To be in compliance, the composite mesh-pad system shall be operated within +/- 1 inch of water column of the pressure drop value established during the initial performance test (i.e. 3.03 inches water column), or shall be operated within the range of compliant values for pressure drop established during multiple performance tests.
- 2. The permittee shall fulfill all recordkeeping requirements in the General Provisions to 40 CFR Part 63, according to the applicability of subpart A.
- 3. The permittee also shall maintain the following records:
 - a. Inspection records for the add-on air pollution control device, if such a device is used, and monitoring equipment, to document that the inspection and maintenance required by the work practice standards of this permit have taken place. The record can take the form of a checklist and should identify the device inspected, the date of inspection, a brief description of the working condition of the device during the inspection, and any actions taken to correct deficiencies found during the inspection.
 - b. Records of all maintenance performed on the emissions unit, add-on air pollution control device, and monitoring equipment.
 - c. Records of the occurrence, duration, and cause (if known) of each malfunction of process, add-on air pollution control device, and monitoring equipment.
 - d. Records of actions taken during periods of malfunction when such actions are inconsistent with the operation and maintenance plan.
 - e. Other records, which may take the form of checklists, necessary to demonstrate consistence with the provisions of the operation and maintenance plan.
 - f. Test reports documenting results of all performance tests.
 - g. All measurements as may be necessary to determine the conditions of performance tests.
 - h. Records of monitoring data that are used to demonstrate compliance with the standard including the date and

- b. The permittee continues to comply with all applicable recordkeeping and monitoring requirements of 40 CFR Part 63, subpart A and this permit.
- c. The appropriate Ohio EPA District Office or local air agency does not object to a reduced reporting frequency. The frequency of submitting ongoing compliance status reports may be reduced if the following requirements are met:
 - i. The permittee notifies the appropriate Ohio EPA District Office or local air agency in writing of its intentions to make such a change. The district office may review information concerning the facility's previous performance history during the 5-year recordkeeping period prior to the intended change, or the recordkeeping period since the emission unit's compliance date, whichever is shorter. Records subject to review include performance test results, monitoring data, and evaluations of the permittee's conformance with emission limitations and work practice standards. If the permittee's request is disapproved, the appropriate Ohio EPA District Office or local air agency will notify the permittee in writing within 45 days after receiving notice. This notification will specify the grounds on which the disapproval is based. In the absence of a notice of disapproval within 45 days, approval is automatically granted.
 - ii. If monitoring data show that the emissions unit is not in compliance with the relevant emission limit, the frequency of reporting shall revert to semiannual, and the permittee shall state this exceedance in the ongoing compliance status report for the next reporting period. After demonstrating ongoing compliance with the relevant emission limit for another full year, the permittee may again request approval to reduce the reporting frequency.
- 7. The permittee shall submit a notification of construction or reconstruction as soon as practicable before the construction or reconstruction has commenced to the appropriate Ohio EPA District Office or local air agency which includes the following:
 - a. The permittee's name, title, and address.
 - b. The address (i.e., physical location) or proposed address of the affected emissions unit if different from the permittee's.
 - c. A notification of intention to construct or make any physical or operational changes to an affected emissions unit that may meet or has been determined to meet the criteria for a reconstruction as defined in 40 CFR part 63.2.
 - d. An identification of 40 CFR Part 63, subpart N as the basis for the notification.
 - e. The expected commencement and completion dates of the construction or reconstruction.
 - f. The anticipated date of (initial) startup.
 - g. The type of process operation to be performed (hard or decorative chromium electroplating or chromium anodizing).
 - h. A description of the air pollution control technique to be used to control emissions, such as preliminary design drawings and design capacity if an add-on air pollution control device is used.
 - i. An estimate of emissions based on engineering calculations and vendor information on control device efficiency, expressed in units consistent with the emissions limits of 40 CFR Part 63, subpart N. Calculations of emission estimates should be in sufficient detail to permit assessment of the validity of the calculations.
- 8. If a reconstruction is to occur, the permittee shall submit as soon as practicable the following information to the appropriate Ohio EPA District Office or local air agency:
 - a. A brief description of the affected emissions unit and the components to be replaced.
 - b. A brief description of the present and proposed emission control technique.
 - c. An estimate of the fixed capital cost of the replacements and of constructing a comparable entirely new emissions unit.
 - d. The estimated life of the affected emissions unit after the replacements.
 - e. A discussion of any economic or technical limitations the emissions unit may have in complying with relevant standards or other requirements after proposed replacements. The discussion shall be sufficiently detailed to demonstrate to the appropriate Ohio EPA District Office or local air agency satisfaction that the technical or economic limitations affected the emissions unit ability to comply with the relevant standard and how they do so.
- 9. The permittee shall report to the appropriate Ohio EPA District Office or local air agency the results of any performance test conducted. The report shall be submitted no later than 90 days following the completion of the performance test, and shall be submitted as part of the notification of compliance status report required by this section.

E. Testing Requirements

- 1. All monitoring equipment shall be installed such that representative measurements of emissions or process parameters from the affected emissions unit are obtained. For monitoring equipment purchased from a vendor, verification of the operational status of the monitoring equipment shall include execution of the manufacturer's written specifications or recommendations for installation, operation, and calibration of the system. Specifications for differential pressure measurement devices used to measure pressure drop across a control system shall be in accordance with the manufacturer's accuracy specifications.
- 2. The permittee shall measure the pressure drop across the add-on air pollution control device in accordance with the following guidelines:
 - a. Pressure taps shall be installed at any of the following locations:

- i. At the inlet and outlet of the control system. The inlet tap should be installed in the ductwork just prior to the control device and the corresponding outlet pressure tap should be installed on the outlet side of the control device prior to the blower or on the downstream side of the blower.
 - ii. On each side of the packed bed within the control system or on each side of each mesh pad within the control system.
 - iii. On the front side of the first mesh pad and back side of the last mesh pad within the control system.
 - b. Pressure taps shall be sited at locations that are:
 - i. As free from pluggage as possible and away from any flow disturbances such as cyclonic demisters.
 - ii. Situated such that no air infiltration at the measurement site will occur that could bias the measurement.
 - c. Pressure taps shall be constructed of either polyethylene, polybutylene, or other nonreactive materials.
 - d. Nonreactive plastic tubing shall be used to connect the pressure taps to the device used to measure pressure drop.
 - e. Any of the following pressure gauges can be used to monitor pressure drop: a magnehelic gauge, an included manometer, or a "U" tube manometer.
 - f. Prior to connecting any pressure lines to the pressure gauge(s), each gauge shall be zeroed. No calibration of the pressure gauges is required.
3. Compliance with the total chromium limitation of 0.03 mg/dscm in the exhaust gases discharged to the atmosphere shall be demonstrated using the following test methods, if required by the Ohio EPA:
- a. Method 306 or Method 306A, "Determination of Chromium Emissions From Decorative and Hard Chromium Electroplating and Anodizing Operations" shall be used to determine the chromium concentration from hard chromium electroplating tanks.
 - i. The sampling time and sample volume for each run of Methods 306 and 306A shall be at least 120 minutes and 1.7 dscm (60 dscf), respectively.
 - ii. Methods 306 and 306A allow the measurement of either total chromium or hexavalent chromium emissions. Emissions units using chromic acid baths can demonstrate compliance with the emission limits by measuring either the total chromium or hexavalent chromium concentration. Hence, the hexavalent chromium concentration measured by these methods is equal to the total chromium concentration for the affected operations.
 - b. The California Air Resources Board (CARB) Method 425 may be used to determine the chromium concentration from hard and decorative chromium electroplating tanks and chromium anodizing tanks if the following conditions are met:
 - i. If a colorimetric analysis method is used, the sampling time and volume shall be sufficient to result in 33-66 micrograms of catch in the sampling train.
 - ii. If an Atomic Absorption Graphite Furnace (AAGF) or Ion Chromatography (with a Post-column Reactor (ICPCR) analyses) is used, the sampling time and volume should be sufficient to result in a sample catch that is 5 to 10 times the minimum detection limit of the analytical method (i.e., 1.0 microgram per liter of sample for AAGF and 0.5 microgram per liter of sample for ICPCR).
 - iii. A minimum of three separate runs must be conducted. The other requirements of ?63.7 of 40 CFR Part 63, subpart A must also be met.
4. Compliance with the visible emission limitation shall be determined by using U.S. EPA Method 9, if required by the Ohio EPA.

F. Miscellaneous Requirements

1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0204010284 Emissions Unit ID: P002 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
One hard chromium electroplating tank with a composite mesh-pad system for controlling chromic acid emissions.	40 CFR Part 63 Subpart N OAC 3745-17-07 OAC 3745-17-11 OAC 3745-31-05 PTI 02-12402	The permittee shall not allow the concentration of total chromium in the exhaust gases discharged to the atmosphere to exceed 0.03 mg/dscm. See A.2.a. Visible emissions from composite mesh-pad control system stack not to exceed 20 percent opacity as a six minute average except as provided by rule. Less stringent than limit from OAC 3745-31-05. Less stringent than 40 CFR Part 63 Subpart N.

2. Additional Terms and Conditions

- (a) This unit is presently shutdown. Immediately upon start-up, the permittee shall notify the Ohio EPA, Northeast District Office. The permittee shall include in this notification an "Intent to Test" notification form for conducting the initial performance test required by 40 CFR Part 63, Subpart N, section 63.343 (b)(1). The emission testing shall be conducted to demonstrate compliance with the mass emission limit for total chromium in accordance with Section E.5. of these terms and conditions.

B. Operational Restrictions

1. At all times, including periods of startup, shutdown, and malfunction, the permittee shall operate and maintain any chromium electroplating or anodizing tank, including associated air pollution control devices and monitoring equipment, in a manner consistent with the operation and maintenance plan required by these terms and conditions.
 2. Malfunctions shall be corrected as soon as practicable after their occurrence in accordance with the operation and maintenance plan.
 3. Determination of whether acceptable operation and maintenance procedures are being used will be based on information available to the appropriate Ohio EPA District Office or local air agency, which may include, but is not limited to, monitoring results; review of the operation and maintenance plan, procedures, and records; and inspection of the emission unit. Based on this information, the appropriate Ohio EPA District Office or local air agency may require that the permittee make changes to the operation and maintenance plan if that plan:
 - a. does not address a malfunction that has occurred;
 - b. fails to provide for the operation of the emission units, the air pollution control techniques, or the control system and process monitoring equipment during a malfunction in a manner consistent with good air pollution practices; or
 - c. does not provide adequate procedures for correcting malfunctioning process equipment, air pollution control techniques, or monitoring equipment as quickly as practicable.
 4. The operation and maintenance plan shall be implemented and shall include the following elements:
 - a. The plan shall specify the operation and maintenance criteria for the affected source, the add-on air pollution control device (if such a device is used to comply with the emissions limits), and the process and control system monitoring equipment, and shall include a standardized checklist to document the operation and maintenance of the equipment.
 - b. The O/M plan shall incorporate the following work practice standards for composite mesh pad systems:
 - i. Visually inspect the device at least once per quarter to ensure there is proper drainage, no chromic acid buildup on the pads, and no evidence of chemical attack on the structural integrity of the device.
 - ii. Visually inspect at least once per quarter the back portion of the mesh pad closest to the fan to ensure there is no breakthrough of chromic acid mist.
 - iii. Visually inspect at least once per quarter the ductwork from the tank to the control device to ensure there are no leaks.
 - iv. Perform washdown of the composite mesh-pads in accordance with the manufacturer's recommendations.
- c. The plan shall specify procedures to be followed to ensure that equipment or process malfunctions due to poor maintenance or other preventable conditions do not occur.
- d. The plan shall include a systematic procedure for identifying malfunctions of process equipment, add-on air pollution control devices, and process and control system monitoring equipment, and for implementing corrective actions to address such malfunctions.
 - e. If the operation and maintenance plan fails to address or inadequately addresses an event that meets the characteristics of a malfunction at the time the plan is initially developed, the permittee shall revise the operation and maintenance plan within 45 days after such an event occurs.

- f. If actions taken by the permittee during periods of malfunction are inconsistent with the procedures specified in the operation and maintenance plan, the permittee shall record the actions taken for that event and shall report such actions within 2 working days after commencing actions inconsistent with the plan. This report shall be followed by a letter within 7 working days after the end of the event, unless the permittee makes alternative reporting arrangements, in advance, with the appropriate Ohio EPA District Office or local air agency.

g. The permittee shall keep the written operation and maintenance plan on record after it is developed to be made available for inspection, upon request, by the appropriate Ohio EPA District Office or local air agency for the life of the emission unit. If the operation and maintenance plan is revised, the permittee shall keep previous versions of the plan on record to be made available for inspection, upon request, by the appropriate Ohio EPA District Office or local air agency for a period of five years after each revision to the plan.

- h. The permittee may use applicable standard operating procedure (SOP) manuals, Occupational Safety and Health Administration (OSHA) plans, or other existing plans to meet the operation and maintenance plan requirements as long as the alternative plans meet the requirements.

- 5. The composite mesh-pad system shall be operated within +/- 1 inch of water column of the pressure drop value established during the initial performance test.

C. Monitoring and/or Record Keeping Requirements

- 1. Composite mesh-pad (CMP) system monitoring requirements to demonstrate continuous compliance:
 - a. The permittee may conduct multiple performance tests to establish a range of compliant pressure drop values, or may set as the compliance value the average pressure drop measured over the three test runs of one performance test and accept +/- 1 inch of water column from this value as the compliant range.
 - b. The permittee shall monitor and record the pressure drop across the composite mesh-pad system once each day that the emission unit is operating. To be in compliance, the composite mesh-pad system shall be operated within +/- 1 inch of water column of the pressure drop value established during the initial performance test (i.e. 3.03 inches of water column), or shall be operated within the range of compliant values for pressure drop established during multiple performance tests.
- 2. The permittee shall fulfill all recordkeeping requirements in the General Provisions to 40 CFR Part 63, according to the applicability of subpart A.
- 3. The permittee also shall maintain the following records:
 - a. Inspection records for the add-on air pollution control device, if such a device is used, and monitoring equipment, to document that the inspection and maintenance required by the work practice standards of this permit have taken place. The record can take the form of a checklist and should identify the device inspected, the date of inspection, a brief description of the working condition of the device during the inspection, and any actions taken to correct deficiencies found during the inspection.
 - b. Records of all maintenance performed on the emissions unit, add-on air pollution control device, and monitoring equipment.
 - c. Records of the occurrence, duration, and cause (if known) of each malfunction of process, add-on air pollution control device, and monitoring equipment.
 - d. Records of actions taken during periods of malfunction when such actions are inconsistent with the operation and maintenance plan.
 - e. Other records, which may take the form of checklists, necessary to demonstrate consistence with the provisions of the operation and maintenance plan.
 - f. Test reports documenting results of all performance tests.
 - g. All measurements as may be necessary to determine the conditions of performance tests.
 - h. Records of monitoring data that are used to demonstrate compliance with the standard including the date and time the data are collected.
 - i. The specific identification (i.e., the date and time of commencement and completion) of each period of excess emissions, as indicated by monitoring data, that occurs during malfunction of the process, add-on air pollution control device, or monitoring equipment.
 - j. The specific identification (i.e., the date and time of commencement and completion) of each period of excess emissions, as indicated by monitoring data, that occurs during periods other than malfunction of the process, add-on air pollution control device, or monitoring equipment.
 - k. The total process operating time of the emission unit during the reporting period.
 - l. All documentation supporting the notifications and reports as outlined in the Reporting Requirements of this permit and Section 63.9 and Section 63.10 of 40 CFR Part 63, subpart A.
- 4. All records shall be maintained for a period of five years.

D. Reporting Requirements

- 1. The permittee shall fulfill all reporting requirement as outlined in 40 CFR part 63 subpart A. These reports shall be made to the appropriate Ohio EPA District Office or local air agency and shall be sent by U.S. mail, fax or by another courier.
 - a. Submittals sent by U.S. mail shall be postmarked on or before the specified date.

- b. Submittals sent by other methods shall be received by the appropriate Ohio EPA District Office or local air agency on or before the specified date.
2. The permittee shall prepare an ongoing compliance status report annually (unless a request to reduce frequency of ongoing compliance status reports has been approved) to document the ongoing compliance status of the emissions unit. This report shall include the following:
 - a. The company name and address of the emissions unit.
 - b. An identification of the operating parameter that is monitored for compliance determination.
 - c. The relevant emission limitation for the emissions unit, and the operating parameter value, or range of values, that correspond to compliance with this emission limitation as specified in the Notification of Compliance Status required by this section.
 - d. The beginning and ending dates of the reporting period.
 - e. The total operating time of the emissions unit during the reporting period.
 - f. A summary of operating parameter values, including the total duration of excess emissions during the reporting period as indicated by those values, the total duration of excess emissions expressed as a percent of the total emissions unit operating time during that reporting period, and a breakdown of the total duration of excess emissions during the reporting period into those that are due to process upsets, control equipment malfunctions, other known causes, and unknown causes.
 - g. A certification by a responsible official that the work practice standards in this permit were followed in accordance with the operation and maintenance plan for the emissions unit.
 - h. If the operation and maintenance plan required by this permit was not followed, an explanation of the reasons for not following the provisions, an assessment of whether any excess emission and/or parameter monitoring exceedances are believed to have occurred, and a copy of the reports required by the work practices in this permit.
 - i. A description of any changes in monitoring, processes, or controls since the last reporting period.
 - j. The name, title, and signature of the responsible official who is certifying the accuracy of the report.
 - k. The date of the report.
3. The permittee shall submit semiannual reports if the following conditions are met:
 - a. the total duration of excess emissions is one percent or greater of the total operating time for the reporting period; and
 - b. the total duration of malfunctions of the add-on air pollution control device and monitoring equipment is 5 percent or greater of the total operating time.
4. Once the permittee reports an exceedance, ongoing compliance status reports shall be submitted semiannually until a request to reduce reporting frequency is approved.
5. The appropriate Ohio EPA District Office or local air agency may determine on a case-by-case basis that the summary report shall be completed more frequently and submitted, or that the annual report shall be submitted instead of being retained on site, if these measures are necessary to accurately assess the compliance status of the emissions unit.
6. The permittee who is required to submit ongoing compliance status reports on a semiannual (or more frequent) basis, or is required to submit its annual report instead of retaining it on site, may reduce the frequency of reporting to annual and/or be allowed to maintain the annual report on site if all of the following conditions are met:
 - a. For 1 full year (e.g., 2 semiannual or 4 quarterly reporting periods), the ongoing compliance status reports demonstrate that the affected emissions unit is in compliance with the relevant emission limit.
 - b. The permittee continues to comply with all applicable recordkeeping and monitoring requirements of 40 CFR Part 63, subpart A and this permit.
 - c. The appropriate Ohio EPA District Office or local air agency does not object to a reduced reporting frequency. The frequency of submitting ongoing compliance status reports may be reduced if the following requirements are met:
 - i. The permittee notifies the appropriate Ohio EPA District Office or local air agency in writing of its intentions to make such a change. The district office may review information concerning the facility's previous performance history during the 5-year recordkeeping period prior to the intended change, or the recordkeeping period since the emission unit's compliance date, whichever is shorter. Records subject to review include performance test results, monitoring data, and evaluations of the permittee's conformance with emission limitations and work practice standards. If the permittee's request is disapproved, the appropriate Ohio EPA District Office or local air agency will notify the permittee in writing within 45 days after receiving notice. This notification will specify the grounds on which the disapproval is based. In the absence of a notice of disapproval within 45 days, approval is automatically granted.
 - ii. If monitoring data show that the emissions unit is not in compliance with the relevant emission limit, the frequency of reporting shall revert to semiannual, and the permittee shall state this exceedance in the ongoing compliance status report for the next reporting period. After demonstrating ongoing compliance with the relevant emission limit for another full year, the permittee may again request approval to reduce the reporting frequency.
7. The permittee shall submit a notification of construction or reconstruction as soon as practicable before the

construction or reconstruction has commenced to the appropriate Ohio EPA District Office or local air agency which includes the following:

- a. The permittee's name, title, and address.
 - b. The address (i.e., physical location) or proposed address of the affected emissions unit if different from the permittee's.
 - c. A notification of intention to construct or make any physical or operational changes to an affected emissions unit that may meet or has been determined to meet the criteria for a reconstruction as defined in 40 CFR part 63.2.
 - d. An identification of 40 CFR Part 63, subpart N as the basis for the notification.
 - e. The expected commencement and completion dates of the construction or reconstruction.
 - f. The anticipated date of (initial) startup.
 - g. The type of process operation to be performed (hard or decorative chromium electroplating or chromium anodizing).
 - h. A description of the air pollution control technique to be used to control emissions, such as preliminary design drawings and design capacity if an add-on air pollution control device is used.
 - i. An estimate of emissions based on engineering calculations and vendor information on control device efficiency, expressed in units consistent with the emissions limits of 40 CFR Part 63, subpart N. Calculations of emission estimates should be in sufficient detail to permit assessment of the validity of the calculations.
8. If a reconstruction is to occur, the permittee shall submit as soon as practicable the following information to the appropriate Ohio EPA District Office or local air agency:
- a. A brief description of the affected emissions unit and the components to be replaced.
 - b. A brief description of the present and proposed emission control technique.
 - c. An estimate of the fixed capital cost of the replacements and of constructing a comparable entirely new emissions unit.
 - d. The estimated life of the affected emissions unit after the replacements.
 - e. A discussion of any economic or technical limitations the emissions unit may have in complying with relevant standards or other requirements after proposed replacements. The discussion shall be sufficiently detailed to demonstrate to the appropriate Ohio EPA District Office or local air agency satisfaction that the technical or economic limitations affected the emissions unit ability to comply with the relevant standard and how they do so.
9. The permittee shall report to the appropriate Ohio EPA District Office or local air agency the results of any performance test conducted. The report shall be submitted no later than 90 days following the completion of the performance test, and shall be submitted as part of the notification of compliance status report required by this section.

E. Testing Requirements

1. All monitoring equipment shall be installed such that representative measurements of emissions or process parameters from the affected emissions unit are obtained. For monitoring equipment purchased from a vendor, verification of the operational status of the monitoring equipment shall include execution of the manufacturer's written specifications or recommendations for installation, operation, and calibration of the system. Specifications for differential pressure measurement devices used to measure pressure drop across a control system shall be in accordance with the manufacturer's accuracy specifications.
2. The permittee shall measure the pressure drop across the add-on air pollution control device in accordance with the following guidelines:
 - a. Pressure taps shall be installed at any of the following locations:
 - i. At the inlet and outlet of the control system. The inlet tap should be installed in the ductwork just prior to the control device and the corresponding outlet pressure tap should be installed on the outlet side of the control device prior to the blower or on the downstream side of the blower.
 - ii. On each side of the packed bed within the control system or on each side of each mesh pad within the control system.
 - iii. On the front side of the first mesh pad and back side of the last mesh pad within the control system.
 - b. Pressure taps shall be sited at locations that are:
 - i. As free from pluggage as possible and away from any flow disturbances such as cyclonic demisters.
 - ii. Situated such that no air infiltration at the measurement site will occur that could bias the measurement.
 - c. Pressure taps shall be constructed of either polyethylene, polybutylene, or other nonreactive materials.
 - d. Nonreactive plastic tubing shall be used to connect the pressure taps to the device used to measure pressure drop.
 - e. Any of the following pressure gauges can be used to monitor pressure drop: a magnehelic gauge, an included manometer, or a "U" tube manometer.
 - f. Prior to connecting any pressure lines to the pressure gauge(s), each gauge shall be zeroed. No calibration of

the pressure gauges is required.

3. Compliance with the total chromium limitation of 0.03 mg/dscm in the exhaust gases discharged to the atmosphere shall be demonstrated using the following test methods, if required by the Ohio EPA:
 - a. Method 306 or Method 306A, "Determination of Chromium Emissions From Decorative and Hard Chromium Electroplating and Anodizing Operations" shall be used to determine the chromium concentration from hard chromium electroplating tanks.
 - i. The sampling time and sample volume for each run or Methods 306 and 306A shall be at least 120 minutes and 1.7 dscm (60 dscf), respectively.
 - ii. Methods 306 and 306A allow the measurement of either total chromium or hexavalent chromium emissions. Emissions units using chromic acid baths can demonstrate compliance with the emission limits by measuring either the total chromium or hexavalent chromium concentration. Hence, the hexavalent chromium concentration measured by these methods is equal to the total chromium concentration for the affected operations.
 - b. The California Air Resources Board (CARB) Method 425 may be used to determine the chromium concentration from hard and decorative chromium electroplating tanks and chromium anodizing tanks if the following conditions are met:
 - i. If a colorimetric analysis method is used, the sampling time and volume shall be sufficient to result in 33-66 micrograms of catch in the sampling train.
 - ii. If an Atomic Absorption Graphite Furnace (AAGF) or Ion Chromatography (with a Post-column Reactor (ICPCR) analyses) is used, the sampling time and volume should be sufficient to result in a sample catch that is 5 to 10 times the minimum detection limit of the analytical method (i.e., 1.0 microgram per liter of sample for AAGF and 0.5 microgram per liter of sample for ICPCR).
 - iii. A minimum of three separate runs must be conducted. The other requirements of ?63.7 of 40 CFR Part 63, subpart A must also be met.
4. Compliance with the visible emission limitation shall be determined using U.S. EPA Method 9, if required by the Ohio EPA.
1. Emission testing requirements

The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:

- i. The emission testing shall be conducted upon start-up of the emissions unit.
- ii. The emission testing shall be conducted to demonstrate compliance with the mass emission limit for total chromium.
- iii. The following test method(s) shall be employed to demonstrate compliance with the allowable mass emission rate(s): Methods 306 or 306A of 40 CFR Part 63, Appendix A.
- iv. The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity, unless otherwise specified or approved by the appropriate Ohio EPA District Office or local air agency. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the appropriate Ohio EPA District Office or local air agency. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time (s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA District Office's or local air agency's refusal to accept the results of the emission test(s).

Personnel from the appropriate Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office or local air agency within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the appropriate Ohio EPA District Office or local air agency.

F. Miscellaneous Requirements

1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0204010284 Emissions Unit ID: P003 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
One hard chromium electroplating tank with a dry packed-bed scrubber and a composite mesh-pad system for controlling chromic acid emissions.	40 CFR 63 Subpart N	The permittee shall not allow the concentration of total chromium in the exhaust gases discharged to the atmosphere to exceed 0.03 mg/dscm.
	OAC 3745-17-07	Visible emissions from control system stack not to exceed 20 percent opacity as a six minute average except as provided by rule.
	OAC 3745-17-11 OAC 3745-31-05 PTI 02-12402	Less stringent than limit from OAC 3745-31-05. Less stringent than 40 CFR Part 63 Subpart N.

2. Additional Terms and Conditions

- (a) None

B. Operational Restrictions

1. At all times, including periods of startup, shutdown, and malfunction, the permittee shall operate and maintain any chromium electroplating or anodizing tank, including associated air pollution control devices and monitoring equipment, in a manner consistent with the operation and maintenance plan required by these terms and conditions.
2. Malfunctions shall be corrected as soon as practicable after their occurrence in accordance with the operation and maintenance plan.
3. Determination of whether acceptable operation and maintenance procedures are being used will be based on information available to the appropriate Ohio EPA District Office or local air agency, which may include, but is not limited to, monitoring results; review of the operation and maintenance plan, procedures, and records; and inspection of the emission unit. Based on this information, the appropriate Ohio EPA District Office or local air agency may require that the permittee make changes to the operation and maintenance plan if that plan:
 - a. does not address a malfunction that has occurred;
 - b. fails to provide for the operation of the emission units, the air pollution control techniques, or the control system and process monitoring equipment during a malfunction in a manner consistent with good air pollution practices; or
 - c. does not provide adequate procedures for correcting malfunctioning process equipment, air pollution control techniques, or monitoring equipment as quickly as practicable.
4. The operation and maintenance plan shall be implemented and shall include the following elements:
 - a. The plan shall specify the operation and maintenance criteria for the affected source, the add-on air pollution control device (if such a device is used to comply with the emissions limits), and the process and control system monitoring equipment, and shall include a standardized checklist to document the operation and maintenance of the equipment.
 - b. The O/M plan shall incorporate the following work practice standards:
 - i. Visually inspect the device at least once per quarter to ensure there is proper drainage, no chronic acid buildup on the pads, and no evidence of chemical attack on the structural integrity of the device.
 - ii. Visually inspect at least once per quarter the back portion of the mesh pad closest to the fan to ensure there is no breakthrough of chromic acid mist.
 - iii. Visually inspect at least once per quarter the ductwork from the tank to the control device to ensure there are no leaks.
 - iv. Perform washdown of the composite mesh-pads in accordance with manufacturer's recommendations.
 - c. The plan shall specify procedures to be followed to ensure that equipment or process malfunctions due to poor maintenance or other preventable conditions do not occur.
 - d. The plan shall include a systematic procedure for identifying malfunctions of process equipment, add-on air pollution control devices, and process and control system monitoring equipment, and for implementing corrective actions to address such malfunctions.

- e. If the operation and maintenance plan fails to address or inadequately addresses an event that meets the characteristics of a malfunction at the time the plan is initially developed, the permittee shall revise the operation and maintenance plan within 45 days after such an event occurs.
- f. If actions taken by the permittee during periods of malfunction are inconsistent with the procedures specified in the operation and maintenance plan, the permittee shall record the actions taken for that event and shall report such actions within 2 working days after commencing actions inconsistent with the plan. This report shall be followed by a letter within 7 working days after the end of the event, unless the permittee makes alternative reporting arrangements, in advance, with the appropriate Ohio EPA District Office or local air agency.

g. The permittee shall keep the written operation and maintenance plan on record after it is developed to be made available for inspection, upon request, by the appropriate Ohio EPA District Office or local air agency for the life of the emission unit. If the operation and maintenance plan is revised, the permittee shall keep previous versions of the plan on record to be made available for inspection, upon request, by the appropriate Ohio EPA District Office or local air agency for a period of five years after each revision to the plan.

- h. The permittee may use applicable standard operating procedure (SOP) manuals, Occupational Safety and Health Administration (OSHA) plans, or other existing plans to meet the operation and maintenance plan requirements as long as the alternative plans meet the requirements.

- 5. The composite mesh-pad system and the packed bed scrubber shall be operated within +/- 1 inch of water column of the pressure drop value of 2.45 inches of water column established during the initial performance test.

C. Monitoring and/or Record Keeping Requirements

- 1. Packed-bed scrubber/composite mesh-pad system monitoring requirements to demonstrate continuous compliance:
 - a. The permittee may conduct multiple performance tests to establish a range of compliant pressure drop values, or may set as the compliance value the average pressure drop measured over the three test runs of one performance test and accept +/- 1 inch of water column from this value as the compliant range.
 - b. The permittee shall monitor and record the pressure drop across the composite mesh-pad system and the packed-bed scrubber once each day that the emission unit is operating. To be in compliance, the composite mesh-pad system and the packed-bed scrubber shall be operated within +/- 1 inch of water column of the pressure drop value established during the initial performance test (i.e. 2.45 inches of water column), or shall be operated within the range of compliant values for pressure drop established during multiple performance tests.
- 2. The permittee shall fulfill all recordkeeping requirements in the General Provisions to 40 CFR Part 63, according to the applicability of subpart A.
- 3. The permittee also shall maintain the following records:
 - a. Inspection records for the add-on air pollution control device, if such a device is used, and monitoring equipment, to document that the inspection and maintenance required by the work practice standards of this permit have taken place. The record can take the form of a checklist and should identify the device inspected, the date of inspection, a brief description of the working condition of the device during the inspection, and any actions taken to correct deficiencies found during the inspection.
 - b. Records of all maintenance performed on the emissions unit, add-on air pollution control device, and monitoring equipment.
 - c. Records of the occurrence, duration, and cause (if known) of each malfunction of process, add-on air pollution control device, and monitoring equipment.
 - d. Records of actions taken during periods of malfunction when such actions are inconsistent with the operation and maintenance plan.
 - e. Other records, which may take the form of checklists, necessary to demonstrate consistence with the provisions of the operation and maintenance plan.
 - f. Test reports documenting results of all performance tests.
 - g. All measurements as may be necessary to determine the conditions of performance tests.
 - h. Records of monitoring data that are used to demonstrate compliance with the standard including the date and time the data are collected.
 - i. The specific identification (i.e., the date and time of commencement and completion) of each period of excess emissions, as indicated by monitoring data, that occurs during malfunction of the process, add-on air pollution control device, or monitoring equipment.
 - j. The specific identification (i.e., the date and time of commencement and completion) of each period of excess emissions, as indicated by monitoring data, that occurs during periods other than malfunction of the process, add-on air pollution control device, or monitoring equipment.
 - k. The total process operating time of the emission unit during the reporting period.
 - l. All documentation supporting the notifications and reports as outlined in the Reporting Requirements of this permit and Section 63.9 and Section 63.10 of 40 CFR Part 63, subpart A.
- 4. All records shall be maintained for a period of five years.

D. Reporting Requirements

1. The permittee shall fulfill all reporting requirement as outlined in 40 CFR part 63 subpart A. These reports shall be made to the appropriate Ohio EPA District Office or local air agency and shall be sent by U.S. mail, fax or by another courier.
 - a. Submittals sent by U.S. mail shall be postmarked on or before the specified date.
 - b. Submittals sent by other methods shall be received by the appropriate Ohio EPA District Office or local air agency on or before the specified date.
2. The permittee shall prepare an ongoing compliance status report annually (unless a request to reduce frequency of ongoing compliance status reports has been approved) to the appropriate Ohio EPA District Office or local air agency to document the ongoing compliance status of the emissions unit. This report shall include the following:
 - a. The company name and address of the emissions unit.
 - b. An identification of the operating parameter that is monitored for compliance determination.
 - c. The relevant emission limitation for the emissions unit, and the operating parameter value, or range of values, that correspond to compliance with this emission limitation as specified in the Notification of Compliance Status required by this section.
 - d. The beginning and ending dates of the reporting period.
 - e. The total operating time of the emissions unit during the reporting period.
 - f. A summary of operating parameter values, including the total duration of excess emissions during the reporting period as indicated by those values, the total duration of excess emissions expressed as a percent of the total emissions unit operating time during that reporting period, and a breakdown of the total duration of excess emissions during the reporting period into those that are due to process upsets, control equipment malfunctions, other known causes, and unknown causes.
 - g. A certification by a responsible official that the work practice standards in this permit were followed in accordance with the operation and maintenance plan for the emissions unit.
 - h. If the operation and maintenance plan required by this permit was not followed, an explanation of the reasons for not following the provisions, an assessment of whether any excess emission and/or parameter monitoring exceedances are believed to have occurred, and a copy of the reports required by the work practices in this permit.
 - i. A description of any changes in monitoring, processes, or controls since the last reporting period.
 - j. The name, title, and signature of the responsible official who is certifying the accuracy of the report.
 - k. The date of the report.
3. The permittee shall submit semiannual reports if the following conditions are met:
 - a. the total duration of excess emissions is one percent or greater of the total operating time for the reporting period; and
 - b. the total duration of malfunctions of the add-on air pollution control device and monitoring equipment is 5 percent or greater of the total operating time.
4. Once the permittee reports an exceedance, ongoing compliance status reports shall be submitted semiannually until a request to reduce reporting frequency is approved.
5. The appropriate Ohio EPA District Office or local air agency may determine on a case-by-case basis that the summary report shall be completed more frequently and submitted, or that the annual report shall be submitted instead of being retained on site, if these measures are necessary to accurately assess the compliance status of the emissions unit.
6. The permittee who is required to submit ongoing compliance status reports on a semiannual (or more frequent) basis, or is required to submit its annual report instead of retaining it on site, may reduce the frequency of reporting to annual and/or be allowed to maintain the annual report on site if all of the following conditions are met:
 - a. For 1 full year (e.g., 2 semiannual or 4 quarterly reporting periods), the ongoing compliance status reports demonstrate that the affected emissions unit is in compliance with the relevant emission limit.
 - b. The permittee continues to comply with all applicable recordkeeping and monitoring requirements of 40 CFR Part 63, subpart A and this permit.
 - c. The appropriate Ohio EPA District Office or local air agency does not object to a reduced reporting frequency. The frequency of submitting ongoing compliance status reports may be reduced if the following requirements are met:
 - i. The permittee notifies the appropriate Ohio EPA District Office or local air agency in writing of its intentions to make such a change. The district office may review information concerning the facility's previous performance history during the 5-year recordkeeping period prior to the intended change, or the recordkeeping period since the emission unit's compliance date, whichever is shorter. Records subject to review include performance test results, monitoring data, and evaluations of the permittee's conformance with emission limitations and work practice standards. If the permittee's request is disapproved, the appropriate Ohio EPA District Office or local air agency will notify the permittee in writing within 45 days after receiving notice. This notification will specify the grounds on which the disapproval is based. In the absence of a notice of disapproval within 45 days, approval is automatically granted.
 - ii. If monitoring data show that the emissions unit is not in compliance with the relevant emission limit, the frequency of reporting shall revert to semiannual, and the permittee shall state this exceedance in the

ongoing compliance status report for the next reporting period. After demonstrating ongoing compliance with the relevant emission limit for another full year, the permittee may again request approval to reduce the reporting frequency.

7. The permittee shall submit a notification of construction or reconstruction as soon as practicable before the construction or reconstruction has commenced to the appropriate Ohio EPA District Office or local air agency which includes the following:
 - a. The permittee's name, title, and address.
 - b. The address (i.e., physical location) or proposed address of the affected emissions unit if different from the permittee's.
 - c. A notification of intention to construct or make any physical or operational changes to an affected emissions unit that may meet or has been determined to meet the criteria for a reconstruction as defined in 40 CFR part 63.2.
 - d. An identification of 40 CFR Part 63, subpart N as the basis for the notification.
 - e. The expected commencement and completion dates of the construction or reconstruction.
 - f. The anticipated date of (initial) startup.
 - g. The type of process operation to be performed (hard or decorative chromium electroplating or chromium anodizing).
 - h. A description of the air pollution control technique to be used to control emissions, such as preliminary design drawings and design capacity if an add-on air pollution control device is used.
 - i. An estimate of emissions based on engineering calculations and vendor information on control device efficiency, expressed in units consistent with the emissions limits of 40 CFR Part 63, subpart N. Calculations of emission estimates should be in sufficient detail to permit assessment of the validity of the calculations.
8. If a reconstruction is to occur, the permittee shall submit as soon as practicable the following information to the appropriate Ohio EPA District Office or local air agency:
 - a. A brief description of the affected emissions unit and the components to be replaced.
 - b. A brief description of the present and proposed emission control technique.
 - c. An estimate of the fixed capital cost of the replacements and of constructing a comparable entirely new emissions unit.
 - d. The estimated life of the affected emissions unit after the replacements.
 - e. A discussion of any economic or technical limitations the emissions unit may have in complying with relevant standards or other requirements after proposed replacements. The discussion shall be sufficiently detailed to demonstrate to the appropriate Ohio EPA District Office or local air agency satisfaction that the technical or economic limitations affected the emissions unit ability to comply with the relevant standard and how they do so.
9. The permittee shall report to the appropriate Ohio EPA District Office or local air agency the results of any performance test conducted. The report shall be submitted no later than 90 days following the completion of the performance test, and shall be submitted as part of the notification of compliance status report required by this section.

E. Testing Requirements

1. All monitoring equipment shall be installed such that representative measurements of emissions or process parameters from the affected emissions unit are obtained. For monitoring equipment purchased from a vendor, verification of the operational status of the monitoring equipment shall include execution of the manufacturer's written specifications or recommendations for installation, operation, and calibration of the system. Specifications for differential pressure measurement devices used to measure pressure drop across a control system shall be in accordance with the manufacturer's accuracy specifications.
2. The permittee shall measure the pressure drop across the add-on air pollution control device in accordance with the following guidelines:
 - a. Pressure taps shall be installed at any of the following locations:
 - i. At the inlet and outlet of the control system. The inlet tap should be installed in the ductwork just prior to the control device and the corresponding outlet pressure tap should be installed on the outlet side of the control device prior to the blower or on the downstream side of the blower.
 - ii. On each side of the packed bed within the control system or on each side of each mesh pad within the control system.
 - iii. On the front side of the first mesh pad and back side of the last mesh pad within the control system.
 - b. Pressure taps shall be sited at locations that are:
 - i. As free from pluggage as possible and away from any flow disturbances such as cyclonic demisters.
 - ii. Situated such that no air infiltration at the measurement site will occur that could bias the measurement.
 - c. Pressure taps shall be constructed of either polyethylene, polybutylene, or other nonreactive materials.
 - d. Nonreactive plastic tubing shall be used to connect the pressure taps to the device used to measure pressure drop.

- e. Any of the following pressure gauges can be used to monitor pressure drop: a magnehelic gauge, an included manometer, or a "U" tube manometer.
 - f. Prior to connecting any pressure lines to the pressure gauge(s), each gauge shall be zeroed. No calibration of the pressure gauges is required.
3. Compliance with the total chromium limitation of 0.03 mg/dscm in the exhaust gases discharged to the atmosphere shall be demonstrated using the following test methods, if required by the Ohio EPA:
- a. Method 306 or Method 306A, "Determination of Chromium Emissions From Decorative and Hard Chromium Electroplating and Anodizing Operations" shall be used to determine the chromium concentration from hard chromium electroplating tanks.
 - i. The sampling time and sample volume for each run of Methods 306 and 306A shall be at least 120 minutes and 1.7 dscm (60 dscf), respectively.
 - ii. Methods 306 and 306A allow the measurement of either total chromium or hexavalent chromium emissions. Emissions units using chromic acid baths can demonstrate compliance with the emission limits by measuring either the total chromium or hexavalent chromium concentration. Hence, the hexavalent chromium concentration measured by these methods is equal to the total chromium concentration for the affected operations.
 - b. The California Air Resources Board (CARB) Method 425 may be used to determine the chromium concentration from hard and decorative chromium electroplating tanks and chromium anodizing tanks if the following conditions are met:
 - i. If a colorimetric analysis method is used, the sampling time and volume shall be sufficient to result in 33-66 micrograms of catch in the sampling train.
 - ii. If an Atomic Absorption Graphite Furnace (AAGF) or Ion Chromatography (with a Post-column Reactor (ICPCR) analyses) is used, the sampling time and volume should be sufficient to result in a sample catch that is 5 to 10 times the minimum detection limit of the analytical method (i.e., 1.0 microgram per liter of sample for AAGF and 0.5 microgram per liter of sample for ICPCR).
 - iii. A minimum of three separate runs must be conducted. The other requirements of ?63.7 of 40 CFR Part 63, subpart A must also be met.
4. Compliance with the visible emission limitation shall be determined by using U.S. EPA Method 9, if required by the Ohio EPA.
- F. **Miscellaneous Requirements**
- 1. None