



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL
FRANKLIN COUNTY**

CERTIFIED MAIL

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049

Application No: 01-08963

Fac ID: 0125043067

DATE: 5/24/2005

PDG Domus Manufacturing LLC
Nathan Pingel
PDG Domus 426 East Whittier Street
Columbus, OH 43206

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, Ohio 43215

Sincerely,

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: USEPA

CDO



**Permit To Install
Terms and Conditions**

**Issue Date: 5/24/2005
Effective Date: 5/24/2005**

FINAL PERMIT TO INSTALL 01-08963

Application Number: 01-08963
Facility ID: 0125043067
Permit Fee: **\$400**
Name of Facility: PDG Domus Manufacturing LLC
Person to Contact: Nathan Pingel
Address: PDG Domus 426 East Whittier Street
Columbus, OH 43206

Location of proposed air contaminant source(s) [emissions unit(s)]:
**1909 E Livingston
Columbus, Ohio**

Description of proposed emissions unit(s):
Composite panel assembly press 1.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized

representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio

Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

PDG Domus Manufacturing LLC
PTI Application: 01-08963
Issued: 5/24/2005

Facility ID: 0125043067

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
 TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
OC	13.04

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P001 - Cast resin and gel coat process for composite panel assembly press (modification of PTI 01-08900)	OAC rule 3745-31-05(A)(3)	Organic compound (OC) emissions shall not exceed 1.64 lbs OC per hour and 7.2 tons OC per year. See sections A.2.a and A.2.b.
	OAC rule 3745-21-07(G)(2)	The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-07(G)(2).
		OC emissions from this emissions unit shall not exceed 40 pounds per day, during any day in which photochemically reactive materials are employed.

2. Additional Terms and Conditions

- 2.a The 1.64 lbs OC/hr and 7.2 tons OC/yr emission limitations for this emissions unit were established to reflect the maximum potential to emit. Therefore, it is not necessary to develop additional monitoring, record keeping and/or reporting requirements to ensure compliance with this limit.
- 2.b The permittee shall maintain a stack height of thirty-five (35) feet or more above ground as measured from the ground to the top of the stack for this emissions unit. The stack shall also be designed with sufficient height from the roof and/or sufficient upward air flow velocity and positioned on the building to minimize or eliminate any building down wash impacts from emissions and/or odors on nearby residences. All air contaminant emissions from this emissions unit shall be emitted through the stack.

B. Operational Restrictions

8

PDG Domus Manufacturing LLC

PTI Application: 01 08063

Issued

Facility ID: 0125043067

Emissions Unit ID: P001

None

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each day for the purpose of determining annual OC emissions:
 - a. the company identification for each liquid material employed and whether or not the material is a photochemically reactive material;
 - b. the number of pounds of each photochemically reactive material employed;
 - c. the OC content of each photochemically reactive material, in percent by weight; and
 - d. for each day during which a photochemically reactive material is employed, the total organic compound emission rate for all photochemically reactive materials, in pounds per day.

Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit. Also, the definitions of "photochemically reactive" and "nonphotochemically reactive" are based upon OAC rule 3745-21-01(C)(5).

2. The permit to install for this emissions unit (P001) was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model. The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: methyl methacrylate, styrene, xylene

TLV (mg/m³): 205, 85, 434

Maximum Hourly Emission Rate (lbs/hr): 0.750, 0.519, 0.233

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 33, 23, 10

MAGLC (ug/m³): 4,875, 2,020, 10,333

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such

Emissions Unit ID: **P001**

parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. In accordance with paragraph A.2. of the General Terms and Conditions, the permittee shall

submit quarterly deviation (excursion) reports that identify each day during which the OC emissions from the photochemically reactive materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day.

2. The permittee shall submit an annual report to the Ohio EPA, CDO which summarize the OC emitted from the facility. This annual report shall be submitted by April 15 of each year. This reporting requirement may be satisfied by including and identifying the specific emission data for this emissions unit in the annual Fee Emission Report.

E. Testing Requirements

1. Compliance with the emission limitations in section A.1. of these terms and conditions shall be determined in accordance with the following methods:

- a. Emissions Limitation:

OC emissions shall not exceed 1.64 pounds per hour, excluding non- photochemically reactive materials.

Applicable Compliance Method:

Compliance with the hourly allowable emission limitation may be derived by summing the calculated emission rates resulting from the average usage of 80.47 lbs cast resin and 3.71 lbs gel coat per hour. The OC emission from the 80.47 pounds cast resin usage is derived by multiplying the weight times the 39.95% MMA by weight multiplied times the 2% volatilization rate (AP42 Table 4.4-2 for vapor suppressed marble resin) results in 0.64 lb MMA plus the product of the 80.47 lbs cast resin multiplied by 12.8% styrene by weight multiplied by the 2% volatilization rate results in 0.206 lb styrene emitted per hour. The OC emission from the 3.71 lbs gel coat usage is derived by multiplying the weight times the 3 % MMA by weight multiplied times the 75% volatilization rate ("Unified Emission Factors" for open molding, Composite Fabricators Association) resulting in 0.084 lb MMA plus the weight times the 30% styrene by weight multiplied times the 28.2% volatilization rate would result in 0.314 lb styrene per hour.

- b. Emission Limitation:

OC emissions from this emissions unit shall not exceed 40 pounds per day, during any day in which photochemically reactive materials are employed.

Applicable Compliance Method:

Compliance with the daily OC emission limit shall be demonstrated by record keeping in section C.1, above.

- c. OC emissions shall not exceed 7.2 tons per year, including non-photochemically reactive materials.

Applicable Compliance Method:

Compliance with the annual OC emission limit shall be demonstrated by record keeping in section C.1, above.

F. Miscellaneous Requirements

13

PDG Domus Manufacturing LLC

PTI Application: 01 08063

Issued

Facility ID: 0125043067

Emissions Unit ID: P001

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
R001 - Liquid insulation blend spray coater	OAC rule 3745-31-05(A)(3)	Organic compound (OC) emissions from this operation shall not exceed 1.34 pounds per hour and 5.87 tons per year. See sections A.2.a and A.2.b, below.
	OAC rule 3745-21-07(G)(9)(f)	The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-07(G)(9)(f).
		See section A.2.c, below.

2. Additional Terms and Conditions

- 2.a The 1.34 pounds OC per hour emission limitation and 5.87 tons per year for this emissions unit was established to reflect the maximum potential to emit. Therefore, it is not necessary to develop additional monitoring, record keeping and/or reporting requirement to ensure compliance with this limit.
- 2.b The permittee shall maintain a stack height of thirty-five (35) feet or more above ground as measured from the ground to the top of the stack for this emissions unit. The stack shall also be designed with sufficient height from the roof and/or sufficient upward air flow velocity and positioned on the building to minimize or eliminate any building downwash impacts from emissions and/or odors on nearby residences. All air contaminant emissions from this emissions unit shall be emitted through the stack.
- 2.c The provisions of OAC rule 3745-21-07(G)(2) shall not apply to the use of any material, in any article, machine, equipment or other contrivance described in paragraph (G)(2) of

this rule, if it can be demonstrated to the director's satisfaction that the emissions of organic materials into the atmosphere from such article, machine, equipment, or other contrivance are not photochemically reactive.

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each month for the purpose of determining annual OC emissions:
 - a. the company identification for each liquid material employed and whether or not the material is a photochemically reactive material;
 - b. the number of pounds of each liquid organic material employed; and
 - c. the OC content of each liquid organic material, in percent by weight.

Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit. Also, the definitions of "photochemically reactive" and "nonphotochemically reactive" are based upon OAC rule 3745-21-01(C)(5).

2. The permit to install for this emissions unit (R001) was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model. The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: HCFC-R22 (chlorodifluoromethane)

TLV (mg/m³): 3,536

Maximum Hourly Emission Rate (lbs/hr): 1.34

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 59

MAGLC (ug/m³): 84, 204

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit an annual report to the Ohio EPA, CDO which summarize the OC emitted from the facility. This annual report shall be submitted by April 15 of each year. This reporting requirement may be satisfied by including and identifying the specific emission data for this emissions unit in the annual Fee Emission Report.

E. Testing Requirements

1. Compliance with the emission limitations in section A.1. of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emissions Limitation:
OC emissions shall not exceed 1.34 pounds per hour.

Applicable Compliance Method:
Compliance with the hourly allowable emission limitation may be derived by summing the calculated emission rates resulting from the average usage of equal parts of 55.95 lbs autofroth A and B per hour. The OC emission is derived by multiplying the 55.95 lbs autofroth B times the 16 % CFC-R22 by weight multiplied times the 15% volatilization rate results in 1.34 lb OC plus the weight from the 55.95 lbs autofroth A times the 45% MDI by weight multiplied times the 0.0001% volatilization rate results in 0.0014 lb MDI per hour.
 - b. Emission Limitation:
OC emissions shall not exceed 5.87 tons per year.

Applicable Compliance Method:
Compliance with the annual OC emission limit shall be demonstrated by record keeping in section C.1, above.

F. Miscellaneous Requirements

None