



State of Ohio Environmental Protection Agency

STREET ADDRESS:

Lazarus Government Center
50 W. Town St., Suite 700
Columbus, Ohio 43215

TELE: (614) 644-3020 FAX: (614) 644-3184
www.epa.ohio.gov

MAILING ADDRESS:

P.O. Box 1049
Columbus, OH 43216-1049

2/9/2010

Certified Mail

Beth Mowrey
Shelly Materials Plant No 82
PO BOX 266
Thornville, OH 43076

| | |
|----|----------------------|
| No | TOXIC REVIEW |
| No | PSD |
| No | SYNTHETIC MINOR |
| No | CEMS |
| No | MACT |
| No | NSPS |
| No | NESHAPS |
| No | NETTING |
| No | MAJOR NON-ATTAINMENT |
| No | MODELING SUBMITTED |

RE: FINAL AIR POLLUTION PERMIT-TO-INSTALL AND OPERATE
Facility ID: 0302020006
Permit Number: P0105409
Permit Type: Renewal
County: Allen

Dear Permit Holder:

Enclosed please find a final Air Pollution Permit-to-Install and Operate ("PTIO") which will allow you to install, modify, and/or operate the described emissions unit(s) in the manner indicated in the permit. Because this permit contains conditions and restrictions, please read it very carefully. Please complete a survey at www.epa.ohio.gov/dapc/permitsurvey.aspx and give us feedback on your permitting experience. We value your opinion.

Ohio EPA maintains a document entitled "Frequently Asked Questions about the PTIO". The document can be downloaded from the DAPC Web page, www.epa.ohio.gov/dapc, from the "Permits" link. This document contains additional information related to your permit, such as what activities are covered under the PTIO, who has enforcement authority over the permit and Ohio EPA's authorization to inspect your facility and records. Please contact the Office of Compliance Assistance and Pollution Prevention at (614) 644-3469 if you need assistance.

The issuance of this PTIO is a final action of the Director and may be appealed to the Environmental Review Appeals Commission ("ERAC") under Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and describe the action complained of and the grounds for the appeal. The appeal must be filed with the ERAC within thirty (30) days after notice of the Director's action. A filing fee of \$70.00 must be submitted to the ERAC with the appeal, although the ERAC, has discretion to reduce the amount of the filing fee if you can demonstrate (by affidavit) that payment of the full amount of the fee would cause extreme hardship. If you file an appeal of this action, you must notify Ohio EPA of the filing of the appeal (by providing a copy to the Director) within three (3) days of filing your appeal with the ERAC. Ohio EPA requests that a copy of the appeal also be provided to the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the ERAC at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, OH 43215

If you have any questions regarding this permit, please contact the Ohio EPA DAPC, Northwest District Office. This permit has been posted to the Division of Air Pollution Control (DAPC) Web page www.epa.ohio.gov/dapc.

Sincerely,

Michael W. Ahern
Michael W. Ahern, Manager
Permit Issuance and Data Management Section, DAPC

Cc: Ohio EPA-NWDO

Ted Strickland, Governor
Lee Fisher, Lieutenant Governor
Chris Korleski, Director



**State of Ohio Environmental Protection Agency
Division of Air Pollution Control**

FINAL

**Air Pollution Permit-to-Install and Operate
for
Shelly Materials Plant No 82**

Facility ID: 0302020006
Permit Number: P0105409
Permit Type: Renewal
Issued: 2/9/2010
Effective: 2/9/2010
Expiration: 2/9/2015



Air Pollution Permit-to-Install and Operate
for
Shelly Materials Plant No 82

Table of Contents

- Authorization 1
- A. Standard Terms and Conditions 3
 - 1. What does this permit-to-install and operate ("PTIO") allow me to do?..... 4
 - 2. Who is responsible for complying with this permit? 4
 - 3. What records must I keep under this permit? 4
 - 4. What are my permit fees and when do I pay them?..... 4
 - 5. When does my PTIO expire, and when do I need to submit my renewal application? 4
 - 6. What happens to this permit if my project is delayed or I do not install or modify my source? 5
 - 7. What reports must I submit under this permit? 5
 - 8. If I am required to obtain a Title V operating permit in the future, what happens to the operating provisions and PER obligations under this permit? 5
 - 9. What are my obligations when I perform scheduled maintenance on air pollution control equipment?... 5
 - 10. Do I have to report malfunctions of emissions units or air pollution control equipment? If so, how must I report? 5
 - 11. Can Ohio EPA or my local air agency inspect the facility where the emission unit(s) is/are located? 6
 - 12. What happens if one or more emissions units operated under this permit is/are shut down permanently? 6
 - 13. Can I transfer this permit to a new owner or operator? 6
 - 14. Does compliance with this permit constitute compliance with OAC rule 3745-15-07, "air pollution nuisance"? 7
 - 15. What happens if a portion of this permit is determined to be invalid? 7
- B. Facility-Wide Terms and Conditions 8
- C. Emissions Unit Terms and Conditions 10
 - 1. P901, 310 TPH drum mix asphalt plant with baghouse 11



State of Ohio Environmental Protection Agency
Division of Air Pollution Control

Final Permit-to-Install and Operate
Permit Number: P0105409
Facility ID: 0302020006
Effective Date: 2/9/2010

Authorization

Facility ID: 0302020006
Application Number(s): M0000563
Permit Number: P0105409
Permit Description: The purpose of this administrative modification permit is to allow for the use of shingles in the aggregate mix. By allowing the use of shingles, the emission limitations will not increase.
Permit Type: Renewal
Permit Fee: \$0.00
Issue Date: 2/9/2010
Effective Date: 2/9/2010
Expiration Date: 2/9/2015
Permit Evaluation Report (PER) Annual Date: Jan 1 - Dec 31, Due Feb 15

This document constitutes issuance to:

Shelly Materials Plant No 82
600 N SUGAR ST
LIMA, OH 45801

of a Permit-to-Install and Operate for the emissions unit(s) identified on the following page.

Ohio EPA District Office or local air agency responsible for processing and administering your permit:

Ohio EPA DAPC, Northwest District Office
347 North Dunbridge Road
Bowling Green, OH 43402
(419)352-8461

The above named entity is hereby granted this Permit-to-Install and Operate for the air contaminant source(s) (emissions unit(s)) listed in this section pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the described emissions unit(s) will operate in compliance with applicable State and federal laws and regulations.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Chris Korleski
Director



State of Ohio Environmental Protection Agency
Division of Air Pollution Control

Final Permit-to-Install and Operate

Permit Number: P0105409

Facility ID: 0302020006

Effective Date: 2/9/2010

Authorization (continued)

Permit Number: P0105409

Permit Description: The purpose of this administrative modification permit is to allow for the use of shingles in the aggregate mix. By allowing the use of shingles, the emission limitations will not increase.

Permits for the following emissions unit(s) or groups of emissions units are in this document as indicated below:

| | |
|-----------------------------------|--|
| Emissions Unit ID: | P901 |
| Company Equipment ID: | 310 TPH drum mix asphalt plant with baghouse |
| Superseded Permit Number: | 03-13933 |
| General Permit Category and Type: | Not Applicable |



State of Ohio Environmental Protection Agency
Division of Air Pollution Control

Final Permit-to-Install and Operate

Permit Number: P0105409

Facility ID: 0302020006

Effective Date: 2/9/2010

A. Standard Terms and Conditions



1. What does this permit-to-install and operate ("PTIO") allow me to do?

This permit allows you to install and operate the emissions unit(s) identified in this PTIO. You must install and operate the unit(s) in accordance with the application you submitted and all the terms and conditions contained in this PTIO, including emission limits and those terms that ensure compliance with the emission limits (for example, operating, recordkeeping and monitoring requirements).

2. Who is responsible for complying with this permit?

The person identified on the "Authorization" page, above, is responsible for complying with this permit until the permit is revoked, terminated, or transferred. "Person" means a person, firm, corporation, association, or partnership. The words "you," "your," or "permittee" refer to the "person" identified on the "Authorization" page above.

The permit applies only to the emissions unit(s) identified in the permit. If you install or modify any other equipment that requires an air permit, you must apply for an additional PTIO(s) for these sources.

3. What records must I keep under this permit?

You must keep all records required by this permit, including monitoring data, test results, strip-chart recordings, calibration data, maintenance records, and any other record required by this permit for five years from the date the record was created. You can keep these records electronically, provided they can be made available to Ohio EPA during an inspection at the facility. Failure to make requested records available to Ohio EPA upon request is a violation of this permit requirement.

4. What are my permit fees and when do I pay them?

There are two fees associated with permitted air contaminant sources in Ohio:

- PTIO fee. This one-time fee is based on a fee schedule in accordance with Ohio Revised Code (ORC) section 3745.11, or based on a time and materials charge for permit application review and permit processing if required by the Director.

You will be sent an invoice for this fee after you receive this PTIO and payment is due within 30 days of the invoice date. You are required to pay the fee for this PTIO even if you do not install or modify your operations as authorized by this permit.

- Annual emissions fee. Ohio EPA will assess a separate fee based on the total annual emissions from your facility. You self-report your emissions in accordance with Ohio Administrative Code (OAC) Chapter 3745-78. This fee assessed is based on a fee schedule in ORC section 3745.11 and funds Ohio EPA's permit compliance oversight activities. For facilities that are permitted as synthetic minor sources, the fee schedule is adjusted annually for inflation. Ohio EPA will notify you when it is time to report your emissions and to pay your annual emission fees.

5. When does my PTIO expire, and when do I need to submit my renewal application?

This permit expires on the date identified at the beginning of this permit document (see "Authorization" page above) and you must submit a renewal application to renew the permit. Ohio EPA will send a renewal notice to you approximately six months prior to the expiration date of this permit. However, it is very important that you submit a complete renewal permit application (postmarked prior to expiration of this permit) even if you do not receive the renewal notice.



If a complete renewal application is submitted before the expiration date, Ohio EPA considers this a timely application for purposes of ORC section 119.06, and you are authorized to continue operating the emissions unit(s) covered by this permit beyond the expiration date of this permit until final action is taken by Ohio EPA on the renewal application.

6. What happens to this permit if my project is delayed or I do not install or modify my source?

This PTIO expires 18 months after the issue date identified on the "Authorization" page above unless otherwise specified if you have not (1) started constructing the new or modified emission sources identified in this permit, or (2) entered into a binding contract to undertake such construction. This deadline can be extended by up to 12 months, provided you apply to Ohio EPA for this extension within a reasonable time before the 18-month period has ended and you can show good cause for any such extension.

7. What reports must I submit under this permit?

An annual permit evaluation report (PER) is required in addition to any malfunction reporting required by OAC rule 3745-15-06 or other specific rule-based reporting requirement identified in this permit. Your PER due date is identified in the Authorization section of this permit.

8. If I am required to obtain a Title V operating permit in the future, what happens to the operating provisions and PER obligations under this permit?

If you are required to obtain a Title V permit under OAC Chapter 3745-77 in the future, the permit-to-operate portion of this permit will be superseded by the issued Title V permit. From the effective date of the Title V permit forward, this PTIO will effectively become a PTI (permit-to-install) in accordance with OAC rule 3745-31-02(B). The following terms and conditions will no longer be applicable after issuance of the Title V permit: Section B, Term 1.b) and Section C, for each emissions unit, Term a)(2).

The PER requirements in this permit remain effective until the date the Title V permit is issued and is effective, and cease to apply after the effective date of the Title V permit. The final PER obligation will cover operations up to the effective date of the Title V permit and must be submitted on or before the submission deadline identified in this permit on the last day prior to the effective date of the Title V permit.

9. What are my obligations when I perform scheduled maintenance on air pollution control equipment?

You must perform scheduled maintenance of air pollution control equipment in accordance with OAC rule 3745-15-06(A). If scheduled maintenance requires shutting down or bypassing any air pollution control equipment, you must also shut down the emissions unit(s) served by the air pollution control equipment during maintenance, unless the conditions of OAC rule 3745-15-06(A)(3) are met. Any emissions that exceed permitted amount(s) under this permit (unless specifically exempted by rule) must be reported as deviations in the annual permit evaluation report (PER), including nonexempt excess emissions that occur during approved scheduled maintenance.

10. Do I have to report malfunctions of emissions units or air pollution control equipment? If so, how must I report?

If you have a reportable malfunction of any emissions unit(s) or any associated air pollution control system, you must report this to the Ohio EPA DAPC, Northwest District Office in accordance with OAC



rule 3745-15-06(B). Malfunctions that must be reported are those that result in emissions that exceed permitted emission levels. It is your responsibility to evaluate control equipment breakdowns and operational upsets to determine if a reportable malfunction has occurred.

If you have a malfunction, but determine that it is not a reportable malfunction under OAC rule 3745-15-06(B), it is recommended that you maintain records associated with control equipment breakdown or process upsets. Although it is not a requirement of this permit, Ohio EPA recommends that you maintain records for non-reportable malfunctions.

11. Can Ohio EPA or my local air agency inspect the facility where the emission unit(s) is/are located?

Yes. Under Ohio law, the Director or his authorized representative may inspect the facility, conduct tests, examine records or reports to determine compliance with air pollution laws and regulations and the terms and conditions of this permit. You must provide, within a reasonable time, any information Ohio EPA requests either verbally or in writing.

12. What happens if one or more emissions units operated under this permit is/are shut down permanently?

Ohio EPA can terminate the permit terms associated with any permanently shut down emissions unit. "Shut down" means the emissions unit has been physically removed from service or has been altered in such a way that it can no longer operate without a subsequent "modification" or "installation" as defined in OAC Chapter 3745-31.

You should notify Ohio EPA of any emissions unit that is permanently shut down by submitting a certification that identifies the date on which the emissions unit was permanently shut down. The certification must be submitted by an authorized official from the facility. You cannot continue to operate an emission unit once the certification has been submitted to Ohio EPA by the authorized official.

You must comply with all recordkeeping and reporting for any permanently shut down emissions unit in accordance with the provisions of the permit, regulations or laws that were enforceable during the period of operation, such as the requirement to submit a PER, air fee emission report, or malfunction report. You must also keep all records relating to any permanently shutdown emissions unit, generated while the emissions unit was in operation, for at least five years from the date the record was generated.

Again, you cannot resume operation of any emissions unit certified by the authorized official as being permanently shut down without first applying for and obtaining a permit pursuant to OAC Chapter 3745-31.

13. Can I transfer this permit to a new owner or operator?

You can transfer this permit to a new owner or operator. If you transfer the permit, you must follow the procedures in OAC Chapter 3745-31, including notifying Ohio EPA or the local air agency of the change in ownership or operator. Any transferee of this permit must assume the responsibilities of the transferor permit holder.



State of Ohio Environmental Protection Agency
Division of Air Pollution Control

Final Permit-to-Install and Operate

Permit Number: P0105409

Facility ID: 0302020006

Effective Date: 2/9/2010

14. Does compliance with this permit constitute compliance with OAC rule 3745-15-07, "air pollution nuisance"?

This permit and OAC rule 3745-15-07 prohibit operation of the air contaminant source(s) regulated under this permit in a manner that causes a nuisance. Ohio EPA can require additional controls or modification of the requirements of this permit through enforcement orders or judicial enforcement action if, upon investigation, Ohio EPA determines existing operations are causing a nuisance.

15. What happens if a portion of this permit is determined to be invalid?

If a portion of this permit is determined to be invalid, the remainder of the terms and conditions remain valid and enforceable. The exception is where the enforceability of terms and conditions are dependent on the term or condition that was declared invalid.



State of Ohio Environmental Protection Agency
Division of Air Pollution Control

Final Permit-to-Install and Operate

Permit Number: P0105409

Facility ID: 0302020006

Effective Date: 2/9/2010

B. Facility-Wide Terms and Conditions



State of Ohio Environmental Protection Agency
Division of Air Pollution Control

Final Permit-to-Install and Operate

Permit Number: P0105409

Facility ID: 0302020006

Effective Date: 2/9/2010

1. This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).
 - a) For the purpose of a permit-to-install document, the facility-wide terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (1) None.
 - b) For the purpose of a permit-to-operate document, the facility-wide terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (1) None.



State of Ohio Environmental Protection Agency
Division of Air Pollution Control

Final Permit-to-Install and Operate

Permit Number: P0105409

Facility ID: 0302020006

Effective Date: 2/9/2010

C. Emissions Unit Terms and Conditions



1. P901, 310 TPH drum mix asphalt plant with baghouse

Operations, Property and/or Equipment Description:

310 TPH drum mix asphalt plant with baghouse.

a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

(1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. g)(2)

(2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

a. b)(1)b., b)(2)d., c)(2), d)(3), d)(4), e)(1), f)(1)b., f)(1)c., f)(1)d., f)(1)e. f)(1)f., f)(1)g. and f)(1)h.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

| | Applicable Rules/Requirements | Applicable Emissions Limitations/Control Measures |
|----|-------------------------------|---|
| a. | OAC rule 3745-31-05(A)(3)(a) | <p><u>Dryer stack emissions:</u></p> <p>Nitrogen oxides (NOx) emissions while burning any approved fuel shall not exceed 37.51 pounds per hour</p> <p>Sulfur dioxide (SO₂) emissions while burning any approved fuel shall not exceed 37.51 pounds per hour</p> <p>Carbon monoxide (CO) emissions while burning any approved fuel shall not exceed 139.50 pounds per hour</p> <p>Volatile organic compound (VOC) emissions while burning any approved fuel shall not exceed 93.31 pounds per hour</p> <p>Particulate emissions (PE) while burning any approved fuel shall not exceed 10.23</p> |



| | Applicable Rules/Requirements | Applicable Emissions Limitations/Control Measures |
|----|-------------------------------|--|
| | | <p>pounds per hour</p> <p>Visible emission restrictions [See b)(2)c.]</p> <p>See b)(2)a. through b)(2)e.</p> |
| b. | OAC rule 3745-31-05(D) | <p><u>Stack emissions</u> NOx emissions shall not exceed 24.20 tons per rolling, 12-month period</p> <p>SO₂ emissions shall not exceed 24.20 tons per rolling, 12-month period</p> <p>CO emissions shall not exceed 90.00 tons per rolling, 12-month period</p> <p>VOC emissions shall not exceed 60.20 tons per rolling, 12-month period</p> <p>PE shall not exceed 6.60 tons per rolling, 12-month period</p> <p><u>Asphalt Load Out Emissions</u> Emissions from the load out operations shall not exceed 0.27 tons of CO per rolling, 12-month period, 0.10 tons of PE per rolling, 12-month period and 0.83 tons of VOC per rolling 12-month period</p> <p><u>Asphalt Silo Filling Emissions</u> Emissions from the silo filling operations shall not exceed 0.24 tons of CO per rolling, 12-month period, 0.12 tons of PE per rolling, 12-month period and 2.44 tons of VOC per rolling 12-month period</p> <p><u>Cold End Fugitive Dust Emissions</u> Emissions of fugitive dust associated with the cold aggregate, sand and RAP loading, and the cold aggregate, sand and RAP transfer operations shall not exceed 1.92 tons of fugitive dust per rolling, 12-month period</p> |
| c. | OAC rule 3745-21-08(B) | See b)(2)f. |
| d. | 40 CFR Part 60, Subpart I | <p>PE shall not exceed 0.04 gr/dscf</p> <p>Visible PE from the stack shall not exceed 20 percent opacity as a 6-minute average.</p> |
| e. | OAC rule 3745-17-07(B) | See b)(2)g. |



| | Applicable Rules/Requirements | Applicable Emissions Limitations/Control Measures |
|--|---|---|
| | OAC rule 3745-17-08(B) OAC rule 3745-17-07(A) OAC rule 3745-17-11(B) OAC rule 3745-18-06(E)(2) | |

(2) Additional Terms and Conditions

- a. "Best Available Technology" (BAT) for this emissions unit has been determined to be use of baghouse for drum mix operations, compliance with OAC rule 3745-31-05(D) and 40 CFR Part 60, Subpart I.
- b. The permittee shall employ best available control measures to minimize or eliminate visible emissions of fugitive dust from emissions unit P901. If the inherent moisture in the asphalt plant raw material is not sufficient to comply with the opacity restrictions in section b)(2)c., the permittee shall install equipment to apply water or any other suitable dust suppressant, at appropriate locations on the line.

Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

- c. Visible particulate emissions of fugitive dust shall be less than or equal to 20 percent opacity, as a three minute average.
- d. All number 2 and on-spec used oil burned in this emission unit shall have a sulfur content equal to or less than 0.5 percent, by weight.
- e. Each shipment of oil burned in this emissions unit shall be "on-specification" (on-spec) oil and shall meet the used oil specifications contained in OAC rule 3745-279-11. The permittee shall determine that the used fuel oil meets these specifications by performing analyses or obtaining copies of analyses or other information from the supplier documenting that the used fuel oil does not exceed (except for flash point which shall not fall below) the following limitations:

Property/Contaminant Allowable Specifications

| | |
|----------------|---|
| arsenic | 5 ppm, maximum |
| cadmium | 2 ppm, maximum |
| chromium | 10 ppm, maximum |
| lead | 100 ppm, maximum |
| total halogens | less than 1,000 ppm; or less than 4,000 ppm if the presumption that the used oil contains hazardous waste is rebutted, as described below |
| flash point | 100°F, minimum |



The used oil burned in this emissions unit shall contain less than the quantifiable levels of PCBs as defined in 40 CFR 761.3, and also shall not exceed the following mercury limitation nor fall below the following heating value:

| | |
|--------------|-----------------------------|
| PCB's | less than 2 ppm |
| heat content | 135,000 Btu/gallon, minimum |
| mercury | 1 ppm, maximum |

Used oil containing 1,000 ppm or greater total halogens is presumed to be a hazardous waste under the rebuttable presumption provided under paragraph (B)(1) of rule 3745-279-10 of the Administrative Code. The permittee may receive and burn used oil equaling or exceeding 1,000 ppm total halogens, but less than 4,000 ppm, only if the permittee has successfully demonstrated, pursuant to OAC rule 3745-279-63, that the used oil does not contain a listed hazardous waste, by either acquiring and maintaining source process information which demonstrates that the used oil was contaminated by halogenated constituents that would not be listed hazardous waste or by demonstrating that the used oil does not contain significant concentrations of halogens by acquiring and maintaining representative analytical data. Acceptable analytical test protocols that can be used to analyze used oil for halogenated hazardous constituents include SW-846 Test Methods 9075, 9076, and 9077.*

If analytical results demonstrate that used oil containing 1,000 ppm or more total halogens, but less than 4,000 total halogens, does not contain greater than 100 ppm of any individual halogenated hazardous constituent found in the F001 and F002 listings in OAC rule 3745-51-31 and there is no information suggesting that any other halogenated hazardous constituent (e.g., chlorinated pesticides) has come in contact with the oil, then the presumption that the oil contains hazardous waste has been successfully rebutted.** The rebuttable presumption does not apply to either metal working oils/fluids containing chlorinated paraffins, if processed through a tolling arrangement as described in OAC rule 3745-279-24(C), or used oils contaminated with chlorofluorocarbons removed from refrigeration units.

The burning of used oil not meeting the above limitations is prohibited in this emissions unit and the fuel oil analyses shall document compliance with each limitation before it is burned. The management and burning of used oil is subject to the Standards for the Management of Used Oil, OAC Chapter 3745-279, and the permittee shall document and assure that used oils burned in this emissions unit meet all of the applicable requirements of this Chapter. If the used oil analyses shows total halogens of 1,000 ppm or greater, the permittee shall obtain and maintain all the necessary records to successfully rebut the presumption that the used oil contains or has been mixed with a listed hazardous waste in accordance with this permit.

*EPA publication SW-846, 3rd (or most current) edition, is available from the Government Printing Office, P.O. Box 371954, Pittsburgh, PA 15250-7954; 202/512-1800, document number 955-001-00000-1.



**DHWM policy documented in "Used Oil Burners - New Guidance for Rebuttable Presumption", published April 2008 or most current policy

- f. The permittee has satisfied the "best available control techniques and operating practices" required pursuant to OAC paragraph 3745-21-08(B) by committing to comply with the best available technology requirements established pursuant to OAC paragraph 3745-31-05(A)(3) in this permit-to-install.

On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the requirement to satisfy the "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

- g. The emission limitation specified by this rule is equivalent to or less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

c) Operational Restrictions

- (1) The permittee may not receive or burn any used oil which does not meet the standards in OAC rule 3745-279-11 and the specifications listed in this permit without first obtaining a permit-to-install or permit-to-install and operate that authorizes the burning of off-specification used oil. The burning of off-specification used oil, subject to OAC rule 3745-279-60 through 67, is prohibited as a fuel in this emissions unit.
- (2) This emissions unit has been in operation for more than 12 months and, as such, the permittee has existing records to generate the rolling, 12-month summation of the asphalt production rate, upon issuance of this permit. The maximum annual asphalt production rate for this emissions unit shall not exceed 400,000 tons, based upon a rolling, 12-month summation of the production rates.
- (3) The permittee may substitute reclaimed asphalt pavement (RAP) in the raw material feed mix in amounts not to exceed 50 percent of all aggregate materials introduced at any given time.

The permittee may substitute asphalt shingles. Asphalt shingles removed from buildings (tear-off material) may be used but only if it has been determined that they do not contain asbestos. Verification that the shingles do not contain asbestos can either be done by actual testing of a representative sample of the shingles, or by verification from the shingle manufacturer that the shingles do not contain asbestos. Records shall be kept documenting the asbestos verification of any shingles used in the feed mix consistent with the language requirements in the standard terms and conditions.

- (4) The permittee shall only burn #2 fuel oil and/or on-spec used oil in this emissions unit. Any changes in the materials employed/combusted may be deemed a "modification" to the emissions unit and, as such will require prior notification to and approval from the Ohio EPA, Division of Air Pollution Control, Northwest District Office.
- (5) The pressure drop across the baghouse shall be maintained within the range of 3 to 6 inches of water while the emissions unit is in operation.



- (6) The permittee shall operate and maintain the fuel burner in accordance with the manufacturer's recommendations to ensure efficient combustion of the fuel(s) and to ensure compliance with the applicable emission limitations for CO and NOx. The permittee shall submit a copy of all *Burner Tuning Reporting Form for Asphalt Concrete Plants* forms produced during the past calendar year to the appropriate Ohio EPA District Office or local air agency responsible for the permitting of the facility with the PER.

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall receive and maintain the chemical analyses from the supplier/marketer for each shipment of used oil burned in this emissions unit (or if the oil is generated on site, the permittee shall conduct the chemical analyses), which shall contain the following information:
 - a. the date the used oil was received at the facility and the amount received;
 - b. the name, address, and U.S. EPA identification number (if applicable) of the generator, transporter, processor/refiner, supplier, and/or marketer;
 - c. the results of the following chemical analyses, demonstrating that the used oil meets the standards in OAC rule 3745-279-11:
 - i. arsenic content, in ppm;
 - ii. the cadmium content, in ppm;
 - iii. the chromium content, in ppm;
 - iv. the lead content, in ppm;
 - v. total halogens, in ppm; and
 - vi. the flash point;
 - d. where the chemical analysis shows a total halogen content between 1,000 ppm, and below 4,000 ppm, the successful demonstration for the rebuttal of the presumption that the used oil contains or has been mixed with a listed hazardous waste, as described in OAC rule 3745-279-63(C); and
 - e. the results of the analyses demonstrating that the used oil meets the heating value and the mercury and PCB limitations contained in this permit.

Each analysis shall be kept in a readily accessible location for a period of not less than 5 years* following the receipt of each shipment of used oil and shall be made available to the Ohio EPA Division of Hazardous Waste Management and/or the Division of Air Pollution Control (the appropriate Ohio EPA District Office or local air agency) upon verbal or written request. Any authorized representative of the Ohio EPA may sample or require sampling of any used oil shipments received, stored, or burned by/at this facility for periodic detailed chemical analyses through an independent laboratory.

*The Division of Air Pollution Control requires these records to be maintained for 5 years.



- (2) The permittee shall maintain daily records of the following information:
 - a. the maximum amount, in percent, of RAP and/or shingles used in any mix.
- (3) The permittee shall maintain monthly records of the following information:
 - a. asphalt production rate in tons per month;
 - b. the rolling, 12-month summation of the monthly asphalt production rate; and
 - c. the rolling, 12-month summation, in tons, of the PE, SO₂, NO_x, VOC and CO emissions.
- (4) For each shipment of number 2 fuel oil and on-spec used oil received for burning in this emissions unit, the permittee shall maintain records of the total quantity of oil received and the permittee's or oil supplier's analyses for sulfur content and heat content.
- (5) The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. the color of the emissions;
 - b. whether the emissions are representative of normal operations;
 - c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. the total duration of any visible emission incident; and
 - e. any corrective actions taken to eliminate the visible emissions.
- (6) The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible emissions of fugitive dust from non stack egress points of this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. the location and color of the emissions;
 - b. whether the emissions are representative of normal operations;
 - c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. the total duration of any visible emission incident; and
 - e. any corrective actions taken to minimize or eliminate the visible emissions.



If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item (d) above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

- (7) The permittee shall install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a daily basis.
- (8) While performing each burner tuning, the permittee shall record the results of the burner tuning using the *Burner Tuning Reporting Form for Asphalt Concrete Plants* form (as found in g)(1)). An alternative form may be used upon approval of the appropriate Ohio EPA District Office or local air agency. The permittee shall submit a copy of all *Burner Tuning Reporting Form for Asphalt Concrete Plants* forms produced during the past calendar year to the appropriate Ohio EPA District Office or local air agency responsible for the permitting of the facility with the PER.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify:
 - a. all deviations (excursions) of the following emission limitations, operational restrictions and/or control device operating parameter limitations that restrict the Potential to Emit (PTE) of any regulated air pollutant and have been detected by the monitoring, record keeping and/or testing requirements in this permit:
 - i. all exceedances of the rolling 12-month asphalt production limitation;
 - ii. all exceedances of the rolling 12-month total PE, SO₂, NO_x, VOC, and CO emission limitations; and
 - iii. all exceedances of the sulfur content limitations for #2 fuel oil and on-spec used oil specifications, as listed in b)(2)d and b)(2)e.
 - b. probable cause of each deviation (excursion);
 - c. any corrective actions that were taken to remedy the deviations (excursions) or prevent future deviations (excursions); and
 - d. the magnitude and duration of each deviation (excursion).

If no deviations (excursions) occurred during a calendar quarter, the permittee shall submit a report that states that no deviations (excursions) occurred during the quarter.



The quarterly reports shall be submitted, electronically through Ohio EPA Air Services, each year by January 31 (covering October to December), April 30 (covering January to March), July 31 (covering April to June), and October 31 (covering July to September), unless an alternative schedule has been established and approved by the Director (the appropriate District Office or local air agency).

- (2) Annual Permit Evaluation Report (PER) forms will be mailed to the permittee at the end of the reporting period specified in the Authorization section of this permit. The permittee shall submit the PER in the form and manner provided by the director by the due date identified in the Authorization section of this permit. The permit evaluation report shall cover a reporting period of no more than twelve-months for each air contaminant source identified in this permit.
- (3) The permittee shall identify in the annual PER the following information concerning the quality of used oil burned in this emissions unit:
 - a. any exceedance of the used oil standards in OAC rule 3745-279-11;
 - b. any occasion where used oil containing 1,000 ppm or more total halogens was burned prior to receiving information demonstrating a successful rebuttal of the presumption that the used oil contains or has been mixed with a listed hazardous waste;
 - c. any exceedance of the limitations for mercury and/or PCBs; and
 - d. any deviation from the minimum heat content of 135,000 Btu/gallon.
- (4) Where the analytical results for any shipment of used oil burned in this emissions unit establish that the used oil contains total halogens greater than 1,000 ppm, but less than 4,000 ppm, the results of the analysis for total halogens (from the appropriate test Method 9075, 9076, or 9077) and the information obtained to rebut the presumption that the used oil contains or has been mixed with a listed hazardous waste shall be submitted to the appropriate District Office or local air agency. Each rebuttal demonstration shall include:
 - a. the date the used oil was received;
 - b. the facility location or identification number where the oil was or will be burned;
 - c. the amount of oil in the shipment; and
 - d. all information, including all the analytical results, relied upon by the permittee to rebut the presumption that the used oil contains or has been mixed with a listed hazardous waste.

The rebuttal demonstrations for used oil received from October to December shall be submitted by January 31; used oil received from January to March, by April 30; used oil received from April to June, by July 31; and used oil received from July to September, by October 31.



f) Testing Requirements

(1) Compliance with the emissions limitation(s) in section b)(1) of these terms and conditions shall be determined in accordance with the following method(s):

a. Emission Limitations:

Nitrogen oxide (NO_x) emissions while burning any approved fuel shall not exceed 37.51 pounds per hour; Sulfur dioxide (SO₂) emissions while burning any approved fuel shall not exceed 37.51 pounds per hour; Carbon monoxide (CO) emissions shall not exceed 139.50 lbs per hour; Volatile organic compound (VOC) emissions shall not exceed 93.31 pounds per hour; and Particulate emissions (PE) shall not exceed 0.04 gr/dscf and 10.23 lbs/hr.

Applicable Compliance Method:

The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:

- i. The emission testing shall be conducted within 120 days after the issuance of this permit or after beginning operation whichever date is later. Emissions testing for secondary fuels shall be conducted within 60 days after the switch to the secondary fuel. Emissions testing shall be necessary for each fuel type used only once per permitting cycle.
- ii. The emission testing shall be conducted to demonstrate compliance with the allowable mass emission rates for PE, VOC, CO, NO_x and SO₂ for the primary fuel. Prior to secondary fuel emissions testing, the permittee shall consult the appropriate Ohio EPA District Office or local air agency to determine which pollutants should be tested.
- iii. The following test method(s) shall be employed to demonstrate compliance with the allowable mass emission rate(s) for:

PE, Methods 1-5 of 40 CFR Part 60, Appendix A.

NO_x, Methods 1-4 and 7 or 7E of 40 CFR Part 60, Appendix A.

SO₂, Methods 1-4 and 6 or 6C of 40 CFR Part 60, Appendix A

CO, Methods 1-4 and 10 of 40 CFR Part 60, Appendix A

VOC, Methods 1-4 and 25 and/or 18 of 40 CFR Part 60, Appendix A

The VOC pounds per hour emission rate observed during the emissions test shall be calculated in accordance with OAC paragraph 3745-21-10(C)(7). In lieu of this the permittee shall convert the mass emission value from VOC as carbon to VOC using the molecular weight of propane, i.e., the VOC as carbon emission rate observed during testing shall be converted to the appropriate units by multiplying the VOC emission rate observed during testing (in lbs./hr) by 44 (propane) and dividing by 36 (3 atoms of carbon).



Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA.

- iv. The test(s) shall be conducted while this emissions unit is operating at or near its maximum capacity and burning number 2 fuel oil or on-spec used oil for PE, VOC, CO, NO_x and SO₂ and employing RAP to verify VOC emissions, unless otherwise specified or approved by the appropriate Ohio EPA District Office or local air agency.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the appropriate Ohio EPA District Office or local air agency. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the appropriate Ohio EPA District Office or local air agency's refusal to accept the results of the emission test(s).

Personnel from the appropriate Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office or local air agency within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the appropriate Ohio EPA District Office or local air agency.

- b. Emission Limitation:

6.60 tons PE per rolling, 12-month period

Applicable Compliance Method:

Compliance shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of PE per ton of asphalt produced, by the actual rolling 12-month summation of asphalt produced, in tons per rolling 12-month period (as derived from the records required by d)(3)), and dividing by 2000.

- c. Emission Limitation:

24.20 tons SO₂ per rolling, 12-month period

Applicable Compliance Method:

Compliance shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of SO₂ per ton of asphalt produced, by the actual rolling 12-month summation of asphalt produced, in tons per rolling



12-month period (as derived from the records required by d)(3)), and dividing by 2000.

d. Emissions Limitation:

24.20 tons NOx per rolling, 12-month period

Applicable Compliance Method:

Compliance shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of NOx per ton of asphalt produced, by the actual rolling 12-month summation of asphalt produced, in tons per rolling 12-month period (as derived from the records required by d)(3)), and dividing by 2000.

e. Emissions Limitation:

90.00 tons CO per rolling, 12-month period

Applicable Compliance Method:

Compliance shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of CO per ton of asphalt produced, by the actual rolling 12-month summation of asphalt produced, in tons per rolling 12-month period (as derived from the records required by d)(3)), and dividing by 2000.

f. Emissions Limitation:

60.20 tons VOC per rolling, 12-month period

Applicable Compliance Method:

Compliance shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of VOC per ton of asphalt produced, by the actual rolling 12-month summation of asphalt produced, in tons per rolling 12-month period (as derived from the records required by d)(3)), and dividing by 2000.

g. Emission Limitation:

Emissions of fugitive dust associated with the cold aggregate, sand and RAP loading, and the cold aggregate, sand and RAP transfer operations shall not exceed 1.92 tons of PE per rolling 12-month period.

Applicable Compliance Method:

Compliance shall be assumed based upon the following worst case calculations:

Fugitives emissions from the cold end are calculated as follows [AP-42-5th Edition, Table 11.12-2 (6/06)]

Hopper loading:



400,000 tons of material/year X 0.0051 lb PE/ton of material = 2040 lbs PE/yr

Aggregate transfer:

200,000 tons of aggregate/year X 0.0069 lb PE/ton of aggregate = 1380 lbs PE/yr

Sand transfer:

200,000 tons of sand/year X 0.0021 lb PE/ton of sand = 420 lbs PE/yr

The sum of the above is 3840 lbs PE/yr X 1 ton/2000 lbs = 1.92 tons of PE

h. Emission Limitation:

Emissions from load out operations shall not exceed 0.27 ton CO per rolling 12-month period, 0.10 ton PE per rolling 12-month period and 0.83 tons of VOC per rolling 12-month period.

Emissions from silo filling operations shall not exceed 0.24 ton CO per rolling, 12-month period, 0.12 ton PE per rolling 12-month period, and 2.44 tons VOC per rolling 12-month period.

Applicable Compliance Method:

Compliance shall be assumed based upon the following worst case calculations:

Asphalt plant silo filling and plant load out emissions from AP-42, Table 11.1-14 dated 3/2004

Known:

V = -0.5 Asphalt volatility factor (default)

T = 325 HMA mix temp (F) (default)

For silo filling, 1.4 percent of TOC is not VOC (AP-42 Table 11.1-16 dated 3/2004)

For plant load out, 7.3 percent of TOC is not VOC (AP-42 Table 11.1-16 dated 3/2004)

| Activity | Pollutant | Predictive Emission Factor Equation, lb/ton |
|--------------|-----------|--|
| Silo filling | PE | $EF=0.000332+0.00105(-V)e^{((0.0251)(T+460)-20.43)}$ |
| Load out | PE | $EF=0.000181+0.00141(-V)e^{((0.0251)(T+460)-20.43)}$ |
| Silo filling | VOC | $EF= [0.0504(-V)e^{((0.0251)(T+460)-20.43)}] \times (1-0.014)$ |
| Load out | VOC | $EF= [0.0172(-V)e^{((0.0251)(T+460)-20.43)}] \times (1-$ |



| | | |
|--------------|----|---|
| | | 0.073) |
| Silo filling | CO | $EF=0.00488(-V)e^{((0.0251)(T+460)-20.43)}$ |
| Load out | CO | $EF=0.00558(-V)e^{((0.0251)(T+460)-20.43)}$ |

Based on the above information, the emission factors and emissions are as follows:

| Activity | Pollutant | lb/ton | tons/yr (at 400,000 tons/yr production) |
|--------------|-----------|-----------------------|---|
| Silo filling | PE | 5.86×10^{-4} | 0.12 |
| Load out | PE | 5.22×10^{-4} | 0.10 |
| Silo filling | VOC | 1.22×10^{-2} | 2.44 |
| Load out | VOC | 4.16×10^{-3} | 0.83 |
| Silo filling | CO | 1.18×10^{-3} | 0.24 |
| Load out | CO | 1.35×10^{-3} | 0.27 |

i. Emissions Limitation:

Visible emissions of fugitive dust shall be less than or equal to 20 percent opacity, as a 6-minute average.

Applicable Compliance Method:

Upon request by the appropriate Ohio EPA District Office or local air agency, visible particulate emissions shall be determined according to USEPA Method 9.

j. Emission Limitation:

Visible particulate emissions from the stack shall not exceed 20 percent opacity as a 6-minute average.

Applicable Compliance Method:

Upon request by the appropriate Ohio EPA District Office or local air agency, visible particulate emissions shall be determined according to USEPA Method 9.

(2) Burner Tuning

a. Introduction

The permittee shall submit a "burner tuning procedure" to Ohio EPA, Central Office for this facility thirty days after receiving this permit to install. The burner tuning procedure shall contain the basic elements as described in the language below with the ability for the permittee to adjust the frequency of the burner tuning procedure depending upon the production of the plant. In the event no burner tuning procedure is submitted then the following shall be adhered to:



b. Qualifications for Burner Tuning

Technicians who conduct the burner tuning must be qualified to perform the expected tasks. The permittee is required to provide training to the technicians who perform the burner tuning procedure. Technicians who are qualified shall, at a minimum, have passed manufacturer's training concerning burner tuning, or have been trained by someone who has completed the manufacturer's training concerning burner tuning.

c. Portable Monitor Requirements

The permittee shall properly operate and maintain portable device(s) to monitor the concentration of NO_x, O₂ and CO in the stack exhaust gases from this emissions unit. The monitor(s) shall be capable of measuring the expected concentrations of the measured gases. The monitoring equipment shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall maintain records of each portable monitoring device's calibration.

d. Burner Tuning Procedure

The first steps concerning burner tuning involve setting the pollutant baseline levels (concentrations) utilizing the portable monitor. These baselines shall be set during the initial U.S. EPA approved emissions testing that demonstrated the emissions unit was in compliance with all applicable emissions limitations as described in f)(1). The baselines shall be determined for NO_x, and CO. Sampling should measure the exhaust gas values exiting the dryer or the baghouse. The duration of each sample shall follow the portable monitor manufacturer's recommendations. Record these values on the *Burner Tuning Reporting Form for Asphalt Concrete Plants* form (as found in g)(1)) in the "Recent Stack Test Basis Values" column.

Once the pollutant baseline levels are set, the burner shall be next tuned based on the frequency described in f)(2)e. The general procedure for tuning the burner involves the following steps:

- i. Review the plant operations to ensure the plant is operating normally.
- ii. Confirm that the portable monitor is calibrated per the manufacturer's specifications.
- iii. Using the calibrated monitor and the monitor manufacturer's recommended sampling duration, measure the stack exhaust gas values for O₂, NO_x, and CO. These measurements shall be taken at the same location as the location where the baseline samples were taken. Record the values in the "Pre-Tuning" results column on the *Burner Tuning Reporting Form for Asphalt Concrete Plants* form.
- iv. Compare the measured stack exhaust gas values with the pollutant baseline values. If all of the measured stack exhaust gas values are equal to or less than 115 percent of the pollutant baseline values, then it is not necessary to tune the burner. Go on to Section v. below.



The permittee shall have the burners tuned within two calendar weeks of any measured stack exhaust values greater than 115 percent of the baseline values. Make any necessary adjustments and repairs. Repeat Sections iii. and iv. until the measured stack exhaust gas values are equal to or less than 115 percent of the pollutant baseline values.

- v. Once all of the measured stack exhaust gas values are within the 115 percent of the pollutant baseline values, record the measured stack exhaust gas values in the "Post Tuning" results column on the *Burner Tuning Reporting Form for Asphalt Concrete Plants* form.

e. Burner Tuning Frequency

The permittee shall conduct the burner tuning procedure within 20 production days after commencement of the production season in the State of Ohio. The permittee shall conduct another burner tuning procedure within 10 production days before or after June 1st of each year and within 10 production days before or after September 1st of each year. For purposes of this permit, the production season is defined as the time period between the date the first ton of asphalt is produced and the date that the last ton of asphalt is produced during the same calendar year. A burner tuning is not required if the production season ends prior to the associated tuning due date. If the baseline level testing or the initial season tuning is done within 30 days prior to June 1 or September 1, the tuning associated with that due date is not required.

In addition to the burner tuning procedure required above, the permittee shall conduct the burner tuning procedure within 20 production days from the date the facility switches to a fuel that is different than the fuel burned during the initial emissions tests that establish the pollutant baseline levels or the fuel burned during the most recent burner tuning procedure, whichever is later.

(3) Used Oil Analyses

The metal content for arsenic, cadmium, chromium, lead, and mercury shall be analyzed using a "Total Analysis" or "Total Metals" testing methodology. The metal contents shall not be analyzed using a leachate procedure such as the "Toxicity Characteristic Leaching Procedure" or "Extraction Procedure Toxicity Test". Chapter 2 of "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods" (SW-846, 3rd Edition, most current update) shall be used for selecting the appropriate test methods for the used oil analyses.

g) Miscellaneous Requirements

- (1) Burner Tuning Form (see next page)
- (2) Modeling to demonstrate compliance with, the "Toxic Air Contaminant Statute", ORC 3704.03(F)(4)(b), was not necessary because the emissions unit's maximum annual emissions for each toxic air contaminant, as defined in OAC rule 3745-114-01, will be less than 1.0 ton per year. OAC Chapter 3745-31 requires permittees to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by



State of Ohio Environmental Protection Agency
Division of Air Pollution Control

Final Permit-to-Install and Operate

Permit Number: P0105409

Facility ID: 0302020006

Effective Date: 2/9/2010

OAC rule 3745-31-01. The permittee is hereby advised that changes in the composition of the materials, or use of new materials, that would cause the emissions of any toxic air contaminant to increase to above 1.0 ton per year may require the permittee to apply for and obtain a new permit to install.



State of Ohio Environmental Protection Agency
Division of Air Pollution Control

Final Permit-to-Install and Operate

Permit Number: P0105409

Facility ID: 0302020006

Effective Date: 2/9/2010

| BURNER TUNING REPORTING FORM FOR ASPHALT CONCRETE PLANTS | |
|--|--|
| Facility ID: | Tuning Date: |
| Legal Name: | Other Company Name (if different than legal name): |
| Mailing Address: | Other Company Site Address: (if different than mailing address): |
| City, State, Zip Code: | Other Company City, County, Zip Code: |
| Site Contact Person: | Site Contact Telephone Number: |
| Site Contact Title: | Site Contact Fax Number: |
| Name of company performing tuning: | Name of company performing emission monitoring: |
| Type of plant (ie: batch, drum mix, etc.): | Calibration date for analyzers: |

Reason for Tuning: Season Initial Tuning June Tuning September Tuning Fuel Switch Other (describe)

Fuel employed during tuning: Natural Gas Propane # 2 Fuel Oil # 4 Fuel Oil Used Oil Other (describe)

Tuning Results:

| Parameter | Recent Stack Test Pollutant Baseline Levels ¹ | Results | |
|--|--|------------|--------------------------|
| | | Pre Tuning | Post Tuning ³ |
| Fuel flow to the burner (gallon/hr) (for fuel oil and on-spec used oil) | | | |
| Fuel pressure (psi) | | | |
| For burners that require compressed air for proper operation, pressure at the burner (psi) | | | |
| Carbon Monoxide (CO) concentrations (ppm) ² | | | |
| NOx concentrations (ppm) ² | | | |
| Oxygen concentrations (per cent) ² | | | |
| Asphalt Production (tons/hr) | | | |

¹These values are based on the results of the most recent Ohio EPA approved emissions test.

² Specify whether on a dry or wet basis.

³ If the burner did not require adjusting, please record N/A in the post tuning column.



State of Ohio Environmental Protection Agency
Division of Air Pollution Control

Final Permit-to-Install and Operate

Permit Number: P0105409

Facility ID: 0302020006

Effective Date: 2/9/2010

Describe in detail a list of adjustments and/or repairs made to bring the operating parameters into conformance with the manufacturers specifications. Use additional paper if necessary.

Authorized Signature: This signature shall constitute personal affirmation that all statements or assertions of fact made in this form are true and complete, comply fully with applicable state requirements, and shall subject the signatory to liability under applicable state laws forbidding false or misleading statements.

| | |
|--------------------------------------|-------------------------------------|
| Name of Official (Printed or Typed): | Title of Official and Phone Number: |
| Signature of Official: | Date: |