



State of Ohio Environmental Protection Agency

Street Address:

Lazarus Gov. Center
122 S. Front Street
Columbus, OH 43215

TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049
Columbus, OH 43216-1049

10/24/01

CERTIFIED MAIL

RE: Final Title V Chapter 3745-77 permit

04-48-01-0220
Citgo Petroleum Corp. - Toledo Terminal
Carl Venzke
CITGO Petroleum Corporation
6433 Cosgray Road
Dublin, OH 43016-8737

Dear Carl Venzke:

Enclosed is the Title V permit that allows you to operate the facility in the manner indicated in the permit. Because this permit may contain several conditions and restrictions, we urge you to read it carefully.

The Ohio EPA is encouraging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action of the Director is final and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed with the Environmental Review Appeals Commission within thirty (30) days after notice of the Director's action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. It is also requested by the Director that a copy of the appeal be served upon the Environmental Enforcement Section of the Office of the Attorney General. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
236 East Town Street
Room 300
Columbus, Ohio 43215

If you have any questions, please contact Toledo Div of Environmental Services.

Very truly yours,

Thomas G. Rigo, Manager
Field Operations and Permit Section
Division of Air Pollution Control

cc: Toledo Div of Environmental Services
File, DAPC PMU



State of Ohio Environmental Protection Agency

FINAL TITLE V PERMIT

Issue Date: 10/24/01

Effective Date: 10/24/01

Expiration Date: 10/24/06

This document constitutes issuance of a Title V permit for Facility ID: 04-48-01-0220 to: Citgo Petroleum Corp. - Toledo Terminal 1840 Otter Creek Road Oregon, OH 43616

Emissions Unit ID (Company ID)/Emissions Unit Activity Description

Table with 3 columns: Emissions Unit ID (Company ID), Emissions Unit Activity Description, and Emissions Unit Activity Description. Rows include J001 (Loading Rack), T001 (Tank 114), T002 (Tank 115), T004 (Tank 217), T005 (Tank 222), T006 (Tank 223), T011 (Tank 281), T012 (Tank 282), T014 (Tank 210), T015 (Tank 283), T018 (Tank 216), T019 (Tank 218), T020 (Tank 219), T021 (Tank 220), T022 (Tank 221), T024 (Tank 236), T029 (Tank 244), T030 (Tank 245), T031 (Tank 284), and T035 (Tank 209).

You will be contacted approximately eighteen (18) months prior to the expiration date regarding the renewal of this permit. If you are not contacted, please contact the appropriate Ohio EPA District Office or local air agency listed below. This permit and the authorization to operate the air contaminant sources (emissions units) at this facility shall expire at midnight on the expiration date shown above. If a renewal permit is not issued prior to the expiration date, the permittee may continue to operate pursuant to OAC rule 3745-77-04(A) and in accordance with the terms of this permit beyond the expiration date, provided that a complete renewal application is submitted no earlier than eighteen (18) months and no later than one-hundred eighty (180) days prior to the expiration date.

Described below is the Ohio EPA District Office or local air agency that is responsible for processing and administering your Title V permit:

Toledo Div of Environmental Services
348 South Erie Street
Toledo, OH 43602-1633
(419) 936-3015

OHIO ENVIRONMENTAL PROTECTION AGENCY

Handwritten signature of Christopher Jones

Christopher Jones
Director

PART I - GENERAL TERMS AND CONDITIONS

A. State and Federally Enforceable Section

1. Monitoring and Related Recordkeeping and Reporting Requirements

- a. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:
 - i. The date, place (as defined in the permit), and time of sampling or measurements.
 - ii. The date(s) analyses were performed.
 - iii. The company or entity that performed the analyses.
 - iv. The analytical techniques or methods used.
 - v. The results of such analyses.
 - vi. The operating conditions existing at the time of sampling or measurement.
- b. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.
- c. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall submit required reports in the following manner:
 - i. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
 - ii. Quarterly written reports of (i) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, excluding deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06, that have been detected by the testing, monitoring and recordkeeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures taken, shall be promptly made to the appropriate Ohio EPA District Office or local air agency. These quarterly written reports shall satisfy the requirements of OAC rule 3745-77-07(A)(3)(c)(i) and (ii) pertaining to the submission of monitoring reports every six months and OAC rule 3745-77-07(A)(3)(c)(iii) pertaining to the prompt reporting of all deviations except malfunctions, which shall be reported in accordance with OAC rule 3745-15-06. The written reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.) See B.8 below if no deviations occurred during the quarter.
 - iii. Written reports, which identify any deviations from the federally enforceable monitoring, recordkeeping, and reporting requirements contained in this permit shall be submitted to

the appropriate Ohio EPA District Office or local air agency every six months, i.e., by January 31 and July 31 of each year for the previous six calendar months. These semi-annual written reports shall satisfy the requirements of OAC rule 3745-77-07(A)(3)(c)(i) and (ii) pertaining to the reporting of any deviations related to the monitoring, recordkeeping, and reporting requirements. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report, which states that no deviations occurred during that period.

- iv. Each written report shall be signed by a responsible official certifying that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.

2. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction, i.e., upset, of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. (The definition of an upset condition shall be the same as that used in OAC rule 3745-15-06(B)(1) for a malfunction.) The verbal and written reports submitted pursuant to OAC rule 3745-15-06 shall satisfy the requirements of OAC rule 3745-77-07(A)(3)(c)(iii) pertaining to the prompt reporting of deviations caused by malfunctions or upsets.

Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emission unit(s) that is (are) served by such control system(s).

3. Risk Management Plans

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. 7401 et seq. ("Act"), the permittee shall comply with the requirement to register such a plan.

4. Title IV Provisions

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

5. Severability Clause

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition declared invalid.

6. General Requirements

- a. The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and reissuance, or modification, or for denial of a permit renewal application.
- b. It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.
- c. This permit may be modified, reopened, revoked, or revoked and reissued, for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.
- d. This permit does not convey any property rights of any sort, or any exclusive privilege.
- e. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

7. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78.

8. Marketable Permit Programs

No revision of this permit is required under any approved economic incentive, marketable permits, emissions trading, and other similar programs or processes for changes that are provided for in this permit.

9. Reasonably Anticipated Operating Scenarios

The permittee is hereby authorized to make changes among operating scenarios authorized in this permit without notice to the Ohio EPA, but, contemporaneous with making a change from one operating scenario to another, the permittee must record in a log at the permitted facility the scenario under which the permittee is operating. The permit shield provided in these general terms and conditions shall apply to all operating scenarios authorized in this permit.

10. Reopening for Cause

This Title V permit will be reopened prior to its expiration date under the following conditions:

- a. Additional applicable requirements under the Act become applicable to one or more emissions units covered by this permit, and this permit has a remaining term of three or more years. Such a reopening shall be completed not later than eighteen months after promulgation of the applicable requirement. No such reopening is required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions has been extended pursuant to paragraph (E)(1) of OAC rule 3745-77-08.
- b. This permit is issued to an affected source under the acid rain program and additional requirements (including excess emissions requirements) become applicable. Upon approval by the Administrator, excess emissions offset plans shall be deemed to be incorporated into the permit, and shall not require a reopening of this permit.
- c. The Director of the Ohio EPA or the Administrator of the U.S. EPA determines that the federally applicable requirements in this permit are based on a material mistake, or that inaccurate statements were made in establishing the emissions standards or other terms and conditions of this permit related to such federally applicable requirements.
- d. The Administrator of the U.S. EPA or the Director of the Ohio EPA determines that this permit must be revised or revoked to assure compliance with the applicable requirements.

11. Federal and State Enforceability

Only those terms and conditions designated in this permit as federally enforceable, that are required under the Act, or any of its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA, the State, and citizens under the Act. All other terms and conditions of this permit shall not be federally enforceable and shall be enforceable under State law only.

12. Compliance Requirements

- a. Any document (including reports) required to be submitted and required by a federally applicable requirement in this Title V permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.
- b. Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:
 - i. At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.

- ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with paragraph (E) of OAC rule 3745-77-03.
 - iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.
 - iv. As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.
- c. The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually, or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:
- i. Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
 - ii. An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.
- d. Compliance certifications concerning the terms and conditions contained in this permit that are federally enforceable emission limitations, standards, or work practices, shall be submitted to the appropriate Ohio EPA District Office or local air agency in the following manner and with the following content:
- i. Compliance certifications shall be submitted annually on a calendar year basis. The annual certification shall be submitted on or before April 30th of each year during the permit term.
 - ii. Compliance certifications shall include the following:
 - (a) An identification of each term or condition of this permit that is the basis of the certification.
 - (b) The permittee's current compliance status.
 - (c) Whether compliance was continuous or intermittent.
 - (d) The method(s) used for determining the compliance status of the source currently and over the required reporting period.
 - (e) Such other facts as the Director of the Ohio EPA may require in the permit to determine the compliance status of the source.
 - iii. Compliance certifications shall contain such additional requirements as may be specified pursuant to sections 114(a)(3) and 504(b) of the Act.

13. Permit Shield

- a. Compliance with the terms and conditions of this permit (including terms and conditions established for alternate operating scenarios, emissions trading, and emissions averaging, but

excluding terms and conditions for which the permit shield is expressly prohibited under OAC rule 3745-77-07) shall be deemed compliance with the applicable requirements identified and addressed in this permit as of the date of permit issuance.

- b. This permit shield provision shall apply to any requirement identified in this permit pursuant to OAC rule 3745-77-07(F)(2), as a requirement that does not apply to the source or to one or more emissions units within the source.

14. Operational Flexibility

The permittee is authorized to make the changes identified in OAC rule 3745-77-07(H)(1)(a) to (H)(1)(c) within the permitted stationary source without obtaining a permit revision, if such change is not a modification under any provision of Title I of the Act [as defined in OAC rule 3745-77-01(JJ)], and does not result in an exceedance of the emissions allowed under this permit (whether expressed therein as a rate of emissions or in terms of total emissions), and the permittee provides the Administrator of the U.S. EPA and the appropriate Ohio EPA District Office or local air agency with written notification within a minimum of seven days in advance of the proposed changes, unless the change is associated with, or in response to, emergency conditions. If less than seven days notice is provided because of a need to respond more quickly to such emergency conditions, the permittee shall provide notice to the Administrator of the U.S. EPA and the appropriate District Office of the Ohio EPA or local air agency as soon as possible after learning of the need to make the change. The notification shall contain the items required under OAC rule 3745-77-07(H)(2)(d).

15. Emergencies

The permittee shall have an affirmative defense of emergency to an action brought for noncompliance with technology-based emission limitations if the conditions of OAC rule 3745-77-07(G)(3) are met. This emergency defense provision is in addition to any emergency or upset provision contained in any applicable requirement.

16. Off Permit Changes

The owner or operator of a Title V source may make any change in its operations or emissions at the source that is not specifically addressed or prohibited in the Title V permit, without obtaining an amendment or modification of the permit, provided that the following conditions are met:

- a. The change does not result in conditions that violate any applicable requirements or that violate any existing federally enforceable permit term or condition;
- b. The permittee provides contemporaneous written notice of the change to the director and the administrator, except that no such notice shall be required for changes that qualify as insignificant emission levels or activities as defined in OAC rule 3745-77-01(U). Such written notice shall describe each such change, the date of such change, any change in emissions or

pollutants emitted, and any federally applicable requirement that would apply as a result of the change;

- c. The change shall not qualify for the permit shield under OAC rule 3745-77-07(F);
- d. The permittee shall keep a record describing all changes made at the source that result in emissions of a regulated air pollutant subject to an applicable requirement, but not otherwise regulated under the permit, and the emissions resulting from those changes; and
- e. The change is not subject to any applicable requirement under Title IV of the Act or is not a modification under any provision of Title I of the Act.

Paragraph (I) of rule 3745-77-07 of the Administrative Code applies only to modification or amendment of the permittee's Title V permit. The change made may require a permit to install under Chapter 3745-31 of the Administrative Code if the change constitutes a modification as defined in that Chapter. Nothing in paragraph (I) of rule 3745-77-07 of the Administrative Code shall affect any applicable obligation under Chapter 3745-31 of the Administrative Code.

(For further clarification, the permittee can refer to Engineering Guide #63 that is available in their STARSHIP software package.)

17. Compliance Method Requirements

Nothing in this permit shall alter or affect the ability of any person to establish compliance with, or a violation of, any applicable requirement through the use of credible evidence to the extent authorized by law. Nothing in this permit shall be construed to waive any defenses otherwise available to the permittee, including but not limited to, any challenge to the Credible Evidence Rule (see 62 Fed. Reg. 8314, Feb. 24, 1997), in the context of any future proceeding.

18. Insignificant Activity

Each insignificant activity that has one or more applicable requirements shall comply with those applicable requirements.

B. State Only Enforceable Section

1. Permit to Install Requirement

Prior to the “installation” or “modification” of any “air contaminant source,” as those terms are defined in OAC rule 3745-31-01, a permit to install must be obtained from the Ohio EPA pursuant to OAC Chapter 3745-31.

2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with

this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations (See Section A of This Permit)

If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.

Part II - Specific Facility Terms and Conditions

A. State and Federally Enforcable Section

None

B. State Only Enforceable Section

1. The following insignificant emissions units are located at this facility:

T036 - 8500-gallon IVD additive tank;
Z006 - rail car slop tank;
Z007 - separator tank;
Z008 - vapor recovery knockout tank;
Z009 - loading rack pour back tank;
Z010 - pipe line pit tank; and
Z014 - tank maintenance painting.

Each insignificant emissions unit at this facility must comply with all applicable State and federal regulations, as well as any emissions limitation and/or control requirements contained within a permit to install for the emissions unit.

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Loading Rack (J001)
Activity Description: Loading Rack

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
gasoline loading rack with carbon adsorption vapor recovery unit	OAC rule 3745-21-09(Q) 40 CFR Part 60, Subpart XX	See A.I.2.a below. 35 milligrams of total organic compounds per liter of gasoline loaded See A.I.2.b - A.I.2.e below.

2. Additional Terms and Conditions

- 2.a The mass emission limitation established by this rule is less stringent than that established by 40 CFR Part 60, Subpart XX.
- 2.b The loading rack shall be equipped with a vapor collection system whereby during the transfer of gasoline to any delivery vessel:
 - i. all vapors displaced from the delivery vessel during loading are vented only to the vapor collection system; and
 - ii. the pressure in the vapor collection system is maintained between minus 6 and plus 18 inches of water gauge pressure.
- 2.c The loading rack shall be equipped with a vapor control system whereby:
 - i. all vapors collected by the vapor collection system are vented to the vapor control system;
 - ii. the mass emissions of VOC from the vapor control system do not exceed 35 milligrams of total organic compounds per liter of gasoline loaded into the delivery vessel; and
 - iii. any liquid gasoline returned to a stationary storage tank from the vapor control system is free of entrained air to the extent possible with good engineering design.
- 2.d A means shall be provided to prevent drainage of gasoline from the loading device when it is not in use or to accomplish complete drainage before the loading device is disconnected.
- 2.e All gasoline loading lines and vapor lines shall be equipped with fittings which are vapor tight.

II. Operational Restrictions

1. The permittee shall not permit gasoline to be spilled, discarded in sewers, stored in open containers or handled in any other manner that would result in evaporation.
2. The permittee shall repair within 15 days any leak from the vapor collection system and vapor control system when such leak is equal to or greater than one hundred percent (100%) of the lower explosive limit as propane, as determined by OAC rule 3745-21-10(K).
3. Each vapor collection system shall be designed to prevent any total organic compound vapors collected at one loading rack from passing to another loading rack.
4. Loadings of liquid product into gasoline tank trucks shall be limited to vapor-tight gasoline tank trucks using the following procedures:
 - a. the permittee shall obtain the vapor tightness documentation described in 40 CFR 60.505(b) for each gasoline tank truck which is to be loaded at the facility;
 - b. the permittee shall require the tank identification number to be recorded as each gasoline tank truck is loaded;
 - c. the permittee shall cross-check each tank identification number, obtained in accordance with section A.II.4.b of this permit, with the file of tank vapor tightness documentation within 2 weeks after the corresponding tank is loaded;
 - d. the permittee shall notify the permittee of each nonvapor-tight gasoline tank truck loaded within 3 weeks after the loading has occurred;
 - e. the permittee shall take steps assuring that the nonvapor-tight gasoline tank truck will not be re-loaded until vapor tightness documentation for that tank is obtained; and
 - f. alternate procedures to those described in sections A.II.4.a through A.II.4.e of this permit for limiting gasoline tank truck loadings may be used upon application to, and approval by, the Toledo Division of Environmental Services.
5. The permittee shall act to assure that loadings of gasoline tank trucks are made only into tanks equipped with vapor collection equipment that is compatible with the terminal's vapor collection system.
6. The permittee shall act to assure that the terminal's and the truck's vapor collection systems are connected during each loading of a gasoline tank truck. Examples of actions to accomplish this include training drivers in the hookup procedures and posting visible reminder signs at the loading racks.
7. The vapor collection and liquid loading equipment shall be designed and operated to prevent gauge pressure in the gasoline tank truck from exceeding 4,500 pascals (450 mm of water) during product loading. This level is not to be exceeded when measured by the procedures specified in 40 CFR 60.503(d).
8. No pressure-vacuum vent in the bulk gasoline terminal's vapor collection system shall begin to open at a system pressure less than 4,500 pascals (450 mm of water).

II. Operational Restrictions (continued)

9. The following carbon adsorption/gasoline absorption vapor recovery unit (VRU) parameters have been identified as key operating parameters for which acceptable operating ranges have been established. The permittee shall operate the VRU within these acceptable operating ranges:
- a. to ensure proper regeneration of the carbon beds, the maximum vacuum pulled during the regeneration cycle shall be greater than or equal to 25 inches of Hg and the air purge solenoid must be open;
 - b. to ensure proper absorption by the absorption tower, the gasoline supply temperature shall not exceed 98 degrees F;
 - c. to ensure a proper flow rate from the absorption tower to the carbon bed, the absorber pressure shall be maintained between 8 psi and 15 psi; and
 - d. to ensure proper adsorption, the carbon bed temperature, at all levels, shall not exceed 150 degrees F.
- Operation of the VRU outside of these specified operating ranges is not necessarily indicative of an emission violation, but rather serves as a trigger level for maintenance and/or repair activities, or further investigation to establish correct operation.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure in the vapor collection system, while the emissions unit is in operation, to demonstrate compliance with the pressure range established in section A.I.2.b.ii. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s).
- Also, the permittee shall properly install, operate, and maintain equipment to monitor the gasoline supply temperature, the absorber pressure, the carbon bed temperature (at all levels), the carbon bed vacuum, and the delivery tank gauge pressure while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s).
2. The permittee shall collect and record the following information each day:
- a. the temperature of the carbon bed after each regeneration cycle, including any cooling cycle(s);
 - b. the temperature of the carbon bed, at all levels;
 - c. a log or record of operating time for the capture (collection) system, control device, monitoring equipment, and the associated emissions unit;
 - d. the carbon bed vacuum, in inches of Hg;
 - e. the gasoline supply temperature, in degrees F;
 - f. the absorber pressure, in psi;
 - g. the delivery tank gauge pressure, in mm of water; and
 - h. the pressure in the vapor collection system, i.e., the pressure in the vapor recovery line before entering the carbon adsorber that is on-line.
3. Each calendar month, the vapor collection system, the vapor processing system, and each loading rack handling gasoline shall be inspected during the loading of gasoline tank trucks for total organic compounds liquid or vapor leaks. Detection methods incorporating sight, sound, or smell are acceptable. Each detection of a leak shall be recorded and the source of the leak repaired within 15 calendar days after it is detected.
4. The tank truck vapor tightness documentation required under 40 CFR 60.502(e)(1) shall be kept on file at the terminal in a permanent form available for inspection.

III. Monitoring and/or Record Keeping Requirements (continued)

5. The documentation file for each gasoline tank truck shall be updated at least once per year to reflect current test results, as determined by Method 27 of 40 CFR Part 60, Appendix A. This documentation shall include, as a minimum, the following information:
 - a. test title (Gasoline Delivery Tank Pressure Test - EPA Reference Method 27);
 - b. tank owner and address;
 - c. tank identification number;
 - d. testing location;
 - e. date of test;
 - f. tester name and signature;
 - g. name, signature, and affiliation of witnessing inspector, if any; and
 - h. test results, including the actual pressure change in 5 minutes, in mm of water column (average for 2 runs).
6. A record of each monthly leak inspection required under 40 CFR 60.502(j) shall be kept on file at the terminal. Inspection records shall include, as a minimum, the following information:
 - a. date of inspection;
 - b. findings (may include no leak(s) discovered, or the location, nature and severity of leak(s));
 - c. leak determination method;
 - d. corrective action taken, including the date each leak was repaired and the reason for any repair interval in excess of 15 days; and
 - e. inspector name and signature.
7. The permittee shall keep documentation of all notifications required under 40 CFR 60.502(e)(4) on file at the terminal. The permittee shall also keep records of all replacements or additions of components performed on an existing vapor processing system.
8. All records required under section A.III of this permit shall be maintained in accordance with the Monitoring and Related Recordkeeping and Reporting Requirements of Part I - General Terms and Conditions.

IV. Reporting Requirements

1. The permittee shall submit pressure deviation (excursion) reports that identify all periods of time during which the pressure in the vapor collection system did not comply with the allowable range of minus 6 to plus 18 inches of water gauge pressure specified in section A.I.2.b.ii above.
2. The permittee shall submit deviation (excursion) reports which identify any parameter readings that are outside of the acceptable value or range for each vapor collection system and VRU key operating parameter established in sections A.II.7 and A.II.10 above.
3. The permittee shall notify the Toledo Division of Environmental Services in writing of any monthly record indicating that a leak was not repaired within 15 days. The notification shall include a copy of such record and shall be sent to the Toledo Division of Environmental Services within 30 days after the leak was discovered.

V. Testing Requirements

1. The permittee shall conduct emission testing for this emissions unit in accordance with the following requirements:
 - 1.a The emission testing shall be conducted within the first year after issuance of the permit between April 30 and May 31 and within 12 months prior to permit renewal, between April 30 and May 31.
 - 1.b The emission testing shall be conducted to demonstrate compliance with the allowable mass emission rate of total organic compounds from gasoline loading.
 - 1.c The following test method(s) shall be employed to demonstrate compliance with the allowable mass emission rate(s): Methods 2A, 21 and 25A or 25B of 40 CFR Part 60, Appendix A. Testing shall be performed in accordance with the requirements of 40 CFR 60.503 and OAC rule 3745-21-10(E).
 - 1.d The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity, unless otherwise specified or approved by the Toledo Division of Environmental Services.

V. Testing Requirements (continued)

- 1.e** Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Toledo Division of Environmental Services. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Toledo Division of Environmental Services refusing to accept the results of the emission test(s).

Personnel from the Toledo Division of Environmental Services shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Toledo Division of Environmental Services within 30 days following completion of the test(s).

- 2.** Compliance with the emission limitation in section A.I.1 of these terms and conditions shall be determined in accordance with the following method:

2.a Emission Limitation:

35 mg of total organic compounds per liter of gasoline loaded

Applicable Compliance Method:

Compliance shall be determined through emissions testing, as required in section A.V.1 of this permit.

The permittee conducted testing on May 12, 1999, to demonstrate compliance with the emission limitation of 35 milligrams of total organic compounds per liter of gasoline loaded, in accordance with 40 CFR 60.503 and OAC rule 3745-21-10(E). Method 25A of 40 CFR Part 60, Appendix A, was performed and determined that emissions were 1.02 milligrams of total organic compounds per liter of gasoline loaded.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
gasoline loading rack with carbon adsorption vapor recovery unit	OAC rule 3745-31-05 (PTI 04-550)	5.5 lbs/hr of volatile organic compounds (VOC)

2. Additional Terms and Conditions

None

II. Operational Restrictions

1. The gasoline loading rate for this emissions unit shall not exceed 577,000 gallons per day. This limitation was established based on the average gasoline loading rate during the May 12, 1999 compliance demonstration, divided by 0.90. Operation of this emissions unit at a loading rate greater than 577,000 gallons per day is not necessarily indicative of an emission violation, but rather serves as a trigger level for additional testing and/or further investigation to establish compliance with the emission limitations. The permittee may increase the daily gasoline loading limitation by demonstrating compliance through testing, performed in accordance with the procedures and method(s) detailed in 40 CFR 60.503 and OAC rule 3745-21-10(E), at a higher average loading rate.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain daily records of the volume of gasoline loaded through J001, in gallons.
2. The permittee shall calculate and record the average hourly VOC emission rate, in accordance with section B.V.1.a of this permit, for each operating day.

IV. Reporting Requirements

1. The permittee shall submit semi-annual reports which document any exceedance(s) of the hourly VOC emission limit established under section B.I.1 of this permit and/or the gasoline throughput restriction established under section B.II.1 of this permit. These reports shall be submitted by February 15 and August 15 of each year and shall address the previous 6 calendar months (July through December and January through June, respectively).

V. Testing Requirements

1. Compliance with the emission limitations in section B.I.1 of these terms and conditions shall be determined in accordance with the following method:

V. Testing Requirements (continued)

1.a Emission Limitation:

5.5 lbs/hr of VOC

Applicable Compliance Method:

Compliance shall be determined based upon the record keeping and reporting requirements of sections B.III.2 and B.IV.1 of this permit.

To calculate the hourly VOC emission rate, multiply the VOC emission factor generated during the most recent compliance demonstration by the daily throughput volume of gasoline loaded recorded in section B.III.1, and divide this product by 24 hours/day.

The most recent emission factor, based on the May 12, 1999 compliance demonstration, is 1.02 milligrams per liter (8.5 E-06 lb/gal).

If required, the permittee shall demonstrate compliance through emissions testing performed in accordance with the procedures and method(s) detailed in 40 CFR 60.503 and OAC rule 3745-21-10(E).

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Tank 114 (T001)
Activity Description: Internal Floating Roof Tank

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
internal floating roof storage tank (9,606 barrels)	OAC rule 3745-21-09(L)	See A.I.2 below.

2. Additional Terms and Conditions

- 2.a The fixed roof storage tank shall be equipped with an internal floating roof.
- 2.b The automatic bleeder vents shall be closed at all times except when the roof is floated off or landed on the roof leg supports, and the rim vents, if provided, shall be set to open when the roof is being floated off the roof leg supports or is at the manufacturer's recommended setting.
- 2.c All openings, except stub drains, shall be equipped with a cover, seal or lid which is to be in a closed position at all times except when in actual use for tank gauging or sampling.

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain records of the following information:
 - a. the types of petroleum liquids stored in the tank; and
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.
2. All records required under section A.III of this permit shall be maintained in accordance with the monitoring and related recordkeeping and reporting requirements of Part I - General Terms and Conditions.

IV. Reporting Requirements

None

V. Testing Requirements

None

Facility Name: **Citgo Petroleum Corporation - Toledo Terminal**
Facility ID: **04-48-01-0220**
Emissions Unit: **Tank 114 (T001)**

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Tank 115 (T002)
Activity Description: Internal Floating Roof Tank

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
internal floating roof storage tank (10,459 barrels)	OAC rule 3745-21-09(L)	See A.I.2 below.

2. Additional Terms and Conditions

- 2.a The fixed roof storage tank shall be equipped with an internal floating roof.
- 2.b The automatic bleeder vents shall be closed at all times except when the roof is floated off or landed on the roof leg supports, and the rim vents, if provided, shall be set to open when the roof is being floated off the roof leg supports or is at the manufacturer's recommended setting
- 2.c All openings, except stub drains, shall be equipped with a cover, seal or lid which is to be in a closed position at all times except when in actual use for tank gauging or sampling.

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain records of the following information:
 - a. the types of petroleum liquids stored in the tank; and
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.
2. All records required under section A.III of this permit shall be maintained in accordance with the monitoring and related recordkeeping and reporting requirements of Part I - General Terms and Conditions.

IV. Reporting Requirements

None

V. Testing Requirements

None

Facility Name: **Citgo Petroleum Corporation - Toledo Terminal**
Facility ID: **04-48-01-0220**
Emissions Unit: **Tank 115 (T002)**

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Tank 217 (T004)
Activity Description: Internal Floating Roof Tank

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
internal floating roof storage tank (56,000 barrels)	OAC rule 3745-21-09(L)	See A.I.2 below.

2. Additional Terms and Conditions

- 2.a The fixed roof storage tank shall be equipped with an internal floating roof.
- 2.b The automatic bleeder vents shall be closed at all times except when the roof is floated off or landed on the roof leg supports, and the rim vents, if provided, shall be set to open when the roof is being floated off the roof leg supports or is at the manufacturer's recommended setting
- 2.c All openings, except stub drains, shall be equipped with a cover, seal or lid which is to be in a closed position at all times except when in actual use for tank gauging or sampling.

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain records of the following information:
 - a. the types of petroleum liquids stored in the tank; and
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.
2. All records required under section A.III of this permit shall be maintained in accordance with the monitoring and related recordkeeping and reporting requirements of Part I - General Terms and Conditions.

IV. Reporting Requirements

None

V. Testing Requirements

None

Facility Name: **Citgo Petroleum Corporation - Toledo Terminal**
Facility ID: **04-48-01-0220**
Emissions Unit: **Tank 217 (T004)**

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Tank 222 (T005)
Activity Description: Internal Floating Roof Tank

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
internal floating roof storage tank (97,443 barrels)	OAC rule 3745-21-09(L)	See A.I.2 below.

2. Additional Terms and Conditions

- 2.a The fixed roof storage tank shall be equipped with an internal floating roof.
- 2.b The automatic bleeder vents shall be closed at all times except when the roof is floated off or landed on the roof leg supports, and the rim vents, if provided, shall be set to open when the roof is being floated off the roof leg supports or is at the manufacturer's recommended setting
- 2.c All openings, except stub drains, shall be equipped with a cover, seal or lid which is to be in a closed position at all times except when in actual use for tank gauging or sampling.

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain records of the following information:
 - a. the types of petroleum liquids stored in the tank; and
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.
2. All records required under section A.III of this permit shall be maintained in accordance with the monitoring and related recordkeeping and reporting requirements of Part I - General Terms and Conditions.

IV. Reporting Requirements

None

V. Testing Requirements

None

Facility Name: **Citgo Petroleum Corporation - Toledo Terminal**
Facility ID: **04-48-01-0220**
Emissions Unit: **Tank 222 (T005)**

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Tank 223 (T006)
Activity Description: External Floating Roof Tank

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
external floating roof tank (179,405 barrels)	OAC rule 3745-21-09(Z)	See A.I.2 below.

2. Additional Terms and Conditions

- 2.a Any welded external floating roof storage tank shall be equipped with a liquid-mounted primary seal and rim-mounted secondary seal, a mechanical shoe primary seal and a rim-mounted secondary seal, a mechanical shoe primary seal and a shoe-mounted, secondary seal, and the shoe-mounted secondary seal was installed prior to 1/10/81, a vapor-mounted primary seal and a rim-mounted secondary seal, and the vapor-mounted primary seal was installed prior to 1/01/81, or a flexible wiper primary seal and a rim-mounted secondary seal, and the flexible wiper primary seal was installed prior to 1/01/81, that meet the following requirements:
 - i. there shall be no visible holes, tears, or other openings in the seal or seal fabric;
 - ii. for the mechanical shoe primary seal, the total seal gap area shall not exceed 10.0 square inches per foot of tank diameter; and
 - iii. for the rim-mounted secondary seal, the total seal gap area shall not exceed 1.0 square inch per foot of tank diameter.

The permittee may change the seal types during the term of this permit provided that a written notification and revised "emission activity category" form, including the results of the latest seal gap measurements, are submitted to Toledo Division of Environmental Services within 30 days after the change occurs.
- 2.b Any opening in the external floating roof, except automatic bleeder vents, rim space vents, leg sleeves, stub drains and slotted gauging/sampling wells, shall be equipped with:
 - i. a cover, seal or lid which remains in the closed position at all times without any visible gaps, except when the opening is in actual use; and
 - ii. a projection into the tank below the liquid surface.
- 2.c Any automatic bleeder vent shall remain in the closed position, except when the external floating roof is floated off or landed on the roof leg supports.
- 2.d Any rim vent shall be set to open at the manufacturer's recommended setting, except when the external floating roof is being floated off the roof leg supports.

2. Additional Terms and Conditions (continued)

- 2.e** Any emergency roof drain shall be equipped with a slotted membrane fabric cover or other device which covers at least 90 percent of the area of the opening.
- 2.f** Any stub drain shall be equipped with a projection into the tank below the liquid surface.
- 2.g** Any slotted gauging/sampling well shall be equipped with an object which floats on the liquid surface within the well and which covers at least 90 percent of the area of the well opening.

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

- 1.** The seal and seal fabric shall be inspected annually for visible holes, tears, or other openings.
- 2.** The secondary seal gap shall be measured annually in accordance with the method specified in paragraph (I) of OAC rule 3745-21-10.
- 3.** The primary seal gap shall be measured at least once every 5 years, in accordance with the method specified in paragraph (I) of OAC rule 3745-21-10.
- 4.** The permittee shall maintain records of the following information:
 - a. the dates and results of any seal and seal fabric inspections and any seal gap measurements;
 - b. the types of petroleum liquids stored in the tank;
 - c. the annual throughput of any petroleum liquid stored in the tank; and
 - d. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.
- 5.** All records required under section A.III of this permit shall be maintained in accordance with the monitoring and related recordkeeping and reporting requirements of Part I - General Terms and Conditions.

IV. Reporting Requirements

- 1.** The permittee shall notify the Director (Toledo Division of Environmental Services) within 30 days of any seal and seal fabric inspection or any seal gap measurement which documents a violation of the applicable control equipment requirements. The notification shall also describe the corrective actions which have been or will be taken to achieve compliance.

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Tank 281 (T011)
Activity Description: External Floating Roof Tank

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
external floating roof tank (100,000 barrels)	OAC rule 3745-21-09(Z)	See A.I.2 below.

2. Additional Terms and Conditions

- 2.a Any welded external floating roof storage tank shall be equipped with a liquid-mounted primary seal and rim-mounted secondary seal, a mechanical shoe primary seal and a rim-mounted secondary seal, a mechanical shoe primary seal and a shoe-mounted, secondary seal, and the shoe-mounted secondary seal was installed prior to 01/01/81, a vapor-mounted primary seal and a rim-mounted secondary seal, and the vapor-mounted primary seal was installed prior to 01/01/81, or a flexible wiper primary seal and a rim-mounted secondary seal, and the flexible wiper primary seal was installed prior to 1/01/81, that meet the following requirements:
 - i. there shall be no visible holes, tears, or other openings in the seal or seal fabric;
 - ii. for the mechanical shoe primary seal, the total seal gap area shall not exceed 10.0 square inches per foot of tank diameter; and
 - iii. for the rim-mounted secondary seal, the total seal gap area shall not exceed 1.0 square inch per foot of tank diameter.

The permittee may change the seal types during the term of this permit provided that a written notification and revised "emission activity category" form, including the results of the latest seal gap measurements, are submitted to Toledo Division of Environmental Services within 30 days after the change occurs.

- 2.b Any opening in the external floating roof, except automatic bleeder vents, rim space vents, leg sleeves, stub drains and slotted gauging/sampling wells, shall be equipped with:
 - i. a cover, seal or lid which remains in the closed position at all times without any visible gaps, except when the opening is in actual use; and
 - ii. a projection into the tank below the liquid surface.
- 2.c Any automatic bleeder vent shall remain in the closed position, except when the external floating roof is floated off or landed on the roof leg supports.
- 2.d Any rim vent shall be set to open at the manufacturer's recommended setting, except when the external floating roof is being floated off the roof leg supports.

2. Additional Terms and Conditions (continued)

- 2.e** Any emergency roof drain shall be equipped with a slotted membrane fabric cover or other device which covers at least 90 percent of the area of the opening.
- 2.f** Any stub drain shall be equipped with a projection into the tank below the liquid surface.
- 2.g** Any slotted gauging/sampling well shall be equipped with an object which floats on the liquid surface within the well and which covers at least 90 percent of the area of the well opening.

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

- 1.** The seal and seal fabric shall be inspected annually for visible holes, tears, or other openings.
- 2.** The secondary seal gap shall be measured annually in accordance with the method specified in paragraph (I) of OAC rule 3745-21-10.
- 3.** The primary seal gap shall be measured at least once every 5 years, in accordance with the method specified in paragraph (I) of OAC rule 3745-21-10.
- 4.** The permittee shall maintain records of the following information:
 - a. the dates and results of any seal and seal fabric inspections and any seal gap measurements;
 - b. the types of petroleum liquids stored in the tank;
 - c. the annual throughput of any petroleum liquid stored in the tank; and
 - d. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.
- 5.** All records required under section A.III of this permit shall be maintained in accordance with the monitoring and related recordkeeping and reporting requirements of Part I - General Terms and Conditions.

IV. Reporting Requirements

- 1.** The permittee shall notify the Director (the Toledo Division of Environmental Services) within 30 days of any seal and seal fabric inspection or any seal gap measurement which documents a violation of the applicable control equipment requirements. The notification shall also describe the corrective actions which have been or will be taken to achieve compliance.

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Tank 282 (T012)
Activity Description: External Floating Roof Tank

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
external floating roof tank (100,000 barrels)	OAC rule 3745-21-09(Z)	See A.I.2 below.

2. Additional Terms and Conditions

- 2.a Any welded external floating roof storage tank shall be equipped with a liquid-mounted primary seal and rim-mounted secondary seal, a mechanical shoe primary seal and a rim-mounted secondary seal, a mechanical shoe primary seal and a shoe-mounted, secondary seal, and the shoe-mounted secondary seal was installed prior to 1/10/81, a vapor-mounted primary seal and a rim-mounted secondary seal, and the vapor-mounted primary seal was installed prior to 1/01/81, or a flexible wiper primary seal and a rim-mounted secondary seal, and the flexible wiper primary seal was installed prior to 1/01/81, that meet the following requirements:
 - i. there shall be no visible holes, tears, or other openings in the seal or seal fabric;
 - ii. for the mechanical shoe primary seal, the total seal gap area shall not exceed 10.0 square inches per foot of tank diameter; and
 - iii. for the rim-mounted secondary seal, the total seal gap area shall not exceed 1.0 square inch per foot of tank diameter.

The permittee may change the seal types during the term of this permit provided that a written notification and revised "emission activity category" form, including the results of the latest seal gap measurements, are submitted to Toledo Division of Environmental Services within 30 days after the change occurs.

- 2.b Any opening in the external floating roof, except automatic bleeder vents, rim space vents, leg sleeves, stub drains and slotted gauging/sampling wells, shall be equipped with:
 - i. a cover, seal or lid which remains in the closed position at all times without any visible gaps, except when the opening is in actual use; and
 - ii. a projection into the tank below the liquid surface.
- 2.c Any automatic bleeder vent shall remain in the closed position, except when the external floating roof is floated off or landed on the roof leg supports.
- 2.d Any rim vent shall be set to open at the manufacturer's recommended setting, except when the external floating roof is being floated off the roof leg supports.

2. Additional Terms and Conditions (continued)

- 2.e** Any emergency roof drain shall be equipped with a slotted membrane fabric cover or other device which covers at least 90 percent of the area of the opening.
- 2.f** Any stub drain shall be equipped with a projection into the tank below the liquid surface.
- 2.g** Any slotted gauging/sampling well shall be equipped with an object which floats on the liquid surface within the well and which covers at least 90 percent of the area of the well opening.

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

- 1.** The seal and seal fabric shall be inspected annually for visible holes, tears, or other openings.
- 2.** The secondary seal gap shall be measured annually in accordance with the method specified in paragraph (I) of OAC rule 3745-21-10.
- 3.** The primary seal gap shall be measured at least once every 5 years, in accordance with the method specified in paragraph (I) of OAC rule 3745-21-10.
- 4.** The permittee shall maintain records of the following information:
 - a. the dates and results of any seal and seal fabric inspections and any seal gap measurements;
 - b. the types of petroleum liquids stored in the tank;
 - c. the annual throughput of any petroleum liquid stored in the tank; and
 - d. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.
- 5.** All records required under section A.III of this permit shall be maintained in accordance with the monitoring and related recordkeeping and reporting requirements of Part I - General Terms and Conditions.

IV. Reporting Requirements

- 1.** The permittee shall notify the Director (the Toledo Division of Environmental Services) within 30 days of any seal and seal fabric inspection or any seal gap measurement which documents a violation of the applicable control equipment requirements. The notification shall also describe the corrective actions which have been or will be taken to achieve compliance.

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Tank 210 (T014)

Activity Description: Fixed Roof Tank. In the process of being switched to a internal floating roof storage tank.

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
fixed roof tank (80,568 barrels)	OAC rule 3745-21-09(L)	exempt (See A.I.2.a below.)

2. Additional Terms and Conditions

- 2.a The permittee shall not place, store, or hold in this fixed roof tank any petroleum liquid which, as stored, has a true vapor pressure greater than 1.52 pounds per square inch absolute, unless such tank is designed or equipped in accordance with the requirements of paragraph (L)(1) of OAC rule 3745-21-09.

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain records of the following information:
 - a. the types of petroleum liquids stored in the tank; and
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.
2. All records required under section A.III of this permit shall be maintained in accordance with the monitoring and related recordkeeping and reporting requirements of Part I - General Terms and Conditions.

IV. Reporting Requirements

1. If the permittee places, stores, or holds in the fixed roof tank any petroleum liquid with a true vapor pressure which is greater than 1.52 pounds per square inch absolute, and such tank does not comply with the requirements of paragraph (L)(1) of OAC rule 3745-21-09, the permittee shall notify the Director (the Toledo Division of Environmental Services) within 30 days of becoming aware of the occurrence.

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Tank 283 (T015)
Activity Description: Internal Floating Roof Tank

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
internal floating roof storage tank (99,938 barrels)	OAC rule 3745-21-09(L)	See A.I.2 below.

2. Additional Terms and Conditions

- 2.a The fixed roof storage tank shall be equipped with an internal floating roof.
- 2.b The automatic bleeder vents shall be closed at all times except when the roof is floated off or landed on the roof leg supports, and the rim vents, if provided, shall be set to open when the roof is being floated off the roof leg supports or is at the manufacturer's recommended setting
- 2.c All openings, except stub drains, shall be equipped with a cover, seal or lid which is to be in a closed position at all times except when in actual use for tank gauging or sampling.

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain records of the following information:
 - a. the types of petroleum liquids stored in the tank; and
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.
2. All records required under section A.III of this permit shall be maintained in accordance with the monitoring and related recordkeeping and reporting requirements of Part I - General Terms and Conditions.

IV. Reporting Requirements

None

V. Testing Requirements

None

Facility Name: **Citgo Petroleum Corporation - Toledo Terminal**
Facility ID: **04-48-01-0220**
Emissions Unit: **Tank 283 (T015)**

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Tank 216 (T018)
Activity Description: Fixed Roof Tank

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
fixed roof tank (56,000 barrels)	OAC rule 3745-21-09(L)	exempt (See A.I.2.a below.)

2. Additional Terms and Conditions

- 2.a The permittee shall not place, store, or hold in this fixed roof tank any petroleum liquid which, as stored, has a true vapor pressure greater than 1.52 pounds per square inch absolute, unless such tank is designed or equipped in accordance with the requirements of paragraph (L)(1) of OAC rule 3745-21-09.

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain records of the following information:
 - a. the types of petroleum liquids stored in the tank; and
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.
2. All records required under section A.III of this permit shall be maintained in accordance with the monitoring and related recordkeeping and reporting requirements of Part I - General Terms and Conditions.

IV. Reporting Requirements

1. If the permittee places, stores, or holds in the fixed roof tank any petroleum liquid with a true vapor pressure which is greater than 1.52 pounds per square inch absolute, and such tank does not comply with the requirements of paragraph (L)(1) of OAC rule 3745-21-09, the permittee shall notify the Director (the Toledo Division of Environmental Services) within 30 days of becoming aware of the occurrence.

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Tank 218 (T019)
Activity Description: Fixed Roof Tank

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
fixed roof tank (29,042 barrels)	OAC rule 3745-21-09(L)	exempt (See A.I.2.a below.)

2. Additional Terms and Conditions

- 2.a The permittee shall not place, store, or hold in this fixed roof tank any petroleum liquid which, as stored, has a true vapor pressure greater than 1.52 pounds per square inch absolute, unless such tank is designed or equipped in accordance with the requirements of paragraph (L)(1) of OAC rule 3745-21-09.

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain records of the following information:
 - a. the types of petroleum liquids stored in the tank; and
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.
2. All records required under section A.III of this permit shall be maintained in accordance with the monitoring and related recordkeeping and reporting requirements of Part I - General Terms and Conditions.

IV. Reporting Requirements

1. If the permittee places, stores, or holds in the fixed roof tank any petroleum liquid with a true vapor pressure which is greater than 1.52 pounds per square inch absolute, and such tank does not comply with the requirements of paragraph (L)(1) of OAC rule 3745-21-09, the permittee shall notify the Director (the Toledo Division of Environmental Services) within 30 days of becoming aware of the occurrence.

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Tank 219 (T020)
Activity Description: Internal Floating Roof Tank

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
internal floating roof storage tank (30,000 barrels)	OAC rule 3745-31-05(A)(3) (PTI 04-1112)	4 tpy of volatile organic compounds (VOC) The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09(L) and 40 CFR Part 60, Subpart Kb.
	OAC rule 3745-21-09(L)	This emission limit established by this rule is equal to or less stringent than the limit established by 40 CFR Part 60, Subpart Kb.
	40 CFR Part 60, Subpart Kb	See A.I.2 below.

2. Additional Terms and Conditions

- 2.a The fixed roof storage tank shall be equipped with an internal floating roof.
- 2.b The internal floating roof shall rest or float on the volatile organic liquid (VOL) surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal floating roof shall be floating on the liquid surface at all times, except during initial fill and during those intervals when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible.
- 2.c Each internal floating roof shall be equipped with a mechanical shoe seal. A mechanical shoe seal is a metal sheet held vertically against the wall of the storage vessel by springs or weighted levers and is connected by braces to the floating roof. A flexible coated fabric (envelope) spans the annular space between the metal sheet and the floating roof.
- 2.d Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use.
- 2.e Rim space vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting.

2. Additional Terms and Conditions (continued)

- 2.f** Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The sample well shall have a slit fabric cover that covers at least 90 percent of the opening.
- 2.g** Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover.
- 2.h** Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover.
- 2.i** Automatic bleeder vents shall be equipped with a gasket and are to be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports.

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

- 1.** The permittee shall visually inspect the internal floating roof and the primary seal through manholes and roof hatches on the fixed roof at least once every 12 months after initial fill. If the internal floating roof is not resting on the surface of the VOL inside the storage vessel, or there is liquid accumulated on the roof, or the seal is detached, or there are holes or tears in the seal fabric, the permittee shall repair the items or empty and remove the storage vessel from service within 45 days. If a failure that is detected during inspections required in this paragraph cannot be repaired within 45 days and if the vessel cannot be emptied within 45 days, a 30-day extension may be requested from the Toledo Division of Environmental Services in the inspection report required in section A.IV.1 of this permit. Such a request for an extension must document that alternate storage capacity is unavailable and specify a schedule of actions the company will take that will assure that the control equipment will be repaired or the vessel will be emptied as soon as possible.
- 2.** The permittee shall visually inspect the internal floating roof, the primary seal, gaskets, slotted membranes and sleeve seals (if any) each time the storage vessel is emptied and degassed. If the internal floating roof has defects, the primary seal has holes, tears, or other openings in the seal or the seal fabric, or the secondary seal has holes, tears, or other openings in the seal or the seal fabric, or the gaskets no longer close off the liquid surfaces from the atmosphere, or the slotted membrane has more than 10 percent open area, the permittee shall repair the items as necessary so that none of the conditions specified in this paragraph exist before refilling the storage vessel with VOL. In no event shall inspections conducted in accordance with this provision occur at intervals greater than 10 years in the case of vessels conducting the annual visual inspection as specified in section A.III.1.
- 3.** The permittee shall notify the Toledo Division of Environmental Services in writing at least 30 days prior to the filling or refilling of each storage vessel for which an inspection is required by section A.III.2 of this permit to afford the Toledo Division of Environmental Services the opportunity to have an observer present. If the inspection required by section A.III.2 is not planned and the owner or operator could not have known about the inspection 30 days in advance of refilling the tank, the owner or operator shall notify the Toledo Division of Environmental Services at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately, followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification, including the written documentation, may be made in writing and sent by express mail so that it is received by the Toledo Division of Environmental Services at least 7 days prior to the refilling.
- 4.** The permittee shall keep readily accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. These records shall be maintained for the life of the emissions unit.
- 5.** The permittee shall maintain a record of the VOL stored, the period of storage, and the maximum true vapor pressure of that VOL during the respective storage period.
- 6.** The permittee shall keep a record of each inspection performed as required by sections A.III.1 - A.III.2. Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment (seals, internal floating roof, and fittings).

III. Monitoring and/or Record Keeping Requirements (continued)

7. All records required under section A.III of this permit shall be maintained in accordance with the monitoring and related recordkeeping and reporting requirements of Part I - General Terms and Conditions.

IV. Reporting Requirements

1. If any of the conditions described in section A.III.1 of this permit are detected during the annual visual inspection, a report shall be furnished to the Toledo Division of Environmental Services within 30 days of the inspection. Each report shall identify the storage vessel, the nature of the defects, and the date the storage vessel was emptied or the nature and date of repairs made.

V. Testing Requirements

1. Compliance with the emission limitation in section A.I.1 of these terms and conditions shall be determined in accordance with the following method:

- 1.a Emission limitation:

4 tpy of VOC

Applicable Compliance Method:

Annual VOC emissions shall be calculated using the total annual throughput volume of the tank and USEPA's "Tanks Program 3.0" or subsequent versions. AP-42, Section 7.1 (2/96 version) may be used in lieu of "Tanks Program 3.0."

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Tank 220 (T021)
Activity Description: Fixed Roof Tank

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
fixed roof tank (29,091 barrels)	OAC rule 3745-21-09(L)	exempt (See A.I.2.a below.)

2. Additional Terms and Conditions

- 2.a The permittee shall not place, store, or hold in this fixed roof tank any petroleum liquid which, as stored, has a true vapor pressure greater than 1.52 pounds per square inch absolute, unless such tank is designed or equipped in accordance with the requirements of paragraph (L)(1) of OAC rule 3745-21-09.

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain records of the following information:
 - a. the types of petroleum liquids stored in the tank; and
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.
2. All records required under section A.III of this permit shall be maintained in accordance with the monitoring and related recordkeeping and reporting requirements of Part I - General Terms and Conditions.

IV. Reporting Requirements

1. If the permittee places, stores, or holds in the fixed roof tank any petroleum liquid with a true vapor pressure which is greater than 1.52 pounds per square inch absolute, and such tank does not comply with the requirements of paragraph (L)(1) of OAC rule 3745-21-09, the permittee shall notify the Director (the Toledo Division of Environmental Services) within 30 days of becoming aware of the occurrence.

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Tank 221 (T022)
Activity Description: Fixed Roof Tank

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
fixed roof tank (29,091 barrels)	OAC rule 3745-21-09(L)	exempt (See A.I.2.a below.)

2. Additional Terms and Conditions

- 2.a The permittee shall not place, store, or hold in this fixed roof tank any petroleum liquid which, as stored, has a true vapor pressure greater than 1.52 pounds per square inch absolute, unless such tank is designed or equipped in accordance with the requirements of paragraph (L)(1) of OAC rule 3745-21-09.

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain records of the following information:
 - a. the types of petroleum liquids stored in the tank; and
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.
2. All records required under section A.III of this permit shall be maintained in accordance with the monitoring and related recordkeeping and reporting requirements of Part I - General Terms and Conditions.

IV. Reporting Requirements

1. If the permittee places, stores, or holds in the fixed roof tank any petroleum liquid with a true vapor pressure which is greater than 1.52 pounds per square inch absolute, and such tank does not comply with the requirements of paragraph (L)(1) of OAC rule 3745-21-09, the permittee shall notify the Director (the Toledo Division of Environmental Services) within 30 days of becoming aware of the occurrence.

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Tank 236 (T024)
Activity Description: Internal Floating Roof Tank

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
internal floating roof storage tank (4,833 barrels)	OAC rule 3745-21-09(L)	See A.I.2 below.

2. Additional Terms and Conditions

- 2.a The fixed roof storage tank shall be equipped with an internal floating roof.
- 2.b The automatic bleeder vents shall be closed at all times except when the roof is floated off or landed on the roof leg supports, and the rim vents, if provided, shall be set to open when the roof is being floated off the roof leg supports or is at the manufacturer's recommended setting
- 2.c All openings, except stub drains, shall be equipped with a cover, seal or lid which is to be in a closed position at all times except when in actual use for tank gauging or sampling.

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain records of the following information:
 - a. the types of petroleum liquids stored in the tank; and
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.
2. All records required under section A.III of this permit shall be maintained in accordance with the monitoring and related recordkeeping and reporting requirements of Part I - General Terms and Conditions.

IV. Reporting Requirements

None

V. Testing Requirements

None

Facility Name: **Citgo Petroleum Corporation - Toledo Terminal**
Facility ID: **04-48-01-0220**
Emissions Unit: **Tank 236 (T024)**

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Tank 244 (T029)
Activity Description: Internal Floating Roof Tank

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
internal floating roof storage tank (10,122 barrels)	OAC rule 3745-21-09(L)	See A.I.2 below.

2. Additional Terms and Conditions

- 2.a The fixed roof storage tank shall be equipped with an internal floating roof.
- 2.b The automatic bleeder vents shall be closed at all times except when the roof is floated off or landed on the roof leg supports, and the rim vents, if provided, shall be set to open when the roof is being floated off the roof leg supports or is at the manufacturer's recommended setting
- 2.c All openings, except stub drains, shall be equipped with a cover, seal or lid which is to be in a closed position at all times except when in actual use for tank gauging or sampling.

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain records of the following information:
 - a. the types of petroleum liquids stored in the tank; and
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.
2. All records required under section A.III of this permit shall be maintained in accordance with the monitoring and related recordkeeping and reporting requirements of Part I - General Terms and Conditions.

IV. Reporting Requirements

None

V. Testing Requirements

None

Facility Name: **Citgo Petroleum Corporation - Toledo Terminal**
Facility ID: **04-48-01-0220**
Emissions Unit: **Tank 244 (T029)**

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Tank 245 (T030)
Activity Description: Internal Floating Roof Tank

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
internal floating roof storage tank (10,122 barrels)	OAC rule 3745-21-09(L)	See A.I.2 below.

2. Additional Terms and Conditions

- 2.a The fixed roof storage tank shall be equipped with an internal floating roof.
- 2.b The automatic bleeder vents shall be closed at all times except when the roof is floated off or landed on the roof leg supports, and the rim vents, if provided, shall be set to open when the roof is being floated off the roof leg supports or is at the manufacturer's recommended setting
- 2.c All openings, except stub drains, shall be equipped with a cover, seal or lid which is to be in a closed position at all times except when in actual use for tank gauging or sampling.

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain records of the following information:
 - a. the types of petroleum liquids stored in the tank; and
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.
2. All records required under section A.III of this permit shall be maintained in accordance with the monitoring and related recordkeeping and reporting requirements of Part I - General Terms and Conditions.

IV. Reporting Requirements

None

V. Testing Requirements

None

Facility Name: **Citgo Petroleum Corporation - Toledo Terminal**
Facility ID: **04-48-01-0220**
Emissions Unit: **Tank 245 (T030)**

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Tank 284 (T031)
Activity Description: Fixed Roof Tank

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
fixed roof tank (99,997 barrels)	OAC rule 3745-21-09(L)	exempt (See A.I.2.a below.)

2. Additional Terms and Conditions

- 2.a The permittee shall not place, store, or hold in this fixed roof tank any petroleum liquid which, as stored, has a true vapor pressure greater than 1.52 pounds per square inch absolute, unless such tank is designed or equipped in accordance with the requirements of paragraph (L)(1) of OAC rule 3745-21-09.

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain records of the following information:
 - a. the types of petroleum liquids stored in the tank; and
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.
2. All records required under section A.III of this permit shall be maintained in accordance with the monitoring and related recordkeeping and reporting requirements of Part I - General Terms and Conditions.

IV. Reporting Requirements

1. If the permittee places, stores, or holds in the fixed roof tank any petroleum liquid with a true vapor pressure which is greater than 1.52 pounds per square inch absolute, and such tank does not comply with the requirements of paragraph (L)(1) of OAC rule 3745-21-09, the permittee shall notify the Director (the Toledo Division of Environmental Services) within 30 days of becoming aware of the occurrence.

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Tank 209 (T035)
Activity Description: Internal Floating Roof Tank

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
internal floating roof storage tank (53,286 barrels)	OAC rule 3745-21-09(L)	See A.I.2 below.

2. Additional Terms and Conditions

- 2.a The fixed roof storage tank shall be equipped with an internal floating roof.
- 2.b The automatic bleeder vents shall be closed at all times except when the roof is floated off or landed on the roof leg supports, and the rim vents, if provided, shall be set to open when the roof is being floated off the roof leg supports or is at the manufacturer's recommended setting
- 2.c All openings, except stub drains, shall be equipped with a cover, seal or lid which is to be in a closed position at all times except when in actual use for tank gauging or sampling.

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain records of the following information:
 - a. the types of petroleum liquids stored in the tank; and
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.
2. All records required under section A.III of this permit shall be maintained in accordance with the monitoring and related recordkeeping and reporting requirements of Part I - General Terms and Conditions.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

THIS IS THE LAST PAGE OF THE PERMIT
