



Environmental
Protection Agency

Ted Strickland, Governor
Lee Fisher, Lt. Governor
Chris Korleski, Director

8/2/2010

Certified Mail

Paul Logsdon
Lima Refining Company
1150 South Metcalf Street
Lima, OH 45804

No	TOXIC REVIEW
No	PSD
No	SYNTHETIC MINOR TO AVOID MAJOR NSR
No	CEMS
No	MACT
No	NSPS
No	NESHAPS
No	NETTING
No	MAJOR NON-ATTAINMENT
No	MODELING SUBMITTED

RE: FINAL AIR POLLUTION PERMIT-TO-INSTALL
Facility ID: 0302020012
Permit Number: P0106610
Permit Type: Administrative Modification
County: Allen

Dear Permit Holder:

Enclosed please find a final Air Pollution Permit-to-Install (PTI) which will allow you to install or modify the described emissions unit(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, we urge you to read it carefully. Please complete a survey at www.epa.ohio.gov/dapc/permitsurvey.aspx and give us feedback on your permitting experience. We value your opinion.

The issuance of this PTI is a final action of the Director and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. The appeal must be filed with the Commission within thirty (30) days after notice of the Director's action. The appeal must be accompanied by a filing fee of \$70.00, made payable to "Ohio Treasurer Kevin Boyce," which the Commission, in its discretion, may reduce if by affidavit you demonstrate that payment of the full amount of the fee would cause extreme hardship. Notice of the filing of the appeal shall be filed with the Director within three (3) days of filing with the Commission. Ohio EPA requests that a copy of the appeal be served upon the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, OH 43215

The Ohio EPA is encouraging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Compliance Assistance and Pollution Prevention at (614) 644-3469. If you have any questions regarding this permit, please contact the Ohio EPA DAPC, Northwest District Office. This permit can be accessed electronically on the Division of Air Pollution Control (DAPC) Web page, www.epa.ohio.gov/dapc by clicking the "Issued Air Pollution Control Permits" link.

Sincerely,


Michael W. Ahern, Manager
Permit Issuance and Data Management Section, DAPC

Cc: U.S. EPA
Ohio EPA-NWDO; Indiana



FINAL

Division of Air Pollution Control
Permit-to-Install
for
Lima Refining Company

Facility ID: 0302020012
Permit Number: P0106610
Permit Type: Administrative Modification
Issued: 8/2/2010
Effective: 8/2/2010



Division of Air Pollution Control
Permit-to-Install
for
Lima Refining Company

Table of Contents

Authorization 1
A. Standard Terms and Conditions 3
1. Federally Enforceable Standard Terms and Conditions 4
2. Severability Clause 4
3. General Requirements 4
4. Monitoring and Related Record Keeping and Reporting Requirements 5
5. Scheduled Maintenance/Malfunction Reporting 6
6. Compliance Requirements 6
7. Best Available Technology 7
8. Air Pollution Nuisance 7
9. Reporting Requirements 7
10. Applicability 8
11. Construction of New Sources(s) and Authorization to Install 8
12. Permit-To-Operate Application 9
13. Construction Compliance Certification 9
14. Public Disclosure 10
15. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations 10
16. Fees 10
17. Permit Transfers 10
18. Risk Management Plans 10
19. Title IV Provisions 10
B. Facility-Wide Terms and Conditions 11
C. Emissions Unit Terms and Conditions 13
1. B004, Process Heater 14
2. Emissions Unit Group - Process Heaters Group #1: B001, B003, B006, B007, B008, 21
3. Emissions Unit Group - Process Heaters Group #2: B002, B005, 27

Authorization

Facility ID: 0302020012

Facility Description: Petroleum Refinery and Storage

Application Number(s): M0000859

Permit Number: P0106610

Permit Description: Administrative modification to PTI #P0106188 to revise the RATA language for the H2S CEMS to the frequency defined in the Consent Decree Paragraph 121 (once every 3 years), and to remove the requirement for monthly fuel gas monitoring.

Permit Type: Administrative Modification

Permit Fee: \$0.00

Issue Date: 8/2/2010

Effective Date: 8/2/2010

This document constitutes issuance to:

Lima Refining Company
1150 South Metcalf Street
Lima, OH 45804

of a Permit-to-Install for the emissions unit(s) identified on the following page.


Ohio EPA District Office or local air agency responsible for processing and administering your permit:

Ohio EPA DAPC, Northwest District Office
347 North Dunbridge Road
Bowling Green, OH 43402
(419)352-8461

The above named entity is hereby granted a Permit-to-Install for the emissions unit(s) listed in this section pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency



Chris Korleski
Director



Authorization (continued)

Permit Number: P0106610
Permit Description: Administrative modification to PTI #P0106188 to revise the RATA language for the H2S CEMS to the frequency defined in the Consent Decree Paragraph 121 (once every 3 years), and to remove the requirement for monthly fuel gas monitoring.

Permits for the following Emissions Unit(s) or groups of Emissions Units are in this document as indicated below:

Emissions Unit ID: B004
Company Equipment ID: Process Heater
Superseded Permit Number: P0106188
General Permit Category and Type: Not Applicable

Group Name: Process Heaters Group #1

Emissions Unit ID:	B001
Company Equipment ID:	Process Heater
Superseded Permit Number:	P0106188
General Permit Category and Type:	Not Applicable
Emissions Unit ID:	B003
Company Equipment ID:	Process Heaters
Superseded Permit Number:	P0106188
General Permit Category and Type:	Not Applicable
Emissions Unit ID:	B006
Company Equipment ID:	Process Heaters
Superseded Permit Number:	P0106188
General Permit Category and Type:	Not Applicable
Emissions Unit ID:	B007
Company Equipment ID:	Process Heater
Superseded Permit Number:	P0106188
General Permit Category and Type:	Not Applicable
Emissions Unit ID:	B008
Company Equipment ID:	Process Heater
Superseded Permit Number:	P0106188
General Permit Category and Type:	Not Applicable

Group Name: Process Heaters Group #2

Emissions Unit ID:	B002
Company Equipment ID:	Process Heaters
Superseded Permit Number:	P0106188
General Permit Category and Type:	Not Applicable
Emissions Unit ID:	B005
Company Equipment ID:	Process Heater
Superseded Permit Number:	P0106188
General Permit Category and Type:	Not Applicable

A. Standard Terms and Conditions

1. Federally Enforceable Standard Terms and Conditions

- a) All Standard Terms and Conditions are federally enforceable, with the exception of those listed below which are enforceable under State law only:
- (1) Standard Term and Condition A.2.a), Severability Clause
 - (2) Standard Term and Condition A.3.c) through A. 3.e) General Requirements
 - (3) Standard Term and Condition A.6.c) and A. 6.d), Compliance Requirements
 - (4) Standard Term and Condition A.9., Reporting Requirements
 - (5) Standard Term and Condition A.10., Applicability
 - (6) Standard Term and Condition A.11.b) through A.11.e), Construction of New Source(s) and Authorization to Install
 - (7) Standard Term and Condition A.14., Public Disclosure
 - (8) Standard Term and Condition A.15., Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations
 - (9) Standard Term and Condition A.16., Fees
 - (10) Standard Term and Condition A.17., Permit Transfers

2. Severability Clause

- a) A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition declared invalid.
- b) All terms and conditions designated in parts B and C of this permit are federally enforceable as a practical matter, if they are required under the Act, or any of its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA and the State and by citizens (to the extent allowed by section 304 of the Act) under the Act. Terms and conditions in parts B and C of this permit shall not be federally enforceable and shall be enforceable under State law only, only if specifically identified in this permit as such.

3. General Requirements

- a) The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and re-issuance, or modification.

- b) It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.
- c) This permit may be modified, revoked, or revoked and reissued, for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.
- d) This permit does not convey any property rights of any sort, or any exclusive privilege.
- e) The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

4. Monitoring and Related Record Keeping and Reporting Requirements

- a) Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:
 - (1) The date, place (as defined in the permit), and time of sampling or measurements.
 - (2) The date(s) analyses were performed.
 - (3) The company or entity that performed the analyses.
 - (4) The analytical techniques or methods used.
 - (5) The results of such analyses.
 - (6) The operating conditions existing at the time of sampling or measurement.
- b) Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.
- c) Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall submit required reports in the following manner:
 - (1) Reports of any required monitoring and/or recordkeeping of federally enforceable information shall be submitted to the Ohio EPA DAPC, Northwest District Office.

- (2) Quarterly written reports of (i) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, excluding deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06, that have been detected by the testing, monitoring and recordkeeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures taken, shall be made to the Ohio EPA DAPC, Northwest District Office. The written reports shall be submitted (i.e., postmarked) quarterly, by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. See A.15. below if no deviations occurred during the quarter.
 - (3) Written reports, which identify any deviations from the federally enforceable monitoring, recordkeeping, and reporting requirements contained in this permit shall be submitted (i.e., postmarked) to the Ohio EPA DAPC, Northwest District Office every six months, by January 31 and July 31 of each year for the previous six calendar months. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report, which states that no deviations occurred during that period.
 - (4) This permit is for an emissions unit located at a Title V facility. Each written report shall be signed by a responsible official certifying that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.
- d) The permittee shall report actual emissions pursuant to OAC Chapter 3745-78 for the purpose of collecting Air Pollution Control Fees.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction, i.e., upset, of any emissions units or any associated air pollution control system(s) shall be reported to the Ohio EPA DAPC, Northwest District Office in accordance with paragraph (B) of OAC rule 3745-15-06. (The definition of an upset condition shall be the same as that used in OAC rule 3745-15-06(B)(1) for a malfunction.) The verbal and written reports shall be submitted pursuant to OAC rule 3745-15-06.

Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emission unit(s) that is (are) served by such control system(s).

6. Compliance Requirements

- a) The emissions unit(s) identified in this Permit shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.
- b) Any document (including reports) required to be submitted and required by a federally applicable requirement in this permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.
- c) Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:

- (1) At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.
 - (2) Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with ORC section 3704.08.
 - (3) Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.
 - (4) As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.
- d) The permittee shall submit progress reports to the Ohio EPA DAPC, Northwest District Office concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:
- (1) Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
 - (2) An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

7. Best Available Technology

As specified in OAC Rule 3745-31-05, new sources that must employ Best Available Technology (BAT) shall comply with the Applicable Emission Limitations/Control Measures identified as BAT for each subject emissions unit.

8. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

9. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a) Reports of any required monitoring and/or recordkeeping of state-only enforceable information shall be submitted to the Ohio EPA DAPC, Northwest District Office.

- b) Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from state-only required emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the Ohio EPA DAPC, Northwest District Office. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted (i.e., postmarked) quarterly, by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

10. Applicability

This Permit-to-Install is applicable only to the emissions unit(s) identified in the Permit-to-Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

11. Construction of New Sources(s) and Authorization to Install

- a) This permit does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. This permit does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the application and terms and conditions of this permit. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of this permit does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Issuance of this permit is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.
- b) If applicable, authorization to install any new emissions unit included in this permit shall terminate within eighteen months of the effective date of the permit if the owner or operator has not undertaken a continuing program of installation or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

- c) The permittee may notify Ohio EPA of any emissions unit that is permanently shut down (i.e., the emissions unit has been physically removed from service or has been altered in such a way that it can no longer operate without a subsequent "modification" or "installation" as defined in OAC Chapter 3745-31) by submitting a certification from the authorized official that identifies the date on which the emissions unit was permanently shut down. Authorization to operate the affected emissions unit shall cease upon the date certified by the authorized official that the emissions unit was permanently shut down. At a minimum, notification of permanent shut down shall be made or confirmed by marking the affected emissions unit(s) as "permanently shut down" in Ohio EPA's "Air Services" along with the date the emissions unit(s) was permanently removed and/or disabled. Submitting the facility profile update will constitute notifying of the permanent shutdown of the affected emissions unit(s).
- d) The provisions of this permit shall cease to be enforceable for each affected emissions unit after the date on which an emissions unit is permanently shut down (i.e., emissions unit has been physically removed from service or has been altered in such a way that it can no longer operate without a subsequent "modification" or "installation" as defined in OAC Chapter 3745-31). All records relating to any permanently shutdown emissions unit, generated while the emissions unit was in operation, must be maintained in accordance with law. All reports required by this permit must be submitted for any period an affected emissions unit operated prior to permanent shut down. At a minimum, the permit requirements must be evaluated as part of the reporting requirements identified in this permit covering the last period the emissions unit operated.

No emissions unit certified by the authorized official as being permanently shut down may resume operation without first applying for and obtaining a permit pursuant to OAC Chapter 3745-31.

- e) The permittee shall comply with any residual requirements related to this permit, such as the requirement to submit a deviation report, air fee emission report, or other any reporting required by this permit for the period the operating provisions of this permit were enforceable, or as required by regulation or law. All reports shall be submitted in a form and manner prescribed by the Director. All records relating to this permit must be maintained in accordance with law.

12. Permit-To-Operate Application

The permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77. The permittee shall submit a complete Title V permit application or a complete Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).

13. Construction Compliance Certification

The applicant shall identify the following dates in the online facility profile for each new emissions unit identified in this permit.

- a) Completion of initial installation date shall be entered upon completion of construction and prior to start-up.

- b) Commence operation after installation or latest modification date shall be entered within 90 days after commencing operation of the applicable emissions unit.

14. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

15. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations

If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly (i.e., postmarked), by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.

16. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable permit-to-install fees within 30 days after the issuance of any permit-to-install. The permittee shall pay all applicable permit-to-operate fees within thirty days of the issuance of the invoice.

17. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The new owner must update and submit the ownership information via the "Owner/Contact Change" functionality in Air Services once the transfer is legally completed. The change must be submitted through Air Services within thirty days of the ownership transfer date.

18. Risk Management Plans

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. 7401 et seq. ("Act"), the permittee shall comply with the requirement to register such a plan.

19. Title IV Provisions

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

B. Facility-Wide Terms and Conditions

1. All the following facility-wide terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only:
 - a) None.

C. Emissions Unit Terms and Conditions

1. B004, Process Heater

Operations, Property and/or Equipment Description:

Refinery Fuel Gas or Natural Gas Fired Crude II Heater, with low NOx burners, 630 million Btu per hour.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-17-10(B)(1)	0.020 lb of particulate emissions (PE) per million Btu of actual heat input
b.	OAC rule 3745-17-07(A)	Visible particulate emissions from any stack shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.
	OAC rule 3745-18-08(C)(2)	1.0 lb of sulfur dioxide (SO ₂) per million Btu of actual heat input
	OAC rule 3745-21-08(B)	See b)(2)c.
	OAC rule 3745-31-05(A)(3)	0.10 lb of NO _x per million Btu of actual heat input, 275.94 tons of NO _x /yr 25.20 lbs of carbon monoxide (CO)/hr, 110.38 tons of CO/yr See b)(2)b.
	OAC rule 3745-31-05(D)	See b)(2)a.
	40 CFR 63.52(a)(2)	See b)(2)d.
	40 CFR, Part 60, Subpart J	See b)(2)e. and b)(2)f.
	40 CFR, Part 60, Subpart A	See 40 CFR 60.1 through 60.19

(2) Additional Terms and Conditions

a. The permittee has requested a federally enforceable limitation for NO_x of 0.10 lb per million Btu of actual heat input, 275.94 tons NO_x/yr, 25.20 lbs CO/hr, and 110.38 tons CO/yr. The federally enforceable limitations shall be established in accordance with OAC rule 3745-31-05(A)(3). The permittee has requested federally enforceable NO_x and CO emission limitations for purposes of avoiding

Prevention of Significant Deterioration (PSD) permitting by emissions netting, as established in PTI No. 03-13794.

- b. Best Available Technology (BAT) control requirements for this emissions unit have been determined to be use of low NOx burners meeting 0.10 lb NOx per million Btu of actual heat input.
- c. The permittee has satisfied the "best available control techniques and operating practices" required pursuant to OAC rule 3745-21-08(B) by committing to comply with the best available technology control requirements established pursuant to OAC rule 3745-31-05(A)(3) in PTI 03-13794.

On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the requirement to satisfy the "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

- d. This emissions unit is subject to a case-by-case MACT determination pursuant to section 112(j) of the Clean Air Act (CAA) due to the June 8, 2007 D.C. Circuit Court of Appeals decision to vacate the Boiler MACT (40 CFR Part 63, Subpart DDDDD).

If notified by the Ohio EPA or U.S. EPA, the permittee shall submit an application for a revision to this Title V permit that meets the requirements of 40 CFR 63.52(a)(2) pertaining to case-by-case MACT determinations. The 30-day clock for submittal of a 112(j) application does not begin until such notification is made by Ohio EPA or U.S. EPA.

- e. This modification involved adding 40 CFR Part 60 - Subpart J as an applicable rule for this emissions unit. The permittee is required to comply with this new source performance standard for fuel combustion by 12/31/09, per paragraph No. 118 and Appendix O of the federal consent decree addendum, civil action No. SA07CA0683RF which became effective on 11/20/07.
- f. The permittee shall not burn any refinery fuel gas in this emissions unit that contains hydrogen sulfide (H₂S) in excess of 230 mg/dscm (0.10 grain/dscf)(the equivalent concentration is 162 parts per million by volume). This H₂S standard in 40 CFR 60.104(a)(1) is also applicable if the permittee combines and combusts natural gas in any proportion with refinery fuel gas in this emissions unit, according to the fuel gas definition in 40 CFR 60.101(d).

c) Operational Restrictions

- (1) The permittee shall burn only refinery fuel gas or natural gas in this emissions unit. The sulfur content of the refinery fuel gas or natural gas burned in this emissions unit shall comply with the allowable SO₂ emission limitation specified in section b)(1)c.

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall record on a monthly basis, the calculated SO₂ emission rate in lb/mmBtu. The SO₂ emission rate shall be calculated as follows:

$$\text{Lbs SO}_2/\text{mmBtu} = \text{lbs H}_2\text{S}/\text{mmBtu} * (64 \text{ lb SO}_2/\text{lbmol}) / (34 \text{ lb H}_2\text{S}/\text{lbmol})$$

Where:

$$\text{Lbs H}_2\text{S}/\text{mmBtu} = \text{ppm H}_2\text{S} * [(0.1 \text{ grain per scf}/162 \text{ ppm}) * (1 \text{ lb}/7000 \text{ grain}) * (1/\text{RFG Btu per scf})] * (10^6 \text{ Btu}/\text{mmBtu})$$

Note: The 0.1 grain per scf = 162 ppm is based directly on the H₂S limits in NSPS Subpart J 40 CFR Part 60.104(a)(1).

- (2) For each day during which the permittee burns a fuel other than refinery fuel gas or natural gas, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.
- (3) In order to demonstrate compliance with the emission limitation of 230 mg/dscm (0.10 grain/dscf)(the equivalent concentration is 162 parts per million by volume) of H₂S in the refinery fuel gas (and if applicable, combined fuel firing as noted in b)(2)f. above), the permittee shall operate and maintain an instrument for continuously monitoring and recording the concentration (dry basis) of H₂S in the refinery fuel gas or combined fuel stream before being burned in this emissions unit. The monitoring shall be conducted in accordance with 40 CFR 60.105(a)(4), as follows
- a. The span value for this instrument is 425 mg/dscm of H₂S.
 - b. Fuel gas combustion devices having a common source of fuel gas may be monitored at only one location, if monitoring at this location accurately represents the concentration of H₂S in the fuel gas being burned.
 - c. The performance evaluations for this H₂S monitor under 40 CFR 60.13(c) shall use Performance Specification 7 of 40 CFR 60, Appendix B. The permittee shall conduct an annual relative accuracy test audit (RATA) for the H₂S continuous emission monitoring equipment. Method 11 of 40 CFR, Part 60, Appendix A, or other approved U.S. EPA methods shall be used for conducting the annual RATAs.
- (4) A statement of certification of the existing H₂S continuous emission monitoring system (CEMS) shall be maintained on site and shall consist of a letter from the Ohio EPA detailing the results of an Agency review of the certification tests and a statement by the Agency that the system is considered certified in accordance with the requirements of 40 CFR, Part 60, Appendix B, Performance Specification 7. Proof of certification shall be made available to representatives of the Ohio EPA, Northwest District Office upon request.
- (5) The permittee shall operate and maintain existing equipment to continuously monitor and record hydrogen sulfide from this emissions unit in units of the applicable standard.

Such continuous monitoring and recording equipment shall comply with the requirements specified in 40 CFR, Part 60.13.

The permittee shall maintain records of all data obtained by the H₂S CEMS including, but not limited to, parts per million of H₂S on an instantaneous (1-minute) basis, emissions of H₂S in units of the applicable standard (grain/dscf and parts per million by volume) as a rolling, 3-hour average, the results of daily zero/span calibration checks, and the magnitudes of manual calibration adjustments.

- (6) The permittee shall maintain a written quality assurance/quality control plan for the CEMS designed to ensure continuous valid and representative readings of H₂S. The plan shall follow the requirements of 40 CFR, Part 60, Appendix F.

A logbook dedicated to the monitoring systems must be kept on site and available for inspection during regular office hours.

The plan shall include the requirement to conduct quarterly cylinder gas audits or relative accuracy audits as required in 40 CFR, Part 60; and to conduct relative accuracy test audits in units of the standard(s), in accordance with and at the frequencies required per 40 CFR Part 60, except as noted below.

Pursuant to paragraph No. 121 of the federal consent decree addendum, civil action No. SA07CA0683RF, dated 11/20/07, the permittee is required to:

- a. Conduct a relative accuracy test audit of the NO_x CEM at a minimum frequency of once every three years; and
- b. Conduct cylinder gas audits on the NO_x CEM during each quarter when a relative accuracy test audit is not conducted.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify each month during which the SO₂ emission limitation of 1.0 lb of SO₂ per million Btu of actual heat input was exceeded, based upon the calculations specified in section d)(1).
- (2) The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than refinery fuel gas or natural gas was burned in this emissions unit. Each report shall be submitted within 30 days after the deviation occurs.
- (3) The permittee shall submit reports within thirty (30) days following the end of each calendar quarter to the Ohio EPA, Northwest District Office documenting any H₂S CEMS downtime while the emissions unit was on line (date, time, duration, and reason), along with any corrective action(s) taken. The permittee shall provide the emissions unit operating time during the reporting period and the date, time, reason, and corrective action(s) taken for each time period of source and control equipment malfunctions.

The total operating time of the emissions unit and the total operating time of the analyzer while the emissions unit was on line shall be included the quarterly report.

- (4) The permittee shall notify the Director (the Ohio EPA, Northwest District Office) on a quarterly basis, in writing, of all rolling, 3-hour periods during which the average

concentration of H₂S as measured by the H₂S CEMS under 40 CFR 60.105(a)(4) exceeds 230 mg/dscm (0.10 grain/dscf)(the equivalent concentration is 162 parts per million by volume). The rolling, 3-hour average shall be determined as the arithmetic average of three contiguous 1-hour averages. The notification shall include a copy of the record and shall be sent to the Director (the Ohio EPA, Northwest District Office) by January 30, April 30, July 30, and October 30 of each year and shall address the data obtained during previous calendar quarters.

- (5) If there are no concentrations of H₂S in the refinery fuel gas (or combined fuel stream, if applicable) greater than 230 mg/dscm (0.10 grain/dscf)(the equivalent concentration is 162 parts per million by volume) during the calendar quarter, then the permittee shall submit a statement to that effect along with the emissions unit and monitor operating times. These quarterly reports shall be submitted by January 30, April 30, July 30, and October 30 of each year and shall address the data obtained during previous calendar quarters.

f) Testing Requirements

- (1) Compliance with the emissions limitations in section b)(1) of the terms and conditions of this permit shall be determined in accordance with the following methods:

a. Emission Limitation:

0.020 lb of PE per million Btu of actual heat input

Applicable Compliance Method:

The permittee may demonstrate compliance with this limitation by dividing the appropriate particulate emission factor of 1.9 lbs per million standard cubic feet, from AP-42 Chapter 1.4 (7/98), by the heat content of 853 Btu per standard cubic foot for the refinery fuel gas fired in this emissions unit.

If natural gas is solely being fired, the permittee shall demonstrate compliance with this limitation by multiplying the maximum hourly natural gas combustion rate, in million standard cubic feet per hour, by the appropriate particulate emission factor, in lb(s) per million standard cubic feet, from AP-42 Chapter 1.4 (7/98), and then dividing by the maximum heat input to the process heater.

If required, the permittee shall demonstrate compliance with this emission limitation by conducting emission testing in accordance with the requirements specified in OAC rule 3745-17-03(B)(9).

b. Emission Limitation:

Visible particulate emissions from any stack shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.

Applicable Compliance Method:

If required, the permittee shall demonstrate compliance with the visible particulate emission limitation above in accordance with the methods and

procedures specified in 40 CFR Part 60, Appendix A, Method 9 and the requirements specified in OAC rule 3745-17-03(B)(1).

c. Emission Limitation:

1.0 lb of SO₂ per million Btu of actual heat input

Applicable Compliance Method:

The monitoring, record keeping and reporting requirements in sections d)(1) and e)(1) of this permit, shall be used to demonstrate compliance with the above limitation. If required, the permittee also shall demonstrate compliance with this emission limitation by conducting emission testing in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 4, and 6 and the requirements specified in OAC rule 3745-18-04(E)(1).

d. Emission Limitation:

0.10 lb of NO_x per million Btu of actual heat input, 275.94 tons of NO_x/yr

Applicable Compliance Method:

Compliance with the lb of NO_x per million Btu emission limitation has been demonstrated by past performance testing. Per Engineering Guide No. 16, periodic testing is no longer required. If required, the permittee shall demonstrate compliance with this emission limitation by conducting emission testing in accordance with the requirements specified in 40 CFR, Part 60, Appendix A, Methods 1 through 4, and 7.

The annual emission limitation was derived by multiplying the 0.10 lb of NO_x per million Btu emission limitation times the maximum heat input capacity of 630 million Btu/hr for the crude II heater, then multiplying by 8,760 hrs/yr and dividing by 2,000 lbs/ton. Compliance with the annual limitation shall be shown as long as compliance with the lb/million Btu emission limitation is maintained.

e. Emission Limitation:

25.20 lbs of CO/hr, 110.38 tons of CO/yr

Applicable Compliance Method

Compliance with the hourly mass emission limitation has been demonstrated by past performance testing. Per Engineering Guide No. 16, periodic testing is no longer required. If required, the permittee shall demonstrate compliance with this emission limitation by conducting emission testing in accordance with the requirements specified in 40 CFR, Part 60, Appendix A, Methods 1 through 4, and 10.

The annual emission limitation was derived by multiplying the hourly emission limitation times 8,760 hrs/yr and dividing by 2,000 lbs/ton. Compliance with the annual limitation shall be shown as long as compliance with the hourly emission limitation is maintained.

f. Emission Limitation:

230 mg/dscm (0.10 grain/dscf)(the equivalent concentration is 162 parts per million by volume) of H₂S in the refinery fuel gas, or combined fuel stream if applicable

Applicable Compliance Method:

Compliance shall be based upon the monitoring and record keeping requirements specified in sections d)(4) through d)(7) for this emissions unit. If required, the permittee shall determine compliance with the H₂S emission limitation by using Method 11 of 40 CFR, Part 60, Appendix A, or other approved U.S. EPA methods.

g) Miscellaneous Requirements

(1) None.

2. Emissions Unit Group - Process Heaters Group #1: B001, B003, B006, B007, B008,

EU ID	Operations, Property and/or Equipment Description
B001	Refinery Fuel Gas or Natural Gas Fired Vacuum Unit II Heater, 162 million Btu/hour maximum heat input (PR 175151).
B003	Refinery Fuel Gas or Natural Gas Fired ISO I & II Heaters, 109 million Btu/hr maximum combined heat input (PR 175152/PR 175159)
B006	Refinery Fuel Gas or Natural Gas Fired U/F PRE, 1, 2, &3 Heater; 1,954 million Btu/hr maximum combined heat input (PR 175156 through PR 175159)
B007	Refinery Fuel Gas or Natural Gas Fired Reformer Regenerator Heater, 110 million Btu/hr maximum heat input (PR 175162)
B008	Refinery Fuel Gas or Natural Gas Fired HDS Heater, 278 million Btu/hr maximum heat input (PR 175169)

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only:

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-17-10(B)(1)	0.020 lb of particulate emissions (PE) per million Btu of actual heat input
b.	OAC rule 3745-18-08(C)(1)	0.15 lb of sulfur dioxide (SO2) per million Btu of actual heat input
	OAC rule 3745-17-07(A)	Visible particulate emissions from any stack shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.
	40 CFR 63.52(a)(2)	See b)(2)a.
	40 CFR, Part 60, Subpart J	See b)(2)b. and b)(2)c.
	40 CFR, Part 60, Subpart A	See 40 CFR 60.1 through 60.19

(2) Additional Terms and Conditions

a. This emissions unit is subject to a case-by-case MACT determination pursuant to section 112(j) of the Clean Air Act (CAA) due to the June 8, 2007 D.C. Circuit Court of Appeals decision to vacate the Boiler MACT (40 CFR Part 63, Subpart DDDDD).

If notified by the Ohio EPA or U.S. EPA, the permittee shall submit an application for a revision to this Title V permit that meets the requirements of 40 CFR 63.52(a)(2) pertaining to case-by-case MACT determinations. The 30-day clock for submittal of a 112(j) application does not begin until such notification is made by Ohio EPA or U.S. EPA.

- b. 40 CFR Part 60 - Subpart J is being added as an applicable rule for this emissions unit. The permittee is required to comply with this new source performance standard for fuel combustion by 12/31/09, per paragraph No. 118 and Appendix O of the federal consent decree addendum, civil action No. SA07CA0683RF which became effective on 11/20/07.
- c. The permittee shall not burn any refinery fuel gas in this emissions unit that contains hydrogen sulfide (H₂S) in excess of 230 mg/dscm (0.10 grain/dscf)(the equivalent concentration is 162 parts per million by volume). This H₂S standard in 40 CFR 60.104(a)(1) is also applicable if the permittee combines and combusts natural gas in any proportion with refinery fuel gas in this emissions unit, according to the fuel gas definition in 40 CFR 60.101(d).

c) Operational Restrictions

- (1) The permittee shall burn only refinery fuel gas or natural gas in this emissions unit. The sulfur content of the refinery fuel gas or natural gas burned in this emissions unit shall comply with the allowable SO₂ emission limitation specified in section b)(1)b.

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall record on a monthly basis, the calculated SO₂ emission rate in lb/mmBtu. The SO₂ emission rate shall be calculated as follows:

$$\text{Lbs SO}_2/\text{mmBtu} = \text{lbs H}_2\text{S}/\text{mmBtu} * (64 \text{ lb SO}_2/\text{lbmol})/(34 \text{ lb H}_2\text{S}/\text{lbmol})$$

Where:

$$\text{Lbs H}_2\text{S}/\text{mmBtu} = \text{ppm H}_2\text{S} * [(0.1 \text{ grain per scf}/162 \text{ ppm}) * (1 \text{ lb}/7000 \text{ grain}) * (1/\text{RFG Btu per scf})] * (10^6 \text{ Btu}/\text{mmBtu})$$

Note: The 0.1 grain per scf = 162 ppm is based directly on the H₂S limits in NSPS Subpart J 40 CFR Part 60.104(a)(1).

- (2) For each day during which the permittee burns a fuel other than refinery fuel gas or natural gas, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.
- (3) In order to demonstrate compliance with the emission limitation of 230 mg/dscm (0.10 grain/dscf)(the equivalent concentration is 162 parts per million by volume) of H₂S in the refinery fuel gas (and if applicable, combined fuel firing as noted in b)(2)c. above), the permittee shall operate and maintain an instrument for continuously monitoring and recording the concentration (dry basis) of H₂S in the refinery fuel gas or combined fuel stream before being burned in this emissions unit. The monitoring shall be conducted in accordance with 40 CFR 60.105(a)(4), as follows

- a. The span value for this instrument is 425 mg/dscm of H₂S.
 - b. Fuel gas combustion devices having a common source of fuel gas may be monitored at only one location, if monitoring at this location accurately represents the concentration of H₂S in the fuel gas being burned.
 - c. The performance evaluations for this H₂S monitor under 40 CFR 60.13(c) shall use Performance Specification 7 of 40 CFR 60, Appendix B. The permittee shall conduct an annual relative accuracy test audit (RATA) for the H₂S continuous emission monitoring equipment. Method 11 of 40 CFR, Part 60, Appendix A, or other approved U.S. EPA methods shall be used for conducting the annual RATAs.
- (4) A statement of certification of the existing H₂S continuous emission monitoring system (CEMS) shall be maintained on site and shall consist of a letter from the Ohio EPA detailing the results of an Agency review of the certification tests and a statement by the Agency that the system is considered certified in accordance with the requirements of 40 CFR, Part 60, Appendix B, Performance Specification 7. Proof of certification shall be made available to representatives of the Ohio EPA, Northwest District Office upon request.
- (5) The permittee shall operate and maintain existing equipment to continuously monitor and record hydrogen sulfide from this emissions unit in units of the applicable standard. Such continuous monitoring and recording equipment shall comply with the requirements specified in 40 CFR, Part 60.13.

The permittee shall maintain records of all data obtained by the H₂S CEMS including, but not limited to, parts per million of H₂S on an instantaneous (1-minute) basis, emissions of H₂S in units of the applicable standard (grain/dscf and parts per million by volume) as a rolling, 3-hour average, the results of daily zero/span calibration checks, and the magnitudes of manual calibration adjustments.

- (6) The permittee shall maintain a written quality assurance/quality control plan for the CEMS designed to ensure continuous valid and representative readings of H₂S. The plan shall follow the requirements of 40 CFR, Part 60, Appendix F.

A logbook dedicated to the monitoring systems must be kept on site and available for inspection during regular office hours.

The plan shall include the requirement to conduct quarterly cylinder gas audits or relative accuracy audits as required in 40 CFR, Part 60; and to conduct relative accuracy test audits in units of the standard(s), in accordance with and at the frequencies required per 40 CFR Part 60, except as noted below.

Pursuant to paragraph No. 121 of the federal consent decree addendum, civil action No. SA07CA0683RF, dated 11/20/07, the permittee is required to:

- a. Conduct a relative accuracy test audit of the NO_x CEM at a minimum frequency of once every three years; and

- b. Conduct cylinder gas audits on the NO_x CEM during each quarter when a relative accuracy test audit is not conducted.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify each month during which the SO₂ emission limitation of 1.0 lb of SO₂ per million Btu of actual heat input was exceeded, based upon the calculations specified in section d)(1).
- (2) The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than refinery fuel gas or natural gas was burned in this emissions unit. Each report shall be submitted within 30 days after the deviation occurs.
- (3) The permittee shall submit reports within thirty (30) days following the end of each calendar quarter to the Ohio EPA, Northwest District Office documenting any H₂S CEMS downtime while the emissions unit was on line (date, time, duration, and reason), along with any corrective action(s) taken. The permittee shall provide the emissions unit operating time during the reporting period and the date, time, reason, and corrective action(s) taken for each time period of source and control equipment malfunctions.

The total operating time of the emissions unit and the total operating time of the analyzer while the emissions unit was on line shall be included the quarterly report.

- (4) The permittee shall notify the Director (the Ohio EPA, Northwest District Office) on a quarterly basis, in writing, of all rolling, 3-hour periods during which the average concentration of H₂S as measured by the H₂S CEMS under 40 CFR 60.105(a)(4) exceeds 230 mg/dscm (0.10 grain/dscf)(the equivalent concentration is 162 parts per million by volume). The rolling, 3-hour average shall be determined as the arithmetic average of three contiguous 1-hour averages. The notification shall include a copy of the record and shall be sent to the Director (the Ohio EPA, Northwest District Office) by January 30, April 30, July 30, and October 30 of each year and shall address the data obtained during previous calendar quarters.
- (5) If there are no concentrations of H₂S in the refinery fuel gas (or combined fuel stream, if applicable) greater than 230 mg/dscm (0.10 grain/dscf)(the equivalent concentration is 162 parts per million by volume) during the calendar quarter, then the permittee shall submit a statement to that effect along with the emissions unit and monitor operating times. These quarterly reports shall be submitted by January 30, April 30, July 30, and October 30 of each year and shall address the data obtained during previous calendar quarters.

f) Testing Requirements

- (1) Compliance with the emission limitations in section b)(1) of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emission Limitation:
0.020 lb of PE per million Btu of actual heat input

Applicable Compliance Method:

The permittee shall demonstrate compliance with this limitation by multiplying the maximum hourly refinery fuel gas or natural gas combustion rate, in million standard cubic feet per hour, by the appropriate particulate emission factor, in lb(s) per million standard cubic feet, from AP-42 Chapter 1.4 (7/98), and then dividing by the maximum heat input to the process heater. If required, the permittee shall demonstrate compliance with this emission limitation by conducting emission testing in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 4, and 5 and the requirements specified in OAC rule 3745-17-03(B)(9).

b. Emission Limitation:

0.15 lb of SO₂ per million Btu of actual heat input

Applicable Compliance Method:

The monitoring, record keeping and reporting requirements in sections d)(1) and e)(1) of this permit, shall be used to demonstrate compliance with the above limitation. If required, the permittee shall demonstrate compliance with this emission limitation by conducting emission testing in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 4, and 6 and the requirements specified in OAC rule 3745-18-04(E)(1).

c. Emission Limitation:

Visible particulate emissions from any stack shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.

Applicable Compliance Method:

If required, the permittee shall demonstrate compliance with the visible particulate emission limitation above in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and the requirements specified in OAC rule 3745-17-03(B)(1).

d. Emission Limitation:

230 mg/dscm (0.10 grain/dscf)(the equivalent concentration is 162 parts per million by volume) of H₂S in the refinery fuel gas, or combined fuel stream if applicable

Applicable Compliance Method:

Compliance shall be based upon the monitoring and record keeping requirements specified in sections d)(4) through d)(7) for this emissions unit. If required, the permittee shall determine compliance with the H₂S emission limitation by using Method 11 of 40 CFR, Part 60, Appendix A, or other approved U.S. EPA methods.

g) Miscellaneous Requirements

- (1) None.

3. Emissions Unit Group - Process Heaters Group #2: B002, B005,

EU ID	Operations, Property and/or Equipment Description
B002	Refinery Fuel Gas or Natural Gas Fired ISO Stabilizer/Splitter Heaters, 369 million Btu/hr maximum heat input (PR 170003/PR 175155)
B005	Refinery Fuel Gas or Natural Gas Fired Reformate Splitter Reboiler, 118 million Btu/hr maximum heat input (PR 175168)

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only:

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-17-10(B)(1)	0.020 lb of particulate emissions (PE) per million Btu of actual heat input
b.	OAC rule 3745-18-08(C)(2)	1.0 lb of sulfur dioxide (SO ₂) per million Btu of actual heat input
	OAC rule 3745-17-07(A)	Visible particulate emissions from any stack shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.
	40 CFR 63.52(a)(2)	See b)(2)a.
	40 CFR, Part 60, Subpart J	See b)(2)b. and b)(2)c.
	40 CFR, Part 60, Subpart A	See 40 CFR 60.1 through 60.19

(2) Additional Terms and Conditions

a. This emissions unit is subject to a case-by-case MACT determination pursuant to section 112(j) of the Clean Air Act (CAA) due to the June 8, 2007 D.C. Circuit Court of Appeals decision to vacate the Boiler MACT (40 CFR Part 63, Subpart DDDDD).

If notified by the Ohio EPA or U.S. EPA, the permittee shall submit an application for a revision to this Title V permit that meets the requirements of 40 CFR 63.52(a)(2) pertaining to case-by-case MACT determinations. The 30-day clock for submittal of a 112(j) application does not begin until such notification is made by Ohio EPA or U.S. EPA.

- b. 40 CFR Part 60 - Subpart J is being added as an applicable rule for this emissions unit. The permittee is required to comply with this new source performance standard for fuel combustion by 12/31/09, per paragraph No. 118 and Appendix O of the federal consent decree addendum, civil action No. SA07CA0683RF which became effective on 11/20/07.
- c. The permittee shall not burn any refinery fuel gas in this emissions unit that contains hydrogen sulfide (H₂S) in excess of 230 mg/dscm (0.10 grain/dscf)(the equivalent concentration is 162 parts per million by volume). This H₂S standard in 40 CFR 60.104(a)(1) is also applicable if the permittee combines and combusts natural gas in any proportion with refinery fuel gas in this emissions unit, according to the fuel gas definition in 40 CFR 60.101(d).

c) Operational Restrictions

- (1) The permittee shall burn only refinery fuel gas or natural gas in this emissions unit. The sulfur content of the refinery fuel gas or natural gas burned in this emissions unit shall comply with the allowable SO₂ emission limitation specified in section b)(1)b.

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall record on a monthly basis, the calculated SO₂ emission rate in lb/mmBtu. The SO₂ emission rate shall be calculated as follows:

$$\text{Lbs SO}_2/\text{mmBtu} = \text{lbs H}_2\text{S}/\text{mmBtu} * (64 \text{ lb SO}_2/\text{lbmol})/(34 \text{ lb H}_2\text{S}/\text{lbmol})$$

Where:

$$\text{Lbs H}_2\text{S}/\text{mmBtu} = \text{ppm H}_2\text{S} * [(0.1 \text{ grain per scf}/162 \text{ ppm}) * (1 \text{ lb}/7000 \text{ grain}) * (1/\text{RFG Btu per scf})] * (10^6 \text{ Btu}/\text{mmBtu})$$

Note: The 0.1 grain per scf = 162 ppm is based directly on the H₂S limits in NSPS Subpart J 40 CFR Part 60.104(a)(1).

- (2) For each day during which the permittee burns a fuel other than refinery fuel gas or natural gas, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.
- (3) In order to demonstrate compliance with the emission limitation of 230 mg/dscm (0.10 grain/dscf)(the equivalent concentration is 162 parts per million by volume) of H₂S in the refinery fuel gas (and if applicable, combined fuel firing as noted in b)(2)c. above), the permittee shall operate and maintain an instrument for continuously monitoring and recording the concentration (dry basis) of H₂S in the refinery fuel gas or combined fuel stream before being burned in this emissions unit. The monitoring shall be conducted in accordance with 40 CFR 60.105(a)(4), as follows
 - a. The span value for this instrument is 425 mg/dscm of H₂S.
 - b. Fuel gas combustion devices having a common source of fuel gas may be monitored at only one location, if monitoring at this location accurately represents the concentration of H₂S in the fuel gas being burned.

- c. The performance evaluations for this H₂S monitor under 40 CFR 60.13(c) shall use Performance Specification 7 of 40 CFR 60, Appendix B. The permittee shall conduct an annual relative accuracy test audit (RATA) for the H₂S continuous emission monitoring equipment. Method 11 of 40 CFR, Part 60, Appendix A, or other approved U.S. EPA methods shall be used for conducting the annual RATAs.
- (4) A statement of certification of the existing H₂S continuous emission monitoring system (CEMS) shall be maintained on site and shall consist of a letter from the Ohio EPA detailing the results of an Agency review of the certification tests and a statement by the Agency that the system is considered certified in accordance with the requirements of 40 CFR, Part 60, Appendix B, Performance Specification 7. Proof of certification shall be made available to representatives of the Ohio EPA, Northwest District Office upon request.
- (5) The permittee shall operate and maintain existing equipment to continuously monitor and record hydrogen sulfide from this emissions unit in units of the applicable standard. Such continuous monitoring and recording equipment shall comply with the requirements specified in 40 CFR, Part 60.13.

The permittee shall maintain records of all data obtained by the H₂S CEMS including, but not limited to, parts per million of H₂S on an instantaneous (1-minute) basis, emissions of H₂S in units of the applicable standard (grain/dscf and parts per million by volume) as a rolling, 3-hour average, the results of daily zero/span calibration checks, and the magnitudes of manual calibration adjustments.

- (6) The permittee shall maintain a written quality assurance/quality control plan for the CEMS designed to ensure continuous valid and representative readings of H₂S. The plan shall follow the requirements of 40 CFR, Part 60, Appendix F.

A logbook dedicated to the monitoring systems must be kept on site and available for inspection during regular office hours.

The plan shall include the requirement to conduct quarterly cylinder gas audits or relative accuracy audits as required in 40 CFR, Part 60; and to conduct relative accuracy test audits in units of the standard(s), in accordance with and at the frequencies required per 40 CFR Part 60, except as noted below.

Pursuant to paragraph No. 121 of the federal consent decree addendum, civil action No. SA07CA0683RF, dated 11/20/07, the permittee is required to:

- a. Conduct a relative accuracy test audit of the NO_x CEM at a minimum frequency of once every three years; and
- b. Conduct cylinder gas audits on the NO_x CEM during each quarter when a relative accuracy test audit is not conducted.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify each month during which the SO₂ emission limitation of 1.0 lb of SO₂ per million Btu of actual heat input was exceeded, based upon the calculations specified in section d)(1).
- (2) The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than refinery fuel gas or natural gas was burned in this emissions unit. Each report shall be submitted within 30 days after the deviation occurs.
- (3) The permittee shall submit reports within thirty (30) days following the end of each calendar quarter to the Ohio EPA, Northwest District Office documenting any H₂S CEMS downtime while the emissions unit was on line (date, time, duration, and reason), along with any corrective action(s) taken. The permittee shall provide the emissions unit operating time during the reporting period and the date, time, reason, and corrective action(s) taken for each time period of source and control equipment malfunctions.

The total operating time of the emissions unit and the total operating time of the analyzer while the emissions unit was on line shall be included the quarterly report.

- (4) The permittee shall notify the Director (the Ohio EPA, Northwest District Office) on a quarterly basis, in writing, of all rolling, 3-hour periods during which the average concentration of H₂S as measured by the H₂S CEMS under 40 CFR 60.105(a)(4) exceeds 230 mg/dscm (0.10 grain/dscf)(the equivalent concentration is 162 parts per million by volume). The rolling, 3-hour average shall be determined as the arithmetic average of three contiguous 1-hour averages. The notification shall include a copy of the record and shall be sent to the Director (the Ohio EPA, Northwest District Office) by January 30, April 30, July 30, and October 30 of each year and shall address the data obtained during previous calendar quarters.
- (5) If there are no concentrations of H₂S in the refinery fuel gas (or combined fuel stream, if applicable) greater than 230 mg/dscm (0.10 grain/dscf)(the equivalent concentration is 162 parts per million by volume) during the calendar quarter, then the permittee shall submit a statement to that effect along with the emissions unit and monitor operating times. These quarterly reports shall be submitted by January 30, April 30, July 30, and October 30 of each year and shall address the data obtained during previous calendar quarters.

f) Testing Requirements

- (1) Compliance with the emission limitations in section b)(1) of these terms and conditions shall be determined in accordance with the following methods:

a. Emission Limitation:

0.020 lb of PE per million Btu of actual heat input

Applicable Compliance Method:

The permittee shall demonstrate compliance with this limitation by multiplying the maximum hourly refinery fuel gas or natural gas combustion rate, in million

standard cubic feet per hour, by the appropriate particulate emission factor, in lb(s) per million standard cubic feet, from AP-42 Chapter 1.4 (7/98), and then dividing by the maximum heat input to the process heater. If required, the permittee shall demonstrate compliance with this emission limitation by conducting emission testing in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 4, and 5 and the requirements specified in OAC rule 3745-17-03(B)(9).

b. Emission Limitation:

1.0 lb of SO₂ per million Btu of actual heat input

Applicable Compliance Method:

The monitoring, record keeping and reporting requirements in sections d)(1) and e)(1) of this permit, shall be used to demonstrate compliance with the above limitation. If required, the permittee shall demonstrate compliance with this emission limitation by conducting emission testing in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 4, and 6 and the requirements specified in OAC rule 3745-18-04(E)(1).

c. Emission Limitation:

Visible particulate emissions from any stack shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.

Applicable Compliance Method:

If required, the permittee shall demonstrate compliance with the visible particulate emission limitation above in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and the requirements specified in OAC rule 3745-17-03(B)(1).

d. Emission Limitation:

230 mg/dscm (0.10 grain/dscf)(the equivalent concentration is 162 parts per million by volume) of H₂S in the refinery fuel gas, or combined fuel stream if applicable

Applicable Compliance Method:

Compliance shall be based upon the monitoring and record keeping requirements specified in sections d)(4) through d)(7) for this emissions unit. If required, the permittee shall determine compliance with the H₂S emission limitation by using Method 11 of 40 CFR, Part 60, Appendix A, or other approved U.S. EPA methods.

g) Miscellaneous Requirements

(1) None.