



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL
UNION COUNTY**

CERTIFIED MAIL

Street Address:

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:
Lazarus Gov.
Center

Application No: 01-08118

DATE: 6/07/00

Honda of America Mfg Inc
Joanna Bambeck
24000 Honda Parkway
Marysville, OH 43040-9190

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Director's action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
236 East Town Street, Room 300
Columbus, Ohio 43215

Very truly yours,

Thomas G. Rigo
Field Operations and Permit Section
Division of Air Pollution Control

CC: USEPA

CDO



STATE OF OHIO ENVIRONMENTAL PROTECTION AGENCY

FINAL PERMIT TO INSTALL 01-08118

Application Number: 01-08118
APS Premise Number: 0180000130
Permit Fee: **\$400**
Name of Facility: Honda of America Mfg Inc
Person to Contact: Joanna Bambeck
Address: 24000 Honda Parkway
Marysville, OH 43040-9190

Location of proposed air contaminant source(s) [emissions unit(s)]:

**24000 Honda Pkwy
Marysville, Ohio**

Description of proposed emissions unit(s):

Welding lines 1 and 2.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. State and Federally Enforceable Permit To Install General Terms and Conditions

1. Monitoring and Related Recordkeeping and Reporting Requirements

- a. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:
 - i. The date, place (as defined in the permit), and time of sampling or measurements.
 - ii. The date(s) analyses were performed.
 - iii. The company or entity that performed the analyses.
 - iv. The analytical techniques or methods used.
 - v. The results of such analyses.
 - vi. The operating conditions existing at the time of sampling or measurement.
- b. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.
- c. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall submit required reports in the following manner:
 - i. Reports of any required monitoring and/or recordkeeping of federally enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
 - ii. Quarterly written reports of (i) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, excluding deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06, that have been detected by the testing, monitoring and recordkeeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures taken, shall be made to the appropriate Ohio EPA District Office or local air agency. The written reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. See B.11 below if no deviations occurred during the quarter.

- iii. Written reports, which identify any deviations from the federally enforceable monitoring, recordkeeping, and reporting requirements contained in this permit shall be submitted to the appropriate Ohio EPA District Office or local air agency every six months, i.e., by January 31 and July 31 of each year for the previous six calendar months. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report, which states that no deviations occurred during that period.
- iv. Each written report shall be signed by a responsible official certifying that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.

2. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction, i.e., upset, of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. (The definition of an upset condition shall be the same as that used in OAC rule 3745-15-06(B)(1) for a malfunction.) The verbal and written reports shall be submitted pursuant to OAC rule 3745-15-06.

Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emission unit(s) that is (are) served by such control system(s).

3. Risk Management Plans

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. 7401 et seq. ("Act"), the permittee shall comply with the requirement to register such a plan.

4. Title IV Provisions

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

5. Severability Clause

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition declared invalid.

6. General Requirements

- a. The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and reissuance, or modification, or for denial of a permit renewal application.
- b. It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.
- c. This permit may be modified, reopened, revoked, or revoked and reissued, for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.
- d. This permit does not convey any property rights of any sort, or any exclusive privilege.
- e. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

7. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit To Install fees within 30 days after the issuance of this Permit To Install.

8. Federal and State Enforceability

Only those terms and conditions designated in this permit as federally enforceable, that are required under the Act, or any of its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA, the State, and citizens under the Act. All other terms and conditions of this permit shall not be federally enforceable and shall be enforceable under State law only.

9. Compliance Requirements

- a. Any document (including reports) required to be submitted and required by a federally

Honda of America Mfg Inc
PTI Application: 01-08118
Issued: June 7, 2000

Facility ID: 0180000130

applicable requirement in this permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.

- b. Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:
 - i. At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.
 - ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with ORC section 3704.08.
 - iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.
 - iv. As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.
- c. The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually, or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:
 - i. Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
 - ii. An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

10. Permit To Operate Application

- a. If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete

Honda of America Mfg Inc
PTI Application: 01-08118
Issued: June 7, 2000

Facility ID: 0180000130

Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).

- b. If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35 , the source(s) identified in this Permit To Install is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within thirty (30) days after commencing operation of the source(s) covered by this permit.

Honda of America Mfg Inc
PTI Application: 01-08118
Issued: June 7, 2000

Facility ID: 0180000130

B. State Only Enforceable Permit To Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping of state-only enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from state-only required emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

4. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

5. Termination of Permit To Install

Honda of America Mfg Inc
PTI Application: 01-08118
Issued: June 7, 2000

Facility ID: 0180000130

This permit to install shall terminate within eighteen months of the effective date of the permit to install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

6. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources are inadequate or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities prove to be inadequate or cannot meet applicable standards.

7. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

8. Applicability

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

9. Best Available Technology

Honda of America Mfg Inc
PTI Application: 01-08118
Issued: June 7, 2000

Facility ID: 0180000130

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

10. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit To Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

11. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations (See Section A of This Permit)

If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.

C. Permit To Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
PM	0.52
OC	11.0

Honda of America Mfg Inc
PTI Application: 01-08118
Issued: June 7, 2000

Facility ID: 0180000130

Honda of America Mfg Inc
PTI Application: 01 00110
Issued

Facility ID: 0180000130

Emissions Unit ID: P004

Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

A. State and Federally Enforceable Permit To Install Facility Specific Terms and Conditions

None

B. State Only Enforceable Permit To Install Facility Specific Terms and Conditions

None

Honda

PTI A

Emissions Unit ID: P004

Issued: June 7, 2000

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P004 - Weld Line 2: robotic & resistance welding, and organic material usage (below) in welding	OAC rule 3745-31-05(D)	Organic compound emissions shall not exceed 11.0 tons per rolling 12 months for welding operations on Line 1 (P330) and Line 2 (P004).
P004- Weld Line 2: MIG welding and brazing	OAC rule 3745-31-05(A)(3)	Fugitive particulate emissions shall not exceed 0.26 lb/hr and 0.52 ton/yr from Weld Line 1 & Line 2 together See Sections A.I.2.c and A.II.1.
Anti-spatter materials and cleaning solution usage	OAC rule 3745-31-05(A)(3)	Anti-spatter materials and cleaning solutions shall not exceed 4.3 lbs OC/gal.
Anti-spatter material and cleaning solution usage	OAC rule 3745-21-07(G)	Use of only non-photochemically reactive materials or materials exempt under 3745-21-07(G)(9) for non-coatings
Miscellaneous sealers/sealants and quality marker coating usage	OAC rule 3745-21-09(U)(2)(e)(iii)	Use of no more than 10 gallons/day of miscellaneous *sealers/sealants and quality marker coatings

Honda

PTI A

Emissions Unit ID: P004

Issued: June 7, 2000

* These sealers and sealants are not the same materials, nor the same application, as those permitted for use in emission units P005 and P200, the phosphate pretreatment processes.

2. Additional Terms and Conditions

2.a This emissions unit shall use only nonphotochemically reactive materials or materials exempt per OAC 3745-21-07(G)(9) for non-coatings.

2.b The maximum annual production rate for Line 1 and Line 2 shall not exceed 470,000 units (cars), based upon a the rolling, 12-month production of cars measured at the "AF Off".

2.c The annual usage of MIG and brazing wire and rod shall not exceed 443,000 pounds per year on Line 1 and Line 2 together.

II. Operational Restrictions

The permittee shall minimize or eliminate visible particulate emissions through the installation and operation of collection hoods and fans at the point of emissions from the primary MIG welding. This collection system shall be vented to a baghouse having a collection efficiency of 90%, whenever the emissions unit is in operation. Capture efficiency at the point source of emissions shall be calculated at 85%, unless testing of the hood collection system demonstrates a different efficiency. Manual repair, mobile MIG welding, and the individual MIG robots on D Zone operations shall not require control.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each month for the welding operations:
 - a. the name and identification for each anti-spatter and cleaning solution employed; and
 - b. the organic compound content of each anti-spatter and cleaning solution, as applied.
2. The permittee shall collect and record the following information each day for the welding operations:
 - a. the name and identification for each miscellaneous sealer/sealant, quality marker coating, and/or miscellaneous organic material employed to the auto body or metal part;

Honda of America Mfg Inc
PTI Application: 01 00110
Issued

Facility ID: 0180000130

Emissions Unit ID: P004

- b. the volume, in gallons, of each miscellaneous sealer/sealant and quality marker coating employed; and
- c. the total volume, in gallons, of all miscellaneous sealers/sealants and quality marker coatings employed.

If the total use of these materials, in any single day, is less than 1 gallon per day, the material used need only be recorded in the daily record as <1 gallon. Monthly emissions shall be calculated using actual monthly usage inventory records, if monthly records prove more accurate than the sum of daily usage.

- 3. The permittee shall collect and record the following information each month for the welding operations:
 - a. the number of gallons of each cleaning solution, anti-spatter material, miscellaneous sealer/sealant, quality marker coating, miscellaneous organic material employed, and pounds (or tons) of MIG and brazing wire/rod consumed;
 - b. the organic compound content of each cleaning solution, anti-spatter material, miscellaneous sealer/sealant, quality marker coating, and/or miscellaneous organic material, in pounds per gallon;
 - c. the total organic compound emissions from all cleaning solutions, anti-spatter materials, miscellaneous sealers/sealants, quality marker coatings, miscellaneous organic material usage, and the vaporization of rust preventive oils from spot welding, in pounds per month;
 - d. the rolling 12-month production of automobiles, measured at the "AF Off" area; and
 - e. the rolling 12-month OC emissions from welding operations on Line 1 and Line 2.
- 4. The permittee shall maintain records that document any time periods when the hood collection or fabric filter systems were not in service when the emissions unit was in operation.

IV. Reporting Requirements

- 1. The permittee shall submit deviation (excursion) reports which include the following:
 - a. any monthly record or calculation showing an exceedance of the 12-month rolling OC emissions limit of 11.0 tons for Line 1 and Line 2 welding operations, and/or the rolling

Honda
PTI A
Issued: June 7, 2000

Emissions Unit ID: P004

12-month production of 470,000 units(cars)
 measured at the "AF Off";

- b. any record showing an exceedance of the annual MIG brazing wire/rod usage of 443,000 pounds per year on welding Lines 1 and 2.
- c. any occurrence of the use of a photochemically reactive material or material not exempted in 3745-21-07(G)(9) for non-coatings, including an identification of the material used, it's composition, and the day(s) and duration of time the material was used.

These exceedance reports shall be submitted as required in the General Terms and Conditions of this permit.

2. The permittee shall notify the Ohio EPA Central District Office in writing of any record showing the use of noncomplying (>4.3 lbs OC/gal) anti-spatter materials or cleaning solutions. The notification shall include a copy of such record and shall be sent to the Ohio EPA Central District Office within 30 days following the end of the calendar month.
3. The permittee shall notify the Ohio EPA Central District Office in writing of any daily record showing that the welding line employed more than 10 gallons per day of miscellaneous sealers/sealant(s) and quality marker coating(s) (together). The notification shall include a copy of such record and shall be sent to the Ohio EPA Central District Office within 45 days after the exceedance occurs.
4. The permittee shall notify the Ohio EPA Central District Office of any daily record showing that the hood collection system/fan and/or fabric filter were not in service when the emissions unit was in operation.
5. The permittee shall also submit annual reports which specify the total OC emissions from this emissions unit for the previous calendar year. This report may be satisfied by including this emissions unit in the submission of the annual Fee Emission Report. Particulate emissions need not be reported, since the potential emissions for this emissions unit is under 1 ton per year from each line.

V. Testing Requirements

Compliance with the emission limitations contained in this permit shall be determined in accordance with the following methods:

1. Emission Limitation

11.0 tons OC/yr for Line 1 and Line 2 welding operations

Honda of America Mfg Inc
PTI Application: 01 00110
Issued

Facility ID: 0180000130

Emissions Unit ID: P004

Applicable Compliance Method

Compliance with the rolling 12-month OC limit shall be determined through monthly and 12-month rolling recordkeeping of units produced, material usage, the organic compound content of each material used, calculation of the volatile emissions from rust protecting oils from the point of weld (calculated, as shown below), and the rolling 12-month summation of calculated OC emissions. Formulation data from the material's manufacturer or USEPA Method 24 shall be used to determine the organic compound content of the cleaning solutions, anti-spatter materials, sealers/sealants, quality marker coatings, and/or miscellaneous organic materials to be used in the calculation of emissions. Twelve month rolling emissions shall be calculated by adding the current monthly emission calculations, from the emissions unit, to the previous 11 month's emission calculations.

Organic compound emissions from the rust protectant oils at the point of weld, shall be calculated as follows:

Annual Emissions = Area of weld (PiR²) or (3.1416)(0.0328 ft)² x amount of rust protective oil on metal sheet (275 mg/ft²) x (0.0022 lb/1000 mg) x (3,000 welds/car) x (500,000 units and parts on Lines 1 & 2/yr) x (4 sides/weld) x (1 ton/2000 lbs) = 6.14 tons OC/year

Unless any of the variables in this equation change, the worst case emission calculations from the evaporation of rust-proofing oil(s) at the point of weld, above, shall be used to document the contribution of this source of OC emissions, to this limit.

2. Emission Limitation

0.26 lb particulate emissions/hr from both Lines 1 and 2
 0.52 ton particulate emissions/yr from both Lines 1 and 2

Applicable Compliance Method

Compliance with the particulate limits contained in this permit shall be determined through annual calculation of worst case emissions. To document the worst case emission rate for particulate matter, the following equations shall be used:

Hourly Emissions = [maximum MIG and brazing wire/rod usage (110.76 pounds per hour for Line 1 and Line 2) X emission factor from Gradient Corporation and by the American Welding Company (0.01 lbs particulate emissions/pound of MIG and brazing wire) X uncaptured fugitive emissions at the point of weld (100%-85%)] + [maximum MIG and brazing wire/rod usage (110.76 pounds per hour for Line 1 and Line 2) X emission factor from Gradient Corporation and by the American Welding Company (0.01 lbs particulate emissions/pound of MIG and brazing wire) X fugitive emissions lost from the baghouse (85%) x (100%-90%)] = 0.26 lbs particulate emissions/hour.

Annual Emissions = [actual or maximum MIG and brazing wire/rod usage (443,000 pounds per

Honda**PTI A**

Emissions Unit ID: P004

Issued: June 7, 2000

year for Line 1 and Line 2) X emission factor from Gradient Corporation and by the American Welding Company (0.01 lbs particulate emissions/pound of MIG wire) X uncaptured fugitive emissions at the point of weld (100%-85%)] + [actual or maximum MIG wire usage (443,000 pounds per year for Line 1 and Line 2) X emission factor from Gradient Corporation and by the American Welding Company (0.01 lbs particulate emissions/pound of MIG wire) X fugitive emissions lost from the baghouse (85%) x (100%-90%)] x [1 ton/2000 lbs] = 0.52 tons particulate emissions/yr.

VI. Miscellaneous Requirements

This Permit to Install (PTI) shall supercede the requirements for this emissions unit in the PTI numbered 01-759 issued June 27, 1990.

Honda

PTI A

Emissions Unit ID: P004

Issued: June 7, 2000

B. State Only Enforceable Section**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P004 - Weld Line 2: robotic & manual MIG & resistance welding, brazing, and organic material usage in welding	OAC rule 3745-15-07	Organic compound emissions shall not exceed 5.9 lbs OC/hour from Line 1 and Line 2; and See Section B.I.2.a below.

2. Additional Terms and Conditions

- 2.a The hourly OC limit was established at maximum usage and production, and was used to establish compliance with the Toxics Policy. Therefore no recordkeeping is necessary to determine compliance with this limit.

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" usage for this pollutant:

Pollutant: dipropylene glycol monomethyl ether

Honda of America Mfg Inc
PTI Application: 01 00110
Issued

Facility ID: 0180000130

Emissions Unit ID: P004

TLV: 606 mg/m³

Maximum Hourly Emission Rate: 1.134 lbs/hr from both welding Lines 1 and 2

Predicted 1-Hour Maximum Ground-Level Concentration: 0.129 mg/m³

MAGLC: 14.43 mg/m³

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

Honda

PTI A

Emissions Unit ID: P004

Issued: June 7, 2000

- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

Honda of America Mfg Inc
PTI Application: 01 00110
Issued

Facility ID: 0180000130

Emissions Unit ID: P004

IV. Reporting Requirements

The permittee shall notify the Ohio EPA Central District Office of any daily record showing the unit production rate to exceed 64 units per hour, as measured at "Weld Off", on either Line 1 or Line 2, this the potential of the each line, excluding spare parts. This exceedance report shall be submitted as required in the General Terms and Conditions of this permit.

V. Testing Requirements

Emission Limit

5.9 lbs OC/hr

Compliance Method

The following worst case emissions calculation for the evaporation of rust-proofing oil(s) at the point of weld, shall document the potential OC emissions from Line 1 and Line 2 welding operations:

Hourly emissions = Area of weld (PiR^2) or $(3.1416) \times (0.0328 \text{ ft})^2 \times$ amount of rust protective oil on metal sheet $(275 \text{ mg/ft}^2) \times (0.0022 \text{ lb/1000 mg}) \times (3,000 \text{ welds/car}) \times (64 \text{ unit/hr}) \times (4 \text{ sides/weld}) \times 2 \text{ Lines} = 3.14 \text{ lbs/hr}$

The following worst case emissions calculations for material usage, shall document the potential OC emissions from Line 1 and Line 2 welding operations:

Cleaning solutions: $0.25 \text{ gal/hr} \times 4.30 \text{ lbs OC/gal} = 1.075 \text{ lbs OC/hr}$
 Anti-spatter materials: $0.565 \text{ gal/hr} \times 0.36 \text{ lbs OC/gal} = 0.203 \text{ lbs OC/hr}$
 Sealants: $0.005 \text{ gal/hr} \times 4.45 \text{ lbs OC/gal} = 0.022 \text{ lbs OC/hr}$
 Quality marker paints: $0.01 \text{ gal/hr} \times 6.40 \text{ lbs OC/gal} = 0.064 \text{ lbs OC/hr}$

$1.075 \text{ lbs OC/hr} + 0.203 \text{ lb OC/hr} + 0.022 \text{ lb OC/hr} + 0.064 \text{ lb OC/hr} = 1.364 \text{ lbs OC/hr} \times 2 \text{ Lines} = 2.73 \text{ lbs OC/hr}$

If, at any time, production exceeds 64 units per hour, the permittee shall submit a deviation report as per the requirements in Section B.IV.

VI. Miscellaneous Requirements

None.

Honda

PTI A

Emissions Unit ID: P330

Issued: June 7, 2000

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P330 - Weld Line 1: robotic & resistance welding, and organic material usage (below) in welding	OAC rule 3745-31-05(D)	Organic compound emissions shall not exceed 11.0 tons per rolling 12 months for welding operations on Line 1 (P330) and Line 2 (P004).
P330- Weld Line 1: MIG welding and brazing	OAC rule 3745-31-05(A)(3)	Fugitive particulate emissions shall not exceed 0.26 lb/hr and 0.52 ton/yr from Weld Line 1 & Line 2 together See Sections A.I.2.c and A.II.1.
Anti-spatter materials and cleaning solution usage	OAC rule 3745-31-05(A)(3)	Anti-spatter materials and cleaning solutions shall not exceed 4.3 lbs OC/gal.
Anti-spatter material and cleaning solution usage	OAC rule 3745-21-07(G)	Use of only non-photochemically reactive materials or materials exempt under 3745-21-07(G)(9) for non-coatings
Miscellaneous sealers/sealants and quality marker coating usage	OAC rule 3745-21-09(U)(2)(e)(iii)	Use of no more than 10 gallons/day of miscellaneous *sealers/sealants and quality marker coatings

Honda

PTI A

Emissions Unit ID: P330

Issued: June 7, 2000

* These sealers and sealants are not the same materials, nor the same application, as those permitted for use in emission units P005 and P200, the phosphate pretreatment processes.

2. Additional Terms and Conditions

- 2.a** This emissions unit shall use only nonphotochemically reactive materials or materials exempt per OAC 3745-21-07(G)(9) for non-coatings.
- 2.b** The maximum annual production rate for Line 1 and Line 2 shall not exceed 470,000 units (cars), based upon a the rolling, 12-month production of cars measured at the "AF Off".
- 2.c** The annual usage of MIG and brazing wire and rod shall not exceed 443,000 pounds per year on Line 1 and Line 2 together.

II. Operational Restrictions

The permittee shall minimize or eliminate visible particulate emissions through the installation and operation of collection hoods and fans at the point of emissions from the primary MIG welding. This collection system shall be vented to a baghouse having a collection efficiency of 90%, whenever the emissions unit is in operation. Capture efficiency at the point source of emissions shall be calculated at 85%, unless testing of the hood collection system demonstrates a different efficiency. Manual repair, mobile MIG welding, and the individual MIG robots on D Zone operations shall not require control.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each month for the welding operations:
 - a. the name and identification for each anti-spatter and cleaning solution employed; and
 - b. the organic compound content of each anti-spatter and cleaning solution, as applied.
2. The permittee shall collect and record the following information each day for the welding operations:
 - a. the name and identification for each miscellaneous sealer/sealant, quality marker coating, and/or miscellaneous organic material employed to the auto body or metal part;

Emissions Unit ID: P330

- b. the volume, in gallons, of each miscellaneous sealer/sealant and quality marker coating employed; and
- c. the total volume, in gallons, of all miscellaneous sealers/sealants and quality marker coatings employed.

If the total use of these materials, in any single day, is less than 1 gallon per day, the material used need only be recorded in the daily record as <1 gallon. Monthly emissions shall be calculated using actual monthly usage inventory records, if monthly records prove more accurate than the sum of daily usage.

3. The permittee shall collect and record the following information each month for the welding operations:

- a. the number of gallons of each cleaning solution, anti-spatter material, miscellaneous sealer/sealant, quality marker coating, miscellaneous organic material employed, and pounds (or tons) of MIG and brazing wire/rod consumed;
- b. the organic compound content of each cleaning solution, anti-spatter material, miscellaneous sealer/sealant, quality marker coating, and/or miscellaneous organic material, in pounds per gallon;
- c. the total organic compound emissions from all cleaning solutions, anti-spatter materials, miscellaneous sealers/sealants, quality marker coatings, miscellaneous organic material usage, and the vaporization of rust preventive oils from spot welding, in pounds per month;
- d. the rolling 12-month production of automobiles, measured at the "AF Off" area; and
- e. the rolling 12-month OC emissions from welding operations on Line 1 and Line 2.

4. The permittee shall maintain records that document any time periods when the hood collection or fabric filter systems were not in service when the emissions unit was in operation.

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which include the following:
 - a. any monthly record or calculation showing an exceedance of the 12-month rolling OC emissions limit of 11.0 tons for Line 1 and Line 2 welding operations, and/or the rolling 12-month production of 470,000 units(cars) measured at the "AF Off";
 - b. any record showing an exceedance of the annual MIG brazing wire/rod usage of 443,000 pounds per year on welding Lines 1 and 2.

Honda**PTI A**

Emissions Unit ID: P330

Issued: June 7, 2000

- c. any occurrence of the use of a photochemically reactive material or material not exempted in 3745-21-07(G)(9) for non-coatings, including an identification of the material used, its composition, and the day(s) and duration of time the material was used.

These exceedance reports shall be submitted as required in the General Terms and Conditions of this permit.

2. The permittee shall notify the Ohio EPA Central District Office in writing of any record showing the use of noncomplying (>4.3 lbs OC/gal) anti-spatter materials or cleaning solutions. The notification shall include a copy of such record and shall be sent to the Ohio EPA Central District Office within 30 days following the end of the calendar month.
3. The permittee shall notify the Ohio EPA Central District Office in writing of any daily record showing that the welding line employed more than 10 gallons per day of miscellaneous sealers/sealant(s) and quality marker coating(s) (together). The notification shall include a copy of such record and shall be sent to the Ohio EPA Central District Office within 45 days after the exceedance occurs.
4. The permittee shall notify the Ohio EPA Central District Office of any daily record showing that the hood collection system/fan and/or fabric filter were not in service when the emissions unit was in operation.
5. The permittee shall also submit annual reports which specify the total OC emissions from this emissions unit for the previous calendar year. This report may be satisfied by including this emissions unit in the submission of the annual Fee Emission Report. Particulate emissions need not be reported, since the potential emissions for this emissions unit is under 1 ton per year from each line.

V. Testing Requirements

Compliance with the emission limitations contained in this permit shall be determined in accordance with the following methods:

1. Emission Limitation

11.0 tons OC/yr for Line 1 and Line 2 welding operations

Applicable Compliance Method

Compliance with the rolling 12-month OC limit shall be determined through monthly and 12-month rolling recordkeeping of units produced, material usage, the organic compound content of each material used, calculation of the volatile emissions from rust protecting oils from the point

Honda of America Mfg Inc
PTI Application: 01-00110
Issued

Facility ID: 0180000130

Emissions Unit ID: P330

of weld (calculated, as shown below), and the rolling 12-month summation of calculated OC emissions. Formulation data from the material's manufacturer or USEPA Method 24 shall be used to determine the organic compound content of the cleaning solutions, anti-spatter materials, sealers/sealants, quality marker coatings, and/or miscellaneous organic materials to be used in the calculation of emissions. Twelve month rolling emissions shall be calculated by adding the current monthly emission calculations, from the emissions unit, to the previous 11 month's emission calculations.

Organic compound emissions from the rust protectant oils at the point of weld, shall be calculated as follows:

Annual Emissions = Area of weld (PiR²) or (3.1416)(0.0328 ft)² x amount of rust protective oil on metal sheet (275 mg/ft²) x (0.0022 lb/1000 mg) x (3,000 welds/car) x (500,000 units and parts on Lines 1 & 2/yr) x (4 sides/weld) x (1 ton/2000 lbs) = 6.14 tons OC/year

Unless any of the variables in this equation change, the worst case emission calculations from the evaporation of rust-proofing oil(s) at the point of weld, above, shall be used to document the contribution of this source of OC emissions, to this limit.

2. Emission Limitation

0.26 lb particulate emissions/hr from both Lines 1 and 2
 0.52 ton particulate emissions/yr from both Lines 1 and 2

Applicable Compliance Method

Compliance with the particulate limits contained in this permit shall be determined through annual calculation of worst case emissions. To document the worst case emission rate for particulate matter, the following equations shall be used:

Hourly Emissions = [maximum MIG and brazing wire/rod usage (110.76 pounds per hour for Line 1 and Line 2) X emission factor from Gradient Corporation and by the American Welding Company (0.01 lbs particulate emissions/pound of MIG and brazing wire) X uncaptured fugitive emissions at the point of weld (100%-85%)] + [maximum MIG and brazing wire/rod usage (110.76 pounds per hour for Line 1 and Line 2) X emission factor from Gradient Corporation and by the American Welding Company (0.01 lbs particulate emissions/pound of MIG and brazing wire) X fugitive emissions lost from the baghouse (85%) x (100%-90%)] = 0.26 lbs particulate emissions/hour.

Annual Emissions = [actual or maximum MIG and brazing wire/rod usage (443,000 pounds per year for Line 1 and Line 2) X emission factor from Gradient Corporation and by the American Welding Company (0.01 lbs particulate emissions/pound of MIG wire) X uncaptured fugitive emissions at the point of weld (100%-85%)] + [actual or maximum MIG wire usage (443,000 pounds per year for Line 1 and Line 2) X emission factor from Gradient Corporation and by the American Welding Company (0.01 lbs particulate emissions/pound of MIG wire) X fugitive

Honda

PTI A

Emissions Unit ID: P330

Issued: June 7, 2000

emissions lost from the baghouse (85%) x (100%-90%) x [1 ton/2000 lbs] = 0.52 tons
particulate emissions/yr.

VI. Miscellaneous Requirements

This Permit to Install (PTI) shall supercede the requirements for this emissions unit (then included in P004) in the PTI numbered 01-759 issued June 27, 1990.

Honda of America Mfg Inc
 PTI Application: 01 00110
 Issued

Facility ID: 0180000130

Emissions Unit ID: P330

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P330 - Weld Line 1: robotic & manual MIG & resistance welding, brazing, and organic material usage in welding	OAC rule 3745-15-07	Organic compound emissions shall not exceed 5.9 lbs OC/hour from Line 1 and Line 2; and See Section B.I.2.a below.

2. Additional Terms and Conditions

- The hourly OC limit was established at maximum usage and production, and was used to establish compliance with the Toxics Policy. Therefore no recordkeeping is necessary to determine compliance with this limit.

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

- The permit to install for this emissions unit was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" usage for this pollutant:

Pollutant: dipropylene glycol monomethyl ether

TLV: 606 mg/m³

Maximum Hourly Emission Rate: 1.134 lbs/hr from both welding Lines 1 and 2

Predicted 1-Hour Maximum Ground-Level Concentration: 0.129 mg/m³

MAGLC: 14.43 mg/m³

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
 - a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.
3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

Honda of America Mfg Inc
PTI Application: 01 00110
Issued

Facility ID: 0180000130

Emissions Unit ID: P330

- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

The permittee shall notify the Ohio EPA Central District Office of any daily record showing the unit production rate to exceed 64 units per hour, as measured at "Weld Off", on either Line 1 or Line 2, this the potential of the each line, excluding spare parts. This exceedance report shall be submitted as required in the General Terms and Conditions of this permit.

V. Testing Requirements

Emission Limit

5.9 lbs OC/hr

Compliance Method

The following worst case emissions calculation for the evaporation of rust-proofing oil(s) at the point of weld, shall document the potential OC emissions from Line 1 and Line 2 welding operations:

Hourly emissions = Area of weld (PiR^2) or $(3.1416) \times (0.0328 \text{ ft})^2 \times$ amount of rust protective oil on metal sheet $(275 \text{ mg/ft}^2) \times (0.0022 \text{ lb/1000 mg}) \times (3,000 \text{ welds/car}) \times (64 \text{ unit/hr}) \times (4 \text{ sides/weld}) \times 2 \text{ Lines} = 3.14 \text{ lbs/hr}$

The following worst case emissions calculations for material usage, shall document the potential OC emissions from Line 1 and Line 2 welding operations:

Cleaning solutions:	$0.25 \text{ gal/hr} \times 4.30 \text{ lbs OC/gal} = 1.075 \text{ lbs OC/hr}$
Anti-spatter materials:	$0.565 \text{ gal/hr} \times 0.36 \text{ lbs OC/gal} = 0.203 \text{ lbs OC/hr}$
Sealants:	$0.005 \text{ gal/hr} \times 4.45 \text{ lbs OC/gal} = 0.022 \text{ lbs OC/hr}$
Quality marker paints:	$0.01 \text{ gal/hr} \times 6.40 \text{ lbs OC/gal} = 0.064 \text{ lbs OC/hr}$

$1.075 \text{ lbs OC/hr} + 0.203 \text{ lb OC/hr} + 0.022 \text{ lb OC/hr} + 0.064 \text{ lb OC/hr} = 1.364 \text{ lbs OC/hr} \times 2 \text{ Lines} = 2.73 \text{ lbs OC/hr}$

If, at any time, production exceeds 64 units per hour, the permittee shall submit a deviation report as per the requirements in Section B.IV.

Honda

PTI A

Issued: June 7, 2000

VI. Miscellaneous Requirements

Emissions Unit ID: P330

None.

NEW SOURCE REVIEW FORM B

PTI Number: 01-08118 Facility ID: 0180000130

FACILITY NAME Honda of America Mfg Inc

FACILITY DESCRIPTION Auto and Motorcycle manufacturer CITY/TWP Marysville

SIC CODE 3711 SCC CODE 3-14-009-01 EMISSIONS UNIT ID P004

EMISSIONS UNIT DESCRIPTION Weld Line 2: robotic & manual MIG & resistance welding, brazing, sealer application, and miscellaneous organic use in welding

DATE INSTALLED 1982

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	Attainment	0.13	0.26	0.13	0.26
PM ₁₀					
Sulfur Dioxide					
Organic Compounds	Attainment	2.95	5.50	2.95	5.50
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? Yes

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT?

\$

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? X YES NOIDENTIFY THE AIR CONTAMINANTS: dipropylene glycol monomethy ether

34 NEW SOURCE REVIEW FORM B

PTI Number: 01-08118 Facility ID: 0180000130

FACILITY NAME Honda of America Mfg Inc

FACILITY DESCRIPTION Auto and Motorcycle manufacturer CITY/TWP Marvsville

Emissions Unit ID: P330

SIC CODE 3711 SCC CODE 3-14-009-01 EMISSIONS UNIT ID P330

EMISSIONS UNIT DESCRIPTION Weld Line 1: robotic & manual MIG & resistance welding, brazing, sealer application, and miscellaneous organic use in welding

DATE INSTALLED 1984

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	Attainment	0.13	0.26	0.13	0.26
PM ₁₀					
Sulfur Dioxide					
Organic Compounds	Attainment	2.95	5.50	2.95	5.50
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NPSPS? NESHAP? PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? Yes

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? X YES NO

IDENTIFY THE AIR CONTAMINANTS: dipropylene glycol monomethyl ether