



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL MODIFICATION  
UNION COUNTY**

**CERTIFIED MAIL**

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center  
P.O. Box 1049

**Application No: 01-05659**

**Fac ID: 0180000130**

**DATE: 12/16/2004**

Honda of America Mfg., Inc.  
Stephen Fogle  
24000 Honda Parkway  
Marysville, OH 430409190

Enclosed Please find a modification to the Ohio EPA Permit To Install referenced above which will modify the terms and conditions.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission  
309 South Fourth Street, Room 222  
Columbus, Ohio 43215

Sincerely,

Michael W. Ahern, Manager  
Permit Issuance and Data Management Section  
Division of Air Pollution Control

cc: USEPA

CDO



**Permit To Install  
Terms and Conditions**

**Issue Date: 12/16/2004  
Effective Date: 12/16/2004**

FINAL ADMINISTRATIVE MODIFICATION OF PERMIT TO INSTALL 01-05659

Application Number: 01-05659  
Facility ID: 0180000130  
Permit Fee: **\$700**  
Name of Facility: Honda of America Mfg., Inc.  
Person to Contact: Stephen Fogle  
Address: 24000 Honda Parkway  
Marysville, OH 430409190

Location of proposed air contaminant source(s) [emissions unit(s)]:  
**24000 Honda Parkway  
Marysville, Ohio**

Description of proposed emissions unit(s):  
**Injection molding.**

The above named entity is hereby granted a modification to the permit to install described above pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this modification does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described source(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans included in the application, the above described source(s) of pollutants will be granted the necessary operating permits.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency  


Director

## Part I - GENERAL TERMS AND CONDITIONS

### A. State and Federally Enforceable Permit To Install General Terms and Conditions

#### 1. Monitoring and Related Recordkeeping and Reporting Requirements

- a. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:
  - i. The date, place (as defined in the permit), and time of sampling or measurements.
  - ii. The date(s) analyses were performed.
  - iii. The company or entity that performed the analyses.
  - iv. The analytical techniques or methods used.
  - v. The results of such analyses.
  - vi. The operating conditions existing at the time of sampling or measurement.
- b. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.
- c. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall submit required reports in the following manner:
  - i. Reports of any required monitoring and/or recordkeeping of federally enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
  - ii. Quarterly written reports of (i) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, excluding deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06, that have been detected by the testing, monitoring and recordkeeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures taken, shall be made to the appropriate Ohio EPA District Office or local air agency. The written reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous

**Honda of America Mfg., Inc.**  
**PTI Application: 01-05659**  
**Modification Issued: 12/16/2004**

**Facility ID: 0180000130**

calendar quarters. See B.9 below if no deviations occurred during the quarter.

- iii. Written reports, which identify any deviations from the federally enforceable monitoring, recordkeeping, and reporting requirements contained in this permit shall be submitted to the appropriate Ohio EPA District Office or local air agency every six months, i.e., by January 31 and July 31 of each year for the previous six calendar months. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report, which states that no deviations occurred during that period.
- iv. Each written report shall be signed by a responsible official certifying that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.

## **2. Scheduled Maintenance/Malfunction Reporting**

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction, i.e., upset, of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. (The definition of an upset condition shall be the same as that used in OAC rule 3745-15-06(B)(1) for a malfunction.) The verbal and written reports shall be submitted pursuant to OAC rule 3745-15-06.

Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emission unit(s) that is (are) served by such control system(s).

## **3. Risk Management Plans**

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. 7401 et seq. ("Act"), the permittee shall comply with the requirement to register such a plan.

## **4. Title IV Provisions**

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

## **5. Severability Clause**

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition

**Honda of America Mfg., Inc.**  
**PTI Application: 01-05659**  
**Modification Issued: 12/16/2004**

**Facility ID: 0180000130**

declared invalid.

## **6. General Requirements**

- a. The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and reissuance, or modification, or for denial of a permit renewal application.
- b. It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.
- c. This permit may be modified, reopened, revoked, or revoked and reissued, for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.
- d. This permit does not convey any property rights of any sort, or any exclusive privilege.
- e. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

## **7. Fees**

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit To Install fees within 30 days after the issuance of this Permit To Install.

## **8. Federal and State Enforceability**

Only those terms and conditions designated in this permit as federally enforceable, that are

required under the Act, or any of its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA, the State, and citizens under the Act. All other terms and conditions of this permit shall not be federally enforceable and shall be enforceable under State law only.

## **9. Compliance Requirements**

- a. Any document (including reports) required to be submitted and required by a federally applicable requirement in this permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.
- b. Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:
  - i. At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.
  - ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with ORC section 3704.08.
  - iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.
  - iv. As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.
- c. The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually, or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:
  - i. Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
  - ii. An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

**10. Permit To Operate Application**

- a. If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).
- b. If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35, the source(s) identified in this Permit To Install is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the source(s) covered by this permit.

**11. Best Available Technology**

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

**12. Air Pollution Nuisance**

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

**Honda of America Mfg., Inc.**  
**PTI Application: 01-05659**  
**Modification Issued: 12/16/2004**

**Facility ID: 0180000130**

**B. State Only Enforceable Permit To Install General Terms and Conditions**

**1. Compliance Requirements**

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

**2. Reporting Requirements**

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping of state-only enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from state-only required emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

**3. Permit Transfers**

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

**4. Termination of Permit To Install**

This permit to install shall terminate within eighteen months of the effective date of the permit to install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete

**Honda of America Mfg., Inc.**  
**PTI Application: 01-05659**  
**Modification Issued: 12/16/2004**

**Facility ID: 0180000130**

within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

**5. Construction of New Sources(s)**

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

**6. Public Disclosure**

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

**7. Applicability**

**Honda of America Mfg., Inc.**

**Facility ID: 0180000130**

**PTI Application: 01-05659**

**Modification Issued: 12/16/2004**

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

**8. Construction Compliance Certification**

If applicable, the applicant shall provide Ohio EPA with a written certification (see enclosed form if applicable) that the facility has been constructed in accordance with the Permit To Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

**9. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations (See Section A of This Permit)**

If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.

**C. Permit To Install Summary of Allowable Emissions**

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

11

**Honda of America Mfg., Inc.**  
**PTI Application: 01-05659**  
**Modification Issued: 12/16/2004**

**Facility ID: 0180000130**

**Honda of America Mfg., Inc.**  
**PTI Application: 01-05659**  
**Modification Issued: 12/16/2004**

**Facility ID: 0180000130**

SUMMARY (for informational purposes only)  
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
OC	27.06

**Honda of America Mfg., Inc.**  
**PTI Application: 01-05659**  
**Modification Issued: 12/16/2004**

**Facility ID: 0180000130**

**Honda**

**PTI A**

**Modification Issued: 12/16/2004**

Emissions Unit ID: P003

**Part II - FACILITY SPECIFIC TERMS AND CONDITIONS**

**A. State and Federally Enforceable Permit To Install Facility Specific Terms and Conditions**

None

**B. State Only Enforceable Permit To Install Facility Specific Terms and Conditions**

None

**Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. State and Federally Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P003 - injection molding machine, F1 (modification)	OAC rule 3745-31-05(C)	3.94 tons of total OC per rolling, 12-month period from molding plastics on P003, P312 and P313 combined
		4.87 tons of total OC per rolling, 12-month period from mold release, mold cleaner, mold protectant, and cleaning solvents used on P003, P312 and P313 combined
		See Section A.II.1 thru A.II.4 below.
	OAC rule 3745-21-07(G)	OC emissions shall not exceed 8 pounds/hr and 40 pounds/day when using photochemically materials or materials.
		This emission unit is exempt from the emission limitation of OAC rule 3845-21-07(G)(2) when employing only non-photochemical reactive materials or material exempt under 3745-21-07(G)(9).

**2. Additional Terms and Conditions**

- 2.a To ensure federal enforceability during the first 12 calendar months of this permit, material usage records from the previous 12 calendar months of operation of P003, P312, and P313, and emissions calculated from these records, shall be used to document compliance with the rolling, 12-month emission and material usage limits. Therefore since the permittee has existing material usage records for this emissions unit, this emissions unit does not need to be restricted on a monthly basis during the first 12 calendar months of this permit.

- 2.b** The permittee shall maintain a label on this emissions unit which shall identify the machine. This identifying label shall be either the emission unit number assigned in this permit or the permittee's identification number, as described in the summary, found in Section A.I.1.

## II. Operational Restrictions

1. Material usage shall not exceed 1,476 gallons of mold release, mold cleaner, mold protectant, and cleaning solvents combined per rolling, 12-month period on molding machines P003, P312, and P313.
2. Material usage shall not exceed 13,140 tons of plastic molding pellets per rolling, 12 month period on molding machines P003, P312, and P313 combined.
3. The OC content of any mold release, mold protectant, mold cleaner, and cleaning solvent shall not exceed 7.05 lbs OC/gal.
4. The OC content of the plastic molding material shall not exceed 0.01 lb OC/lb of material.

## III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information on a monthly basis for P003, P312, and P313 combined:
  - a. the company identification for each mold release, mold cleaner, mold protectant, cleaning solvent, and polymer type of plastic pellets employed;
  - b. documentation on whether or not each mold release, mold cleaner, mold protectant, cleaning solvent, and polymer type of plastic pellets employed is photochemically reactive;
  - c. the total number of gallons of each mold release, mold cleaner, mold protectant, and cleaning solvent employed, in gallons/month;
  - d. the OC content of each mold release, mold cleaner, mold protectant, cleaning solvent, and polymer type of plastic pellets, in pounds/gallon or pounds/pound;
  - e. the calculated OC emissions from mold release, mold cleaner, mold protectant, cleaning solvent, and polymer type of plastic pellets;
  - f. the total amount of each polymer type of plastic pellets molded, in pounds *or tons*;

- g. the calculated OC emissions from plastic molding;
  - h. the rolling, 12-month summation of the total number of gallons of the mold release, mold cleaner, mold protectant, and cleaning solvent employed;
  - i. the rolling, 12-month summation of the total ~~pounds~~ **tons** of plastic pellets molded;
  - j. the calculated rolling, 12-month summation of total OC emissions from mold release, mold cleaner, mold protectant, and cleaning solvent employed, in tons; and
  - k. the calculated rolling, 12-month summation of total OC emissions from the molded plastic pellets, in tons.
2. The permittee shall collect and record the following information on a daily basis when employing photochemically reactive materials:
    - a. the number of gallons of each mold release, mold cleaner, mold protectant, and cleaning solvent employed in this emissions unit;
    - b. the OC content of each mold release, mold cleaner, mold protectant, cleaning solvent, and polymer type of plastic pellets employed in this emissions unit, in pounds/gallon or pounds/pound;
    - c. the total amount of each polymer type of plastic pellets molded, in pounds;
    - d. the calculated total OC emission rate for all mold release, mold cleaner, mold protectant, cleaning solvent, and molded plastic employed in this emissions unit, in pounds per day;
    - e. the total number of hours this emissions unit was in operation; and
    - f. the average hourly OC emission rate from all mold release, mold cleaner, mold protectant, cleaning solvent, and molded plastic employed in this emissions unit (i.e., (c)/(d)), in pounds per hour.

#### IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports which include the following information:

**Honda of America Mfg., Inc.**  
**PTI Application: 01-05650**  
**Modif**

**Facility ID: 0180000130**

Emissions Unit ID: P003

- a. for the days during which a photochemically reactive material was employed, an identification of each day during which the average hourly organic compound emissions from the mold release agents, cleaning and protectant agents, cleaning solvents, and molded plastic exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day;
- b. for the days during which a photochemically reactive material was employed, an identification of each day during which the organic compound emissions from the mold release agents, cleaning and protectant agents, cleaning solvents, and molded plastic exceeded 40 pounds per day, and the actual organic compound emissions for each such day;
- c. an identification of any monthly record showing OC emissions from the mold release, mold cleaner, mold protectant, and cleaning solvents exceeded 4.87 tons of OC per rolling, 12-month period from emissions units P003, P312, and P313 combined;
- d. an identification of any monthly record showing OC emissions from the molded plastic exceeded 3.94 tons of OC per rolling, 12-month period from emissions units P003, P312, and P313 combined;
- e. an identification of any rolling, 12-month summation record showing the total usage of mold release, mold cleaner, mold protectant, and cleaning solvents exceeded 1,476 gallons from emissions units P003, P312, and P313 combined;
- f. an identification of any rolling, 12-month summation record showing the total amount of plastic molded exceeded 13,140 tons from emissions units P003, P312, and P313 combined;
- g. an identification of any record showing the OC content of the mold release, mold protectant, mold cleaner, and/or cleaning solvent exceeded 7.05 lbs OC/gal; and
- h. an identification of any record showing the OC content of the plastic molding material exceeded 0.01 lb OC/lb of material.

These quarterly reports shall be submitted to the Ohio EPA, Central District Office in accordance with Part I, Section A.1.c. of the General Terms and Conditions.

2. The permittee shall submit annual reports by April 15th which specify the total OC emissions from this emissions unit for the previous calendar year. These emissions may be reported per machine, as an average of P003, P312, and P313, or may be included as a total of all machines. These reports may be satisfied by including this emissions unit in the submission of the annual Fee Emission Report due by April 15th of each year.

## **V. Testing Requirements**

1. Compliance with the emission limitations contained in this permit shall be determined in

accordance with the following methods:

a. Emission Limitations:

3.94 tons of OC/rolling, 12-month period from molding plastics on P003, P312, and P313 combined

4.87 tons of OC/per rolling, 12-month period from mold release, mold cleaner, mold protectant, and cleaning solvents used on P003, P312, and P313 combined

Applicable Compliance Method:

Compliance with these rolling 12-month limitations may be determined through the record keeping specified in Section A.III.1.j and 1.k above.

U.S. EPA Method 24 or formulation data for the mold release, mold cleaner, mold protectant, cleaning solvents, and molded plastic shall be used to determine the OC content of the materials to be used in the calculation of emissions.

b. Usage Limitation:

1,476 gallons of mold release, mold cleaner, mold protectant, and cleaning solvents combined per rolling, 12-month period from P003, P312, and P313

Applicable Compliance Determination:

Compliance may be determined by the record keeping specified in Section A.III.1.h above.

c. Usage Limitation:

13,140 tons of plastic pellets molded per rolling, 12-month period from P003, P312, and P313 combined

Applicable Compliance Determination:

Compliance may be determined by the record keeping specified in Section A.III.1.i above.

d. Emission Limitations:

8 pounds OC/hr and 40 pounds OC/day when using photochemically materials

Applicable Compliance Determination:

Compliance may be determined by the record keeping specified in Sections A.III.2.d and 2.f above.

e. Emission Limitation:

**Honda of America Mfg., Inc.**

**PTI Application: 01-05650**

**Modif**

**Facility ID: 0180000130**

Emissions Unit ID: P003

7.05 lbs OC/gal of any mold release, mold protectant, mold cleaner, and cleaning solvent  
0.01 lb OC/lb of material of the plastic molding material

Applicable Compliance Method:

Compliance may be determined by the record keeping specified in Section A.III.1.d above.

**VI. Miscellaneous Requirements**

None

Honda

PTI A

Modification Issued: 12/16/2004

Emissions Unit ID: P003

**B. State Only Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P003 - injection molding machine, F1	Ohio Air Toxic Policy	None

**2. Additional Terms and Conditions**

2.a None

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

1. The permit to install for emissions units P003 was evaluated based on actual materials (typically coatings and cleanup materials) and the design parameters of the emission unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by these emissions units using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA-approved model). The predicted 1-hour maximum ground level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutants:

Pollutant: Isopropanol

TLV (ug/m3): 492,000

Maximum Hourly Emission Rate (lbs/hr): ~~5.95~~ **24.0 (from 7 injection machines)**

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): ~~483~~ **870**

MAGLC (ug/m3): 11,703

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change..

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

**Honda of America Mfg., Inc.**  
**PTI Application: 01 05650**  
**Modif**

**Facility ID: 0180000130**

Emissions Unit ID: P003

- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None

Honda

PTI A

Modification Issued: 12/16/2004

Emissions Unit ID: P312

**Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. State and Federally Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P312 - injection molding machine, HPM 2	OAC rule 3745-31-05(C)	3.94 tons of total OC per rolling, 12-month period from molding plastics on P003, P312 and P313 combined  4.87 tons of total OC per rolling, 12-month period from mold release, mold cleaner, mold protectant, and cleaning solvents used on P003, P312 and P313 combined
	OAC rule 3745-21-07(G)	See Section A.II.1 thru A.II.4 below.  OC emissions shall not exceed 8 pounds/hr and 40 pounds/day when using photochemically reactive materials  This emission unit is exempt from the emission limitation of OAC rule 3845-21-07(G)(2) when employing only non-photochemical reactive materials or material exempt under 3745-21-07(G)(9).

**2. Additional Terms and Conditions**

- 2.a To ensure federal enforceability during the first 12 calendar months of this permit, material

**Honda****PTI A****Modification Issued: 12/16/2004**

Emissions Unit ID: P312

usage records from the previous 12 calendar months of operation of P003, P312, and P313, and emissions calculated from these records, shall be used to document compliance with the rolling, 12-month emission and material usage limits. Therefore since the permittee has existing material usage records for this emissions unit, this emissions unit does not need to be restricted on a monthly basis during the first 12 calendar months of this permit.

- 2.b** The permittee shall maintain a label on this emissions unit which shall identify the machine. This identifying label shall be either the emission unit number assigned in this permit or the permittee's identification number, as described in the summary, found in Section A.I.1.

## **II. Operational Restrictions**

1. Material usage shall not exceed 1,476 gallons of mold release, mold cleaner, mold protectant, and cleaning solvents combined per rolling, 12-month period on molding machines P003, P312, and P313.
2. Material usage shall not exceed 13,140 tons of plastic molding pellets per rolling, 12 month period on molding machines P003, P312, and P313 combined.
3. The OC content of any mold release, mold protectant, mold cleaner, and cleaning solvent shall not exceed 7.05 lbs OC/gal.
4. The OC content of the plastic molding material shall not exceed 0.01 lb OC/lb of material.

## **III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information on a monthly basis for P003, P312, and P313 combined:
  - a. the company identification for each mold release, mold cleaner, mold protectant, cleaning solvent, and polymer type of plastic pellets employed;
  - b. documentation on whether or not each mold release, mold cleaner, mold protectant, cleaning solvent, and polymer type of plastic pellets employed is photochemically reactive;
  - c. the total number of gallons of each mold release, mold cleaner, mold protectant, and cleaning solvent employed, in gallons/month;
  - d. the OC content of each mold release, mold cleaner, mold protectant, cleaning solvent, and

Emissions Unit ID: P312

- polymer type of plastic pellets, in pounds/gallon or pounds/pound;
- e. the calculated OC emissions from mold release, mold cleaner, mold protectant, cleaning solvent, and polymer type of plastic pellets;
  - f. the total amount of each polymer type of plastic pellets molded, in pounds *or tons*;
  - g. the calculated OC emissions from plastic molding;
  - h. the rolling, 12-month summation of the total number of gallons of the mold release, mold cleaner, mold protectant, and cleaning solvent employed;
  - i. the rolling, 12-month summation of the total ~~pounds~~ *tons* of plastic pellets molded;
  - j. the calculated rolling, 12-month summation of total OC emissions from mold release, mold cleaner, mold protectant, and cleaning solvent employed, in tons; and
  - k. the calculated rolling, 12-month summation of total OC emissions from the molded plastic pellets, in tons.
2. The permittee shall collect and record the following information on a daily basis when employing photochemically reactive materials:
    - a. the number of gallons of each mold release, mold cleaner, mold protectant, and cleaning solvent employed in this emissions unit;
    - b. the OC content of each mold release, mold cleaner, mold protectant, cleaning solvent, and polymer type of plastic pellets employed in this emissions unit, in pounds/gallon or pounds/pound;
    - c. the total amount of each polymer type of plastic pellets molded, in pounds;
    - d. the calculated total OC emission rate for all mold release, mold cleaner, mold protectant, cleaning solvent, and molded plastic employed in this emissions unit, in pounds per day;
    - e. the total number of hours this emissions unit was in operation; and
    - f. the average hourly OC emission rate from all mold release, mold cleaner, mold protectant, cleaning solvent, and molded plastic employed in this emissions unit (i.e., (c)/(d)), in pounds per hour.

#### IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports which include the following information:

**Honda****PTI A****Modification Issued: 12/16/2004**

Emissions Unit ID: P312

- a. for the days during which a photochemically reactive material was employed, an identification of each day during which the average hourly organic compound emissions from the mold release agents, cleaning and protectant agents, cleaning solvents, and molded plastic exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day;
- b. for the days during which a photochemically reactive material was employed, an identification of each day during which the organic compound emissions from the mold release agents, cleaning and protectant agents, cleaning solvents, and molded plastic exceeded 40 pounds per day, and the actual organic compound emissions for each such day;
- c. an identification of any monthly record showing OC emissions from the mold release, mold cleaner, mold protectant, and cleaning solvents exceeded 4.87 tons of OC per rolling, 12-month period from emissions units P003, P312, and P313 combined;
- d. an identification of any monthly record showing OC emissions from the molded plastic exceeded 3.94 tons of OC per rolling, 12-month period from emissions units P003, P312, and P313 combined;
- e. an identification of any rolling, 12-month summation record showing the total usage of mold release, mold cleaner, mold protectant, and cleaning solvents exceeded 1,476 gallons from emissions units P003, P312, and P313 combined;
- f. an identification of any rolling, 12-month summation record showing the total amount of plastic molded exceeded 13,140 tons from emissions units P003, P312, and P313 combined;
- g. an identification of any record showing the OC content of the mold release, mold protectant, mold cleaner, and/or cleaning solvent exceeded 7.05 lbs OC/gal; and
- h. an identification of any record showing the OC content of the plastic molding material exceeded 0.01 lb OC/lb of material.

These quarterly reports shall be submitted to the Ohio EPA, Central District Office in accordance with Part I, Section A.1.c. of the General Terms and Conditions.

2. The permittee shall submit annual reports by April 15th which specify the total OC emissions from this emissions unit for the previous calendar year. These emissions may be reported per machine, as an average of P003, P312, and P313, or may be included as a total of all

Emissions Unit ID: P312

machines. These reports may be satisfied by including this emissions unit in the submission of the annual Fee Emission Report due by April 15th of each year.

## **V. Testing Requirements**

1. Compliance with the emission limitations contained in this permit shall be determined in accordance with the following methods:

- a. Emission Limitations:

3.94 tons of OC/rolling, 12-month period from molding plastics on P003, P312, and P313 combined

4.87 tons of OC/per rolling, 12-month period from mold release, mold cleaner, mold protectant, and cleaning solvents used on P003, P312, and P313 combined

**Applicable Compliance Method:**

Compliance with these rolling 12-month limitations may be determined through the record keeping specified in Section A.III.1.j and 1.k above.

U.S. EPA Method 24 or formulation data for the mold release, mold cleaner, mold protectant, cleaning solvents, and molded plastic shall be used to determine the OC content of the materials to be used in the calculation of emissions.

- b. Usage Limitation:

1,476 gallons of mold release, mold cleaner, mold protectant, and cleaning solvents combined per rolling, 12-month period from P003, P312, and P313

**Applicable Compliance Determination:**

Compliance may be determined by the record keeping specified in Section A.III.1.h above.

- c. Usage Limitation:

13,140 tons of plastic pellets molded per rolling, 12-month period from P003, P312, and P313 combined

**Applicable Compliance Determination:**

Compliance may be determined by the record keeping specified in Section A.III.1.i above.

- d. Emission Limitations:

8 pounds OC/hr and 40 pounds OC/day when using photochemically reactive materials

**Applicable Compliance Determination:**

Compliance may be determined by the record keeping specified in Sections A.III.2.d and 2.f above.

- e. Emission Limitation:

**Honda**

**PTI A**

**Modification Issued: 12/16/2004**

Emissions Unit ID: P312

7.05 lbs OC/gal of any mold release, mold protectant, mold cleaner, and cleaning solvent  
0.01 lb OC/lb of material of the plastic molding material

Applicable Compliance Method:

Compliance may be determined by the record keeping specified in Section A.III.1.d above.

**VI. Miscellaneous Requirements**

None

Honda

PTI A

Modification Issued: 12/16/2004

Emissions Unit ID: P312

**B. State Only Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P312 - injection molding machine, HPM 2	Ohio Air Toxic Policy	None

**2. Additional Terms and Conditions**

2.a None

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

1. The permit to install for emissions units P312 was evaluated based on actual materials (typically coatings and cleanup materials) and the design parameters of the emission unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by these emissions units using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA-approved model). The predicted 1-hour maximum ground level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutants:

Pollutant: Isopropanol

TLV (ug/m3): 492,000

Maximum Hourly Emission Rate (lbs/hr): ~~5.95~~ **24.0 (from 7 injection machines)**Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): ~~483~~ **870**

MAGLC (ug/m3): 11,703

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change..

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

#### **IV. Reporting Requirements**

None

32

**Honda**

**PTI A**

**Modification Issued: 12/16/2004**

Emissions Unit ID: P312

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None

**Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. State and Federally Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P313 - injection molding machine, HPM 3	OAC rule 3745-31-05(C)	3.94 tons of total OC per rolling, 12-month period from molding plastics on P003, P312 and P313 combined
	OAC rule 3745-21-07(G)	4.87 tons of total OC per rolling, 12-month period from mold release, mold cleaner, mold protectant, and cleaning solvents used on P003, P312 and P313 combined
		See Section A.II.1 thru A.II.4 below.
		OC emissions shall not exceed 8 pounds/hr and 40 pounds/day when using photochemically reactive materials
		This emission unit is exempt from the emission limitation of OAC rule 3845-21-07(G)(2) when employing only non-photochemical reactive materials or material exempt under 3745-21-07(G)(9).

**2. Additional Terms and Conditions**

- 2.a To ensure federal enforceability during the first 12 calendar months of this permit, material usage records from the previous 12 calendar months of operation of P003, P312, and P313, and emissions calculated from these records, shall be used to document compliance with the rolling, 12-month emission and material usage limits. Therefore since the permittee has existing material usage records for this emissions unit, this emissions unit does not need to be restricted on a monthly basis during the first 12 calendar months of this permit.

- 2.b** The permittee shall maintain a label on this emissions unit which shall identify the machine. This identifying label shall be either the emission unit number assigned in this permit or the permittee's identification number, as described in the summary, found in Section A.I.1.

## II. Operational Restrictions

1. Material usage shall not exceed 1,476 gallons of mold release, mold cleaner, mold protectant, and cleaning solvents combined per rolling, 12-month period on molding machines P003, P312, and P313.
2. Material usage shall not exceed 13,140 tons of plastic molding pellets per rolling, 12 month period on molding machines P003, P312, and P313 combined.
3. The OC content of any mold release, mold protectant, mold cleaner, and cleaning solvent shall not exceed 7.05 lbs OC/gal.
4. The OC content of the plastic molding material shall not exceed 0.01 lb OC/lb of material.

## III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information on a monthly basis for P003, P312, and P313 combined:
  - a. the company identification for each mold release, mold cleaner, mold protectant, cleaning solvent, and polymer type of plastic pellets employed;
  - b. documentation on whether or not each mold release, mold cleaner, mold protectant, cleaning solvent, and polymer type of plastic pellets employed is photochemically reactive;
  - c. the total number of gallons of each mold release, mold cleaner, mold protectant, and cleaning solvent employed, in gallons/month;
  - d. the OC content of each mold release, mold cleaner, mold protectant, cleaning solvent, and polymer type of plastic pellets, in pounds/gallon or pounds/pound;
  - e. the calculated OC emissions from mold release, mold cleaner, mold protectant, cleaning solvent, and polymer type of plastic pellets;
  - f. the total amount of each polymer type of plastic pellets molded, in pounds *or tons*;

- g. the calculated OC emissions from plastic molding;
  - h. the rolling, 12-month summation of the total number of gallons of the mold release, mold cleaner, mold protectant, and cleaning solvent employed;
  - i. the rolling, 12-month summation of the total ~~pounds~~ **tons** of plastic pellets molded;
  - j. the calculated rolling, 12-month summation of total OC emissions from mold release, mold cleaner, mold protectant, and cleaning solvent employed, in tons; and
  - k. the calculated rolling, 12-month summation of total OC emissions from the molded plastic pellets, in tons.
2. The permittee shall collect and record the following information on a daily basis when employing photochemically reactive materials:
    - a. the number of gallons of each mold release, mold cleaner, mold protectant, and cleaning solvent employed in this emissions unit;
    - b. the OC content of each mold release, mold cleaner, mold protectant, cleaning solvent, and polymer type of plastic pellets employed in this emissions unit, in pounds/gallon or pounds/pound;
    - c. the total amount of each polymer type of plastic pellets molded, in pounds;
    - d. the calculated total OC emission rate for all mold release, mold cleaner, mold protectant, cleaning solvent, and molded plastic employed in this emissions unit, in pounds per day;
    - e. the total number of hours this emissions unit was in operation; and
    - f. the average hourly OC emission rate from all mold release, mold cleaner, mold protectant, cleaning solvent, and molded plastic employed in this emissions unit (i.e., (c)/(d)), in pounds per hour.

#### IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports which include the following information:

**Honda of America Mfg., Inc.**  
**PTI Application: 01-05650**  
**Modif**

**Facility ID: 0180000130**

Emissions Unit ID: P313

- a. for the days during which a photochemically reactive material was employed, an identification of each day during which the average hourly organic compound emissions from the mold release agents, cleaning and protectant agents, cleaning solvents, and molded plastic exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day;
- b. for the days during which a photochemically reactive material was employed, an identification of each day during which the organic compound emissions from the mold release agents, cleaning and protectant agents, cleaning solvents, and molded plastic exceeded 40 pounds per day, and the actual organic compound emissions for each such day;
- c. an identification of any monthly record showing OC emissions from the mold release, mold cleaner, mold protectant, and cleaning solvents exceeded 4.87 tons of OC per rolling, 12-month period from emissions units P003, P312, and P313 combined;
- d. an identification of any monthly record showing OC emissions from the molded plastic exceeded 3.94 tons of OC per rolling, 12-month period from emissions units P003, P312, and P313 combined;
- e. an identification of any rolling, 12-month summation record showing the total usage of mold release, mold cleaner, mold protectant, and cleaning solvents exceeded 1,476 gallons from emissions units P003, P312, and P313 combined;
- f. an identification of any rolling, 12-month summation record showing the total amount of plastic molded exceeded 13,140 tons from emissions units P003, P312, and P313 combined;
- g. an identification of any record showing the OC content of the mold release, mold protectant, mold cleaner, and/or cleaning solvent exceeded 7.05 lbs OC/gal; and
- h. an identification of any record showing the OC content of the plastic molding material exceeded 0.01 lb OC/lb of material.

These quarterly reports shall be submitted to the Ohio EPA, Central District Office in accordance with Part I, Section A.1.c. of the General Terms and Conditions.

2. The permittee shall submit annual reports by April 15th which specify the total OC emissions from this emissions unit for the previous calendar year. These emissions may be reported per machine, as an average of P003, P312, and P313, or may be included as a total of all machines. These reports may be satisfied by including this emissions unit in the submission of the annual Fee Emission Report due by April 15th of each year.

## **V. Testing Requirements**

1. Compliance with the emission limitations contained in this permit shall be determined in

accordance with the following methods:

a. Emission Limitations:

3.94 tons of OC/rolling, 12-month period from molding plastics on P003, P312, and P313 combined

4.87 tons of OC/per rolling, 12-month period from mold release, mold cleaner, mold protectant, and cleaning solvents used on P003, P312, and P313 combined

Applicable Compliance Method:

Compliance with these rolling 12-month limitations may be determined through the record keeping specified in Section A.III.1.j and 1.k above.

U.S. EPA Method 24 or formulation data for the mold release, mold cleaner, mold protectant, cleaning solvents, and molded plastic shall be used to determine the OC content of the materials to be used in the calculation of emissions.

b. Usage Limitation:

1,476 gallons of mold release, mold cleaner, mold protectant, and cleaning solvents combined per rolling, 12-month period from P003, P312, and P313

Applicable Compliance Determination:

Compliance may be determined by the record keeping specified in Section A.III.1.h above.

c. Usage Limitation:

13,140 tons of plastic pellets molded per rolling, 12-month period from P003, P312, and P313 combined

Applicable Compliance Determination:

Compliance may be determined by the record keeping specified in Section A.III.1.i above.

d. Emission Limitations:

8 pounds OC/hr and 40 pounds OC/day when using photochemically reactive materials

Applicable Compliance Determination:

Compliance may be determined by the record keeping specified in Sections A.III.2.d and 2.f above.

e. Emission Limitation:

**Honda of America Mfg., Inc.**

**PTI Application: 01-05650**

**Modif**

**Facility ID: 0180000130**

Emissions Unit ID: P313

7.05 lbs OC/gal of any mold release, mold protectant, mold cleaner, and cleaning solvent  
0.01 lb OC/lb of material of the plastic molding material

Applicable Compliance Method:

Compliance may be determined by the record keeping specified in Section A.III.1.d above.

**VI. Miscellaneous Requirements**

None

Honda

PTI A

Modification Issued: 12/16/2004

Emissions Unit ID: P313

**B. State Only Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P313 - injection molding machine, HPM 3	Ohio Air Toxic Policy	None

**2. Additional Terms and Conditions**

2.a None

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

1. The permit to install for emissions units P313 was evaluated based on actual materials (typically coatings and cleanup materials) and the design parameters of the emission unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by these emissions units using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA-approved model). The predicted 1-hour maximum ground level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutants:

Pollutant: Isopropanol

TLV (ug/m3): 492,000

Maximum Hourly Emission Rate (lbs/hr): ~~5.95~~ **24.0 (from 7 injection machines)**Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): ~~483~~ **870**

MAGLC (ug/m3): 11,703

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change..

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None

Honda

PTI A

Modification Issued: 12/16/2004

Emissions Unit ID: P315

**Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. State and Federally Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P315 - injection molding machine, HPM 6	OAC rule 3745-31-05(A)(3)	Organic compound (OC) emissions shall not exceed 56.0 pounds/hour from emissions units P315, P336, P333, P318, P319, P332, and P345 combined.
		The requirements of this rule also include compliance with the requirements of OAC rules 3745-21-07(G)(2) and 3745-31-05(C).
	OAC rule 3745-31-05(C)	OC emissions shall not exceed 11.65 tons per rolling, 12-month period from molding plastics on P315, P336, P333, P318, P319, P332, and P345 combined.
		OC emissions shall not exceed 6.60 tons per rolling, 12-month period from mold release, mold cleaner, mold protectant, and cleaning solvents used on P315, P336, P333, P318, P319, P332, and P345 combined.
		See Section A.II.1 thru A.II.4 below.
	OAC rule 3745-21-07(G)	OC emissions shall not exceed 8 pounds/hr and 40 pounds/day when using photochemically materials.

**Honda****PTI A****Modification Issued: 12/16/2004**

Emissions Unit ID: P315

This emission unit is exempt from the emission limitation of OAC rule 3845-21-07(G)(2) when employing only non-photochemical reactive materials or material exempt under 3745-21-07(G)(9).

## 2. Additional Terms and Conditions

- 2.a** The hourly OC limit of 56.0 lbs OC/hr for molding machines P315, P336, P333, P318, P319, P332, and P345 is greater than the hourly potential to emit for each molding machine. Therefore no additional monitoring, record keeping, or reporting is necessary to determine compliance with this limit.
- 2.b** To ensure federal enforceability during the first 12 calendar months of this permit, material usage records from the previous 12 calendar months of operation of P315, P336, P333, P318, P319, P332, and P345 and emissions calculated from these records, shall be used to document compliance with the rolling, 12-month emission and material usage limits. Therefore since the permittee has existing material usage records for this emissions unit, this emissions unit does not need to be restricted on a monthly basis during the first 12 calendar months of this permit.
- 2.c** The permittee shall maintain a label on this emissions unit which shall identify the machine. This identifying label shall be either the emission unit number assigned in this permit or the permittee's identification number, as described in the summary, found in Section A.I.1.

## II. Operational Restrictions

1. Material usage shall not exceed 2,000 gallons of mold release, mold cleaner, mold protectant, and cleaning solvents combined per rolling, 12-month period on molding machines P315, P336, P333, P318, P319, P332, and P345.
2. Material usage shall not exceed 38,829 tons of plastic molding pellets per rolling, 12 month period on molding machines P315, P336, P333, P318, P319, P332, and P345 combined.
3. The OC content of any mold release, mold protectant, mold cleaner, and cleaning solvent shall not exceed 7.05 lbs OC/gal.

4. The OC content of the plastic molding material shall not exceed 0.01 lb OC/lb of material.

### III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information on a monthly basis for P315, P336, P333, P318, P319, P332, and P345 combined:
  - a. the company identification for each mold release, mold cleaner, mold protectant, cleaning solvent, and polymer type of plastic pellets employed;
  - b. documentation on whether or not each mold release, mold cleaner, mold protectant, cleaning solvent, and polymer type of plastic pellets employed is photochemically reactive;
  - c. the total number of gallons of each mold release, mold cleaner, mold protectant, and cleaning solvent employed, in gallons/month;
  - d. the OC content of each mold release, mold cleaner, mold protectant, cleaning solvent, and polymer type of plastic pellets, in pounds/gallon or pounds/pound;
  - e. the calculated OC emissions from mold release, mold cleaner, mold protectant, cleaning solvent, and polymer type of plastic pellets;
  - f. the total amount of each polymer type of plastic pellets molded, in pounds *or tons*;
  - g. the calculated OC emissions from plastic molding;
  - h. the rolling, 12-month summation of the total number of gallons of the mold release, mold cleaner, mold protectant, and cleaning solvent employed;
  - i. the rolling, 12-month summation of the total pounds *or tons* of plastic pellets molded;
  - j. the calculated rolling, 12-month summation of total OC emissions from mold release, mold cleaner, mold protectant, and cleaning solvent employed, in tons; and
  - k. the calculated rolling, 12-month summation of total OC emissions from the molded plastic pellets, in tons.
2. The permittee shall collect and record the following information on a daily basis when employing photochemically reactive materials:
  - a. the number of gallons of each mold release, mold cleaner, mold protectant, and cleaning solvent employed in this emissions unit;
  - b. the OC content of each mold release, mold cleaner, mold protectant, cleaning solvent, and polymer type of plastic pellets employed in this emissions unit, in pounds/gallon or

pounds/pound;

- c. the total amount of each polymer type of plastic pellets molded, in pounds;
- d. the calculated total OC emission rate for all mold release, mold cleaner, mold protectant, cleaning solvent, and molded plastic employed in this emissions unit, in pounds per day;
- e. the total number of hours this emissions unit was in operation; and
- f. the average hourly OC emission rate from all mold release, mold cleaner, mold protectant, cleaning solvent, and molded plastic employed in this emissions unit (i.e., (c)/(d)), in pounds per hour.

#### IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports which include the following information:
  - a. for the days during which a photochemically reactive material was employed, an identification of each day during which the average hourly organic compound emissions from the mold release agents, cleaning and protectant agents, cleaning solvents, and molded plastic exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day;
  - b. for the days during which a photochemically reactive material was employed, an identification of each day during which the organic compound emissions from the mold release agents, cleaning and protectant agents, cleaning solvents, and molded plastic exceeded 40 pounds per day, and the actual organic compound emissions for each such day;
  - c. an identification of any monthly record showing OC emissions from the mold release, mold cleaner, mold protectant, and cleaning solvents exceeded 6.60 tons of OC per rolling, 12-month period from emissions units P315, P336, P333, P318, P319, P332, and P345 combined;
  - d. an identification of any monthly record showing OC emissions from the molded plastic exceeded 11.65 tons of OC per rolling, 12-month period from emissions units P315, P336, P333, P318, P319, P332, and P345 combined;
  - e. an identification of any rolling, 12-month summation record showing the total usage of

**Honda of America Mfg., Inc.**  
**PTI Application: 01-05650**  
**Modif**

**Facility ID: 0180000130**

Emissions Unit ID: P315

mold release, mold cleaner, mold protectant, and cleaning solvents exceeded 2,000 gallons from emissions units P315, P336, P333, P318, P319, P332, and P345 combined; and

- f. an identification of any rolling, 12-month summation record showing the total amount of plastic molded exceeded 38,829 tons from emissions units P315, P336, P333, P318, P319, P332, and P345 combined.
- g. an identification of any record showing the OC content of the mold release, mold protectant, mold cleaner, and/or cleaning solvent exceeded 7.05 lbs OC/gal; and
- h. an identification of any record showing the OC content of the plastic molding material exceeded 0.01 lb OC/lb of material.

These quarterly reports shall be submitted to the Ohio EPA, Central District Office in accordance with Part I, Section A.1.c. of the General Terms and Conditions.

2. The permittee shall submit annual reports which specify the total OC emissions from this emissions unit for the previous calendar year. These emissions may be reported per machine, as an average of P315, P336, P333, P318, P319, P332, and P345, or may be included as a total of all machines. These reports may be satisfied by including this emissions unit in the submission of the annual Fee Emission Report due by April 15th of each year.

## **V. Testing Requirements**

1. Compliance with the emission limitations contained in this permit shall be determined in accordance with the following methods:

- a. Emission Limitations:

11.65 tons of OC/rolling, 12-month period from molding plastics on P315, P336, P333, P318, P319, P332, and P345 combined.

6.60 tons of OC per rolling, 12-month period from mold release, mold cleaner, mold protectant, and cleaning solvents used on P315, P336, P333, P318, P319, P332, and P345 combined.

Applicable Compliance Method:

Compliance with these rolling 12-month limitations may be determined through the record keeping specified in Section A.III.1.j and 1.k above.

U.S. EPA Method 24 or formulation data for the mold release, mold cleaner, mold protectant, cleaning solvents, and molded plastic shall be used to determine the OC content of the materials to be used in the calculation of emissions.

- b. Usage Limitation:

2,000 gallons of mold release, mold cleaner, mold protectant, and cleaning solvents

Honda

PTI A

Modification Issued: 12/16/2004

Emissions Unit ID: P315

combined per rolling, 12-month period from P315, P336, P333, P318, P319, P332, and P345.

Applicable Compliance Determination:

Compliance may be determined by the record keeping specified in Section A.III.1.h above.

c. Usage Limitation:

38,829 tons of plastic pellets molded per rolling, 12-month period from P315, P336, P333, P318, P319, P332, and P345 combined.

Applicable Compliance Determination:

Compliance may be determined by the record keeping specified in Section A.III.1.i above.

d. Emission Limitations:

8 pounds OC/hr and 40 pounds OC/day when using photochemically reactive mold materials

Applicable Compliance Determination:

Compliance may be determined by the record keeping specified in Sections A.III.2.d and 2.f above.

e. Emission Limitation:

OC emissions shall not exceed 56.0 lbs/hr for molding machines P315, P336, P333, P318, P319, P332, and P345 combined.

Applicable Compliance Method:

56.0 pounds of OC/hour is more than the potential to emit for the operations P315, P336, P333, P318, P319, P332, and P345. The following calculations shall be maintained on file and shall document the potential to emit for the emissions units contained in this permit:

Isopropanol (IPA):

$1.6 \text{ grams/pump} \times 7 \text{ pumps*/bumper} \times 55 \text{ bumpers/hr} \times 0.002205 \text{ lbs/gram} \times 50\% \text{ IPA} = 0.68 \text{ lb IPA/hr per machine}$

$0.68 \text{ lbs IPA/hr} \times 7 \text{ machines} = 4.76 \text{ lbs IPA/hr for all 7 machines}$

Mold Agents:

$1.49 \text{ grams/sec} \times 60 \text{ sec/min} \times 10 \text{ min/use} \times 0.002205 \text{ lb/gram} \times 2 \text{ mold changes/hr} = 3.94 \text{ lbs petro/hr per machine}$

**Honda of America Mfg., Inc.**  
**PTI Application: 01 05650**  
**Modif**

**Facility ID: 0180000130**

Emissions Unit ID: P315

3.94 lbs petro/hr per machine x (7 machines + 1 mold in maintenance) = 31.52 lbs petro/hr for all 7 machines + 1 mold in maintenance.

Plastic Molding:

2160 lbs pellets/hr x emission factor of 3% from AP-42, Fifth Edition, Table 4.4-2, 9/88\* x 1% OC content= 0.648 lb OC/hr per machine

0.648 lb/hr OC x 7 machines= 4.54 lbs OC/hr for all 7 machines

Total OC emission: 4.76 lbs OC/hr from IPA + 31.52 lbs OC/hr from cleaning mold + 4.54 lbs OC from molding = 40.82 lbs OC/hr from all 7 machines + 1 mold in maintenance.

\* On March 18, 1998, this section of AP-42 was temporarily removed because of an inconsistency with the emission factors for open molding processes. U.S. EPA has stated that the emission factors for the closed molding operations listed in Table 4.4-2 are still valid. This emission factor reflects the total weight percentage of the inputted resin emitted during closed molding operations. The total OC emissions are dependent on the OC content of the plastic material.

- f. Emission Limitation:  
 7.05 lbs OC/gal of any mold release, mold protectant, mold cleaner, and cleaning solvent  
 0.01 lb OC/lb of material of the plastic molding material

Applicable Compliance Method:

Compliance may be determined by the record keeping specified in Section A.III.1.d above.

**VI. Miscellaneous Requirements**

None

**Honda  
PTI A**

Emissions Unit ID: P315

**Modification Issued: 12/16/2004**

**B. State Only Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P315 - injection molding machine, HPM 6	Ohio Air Toxic Policy	None

**2. Additional Terms and Conditions**

**2.a** None

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

1. The permit to install for this emissions unit was evaluated based on actual materials (typically coatings and cleanup materials) and the design parameters of the emission unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by these emissions units using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA-approved model). The predicted 1-hour maximum ground level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutants:

Pollutant: Isopropanol  
 TLV (ug/m3): 492,000  
 Maximum Hourly Emission Rate (lbs/hr): 56.0 (from 7 machines combined)  
 Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): ~~44043~~ **4,546**

**Honda of America Mfg., Inc.**  
**PTI Application: 01-05650**  
**Modif**

**Facility ID: 0180000130**

Emissions Unit ID: P315

MAGLC (ug/m3): 11,703

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

#### **IV. Reporting Requirements**

None

51

**Honda**

**PTI A**

**Modification Issued: 12/16/2004**

Emissions Unit ID: P315

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None