



Environmental
Protection Agency

Ted Strickland, Governor
Lee Fisher, Lt. Governor
Chris Korleski, Director

10/14/2010

Certified Mail

Robert Brennan
Core Composites Cincinnati, LLC
4174 Half Acre Rd
Batavia, OH 45103-4174

Facility ID: 1413020248
Permit Number: P0104748
County: Clermont

RE: DRAFT AIR POLLUTION TITLE V PERMIT
Permit Type: Renewal

Dear Permit Holder:

A draft of the OAC Chapter 3745-77 Title V permit for the referenced facility has been issued. The purpose of this draft is to solicit public comments. A public notice will appear in the Ohio EPA Weekly Review and the local newspaper, The Clermont Sun. A copy of the public notice, the Statement of Basis, and the draft permit are enclosed. This permit can be accessed electronically on the Division of Air Pollution Control (DAPC) Web page, www.epa.ohio.gov/dapc by clicking the "Issued Air Pollution Control Permits" link. Comments will be accepted as a marked-up copy of the draft permit or in narrative format. Any comments must be sent to the following:

Andrew Hall
Permit Review/Development Section
Ohio EPA, DAPC
122 South Front Street
Columbus, Ohio 43215

and Hamilton County Dept. of Environmental Services
250 William Howard Taft Pkwy.
Cincinnati, OH 45219-2660

Comments and/or a request for a public hearing will be accepted within 30 days of the date the notice is published in the newspaper. You will be notified in writing if a public hearing is scheduled. A decision on processing the Title V permit will be made after consideration of comments received and oral testimony if a public hearing is conducted. You will then be provided with a Preliminary Proposed Title V permit and another opportunity to comment prior to the 45-day Proposed Title V permit submittal to U.S. EPA Region 5. The permit will be issued final after U.S. EPA review is completed and no objections to the final issuance have been received. If you have any questions, please contact Hamilton County Dept. of Environmental Services at (513)946-7777.

Sincerely,


Michael W. Ahern, Manager
Permit Issuance and Data Management Section, DAPC

Cc: U.S. EPA Region 5 - *Via E-Mail Notification*
HCDOES; Indiana; Kentucky



Statement of Basis For Air Pollution Title V Permit

Facility ID:	1413020248
Facility Name:	Core Composites Cincinnati, LLC
Facility Description:	Manufacturer of custom fiber glass products.
Facility Address:	4174 Half Acre Road, Batavia, OH 45103
Permit #:	P0104748, Renewal
This facility is subject to Title V because it is major for: <input type="checkbox"/> Lead <input type="checkbox"/> Sulfur Dioxide <input type="checkbox"/> Carbon Monoxide <input type="checkbox"/> Volatile Organic Compounds <input type="checkbox"/> Nitrogen Oxides <input type="checkbox"/> Particulate Matter ≤ 10 microns <input checked="" type="checkbox"/> Single Hazardous Air Pollutant <input type="checkbox"/> Combined Hazardous Air Pollutants <input type="checkbox"/> Maximum Available Control Technology Standard(s)	

A. Standard Terms and Conditions

Has each insignificant emissions unit been reviewed to confirm it meets the definition in OAC rule 3745-77-01 (U)?	Yes
Were there any "common control" issues associated with this facility? If yes, provide a summary of those issues and explain how the DAPC decided to resolve them.	No
Please identify the affected unit(s) and associated PTI, if applicable, along with a brief description of any changes to the permit document that qualify as a minor permit modification per OAC rule 3745-77-08(C)(1)	N/A
Please identify the affected unit(s) and associated PTI, if applicable, along with a brief description of any changes to the permit document that qualify as a significant permit modification per OAC rule 3745-77-08(C)(3)	N/A



Please identify the affected unit(s) and associated PTI, if applicable, along with a brief description of any changes to the permit document that qualify as a reopening per OAC rule 3745-77-08(D)	N/A
Please identify the affected unit(s) and associated PTI, if applicable, along with a brief description of any changes to the permit document resulting from a renewal per OAC rule 3745-77-08(E)	N/A

B. Facility-Wide Terms and Conditions

Term and Condition (paragraph)	Basis		<u>Comments</u>
	SIP (3745-)	Other	

C. Emissions Unit Terms and Conditions

<p>Key: EU = emissions unit ID ND = negative declaration (i.e., term that indicates that a particular rule(s) is (are) not applicable to a specific emissions unit) OR = operational restriction M = monitoring requirements St = streamlining term used to replace a PTI monitoring, record keeping, or reporting requirement with an equivalent or more stringent requirement</p>															
<p align="right">ENF = did noncompliance issues drive the monitoring requirements? R = record keeping requirements Rp = reporting requirements ET = emission testing requirements (not including compliance method terms) Misc = miscellaneous requirements</p>															
EU(s)	Limitation	Basis		ND	OR	M	St	ENF	R	St	Rp	St	ET	Misc	<u>Comments</u>
		SIP (3745-)	Other												
P014	See Comment Section for Emission Limitations	31-05		N	Y	Y	Y	N	Y	Y	Y	Y	Y	N	OR-Monitoring for the relevant time frames and deviation reports are present in the permit to demonstrate compliance with the operating restrictions. <u>Emission Limitations:</u> -OC emissions shall not exceed 1.5 pounds per



															<p>hour and 40 pounds per day from coating materials (resins and gel coat).</p> <p>-OC emissions (Acetone) shall not exceed 19.8 pounds per day from cleanup materials.</p> <p>-OC emissions (Acetone) shall not exceed 2.97 tons per year (TPY) from cleanup materials.</p> <p>-OC emission limitation, for the coatings employed in emissions units P006, P013 through P017, P021, P027, P028, P032 and P035, combined, shall not exceed 20.0 tons per year, based on a rolling, 12-month summation.</p> <p>-The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3.0 gallons per day and 900.0 gallons per year.</p> <p>-The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.</p> <p>-The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.</p> <p>-The permittee shall not employ volatile organic compound (VOC) cleanup materials as VOC is defined in OAC rule 3745-21-01.</p>
P020	See Comment Section for Emission Limitations	31-05		N	Y	Y	Y	N	Y	Y	Y	Y	Y	N	<p>OR-Monitoring for the relevant time frames and deviation reports are present in the permit to demonstrate compliance with the operating restrictions.</p> <p><u>Emission Limitations:</u></p> <p>OC emissions from resin application shall not exceed 8 pounds per hour and 40 lbs/day.</p> <p>OC emissions (acetone) shall not exceed 9.9 pounds per day from cleanup materials.</p> <p>OC emissions (acetone) shall not exceed 1.8 tons per year from cleanup materials.</p> <p>PE/PM-10 shall not exceed 0.81 pounds per hour.</p> <p>PE/PM10 emissions shall not exceed 4.1 pounds per day.</p>



																<p>PE/PM10 emissions shall not exceed 0.51 tons per year based on a rolling, 12-month summation.</p> <p>The annual OC emission limit, for the coatings, employed in emissions units P018 through P020, combined shall not exceed 15.0 TPY, based on a rolling, 12-month summation.</p> <p>The maximum amount of all cleanup material employed in this emissions unit shall not exceed 1.5 gallons per day and 550 gallons per year.</p> <p>The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 lbs of OC/gallon.</p> <p>The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.</p>
<p>P020 P022 P025 P026 P027 P028 P029 P030 P031 P037 P038</p>	<p>See Comment Section for Emission Limitations</p>		<p>40 CFR Part 63 Subpart WWW</p>	N	Y	Y	Y	N	Y	Y	Y	Y	Y	N	<p>OR-Monitoring and deviation reports are present in the permit to demonstrate compliance with the work place operating standards listed below.</p> <p><u>Emission Limitations:</u></p> <p>Organic HAP Emission Limits</p> <p>Tooling gel coating 440 lbs/ton</p> <p>White/off white pigmented gel coating 267 lbs/ton</p> <p>All other pigmented gel coating 377 lbs/ton</p> <p>CR/HS or high performance gel coating 605 lbs/ton</p> <p>Fire retardant gel coat 854 lbs/ton</p> <p>Clear Production gel coat 522 lbs/ton</p> <p>The permittee shall employ only non-HAP-containing cleanup.</p> <p>The permittee shall keep containers that store HAP-containing coating materials and cleanup materials closed or covered, except during the addition or removal of materials. Bulk HAP-containing materials storage tanks may be vented as necessary for safety.</p>	



P018	20 % VE	17-07(A)		N	Y	Y	Y	N	Y	Y	Y	Y	Y	N	OR-A dry filtration system and the associated monitoring and record keeping is in place to ensure compliance with the VE limitation.
P019															
P020															
P022															
P023															
P024															
P025															
P026															
P027															
P028															
P029															
P030															
P031															
P037															
P038															
R001															
R002															
R003															
R004															
P022	See Comment Section for Emission Limitations	31-05		N	Y	Y	Y	N	Y	Y	Y	Y	Y	N	<p>OR-Monitoring for the relevant time frames and deviation reports are present in the permit to demonstrate compliance with the operating restrictions.</p> <p><u>Emission Limitations:</u> PE/PM10 shall not exceed 0.39 pounds per hour. PE/PM10 emissions shall not exceed 6.07 pounds per day. PE/PM10 emissions shall not exceed .60 TPY. OC emissions shall not exceed 15.5 TPY from coatings, based on a rolling 12-month summation. The maximum amount of all cleanup material employed in this emissions unit shall not exceed 2.0 gallons per day and 350 gallons per year. The styrene content of the gel coats (gel coat is a polyester resin surface coating, either</p>



																<p>tons per year from cleanup materials.</p> <p>PE/PM10 shall not exceed 0.28 pounds per hour.</p> <p>PE/PM10 emissions shall not exceed 1.38 pounds per day.</p> <p>PE/PM10 emissions shall not exceed 0.18 tons per year based on a rolling, 12-month summation.</p> <p>The annual OC emission limit, for the coatings employed in this emissions unit shall not exceed 7.0 TPY, based on a rolling, 12-month summation.</p> <p>The maximum amount of all cleanup material employed in this emissions unit shall not exceed .5 gallons per day and 150 gallons per year.</p> <p>The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 lbs of OC/gallon.</p> <p>The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.</p>
P027	See Comment Section for Emission Limitations	31-05		N	Y	Y	Y	N	Y	Y	Y	Y	Y	N	<p>OR-Monitoring for the relevant time frames and deviation reports are present in the permit to demonstrate compliance with the operating restrictions.</p> <p><u>Emission Limitations:</u></p> <p>OC emissions from resin application shall not exceed 8 pounds per hour and 40 lbs/day.</p> <p>OC emissions (acetone) shall not exceed 3.3 pounds per day from cleanup materials.</p> <p>OC emissions (acetone) shall not exceed .495 tons per year from cleanup materials.</p> <p>PE/PM10 shall not exceed 0.28 pounds per hour.</p> <p>PE/PM10 emissions shall not exceed 1.38 pounds per day.</p> <p>PE/PM10 emissions shall not exceed 0.24 tons per year based on a rolling, 12-month</p>	



																<p>summation.</p> <p>The annual OC emission limit, for the coatings, employed in emissions units P006, P013 through P017, P021, P027, P028, P032 and P035 combined shall not exceed 20.0 TPY, based on a rolling, 12-month summation.</p> <p>The maximum amount of all cleanup material employed in this emissions unit shall not exceed .5 gallons per day and 150 gallons per year.</p> <p>The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 lbs of OC/gallon.</p> <p>The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.</p>
P028	See Comment Section for Emission Limitations	31-05		N	Y	Y	Y	N	Y	Y	Y	Y	Y	N		<p>OR-Monitoring for the relevant time frames and deviation reports are present in the permit to demonstrate compliance with the operating restrictions.</p> <p><u>Emission Limitations:</u></p> <p>OC emissions from resin application shall not exceed 8 pounds per hour and 40 lbs/day.</p> <p>OC emissions (acetone) shall not exceed 3.3 pounds per day from cleanup materials.</p> <p>OC emissions (acetone) shall not exceed .495 tons per year from cleanup materials.</p> <p>PE/PM10 shall not exceed 0.28 pounds per hour.</p> <p>PE/PM10 emissions shall not exceed 1.38 pounds per day.</p> <p>PE/PM10 emissions shall not exceed 0.06 tons per year based on a rolling, 12-month summation.</p> <p>The annual OC emission limit, for the coatings, employed in emissions units P006, P013 through P017, P021, P027, P028, P032 and P035 combined shall not exceed 20.0 TPY, based on a rolling, 12-month summation.</p> <p>The maximum amount of all cleanup material employed in this emissions unit shall not exceed</p>



																<p>The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon.</p> <p>The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01, in this emissions unit.</p> <p>The permittee shall employ non-VOC based cleanup materials</p>
P030	See Comment Section for Emission Limitations	21-07(G)(9)(g)		N	N	Y	Y	N	Y	Y	Y	Y	Y	N		<p><u>Emission Limitations:</u></p> <p>OC emissions from resin application shall not exceed 10.1 pounds per hour and 157 lbs/day.</p> <p>OC (acetone)emissions shall not exceed 13.2 pounds per day from cleanup materials.</p> <p>OC(acetone) emissions shall not exceed 2.4 tons per year from cleanup materials.</p>
P031	See Comment Section for Emission Limitations	31-05		N	Y	Y	Y	N	Y	Y	Y	Y	Y	N		<p>OR-Monitoring for the relevant time frames and deviation reports are present in the permit to demonstrate compliance with the operating restrictions.</p> <p><u>Emission Limitations:</u></p> <p>OC emissions from resin application shall not exceed 8 pounds per hour and 40 lbs/day.</p> <p>OC emissions (acetone) shall not exceed 3.3 pounds per day from cleanup materials.</p> <p>OC emissions (acetone) shall not exceed .495 tons per year from cleanup materials.</p> <p>PE/PM10 shall not exceed 0.28 pounds per hour.</p> <p>PE/PM10 emissions shall not exceed 1.38 pounds per day.</p> <p>PE/PM10 emissions shall not exceed 0.06 tons per year based on a rolling, 12-month summation.</p> <p>The annual OC emission limit, for the coatings, employed in emissions units P002 through P005, P030, P031, P033 and P034, combined shall not exceed 25.0 TPY, based on a rolling, 12-month summation.</p> <p>The maximum amount of all cleanup material</p>



															<p>employed in this emissions unit shall not exceed .5 gallons per day and 150 gallons per year.</p> <p>The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 lbs of OC/gallon.</p> <p>The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.</p>
P036	See Comment Section for Emission Limitations	31-05		N	Y	Y	Y	N	Y	Y	Y	Y	Y	N	<p>OR-Monitoring for the relevant time frames and deviation reports are present in the permit to demonstrate compliance with the operating restrictions.</p> <p><u>Emission Limitations:</u></p> <p>OC emissions from resin application shall not exceed 1 pounds per hour and 40 lbs/day.</p> <p>OC emissions (acetone) shall not exceed 19.8 pounds per day from cleanup materials.</p> <p>OC emissions (acetone) shall not exceed 2.97 tons per year from cleanup materials.</p> <p>The annual OC emission limit, for the coatings employed in this emission unit shall not exceed 1.0 TPY, based on a rolling, 12-month summation.</p> <p>The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3.0 gallons per day and 900.0 gallons per year.</p> <p>The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 lbs of OC/gallon.</p> <p>The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.</p>
P036 P039	See Comment Section for Emission Limitations		40 CFR Part 63 Subpart WWWW	N	Y	Y	Y	N	Y	Y	Y	Y	Y	N	<p>OR-Monitoring and deviation reports are present in the permit to demonstrate compliance with the work place operating standards listed below.</p> <p><u>Emission Limitations:</u></p> <p>Organic HAP Emission Limit CR/HS 123 lbs/ton</p>



																<p>Non-CR/HS 87 lbs/ton Tooling 157 lbs/ton Low flame /low smoke products 238 lbs/ton Shrinkage Controlled Resin 180 lbs/ton The permittee shall employ only non-HAP-containing cleanup. The permittee shall keep containers that store HAP-containing coating materials and cleanup materials closed or covered, except during the addition or removal of materials. Bulk HAP-containing materials storage tanks may be vented as necessary for safety.</p>
P037	See Comment Section for Emission Limitations	31-05		N	Y	Y	Y	N	Y	Y	Y	Y	Y	N	<p>OR-Monitoring for the relevant time frames and deviation reports are present in the permit to demonstrate compliance with the operating restrictions.</p> <p><u>Emission Limitations:</u> OC emissions from resin application shall not exceed 2 pounds per hour and 40 lbs/day. OC emissions (acetone) shall not exceed 3.3 pounds per day from cleanup materials. OC emissions (acetone) shall not exceed .495 tons per year from cleanup materials. PE/PM10 shall not exceed 0.27 pounds per hour. PE/PM10 emissions shall not exceed 1.8 pounds per day. PE/PM10 emissions shall not exceed 0.01 tons per year based on a rolling, 12-month summation. The annual OC emission limit, for the coatings, employed in this emission unit shall not exceed 0.3 TPY, based on a rolling, 12-month summation. The maximum amount of all cleanup material employed in this emissions unit shall not exceed 0.5 gallons per day and 150 gallons per year. The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 lbs of OC/gallon.</p>	



P024 P038	Limitations		WWWW												<p><u>Emission Limitations:</u> Organic HAP Emission Limit CR/HS 113 lbs/ton Non-CR/HS 88 lbs/ton Tooling 254 lbs/ton Low flame /low smoke products 497lbs/ton Shrinkage Controlled Resin 454 lbs/ton The permittee shall employ only non-HAP-containing cleanup. The permittee shall keep containers that store HAP-containing coating materials and cleanup materials closed or covered, except during the addition or removal of materials. Bulk HAP-containing materials storage tanks may be vented as necessary for safety.</p>
P039	See Comment Section for Emission Limitations	31-05		N	Y	Y	Y	N	Y	Y	Y	Y	Y	N	<p>OR-Monitoring for the relevant time frames and deviation reports are present in the permit to demonstrate compliance with the operating restrictions.</p> <p><u>Emission Limitations:</u> OC emissions from resin application shall not exceed 2 pounds per hour and 40 lbs/day. OC emissions (acetone) shall not exceed 3.3 pounds per day from cleanup materials. OC emissions (acetone) shall not exceed .495 tons per year from cleanup materials. The annual OC emissions, for the coatings employed in this emission unit shall not exceed 0.2 TPY, based on a rolling, 12-month summation. The maximum amount of all cleanup material employed in this emissions unit shall not exceed 0.5 gallons per day and 150.0 gallons per year. The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 lbs of OC/gallon. The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this</p>



															emissions unit.
P026 P029	See Comment Section for Emission Limitation s	31-05		N	Y	Y	Y	N	Y	Y	Y	Y	Y	N	<p>OR-Monitoring for the relevant time frames and deviation reports are present in the permit to demonstrate compliance with the operating restrictions.</p> <p><u>Emission Limitations:</u></p> <p>OC emissions from resin application shall not exceed 8 pounds per hour and 40 lbs/day.</p> <p>OC emissions (acetone) shall not exceed 19.8 pounds per day from cleanup materials.</p> <p>OC emissions (acetone) shall not exceed 2.97 tons per year from cleanup materials.</p> <p>PE/PM10 shall not exceed 0.28 pounds per hour.</p> <p>PE/PM10 emissions shall not exceed 1.38 pounds per day.</p> <p>PE/PM10 emissions shall not exceed 0.24 tons per year based on a rolling, 12-month summation.</p> <p>The annual OC emission limit, for the coatings, employed in emissions units P026, P029, P040, and P041, combined shall not exceed 28.0 TPY, based on a rolling, 12-month summation.</p> <p>The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3 gallons per day and 900 gallons per year.</p> <p>The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 lbs of OC/gallon.</p> <p>The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.</p>
P018 P019	See Comment Section for Emission Limitation	31-05		N	Y	Y	Y	N	Y	Y	Y	Y	Y	N	<p>OR-Monitoring for the relevant time frames and deviation reports are present in the permit to demonstrate compliance with the operating restrictions.</p> <p><u>Emission Limitations:</u></p> <p>OC emissions from resin application shall not</p>



	s															<p>exceed 8 pounds per hour and 40 lbs/day.</p> <p>OC emissions (acetone) shall not exceed 9.9 pounds per day from cleanup materials.</p> <p>OC emissions (acetone) shall not exceed 1.8 tons per year from cleanup materials.</p> <p>PE/PM10 shall not exceed 0.81 pounds per hour.</p> <p>PE/PM10 emissions shall not exceed 4.1 pounds per day.</p> <p>PE/PM10 emissions shall not exceed 0.51 tons per year based on a rolling, 12-month summation.</p> <p>The annual OC emission limit, for the coatings, employed in emissions units P018 through P020, combined shall not exceed 15.0 TPY, based on a rolling, 12-month summation.</p> <p>The maximum amount of all cleanup material employed in this emissions unit shall not exceed 1.5 gallons per day and 550 gallons per year.</p> <p>The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 lbs of OC/gallon.</p> <p>The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.</p>
P023 P024	See Comment Section for Emission Limitation s	31-05		N	Y	Y	Y	N	Y	Y	Y	Y	Y	N		<p>OR-Monitoring for the relevant time frames and deviation reports are present in the permit to demonstrate compliance with the operating restrictions.</p> <p><u>Emission Limitations:</u></p> <p>PE/PM10 shall not exceed 2.05 pounds per hour.</p> <p>PE/PM10 emissions shall not exceed 22.9 pounds per day.</p> <p>PE/PM10 emissions shall not exceed 2.77 TPY.</p> <p>OC emissions shall not exceed 25.0 TPY from coatings, based on a rolling 12-month summation.</p> <p>The maximum amount of all cleanup material</p>



																<p>employed in this emissions unit shall not exceed 2.0 gallons per day and 350 gallons per year.</p> <p>The styrene content of the neat resins shall not exceed the following limitations:</p> <p>a. 48%, by weight, as applied for each corrosion resistant material (Corrosion resistant materials are polyester resin materials used to make products for corrosion retardant applications such as tooling, fuel or chemical tanks and boat hulls.</p> <p>42%, by weight, as applied for each fire retardant material (Fire retardant materials are polyester resin materials used to make products resistant to flame or fire.); and</p> <p>38%, by weight, as applied for all other materials.</p> <p>The amount of coatings (resins) employed in this emissions unit shall not exceed 840.9 pounds per hour, 9,412 pounds per day and 1,135 tons per year. The tons per year limitation is based upon a rolling, 12-month summation.</p> <p>The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon.</p> <p>The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01, in this emissions unit.</p> <p>The permittee shall employ non-VOC based cleanup materials. No cleanup materials with VOC as defined in OAC rule 3745-21-01(B)(14) shall be employed.</p>
P023 P024	See Comment Section for Emission Limitation s	21-07(G)(9)(g)		N	N	Y	Y	N	Y	Y	Y	Y	Y	N	<p><u>Emission Limitations:</u></p> <p>OC emissions from resin application shall not exceed 18.5 pounds per hour and 208 lbs/day.</p> <p>OC (acetone)emissions shall not exceed 13.2 pounds per day from cleanup materials.</p> <p>OC(acetone) emissions shall not exceed 1.16 tons per year from cleanup materials.</p>	



R001 R002	See Comment Section for Emission Limitation s	31-05		N	Y	Y	Y	N	Y	Y	Y	Y	Y	N	<p>OR-Monitoring for the relevant time frames and deviation reports are present in the permit to demonstrate compliance with the operating restrictions.</p> <p><u>Emission Limitations:</u></p> <p>OC emissions from resin application shall not exceed 8 pounds per hour and 40 lbs/day.</p> <p>OC emissions shall not exceed 7.0 pounds per day from cleanup materials.</p> <p>PE/PM10 shall not exceed 0.17 pounds per hour.</p> <p>PE/PM10 emissions shall not exceed 0.73 tons per year.</p> <p>OC emissions shall not exceed 5.0 tons per year from all coatings and cleanup materials employed, based on a rolling, 12- month summation.</p> <p>The maximum amount of all cleanup material employed in this emissions unit shall not exceed 0.936 gallons per day and 220 gallons per year, based upon a rolling, 12-month summation of the cleanup material usage.</p> <p>The maximum coating usage for this emissions unit shall not exceed 13.3 gallons/day and 2,820 gallons/year based upon a rolling, 12-month summation of the coating usage.</p> <p>The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 7.0 lbs of OC/gallon.</p> <p>The maximum OC content of each coating employed in this emissions unit shall not exceed 3.0 lbs of OC/gallon, including water and exempt solvents, as applied.</p> <p>The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01, in this emissions unit.</p>
--------------	---	-------	--	---	---	---	---	---	---	---	---	---	---	---	---



R003 R004	See Comment Section for Emission Limitations	31-05		N	Y	Y	Y	N	Y	Y	Y	Y	Y	N	<p>OR-Monitoring for the relevant time frames and deviation reports are present in the permit to demonstrate compliance with the operating restrictions.</p> <p><u>Emission Limitations:</u></p> <p>OC emissions from resin application shall not exceed 8 pounds per hour and 40 lbs/day.</p> <p>OC emissions shall not exceed 7.0 pounds per day from cleanup materials.</p> <p>PE/PM10 shall not exceed 0.17 pounds per hour.</p> <p>PE/PM10 emissions shall not exceed 0.73 tons per year.</p> <p>OC emissions shall not exceed 7.5 tons per year from all coatings and cleanup materials employed, based on a rolling, 12- month summation.</p> <p>The maximum amount of all cleanup material employed in this emissions unit shall not exceed 0.936 gallons per day and 220 gallons per year, based upon a rolling, 12-month summation of the cleanup material usage.</p> <p>The maximum coating usage for this emissions unit shall not exceed 13.3 gallons/day and 2,820 gallons/year based upon a rolling, 12-month summation of the coating usage.</p> <p>The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 7.0 lbs of OC/gallon.</p> <p>The maximum OC content of each coating employed in this emissions unit shall not exceed 3.0 lbs of OC/gallon, including water and exempt solvents, as applied.</p> <p>The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01, in this emissions unit.</p>
P040 P041	See Comment Section for	31-05		N	Y	Y	Y	N	Y	Y	Y	Y	Y	N	<p>OR-Monitoring for the relevant time frames and deviation reports are present in the permit to demonstrate compliance with the operating restrictions.</p>



	Emission Limitations															<p><u>Emission Limitations:</u></p> <p>OC emissions shall not exceed 5 pounds per hour and 40 pounds per day from coating materials (resins and gel coat).</p> <p>OC emissions (Acetone) shall not exceed 19.8 pounds per day from cleanup materials.</p> <p>OC emissions (Acetone) shall not exceed 2.97 tons per year (TPY) from cleanup materials.</p> <p>The annual OC emission limitation, for the coatings employed in emissions units P026, P029, P040, and P041, combined, shall not exceed 28.0 tons per year, based on a rolling, 12-month summation of the coating emissions.</p> <p>The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3.0 gallons per day and 900.0 gallons per year.</p> <p>The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.</p> <p>The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.</p> <p>The permittee shall not employ volatile organic compound (VOC) cleanup materials as VOC is defined in OAC rule 3745-21-01.</p>
P015 P016 P017	See Comment Section for Emission Limitations	31-05		N	Y	Y	Y	N	Y	Y	Y	Y	Y	N	<p>OR-Monitoring for the relevant time frames and deviation reports are present in the permit to demonstrate compliance with the operating restrictions.</p> <p><u>Emission Limitations:</u></p> <p>OC emissions shall not exceed 2.0 pounds per hour and 40 pounds per day from coating materials (resins and gel coat).</p> <p>OC emissions (Acetone) shall not exceed 19.8 pounds per day from cleanup materials.</p> <p>OC emissions (Acetone) shall not exceed 2.97 tons per year (TPY) from cleanup materials.</p> <p>The annual OC emission limitation, for the coatings employed in emissions units P006,</p>	



																<p>exceed 6.6 pounds of OC per gallon of cleanup material.</p> <p>The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.</p> <p>The permittee shall not employ volatile organic compound (VOC) cleanup materials as VOC is defined in OAC rule 3745-21-01.</p>
P033 P034	See Comment Section for Emission Limitations	31-05		N	Y	Y	Y	N	Y	Y	Y	Y	Y	N		<p>OR-Monitoring for the relevant time frames and deviation reports are present in the permit to demonstrate compliance with the operating restrictions.</p> <p><u>Emission Limitations:</u></p> <p>OC emissions shall not exceed 3 pounds per hour and 40 pounds per day from coating materials (resins and gel coat).</p> <p>OC emissions (Acetone) shall not exceed 19.8 pounds per day from cleanup materials.</p> <p>OC emissions (Acetone) shall not exceed 2.97 tons per year (TPY) from cleanup materials.</p> <p>The annual OC emission limitation, for the coatings employed in emissions units P002 through P005, P030, P031, P033 and P034, combined, shall not exceed 25.0 tons per year, based on a rolling, 12-month summation of the coating emissions.</p> <p>The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3.0 gallons per day and 900.0 gallons per year.</p> <p>The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.</p> <p>The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.</p> <p>The permittee shall not employ volatile organic compound (VOC) cleanup materials as VOC is defined in OAC rule 3745-21-01.</p>



P006 P013 P035	See Comment Section for Emission Limitations	31-05		N	Y	Y	Y	N	Y	Y	Y	Y	Y	N	<p>OR-Monitoring for the relevant time frames and deviation reports are present in the permit to demonstrate compliance with the operating restrictions.</p> <p><u>Emission Limitations:</u></p> <p>OC emissions shall not exceed 5 pounds per hour and 40 pounds per day from coating materials (resins and gel coat).</p> <p>OC emissions (Acetone) shall not exceed 19.8 pounds per day from cleanup materials.</p> <p>OC emissions (Acetone) shall not exceed 2.97 tons per year (TPY) from cleanup materials.</p> <p>The annual OC emission limitation, for the coatings employed in emissions units P006, P013 through P017, P021, P027, P028, P032 and P035, combined, shall not exceed 20.0 tons per year, based on a rolling, 12-month summation.</p> <p>The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3.0 gallons per day and 900.0 gallons per year.</p> <p>The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.</p> <p>The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.</p> <p>The permittee shall not employ volatile organic compound (VOC) cleanup materials as VOC is defined in OAC rule 3745-21-01.</p>
P021 P032	See Comment Section for Emission Limitations	31-05		N	Y	Y	Y	N	Y	Y	Y	Y	Y	N	<p>OR-Monitoring for the relevant time frames and deviation reports are present in the permit to demonstrate compliance with the operating restrictions.</p> <p><u>Emission Limitations:</u></p> <p>OC emissions shall not exceed 3 pounds per hour and 40 pounds per day from coating materials</p> <p>OC emissions (Acetone) shall not exceed 19.8</p>

PUBLIC NOTICE
Issuance of Draft Air Pollution Title V Permit
Core Composites Cincinnati, LLC

Issue Date: 10/14/2010
Permit Number: P0104748
Permit Type: Renewal
Permit Description: Manufacturer of custom fiber glass products.
Facility ID: 1413020248
Facility Location: Core Composites Cincinnati, LLC
4174 Half Acre Road,
Batavia, OH 45103
Facility Description: All Other Plastics Product Manufacturing

Chris Korleski, Director of the Ohio Environmental Protection Agency, 50 West Town Street, Columbus Ohio, has issued a draft action of an air pollution control Title V operating permit for the facility at the location identified above on the date indicated. Comments concerning this draft action, or a request for a public meeting, must be sent in writing no later than thirty (30) days from the date this notice is published. All comments, questions, requests for permit applications or other pertinent documentation, and correspondence concerning this action must be directed to Alberta Mellon at Hamilton County Dept. of Environmental Services, 250 William Howard Taft Pkwy., Cincinnati, OH 45219-2660 or (513)946-7777. The permit, which includes a detailed description of the operations, and associated statement of basis for the permit requirements, can be downloaded from the Web page: www.epa.ohio.gov/dapc



DRAFT

**Division of Air Pollution Control
Title V Permit
for
Core Composites Cincinnati, LLC**

Facility ID: 1413020248
Permit Number: P0104748
Permit Type: Renewal
Issued: 10/14/2010
Effective: To be entered upon final issuance
Expiration: To be entered upon final issuance



Division of Air Pollution Control
Title V Permit
for
Core Composites Cincinnati, LLC

Table of Contents

Authorization 1
A. Standard Terms and Conditions 2
1. Federally Enforceable Standard Terms and Conditions 3
2. Monitoring and Related Record Keeping and Reporting Requirements..... 3
3. Scheduled Maintenance..... 6
4. Risk Management Plans 6
5. Title IV Provisions 6
6. Severability Clause 7
7. General Requirements 7
8. Fees..... 8
9. Marketable Permit Programs..... 8
10. Reasonably Anticipated Operating Scenarios 8
11. Reopening for Cause 8
12. Federal and State Enforceability 9
13. Compliance Requirements 9
14. Permit Shield 10
15. Operational Flexibility..... 10
16. Emergencies..... 11
17. Off-Permit Changes 11
18. Compliance Method Requirements 11
19. Insignificant Activities or Emissions Levels..... 12
20. Permit to Install Requirement 12
21. Air Pollution Nuisance 12
22. Permanent Shutdown of an Emissions Unit 12
23. Title VI Provisions 12
24. Reporting Requirements Related to Monitoring and Record Keeping Requirements Under State Law Only 13
25. Records Retention Requirements Under State Law Only..... 13
26. Inspections and Information Requests 13
27. Scheduled Maintenance/Malfunction Reporting 14
28. Permit Transfers 14



29. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations	14
B. Facility-Wide Terms and Conditions.....	15
C. Emissions Unit Terms and Conditions	17
1. P014, RTM Pump 3 Bldg A	18
2. P020, Main Spray Booth Gel Coat	26
3. P022, Robot (Venus) Gel Coat Booth	40
4. P025, Main Spray Booth Gel Coat - 2	54
5. P027, Service Gel Coat Main Bldg - 2.....	67
6. P028, Service Gel Coat Main Bldg - 3.....	81
7. P030, Service Gel Coat Bldg B - 1	95
8. P031, Service Gel Coat Bldg B - 2.....	109
9. P036, Hand Layup Area.....	123
10. P037, Tooling Gel Coat.....	134
11. P038, Tooling Spray Chop	147
12. P039, Tooling Layup	161
13. Emissions Unit Group - Gel Coat: P026, P029,	172
14. Emissions Unit Group - Open Molding Manual: P018, P019,	186
15. Emissions Unit Group - Open Molding Mechanical: P023, P024,	200
16. Emissions Unit Group - Primer Booths: R001, R002,	214
17. Emissions Unit Group - Primer Booths: R003, R004,	224
18. Emissions Unit Group - RTM Units: P040, P041,	234
19. Emissions Unit Group - RTM Units: P015, P016, P017,	242
20. Emissions Unit Group - RTM Units: P002, P003, P004, P005,	250
21. Emissions Unit Group - RTM Units: P033, P034,	258
22. Emissions Unit Group - RTM Units: P006, P013, P035,	266
23. Emissions Unit Group - RTM Units: P021, P032,	274



Authorization

Facility ID: 1413020248
Facility Description: Manufacturer of custom fiber glass products.
Application Number(s): A0029165, A0029166, A0036800
Permit Number: P0104748
Permit Description: Manufacturer of custom fiber glass products.
Permit Type: Renewal
Issue Date: 10/14/2010
Effective Date: To be entered upon final issuance
Expiration Date: To be entered upon final issuance
Superseded Permit Number: P0097515

This document constitutes issuance of an OAC Chapter 3745-77 Title V permit to:

Core Composites Cincinnati, LLC
4174 Half Acre Road
Batavia, OH 45103

Ohio EPA District Office or local air agency responsible for processing and administering your permit:

Hamilton County Dept. of Environmental Services
250 William Howard Taft Pkwy.
Cincinnati, OH 45219-2660
(513)946-7777

The above named entity is hereby granted a Title V permit pursuant to Chapter 3745-77 of the Ohio Administrative Code. This permit and the authorization to operate the air contaminant sources (emissions units) at this facility shall expire at midnight on the expiration date shown above. You will be sent a notice approximately 18 months prior to the expiration date regarding the renewal of this permit. If you do not receive a notice, please contact the Hamilton County Dept. of Environmental Services. If a renewal permit is not issued prior to the expiration date, the permittee may continue to operate pursuant to OAC rule 3745-77-08(E) and in accordance with the terms of this permit beyond the expiration date, if a timely renewal application is submitted. A renewal application will be considered timely if it is submitted no earlier than 18 months (540 days) and no later than 6 months (180 days) prior to the expiration date.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Chris Korleski
Director



A. Standard Terms and Conditions



1. Federally Enforceable Standard Terms and Conditions

- a) All Standard Terms and Conditions are federally enforceable, with the exception of those listed below which are enforceable under State law only:
- (1) Standard Term and Condition A. 24., Reporting Requirements Related to Monitoring and Record Keeping Requirements of State-Only Enforceable Permit Terms and Conditions
 - (2) Standard Term and Condition A. 25., Records Retention Requirements for State-Only Enforceable Permit Terms and Conditions
 - (3) Standard Term and Condition A. 27., Scheduled Maintenance/Malfunction Reporting
 - (4) Standard Term and Condition A. 29., Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations

(Authority for term: ORC 3704.036(A))

2. Monitoring and Related Record Keeping and Reporting Requirements

- a) Except as may otherwise be provided in the terms and conditions for a specific emissions unit (i.e., in section C. Emissions Unit Terms and Conditions of this Title V permit), the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:
- (1) The date, place (as defined in the permit), and time of sampling or measurements.
 - (2) The date(s) analyses were performed.
 - (3) The company or entity that performed the analyses.
 - (4) The analytical techniques or methods used.
 - (5) The results of such analyses.
 - (6) The operating conditions existing at the time of sampling or measurement.

(Authority for term: OAC rule 3745-77-07(A)(3)(b)(i))

- b) Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

(Authority for term: OAC rule 3745-77-07(A)(3)(b)(ii))

- c) The permittee shall submit required reports in the following manner:

- (1) All reporting required in accordance with OAC rule 3745-77-07(A)(3)(c) for deviations caused by malfunctions shall be submitted in the following manner:

Any malfunction, as defined in OAC rule 3745-15-06(B)(1), shall be promptly reported to the Ohio EPA in accordance with OAC rule 3745-15-06. In addition, to fulfill the OAC rule 3745-77-07(A)(3)(c) deviation reporting requirements for malfunctions, written reports that identify each malfunction that occurred during each calendar quarter (including each malfunction reported only verbally in accordance with OAC rule 3745-15-06) shall be submitted (i.e., postmarked) by January 31, April 30, July 31, and October 31 of each year in accordance with Standard Term and Condition A.2.c)(2) below; and each report shall cover the previous calendar quarter. An exceedance of the visible emission limitations specified in OAC rule 3745-17-07(A)(1) that is caused by a malfunction is not a violation and does not need to be reported as a deviation if the owner or operator of the affected air contaminant source or air pollution control equipment complies with the requirements of OAC rule 3745-17-07(A)(3)(c).

In accordance with OAC rule 3745-15-06, a malfunction reportable under OAC rule 3745-15-06(B) is a deviation of the federally enforceable permit requirements. Even though verbal notifications and written reports are required for malfunctions pursuant to OAC rule 3745-15-06, the written reports required pursuant to this term must be submitted quarterly to satisfy the prompt reporting provision of OAC rule 3745-77-07(A)(3)(c).

In identifying each deviation caused by a malfunction, the permittee shall specify the emission limitation(s) (or control requirement(s)) for which the deviation occurred, describe each deviation, and provide the magnitude and duration of each deviation. For a specific malfunction, if this information has been provided in a written report that was submitted in accordance with OAC rule 3745-15-06, the permittee may simply reference that written report to identify the deviation. Nevertheless, all malfunctions, including those reported only verbally in accordance with OAC rule 3745-15-06, must be reported in writing on a quarterly basis.

Any scheduled maintenance, as referenced in OAC rule 3745-15-06(A)(1), that results in a deviation from a federally enforceable emission limitation (or control requirement) shall be reported in the same manner as described above for malfunctions.

(Authority for term: OAC rule 3745-77-07(A)(3)(c))

- (2) Except as may otherwise be provided in the terms and conditions for a specific emissions unit (i.e., in section C. Emissions Unit Terms and Conditions of this Title V permit or, in some cases, in section B. Facility-Wide Terms and Conditions of this Title V permit), all reporting required in accordance with OAC rule 3745-77-07(A)(3)(c) for deviations of the emission limitations, operational restrictions, and control device operating parameter limitations shall be submitted in the following manner:

Written reports of (a) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures taken, shall be promptly made to the appropriate Ohio EPA District Office or local air agency. Except as provided below, the written reports shall be submitted (i.e., postmarked) by January 31, April 30, July 31, and October 31 of each year; and each report shall cover the previous calendar quarter.

In identifying each deviation, the permittee shall specify the emission limitation(s), operational restriction(s), and/or control device operating parameter limitation(s) for which the deviation occurred, describe each deviation, and provide the estimated magnitude and duration of each deviation.

These written deviation reports shall satisfy the requirements of OAC rule 3745-77-07(A)(3)(c) pertaining to the submission of monitoring reports every six months and to the prompt reporting of all deviations. Full compliance with OAC rule 3745-77-07(A)(3)(c) requires reporting of all other deviations of the federally enforceable requirements specified in the permit as required by such rule.

If an emissions unit has a deviation reporting requirement for a specific emission limitation, operational restriction, or control device operating parameter limitation that is not on a quarterly basis (e.g., within 30 days following the end of the calendar month, or within 30 or 45 days after the exceedance occurs), that deviation reporting requirement satisfies the reporting requirements specified in this Standard Term and Condition for that specific emission limitation, operational restriction, or control device parameter limitation. Following the provisions of that non-quarterly deviation reporting requirement will also satisfy (for the deviations so reported) the requirements of OAC rule 3745-77-07(A)(3)(c) pertaining to the submission of monitoring reports every six months and to the prompt reporting of all deviations, and additional quarterly deviation reports for that specific emission limitation, operational restriction, or control device parameter limitation are not required pursuant to this Standard Term and Condition.

See A.29 below if no deviations occurred during the quarter.

(Authority for term: OAC rule 3745-77-07(A)(3)(c))

- (3) All reporting required in accordance with the OAC rule 3745-77-07(A)(3)(c) for other deviations of the federally enforceable permit requirements which are not reported in accordance with Standard Term and Condition A.2)c)(2) above shall be submitted in the following manner:

Unless otherwise specified by rule, written reports that identify deviations of the following federally enforceable requirements contained in this permit; Standard Terms and Conditions: A.3, A.4, A.5, A.7.e), A.8, A.13, A.15, A.19, A.20, A.21, and A.23 of this Title V permit, as well as any deviations from the requirements in section C. Emissions Unit Terms and Conditions of this Title V permit, and any monitoring, record keeping, and reporting requirements, which are not reported in accordance with Standard Term and Condition A.2.c)(2) above shall be submitted (i.e., postmarked) to the appropriate Ohio EPA District Office or local air agency by January 31 and July 31 of each year; and each report shall cover the previous six calendar months. Unless otherwise specified by rule, all other deviations from federally enforceable requirements identified in this permit shall be submitted annually as part of the annual compliance certification, including deviations of federally enforceable requirements not specifically addressed by permit or rule for the insignificant activities or emissions levels (IEU) identified in section B. Facility-Wide Terms and Conditions of this Title V permit. Annual reporting of deviations is deemed adequate to meet the deviation reporting requirements for IEUs unless otherwise specified by permit or rule.

In identifying each deviation, the permittee shall specify the federally enforceable requirement for which the deviation occurred, describe each deviation, and provide the magnitude and duration of each deviation.

These semi-annual and annual written reports shall satisfy the reporting requirements of OAC rule 3745-77-07(A)(3)(c) for any deviations from the federally enforceable requirements contained in this permit that are not reported in accordance with Standard Term and Condition A.2.c)(2) above.

If no such deviations occurred during a six-month period, the permittee shall submit a semi-annual report which states that no such deviations occurred during that period.



(Authority for term: OAC rules 3745-77-07(A)(3)(c)(i) and (ii) and OAC rule 3745-77-07(A)(13)(b))

- (4) Each written report shall be signed by a responsible official certifying that, "based on information and belief formed after reasonable inquiry, the statements and information in the report (including any written malfunction reports required by OAC rule 3745-15-06 that are referenced in the deviation reports) are true, accurate, and complete."

(Authority for term: OAC rule 3745-77-07(A)(3)(c)(iv))

- (5) Reports of any required monitoring and/or record keeping information shall be submitted to Hamilton County Dept. of Environmental Services.

(Authority for term: OAC rule 3745-77-07(A)(3)(c))

3. Scheduled Maintenance

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. Except as provided in OAC rule 3745-15-06(A)(3), any scheduled maintenance necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s). Any scheduled maintenance, as defined in OAC rule 3745-15-06(A)(1), that results in a deviation from a federally enforceable emission limitation (or control requirement) shall be reported in the same manner as described for malfunctions in Standard Term and Condition A.2.c)(1) above.

(Authority for term: OAC rule 3745-77-07(A)(3)(c))

4. Risk Management Plans

If applicable, the permittee shall develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. § 7401 et seq. ("Act"); and, pursuant to 40 C.F.R. 68.215(a), the permittee shall submit either of the following:

- a) a compliance plan for meeting the requirements of 40 C.F.R. Part 68 by the date specified in 40 C.F.R. 68.10(a) and OAC 3745-104-05(A); or
- b) as part of the compliance certification submitted under 40 C.F.R. 70.6(c)(5), a certification statement that the source is in compliance with all requirements of 40 C.F.R. Part 68 and OAC Chapter 3745-104, including the registration and submission of the risk management plan.

(Authority for term: OAC rule 3745-77-07(A)(4))

5. Title IV Provisions

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

(Authority for term: OAC rule 3745-77-07(A)(5))

6. Severability Clause

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition declared invalid.

(Authority for term: OAC rule 3745-77-07(A)(6))

7. General Requirements

- a) The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and reissuance, or modification, or for denial of a permit renewal application.
- b) It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.
- c) This permit may be modified, reopened, revoked, or revoked and reissued, for cause, in accordance with Standard Term and Condition A.11 below. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.
- d) This permit does not convey any property rights of any sort, or any exclusive privilege.
- e) The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.
- f) Except as otherwise indicated below, this Title V permit, or permit modification, is effective for five years from the original effective date specified in the permit. In the event that this facility becomes eligible for non-title V permits, this permit shall cease to be enforceable when:
 - (1) the permittee submits an approved facility-wide potential to emit analysis supporting a claim that the facility no longer meets the definition of a "major source" as defined in OAC rule 3745-77-01(W) based on the permanent shutdown and removal of one or more emissions units identified in this permit; or
 - (2) the permittee no longer meets the definition of a "major source" as defined in OAC rule 3745-77-01(W) based on obtaining restrictions on the facility-wide potential(s) to emit that are federally enforceable or legally and practically enforceable ; or
 - (3) a combination of (1) and (2) above.

The permittee shall continue to comply with all applicable OAC Chapter 3745-31 requirements for all regulated air contaminant sources once this permit ceases to be enforceable. The permittee shall comply with any residual requirements, such as quarterly deviation reports, semi-annual deviation reports, and annual compliance certifications covering the period during which this Title V permit was enforceable. All records relating to this permit must be maintained in accordance with law.

(Authority for term: OAC rule 3745-77-01(W), OAC rule 3745-77-07(A)(3)(b)(ii), OAC rule 3745-77(A)(7))

8. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78.

(Authority for term: OAC rule 3745-77-07(A)(8))

9. Marketable Permit Programs

No revision of this permit is required under any approved economic incentive, marketable permits, emissions trading, and other similar programs or processes for changes that are provided for in this permit.

(Authority for term: OAC rule 3745-77-07(A)(9))

10. Reasonably Anticipated Operating Scenarios

The permittee is hereby authorized to make changes among operating scenarios authorized in this permit without notice to the Ohio EPA, but, contemporaneous with making a change from one operating scenario to another, the permittee must record in a log at the permitted facility the scenario under which the permittee is operating. The permit shield provided in these standard terms and conditions shall apply to all operating scenarios authorized in this permit.

(Authority for term: OAC rule 3745-77-07(A)(10))

11. Reopening for Cause

This Title V permit will be reopened prior to its expiration date under the following conditions:

- a) Additional applicable requirements under the Act become applicable to one or more emissions units covered by this permit, and this permit has a remaining term of three or more years. Such a reopening shall be completed not later than eighteen (18) months after promulgation of the applicable requirement. No such reopening is required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions has been extended pursuant to paragraph (E)(1) of OAC rule 3745-77-08.
- b) This permit is issued to an affected source under the acid rain program and additional requirements (including excess emissions requirements) become applicable. Upon approval by the Administrator, excess emissions offset plans shall be deemed to be incorporated into the permit, and shall not require a reopening of this permit.
- c) The Director of the Ohio EPA or the Administrator of the U.S. EPA determines that the federally applicable requirements in this permit are based on a material mistake, or that inaccurate statements were made in establishing the emissions standards or other terms and conditions of this permit related to such federally applicable requirements.

- d) The Administrator of the U.S. EPA or the Director of the Ohio EPA determines that this permit must be revised or revoked to assure compliance with the applicable requirements.

(Authority for term: OAC rules 3745-77-07(A)(12) and 3745-77-08(D))

12. Federal and State Enforceability

Only those terms and conditions designated in this permit as federally enforceable, that are required under the Act, or any of its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA, the State, and citizens under the Act. All other terms and conditions of this permit shall not be federally enforceable and shall be enforceable under State law only.

(Authority for term: OAC rule 3745-77-07(B))

13. Compliance Requirements

- a) Any document (including reports) required to be submitted and required by a federally applicable requirement in this Title V permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.
- b) Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:
 - (1) At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.
 - (2) Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with paragraph (E) of OAC rule 3745-77-03.
 - (3) Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.
 - (4) As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.
- c) The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:
 - (1) Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
 - (2) An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

- d) Compliance certifications concerning the terms and conditions contained in this permit that are federally enforceable emission limitations, standards, or work practices, shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) and the Administrator of the U.S. EPA in the following manner and with the following content:
- (1) Compliance certifications shall be submitted annually on a calendar year basis. The annual certification shall be submitted (i.e., postmarked) on or before April 30th of each year during the permit term.
 - (2) Compliance certifications shall include the following:
 - a. An identification of each term or condition of this permit that is the basis of the certification.
 - b. The permittee's current compliance status.
 - c. Whether compliance was continuous or intermittent.
 - d. The method(s) used for determining the compliance status of the source currently and over the required reporting period.
 - e. Such other facts as the Director of the Ohio EPA may require in the permit to determine the compliance status of the source.
 - (3) Compliance certifications shall contain such additional requirements as may be specified pursuant to sections 114(a)(3) and 504(b) of the Act.

(Authority for term: OAC rules 3745-77-07(C)(1),(2),(4) and (5) and ORC section 3704.03(L))

14. Permit Shield

- a) Compliance with the terms and conditions of this permit (including terms and conditions established for alternate operating scenarios, emissions trading, and emissions averaging, but excluding terms and conditions for which the permit shield is expressly prohibited under OAC rule 3745-77-07) shall be deemed compliance with the applicable requirements identified and addressed in this permit as of the date of permit issuance.
- b) This permit shield provision shall apply to any requirement identified in this permit pursuant to OAC rule 3745-77-07(F)(2), as a requirement that does not apply to the source or to one or more emissions units within the source.

(Authority for term: OAC rule 3745-77-07(F))

15. Operational Flexibility

The permittee is authorized to make the changes identified in OAC rule 3745-77-07(H)(1)(a) to (H)(1)(c) within the permitted stationary source without obtaining a permit revision, if such change is not a modification under any provision of Title I of the Act [as defined in OAC rule 3745-77-01(JJ)], and does not result in an exceedance of the emissions allowed under this permit (whether expressed therein as a rate of emissions or in terms of total emissions), and the permittee provides the Administrator of the U.S. EPA and the appropriate Ohio EPA District Office or local air agency with written notification within a minimum of seven days in advance of the proposed changes, unless the change is associated with,



or in response to, emergency conditions. If less than seven days notice is provided because of a need to respond more quickly to such emergency conditions, the permittee shall provide notice to the Administrator of the U.S. EPA and the appropriate District Office of the Ohio EPA or local air agency as soon as possible after learning of the need to make the change. The notification shall contain the items required under OAC rule 3745-77-07(H)(2)(d).

(Authority for term: OAC rules 3745-77-07(H)(1) and (2))

16. Emergencies

The permittee shall have an affirmative defense of emergency to an action brought for noncompliance with technology-based emission limitations if the conditions of OAC rule 3745-77-07(G)(3) are met. This emergency defense provision is in addition to any emergency or upset provision contained in any applicable requirement.

(Authority for term: OAC rule 3745-77-07(G))

17. Off-Permit Changes

The owner or operator of a Title V source may make any change in its operations or emissions at the source that is not specifically addressed or prohibited in the Title V permit, without obtaining an amendment or modification of the permit, provided that the following conditions are met:

- a) The change does not result in conditions that violate any applicable requirements or that violate any existing federally enforceable permit term or condition.
- b) The permittee provides contemporaneous written notice of the change to the Director and the Administrator of the U.S. EPA, except that no such notice shall be required for changes that qualify as insignificant emissions levels or activities as defined in OAC rule 3745-77-01(U). Such written notice shall describe each such change, the date of such change, any change in emissions or pollutants emitted, and any federally applicable requirement that would apply as a result of the change.
- c) The change shall not qualify for the permit shield under OAC rule 3745-77-07(F).
- d) The permittee shall keep a record describing all changes made at the source that result in emissions of a regulated air pollutant subject to an applicable requirement, but not otherwise regulated under the permit, and the emissions resulting from those changes.
- e) The change is not subject to any applicable requirement under Title IV of the Act or is not a modification under any provision of Title I of the Act.

Paragraph (I) of rule 3745-77-07 of the Administrative Code applies only to modification or amendment of the permittee's Title V permit. The change made may require a permit-to-install under Chapter 3745-31 of the Administrative Code if the change constitutes a modification as defined in that Chapter. Nothing in paragraph (I) of rule 3745-77-07 of the Administrative Code shall affect any applicable obligation under Chapter 3745-31 of the Administrative Code.

(Authority for term: OAC rule 3745-77-07(I))

18. Compliance Method Requirements

Nothing in this permit shall alter or affect the ability of any person to establish compliance with, or a violation of, any applicable requirement through the use of credible evidence to the extent authorized by

law. Nothing in this permit shall be construed to waive any defenses otherwise available to the permittee, including but not limited to, any challenge to the Credible Evidence Rule (see 62 Fed. Reg. 8314, Feb. 24, 1997), in the context of any future proceeding.
(This term is provided for informational purposes only.)

19. Insignificant Activities or Emissions Levels

Each IEU that has one or more applicable requirements shall comply with those applicable requirements.

(Authority for term: OAC rule 3745-77-07(A)(1))

20. Permit to Install Requirement

Prior to the "installation" or "modification" of any "air contaminant source," as those terms are defined in OAC rule 3745-31-01, a permit to install must be obtained from the Ohio EPA pursuant to OAC Chapter 3745-31.

(Authority for term: OAC rule 3745-77-07(A)(1))

21. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

(Authority for term: OAC rule 3745-77-07(A)(1))

22. Permanent Shutdown of an Emissions Unit

The permittee may notify Ohio EPA of any emissions unit that is permanently shut down by submitting a certification from the responsible official that identifies the date on which the emissions unit was permanently shut down. Authorization to operate the affected emissions unit shall cease upon the date certified by the responsible official that the emissions unit was permanently shut down.

After the date on which an emissions unit is permanently shut down (i.e., that has been physically removed from service or has been altered in such a way that it can no longer operate without a subsequent "modification" or "installation" as defined in OAC Chapter 3745-31 and therefore ceases to meet the definition of an "emissions unit" as defined in OAC rule 3745-77-01(O)), rendering existing permit terms and conditions irrelevant, the permittee shall not be required, after the date of the certification and submission to Ohio EPA, to meet any Title V permit requirements applicable to that emissions unit, except for any residual requirements, such as the quarterly deviation reports, semi-annual deviation reports and annual compliance certification covering the period during which the emissions unit last operated. All records relating to the shutdown emissions unit, generated while the emissions unit was in operation, must be maintained in accordance with law.

No emissions unit certified by the responsible official as being permanently shut down may resume operation without first applying for and obtaining a permit to install pursuant to OAC Chapter 3745-31.

(Authority for term: OAC rule 3745-77-01)

23. Title VI Provisions

If applicable, the permittee shall comply with the standards for recycling and reducing emissions of ozone depleting substances pursuant to 40 CFR Part 82, Subpart F, except as provided for motor vehicle air conditioners in Subpart B of 40 CFR Part 82:



- a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices specified in 40 CFR 82.156.
- b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment specified in 40 CFR 82.158.
- c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

(Authority for term: OAC rule 3745-77-01(H)(11))

24. Reporting Requirements Related to Monitoring and Record Keeping Requirements Under State Law Only

The permittee shall submit required reports in the following manner:

- a) Reports of any required monitoring and/or record keeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b) Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (i) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and record keeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. In identifying each deviation, the permittee shall specify the applicable requirement for which the deviation occurred, describe each deviation, and provide the magnitude and duration of each deviation. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted (i.e., postmarked) quarterly, by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

25. Records Retention Requirements Under State Law Only

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

26. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine



whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

(Authority for term: OAC rule 3745-77-07(C))

27. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

28. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

(Authority for term: OAC rule 3745-77-01(C))

29. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations

If no emission limitation (or control requirement), operational restriction and/or control device parameter limitation deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted (i.e., postmarked) by January 31, April 30, July 31, and October 31 of each year; and each report shall cover the previous calendar quarter.

The permittee is not required to submit a quarterly report which states that no deviations occurred during that quarter for the following situations:

- a) where an emissions unit has deviation reporting requirements for a specific emission limitation, operational restriction, or control device parameter limitation that override the deviation reporting requirements specified in Standard Term and Condition A.2.c)(2); or
- b) where an uncontrolled emissions unit has no monitoring, record keeping, or reporting requirements and the emissions unit's applicable emission limitations are established at the potentials to emit; or
- c) where the company's responsible official has certified that an emissions unit has been permanently shut down.

B. Facility-Wide Terms and Conditions

Effective Date: To be entered upon final issuance

1. All the following facility-wide terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only:
2. There are no insignificant emissions units at this facility.

C. Emissions Unit Terms and Conditions



Effective Date: To be entered upon final issuance

1. P014, RTM Pump 3 Bldg A

Operations, Property and/or Equipment Description:

RTM Pump 3 Main Bldg

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) See d)(4) and d)(5).

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05196)	Organic compound (OC) emissions shall not exceed 1.5 pounds per hour and 40 pounds per day from coating materials (resins and gel coat). OC emissions (Acetone) shall not exceed 19.8 pounds per day from cleanup materials. OC emissions (Acetone) shall not exceed 2.97 tons per year (TPY) from cleanup materials. See c)(1) through c)(3). Compliance with this rule also include compliance with the requirements of OAC rules 3745-31-05(D).
b.	OAC rule 3745-31-05(D) (PTI 14-05196) Synthetic Minor Determination to avoid the Emission Offset Policy for VOC.	See b)(2)a.
c.	OAC rule 3745-21-07(G)(2)	The emission limitations specified by this rule are the same as or less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3). See b)(2)b.

- (2) Additional Terms and Conditions
- a. The annual OC emission limitation, for the coatings employed in emissions units P006, P013 through P017, P021, P027, P028, P032 and P035, combined, shall not exceed 20.0 tons per year, based on a rolling, 12-month summation of the coating emissions. For purposes of clarification of non attainment new source review (NSR) permitting requirements and this Title V renewal permitting action, the permittee shall only employ non-VOC based cleanup materials. No cleanup materials with VOC as defined in OAC rule 3745-21-01 shall be employed. The emission of non-VOC based cleanup materials does not count towards the Synthetic Minor Determination to avoid the Emission Offset Policy for VOC established in PTI 14-05196.
 - b. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP); however, until the U. S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio.
- c) Operational Restrictions
- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3.0 gallons per day and 900 gallons per year.
[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]
 - (2) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.
[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]
 - (3) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.
[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]
 - (4) The permittee shall not employ volatile organic compound (VOC) cleanup materials as VOC is defined in OAC rule 3745-21-01.
[Authority for term: OAC rule 3745-77-07(A)(1)]
- d) Monitoring and/or Recordkeeping Requirements
- (1) The permittee shall collect and record the following information for each day for this emissions unit:
 - a. company identification for each coating (resin) and cleanup material employed;
 - b. number of pounds of each coating material employed;

Effective Date: To be entered upon final issuance

- c. the OC (styrene) content, recorded in percent by weight, of each coating employed in this emissions unit;
- d. total number of gallons of cleanup material employed;
- e. OC content of the cleanup material employed, in pounds per gallon;
- f. daily OC emissions from the cleanup material employed, in pounds [d)(1)d. multiplied by d)(1)e.];
- g. daily OC emissions from all coatings employed, in pounds [the summation d)(1)b. X d)(1)c. X 0.02* for all coatings employed during the day];
- h. number of hours this emissions unit was in operation;
- i. average hourly OC emission rate from all coatings, in pounds per hour [d)(1)g./d)(1)h.];
- j. a determination whether or not each cleanup material employed is a photochemically reactive material, as defined in OAC rule 3745-21-05(C)(5); and
- k. a determination whether or not each cleanup material employed is a volatile organic compound, as defined in OAC rule 3745-21-01.

[Note: The coating information must be for the coatings, as employed, including any thinning solvents added at the emissions unit].

* The 2% evaporation loss is the worst case emission factor for closed mold vapor suppressed resins specified in AP-42, Fifth Edition, Chapter 4.4, Polyester Resin Plastic Products Fabrication, Table 4.4-2, published January 1995.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:
 - a. total OC emissions from all the coatings employed, in tons [summation of d)(1)g. for all days of the calendar month, and divided by 2000 pounds per ton];
 - b. updated rolling, 12-month summation of OC emission from all the coatings employed, in tons [this shall include the total for the current month, plus the total for the preceding eleven calendar months]; and
 - c. rolling, 12-month summation of OC emissions from all the coatings employed, in tons, for emissions units P006, P013 through P017, P021, P027, P028, P032 and P035 combined.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)]

- (3) The permittee shall maintain monthly records of the following information for this emissions unit:
- a. total number of gallons of cleanup material employed [summation of d)(1)d. for all days of the calendar month];
 - b. total OC emissions from the cleanup material employed, in pounds [summation of d)(1)f. for all days of the calendar month];
 - c. the year-to-date total number of gallons of cleanup material employed [summation of the data from d)(3)a. for all months of the calendar year]; and
 - d. the year-to-date total OC emissions from the cleanup materials, in tons [summation of the data from d)(3)b. for all months of the calendar year, divided by 2000 pounds per ton].

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and 3745-21-07(G)(2)]

- (4) The permit to install for this emissions unit was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Styrene

TLV (mg/m³): 85,000

Maximum Hourly Emission Rate (lbs/hr): 125.5

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 1,857

MAGLC (ug/m³): 2,029

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled

"American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (5) If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (6) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05196: d)(1) through d)(5). The monitoring and recordkeeping requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
- a. daily cleanup material usage restriction;



Effective Date: To be entered upon final issuance

- b. OC content limitation for the cleanup material;
- c. daily OC emission limitation for the cleanup material;
- d. hourly OC emission limitation for coatings;
- e. daily OC emission limitation for coatings; and
- f. rolling, 12-month summation of OC emissions for emissions units P006, P013 through P017, P021, P027, P028, P032 and P035 combined.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

- (2) The permittee shall submit annual reports to the Hamilton County Department of Environmental Services that specify the rolling, 12-month summation of OC emissions for emissions units P006, P013 through P017, P021, P027, P028, P032 and P035 combined recorded in tons.

The reports shall be submitted by January 31 of each year and cover the previous calendar year.

[Authority for term: OAC rules 3745-77-07(C)(1)].

- (3) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05196: e)(1) through e)(2). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.

f) Testing Requirements

- (1) Compliance with the emission limitations and material usage restrictions specified in b) and c) shall be determined by the following methods:

- a. Emission Limitations:

- OC emissions shall not exceed 1.5 pounds per hour from coatings (resin);

- OC emissions shall not exceed 40 pounds per day from coatings (resin);

- OC emissions shall not exceed 20 tons per year (TPY) from coatings for emissions units P006, P013 through P017, P021, P027, P028, P032 and P035 combined, based on a rolling, 12-month summation of the coating emissions.

- Applicable Compliance Method:

- Compliance with the hourly OC emission limitation shall be determined by the record keeping requirements specified in d)(1). If required, the permittee shall demonstrate compliance with the hourly OC emission limitation through emission

Effective Date: To be entered upon final issuance

tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 – 4, 18 and 25.

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

b. Emission Limitations:

OC emissions shall not exceed 19.8 pounds per day from cleanup material.

OC emissions shall not exceed 2.97 tons per year from cleanup material.

Applicable Compliance Method:

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

c. Emission Limitation:

The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.

Applicable Compliance Method:

Compliance with the OC content limitation shall be determined by the record keeping requirements specified in d)(1). Formulation data or US EPA Method 24 shall be used to determine the OC content of any cleanup material employed in this emissions unit.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

d. Material Usage Restrictions:

The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3.0 gallons per day and 900 gallons per year.

Nonphotochemically reactive cleanup materials shall be employed.

Non-VOC based cleanup materials shall be employed.



Effective Date: To be entered upon final issuance

Applicable Compliance Method:

Compliance with the daily cleanup material usage and content restrictions shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual cleanup material usage restriction shall be determined by the recordkeeping requirements specified in d)(3).

Compliance with the Nonphotochemically reactive and Non-VOC cleanup material limitations shall be employed shall be determined by the recordkeeping requirements specified in d).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (2) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05196: f)(1)a. through f)(1)d. The testing requirements contained in the above-referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.

g) Miscellaneous Requirements

- (1) None.



2. P020, Main Spray Booth Gel Coat

Operations, Property and/or Equipment Description:

Manual Gel Coat Booth

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05196)	<p>The Organic Compound (OC) emissions from resin application shall not exceed 8 pounds per hour and 40 lbs/day.</p> <p>OC emissions (acetone) shall not exceed 9.9 pounds per day from cleanup materials.</p> <p>OC emissions (acetone) shall not exceed 1.8 tons per year from cleanup materials.</p> <p>Particulate emissions (PE) and Particulate matter with a diameter of 10 microns or less (PM-10) shall not exceed 0.81 pound per hour.</p> <p>PE/PM10 emissions shall not exceed 4.1 pounds per day.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(D) and 3745-17-07(A)(1).</p> <p>See c)(1) - c)(4).</p>
b.	OAC rule 3745-31-05(D)	<p>See b)(2)a.</p> <p>PE/PM10 emissions shall not exceed 0.51 tons per year based on a rolling, 12-month summation.</p>



Effective Date: To be entered upon final issuance

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
c.	OAC rule 3745-17-07(A)(1)	Visible particulate emissions from any stack shall not exceed 20% opacity, as a six minute average, except as specified by rule.
d.	OAC rule 3745-17-11(B)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
e.	OAC rule 3745-17-11(C)(3)	The Permit to Install for this emissions unit was issued July 9, 2002 (post January 1, 1990). Therefore, the emissions unit is exempt from the requirements of OAC rule 3745-17-11(C)(1) and (2). See b)(2)c.
f.	OAC rule 3745-21-07(G)(2)	The emission limitations specified by this rule are the same as the emission limitation established pursuant to OAC rule 3745-31-05(A)(3). See b)(2)d.
g.	40 CFR Part 63, Subpart WWWW (40 CFR 63.5780-5935) [In accordance with 63.5805(b), this emissions unit is an open molding gel coating application at an existing reinforced plastic composites production facility subject to the emission limitations and work practices specified in 40 CFR 63.5805(b)]	Table 3 to 40 CFR Part 63, Subpart WWWW – Organic Hazardous Air Pollutant (HAP) Emission Limits for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. See b)(2)b. and e. Table 4 to 40 CFR Part 63, Subpart WWWW – Applicable Work Practice Standards. See c)(5) and c)(6).
h.	40 CFR 63.1-15, Subpart A (40 CFR 63.5925)	Table 15 to 40 CFR Part 63, Subpart WWWW – Applicability of General Provisions (Subpart A) to Subpart WWWW shows which parts of the General Provisions in 40 CFR Part 63.1 – 15 apply.

(2) Additional Terms and Conditions

- a. The annual OC emission limit, for the coatings, employed in emissions units P018 through P020, combined shall not exceed 15.0 TPY, based on a rolling,



Effective Date: To be entered upon final issuance

12-month summation. For purposes of clarification of non attainment new source review (NSR) permitting requirements and this Title V renewal permitting action, the permittee shall only employ non-VOC based cleanup materials. No cleanup materials with VOC as defined in OAC rule 3745-21-01 shall be employed. The emission of non-VOC based cleanup materials does not count towards the Synthetic Minor Determination to avoid the Emission Offset Policy for VOC established in PTI 14-05196.

- b. The following organic HAP emission limitations shall not be exceeded based on a 12-month rolling average.

Gel Coat Type	Organic HAP Emission Limit
Tooling gel coating	440 lbs/ton
White/off white pigmented gel coating	267 lbs/ton
All other pigmented gel coating	377 lbs/ton
CR/HS or high performance gel coating	605 lbs/ton
Fire retardant gel coat	854 lbs/ton
Clear Production gel coat	522 lbs/ton

- c. On February 1, 2008, OAC rule 3745-17-11 was revised to include paragraph (C), pertaining to control requirements for particulate emissions from surface coating processes. These control requirements and the associated operational restrictions, monitoring, record keeping, and reporting requirements contained in this permit shall become federally enforceable on the date the U.S. EPA approves paragraph (C) of OAC rule 3745-17-11 as a revision to the Ohio State Implementation Plan.
- d. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP); however, until the U.S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio.
- e. This emissions unit is subject to the requirements of 40 CFR Part 63 Subpart WWWW - National Emissions Standards for Hazardous Air Pollutants for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. The permittee shall comply with the applicable emission limitations and operational restrictions specified in 40 CFR Part 63.5780 – 63.5930. The complete MACT requirements, including the MACT General Provisions may be accessed via the internet from the Electronic Code of Federal Regulations (e-CFR) website <http://ecfr.gpoaccess.gov> or by contacting the appropriate Ohio EPA District Office or local air agency.

c) Operational Restrictions

- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 1.5 gallons per day and 550 gallons per year.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (2) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 lbs of OC/gallon.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (3) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1), 3745-31-05(A)(3) and 3745-21-07(G)(2)]

- (4) The permittee shall operate the dry filtration system for the control of particulate emissions whenever this emissions unit is in operation and shall maintain the dry particulate filter in accordance with the manufacturer's recommendations, instructions, and/or operating manual(s), with any modifications deemed necessary by the permittee.

In the event the particulate filter system is not operating in accordance with the manufacturer's recommendations, instructions, or operating manual, with any modifications deemed necessary by the permittee, the control device shall be expeditiously repaired or otherwise returned to these documented operating conditions.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (5) The permittee shall employ only non-HAP-containing cleanup materials in each emissions unit, except that styrene may be used as a cleaner in closed systems, and organic HAP containing cleaners may be used to clean cured resin from application equipment. Application equipment includes any equipment that directly contacts resin.

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR Part 63, Subpart WWWW Table 4]

- (6) The permittee shall keep containers that store HAP-containing coating materials and cleanup materials closed or covered, except during the addition or removal of materials. Bulk HAP-containing materials storage tanks may be vented as necessary for safety.

[Authority for term: OAC rules 3745-77-07(A)(1) and 40 CFR Part 63, Subpart WWWW Table 4]

d) **Monitoring and/or Recordkeeping Requirements**

- (1) The permittee shall collect and record the following information each day this emissions unit is in operation:
 - a. company identification for each coating material (resin and/or gel coat) and cleanup material applied;
 - b. number of pounds of each coating material (resin and/or gel coat) applied;
 - c. the HAP content, recorded in percent by weight, of each coating material (resin and/or gel coat) employed in this emissions unit;

Effective Date: To be entered upon final issuance

- d. calculated OC (assumed equal to the organic HAP) emission factor using the equations to calculate organic HAP emission factors from Table 1 of 40 CFR Part 63, Subpart WWWW, in pounds of OC per ton of coating material (resin and/or gel coat) applied;
- e. total daily OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per day $[d)(1)b./2000 \times d)(1)d]$;
- f. number of hours the emissions unit was in operation;
- g. average hourly OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per hour $[d)(1)e. \text{ divided by } d)(1)f.]$;
- h. total number of gallons of cleanup material applied;
- i. OC content of the cleanup material employed, in pounds per gallon;
- j. daily OC emissions from the cleanup material employed, in pounds $[d)(1)h. \times d)(1)i.]$;
- k. total PE/PM10 emission rate for all coatings employed, in pounds per day $[\text{summation of } d)(1)b. \times (1 - \text{HAP content, percent by weight}) \times 0.25 \text{ (25\% overspray)} \times (1 - 0.985, \text{ the control efficiency of the dry filtration system})]**$;
- l. average hourly PE/PM10 emission rate for all coatings employed, in pounds/hour $[d)(1)k. \text{ divided by } d)(1)f.]$;
- m. a determination whether or not each cleanup material employed is a photochemically reactive material, as defined in OAC rule 3745-21-05(C)(5); and
- n. a determination whether or not each cleanup material employed is a non-HAP material, as identified in Section 112(b) of the Clean Air Act.

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit].

** The 25% overspray and 98.5% control efficiency were used to establish the PE/PM10 emission rates established in PTI 14-05196 and are based on conservative engineering assumptions.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D), 3745-21-07(G)(2), and 40 CFR Part 63 Subpart WWWW]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:
 - a. total OC emissions from all the coatings (resins and/or gel coat) employed, in tons $[\text{summation of } d)(1)e. \text{ for all days of the calendar month, and divided by } 2000 \text{ pounds per ton}]$;

Effective Date: To be entered upon final issuance

- b. updated rolling, 12-month summation of OC emission from all the coatings (resins and/or gel coats) employed, in tons [this shall include the total for the current month's OC emissions, plus the total for the preceding eleven calendar months];
- c. rolling, 12-month summation of OC emissions from all the coatings (resins and/or gel coats) employed, in tons, for emissions units P018 through P020;
- d. total PE/PM10 emissions for all coatings employed, in tons [summation of the data from d)(1)k. for all days of the calendar month divided by 2000 pounds per ton];
- e. rolling, 12-month summation of PE/PM10 emissions from all coatings employed, in tons [this shall include the total for the current month's PE/PM10 emissions, plus the total for the preceding eleven calendar months].

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and 3745-31-05(D)]

- (3) The permittee shall maintain annual records of the following information for this emissions unit:
- a. total number of gallons of cleanup material employed [summation of d)(1)h. for all days the emissions unit was in operation];
 - b. total OC emissions from cleanup materials employed, in pounds [summation of d)(1)j. for all days of the emissions unit was in operation].

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) The permittee shall operate and maintain metering equipment to measure the amount of all resins and gel coats used in each emissions unit. The permittee shall calibrate the metering equipment to measure the amount, in weight or volume, of all resins and gel coats used in each emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the metering equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the metering equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the metering equipment, the permittee shall perform calibration and accuracy tests on the metering equipment on a monthly basis during the first six months of operation of the meters. The permittee calibration and accuracy tests for the metering equipment shall include two resins (the highest and lowest density resins) and two gel coats (the highest and lowest density gel coats). After completing six months of calibration and accuracy tests of the metering equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (5) The permittee shall operate and maintain measuring equipment to measure the amount of cleanup materials employed in this emissions unit. The permittee shall calibrate the measuring equipment to measure the amount, in weight or volume, of all cleanup materials employed in this emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the measuring equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the measuring equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the measuring equipment, the permittee shall perform calibration and accuracy tests on the measuring equipment on a monthly basis during the first six months of operation of the measuring equipment. The permittee calibration and accuracy tests for the measuring equipment shall include the cleanup material employed by the permittee. After completing six months of calibration and accuracy tests of the measuring equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (6) The permittee shall utilize one or more compliance options, as specified in 40 CFR 63.5810 to demonstrate compliance with the emission standards for open molding in Table 3 of this subpart, as described in the following sections:

63.5810(a)	individual resin or gel coat compliance demonstration.
63.5810(b)	average individual organic HAP emissions limit compliance demonstration for all operations and application methods.
63.5810(c)	weighted average emission limit compliance demonstration.
63.5810(d)	organic HAP emission limit compliance demonstration for one resin type and application method.

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR 63.5810]

- (7) The permittee is currently demonstrating compliance through the option specified in 63.5810(a). The permittee shall comply with the following data collection, emission calculation, and record keeping requirements, in addition to those listed in d)(8) below:
- a. Calculate your actual organic HAP emissions factor for each different process stream within this emissions unit. A process stream is defined as each individual combination of resin or gel coat, application technique, and control technique. Process streams within operations types are considered different

from each other if any of the following four characteristics vary: the neat resin plus or neat gel coat plus organic HAP content, the gel coat type, the application technique, or the control technique. You must calculate organic HAP emissions factors for each different process stream by using the appropriate equations in Table 1 of 40 CFR Part 63 Subpart WWWW for open molding and for centrifugal casting, or site-specific organic HAP emissions factors discussed in §63.5796. The emission factor calculation should include any and all emission reduction techniques used. If you are using vapor suppressants to reduce HAP emissions, you must determine the vapor suppressant effectiveness (VSE) by conducting testing according to the procedures specified in appendix A to subpart WWWW of 40 CFR part 63.

Should the permittee choose to demonstrate compliance with the emission limitations listed in b)(2)b. by one of the alternative compliance demonstrations specified in d)(6), the permittee shall collect and record the information specified in 40 CFR 63.5810(b),(c), or (d), as appropriate.

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR 63.5810]

- (8) The permittee shall comply with the applicable monitoring and record keeping requirements under 40 CFR Part 63, Subpart WWWW, including the following sections:

63.5895(c) - (d)	records of resin and gel coat use, organic HAP content, operation and application method(s)
63.5915(a)	copy of compliance notification(s) and report(s)
63.5915(c)	records of all calculations and data used to determine organic HAP emissions factors or average organic HAP contents for operations and application methods as specified under 63.5810
63.5915(d)	certified statement of compliance with work practice requirements
63.5920(a) – (d)	record keeping format and retention requirements

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (9) The permittee shall maintain documentation of the manufacturer's recommendations, instructions, or operating manuals for the dry particulate filter, along with documentation of any modifications deemed necessary by the permittee. These documents shall be maintained at the facility and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

Effective Date: To be entered upon final issuance

- (10) The permittee shall conduct periodic inspections of the dry particulate filter to determine whether it is operating in accordance with the manufacturer's recommendations, instructions, or operating manuals with any modifications deemed necessary by the permittee or operator. These inspections shall be performed at a frequency that shall be based upon the recommendation of the manufacturer and the permittee shall maintain a copy of the manufacturer's recommended inspection frequency and it shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (11) In addition to the recommended periodic inspections, not less than once each calendar year the permittee shall conduct a comprehensive inspection of the dry particulate filter while the emissions unit is shut down and perform any needed maintenance and repair to ensure that it is operated in accordance with the manufacturer's recommendations.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (12) The permittee shall document each inspection (periodic and annual) of the dry particulate filter system and shall maintain the following information:

- a. the date of the inspection;
- b. a description of each/any problem identified and the date it was corrected;
- c. a description of any maintenance and repairs performed; and
- d. the name of person who performed the inspection.

These records shall be maintained at the facility for not less than five years from the date the inspection and any necessary maintenance or repairs were completed and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (13) The permittee shall maintain records that document any time periods when the dry particulate filter was not in service when the emissions unit(s) was/were in operation, as well as, a record of all operations during which the dry particulate filter was not operated according to the manufacturer's recommendations with any documented modifications made by the permittee. These records shall be maintained for a period of not less than five years and shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (14) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05196: d)(1) through d)(13). The monitoring and recordkeeping requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
 - a. daily cleanup material usage restriction;
 - b. OC content limitation for the cleanup material;
 - c. daily OC emission limitation for the cleanup material;
 - d. hourly OC emission limitation for coatings;
 - e. daily OC emission limitation for coatings;
 - f. hourly PE/PM10 emission limitation;
 - g. daily PE/PM10 emission limitation;
 - h. rolling 12-month emission limitation for PE/PM10;
 - i. rolling 12-month combined OC emission limitation for P018-P020; and
 - j. any daily record showing that the dry particulate filter system was not in service or not operated according to manufacturer's recommendations (with any documented modifications made by the permittee) when the emissions unit(s) was/were in operation.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

- (2) The permittee shall submit annual reports to the Hamilton County Department of Environmental Services that specify the following:
 - a. total amount, in gallons, of cleanup material employed for the calendar year;
 - b. total OC emissions from the cleanup material employed, in tons, for the calendar year; and
 - c. rolling, 12-month summation of OC emissions from emissions units P018 through P020, combined, for each calendar month.

This report shall be submitted by January 31 of each year and cover the previous calendar year.

[Authority for term: OAC rules 3745-77-07(C)(1)].

- (3) The permittee shall notify the Hamilton County Department of Environmental Services in writing of each day during which any photochemically reactive cleanup material [as defined in OAC rule 3745-21-01(C)(5)] was employed in this emissions unit. The notification shall include a copy of such record and shall be sent to the Hamilton County Department of Environmental Services within 45 days after the exceedance occurs.



Effective Date: To be entered upon final issuance

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) Upon replacement and/or initial operation of any metering or measuring equipment as specified in d)(4) and d)(5) of this permit, the permittee shall provide the Hamilton County Department of Environmental Services the following information: the name of the manufacturer of the metering/measuring equipment, the make and model of the metering/measuring equipment, calibration data (e.g., volume of coating per pump stroke), a copy of the manufacturer's specifications and warranty for the accuracy of the metering/measuring equipment and the actual accuracy of the material measurements (by weight or by volume) recorded for the metering/measuring equipment.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (5) The permittee shall submit calibration and accuracy test results for the metering equipment and measuring equipment specified in d)(4) and d)(5) of the terms and conditions of this permit. The calibration and accuracy tests results shall be submitted to the Hamilton County Department of Environmental Services by January 30 and July 30 of each calendar year, and shall cover the previous six-month period.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (6) The permittee shall submit semi-annual reports and such other notifications and reports to the Hamilton County Department of Environmental Services as are required in 40 CFR Part 63, Subpart WWWW, pursuant to the following sections:

63.5905(b)	15-day notification of change(s)
63.5910(a) - (b) and Table 14	semi-annual compliance reports
63.5910(c) - (i) and Table 14	content of semi-annual compliance reports

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (7) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05196: e)(1) through e)(6). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.

f) Testing Requirements

- (1) Compliance with the emission limitations and material usage restrictions specified in b) and c) shall be determined by the following methods:

a. Emission Limitations:

OC emissions shall not exceed 8 pounds per hour from coatings (resin and gel coat);

Effective Date: To be entered upon final issuance

OC emissions shall not exceed 40 pounds per day from coatings (resin and gel coat); and

OC emissions shall not exceed 15.0 tons per year (TPY) from coatings (resins and gel coats) for emissions units P018 through P020, combined, based on a rolling, 12-month summation of the coating emissions.

Applicable Compliance Method:

Compliance with the hourly OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly OC emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 – 4, 18 and 25.

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), OAC rule 3745-31-05(A)(3), 3745-31-05(D), and 3745-21-07(G)(2)].

b. Emission Limitations:

OC emissions shall not exceed 9.9 pounds per day from cleanup materials

OC emissions shall not exceed 1.8 tons per year from cleanup materials.

Applicable Compliance Method:

Compliance with the daily OC emission limitation from cleanup materials shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation from cleanup material shall be determined by the record keeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)].

c. Emission Limitation:

The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.

Applicable Compliance Method:

Compliance with the OC content limitation shall be determined by the record keeping requirements specified in d)(1). Formulation data or US EPA Method 24 shall be used to determine the OC content of any cleanup material employed in this emissions unit.



[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

d. Material Usage Restriction:

The maximum amount of all cleanup material employed in this emissions unit shall not exceed 1.5 gallons per day and 550 gallons per year.

Applicable Compliance Method:

Compliance with the daily cleanup material usage restriction shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual cleanup material usage restriction shall be determined by the recordkeeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

e. Emission Limitation:

See the organic HAP emission limitations noted in b)(2)b.

Applicable Compliance Method:

Compliance with the organic HAP emission limitation shall be based upon the information collected and recorded in d)(6) - d)(8) of this permit.

[Authority for term: OAC rules 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

f. Emission Limitations:

PE/PM-10 emissions shall not exceed 0.81 pound per hour;

PE/PM-10 emissions shall not exceed 4.1 pounds per day; and

PE/PM-10 emissions shall not exceed 0.51 ton per year, based on a rolling, 12-month summation.

Applicable Compliance Method:

Compliance with the hourly PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly PE/PM10 emission limitation through emission tests performed in accordance with 40 CFR, Part 60, Appendix A, Methods 1-5.

Compliance with the daily PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(2).



[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and OAC 3745-31-05(D)].

- (2) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05196: f)(1)a. through f)(1)f. The testing requirements contained in the above-referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.
- g) Miscellaneous Requirements
 - (1) None.



3. P022, Robot (Venus) Gel Coat Booth

Operations, Property and/or Equipment Description:

Robotic Gel Coat Applicator Booth

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05223)	Particulate emissions (PE) and Particulate matter with a diameter of 10 microns or less (PM-10) shall not exceed 0.39 pound per hour. PE/PM10 emissions shall not exceed 6.07 pounds per day. PE/PM10 emissions shall not exceed 0.60 TPY. The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(D), 3745-21-07(G)(9)(g), and 3745-17-07(A)(1). See c)(1) - c)(8).
b.	OAC rule 3745-31-05(D) Synthetic Minor Determination to avoid the Emission Offset Policy for VOC.	See b)(2)a.
c.	OAC rule 3745-17-07(A)(1)	Visible particulate emissions from any stack shall not exceed 20% opacity, as a six minute average, except as specified by rule.
d.	OAC rule 3745-17-11(B)	The emission limitation specified by this rule is less stringent than the emission



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		limitation established pursuant to OAC rule 3745-31-05(A)(3).
e.	OAC rule 3745-17-11(C)(3)	<p>The Permit to Install for this emissions unit was issued July 9, 2002 (post January 1, 1990). Therefore, the emissions unit is exempt from the requirements of OAC rule 3745-17-11(C)(1) and (2).</p> <p>See b)(2)c.</p>
f.	OAC rule 3745-21-07(G)(9)(g)	<p>The Organic Compound (OC) emissions from resin application shall not exceed 10 pounds per hour and 157 lbs/day.</p> <p>OC (acetone) emissions shall not exceed 13.2 pounds per day from cleanup materials.</p> <p>OC (acetone) emissions shall not exceed 1.16 tons per year from cleanup materials.</p> <p>See b)(2)d.</p>
g.	<p>40 CFR Part 63, Subpart WWWW (40 CFR 63.5780-5935)</p> <p>[In accordance with 63.5805(b), this emissions unit is an open molding gel coating application at an existing reinforced plastic composites production facility subject to the emission limitations and work practices specified in 40 CFR 63.5805(b)]</p>	<p>Table 3 to 40 CFR Part 63, Subpart WWWW – Organic Hazardous Air Pollutant (HAP) Emission Limits for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations.</p> <p>See b)(2)b. and e.</p> <p>Table 4 to 40 CFR Part 63, Subpart WWWW – Applicable Work Practice Standards.</p> <p>See c)(10) and c)(11).</p>
h.	40 CFR 63.1-15, Subpart A (40 CFR 63.5925)	Table 15 to 40 CFR Part 63, Subpart WWWW – Applicability of General Provisions (Subpart A) to Subpart WWWW shows which parts of the General Provisions in 40 CFR Part 63.1 – 15 apply.

(2) Additional Terms and Conditions

a. Organic Compound (OC) emissions shall not exceed 15.5 TPY from coatings, based on a rolling 12-month summation. For purposes of clarification of non attainment new source review (NSR) permitting requirements and this Title V renewal permitting action, the permittee shall only employ non-VOC based cleanup materials. No cleanup materials with VOC as defined in OAC rule 3745-21-01 shall be employed. The emission of non-VOC based cleanup materials does not count towards the Synthetic Minor Determination to avoid the Emission Offset Policy for VOC established in PTI 14-05223.

b. The following organic HAP emission limitations shall not be exceeded based on a 12-month rolling average.

Gel Coat Type	Organic HAP Emission Limit
Tooling gel coating	440 lbs/ton
White/off white pigmented gel coating	267 lbs/ton
All other pigmented gel coating	377 lbs/ton
CR/HS or high performance gel coating	605 lbs/ton
Fire retardant gel coat	854 lbs/ton
Clear Production gel coat	522 lbs/ton

c. On February 1, 2008, OAC rule 3745-17-11 was revised to include paragraph (C), pertaining to control requirements for particulate emissions from surface coating processes. These control requirements and the associated operational restrictions, monitoring, record keeping, and reporting requirements contained in this permit shall become federally enforceable on the date the U.S. EPA approves paragraph (C) of OAC rule 3745-17-11 as a revision to the Ohio State Implementation Plan.

d. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP); however, until the U.S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio. The requirements of OAC 3745-21-07(G)(9)(g) have been carried over into 3745-21-07(M)(5)(e). Therefore, no change in emission limitations or terms and conditions will take place after the SIP is modified.

e. This emissions unit is subject to the requirements of 40 CFR Part 63 Subpart WWWW - National Emissions Standards for Hazardous Air Pollutants for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. The permittee shall comply with the applicable emission limitations and operational restrictions specified in 40 CFR Part 63.5780 – 63.5930. The complete MACT requirements, including the MACT General Provisions may be accessed via the internet from the Electronic Code

of Federal Regulations (e-CFR) website <http://ecfr.gpoaccess.gov> or by contacting the appropriate Ohio EPA District Office or local air agency.

c) Operational Restrictions

- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 2.0 gallons per day and 350 gallons per year.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (2) The styrene content of the gel coats (gel coat is a polyester resin surface coating, either pigmented or clear, that provides a cosmetic enhancement and improves resistance to degradation from exposure to the elements) shall not exceed the following limitations:

- a. 50%, by weight, as applied for each clear gel coat; and (clear gel coat is gel coat without pigment); and
- b. 45%, by weight, as applied for each pigmented gel coat (pigmented gel coat is clear gel coat with pigments added).

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (3) The amount of gel coat used in this emissions unit shall not exceed 144 pounds per hour, 2,248 pounds per day and 220.95 tons per year. The tons per year limitation is based upon a rolling, 12-month summation.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (4) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (5) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01, in this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (6) The permittee shall operate the dry filtration system for the control of particulate emissions whenever this emissions unit is in operation and shall maintain the dry particulate filter in accordance with the manufacturer's recommendations, instructions, and/or operating manual(s), with any modifications deemed necessary by the permittee.

In the event the particulate filter system is not operating in accordance with the manufacturer's recommendations, instructions, or operating manual, with any modifications deemed necessary by the permittee, the control device shall be expeditiously repaired or otherwise returned to these documented operating conditions.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (7) The permittee shall electronically monitor the amount of coating pumped by this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (8) The permittee shall only utilize robotic application equipment in this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (9) The permittee shall employ only non-HAP-containing cleanup materials in each emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3), and 40 CFR Part 63, Subpart WWWW Table 4]

- (10) The permittee shall keep containers that store HAP-containing coating materials and cleanup materials closed or covered, except during the addition or removal of materials.

[Authority for term: OAC rules 3745-77-07(A)(1), 3745-31-05(A)(3), and 40 CFR Part 63, Subpart WWWW Table 4]

d) **Monitoring and/or Recordkeeping Requirements**

- (1) The permittee shall collect and record the following information each day this emissions unit is in operation:
- a. company identification for each coating material (resin and/or gel coat) and cleanup material applied;
 - b. number of pounds of each coating material (resin and/or gel coat) applied;
 - c. the HAP content, recorded in percent by weight, of each coating material (resin and/or gel coat) employed in this emissions unit;
 - d. calculated OC (assumed equal to the organic HAP) emission factor using the equations to calculate organic HAP emission factors from Table 1 of 40 CFR Part 63, Subpart WWWW, in pounds of OC per ton of coating material (resin and/or gel coat) applied;
 - e. total daily OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per day $[d)(1)b./2000 \times d)(1)d.]$;
 - f. number of hours the emissions unit was in operation;
 - g. average hourly OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per hour $[d)(1)e. \text{ divided by } d)(1)f.]$.
 - h. total number of gallons of cleanup material applied;
 - i. OC content of the cleanup material employed, in pounds per gallon;
 - j. daily OC emissions from the cleanup material employed, in pounds $[d)(1)h. \times d)(1)i.]$;

Effective Date: To be entered upon final issuance

- k. total PE/PM10 emission rate for all coatings employed, in pounds per day [summation of d)(1)b. x (1 - HAP content, percent by weight) x 0.25 (25% overspray) x (1 - 0.985, the control efficiency of the dry filtration system)]**;
- l. average hourly PE/PM10 emission rate for all coatings employed, in pounds/hour [d)(1)k. divided by d)(1)f.];
- m. a determination whether or not each cleanup material employed is a photochemically reactive material, as defined in OAC rule 3745-21-05(C)(5); and
- n. a determination whether or not each cleanup material employed is a non-HAP material, as identified in Section 112(b) of the Clean Air Act.

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit].

** The 25% overspray and 98.5% control efficiency were used to establish the PE/PM10 emission rates established in PTI 14-05223 and are based on conservative engineering assumptions.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D), 3745-21-07(G)(2), and 40 CFR Part 63 Subpart WWWW]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:
 - a. total OC emissions from all the coatings (resins and/or gel coat) employed, in tons [summation of d)(1)e. for all days of the calendar month, and divided by 2000 pounds per ton];
 - b. updated rolling, 12-month summation of OC emission from all the coatings (resins and/or gel coats) employed, in tons [this shall include the total for the current month's OC emissions, plus the total for the preceding eleven calendar months];
 - c. total PE/PM10 emissions for all coatings employed, in tons [summation of the data from d)(1)k. for all days of the calendar month divided by 2000 pounds per ton];
 - d. rolling, 12-month summation of PE/PM10 emissions from all coatings employed, in tons [this shall include the total for the current month's PE/PM10 emissions, plus the total for the preceding eleven calendar months]; and
 - e. rolling, 12-month summation of all coatings employed, in tons [this shall include the total for the current month, plus the total for the preceding eleven calendar months].

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and 3745-31-05(D)]

- (3) The permittee shall maintain annual records of the following information for this emissions unit:

Effective Date: To be entered upon final issuance

- a. total number of gallons of cleanup material employed [summation of d)(1)h. for all days the emissions unit was in operation];
- b. total OC emissions from cleanup materials employed, in pounds [summation of d)(1)j. for all days of the emissions unit was in operation].

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) The permittee shall operate and maintain metering equipment to measure the amount of all resins and gel coats used in each emissions unit. The permittee shall calibrate the metering equipment to measure the amount, in weight or volume, of all resins and gel coats used in each emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the metering equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the metering equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the metering equipment, the permittee shall perform calibration and accuracy tests on the metering equipment on a monthly basis during the first six months of operation of the meters. The permittee calibration and accuracy tests for the metering equipment shall include two resins (the highest and lowest density resins) and two gel coats (the highest and lowest density gel coats). After completing six months of calibration and accuracy tests of the metering equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (5) The permittee shall operate and maintain measuring equipment to measure the amount of cleanup materials employed in this emissions unit. The permittee shall calibrate the measuring equipment to measure the amount, in weight or volume, of all cleanup materials employed in this emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the measuring equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the measuring equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the measuring equipment, the permittee shall perform calibration and accuracy tests on the measuring equipment on a monthly basis during the first six months of operation of the measuring equipment. The permittee calibration and accuracy tests for the measuring equipment shall include the cleanup material employed by the permittee. After completing six months of calibration and accuracy tests of the measuring equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (6) The permittee shall utilize one or more compliance options, as specified in 40 CFR 63.5810 to demonstrate compliance with the emission standards for open molding in Table 3 of this subpart, as described in the following sections:

63.5810(a)	individual resin or gel coat compliance demonstration
63.5810(b)	average individual organic HAP emissions limit compliance demonstration for all operations and application methods
63.5810(c)	weighted average emission limit compliance demonstration
63.5810(d)	organic HAP emission limit compliance demonstration for one resin type and application method

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR 63.5810]

- (7) The permittee is currently demonstrating compliance through the option specified in 63.5810(a). The permittee shall comply with the following data collection, emission calculation, and record keeping requirements, in addition to those listed in d)(8) below:

- a. Calculate your actual organic HAP emissions factor for each different process stream within this emissions unit. A process stream is defined as each individual combination of resin or gel coat, application technique, and control technique. Process streams within operations types are considered different from each other if any of the following four characteristics vary: the neat resin plus or neat gel coat plus organic HAP content, the gel coat type, the application technique, or the control technique. You must calculate organic HAP emissions factors for each different process stream by using the appropriate equations in Table 1 of 40 CFR Part 63 Subpart WWWW for open molding and for centrifugal casting, or site-specific organic HAP emissions factors discussed in §63.5796. The emission factor calculation should include any and all emission reduction techniques used. If you are using vapor suppressants to reduce HAP emissions, you must determine the vapor suppressant effectiveness (VSE) by conducting testing according to the procedures specified in appendix A to subpart WWWW of 40 CFR part 63.

Should the permittee choose to demonstrate compliance with the emission limitations listed in b)(2)b. by one of the alternative compliance demonstrations specified in d)(6), the permittee shall collect and record the information specified in 40 CFR 63.5810(b), (c), or (d), as appropriate.

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR 63.5810]

- (8) The permittee shall comply with the applicable monitoring and record keeping requirements under 40 CFR Part 63, Subpart WWWW, including the following sections:

63.5895(c) - (d)	records of resin and gel coat use, organic HAP content, operation and application method(s)
------------------	---



63.5915(a)	copy of compliance notification(s) and report(s)
63.5915(c)	records of all calculations and data used to determine organic HAP emissions factors or average organic HAP contents for operations and application methods as specified under 63.5810
63.5915(d)	certified statement of compliance with work practice requirements
63.5920(a) – (d)	record keeping format and retention requirements

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (9) The permittee shall maintain documentation of the manufacturer's recommendations, instructions, or operating manuals for the dry particulate filter, along with documentation of any modifications deemed necessary by the permittee. These documents shall be maintained at the facility and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (10) The permittee shall conduct periodic inspections of the dry particulate filter to determine whether it is operating in accordance with the manufacturer's recommendations, instructions, or operating manuals with any modifications deemed necessary by the permittee or operator. These inspections shall be performed at a frequency that shall be based upon the recommendation of the manufacturer and the permittee shall maintain a copy of the manufacturer's recommended inspection frequency and it shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (11) In addition to the recommended periodic inspections, not less than once each calendar year the permittee shall conduct a comprehensive inspection of the dry particulate filter while the emissions unit is shut down and perform any needed maintenance and repair to ensure that it is operated in accordance with the manufacturer's recommendations.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (12) The permittee shall document each inspection (periodic and annual) of the dry particulate filter system and shall maintain the following information:
 - a. the date of the inspection;
 - b. a description of each/any problem identified and the date it was corrected;
 - c. a description of any maintenance and repairs performed; and
 - d. the name of person who performed the inspection.

These records shall be maintained at the facility for not less than five years from the date the inspection and any necessary maintenance or repairs were completed and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (13) The permittee shall maintain records that document any time periods when the dry particulate filter was not in service when the emissions unit(s) was/were in operation, as well as, a record of all operations during which the dry particulate filter was not operated according to the manufacturer's recommendations with any documented modifications made by the permittee. These records shall be maintained for a period of not less than five years and shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (14) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05223: d)(1) through d)(13). The monitoring and recordkeeping requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
- a. daily cleanup material usage restriction;
 - b. OC content limitation for the cleanup material;
 - c. daily OC emission limitation for the cleanup material;
 - d. hourly OC emission limitation for coatings;
 - e. daily OC emission limitation for coatings;
 - f. hourly PE/PM10 emission limitation;
 - g. daily PE/PM10 emission limitation;
 - h. rolling 12-month emission limitation for PE/PM10;
 - i. the hourly gel coat usage limitation;
 - j. the daily get coat usage limitation;
 - k. rolling 12-month gel coat usage limitation; and
 - l. any daily record showing that the dry particulate filter system was not in service or not operated according to manufacturer's recommendations (with any documented modifications made by the permittee) when the emissions unit(s) was/were in operation.



Effective Date: To be entered upon final issuance

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

- (2) The permittee shall submit annual reports to the Hamilton County Department of Environmental Services that specify the following:
 - a. total amount, in gallons, of cleanup material employed for the calendar year;
 - b. total OC emissions from the cleanup material employed, in tons, for the calendar year; and
 - c. rolling, 12-month summation of OC emissions from this emissions unit, for each calendar month.

This report shall be submitted by January 31 of each year and cover the previous calendar year.

[Authority for term: OAC rules 3745-77-07(C)(1)].

- (3) The permittee shall notify the Hamilton County Department of Environmental Services in writing of each day during which any photochemically reactive cleanup material [as defined in OAC rule 3745-21-01(C)(5)] was employed in this emissions unit. The notification shall include a copy of such record and shall be sent to the Hamilton County Department of Environmental Services within 45 days after the exceedance occurs.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) Upon replacement and/or initial operation of any metering or measuring equipment as specified in d)(4) and d)(5) of this permit, the permittee shall provide the Hamilton County Department of Environmental Services the following information: the name of the manufacturer of the metering/measuring equipment, the make and model of the metering/measuring equipment, calibration data (e.g., volume of coating per pump stroke), a copy of the manufacturer's specifications and warranty for the accuracy of the metering/measuring equipment and the actual accuracy of the material measurements (by weight or by volume) recorded for the metering/measuring equipment.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (5) The permittee shall submit calibration and accuracy test results for the metering equipment and measuring equipment specified in d)(4) and d)(5) of the terms and conditions of this permit. The calibration and accuracy tests results shall be submitted to the Hamilton County Department of Environmental Services by January 30 and July 30 of each calendar year, and shall cover the previous six-month period.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (6) The permittee shall submit semi-annual reports and such other notifications and reports to the Hamilton County Department of Environmental Services as are required in 40 CFR Part 63, Subpart WWWW, pursuant to the following sections:

63.5905(b)	15-day notification of change(s)
------------	----------------------------------



Effective Date: To be entered upon final issuance

63.5910(a) - (b) and Table 14	semi-annual compliance reports
63.5910(c) - (i) and Table 14	content of semi-annual compliance reports

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

(7) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05223: e)(1) through e)(6). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.

f) Testing Requirements

(1) Compliance with the emission limitations and material usage restrictions specified in b) and c) shall be determined by the following methods:

a. Emission Limitations:

OC emissions shall not exceed 10 pounds per hour from coatings (resin and gel coat);

OC emissions shall not exceed 157 pounds per day from coatings (resin and gel coat); and

OC emissions shall not exceed 15.5 tons per year (TPY) from coatings (resins and gel coats) for this emissions units, based on a rolling, 12-month summation of the coating emissions.

Applicable Compliance Method:

Compliance with the hourly OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly OC emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 – 4, 18 and 25.

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), OAC rule 3745-31-05(A)(3), 3745-31-05(D), and 3745-21-07(G)(2)].

b. Emission Limitations:

OC emissions shall not exceed 13.2 pounds per day from cleanup materials; and

OC emissions shall not exceed 1.16 tons per year from cleanup materials.

Applicable Compliance Method:

Compliance with the daily OC emission limitation from cleanup materials shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation from cleanup material shall be determined by the record keeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)].

c. Emission Limitation:

The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.

Applicable Compliance Method:

Compliance with the OC content limitation shall be determined by the record keeping requirements specified in d)(1). Formulation data or US EPA Method 24 shall be used to determine the OC content of any cleanup material employed in this emissions unit.

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

d. Material Usage Restriction:

The maximum amount of all cleanup material employed in this emissions unit shall not exceed 2 gallons per day and 350 gallons per year.

Applicable Compliance Method:

Compliance with the daily cleanup material usage restriction shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual cleanup material usage restriction shall be determined by the recordkeeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

e. Emission Limitation:

See the organic HAP emission limitations noted in b)(2)b.

Applicable Compliance Method:

Compliance with the organic HAP emission limitation shall be based upon the information collected and recorded in d)(6) - d)(8) of this permit.

[Authority for term: OAC rules 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]



Effective Date: To be entered upon final issuance

f. Emission Limitations:

PE/PM-10 emissions shall not exceed 0.39 pound per hour;

PE/PM-10 emissions shall not exceed 6.07 pounds per day; and

PE/PM-10 emissions shall not exceed 0.60 tons per year.

Applicable Compliance Method:

Compliance with the hourly PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly PE/PM10 emission limitation through emission tests performed in accordance with 40 CFR, Part 60, Appendix A, Methods 1-5.

Compliance with the daily PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and OAC 3745-31-05(D)].

- (2) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05223: f)(1)a. through f)(1)f. The testing requirements contained in the above-referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.

g) Miscellaneous Requirements

- (1) None.



4. P025, Main Spray Booth Gel Coat - 2

Operations, Property and/or Equipment Description:

Main Gel Coat Spray Booth 2

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05196)	The Organic Compound (OC) emissions from resin application shall not exceed 8 pounds per hour and 40 lbs/day. OC emissions (acetone) shall not exceed 3.3 pounds per day from cleanup materials. OC emissions (acetone) shall not exceed 0.495 ton per year from cleanup materials. Particulate emissions (PE) and Particulate matter with a diameter of 10 microns or less (PM-10) shall not exceed 0.28 pound per hour. PE/PM10 emissions shall not exceed 1.38 pounds per day. The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(D) and 3745-17-07(A)(1). See c)(1) - c)(4).
b.	OAC rule 3745-31-05(D) Synthetic Minor Determination to avoid the Emission Offset Policy for	See b)(2)a. PE/PM10 emissions shall not exceed 0.18 ton per year based on a rolling, 12-



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
	VOC.	month summation.
c.	OAC rule 3745-17-07(A)(1)	Visible particulate emissions from any stack shall not exceed 20% opacity, as a six minute average, except as specified by rule.
d.	OAC rule 3745-17-11(B)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
e.	OAC rule 3745-17-11(C)(3)	The Permit to Install for this emissions unit was issued July 9, 2002 (post January 1, 1990). Therefore, the emissions unit is exempt from the requirements of OAC rule 3745-17-11(C)(1) and (2). See b)(2)c.
f.	OAC rule 3745-21-07(G)(2)	The emission limitations specified by this rule are the same as the emission limitation established pursuant to OAC rule 3745-31-05(A)(3). See b)(2)d.
g.	40 CFR Part 63, Subpart WWWW (40 CFR 63.5780-5935) [In accordance with 63.5805(b), this emissions unit is an open molding gel coating application at an existing reinforced plastic composites production facility subject to the emission limitations and work practices specified in 40 CFR 63.5805(b)]	Table 3 to 40 CFR Part 63, Subpart WWWW – Organic Hazardous Air Pollutant (HAP) Emission Limits for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. See b)(2)b. and e. Table 4 to 40 CFR Part 63, Subpart WWWW – Applicable Work Practice Standards. See c)(5) and c)(6).
h.	40 CFR 63.1-15, Subpart A (40 CFR 63.5925)	Table 15 to 40 CFR Part 63, Subpart WWWW – Applicability of General Provisions (Subpart A) to Subpart WWWW shows which parts of the General Provisions in 40 CFR Part 63.1 – 15 apply.

(2) Additional Terms and Conditions

a. The annual OC emission limit, for the coatings employed in this emissions unit shall not exceed 7.0 TPY, based on a rolling, 12-month summation. For purposes of clarification of non attainment new source review (NSR) permitting requirements and this Title V renewal permitting action, the permittee shall only employ non-VOC based cleanup materials. No cleanup materials with VOC as defined in OAC rule 3745-21-01 shall be employed. The emission of non-VOC based cleanup materials does not count towards the Synthetic Minor Determination to avoid the Emission Offset Policy for VOC established in PTI 14-05196.

b. The following organic HAP emission limitations shall not be exceeded based on a 12-month rolling average.

Gel Coat Type	Organic HAP Emission Limit
Tooling gel coating	440 lbs/ton
White/off white pigmented gel coating	267 lbs/ton
All other pigmented gel coating	377 lbs/ton
CR/HS or high performance gel coating	605 lbs/ton
Fire retardant gel coat	854 lbs/ton
Clear Production gel coat	522 lbs/ton

c. On February 1, 2008, OAC rule 3745-17-11 was revised to include paragraph (C), pertaining to control requirements for particulate emissions from surface coating processes. These control requirements and the associated operational restrictions, monitoring, record keeping, and reporting requirements contained in this permit shall become federally enforceable on the date the U.S. EPA approves paragraph (C) of OAC rule 3745-17-11 as a revision to the Ohio State Implementation Plan.

d. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP); however, until the U.S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio.

e. This emissions unit is subject to the requirements of 40 CFR Part 63 Subpart WWWW - National Emissions Standards for Hazardous Air Pollutants for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. The permittee shall comply with the applicable emission limitations and operational restrictions specified in 40 CFR Part 63.5780 – 63.5930. The complete MACT requirements, including the MACT General Provisions may be accessed via the internet from the Electronic Code of Federal Regulations (e-CFR) website <http://ecfr.gpoaccess.gov> or by contacting the appropriate Ohio EPA District Office or local air agency.

c) Operational Restrictions

- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 0.5 gallon per day and 150 gallons per year.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (2) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 lbs of OC/gallon.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (3) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1), 3745-31-05(A)(3) and 3745-21-07(G)(2)]

- (4) The permittee shall operate the dry filtration system for the control of particulate emissions whenever this emissions unit is in operation and shall maintain the dry particulate filter in accordance with the manufacturer's recommendations, instructions, and/or operating manual(s), with any modifications deemed necessary by the permittee.

In the event the particulate filter system is not operating in accordance with the manufacturer's recommendations, instructions, or operating manual, with any modifications deemed necessary by the permittee, the control device shall be expeditiously repaired or otherwise returned to these documented operating conditions.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (5) The permittee shall employ only non-HAP-containing cleanup materials in each emissions unit, except that styrene may be used as a cleaner in closed systems, and organic HAP containing cleaners may be used to clean cured resin from application equipment. Application equipment includes any equipment that directly contacts resin.

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR Part 63, Subpart WWWW Table 4]

- (6) The permittee shall keep containers that store HAP-containing coating materials and cleanup materials closed or covered, except during the addition or removal of materials. Bulk HAP-containing materials storage tanks may be vented as necessary for safety.

[Authority for term: OAC rules 3745-77-07(A)(1) and 40 CFR Part 63, Subpart WWWW Table 4]

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall collect and record the following information each day this emissions unit is in operation:

- a. company identification for each coating material (resin and/or gel coat) and cleanup material applied;

Effective Date: To be entered upon final issuance

- b. number of pounds of each coating material (resin and/or gel coat) applied;
- c. the HAP content, recorded in percent by weight, of each coating material (resin and/or gel coat) employed in this emissions unit;
- d. calculated OC (assumed equal to the organic HAP) emission factor using the equations to calculate organic HAP emission factors from Table 1 of 40 CFR Part 63, Subpart WWWW, in pounds of OC per ton of coating material (resin and/or gel coat) applied;
- e. total daily OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per day $[d)(1)b./2000 \times d)(1)d.]$;
- f. number of hours the emissions unit was in operation;
- g. average hourly OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per hour $[d)(1)e. \text{ divided by } d)(1)f.]$.
- h. total number of gallons of cleanup material applied;
- i. OC content of the cleanup material employed, in pounds per gallon;
- j. daily OC emissions from the cleanup material employed, in pounds $[d)(1)h. \times d)(1)i.]$;
- k. total PE/PM10 emission rate for all coatings employed, in pounds per day $[\text{summation of } d)(1)b. \times (1 - \text{HAP content, percent by weight}) \times 0.25 \text{ (25\% overspray)} \times (1 - 0.985, \text{ the control efficiency of the dry filtration system})]^{**}$;
- l. average hourly PE/PM10 emission rate for all coatings employed, in pounds/hour $[d)(1)k. \text{ divided by } d)(1)f.]$;
- m. a determination whether or not each cleanup material employed is a photochemically reactive material, as defined in OAC rule 3745-21-05(C)(5); and
- n. a determination whether or not each cleanup material employed is a non-HAP material, as identified in Section 112(b) of the Clean Air Act.

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit].

** The 25% overspray and 98.5% control efficiency were used to establish the PE/PM10 emission rates established in PTI 14-05196 and are based on conservative engineering assumptions.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D), 3745-21-07(G)(2), and 40 CFR Part 63 Subpart WWWW]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:

Effective Date: To be entered upon final issuance

- a. total OC emissions from all the coatings (resins and/or gel coat) employed, in tons [summation of d)(1)e. for all days of the calendar month, and divided by 2000 pounds per ton];
- b. updated rolling, 12-month summation of OC emission from all the coatings (resins and/or gel coats) employed, in tons [this shall include the total for the current month's OC emissions, plus the total for the preceding eleven calendar months];
- c. total PE/PM10 emissions for all coatings employed, in tons [summation of the data from d)(1)k. for all days of the calendar month divided by 2000 pounds per ton]; and
- d. rolling, 12-month summation of PE/PM10 emissions from all coatings employed, in tons [this shall include the total for the current month's PE/PM10 emissions, plus the total for the preceding eleven calendar months].

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and 3745-31-05(D)]

- (3) The permittee shall maintain annual records of the following information for this emissions unit:
 - a. total number of gallons of cleanup material employed [summation of d)(1)h. for all days the emissions unit was in operation];
 - b. total OC emissions from cleanup materials employed, in pounds [summation of d)(1)j. for all days of the emissions unit was in operation].

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) The permittee shall operate and maintain metering equipment to measure the amount of all resins and gel coats used in each emissions unit. The permittee shall calibrate the metering equipment to measure the amount, in weight or volume, of all resins and gel coats used in each emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the metering equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the metering equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the metering equipment, the permittee shall perform calibration and accuracy tests on the metering equipment on a monthly basis during the first six months of operation of the meters. The permittee calibration and accuracy tests for the metering equipment shall include two resins (the highest and lowest density resins) and two gel coats (the highest and lowest density gel coats). After completing six months of calibration and accuracy tests of the metering equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (5) The permittee shall operate and maintain measuring equipment to measure the amount of cleanup materials employed in this emissions unit. The permittee shall calibrate the measuring equipment to measure the amount, in weight or volume, of all cleanup materials employed in this emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the measuring equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the measuring equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the measuring equipment, the permittee shall perform calibration and accuracy tests on the measuring equipment on a monthly basis during the first six months of operation of the measuring equipment. The permittee calibration and accuracy tests for the measuring equipment shall include the cleanup material employed by the permittee. After completing six months of calibration and accuracy tests of the measuring equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (6) The permittee shall utilize one or more compliance options, as specified in 40 CFR 63.5810 to demonstrate compliance with the emission standards for open molding in Table 3 of this subpart, as described in the following sections:

63.5810(a)	individual resin or gel coat compliance demonstration
63.5810(b)	average individual organic HAP emissions limit compliance demonstration for all operations and application methods
63.5810(c)	weighted average emission limit compliance demonstration
63.5810(d)	organic HAP emission limit compliance demonstration for one resin type and application method

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR 63.5810]

- (7) The permittee is currently demonstrating compliance through the option specified in 63.5810(a). The permittee shall comply with the following data collection, emission calculation, and record keeping requirements, in addition to those listed in d)(8) below:
- a. Calculate your actual organic HAP emissions factor for each different process stream within this emissions unit. A process stream is defined as each individual combination of resin or gel coat, application technique, and control technique. Process streams within operations types are considered different from each other if any of the following four characteristics vary: the neat resin plus or neat gel coat plus organic HAP content, the gel coat type, the application technique, or the control technique. You must calculate organic HAP emissions factors for each different process stream by using the

appropriate equations in Table 1 of 40 CFR Part 63 Subpart WWWW for open molding and for centrifugal casting, or site-specific organic HAP emissions factors discussed in §63.5796. The emission factor calculation should include any and all emission reduction techniques used. If you are using vapor suppressants to reduce HAP emissions, you must determine the vapor suppressant effectiveness (VSE) by conducting testing according to the procedures specified in appendix A to subpart WWWW of 40 CFR part 63.

Should the permittee choose to demonstrate compliance with the emission limitations listed in b)(2)b. by one of the alternative compliance demonstrations specified in d)(6), the permittee shall collect and record the information specified in 40 CFR 63.5810(b), (c), or (d), as appropriate.

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR 63.5810]

- (8) The permittee shall comply with the applicable monitoring and record keeping requirements under 40 CFR Part 63, Subpart WWWW, including the following sections:

63.5895(c) - (d)	records of resin and gel coat use, organic HAP content, operation and application method(s)
63.5915(a)	copy of compliance notification(s) and report(s)
63.5915(c)	records of all calculations and data used to determine organic HAP emissions factors or average organic HAP contents for operations and application methods as specified under 63.5810
63.5915(d)	certified statement of compliance with work practice requirements
63.5920(a) – (d)	record keeping format and retention requirements

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (9) The permittee shall maintain documentation of the manufacturer's recommendations, instructions, or operating manuals for the dry particulate filter, along with documentation of any modifications deemed necessary by the permittee. These documents shall be maintained at the facility and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (10) The permittee shall conduct periodic inspections of the dry particulate filter to determine whether it is operating in accordance with the manufacturer's recommendations, instructions, or operating manuals with any modifications deemed necessary by the permittee or operator. These inspections shall be performed at a frequency that shall be based upon the recommendation of the manufacturer and the permittee shall maintain a copy of the manufacturer's recommended inspection frequency and it shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

Effective Date: To be entered upon final issuance

- (11) In addition to the recommended periodic inspections, not less than once each calendar year the permittee shall conduct a comprehensive inspection of the dry particulate filter while the emissions unit is shut down and perform any needed maintenance and repair to ensure that it is operated in accordance with the manufacturer's recommendations.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (12) The permittee shall document each inspection (periodic and annual) of the dry particulate filter system and shall maintain the following information:
- a. the date of the inspection;
 - b. a description of each/any problem identified and the date it was corrected;
 - c. a description of any maintenance and repairs performed; and
 - d. the name of person who performed the inspection.

These records shall be maintained at the facility for not less than five years from the date the inspection and any necessary maintenance or repairs were completed and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (13) The permittee shall maintain records that document any time periods when the dry particulate filter was not in service when the emissions unit(s) was/were in operation, as well as, a record of all operations during which the dry particulate filter was not operated according to the manufacturer's recommendations with any documented modifications made by the permittee. These records shall be maintained for a period of not less than five years and shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (14) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05196: d)(1) through d)(13). The monitoring and recordkeeping requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
- a. daily cleanup material usage restriction;
 - b. OC content limitation for the cleanup material;
 - c. daily OC emission limitation for the cleanup material;
 - d. hourly OC emission limitation for coatings;

Effective Date: To be entered upon final issuance

- e. daily OC emission limitation for coatings;
- f. hourly PE/PM10 emission limitation;
- g. daily PE/PM10 emission limitation;
- h. rolling 12-month emission limitation for PE/PM10;
- i. rolling 12-month combined OC emission limitation for P018-P020; and
- j. any daily record showing that the dry particulate filter system was not in service or not operated according to manufacturer's recommendations (with any documented modifications made by the permittee) when the emissions unit(s) was/were in operation.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

- (2) The permittee shall submit annual reports to the Hamilton County Department of Environmental Services that specify the following:
- a. total amount, in gallons, of cleanup material employed for the calendar year; and
 - b. total OC emissions from the cleanup material employed, in tons, for the calendar year.

This report shall be submitted by January 31 of each year and cover the previous calendar year.

[Authority for term: OAC rules 3745-77-07(C)(1)].

- (3) The permittee shall notify the Hamilton County Department of Environmental Services in writing of each day during which any photochemically reactive cleanup material [as defined in OAC rule 3745-21-01] was employed in this emissions unit. The notification shall include a copy of such record and shall be sent to the Hamilton County Department of Environmental Services within 45 days after the exceedance occurs.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) Upon replacement and/or initial operation of any metering or measuring equipment as specified in d)(4) and d)(5) of this permit, the permittee shall provide the Hamilton County Department of Environmental Services the following information: the name of the manufacturer of the metering/measuring equipment, the make and model of the metering/measuring equipment, calibration data (e.g., volume of coating per pump stroke), a copy of the manufacturer's specifications and warranty for the accuracy of the metering/measuring equipment and the actual accuracy of the material measurements (by weight or by volume) recorded for the metering/measuring equipment.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (5) The permittee shall submit calibration and accuracy test results for the metering equipment and measuring equipment specified in d)(4) and d)(5) of the terms and conditions of this permit. The calibration and accuracy tests results shall be submitted to the Hamilton County Department of Environmental Services by January 30 and July 30 of each calendar year, and shall cover the previous six-month period.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (6) The permittee shall submit semi-annual reports and such other notifications and reports to the Hamilton County Department of Environmental Services as are required in 40 CFR Part 63, Subpart WWWW, pursuant to the following sections:

63.5905(b)	15-day notification of change(s)
63.5910(a) - (b) and Table 14	semi-annual compliance reports
63.5910(c) - (i) and Table 14	content of semi-annual compliance reports

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (7) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05196: e)(1) through e)(6). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.

f) **Testing Requirements**

- (1) Compliance with the emission limitations and material usage restrictions specified in b) and c) shall be determined by the following methods:

- a. **Emission Limitations:**

OC emissions shall not exceed 8 pounds per hour from coatings (resin and gel coat);

OC emissions shall not exceed 40 pounds per day from coatings (resin and gel coat); and

OC emissions shall not exceed 7.0 TPY from coatings (resins and gel coats), based on a rolling, 12-month summation of the coating emissions.

Applicable Compliance Method:

Compliance with the hourly OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly OC emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 – 4, 18 and 25.

Effective Date: To be entered upon final issuance

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), OAC rule 3745-31-05(A)(3), 3745-31-05(D), and 3745-21-07(G)(2)].

b. Emission Limitations:

OC emissions shall not exceed 3.3 pounds per day from cleanup materials

OC emissions shall not exceed 0.495 ton per year from cleanup materials

Applicable Compliance Method:

Compliance with the daily OC emission limitation from cleanup materials shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation from cleanup material shall be determined by the record keeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)].

c. Emission Limitation:

The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.

Applicable Compliance Method:

Compliance with the OC content limitation shall be determined by the record keeping requirements specified in d)(1). Formulation data or US EPA Method 24 shall be used to determine the OC content of any cleanup material employed in this emissions unit.

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

d. Material Usage Restriction:

The maximum amount of all cleanup material employed in this emissions unit shall not exceed 0.5 gallon per day and 150 gallons per year.

Applicable Compliance Method:

Compliance with the daily cleanup material usage restriction shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual cleanup material usage restriction shall be determined by the recordkeeping requirements specified in d)(3).



Effective Date: To be entered upon final issuance

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

e. Emission Limitation:

See the organic HAP emission limitations noted in b)(2)b.

Applicable Compliance Method:

Compliance with the organic HAP emission limitation shall be based upon the information collected and recorded in d)(6) - d)(8) of this permit.

[Authority for term: OAC rules 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

f. Emission Limitations:

PE/PM-10 emissions shall not exceed 0.28 pound per hour;

PE/PM-10 emissions shall not exceed 1.38 pounds per day; and

PE/PM-10 emissions shall not exceed 0.18 ton per year, based on a rolling, 12-month summation.

Applicable Compliance Method:

Compliance with the hourly PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly PE/PM10 emission limitation through emission tests performed in accordance with 40 CFR, Part 60, Appendix A, Methods 1-5.

Compliance with the daily PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and OAC 3745-31-05(D)].

- (2) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05196: f)(1)a. through f)(1)f. The testing requirements contained in the above-referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.

g) Miscellaneous Requirements

- (1) None.



Effective Date: To be entered upon final issuance

5. P027, Service Gel Coat Main Bldg - 2

Operations, Property and/or Equipment Description:

Service Gel Coat 2 Main Bldg

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05196)	<p>The Organic Compound (OC) emissions from resin application shall not exceed 8 pounds per hour and 40 lbs/day.</p> <p>OC emissions (acetone) shall not exceed 3.3 pounds per day from cleanup materials.</p> <p>OC emissions (acetone) shall not exceed 0.495 ton per year from cleanup materials.</p> <p>Particulate emissions (PE) and Particulate matter with a diameter of 10 microns or less (PM-10) shall not exceed 0.28 pound per hour.</p> <p>PE/PM10 emissions shall not exceed 1.38 pounds per day.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(D) and 3745-17-07(A)(1).</p> <p>See c)(1) - c)(4).</p>
b.	OAC rule 3745-31-05(D) Synthetic Minor Determination to avoid the Emission Offset Policy for	<p>See b)(2)a.</p> <p>PE/PM10 emissions shall not exceed 0.24 ton per year based on a rolling, 12-</p>



Effective Date: To be entered upon final issuance

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
	VOC.	month summation.
c.	OAC rule 3745-17-07(A)(1)	Visible particulate emissions from any stack shall not exceed 20% opacity, as a six minute average, except as specified by rule.
d.	OAC rule 3745-17-11(B)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
e.	OAC rule 3745-17-11(C)(3)	The Permit to Install for this emissions unit was issued July 9, 2002 (post January 1, 1990). Therefore, the emissions unit is exempt from the requirements of OAC rule 3745-17-11(C)(1) and (2). See b)(2)c.
f.	OAC rule 3745-21-07(G)(2)	The emission limitations specified by this rule are the same as the emission limitation established pursuant to OAC rule 3745-31-05(A)(3). See b)(2)d.
g.	40 CFR Part 63, Subpart WWWW (40 CFR 63.5780-5935) [In accordance with 63.5805(b), this emissions unit is an open molding gel coating application at an existing reinforced plastic composites production facility subject to the emission limitations and work practices specified in 40 CFR 63.5805(b)]	Table 3 to 40 CFR Part 63, Subpart WWWW – Organic Hazardous Air Pollutant (HAP) Emission Limits for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. See b)(2)b and e. Table 4 to 40 CFR Part 63, Subpart WWWW – Applicable Work Practice Standards. See c)(5) and c)(6).
h.	40 CFR 63.1-15, Subpart A (40 CFR 63.5925)	Table 15 to 40 CFR Part 63, Subpart WWWW – Applicability of General Provisions (Subpart A) to Subpart WWWW shows which parts of the General Provisions in 40 CFR Part 63.1 – 15 apply.

(2) Additional Terms and Conditions

- a. The annual OC emission limit, for the coatings, employed in emissions units P006, P013 through P017, P021, P027, P028, P032 and P035 combined shall not exceed 20.0 TPY, based on a rolling, 12-month summation.

For purposes of clarification of non attainment new source review (NSR) permitting requirements and this Title V renewal permitting action, the permittee shall only employ non-VOC based cleanup materials. No cleanup materials with VOC as defined in OAC rule 3745-21-01 shall be employed. The emission of non-VOC based cleanup materials does not count towards the Synthetic Minor Determination to avoid the Emission Offset Policy for VOC established in PTI 14-05196.

- b. The following organic HAP emission limitations shall not be exceeded based on a 12-month rolling average.

Gel Coat Type	Organic HAP Emission Limit
Tooling gel coating	440 lbs/ton
White/off white pigmented gel coating	267 lbs/ton
All other pigmented gel coating	377 lbs/ton
CR/HS or high performance gel coating	605 lbs/ton
Fire retardant gel coat	854 lbs/ton
Clear Production gel coat	522 lbs/ton

- c. On February 1, 2008, OAC rule 3745-17-11 was revised to include paragraph (C), pertaining to control requirements for particulate emissions from surface coating processes. These control requirements and the associated operational restrictions, monitoring, record keeping, and reporting requirements contained in this permit shall become federally enforceable on the date the U.S. EPA approves paragraph (C) of OAC rule 3745-17-11 as a revision to the Ohio State Implementation Plan.
- d. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP); however, until the U.S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio.
- e. This emissions unit is subject to the requirements of 40 CFR Part 63 Subpart WWWW - National Emissions Standards for Hazardous Air Pollutants for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. The permittee shall comply with the applicable emission limitations and operational restrictions specified in 40 CFR Part 63.5780 – 63.5930. The complete MACT requirements, including the MACT General Provisions may be accessed via the internet from the Electronic Code

of Federal Regulations (e-CFR) website <http://ecfr.gpoaccess.gov> or by contacting the appropriate Ohio EPA District Office or local air agency.

c) Operational Restrictions

- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 0.5 gallon per day and 150 gallons per year.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (2) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 lbs of OC/gallon.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (3) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1), 3745-31-05(A)(3) and 3745-21-07(G)(2)]

- (4) The permittee shall operate the dry filtration system for the control of particulate emissions whenever this emissions unit is in operation and shall maintain the dry particulate filter in accordance with the manufacturer's recommendations, instructions, and/or operating manual(s), with any modifications deemed necessary by the permittee.

In the event the particulate filter system is not operating in accordance with the manufacturer's recommendations, instructions, or operating manual, with any modifications deemed necessary by the permittee, the control device shall be expeditiously repaired or otherwise returned to these documented operating conditions.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (5) The permittee shall employ only non-HAP-containing cleanup materials in each emissions unit, except that styrene may be used as a cleaner in closed systems, and organic HAP containing cleaners may be used to clean cured resin from application equipment. Application equipment includes any equipment that directly contacts resin.

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR Part 63, Subpart WWWW Table 4]

- (6) The permittee shall keep containers that store HAP-containing coating materials and cleanup materials closed or covered, except during the addition or removal of materials. Bulk HAP-containing materials storage tanks may be vented as necessary for safety.

[Authority for term: OAC rules 3745-77-07(A)(1) and 40 CFR Part 63, Subpart WWWW Table 4]

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall collect and record the following information each day this emissions unit is in operation:

Effective Date: To be entered upon final issuance

- a. company identification for each coating material (resin and/or gel coat) and cleanup material applied;
- b. number of pounds of each coating material (resin and/or gel coat) applied;
- c. the HAP content, recorded in percent by weight, of each coating material (resin and/or gel coat) employed in this emissions unit;
- d. calculated OC (assumed equal to the organic HAP) emission factor using the equations to calculate organic HAP emission factors from Table 1 of 40 CFR Part 63, Subpart WWWW, in pounds of OC per ton of coating material (resin and/or gel coat) applied;
- e. total daily OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per day $[d)(1)b./2000 \times d)(1)d.]$;
- f. number of hours the emissions unit was in operation;
- g. average hourly OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per hour $[d)(1)e. \text{ divided by } d)(1)f.]$.
- h. total number of gallons of cleanup material applied;
- i. OC content of the cleanup material employed, in pounds per gallon;
- j. daily OC emissions from the cleanup material employed, in pounds $[d)(1)h. \times d)(1)i.]$;
- k. total PE/PM10 emission rate for all coatings employed, in pounds per day $[\text{summation of } d)(1)b. \times (1 - \text{HAP content, percent by weight}) \times 0.25 \text{ (25\% overspray)} \times (1 - 0.985, \text{ the control efficiency of the dry filtration system})]**$;
- l. average hourly PE/PM10 emission rate for all coatings employed, in pounds/hour $[d)(1)k. \text{ divided by } d)(1)f.]$;
- m. a determination whether or not each cleanup material employed is a photochemically reactive material, as defined in OAC rule 3745-21-05(C)(5); and
- n. a determination whether or not each cleanup material employed is a non-HAP material, as identified in Section 112(b) of the Clean Air Act.

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit].

** The 25% overspray and 98.5% control efficiency were used to establish the PE/PM10 emission rates established in PTI 14-05196 and are based on conservative engineering assumptions.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D), 3745-21-07(G)(2), and 40 CFR Part 63 Subpart WWWW]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:
- a. total OC emissions from all the coatings (resins and/or gel coat) employed, in tons [summation of d)(1)e. for all days of the calendar month, and divided by 2000 pounds per ton];
 - b. updated rolling, 12-month summation of OC emission from all the coatings (resins and/or gel coats) employed, in tons [this shall include the total for the current month's OC emissions, plus the total for the preceding eleven calendar months];
 - c. rolling, 12-month summation of OC emissions from all the coatings (resins and/or gel coats) employed, in tons, for emissions units P006, P013 through P017, P021 P027, P028, P032 and P035;
 - d. total PE/PM10 emissions for all coatings employed, in tons [summation of the data from d)(1)k. for all days of the calendar month divided by 2000 pounds per ton]; and
 - e. rolling, 12-month summation of PE/PM10 emissions from all coatings employed, in tons [this shall include the total for the current month's PE/PM10 emissions, plus the total for the preceding eleven calendar months].

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and 3745-31-05(D)]

- (3) The permittee shall maintain annual records of the following information for this emissions unit:
- a. total number of gallons of cleanup material employed [summation of d)(1)h. for all days the emissions unit was in operation]; and
 - b. total OC emissions from cleanup materials employed, in pounds [summation of d)(1)j. for all days of the emissions unit was in operation].

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) The permittee shall operate and maintain metering equipment to measure the amount of all resins and gel coats used in each emissions unit. The permittee shall calibrate the metering equipment to measure the amount, in weight or volume, of all resins and gel coats used in each emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the metering equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the metering equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the metering equipment, the permittee shall perform calibration and accuracy tests on the metering equipment on a monthly basis during the first six months of operation of the meters. The permittee calibration and accuracy tests for the metering equipment shall



Effective Date: To be entered upon final issuance

include two resins (the highest and lowest density resins) and two gel coats (the highest and lowest density gel coats). After completing six months of calibration and accuracy tests of the metering equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (5) The permittee shall operate and maintain measuring equipment to measure the amount of cleanup materials employed in this emissions unit. The permittee shall calibrate the measuring equipment to measure the amount, in weight or volume, of all cleanup materials employed in this emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the measuring equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the measuring equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the measuring equipment, the permittee shall perform calibration and accuracy tests on the measuring equipment on a monthly basis during the first six months of operation of the measuring equipment. The permittee calibration and accuracy tests for the measuring equipment shall include the cleanup material employed by the permittee. After completing six months of calibration and accuracy tests of the measuring equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (6) The permittee shall utilize one or more compliance options, as specified in 40 CFR 63.5810 to demonstrate compliance with the emission standards for open molding in Table 3 of this subpart, as described in the following sections:

63.5810(a)	individual resin or gel coat compliance demonstration
63.5810(b)	average individual organic HAP emissions limit compliance demonstration for all operations and application methods
63.5810(c)	weighted average emission limit compliance demonstration
63.5810(d)	organic HAP emission limit compliance demonstration for one resin type and application method

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR 63.5810]

- (7) The permittee is currently demonstrating compliance through the option specified in 63.5810(a). The permittee shall comply with the following data collection, emission calculation, and record keeping requirements, in addition to those listed in d)(8) below:

- a. Calculate your actual organic HAP emissions factor for each different process stream within this emissions unit. A process stream is defined as each individual combination of resin or gel coat, application technique, and control technique. Process streams within operations types are considered different from each other if any of the following four characteristics vary: the neat resin plus or neat gel coat plus organic HAP content, the gel coat type, the application technique, or the control technique. You must calculate organic HAP emissions factors for each different process stream by using the appropriate equations in Table 1 of 40 CFR Part 63 Subpart WWWW for open molding and for centrifugal casting, or site-specific organic HAP emissions factors discussed in §63.5796. The emission factor calculation should include any and all emission reduction techniques used. If you are using vapor suppressants to reduce HAP emissions, you must determine the vapor suppressant effectiveness (VSE) by conducting testing according to the procedures specified in appendix A to subpart WWWW of 40 CFR part 63.

Should the permittee choose to demonstrate compliance with the emission limitations listed in b)(2)b. by one of the alternative compliance demonstrations specified in d)(6), the permittee shall collect and record the information specified in 40 CFR 63.5810(b),(c), or (d), as appropriate.

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR 63.5810]

- (8) The permittee shall comply with the applicable monitoring and record keeping requirements under 40 CFR Part 63, Subpart WWWW, including the following sections:

63.5895(c) - (d)	records of resin and gel coat use, organic HAP content, operation and application method(s)
63.5915(a)	copy of compliance notification(s) and report(s)
63.5915(c)	records of all calculations and data used to determine organic HAP emissions factors or average organic HAP contents for operations and application methods as specified under 63.5810
63.5915(d)	certified statement of compliance with work practice requirements
63.5920(a) – (d)	record keeping format and retention requirements

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (9) The permittee shall maintain documentation of the manufacturer's recommendations, instructions, or operating manuals for the dry particulate filter, along with documentation of any modifications deemed necessary by the permittee. These documents shall be maintained at the facility and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

Effective Date: To be entered upon final issuance

- (10) The permittee shall conduct periodic inspections of the dry particulate filter to determine whether it is operating in accordance with the manufacturer's recommendations, instructions, or operating manuals with any modifications deemed necessary by the permittee or operator. These inspections shall be performed at a frequency that shall be based upon the recommendation of the manufacturer and the permittee shall maintain a copy of the manufacturer's recommended inspection frequency and it shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (11) In addition to the recommended periodic inspections, not less than once each calendar year the permittee shall conduct a comprehensive inspection of the dry particulate filter while the emissions unit is shut down and perform any needed maintenance and repair to ensure that it is operated in accordance with the manufacturer's recommendations.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (12) The permittee shall document each inspection (periodic and annual) of the dry particulate filter system and shall maintain the following information:

- a. the date of the inspection;
- b. a description of each/any problem identified and the date it was corrected;
- c. a description of any maintenance and repairs performed; and
- d. the name of person who performed the inspection.

These records shall be maintained at the facility for not less than five years from the date the inspection and any necessary maintenance or repairs were completed and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (13) The permittee shall maintain records that document any time periods when the dry particulate filter was not in service when the emissions unit(s) was/were in operation, as well as, a record of all operations during which the dry particulate filter was not operated according to the manufacturer's recommendations with any documented modifications made by the permittee. These records shall be maintained for a period of not less than five years and shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (14) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05196: d)(1) through d)(13). The monitoring and recordkeeping requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
 - a. daily cleanup material usage restriction;
 - b. OC content limitation for the cleanup material;
 - c. daily OC emission limitation for the cleanup material;
 - d. hourly OC emission limitation for coatings;
 - e. daily OC emission limitation for coatings;
 - f. hourly PE/PM10 emission limitation;
 - g. daily PE/PM10 emission limitation;
 - h. rolling 12-month emission limitation for PE/PM10;
 - i. rolling 12-month combined OC emission limitation for P006, P013 through P017, P021, P027, P028, P032 and P035; and
 - j. any daily record showing that the dry particulate filter system was not in service or not operated according to manufacturer's recommendations (with any documented modifications made by the permittee) when the emissions unit(s) was/were in operation.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

- (2) The permittee shall submit annual reports to the Hamilton County Department of Environmental Services that specify the following:
 - a. total amount, in gallons, of cleanup material employed for the calendar year; and
 - b. total OC emissions from the cleanup material employed, in tons, for the calendar year.

This report shall be submitted by January 31 of each year and cover the previous calendar year.

[Authority for term: OAC rules 3745-77-07(C)(1)].

- (3) The permittee shall notify the Hamilton County Department of Environmental Services in writing of each day during which any photochemically reactive cleanup material [as defined in OAC rule 3745-21-01] was employed in this emissions unit. The notification shall include a copy of such record and shall be sent to the Hamilton County Department of Environmental Services within 45 days after the exceedance occurs.



Effective Date: To be entered upon final issuance

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) Upon replacement and/or initial operation of any metering or measuring equipment as specified in d)(4) and d)(5) of this permit, the permittee shall provide the Hamilton County Department of Environmental Services the following information: the name of the manufacturer of the metering/measuring equipment, the make and model of the metering/measuring equipment, calibration data (e.g., volume of coating per pump stroke), a copy of the manufacturer's specifications and warranty for the accuracy of the metering/measuring equipment and the actual accuracy of the material measurements (by weight or by volume) recorded for the metering/measuring equipment.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (5) The permittee shall submit calibration and accuracy test results for the metering equipment and measuring equipment specified in d)(4) and d)(5) of the terms and conditions of this permit. The calibration and accuracy tests results shall be submitted to the Hamilton County Department of Environmental Services by January 30 and July 30 of each calendar year, and shall cover the previous six-month period.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (6) The permittee shall submit semi-annual reports and such other notifications and reports to the Hamilton County Department of Environmental Services as are required in 40 CFR Part 63, Subpart WWWW, pursuant to the following sections:

63.5905(b)	15-day notification of change(s)
63.5910(a) - (b) and Table 14	semi-annual compliance reports
63.5910(c) - (i) and Table 14	content of semi-annual compliance reports

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (7) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05196: e)(1) through e)(6). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.

f) Testing Requirements

- (1) Compliance with the emission limitations and material usage restrictions specified in b) and c) shall be determined by the following methods:

a. Emission Limitations:

OC emissions shall not exceed 8 pounds per hour from coatings (resin and gel coat);

Effective Date: To be entered upon final issuance

OC emissions shall not exceed 40 pounds per day from coatings (resin and gel coat); and

OC emissions shall not exceed 20.0 TPY from coatings (resins and gel coats) from emissions units P006, P013 through P017, P021, P027, P028, P032 and P035, combined, based on a rolling, 12-month summation of the coating emissions.

Applicable Compliance Method:

Compliance with the hourly OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly OC emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 – 4, 18 and 25.

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), OAC rule 3745-31-05(A)(3), 3745-31-05(D), and 3745-21-07(G)(2)].

b. Emission Limitations:

OC emissions shall not exceed 3.3 pounds per day from cleanup materials

OC emissions shall not exceed 0.495 ton per year from cleanup materials

Applicable Compliance Method:

Compliance with the daily OC emission limitation from cleanup materials shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation from cleanup material shall be determined by the record keeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)].

c. Emission Limitation:

The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.

Applicable Compliance Method:

Compliance with the OC content limitation shall be determined by the record keeping requirements specified in d)(1). Formulation data or US EPA Method 24

shall be used to determine the OC content of any cleanup material employed in this emissions unit.

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

d. Material Usage Restriction:

The maximum amount of all cleanup material employed in this emissions unit shall not exceed 0.5 gallon per day and 150 gallons per year.

Applicable Compliance Method:

Compliance with the daily cleanup material usage restriction shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual cleanup material usage restriction shall be determined by the recordkeeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

e. Emission Limitation:

See the organic HAP emission limitations noted in b)(2)b.

Applicable Compliance Method:

Compliance with the organic HAP emission limitation shall be based upon the information collected and recorded in d)(6) - d)(8) of this permit.

[Authority for term: OAC rules 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

f. Emission Limitations:

PE/PM-10 emissions shall not exceed 0.28 pounds per hour;

PE/PM-10 emissions shall not exceed 1.38 pounds per day; and

PE/PM-10 emissions shall not exceed 0.24 ton per year, based on a rolling, 12-month summation.

Applicable Compliance Method:

Compliance with the hourly PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly PE/PM10 emission limitation through emission tests performed in accordance with 40 CFR, Part 60, Appendix A, Methods 1-5.

Compliance with the daily PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).



Compliance with the annual PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and OAC 3745-31-05(D)].

- (2) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05196: f)(1)a. through f)(1)f. The testing requirements contained in the above-referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.
- g) Miscellaneous Requirements
 - (1) None.



Effective Date: To be entered upon final issuance

6. P028, Service Gel Coat Main Bldg - 3

Operations, Property and/or Equipment Description:

Service Gel Coat 3 Main Bldg

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05196)	The Organic Compound (OC) emissions from resin application shall not exceed 8 pounds per hour and 40 lbs/day. OC emissions (acetone) shall not exceed 3.3 pounds per day from cleanup materials. OC emissions (acetone) shall not exceed 0.495 ton per year from cleanup materials. Particulate emissions (PE) and Particulate matter with a diameter of 10 microns or less (PM-10) shall not exceed 0.28 pound per hour. PE/PM10 emissions shall not exceed 1.38 pounds per day. The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(D) and 3745-17-07(A)(1). See c)(1) - c)(4).
b.	OAC rule 3745-31-05(D) Synthetic Minor Determination to avoid the Emission Offset Policy for	See b)(2)a. PE/PM10 emissions shall not exceed 0.06 ton per year based on a rolling, 12-



Effective Date: To be entered upon final issuance

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
	VOC.	month summation.
c.	OAC rule 3745-17-07(A)(1)	Visible particulate emissions from any stack shall not exceed 20% opacity, as a six minute average, except as specified by rule.
d.	OAC rule 3745-17-11(B)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
e.	OAC rule 3745-17-11(C)(3)	The Permit to Install for this emissions unit was issued July 9, 2002 (post January 1, 1990). Therefore, the emissions unit is exempt from the requirements of OAC rule 3745-17-11(C)(1) and (2). See b)(2)c.
f.	OAC rule 3745-21-07(G)(2)	The emission limitations specified by this rule are the same as the emission limitation established pursuant to OAC rule 3745-31-05(A)(3). See b)(2)d.
g.	40 CFR Part 63, Subpart WWWW (40 CFR 63.5780-5935) [In accordance with 63.5805(b), this emissions unit is an open molding gel coating application at an existing reinforced plastic composites production facility subject to the emission limitations and work practices specified in 40 CFR 63.5805(b)]	Table 3 to 40 CFR Part 63, Subpart WWWW – Organic Hazardous Air Pollutant (HAP) Emission Limits for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. See b)(2)b. and e. Table 4 to 40 CFR Part 63, Subpart WWWW – Applicable Work Practice Standards. See c)(5) and c)(6).
h.	40 CFR 63.1-15, Subpart A (40 CFR 63.5925)	Table 15 to 40 CFR Part 63, Subpart WWWW – Applicability of General Provisions (Subpart A) to Subpart WWWW shows which parts of the General Provisions in 40 CFR Part 63.1 – 15 apply.

(2) Additional Terms and Conditions

- a. The annual OC emission limit, for the coatings, employed in emissions units P006, P013 through P017, P021, P027, P028, P032 and P035 combined shall not exceed 20.0 TPY, based on a rolling, 12-month summation.

For purposes of clarification of non attainment new source review (NSR) permitting requirements and this Title V renewal permitting action, the permittee shall only employ non-VOC based cleanup materials. No cleanup materials with VOC as defined in OAC rule 3745-21-01 shall be employed. The emission of non-VOC based cleanup materials does not count towards the Synthetic Minor Determination to avoid the Emission Offset Policy for VOC established in PTI 14-05196.

- b. The following organic HAP emission limitations shall not be exceeded based on a 12-month rolling average.

Gel Coat Type	Organic HAP Emission Limit
Tooling gel coating	440 lbs/ton
White/off white pigmented gel coating	267 lbs/ton
All other pigmented gel coating	377 lbs/ton
CR/HS or high performance gel coating	605 lbs/ton
Fire retardant gel coat	854 lbs/ton
Clear Production gel coat	522 lbs/ton

- c. On February 1, 2008, OAC rule 3745-17-11 was revised to include paragraph (C), pertaining to control requirements for particulate emissions from surface coating processes. These control requirements and the associated operational restrictions, monitoring, record keeping, and reporting requirements contained in this permit shall become federally enforceable on the date the U.S. EPA approves paragraph (C) of OAC rule 3745-17-11 as a revision to the Ohio State Implementation Plan.
- d. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP); however, until the U.S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio.
- e. This emissions unit is subject to the requirements of 40 CFR Part 63 Subpart WWWW - National Emissions Standards for Hazardous Air Pollutants for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. The permittee shall comply with the applicable emission limitations and operational restrictions specified in 40 CFR Part 63.5780 – 63.5930. The complete MACT requirements, including the MACT General Provisions may be accessed via the internet from the Electronic Code

of Federal Regulations (e-CFR) website <http://ecfr.gpoaccess.gov> or by contacting the appropriate Ohio EPA District Office or local air agency.

c) Operational Restrictions

- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 0.5 gallon per day and 150 gallons per year.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (2) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 lbs of OC/gallon.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (3) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1), 3745-31-05(A)(3) and 3745-21-07(G)(2)]

- (4) The permittee shall operate the dry filtration system for the control of particulate emissions whenever this emissions unit is in operation and shall maintain the dry particulate filter in accordance with the manufacturer's recommendations, instructions, and/or operating manual(s), with any modifications deemed necessary by the permittee.

In the event the particulate filter system is not operating in accordance with the manufacturer's recommendations, instructions, or operating manual, with any modifications deemed necessary by the permittee, the control device shall be expeditiously repaired or otherwise returned to these documented operating conditions.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (5) The permittee shall employ only non-HAP-containing cleanup materials in each emissions unit, except that styrene may be used as a cleaner in closed systems, and organic HAP containing cleaners may be used to clean cured resin from application equipment. Application equipment includes any equipment that directly contacts resin.

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR Part 63, Subpart WWWW Table 4]

- (6) The permittee shall keep containers that store HAP-containing coating materials and cleanup materials closed or covered, except during the addition or removal of materials. Bulk HAP-containing materials storage tanks may be vented as necessary for safety.

[Authority for term: OAC rules 3745-77-07(A)(1) and 40 CFR Part 63, Subpart WWWW Table 4]

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall collect and record the following information each day this emissions unit is in operation:

- a. company identification for each coating material (resin and/or gel coat) and cleanup material applied;
- b. number of pounds of each coating material (resin and/or gel coat) applied;
- c. the HAP content, recorded in percent by weight, of each coating material (resin and/or gel coat) employed in this emissions unit;
- d. calculated OC (assumed equal to the organic HAP) emission factor using the equations to calculate organic HAP emission factors from Table 1 of 40 CFR Part 63, Subpart WWWW, in pounds of OC per ton of coating material (resin and/or gel coat) applied;
- e. total daily OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per day $[d)(1)b./2000 \times d)(1)d.]$;
- f. number of hours the emissions unit was in operation;
- g. average hourly OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per hour $[d)(1)e. \text{ divided by } d)(1)f.]$.
- h. total number of gallons of cleanup material applied;
- i. OC content of the cleanup material employed, in pounds per gallon;
- j. daily OC emissions from the cleanup material employed, in pounds $[d)(1)h. \times d)(1)i.]$;
- k. total PE/PM10 emission rate for all coatings employed, in pounds per day $[\text{summation of } d)(1)b. \times (1 - \text{HAP content, percent by weight}) \times 0.25 \text{ (25\% overspray)} \times (1 - 0.985, \text{ the control efficiency of the dry filtration system})]**$;
- l. average hourly PE/PM10 emission rate for all coatings employed, in pounds/hour $[d)(1)k \text{ divided by } d)(1)f.]$;
- m. a determination whether or not each cleanup material employed is a photochemically reactive material, as defined in OAC rule 3745-21-05(C)(5); and
- n. a determination whether or not each cleanup material employed is a non-HAP material, as identified in Section 112(b) of the Clean Air Act.

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit].

** The 25% overspray and 98.5% control efficiency were used to establish the PE/PM10

emission rates established in PTI 14-05196 and are based on conservative engineering assumptions.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D), 3745-21-07(G)(2), and 40 CFR Part 63 Subpart WWWW]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:
- a. total OC emissions from all the coatings (resins and/or gel coat) employed, in tons [summation of d)(1)e. for all days of the calendar month, and divided by 2000 pounds per ton];
 - b. updated rolling, 12-month summation of OC emission from all the coatings (resins and/or gel coats) employed, in tons [this shall include the total for the current month's OC emissions, plus the total for the preceding eleven calendar months];
 - c. rolling, 12-month summation of OC emissions from all the coatings (resins and/or gel coats) employed, in tons, for emissions units P006, P013 through P017, P021 P027, P028, P032 and P035;
 - d. total PE/PM10 emissions for all coatings employed, in tons [summation of the data from d)(1)k. for all days of the calendar month divided by 2000 pounds per ton];
 - e. rolling, 12-month summation of PE/PM10 emissions from all coatings employed, in tons [this shall include the total for the current month's PE/PM10 emissions, plus the total for the preceding eleven calendar months].

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and 3745-31-05(D)]

- (3) The permittee shall maintain annual records of the following information for this emissions unit:
- a. total number of gallons of cleanup material employed [summation of d)(1)h. for all days the emissions unit was in operation]; and
 - b. total OC emissions from cleanup materials employed, in pounds [summation of d)(1)j. for all days of the emissions unit was in operation].

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) The permittee shall operate and maintain metering equipment to measure the amount of all resins and gel coats used in each emissions unit. The permittee shall calibrate the metering equipment to measure the amount, in weight or volume, of all resins and gel coats used in each emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the metering equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the metering equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the metering equipment, the permittee shall perform calibration and accuracy tests on the metering equipment on a monthly basis during the first six months of operation of the meters. The permittee calibration and accuracy tests for the metering equipment shall include two resins (the highest and lowest density resins) and two gel coats (the highest and lowest density gel coats). After completing six months of calibration and accuracy tests of the metering equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (5) The permittee shall operate and maintain measuring equipment to measure the amount of cleanup materials employed in this emissions unit. The permittee shall calibrate the measuring equipment to measure the amount, in weight or volume, of all cleanup materials employed in this emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the measuring equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the measuring equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the measuring equipment, the permittee shall perform calibration and accuracy tests on the measuring equipment on a monthly basis during the first six months of operation of the measuring equipment. The permittee calibration and accuracy tests for the measuring equipment shall include the cleanup material employed by the permittee. After completing six months of calibration and accuracy tests of the measuring equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (6) The permittee shall utilize one or more compliance options, as specified in 40 CFR 63.5810 to demonstrate compliance with the emission standards for open molding in Table 3 of this subpart, as described in the following sections:

63.5810(a)	individual resin or gel coat compliance demonstration
63.5810(b)	average individual organic HAP emissions limit compliance demonstration for all operations and application methods
63.5810(c)	weighted average emission limit compliance demonstration
63.5810(d)	organic HAP emission limit compliance demonstration for one resin type and application method



[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR 63.5810]

- (7) The permittee is currently demonstrating compliance through the option specified in 63.5810(a). The permittee shall comply with the following data collection, emission calculation, and record keeping requirements, in addition to those listed in d)(8) below:
 - a. Calculate your actual organic HAP emissions factor for each different process stream within this emissions unit. A process stream is defined as each individual combination of resin or gel coat, application technique, and control technique. Process streams within operations types are considered different from each other if any of the following four characteristics vary: the neat resin plus or neat gel coat plus organic HAP content, the gel coat type, the application technique, or the control technique. You must calculate organic HAP emissions factors for each different process stream by using the appropriate equations in Table 1 of 40 CFR Part 63 Subpart WWWW for open molding and for centrifugal casting, or site-specific organic HAP emissions factors discussed in §63.5796. The emission factor calculation should include any and all emission reduction techniques used. If you are using vapor suppressants to reduce HAP emissions, you must determine the vapor suppressant effectiveness (VSE) by conducting testing according to the procedures specified in appendix A to subpart WWWW of 40 CFR part 63.

Should the permittee choose to demonstrate compliance with the emission limitations listed in b)(2)b. by one of the alternative compliance demonstrations specified in d)(6), the permittee shall collect and record the information specified in 40 CFR 63.5810(b),(c), or (d), as appropriate.

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR 63.5810]

- (8) The permittee shall comply with the applicable monitoring and record keeping requirements under 40 CFR Part 63, Subpart WWWW, including the following sections:

63.5895(c) - (d)	records of resin and gel coat use, organic HAP content, operation and application method(s)
63.5915(a)	copy of compliance notification(s) and report(s)
63.5915(c)	records of all calculations and data used to determine organic HAP emissions factors or average organic HAP contents for operations and application methods as specified under 63.5810
63.5915(d)	certified statement of compliance with work practice requirements
63.5920(a) – (d)	record keeping format and retention requirements

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (9) The permittee shall maintain documentation of the manufacturer's recommendations, instructions, or operating manuals for the dry particulate filter, along with documentation

of any modifications deemed necessary by the permittee. These documents shall be maintained at the facility and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (10) The permittee shall conduct periodic inspections of the dry particulate filter to determine whether it is operating in accordance with the manufacturer's recommendations, instructions, or operating manuals with any modifications deemed necessary by the permittee or operator. These inspections shall be performed at a frequency that shall be based upon the recommendation of the manufacturer and the permittee shall maintain a copy of the manufacturer's recommended inspection frequency and it shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (11) In addition to the recommended periodic inspections, not less than once each calendar year the permittee shall conduct a comprehensive inspection of the dry particulate filter while the emissions unit is shut down and perform any needed maintenance and repair to ensure that it is operated in accordance with the manufacturer's recommendations.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (12) The permittee shall document each inspection (periodic and annual) of the dry particulate filter system and shall maintain the following information:
- a. the date of the inspection;
 - b. a description of each/any problem identified and the date it was corrected;
 - c. a description of any maintenance and repairs performed; and
 - d. the name of person who performed the inspection.

These records shall be maintained at the facility for not less than five years from the date the inspection and any necessary maintenance or repairs were completed and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (13) The permittee shall maintain records that document any time periods when the dry particulate filter was not in service when the emissions unit(s) was/were in operation, as well as, a record of all operations during which the dry particulate filter was not operated according to the manufacturer's recommendations with any documented modifications made by the permittee. These records shall be maintained for a period of not less than five years and shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (14) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05196: d)(1) through d)(13). The monitoring and recordkeeping requirements contained in the above-referenced

Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
 - a. daily cleanup material usage restriction;
 - b. OC content limitation for the cleanup material;
 - c. daily OC emission limitation for the cleanup material;
 - d. hourly OC emission limitation for coatings;
 - e. daily OC emission limitation for coatings;
 - f. hourly PE/PM10 emission limitation;
 - g. daily PE/PM10 emission limitation;
 - h. rolling 12-month emission limitation for PE/PM10;
 - i. rolling 12-month combined OC emission limitation for P006, P013 through P017, P021, P027, P028, P032 and P035; and
 - j. any daily record showing that the dry particulate filter system was not in service or not operated according to manufacturer's recommendations (with any documented modifications made by the permittee) when the emissions unit(s) was/were in operation.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

- (2) The permittee shall submit annual reports to the Hamilton County Department of Environmental Services that specify the following:
 - a. total amount, in gallons, of cleanup material employed for the calendar year; and
 - b. total OC emissions from the cleanup material employed, in tons, for the calendar year.

This report shall be submitted by January 31 of each year and cover the previous calendar year.

[Authority for term: OAC rules 3745-77-07(C)(1)].

- (3) The permittee shall notify the Hamilton County Department of Environmental Services in writing of each day during which any photochemically reactive cleanup material [as



Effective Date: To be entered upon final issuance

defined in OAC rule 3745-21-01] was employed in this emissions unit. The notification shall include a copy of such record and shall be sent to the Hamilton County Department of Environmental Services within 45 days after the exceedance occurs.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) Upon replacement and/or initial operation of any metering or measuring equipment as specified in d)(4) and d)(5) of this permit, the permittee shall provide the Hamilton County Department of Environmental Services the following information: the name of the manufacturer of the metering/measuring equipment, the make and model of the metering/measuring equipment, calibration data (e.g., volume of coating per pump stroke), a copy of the manufacturer's specifications and warranty for the accuracy of the metering/measuring equipment and the actual accuracy of the material measurements (by weight or by volume) recorded for the metering/measuring equipment.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (5) The permittee shall submit calibration and accuracy test results for the metering equipment and measuring equipment specified in d)(4) and d)(5) of the terms and conditions of this permit. The calibration and accuracy tests results shall be submitted to the Hamilton County Department of Environmental Services by January 30 and July 30 of each calendar year, and shall cover the previous six-month period.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (6) The permittee shall submit semi-annual reports and such other notifications and reports to the Hamilton County Department of Environmental Services as are required in 40 CFR Part 63, Subpart WWWW, pursuant to the following sections:

63.5905(b)	15-day notification of change(s)
63.5910(a) - (b) and Table 14	semi-annual compliance reports
63.5910(c) - (i) and Table 14	content of semi-annual compliance reports

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (7) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05196: e)(1) through e)(6). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.

f) Testing Requirements

- (1) Compliance with the emission limitations and material usage restrictions specified in b) and c) shall be determined by the following methods:
 - a. Emission Limitations:

Effective Date: To be entered upon final issuance

OC emissions shall not exceed 8 pounds per hour from coatings (resin and gel coat);

OC emissions shall not exceed 40 pounds per day from coatings (resin and gel coat); and

OC emissions shall not exceed 20.0 TPY from coatings (resins and gel coats) from emissions units P006, P013 through P017, P021, P027, P028, P032 and P035, combined, based on a rolling, 12-month summation of the coating emissions.

Applicable Compliance Method:

Compliance with the hourly OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly OC emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 – 4, 18 and 25.

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), OAC rule 3745-31-05(A)(3), 3745-31-05(D), and 3745-21-07(G)(2)].

b. Emission Limitations:

OC emissions shall not exceed 3.3 pounds per day from cleanup materials

OC emissions shall not exceed 0.495 ton per year from cleanup materials

Applicable Compliance Method:

Compliance with the daily OC emission limitation from cleanup materials shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation from cleanup material shall be determined by the record keeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)].

c. Emission Limitation:

The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.

Applicable Compliance Method:

Compliance with the OC content limitation shall be determined by the record keeping requirements specified in d)(1). Formulation data or US EPA Method 24 shall be used to determine the OC content of any cleanup material employed in this emissions unit.

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

d. Material Usage Restriction:

The maximum amount of all cleanup material employed in this emissions unit shall not exceed 0.5 gallon per day and 150 gallons per year.

Applicable Compliance Method:

Compliance with the daily cleanup material usage restriction shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual cleanup material usage restriction shall be determined by the recordkeeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

e. Emission Limitation:

See the organic HAP emission limitations noted in b)(2)b.

Applicable Compliance Method:

Compliance with the organic HAP emission limitation shall be based upon the information collected and recorded in d)(6) - d)(8) of this permit.

[Authority for term: OAC rules 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

f. Emission Limitations:

PE/PM-10 emissions shall not exceed 0.28 pound per hour;

PE/PM-10 emissions shall not exceed 1.38 pounds per day; and

PE/PM-10 emissions shall not exceed 0.06 tons per year, based on a rolling, 12-month summation.

Applicable Compliance Method:

Compliance with the hourly PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).



Effective Date: To be entered upon final issuance

If required, the permittee shall demonstrate compliance with the hourly PE/PM10 emission limitation through emission tests performed in accordance with 40 CFR, Part 60, Appendix A, Methods 1-5.

Compliance with the daily PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and OAC 3745-31-05(D)].

- (2) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05196: f)(1)a. through f)(1)f. The testing requirements contained in the above-referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.

g) **Miscellaneous Requirements**

- (1) None.



7. P030, Service Gel Coat Bldg B - 1

Operations, Property and/or Equipment Description:

Robotic Gel Coat Applicator Booth

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05474)	Particulate emissions (PE) and Particulate matter with a diameter of 10 microns or less (PM-10) shall not exceed 0.39 pound per hour. PE/PM10 emissions shall not exceed 6.07 pounds per day. PE/PM10 emissions shall not exceed 0.60 TPY. The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(D), 3745-21-07(G)(9)(g), and 3745-17-07(A)(1). See c)(1) - c)(8).
b.	OAC rule 3745-31-05(D) Synthetic Minor Determination to avoid the Emission Offset Policy for VOC.	See b)(2)a.
c.	OAC rule 3745-17-07(A)(1)	Visible particulate emissions from any stack shall not exceed 20% opacity, as a six minute average, except as specified by rule.
d.	OAC rule 3745-17-11(B)	The emission limitation specified by this rule is less stringent than the emission



Effective Date: To be entered upon final issuance

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		limitation established pursuant to OAC rule 3745-31-05(A)(3).
e.	OAC rule 3745-17-11(C)(3)	The Permit to Install for this emissions unit was issued July 9, 2002 (post January 1, 1990). Therefore, the emissions unit is exempt from the requirements of OAC rule 3745-17-11(C)(1) and (2). See b)(2)c.
f.	OAC rule 3745-21-07(G)(9)(g)	The Organic Compound (OC) emissions from resin application shall not exceed 10.1 pounds per hour and 157 lbs/day. OC (acetone) emissions shall not exceed 13.2 pounds per day from cleanup materials. OC (acetone) emissions shall not exceed 2.4 tons per year from cleanup materials. See b)(2)d.
g.	40 CFR Part 63, Subpart WWWW (40 CFR 63.5780-5935) [In accordance with 63.5805(b), this emissions unit is an open molding gel coating application at an existing reinforced plastic composites production facility subject to the emission limitations and work practices specified in 40 CFR 63.5805(b)]	Table 3 to 40 CFR Part 63, Subpart WWWW – Organic Hazardous Air Pollutant (HAP) Emission Limits for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. See b)(2)b. and e. Table 4 to 40 CFR Part 63, Subpart WWWW – Applicable Work Practice Standards. See c)(10) and c)(11).
h.	40 CFR 63.1-15, Subpart A (40 CFR 63.5925)	Table 15 to 40 CFR Part 63, Subpart WWWW – Applicability of General Provisions (Subpart A) to Subpart WWWW shows which parts of the General Provisions in 40 CFR Part 63.1 – 15 apply.

(2) Additional Terms and Conditions

- a. Organic Compound (OC) emissions shall not exceed 15.5 TPY from coatings, based on a rolling 12-month summation. For purposes of clarification of non

attainment new source review (NSR) permitting requirements and this Title V renewal permitting action, the permittee shall only employ non-VOC based cleanup materials. No cleanup materials with VOC as defined in OAC rule 3745-21-01 shall be employed. The emission of non-VOC based cleanup materials does not count towards the Synthetic Minor Determination to avoid the Emission Offset Policy for VOC established in PTI 14-05474.

- b. The following organic HAP emission limitations shall not be exceeded based on a 12-month rolling average.

Gel Coat Type	Organic HAP Emission Limit
Tooling gel coating	440 lbs/ton
White/off white pigmented gel coating	267 lbs/ton
All other pigmented gel coating	377 lbs/ton
CR/HS or high performance gel coating	605 lbs/ton
Fire retardant gel coat	854 lbs/ton
Clear Production gel coat	522 lbs/ton

- c. On February 1, 2008, OAC rule 3745-17-11 was revised to include paragraph (C), pertaining to control requirements for particulate emissions from surface coating processes. These control requirements and the associated operational restrictions, monitoring, record keeping, and reporting requirements contained in this permit shall become federally enforceable on the date the U.S. EPA approves paragraph (C) of OAC rule 3745-17-11 as a revision to the Ohio State Implementation Plan.
- d. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP); however, until the U.S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio. The requirements of OAC 3745-21-07(G)(9)(g) have been carried over into 3745-21-07(M)(5)(e). Therefore, no change in emission limitations or terms and conditions will take place after the SIP is modified.
- e. This emissions unit is subject to the requirements of 40 CFR Part 63 Subpart WWWW - National Emissions Standards for Hazardous Air Pollutants for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. The permittee shall comply with the applicable emission limitations and operational restrictions specified in 40 CFR Part 63.5780 – 63.5930. The complete MACT requirements, including the MACT General Provisions may be accessed via the internet from the Electronic Code of Federal Regulations (e-CFR) website <http://ecfr.gpoaccess.gov> or by contacting the appropriate Ohio EPA District Office or local air agency.

c) Operational Restrictions

- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 2.0 gallons per day and 720 gallons per year.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (2) The styrene content of the gel coats (gel coat is a polyester resin surface coating, either pigmented or clear, that provides a cosmetic enhancement and improves resistance to degradation from exposure to the elements) shall not exceed the following limitations:

- a. 50%, by weight, as applied for each clear gel coat; and (clear gel coat is gel coat without pigment); and
- b. 45%, by weight, as applied for each pigmented gel coat (pigmented gel coat is clear gel coat with pigments added).

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (3) The amount of gel coat used in this emissions unit shall not exceed 144 pounds per hour, 2,248 pounds per day and 220.95 tons per year. The tons per year limitation is based upon a rolling, 12-month summation.

- (4) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (5) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01, in this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (6) The permittee shall operate the dry filtration system for the control of particulate emissions whenever this emissions unit is in operation and shall maintain the dry particulate filter in accordance with the manufacturer's recommendations, instructions, and/or operating manual(s), with any modifications deemed necessary by the permittee.

In the event the particulate filter system is not operating in accordance with the manufacturer's recommendations, instructions, or operating manual, with any modifications deemed necessary by the permittee, the control device shall be expeditiously repaired or otherwise returned to these documented operating conditions.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (7) The permittee shall electronically monitor the amount of coating pumped by this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (8) The permittee shall only utilize robotic application equipment in this emissions unit.
[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]
- (9) The permittee shall employ only non-HAP-containing cleanup materials in each emissions unit.
[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3), and 40 CFR Part 63, Subpart WWWW Table 4]
- (10) The permittee shall keep containers that store HAP-containing coating materials and cleanup materials closed or covered, except during the addition or removal of materials.
[Authority for term: OAC rules 3745-77-07(A)(1), 3745-31-05(A)(3), and 40 CFR Part 63, Subpart WWWW Table 4]
- d) Monitoring and/or Recordkeeping Requirements
- (1) The permittee shall collect and record the following information each day this emissions unit is in operation:
- a. company identification for each coating material (resin and/or gel coat) and cleanup material applied;
 - b. number of pounds of each coating material (resin and/or gel coat) applied;
 - c. the HAP content, recorded in percent by weight, of each coating material (resin and/or gel coat) employed in this emissions unit;
 - d. calculated OC (assumed equal to the organic HAP) emission factor using the equations to calculate organic HAP emission factors from Table 1 of 40 CFR Part 63, Subpart WWWW, in pounds of OC per ton of coating material (resin and/or gel coat) applied;
 - e. total daily OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per day $[d)(1)b./2000 \times d)(1)d.]$;
 - f. number of hours the emissions unit was in operation;
 - g. average hourly OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per hour $[d)(1)e. \text{ divided by } d)(1)f.]$.
 - h. total number of gallons of cleanup material applied;
 - i. OC content of the cleanup material employed, in pounds per gallon;
 - j. daily OC emissions from the cleanup material employed, in pounds $[d)(1)h. \times d)(1)i.]$;

Effective Date: To be entered upon final issuance

- k. total PE/PM10 emission rate for all coatings employed, in pounds per day [summation of d)(1)b. x (1 - HAP content, percent by weight) x 0.25 (25% overspray) x (1 - 0.985, the control efficiency of the dry filtration system)]**;
- l. average hourly PE/PM10 emission rate for all coatings employed, in pounds/hour [d)(1)k. divided by d)(1)f.];
- m. a determination whether or not each cleanup material employed is a photochemically reactive material, as defined in OAC rule 3745-21-05(C)(5); and
- n. a determination whether or not each cleanup material employed is a non-HAP material, as identified in Section 112(b) of the Clean Air Act.

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit].

** The 25% overspray and 98.5% control efficiency were used to establish the PE/PM10 emission rates established in PTI 14-05474 and are based on conservative engineering assumptions.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D), 3745-21-07(G)(2), and 40 CFR Part 63 Subpart WWWW]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:
 - a. total OC emissions from all the coatings (resins and/or gel coat) employed, in tons [summation of d)(1)e. for all days of the calendar month, and divided by 2000 pounds per ton];
 - b. updated rolling, 12-month summation of OC emission from all the coatings (resins and/or gel coats) employed, in tons [this shall include the total for the current month's OC emissions, plus the total for the preceding eleven calendar months];
 - c. total PE/PM10 emissions for all coatings employed, in tons [summation of the data from d)(1)k. for all days of the calendar month divided by 2000 pounds per ton]; and
 - d. rolling, 12-month summation of PE/PM10 emissions from all coatings employed, in tons [this shall include the total for the current month's PE/PM10 emissions, plus the total for the preceding eleven calendar months]; and
 - e. rolling, 12-month summation of all coatings employed, in tons [this shall include the total for the current month, plus the total for the preceding eleven calendar months].

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and 3745-31-05(D)]

- (3) The permittee shall maintain annual records of the following information for this emissions unit:

Effective Date: To be entered upon final issuance

- a. total number of gallons of cleanup material employed [summation of d)(1)h. for all days the emissions unit was in operation]; and
- b. total OC emissions from cleanup materials employed, in pounds [summation of d)(1)j. for all days of the emissions unit was in operation].

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) The permittee shall operate and maintain metering equipment to measure the amount of all resins and gel coats used in each emissions unit. The permittee shall calibrate the metering equipment to measure the amount, in weight or volume, of all resins and gel coats used in each emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the metering equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the metering equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the metering equipment, the permittee shall perform calibration and accuracy tests on the metering equipment on a monthly basis during the first six months of operation of the meters. The permittee calibration and accuracy tests for the metering equipment shall include two resins (the highest and lowest density resins) and two gel coats (the highest and lowest density gel coats). After completing six months of calibration and accuracy tests of the metering equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (5) The permittee shall operate and maintain measuring equipment to measure the amount of cleanup materials employed in this emissions unit. The permittee shall calibrate the measuring equipment to measure the amount, in weight or volume, of all cleanup materials employed in this emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the measuring equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the measuring equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the measuring equipment, the permittee shall perform calibration and accuracy tests on the measuring equipment on a monthly basis during the first six months of operation of the measuring equipment. The permittee calibration and accuracy tests for the measuring equipment shall include the cleanup material employed by the permittee. After completing six months of calibration and accuracy tests of the measuring equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (6) The permittee shall utilize one or more compliance options, as specified in 40 CFR 63.5810 to demonstrate compliance with the emission standards for open molding in Table 3 of this subpart, as described in the following sections:

63.5810(a)	individual resin or gel coat compliance demonstration
63.5810(b)	average individual organic HAP emissions limit compliance demonstration for all operations and application methods
63.5810(c)	weighted average emission limit compliance demonstration
63.5810(d)	organic HAP emission limit compliance demonstration for one resin type and application method

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR 63.5810]

- (7) The permittee is currently demonstrating compliance through the option specified in 63.5810(a). The permittee shall comply with the following data collection, emission calculation, and record keeping requirements, in addition to those listed in d)(8) below:

- a. Calculate your actual organic HAP emissions factor for each different process stream within this emissions unit. A process stream is defined as each individual combination of resin or gel coat, application technique, and control technique. Process streams within operations types are considered different from each other if any of the following four characteristics vary: the neat resin plus or neat gel coat plus organic HAP content, the gel coat type, the application technique, or the control technique. You must calculate organic HAP emissions factors for each different process stream by using the appropriate equations in Table 1 of 40 CFR Part 63 Subpart WWWW for open molding and for centrifugal casting, or site-specific organic HAP emissions factors discussed in §63.5796. The emission factor calculation should include any and all emission reduction techniques used. If you are using vapor suppressants to reduce HAP emissions, you must determine the vapor suppressant effectiveness (VSE) by conducting testing according to the procedures specified in appendix A to subpart WWWW of 40 CFR part 63.

Should the permittee choose to demonstrate compliance with the emission limitations listed in b)(2)b. by one of the alternative compliance demonstrations specified in d)(6), the permittee shall collect and record the information specified in 40 CFR 63.5810(b),(c), or (d), as appropriate.

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR 63.5810]

- (8) The permittee shall comply with the applicable monitoring and record keeping requirements under 40 CFR Part 63, Subpart WWWW, including the following sections:

63.5895(c) - (d)	records of resin and gel coat use, organic HAP content, operation and application method(s)
------------------	---



Effective Date: To be entered upon final issuance

63.5915(a)	copy of compliance notification(s) and report(s)
63.5915(c)	records of all calculations and data used to determine organic HAP emissions factors or average organic HAP contents for operations and application methods as specified under 63.5810
63.5915(d)	certified statement of compliance with work practice requirements
63.5920(a) – (d)	record keeping format and retention requirements

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (9) The permittee shall maintain documentation of the manufacturer's recommendations, instructions, or operating manuals for the dry particulate filter, along with documentation of any modifications deemed necessary by the permittee. These documents shall be maintained at the facility and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (10) The permittee shall conduct periodic inspections of the dry particulate filter to determine whether it is operating in accordance with the manufacturer's recommendations, instructions, or operating manuals with any modifications deemed necessary by the permittee or operator. These inspections shall be performed at a frequency that shall be based upon the recommendation of the manufacturer and the permittee shall maintain a copy of the manufacturer's recommended inspection frequency and it shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (11) In addition to the recommended periodic inspections, not less than once each calendar year the permittee shall conduct a comprehensive inspection of the dry particulate filter while the emissions unit is shut down and perform any needed maintenance and repair to ensure that it is operated in accordance with the manufacturer's recommendations.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (12) The permittee shall document each inspection (periodic and annual) of the dry particulate filter system and shall maintain the following information:
 - a. the date of the inspection;
 - b. a description of each/any problem identified and the date it was corrected;
 - c. a description of any maintenance and repairs performed; and
 - d. the name of person who performed the inspection.

These records shall be maintained at the facility for not less than five years from the date the inspection and any necessary maintenance or repairs were completed and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (13) The permittee shall maintain records that document any time periods when the dry particulate filter was not in service when the emissions unit(s) was/were in operation, as well as, a record of all operations during which the dry particulate filter was not operated according to the manufacturer's recommendations with any documented modifications made by the permittee. These records shall be maintained for a period of not less than five years and shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (14) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05474: d)(1) through d)(13). The monitoring and recordkeeping requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
- a. daily cleanup material usage restriction;
 - b. OC content limitation for the cleanup material;
 - c. daily OC emission limitation for the cleanup material;
 - d. hourly OC emission limitation for coatings;
 - e. daily OC emission limitation for coatings;
 - f. hourly PE/PM10 emission limitation;
 - g. daily PE/PM10 emission limitation;
 - h. rolling 12-month emission limitation for PE/PM10;
 - i. hourly usage limitation
 - j. daily usage limitation;
 - k. rolling 12-month usage limitation; and
 - l. any daily record showing that the dry particulate filter system was not in service or not operated according to manufacturer's recommendations (with any documented modifications made by the permittee) when the emissions unit(s) was/were in operation.



Effective Date: To be entered upon final issuance

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

- (2) The permittee shall submit annual reports to the Hamilton County Department of Environmental Services that specify the following:
 - a. total amount, in gallons, of cleanup material employed for the calendar year;
 - b. total OC emissions from the cleanup material employed, in tons, for the calendar year; and
 - c. rolling, 12-month summation of OC emissions from this emissions unit, for each calendar month.

This report shall be submitted by January 31 of each year and cover the previous calendar year.

[Authority for term: OAC rules 3745-77-07(C)(1)].

- (3) The permittee shall notify the Hamilton County Department of Environmental Services in writing of each day during which any photochemically reactive cleanup material [as defined in OAC rule 3745-21-01(C)(5)] was employed in this emissions unit. The notification shall include a copy of such record and shall be sent to the Hamilton County Department of Environmental Services within 45 days after the exceedance occurs.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) Upon replacement and/or initial operation of any metering or measuring equipment as specified in d)(4) and d)(5) of this permit, the permittee shall provide the Hamilton County Department of Environmental Services the following information: the name of the manufacturer of the metering/measuring equipment, the make and model of the metering/measuring equipment, calibration data (e.g., volume of coating per pump stroke), a copy of the manufacturer's specifications and warranty for the accuracy of the metering/measuring equipment and the actual accuracy of the material measurements (by weight or by volume) recorded for the metering/measuring equipment.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (5) The permittee shall submit calibration and accuracy test results for the metering equipment and measuring equipment specified in d)(4) and d)(5) of the terms and conditions of this permit. The calibration and accuracy tests results shall be submitted to the Hamilton County Department of Environmental Services by January 30 and July 30 of each calendar year, and shall cover the previous six-month period.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (6) The permittee shall submit semi-annual reports and such other notifications and reports to the Hamilton County Department of Environmental Services as are required in 40 CFR Part 63, Subpart WWWW, pursuant to the following sections:

63.5905(b)	15-day notification of change(s)
------------	----------------------------------



63.5910(a) - (b) and Table 14	semi-annual compliance reports
63.5910(c) - (i) and Table 14	content of semi-annual compliance reports

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

(7) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05474: e)(1) through e)(6). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.

f) Testing Requirements

(1) Compliance with the emission limitations and material usage restrictions specified in b) and c) shall be determined by the following methods:

a. Emission Limitations:

OC emissions shall not exceed 10.1 pounds per hour from coatings (resin and gel coat);

OC emissions shall not exceed 157 pounds per day from coatings (resin and gel coat);

OC emissions shall not exceed 15.5 tons per year (TPY) from coatings (resins and gel coats) for this emissions units, based on a rolling, 12-month summation of the coating emissions.

Applicable Compliance Method:

Compliance with the hourly OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly OC emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 – 4, 18 and 25.

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), OAC rule 3745-31-05(A)(3), 3745-31-05(D), and 3745-21-07(G)(2)].

b. Emission Limitations:

OC emissions shall not exceed 13.2 pounds per day from cleanup materials.

OC emissions shall not exceed 2.4 tons per year from cleanup materials.

Applicable Compliance Method:

Compliance with the daily OC emission limitation from cleanup materials shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation from cleanup material shall be determined by the record keeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)].

c. Emission Limitation:

The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.

Applicable Compliance Method:

Compliance with the OC content limitation shall be determined by the record keeping requirements specified in d)(1). Formulation data or US EPA Method 24 shall be used to determine the OC content of any cleanup material employed in this emissions unit.

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

d. Material Usage Restriction:

The maximum amount of all cleanup material employed in this emissions unit shall not exceed 2 gallons per day and 720 gallons per year.

Applicable Compliance Method:

Compliance with the daily cleanup material usage restriction shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual cleanup material usage restriction shall be determined by the recordkeeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

e. Emission Limitation:

See the organic HAP emission limitations noted in b)(2)b.

Applicable Compliance Method:

Compliance with the organic HAP emission limitation shall be based upon the information collected and recorded in d)(6) - d)(8) of this permit.

[Authority for term: OAC rules 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

f. Emission Limitations:

PE/PM-10 emissions shall not exceed 0.39 pound per hour;

PE/PM-10 emissions shall not exceed 6.07 pounds per day; and

PE/PM-10 emissions shall not exceed 0.60 ton per year.

Applicable Compliance Method:

Compliance with the hourly PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly PE/PM10 emission limitation through emission tests performed in accordance with 40 CFR, Part 60, Appendix A, Methods 1-5.

Compliance with the daily PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and OAC 3745-31-05(D)].

- (2) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05474: f)(1)a. through f)(1)f. The testing requirements contained in the above-referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.

g) Miscellaneous Requirements

- (1) None.



8. P031, Service Gel Coat Bldg B - 2

Operations, Property and/or Equipment Description:

Service Gel Coat 2 Bldg B

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05196)	<p>The Organic Compound (OC) emissions from resin application shall not exceed 8 pounds per hour and 40 lbs/day.</p> <p>OC emissions (acetone) shall not exceed 3.3 pounds per day from cleanup materials.</p> <p>OC emissions (acetone) shall not exceed 0.495 ton per year from cleanup materials.</p> <p>Particulate emissions (PE) and Particulate matter with a diameter of 10 microns or less (PM-10) shall not exceed 0.28 pound per hour.</p> <p>PE/PM10 emissions shall not exceed 1.38 pounds per day.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(D) and 3745-17-07(A)(1).</p> <p>See c)(1) - c)(4).</p>
b.	OAC rule 3745-31-05(D) Synthetic Minor Determination to avoid the Emission Offset Policy for	<p>See b)(2)a.</p> <p>PE/PM10 emissions shall not exceed 0.06 ton per year based on a rolling, 12-</p>



Effective Date: To be entered upon final issuance

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
	VOC.	month summation.
c.	OAC rule 3745-17-07(A)(1)	Visible particulate emissions from any stack shall not exceed 20% opacity, as a six minute average, except as specified by rule.
d.	OAC rule 3745-17-11(B)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
e.	OAC rule 3745-17-11(C)(3)	The Permit to Install for this emissions unit was issued July 9, 2002 (post January 1, 1990). Therefore, the emissions unit is exempt from the requirements of OAC rule 3745-17-11(C)(1) and (2). See b)(2)c.
f.	OAC rule 3745-21-07(G)(2)	The emission limitations specified by this rule are the same as the emission limitation established pursuant to OAC rule 3745-31-05(A)(3). See b)(2)d.
g.	40 CFR Part 63, Subpart WWWW (40 CFR 63.5780-5935) [In accordance with 63.5805(b), this emissions unit is an open molding gel coating application at an existing reinforced plastic composites production facility subject to the emission limitations and work practices specified in 40 CFR 63.5805(b)]	Table 3 to 40 CFR Part 63, Subpart WWWW – Organic Hazardous Air Pollutant (HAP) Emission Limits for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. See b)(2)b. and e. Table 4 to 40 CFR Part 63, Subpart WWWW – Applicable Work Practice Standards. See c)(5) and c)(6).
h.	40 CFR 63.1-15, Subpart A (40 CFR 63.5925)	Table 15 to 40 CFR Part 63, Subpart WWWW – Applicability of General Provisions (Subpart A) to Subpart WWWW shows which parts of the General Provisions in 40 CFR Part 63.1 – 15 apply.

(2) Additional Terms and Conditions

- a. The annual OC emission limit, for the coatings, employed in emissions units P002 through P005, P030, P031, P033 and P034, combined shall not exceed 25.0 TPY, based on a rolling, 12-month summation.

For purposes of clarification of non attainment new source review (NSR) permitting requirements and this Title V renewal permitting action, the permittee shall only employ non-VOC based cleanup materials. No cleanup materials with VOC as defined in OAC rule 3745-21-01 shall be employed. The emission of non-VOC based cleanup materials does not count towards the Synthetic Minor Determination to avoid the Emission Offset Policy for VOC established in PTI 14-05196.

- b. The following organic HAP emission limitations shall not be exceeded based on a 12-month rolling average.

Gel Coat Type	Organic HAP Emission Limit
Tooling gel coating	440 lbs/ton
White/off white pigmented gel coating	267 lbs/ton
All other pigmented gel coating	377 lbs/ton
CR/HS or high performance gel coating	605 lbs/ton
Fire retardant gel coat	854 lbs/ton
Clear Production gel coat	522 lbs/ton

- c. On February 1, 2008, OAC rule 3745-17-11 was revised to include paragraph (C), pertaining to control requirements for particulate emissions from surface coating processes. These control requirements and the associated operational restrictions, monitoring, record keeping, and reporting requirements contained in this permit shall become federally enforceable on the date the U.S. EPA approves paragraph (C) of OAC rule 3745-17-11 as a revision to the Ohio State Implementation Plan.
- d. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP); however, until the U.S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio.
- e. This emissions unit is subject to the requirements of 40 CFR Part 63 Subpart WWWW - National Emissions Standards for Hazardous Air Pollutants for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. The permittee shall comply with the applicable emission limitations and operational restrictions specified in 40 CFR Part 63.5780 – 63.5930. The complete MACT requirements, including the MACT General Provisions may be accessed via the internet from the Electronic Code

Effective Date: To be entered upon final issuance

of Federal Regulations (e-CFR) website <http://ecfr.gpoaccess.gov> or by contacting the appropriate Ohio EPA District Office or local air agency.

c) Operational Restrictions

- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 0.5 gallon per day and 150 gallons per year.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (2) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 lbs of OC/gallon.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (3) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1), 3745-31-05(A)(3) and 3745-21-07(G)(2)]

- (4) The permittee shall operate the dry filtration system for the control of particulate emissions whenever this emissions unit is in operation and shall maintain the dry particulate filter in accordance with the manufacturer's recommendations, instructions, and/or operating manual(s), with any modifications deemed necessary by the permittee.

In the event the particulate filter system is not operating in accordance with the manufacturer's recommendations, instructions, or operating manual, with any modifications deemed necessary by the permittee, the control device shall be expeditiously repaired or otherwise returned to these documented operating conditions.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (5) The permittee shall employ only non-HAP-containing cleanup materials in each emissions unit, except that styrene may be used as a cleaner in closed systems, and organic HAP containing cleaners may be used to clean cured resin from application equipment. Application equipment includes any equipment that directly contacts resin.

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR Part 63, Subpart WWWW Table 4]

- (6) The permittee shall keep containers that store HAP-containing coating materials and cleanup materials closed or covered, except during the addition or removal of materials. Bulk HAP-containing materials storage tanks may be vented as necessary for safety.

[Authority for term: OAC rules 3745-77-07(A)(1) and 40 CFR Part 63, Subpart WWWW Table 4]

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall collect and record the following information each day this emissions unit is in operation:

- a. company identification for each coating material (resin and/or gel coat) and cleanup material applied;
- b. number of pounds of each coating material (resin and/or gel coat) applied;
- c. the HAP content, recorded in percent by weight, of each coating material (resin and/or gel coat) employed in this emissions unit;
- d. calculated OC (assumed equal to the organic HAP) emission factor using the equations to calculate organic HAP emission factors from Table 1 of 40 CFR Part 63, Subpart WWWW, in pounds of OC per ton of coating material (resin and/or gel coat) applied;
- e. total daily OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per day $[d)(1)b./2000 \times d)(1)d.]$;
- f. number of hours the emissions unit was in operation;
- g. average hourly OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per hour $[d)(1)e. \text{ divided by } d)(1)f.]$.
- h. total number of gallons of cleanup material applied;
- i. OC content of the cleanup material employed, in pounds per gallon;
- j. daily OC emissions from the cleanup material employed, in pounds $[d)(1)h. \times d)(1)i.]$;
- k. total PE/PM10 emission rate for all coatings employed, in pounds per day $[\text{summation of } d)(1)b. \times (1 - \text{HAP content, percent by weight}) \times 0.25 \text{ (25\% overspray)} \times (1 - 0.985, \text{ the control efficiency of the dry filtration system})]**$;
- l. average hourly PE/PM10 emission rate for all coatings employed, in pounds/hour $[d)(1)k \text{ divided by } d)(1)f.]$;
- m. a determination whether or not each cleanup material employed is a photochemically reactive material, as defined in OAC rule 3745-21-05(C)(5); and
- n. a determination whether or not each cleanup material employed is a non-HAP material, as identified in Section 112(b) of the Clean Air Act.

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit].

** The 25% overspray and 98.5% control efficiency were used to establish the PE/PM10 emission rates established in PTI 14-05196 and are based on conservative engineering assumptions.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D), 3745-21-07(G)(2), and 40 CFR Part 63 Subpart WWWW]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:
- a. total OC emissions from all the coatings (resins and/or gel coat) employed, in tons [summation of d)(1)e. for all days of the calendar month, and divided by 2000 pounds per ton];
 - b. updated rolling, 12-month summation of OC emission from all the coatings (resins and/or gel coats) employed, in tons [this shall include the total for the current month's OC emissions, plus the total for the preceding eleven calendar months];
 - c. rolling, 12-month summation of OC emissions from all the coatings (resins and/or gel coats) employed, in tons, for emissions units P002 through P005, P030, P031, P033 and P034;
 - d. total PE/PM10 emissions for all coatings employed, in tons [summation of the data from d)(1)k. for all days of the calendar month divided by 2000 pounds per ton]; and
 - e. rolling, 12-month summation of PE/PM10 emissions from all coatings employed, in tons [this shall include the total for the current month's PE/PM10 emissions, plus the total for the preceding eleven calendar months].

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and 3745-31-05(D)]

- (3) The permittee shall maintain annual records of the following information for this emissions unit:
- a. total number of gallons of cleanup material employed [summation of d)(1)h. for all days the emissions unit was in operation]; and
 - b. total OC emissions from cleanup materials employed, in pounds [summation of d)(1)j. for all days of the emissions unit was in operation].

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) The permittee shall operate and maintain metering equipment to measure the amount of all resins and gel coats used in each emissions unit. The permittee shall calibrate the metering equipment to measure the amount, in weight or volume, of all resins and gel coats used in each emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the metering equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the metering equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the metering equipment, the permittee shall perform calibration and accuracy tests on the metering equipment on a monthly basis during the first six months of operation of the meters. The permittee calibration and accuracy tests for the metering equipment shall



Effective Date: To be entered upon final issuance

include two resins (the highest and lowest density resins) and two gel coats (the highest and lowest density gel coats). After completing six months of calibration and accuracy tests of the metering equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (5) The permittee shall operate and maintain measuring equipment to measure the amount of cleanup materials employed in this emissions unit. The permittee shall calibrate the measuring equipment to measure the amount, in weight or volume, of all cleanup materials employed in this emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the measuring equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the measuring equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the measuring equipment, the permittee shall perform calibration and accuracy tests on the measuring equipment on a monthly basis during the first six months of operation of the measuring equipment. The permittee calibration and accuracy tests for the measuring equipment shall include the cleanup material employed by the permittee. After completing six months of calibration and accuracy tests of the measuring equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (6) The permittee shall utilize one or more compliance options, as specified in 40 CFR 63.5810 to demonstrate compliance with the emission standards for open molding in Table 3 of this subpart, as described in the following sections:

63.5810(a)	individual resin or gel coat compliance demonstration
63.5810(b)	average individual organic HAP emissions limit compliance demonstration for all operations and application methods
63.5810(c)	weighted average emission limit compliance demonstration
63.5810(d)	organic HAP emission limit compliance demonstration for one resin type and application method

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR 63.5810]

- (7) The permittee is currently demonstrating compliance through the option specified in 63.5810(a). The permittee shall comply with the following data collection, emission calculation, and record keeping requirements, in addition to those listed in d)(8) below:

- a. Calculate your actual organic HAP emissions factor for each different process stream within this emissions unit. A process stream is defined as each individual combination of resin or gel coat, application technique, and control technique. Process streams within operations types are considered different from each other if any of the following four characteristics vary: the neat resin plus or neat gel coat plus organic HAP content, the gel coat type, the application technique, or the control technique. You must calculate organic HAP emissions factors for each different process stream by using the appropriate equations in Table 1 of 40 CFR Part 63 Subpart WWWW for open molding and for centrifugal casting, or site-specific organic HAP emissions factors discussed in §63.5796. The emission factor calculation should include any and all emission reduction techniques used. If you are using vapor suppressants to reduce HAP emissions, you must determine the vapor suppressant effectiveness (VSE) by conducting testing according to the procedures specified in appendix A to subpart WWWW of 40 CFR part 63.

Should the permittee choose to demonstrate compliance with the emission limitations listed in b)(2)b. by one of the alternative compliance demonstrations specified in d)(6), the permittee shall collect and record the information specified in 40 CFR 63.5810(b),(c), or (d), as appropriate.

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR 63.5810]

- (8) The permittee shall comply with the applicable monitoring and record keeping requirements under 40 CFR Part 63, Subpart WWWW, including the following sections:

63.5895(c) - (d)	records of resin and gel coat use, organic HAP content, operation and application method(s)
63.5915(a)	copy of compliance notification(s) and report(s)
63.5915(c)	records of all calculations and data used to determine organic HAP emissions factors or average organic HAP contents for operations and application methods as specified under 63.5810
63.5915(d)	certified statement of compliance with work practice requirements
63.5920(a) – (d)	record keeping format and retention requirements

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (9) The permittee shall maintain documentation of the manufacturer's recommendations, instructions, or operating manuals for the dry particulate filter, along with documentation of any modifications deemed necessary by the permittee. These documents shall be maintained at the facility and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (10) The permittee shall conduct periodic inspections of the dry particulate filter to determine whether it is operating in accordance with the manufacturer's recommendations, instructions, or operating manuals with any modifications deemed necessary by the permittee or operator. These inspections shall be performed at a frequency that shall be based upon the recommendation of the manufacturer and the permittee shall maintain a copy of the manufacturer's recommended inspection frequency and it shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (11) In addition to the recommended periodic inspections, not less than once each calendar year the permittee shall conduct a comprehensive inspection of the dry particulate filter while the emissions unit is shut down and perform any needed maintenance and repair to ensure that it is operated in accordance with the manufacturer's recommendations.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (12) The permittee shall document each inspection (periodic and annual) of the dry particulate filter system and shall maintain the following information:

- a. the date of the inspection;
- b. a description of each/any problem identified and the date it was corrected;
- c. a description of any maintenance and repairs performed; and
- d. the name of person who performed the inspection.

These records shall be maintained at the facility for not less than five years from the date the inspection and any necessary maintenance or repairs were completed and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (13) The permittee shall maintain records that document any time periods when the dry particulate filter was not in service when the emissions unit(s) was/were in operation, as well as, a record of all operations during which the dry particulate filter was not operated according to the manufacturer's recommendations with any documented modifications made by the permittee. These records shall be maintained for a period of not less than five years and shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (14) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05196: d)(1) through d)(13). The monitoring and recordkeeping requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
 - a. daily cleanup material usage restriction;
 - b. OC content limitation for the cleanup material;
 - c. daily OC emission limitation for the cleanup material;
 - d. hourly OC emission limitation for coatings;
 - e. daily OC emission limitation for coatings;
 - f. hourly PE/PM10 emission limitation;
 - g. daily PE/PM10 emission limitation;
 - h. rolling 12-month emission limitation for PE/PM10;
 - i. rolling 12-month combined OC emission limitation for P002 through P005, P030, P031, P033 and P034; and
 - j. any daily record showing that the dry particulate filter system was not in service or not operated according to manufacturer's recommendations (with any documented modifications made by the permittee) when the emissions unit(s) was/were in operation.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

- (2) The permittee shall submit annual reports to the Hamilton County Department of Environmental Services that specify the following:
 - a. total amount, in gallons, of cleanup material employed for the calendar year; and
 - b. total OC emissions from the cleanup material employed, in tons, for the calendar year.

This report shall be submitted by January 31 of each year and cover the previous calendar year.

[Authority for term: OAC rules 3745-77-07(C)(1)].

- (3) The permittee shall notify the Hamilton County Department of Environmental Services in writing of each day during which any photochemically reactive cleanup material [as defined in OAC rule 3745-21-01] was employed in this emissions unit. The notification shall include a copy of such record and shall be sent to the Hamilton County Department of Environmental Services within 45 days after the exceedance occurs.



Effective Date: To be entered upon final issuance

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) Upon replacement and/or initial operation of any metering or measuring equipment as specified in d)(4) and d)(5) of this permit, the permittee shall provide the Hamilton County Department of Environmental Services the following information: the name of the manufacturer of the metering/measuring equipment, the make and model of the metering/measuring equipment, calibration data (e.g., volume of coating per pump stroke), a copy of the manufacturer's specifications and warranty for the accuracy of the metering/measuring equipment and the actual accuracy of the material measurements (by weight or by volume) recorded for the metering/measuring equipment.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (5) The permittee shall submit calibration and accuracy test results for the metering equipment and measuring equipment specified in d)(4) and d)(5) of the terms and conditions of this permit. The calibration and accuracy tests results shall be submitted to the Hamilton County Department of Environmental Services by January 30 and July 30 of each calendar year, and shall cover the previous six-month period.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (6) The permittee shall submit semi-annual reports and such other notifications and reports to the Hamilton County Department of Environmental Services as are required in 40 CFR Part 63, Subpart WWWW, pursuant to the following sections:

63.5905(b)	15-day notification of change(s)
63.5910(a) - (b) and Table 14	semi-annual compliance reports
63.5910(c) - (i) and Table 14	content of semi-annual compliance reports

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (7) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05196: e)(1) through e)(6). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.

f) Testing Requirements

- (1) Compliance with the emission limitations and material usage restrictions specified in b) and c) shall be determined by the following methods:

a. Emission Limitations:

OC emissions shall not exceed 8 pounds per hour from coatings (resin and gel coat);

Effective Date: To be entered upon final issuance

OC emissions shall not exceed 40 pounds per day from coatings (resin and gel coat); and

OC emissions shall not exceed 25.0 TPY from coatings (resins and gel coats) from emissions units P002 through P005, P030, P031, P033 and P034, combined, based on a rolling, 12-month summation of the coating emissions.

Applicable Compliance Method:

Compliance with the hourly OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly OC emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 – 4, 18 and 25.

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), OAC rule 3745-31-05(A)(3), 3745-31-05(D), and 3745-21-07(G)(2)].

b. Emission Limitations:

OC emissions shall not exceed 3.3 pounds per day from cleanup materials.

OC emissions shall not exceed 0.495 ton per year from cleanup materials.

Applicable Compliance Method:

Compliance with the daily OC emission limitation from cleanup materials shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation from cleanup material shall be determined by the record keeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)].

c. Emission Limitation:

The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.

Applicable Compliance Method:

Compliance with the OC content limitation shall be determined by the record keeping requirements specified in d)(1). Formulation data or US EPA Method 24 shall be used to determine the OC content of any cleanup material employed in this emissions unit.



[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

d. Material Usage Restriction:

The maximum amount of all cleanup material employed in this emissions unit shall not exceed 0.5 gallon per day and 150 gallons per year.

Applicable Compliance Method:

Compliance with the daily cleanup material usage restriction shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual cleanup material usage restriction shall be determined by the recordkeeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

e. Emission Limitation:

See the organic HAP emission limitations noted in b)(2)b.

Applicable Compliance Method:

Compliance with the organic HAP emission limitation shall be based upon the information collected and recorded in d)(6) - d)(8) of this permit.

[Authority for term: OAC rules 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

f. Emission Limitations:

PE/PM-10 emissions shall not exceed 0.28 pound per hour;

PE/PM-10 emissions shall not exceed 1.38 pounds per day; and

PE/PM-10 emissions shall not exceed 0.06 ton per year, based on a rolling, 12-month summation.

Applicable Compliance Method:

Compliance with the hourly PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly PE/PM10 emission limitation through emission tests performed in accordance with 40 CFR, Part 60, Appendix A, Methods 1-5.

Compliance with the daily PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(2).



[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and OAC 3745-31-05(D)].

- (2) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05196: f)(1)a. through f)(1)f. The testing requirements contained in the above-referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.
- g) Miscellaneous Requirements
 - (1) None.



9. P036, Hand Layup Area

Operations, Property and/or Equipment Description:

Hand Layup Area

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05196)	The Organic Compound (OC) emissions from resin application shall not exceed 1 pound per hour and 40 lbs/day. OC emissions (acetone) shall not exceed 19.8 pounds per day from cleanup materials. OC emissions (acetone) shall not exceed 2.97 tons per year from cleanup materials. The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(D) See c)(1) - c)(3).
b.	OAC rule 3745-31-05(D) Synthetic Minor Determination to avoid the Emission Offset Policy for VOC.	See b)(2)a.
c.	OAC rule 3745-21-07(G)(2)	The emission limitations specified by this rule are the same as or less stringent than emission limitation established pursuant to OAC rule 3745-31-05(A)(3). See b)(2)c.



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
d.	40 CFR Part 63, Subpart WWWW (40 CFR 63.5780-5935) [In accordance with 63.5805(b), this emissions unit is an open molding using manual resin application at an existing reinforced plastic composites production facility subject to the emission limitations and work practices specified in 40 CFR 63.5805(b)]	Table 3 to 40 CFR Part 63, Subpart WWWW – Organic Hazardous Air Pollutant (HAP) Emission Limits for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. See b)(2)b. and d. Table 4 to 40 CFR Part 63, Subpart WWWW – Applicable Work Practice Standards. See c)(4) and c)(5).
e.	40 CFR 63.1-15, Subpart A (40 CFR 63.5925)	Table 15 to 40 CFR Part 63, Subpart WWWW – Applicability of General Provisions (Subpart A) to Subpart WWWW shows which parts of the General Provisions in 40 CFR Part 63.1 – 15 apply.

(2) Additional Terms and Conditions

- a. The annual OC emission limit, for the coatings employed in this emissions unit shall not exceed 1.0 TPY, based on a rolling, 12-month summation. For purposes of clarification of non attainment new source review (NSR) permitting requirements and this Title V renewal permitting action, the permittee shall only employ non-VOC based cleanup materials. No cleanup materials with VOC as defined in OAC rule 3745-21-01 shall be employed. The emission of non-VOC based cleanup materials does not count towards the Synthetic Minor Determination to avoid the Emission Offset Policy for VOC established in PTI 14-05196.
- b. The following organic HAP emission limitations shall not be exceeded based on a 12-month rolling average.

Operation Type	Organic HAP Emission Limit
Corrosion Resistant/Highs Strength (CR/HS)	123 lbs/ton
Non-CR/HS	87 lbs/ton
Tooling	157 lbs/ton
Low flame spread/low smoke products	238 lbs/ton
Shrinkage Controlled Resin	180 lbs/ton

- c. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the

Effective Date: To be entered upon final issuance

U.S. EPA as a revision to Ohio's State Implementation Plan (SIP); however, until the U.S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio.

- d. This emissions unit is subject to the requirements of 40 CFR Part 63 Subpart WWWW - National Emissions Standards for Hazardous Air Pollutants for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. The permittee shall comply with the applicable emission limitations and operational restrictions specified in 40 CFR Part 63.5780 – 63.5930. The complete MACT requirements, including the MACT General Provisions may be accessed via the internet from the Electronic Code of Federal Regulations (e-CFR) website <http://ecfr.gpoaccess.gov> or by contacting the appropriate Ohio EPA District Office or local air agency.

c) Operational Restrictions

- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3.0 gallons per day and 900 gallons per year.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (2) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 lbs of OC/gallon.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (3) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1), 3745-31-05(A)(3) and 3745-21-07(G)(2)]

- (4) The permittee shall employ only non-HAP-containing cleanup materials in each emissions unit, except that styrene may be used as a cleaner in closed systems, and organic HAP containing cleaners may be used to clean cured resin from application equipment. Application equipment includes any equipment that directly contacts resin.

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR Part 63, Subpart WWWW Table 4]

- (5) The permittee shall keep containers that store HAP-containing coating materials and cleanup materials closed or covered, except during the addition or removal of materials. Bulk HAP-containing materials storage tanks may be vented as necessary for safety.

[Authority for term: OAC rules 3745-77-07(A)(1) and 40 CFR Part 63, Subpart WWWW Table 4]

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall collect and record the following information each day this emissions unit is in operation:

Effective Date: To be entered upon final issuance

- a. company identification for each coating material (resin and/or gel coat) and cleanup material applied;
- b. number of pounds of each coating material (resin and/or gel coat) applied;
- c. the HAP content, recorded in percent by weight, of each coating material (resin and/or gel coat) employed in this emissions unit;
- d. calculated OC (assumed equal to the organic HAP) emission factor using the equations to calculate organic HAP emission factors from Table 1 of 40 CFR Part 63, Subpart WWWW, in pounds of OC per ton of coating material (resin and/or gel coat) applied;
- e. total daily OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per day $[d)(1)b./2000 \times d)(1)d.]$;
- f. number of hours the emissions unit was in operation;
- g. average hourly OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per hour $[d)(1)e. \text{ divided by } d)(1)f.]$.
- h. total number of gallons of cleanup material applied;
- i. OC content of the cleanup material employed, in pounds per gallon;
- j. daily OC emissions from the cleanup material employed, in pounds $[d)(1)h. \times d)(1)i.]$;
- k. a determination whether or not each cleanup material employed is a photochemically reactive material, as defined in OAC rule 3745-21-05(C)(5); and
- l. a determination whether or not each cleanup material employed is a non-HAP material, as identified in Section 112(b) of the Clean Air Act.

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit].

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D), 3745-21-07(G)(2), and 40 CFR Part 63 Subpart WWWW]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:
 - a. total OC emissions from all the coatings (resins and/or gel coat) employed, in tons $[\text{summation of } d)(1)e. \text{ for all days of the calendar month, and divided by } 2000 \text{ pounds per ton}]$; and
 - b. updated rolling, 12-month summation of OC emission from all the coatings (resins and/or gel coats) employed, in tons $[\text{this shall include the total for the current month's OC emissions, plus the total for the preceding eleven calendar months}]$.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and 3745-31-05(D)]

- (3) The permittee shall maintain annual records of the following information for this emissions unit:
- a. total number of gallons of cleanup material employed [summation of d)(1)h. for all days the emissions unit was in operation]; and
 - b. total OC emissions from cleanup materials employed, in pounds [summation of d)(1)j. for all days of the emissions unit was in operation].

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) The permittee shall operate and maintain metering equipment to measure the amount of all resins and gel coats used in each emissions unit. The permittee shall calibrate the metering equipment to measure the amount, in weight or volume, of all resins and gel coats used in each emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the metering equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the metering equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the metering equipment, the permittee shall perform calibration and accuracy tests on the metering equipment on a monthly basis during the first six months of operation of the meters. The permittee calibration and accuracy tests for the metering equipment shall include two resins (the highest and lowest density resins) and two gel coats (the highest and lowest density gel coats). After completing six months of calibration and accuracy tests of the metering equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (5) The permittee shall operate and maintain measuring equipment to measure the amount of cleanup materials employed in this emissions unit. The permittee shall calibrate the measuring equipment to measure the amount, in weight or volume, of all cleanup materials employed in this emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the measuring equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the measuring equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the measuring equipment, the permittee shall perform calibration and accuracy tests on the measuring equipment on a monthly basis during the first six months of operation of the measuring equipment. The permittee calibration and accuracy tests for the measuring equipment shall include the cleanup material employed by the permittee. After completing six months of calibration and accuracy tests of the measuring equipment and

upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (6) The permittee shall utilize one or more compliance options, as specified in 40 CFR 63.5810 to demonstrate compliance with the emission standards for open molding in Table 3 of this subpart, as described in the following sections:

63.5810(a)	individual resin or gel coat compliance demonstration
63.5810(b)	average individual organic HAP emissions limit compliance demonstration for all operations and application methods
63.5810(c)	weighted average emission limit compliance demonstration
63.5810(d)	organic HAP emission limit compliance demonstration for one resin type and application method

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR 63.5810]

- (7) The permittee is currently demonstrating compliance through the option specified in 63.5810(a). The permittee shall comply with the following data collection, emission calculation, and record keeping requirements, in addition to those listed in d)(8) below:

- a. Calculate your actual organic HAP emissions factor for each different process stream within this emissions unit. A process stream is defined as each individual combination of resin or gel coat, application technique, and control technique. Process streams within operations types are considered different from each other if any of the following four characteristics vary: the neat resin plus or neat gel coat plus organic HAP content, the gel coat type, the application technique, or the control technique. You must calculate organic HAP emissions factors for each different process stream by using the appropriate equations in Table 1 of 40 CFR Part 63 Subpart WWWW for open molding and for centrifugal casting, or site-specific organic HAP emissions factors discussed in §63.5796. The emission factor calculation should include any and all emission reduction techniques used. If you are using vapor suppressants to reduce HAP emissions, you must determine the vapor suppressant effectiveness (VSE) by conducting testing according to the procedures specified in appendix A to subpart WWWW of 40 CFR part 63.

Should the permittee choose to demonstrate compliance with the emission limitations listed in b)(2)b. by one of the alternative compliance demonstrations specified in d)(6), the permittee shall collect and record the information specified in 40 CFR 63.5810(b),(c), or (d), as appropriate.

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR 63.5810]

- (8) The permittee shall comply with the applicable monitoring and record keeping requirements under 40 CFR Part 63, Subpart WWWW, including the following sections:

63.5895(c) - (d)	records of resin and gel coat use, organic HAP content, operation and application method(s)
63.5915(a)	copy of compliance notification(s) and report(s)
63.5915(c)	records of all calculations and data used to determine organic HAP emissions factors or average organic HAP contents for operations and application methods as specified under 63.5810
63.5915(d)	certified statement of compliance with work practice requirements
63.5920(a) – (d)	record keeping format and retention requirements

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (9) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05196: d)(1) through d)(8). The monitoring and recordkeeping requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
- a. daily cleanup material usage restriction;
 - b. OC content limitation for the cleanup material;
 - c. daily OC emission limitation for the cleanup material;
 - d. hourly OC emission limitation for coatings;
 - e. daily OC emission limitation for coatings; and
 - f. any daily record showing that the dry particulate filter system was not in service or not operated according to manufacturer’s recommendations (with any documented modifications made by the permittee) when the emissions unit(s) was/were in operation.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

- (2) The permittee shall submit annual reports to the Hamilton County Department of Environmental Services that specify the following:



Effective Date: To be entered upon final issuance

- a. total amount, in gallons, of cleanup material employed for the calendar year;
- b. total OC emissions from the cleanup material employed, in tons, for the calendar year; and
- c. rolling, 12-month summation of OC emissions from this emissions unit, for each calendar month.

This report shall be submitted by January 31 of each year and cover the previous calendar year.

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)].

- (3) The permittee shall notify the Hamilton County Department of Environmental Services in writing of each day during which any photochemically reactive cleanup material [as defined in OAC rule 3745-21-01(C)(5)] was employed in this emissions unit. The notification shall include a copy of such record and shall be sent to the Hamilton County Department of Environmental Services within 45 days after the exceedance occurs.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) Upon replacement and/or initial operation of any metering or measuring equipment as specified in d)(4) and d)(5) of this permit, the permittee shall provide the Hamilton County Department of Environmental Services the following information: the name of the manufacturer of the metering/measuring equipment, the make and model of the metering/measuring equipment, calibration data (e.g., volume of coating per pump stroke), a copy of the manufacturer's specifications and warranty for the accuracy of the metering/measuring equipment and the actual accuracy of the material measurements (by weight or by volume) recorded for the metering/measuring equipment.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (5) The permittee shall submit calibration and accuracy test results for the metering equipment and measuring equipment specified in d)(4) and d)(5) of the terms and conditions of this permit. The calibration and accuracy tests results shall be submitted to the Hamilton County Department of Environmental Services by January 30 and July 30 of each calendar year, and shall cover the previous six-month period.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (6) The permittee shall submit semi-annual reports and such other notifications and reports to the Hamilton County Department of Environmental Services as are required in 40 CFR Part 63, Subpart WWWW, pursuant to the following sections:

63.5905(b)	15-day notification of change(s)
63.5910(a) - (b) and Table 14	semi-annual compliance reports
63.5910(c) - (i) and Table 14	content of semi-annual compliance reports

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (7) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05196: e)(1) through e)(6). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.
- f) **Testing Requirements**
- (1) Compliance with the emission limitations and material usage restrictions specified in b) and c) shall be determined by the following methods:
- a. **Emission Limitations:**
- OC emissions shall not exceed 1 pound per hour from coatings (resin and gel coat);
- OC emissions shall not exceed 40 pounds per day from coatings (resin and gel coat); and
- OC emissions shall not exceed 1.0 ton per year (TPY) from coatings (resins and gel coats) based on a rolling, 12-month summation of the coating emissions.
- Applicable Compliance Method:**
- Compliance with the hourly OC emission limitation shall be determined by the record keeping requirements specified in d)(1).
- If required, the permittee shall demonstrate compliance with the hourly OC emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 – 4, 18 and 25.
- Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).
- Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).
- [Authority for term: OAC rules 3745-77-07(C)(1), OAC rule 3745-31-05(A)(3), 3745-31-05(D), and 3745-21-07(G)(2)].
- b. **Emission Limitations:**
- OC emissions shall not exceed 19.8 pounds per day from cleanup materials.
- OC emissions shall not exceed 2.97 tons per year from cleanup materials.
- Applicable Compliance Method:**
- Compliance with the daily OC emission limitation from cleanup materials shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation from cleanup material shall be determined by the record keeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)].

c. Emission Limitation:

The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.

Applicable Compliance Method:

Compliance with the OC content limitation shall be determined by the record keeping requirements specified in d)(1). Formulation data or US EPA Method 24 shall be used to determine the OC content of any cleanup material employed in this emissions unit.

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

d. Material Usage Restriction:

The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3 gallons per day and 900 gallons per year.

Applicable Compliance Method:

Compliance with the daily cleanup material usage restriction shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual cleanup material usage restriction shall be determined by the recordkeeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

e. Emission Limitation:

See the organic HAP emission limitations noted in b)(2)b.

Applicable Compliance Method:

Compliance with the organic HAP emission limitation shall be based upon the information collected and recorded in d)(6) - d)(8) of this permit.

[Authority for term: OAC rules 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (2) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05196: f)(1)a. through f)(1)e. The testing requirements contained in the above-referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.

Effective Date: To be entered upon final issuance

g) Miscellaneous Requirements

(1) None.



Effective Date: To be entered upon final issuance

10. P037, Tooling Gel Coat

Operations, Property and/or Equipment Description:

Tooling Gel Coat Pump

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05196)	The Organic Compound (OC) emissions from resin application shall not exceed 2 pounds per hour and 40 lbs/day. OC emissions (acetone) shall not exceed 3.3 pounds per day from cleanup materials. OC emissions (acetone) shall not exceed 0.495 ton per year from cleanup materials. Particulate emissions (PE) and Particulate matter with a diameter of 10 microns or less (PM-10) shall not exceed 0.27 pound per hour. PE/PM10 emissions shall not exceed 1.8 pounds per day. The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(D) and 3745-17-07(A)(1). See c)(1) - c)(4).
b.	OAC rule 3745-31-05(D) Synthetic Minor Determination to avoid the Emission Offset Policy for	See b)(2)a. PE/PM10 emissions shall not exceed 0.01 ton per year based on a rolling, 12-



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
	VOC.	month summation.
c.	OAC rule 3745-17-07(A)(1)	Visible particulate emissions from any stack shall not exceed 20% opacity, as a six minute average, except as specified by rule.
d.	OAC rule 3745-17-11(B)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
e.	OAC rule 3745-17-11(C)(3)	The Permit to Install for this emissions unit was issued July 9, 2002 (post January 1, 1990). Therefore, the emissions unit is exempt from the requirements of OAC rule 3745-17-11(C)(1) and (2). See b)(2)c.
f.	OAC rule 3745-21-07(G)(2)	The emission limitations specified by this rule are the same as or less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3). See b)(2)d.
g.	40 CFR Part 63, Subpart WWWW (40 CFR 63.5780-5935) [In accordance with 63.5805(b), this emissions unit is an open molding gel coating application at an existing reinforced plastic composites production facility subject to the emission limitations and work practices specified in 40 CFR 63.5805(b)]	Table 3 to 40 CFR Part 63, Subpart WWWW – Organic Hazardous Air Pollutant (HAP) Emission Limits for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. See b)(2)b. and e. Table 4 to 40 CFR Part 63, Subpart WWWW – Applicable Work Practice Standards. See c)(5) and c)(6).
h.	40 CFR 63.1-15, Subpart A (40 CFR 63.5925)	Table 15 to 40 CFR Part 63, Subpart WWWW – Applicability of General Provisions (Subpart A) to Subpart WWWW shows which parts of the General Provisions in 40 CFR Part 63.1 – 15 apply.

(2) Additional Terms and Conditions

a. The annual OC emission limit, for the coatings, employed in this emissions unit shall not exceed 0.3 TPY, based on a rolling, 12-month summation. For purposes of clarification of non attainment new source review (NSR) permitting requirements and this Title V renewal permitting action, the permittee shall only employ non-VOC based cleanup materials. No cleanup materials with VOC as defined in OAC rule 3745-21-01 shall be employed. The emission of non-VOC based cleanup materials does not count towards the Synthetic Minor Determination to avoid the Emission Offset Policy for VOC established in PTI 14-05196.

b. The following organic HAP emission limitations shall not be exceeded based on a 12-month rolling average.

Gel Coat Type	Organic HAP Emission Limit
Tooling gel coating	440 lbs/ton
White/off white pigmented gel coating	267 lbs/ton
All other pigmented gel coating	377 lbs/ton
CR/HS or high performance gel coating	605 lbs/ton
Fire retardant gel coat	854 lbs/ton
Clear Production gel coat	522 lbs/ton

c. On February 1, 2008, OAC rule 3745-17-11 was revised to include paragraph (C), pertaining to control requirements for particulate emissions from surface coating processes. These control requirements and the associated operational restrictions, monitoring, record keeping, and reporting requirements contained in this permit shall become federally enforceable on the date the U.S. EPA approves paragraph (C) of OAC rule 3745-17-11 as a revision to the Ohio State Implementation Plan.

d. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP); however, until the U.S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio.

e. This emissions unit is subject to the requirements of 40 CFR Part 63 Subpart WWWW - National Emissions Standards for Hazardous Air Pollutants for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. The permittee shall comply with the applicable emission limitations and operational restrictions specified in 40 CFR Part 63.5780 – 63.5930. The complete MACT requirements, including the MACT General Provisions may be accessed via the internet from the Electronic Code of Federal Regulations (e-CFR) website <http://ecfr.gpoaccess.gov> or by contacting the appropriate Ohio EPA District Office or local air agency.

c) Operational Restrictions

- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 0.5 gallon per day and 150 gallons per year.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (2) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 lbs of OC/gallon.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (3) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1), 3745-31-05(A)(3) and 3745-21-07(G)(2)]

- (4) The permittee shall operate the dry filtration system for the control of particulate emissions whenever this emissions unit is in operation and shall maintain the dry particulate filter in accordance with the manufacturer's recommendations, instructions, and/or operating manual(s), with any modifications deemed necessary by the permittee.

In the event the particulate filter system is not operating in accordance with the manufacturer's recommendations, instructions, or operating manual, with any modifications deemed necessary by the permittee, the control device shall be expeditiously repaired or otherwise returned to these documented operating conditions.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (5) The permittee shall employ only non-HAP-containing cleanup materials in each emissions unit, except that styrene may be used as a cleaner in closed systems, and organic HAP containing cleaners may be used to clean cured resin from application equipment. Application equipment includes any equipment that directly contacts resin.

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR Part 63, Subpart WWWW Table 4]

- (6) The permittee shall keep containers that store HAP-containing coating materials and cleanup materials closed or covered, except during the addition or removal of materials. Bulk HAP-containing materials storage tanks may be vented as necessary for safety.

[Authority for term: OAC rules 3745-77-07(A)(1) and 40 CFR Part 63, Subpart WWWW Table 4]

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall collect and record the following information each day this emissions unit is in operation:

- a. company identification for each coating material (resin and/or gel coat) and cleanup material applied;

Effective Date: To be entered upon final issuance

- b. number of pounds of each coating material (resin and/or gel coat) applied;
- c. the HAP content, recorded in percent by weight, of each coating material (resin and/or gel coat) employed in this emissions unit;
- d. calculated OC (assumed equal to the organic HAP) emission factor using the equations to calculate organic HAP emission factors from Table 1 of 40 CFR Part 63, Subpart WWWW, in pounds of OC per ton of coating material (resin and/or gel coat) applied;
- e. total daily OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per day $[d)(1)b./2000 \times d)(1)d.]$;
- f. number of hours the emissions unit was in operation;
- g. average hourly OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per hour $[d)(1)e. \text{ divided by } d)(1)f.]$.
- h. total number of gallons of cleanup material applied;
- i. OC content of the cleanup material employed, in pounds per gallon;
- j. daily OC emissions from the cleanup material employed, in pounds $[d)(1)h. \times d)(1)i.]$;
- k. total PE/PM10 emission rate for all coatings employed, in pounds per day $[\text{summation of } d)(1)b. \times (1 - \text{HAP content, percent by weight}) \times 0.25 \text{ (25\% overspray)} \times (1 - 0.985, \text{ the control efficiency of the dry filtration system})]**$;
- l. average hourly PE/PM10 emission rate for all coatings employed, in pounds/hour $[d)(1)k. \text{ divided by } d)(1)f.]$;
- m. a determination whether or not each cleanup material employed is a photochemically reactive material, as defined in OAC rule 3745-21-05(C)(5); and
- n. a determination whether or not each cleanup material employed is a non-HAP material, as identified in Section 112(b) of the Clean Air Act.

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit].

** The 25% overspray and 98.5% control efficiency were used to establish the PE/PM10 emission rates established in PTI 14-05196 and are based on conservative engineering assumptions.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D), 3745-21-07(G)(2), and 40 CFR Part 63 Subpart WWWW]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:

Effective Date: To be entered upon final issuance

- a. total OC emissions from all the coatings (resins and/or gel coat) employed, in tons [summation of d)(1)e. for all days of the calendar month, and divided by 2000 pounds per ton];
- b. updated rolling, 12-month summation of OC emission from all the coatings (resins and/or gel coats) employed, in tons [this shall include the total for the current month's OC emissions, plus the total for the preceding eleven calendar months];
- c. total PE/PM10 emissions for all coatings employed, in tons [summation of the data from d)(1)k. for all days of the calendar month divided by 2000 pounds per ton]; and
- d. rolling, 12-month summation of PE/PM10 emissions from all coatings employed, in tons [this shall include the total for the current month's PE/PM10 emissions, plus the total for the preceding eleven calendar months].

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and 3745-31-05(D)]

- (3) The permittee shall maintain annual records of the following information for this emissions unit:
 - a. total number of gallons of cleanup material employed [summation of d)(1)h. for all days the emissions unit was in operation];
 - b. total OC emissions from cleanup materials employed, in pounds [summation of d)(1)j. for all days of the emissions unit was in operation].

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) The permittee shall operate and maintain metering equipment to measure the amount of all resins and gel coats used in each emissions unit. The permittee shall calibrate the metering equipment to measure the amount, in weight or volume, of all resins and gel coats used in each emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the metering equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the metering equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the metering equipment, the permittee shall perform calibration and accuracy tests on the metering equipment on a monthly basis during the first six months of operation of the meters. The permittee calibration and accuracy tests for the metering equipment shall include two resins (the highest and lowest density resins) and two gel coats (the highest and lowest density gel coats). After completing six months of calibration and accuracy tests of the metering equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (5) The permittee shall operate and maintain measuring equipment to measure the amount of cleanup materials employed in this emissions unit. The permittee shall calibrate the measuring equipment to measure the amount, in weight or volume, of all cleanup materials employed in this emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the measuring equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the measuring equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the measuring equipment, the permittee shall perform calibration and accuracy tests on the measuring equipment on a monthly basis during the first six months of operation of the measuring equipment. The permittee calibration and accuracy tests for the measuring equipment shall include the cleanup material employed by the permittee. After completing six months of calibration and accuracy tests of the measuring equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (6) The permittee shall utilize one or more compliance options, as specified in 40 CFR 63.5810 to demonstrate compliance with the emission standards for open molding in Table 3 of this subpart, as described in the following sections:

63.5810(a)	individual resin or gel coat compliance demonstration
63.5810(b)	average individual organic HAP emissions limit compliance demonstration for all operations and application methods
63.5810(c)	weighted average emission limit compliance demonstration
63.5810(d)	organic HAP emission limit compliance demonstration for one resin type and application method

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR 63.5810]

- (7) The permittee is currently demonstrating compliance through the option specified in 63.5810(a). The permittee shall comply with the following data collection, emission calculation, and record keeping requirements, in addition to those listed in d)(8) below:
- a. Calculate your actual organic HAP emissions factor for each different process stream within this emissions unit. A process stream is defined as each individual combination of resin or gel coat, application technique, and control technique. Process streams within operations types are considered different from each other if any of the following four characteristics vary: the neat resin plus or neat gel coat plus organic HAP content, the gel coat type, the application technique, or the control technique. You must calculate organic HAP emissions factors for each different process stream by using the

appropriate equations in Table 1 of 40 CFR Part 63 Subpart WWWW for open molding and for centrifugal casting, or site-specific organic HAP emissions factors discussed in §63.5796. The emission factor calculation should include any and all emission reduction techniques used. If you are using vapor suppressants to reduce HAP emissions, you must determine the vapor suppressant effectiveness (VSE) by conducting testing according to the procedures specified in appendix A to subpart WWWW of 40 CFR part 63.

Should the permittee choose to demonstrate compliance with the emission limitations listed in b)(2)b. by one of the alternative compliance demonstrations specified in d)(6), the permittee shall collect and record the information specified in 40 CFR 63.5810(b),(c), or (d), as appropriate.

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR 63.5810]

- (8) The permittee shall comply with the applicable monitoring and record keeping requirements under 40 CFR Part 63, Subpart WWWW, including the following sections:

63.5895(c) - (d)	records of resin and gel coat use, organic HAP content, operation and application method(s)
63.5915(a)	copy of compliance notification(s) and report(s)
63.5915(c)	records of all calculations and data used to determine organic HAP emissions factors or average organic HAP contents for operations and application methods as specified under 63.5810
63.5915(d)	certified statement of compliance with work practice requirements
63.5920(a) – (d)	record keeping format and retention requirements

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (9) The permittee shall maintain documentation of the manufacturer's recommendations, instructions, or operating manuals for the dry particulate filter, along with documentation of any modifications deemed necessary by the permittee. These documents shall be maintained at the facility and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (10) The permittee shall conduct periodic inspections of the dry particulate filter to determine whether it is operating in accordance with the manufacturer's recommendations, instructions, or operating manuals with any modifications deemed necessary by the permittee or operator. These inspections shall be performed at a frequency that shall be based upon the recommendation of the manufacturer and the permittee shall maintain a copy of the manufacturer's recommended inspection frequency and it shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

Effective Date: To be entered upon final issuance

- (11) In addition to the recommended periodic inspections, not less than once each calendar year the permittee shall conduct a comprehensive inspection of the dry particulate filter while the emissions unit is shut down and perform any needed maintenance and repair to ensure that it is operated in accordance with the manufacturer's recommendations.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (12) The permittee shall document each inspection (periodic and annual) of the dry particulate filter system and shall maintain the following information:
- a. the date of the inspection;
 - b. a description of each/any problem identified and the date it was corrected;
 - c. a description of any maintenance and repairs performed; and
 - d. the name of person who performed the inspection.

These records shall be maintained at the facility for not less than five years from the date the inspection and any necessary maintenance or repairs were completed and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (13) The permittee shall maintain records that document any time periods when the dry particulate filter was not in service when the emissions unit(s) was/were in operation, as well as, a record of all operations during which the dry particulate filter was not operated according to the manufacturer's recommendations with any documented modifications made by the permittee. These records shall be maintained for a period of not less than five years and shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (14) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05196: d)(1) through d)(13). The monitoring and recordkeeping requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
- a. daily cleanup material usage restriction;
 - b. OC content limitation for the cleanup material;
 - c. daily OC emission limitation for the cleanup material;
 - d. hourly OC emission limitation for coatings;

- e. daily OC emission limitation for coatings;
- f. hourly PE/PM10 emission limitation;
- g. daily PE/PM10 emission limitation;
- h. rolling 12-month emission limitation for PE/PM10;
- i. rolling 12-month OC emission limitation; and
- j. any daily record showing that the dry particulate filter system was not in service or not operated according to manufacturer's recommendations (with any documented modifications made by the permittee) when the emissions unit(s) was/were in operation.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

- (2) The permittee shall submit annual reports to the Hamilton County Department of Environmental Services that specify the following:
- a. total amount, in gallons, of cleanup material employed for the calendar year; and
 - b. total OC emissions from the cleanup material employed, in tons, for the calendar year;

This report shall be submitted by January 31 of each year and cover the previous calendar year.

[Authority for term: OAC rules 3745-77-07(C)(1)].

- (3) The permittee shall notify the Hamilton County Department of Environmental Services in writing of each day during which any photochemically reactive cleanup material [as defined in OAC rule 3745-21-01(C)(5)] was employed in this emissions unit. The notification shall include a copy of such record and shall be sent to the Hamilton County Department of Environmental Services within 45 days after the exceedance occurs.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) Upon replacement and/or initial operation of any metering or measuring equipment as specified in d)(4) and d)(5) of this permit, the permittee shall provide the Hamilton County Department of Environmental Services the following information: the name of the manufacturer of the metering/measuring equipment, the make and model of the metering/measuring equipment, calibration data (e.g., volume of coating per pump stroke), a copy of the manufacturer's specifications and warranty for the accuracy of the metering/measuring equipment and the actual accuracy of the material measurements (by weight or by volume) recorded for the metering/measuring equipment.

[Authority for term: OAC rules 3745-77-07(C)(1)]



Effective Date: To be entered upon final issuance

- (5) The permittee shall submit calibration and accuracy test results for the metering equipment and measuring equipment specified in d)(4) and d)(5) of the terms and conditions of this permit. The calibration and accuracy tests results shall be submitted to the Hamilton County Department of Environmental Services by January 30 and July 30 of each calendar year, and shall cover the previous six-month period.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (6) The permittee shall submit semi-annual reports and such other notifications and reports to the Hamilton County Department of Environmental Services as are required in 40 CFR Part 63, Subpart WWWW, pursuant to the following sections:

63.5905(b)	15-day notification of change(s)
63.5910(a) - (b) and Table 14	semi-annual compliance reports
63.5910(c) - (i) and Table 14	content of semi-annual compliance reports

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (7) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05196: e)(1) through e)(6). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.

f) Testing Requirements

- (1) Compliance with the emission limitations and material usage restrictions specified in b) and c) shall be determined by the following methods:

a. Emission Limitations:

OC emissions shall not exceed 2 pounds per hour from coatings (resin and gel coat);

OC emissions shall not exceed 40 pounds per day from coatings (resin and gel coat); and

OC emissions shall not exceed 0.3 ton per year (TPY) from coatings (resins and gel coats) based on a rolling, 12-month summation of the coating emissions.

Applicable Compliance Method:

Compliance with the hourly OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly OC emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 – 4, 18 and 25.

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), OAC rule 3745-31-05(A)(3), 3745-31-05(D), and 3745-21-07(G)(2)].

b. Emission Limitations:

OC emissions shall not exceed 3.3 pounds per day from cleanup materials.

OC emissions shall not exceed 0.495 ton per year from cleanup materials.

Applicable Compliance Method:

Compliance with the daily OC emission limitation from cleanup materials shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation from cleanup material shall be determined by the record keeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)].

c. Emission Limitation:

The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.

Applicable Compliance Method:

Compliance with the OC content limitation shall be determined by the record keeping requirements specified in d)(1). Formulation data or US EPA Method 24 shall be used to determine the OC content of any cleanup material employed in this emissions unit.

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

d. Material Usage Restriction:

The maximum amount of all cleanup material employed in this emissions unit shall not exceed 0.5 gallon per day and 150 gallons per year.

Applicable Compliance Method:

Compliance with the daily cleanup material usage restriction shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual cleanup material usage restriction shall be determined by the recordkeeping requirements specified in d)(3).



[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

e. Emission Limitation:

See the organic HAP emission limitations noted in b)(2)b.

Applicable Compliance Method:

Compliance with the organic HAP emission limitation shall be based upon the information collected and recorded in d)(6) - d)(8) of this permit.

[Authority for term: OAC rules 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

f. Emission Limitations:

PE/PM-10 emissions shall not exceed 0.27 pound per hour;

PE/PM-10 emissions shall not exceed 1.38 pounds per day; and

PE/PM-10 emissions shall not exceed 0.01 ton per year, based on a rolling, 12-month summation.

Applicable Compliance Method:

Compliance with the hourly PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly PE/PM10 emission limitation through emission tests performed in accordance with 40 CFR, Part 60, Appendix A, Methods 1-5.

Compliance with the daily PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and OAC 3745-31-05(D)].

- (2) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05196: f)(1)a. through f)(1)f. The testing requirements contained in the above-referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.

g) Miscellaneous Requirements

- (1) None.



11. P038, Tooling Spray Chop

Operations, Property and/or Equipment Description:

Tooling Spray Chop

- a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (1) None.
- b) Applicable Emissions Limitations and/or Control Requirements
 - (1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05196)	<p>The Organic Compound (OC) emissions from resin application shall not exceed 2 pounds per hour and 40 lbs/day.</p> <p>OC emissions (acetone) shall not exceed 3.3 pounds per day from cleanup materials.</p> <p>OC emissions (acetone) shall not exceed 0.495 ton per year from cleanup materials.</p> <p>Particulate emissions (PE) and Particulate matter with a diameter of 10 microns or less (PM-10) shall not exceed 0.814 pound per hour.</p> <p>PE/PM10 emissions shall not exceed 4.07 pounds per day.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(D) and 3745-17-07(A)(1).</p> <p>See c)(1) - c)(4).</p>
b.	OAC rule 3745-31-05(D) Synthetic Minor Determination to avoid the Emission Offset Policy for	<p>See b)(2)a.</p> <p>PE/PM10 emissions shall not exceed 0.05 ton per year based on a rolling, 12-</p>



Effective Date: To be entered upon final issuance

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
	VOC.	month summation.
c.	OAC rule 3745-17-07(A)(1)	Visible particulate emissions from any stack shall not exceed 20% opacity, as a six minute average, except as specified by rule.
d.	OAC rule 3745-17-11(B)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
e.	OAC rule 3745-17-11(C)(3)	The Permit to Install for this emissions unit was issued July 9, 2002 (post January 1, 1990). Therefore, the emissions unit is exempt from the requirements of OAC rule 3745-17-11(C)(1) and (2). See b)(2)c.
f.	OAC rule 3745-21-07(G)(2)	The emission limitations specified by this rule are the same as or less stringent the emission limitation established pursuant to OAC rule 3745-31-05(A)(3). See b)(2)d.
g.	40 CFR Part 63, Subpart WWWW (40 CFR 63.5780-5935) [In accordance with 63.5805(b), this emissions unit is an open molding using mechanical resin application at an existing reinforced plastic composites production facility subject to the emission limitations and work practices specified in 40 CFR 63.5805(b)]	Table 3 to 40 CFR Part 63, Subpart WWWW – Organic Hazardous Air Pollutant (HAP) Emission Limits for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. See b)(2)b. and e. Table 4 to 40 CFR Part 63, Subpart WWWW – Applicable Work Practice Standards. See c)(5) and c)(6).
h.	40 CFR 63.1-15, Subpart A (40 CFR 63.5925)	Table 15 to 40 CFR Part 63, Subpart WWWW – Applicability of General Provisions (Subpart A) to Subpart WWWW shows which parts of the General Provisions in 40 CFR Part 63.1 – 15 apply.



(2) Additional Terms and Conditions

a. The annual OC emission limit, for the coatings, employed in this emissions unit shall not exceed 0.5 TPY, based on a rolling, 12-month summation. For purposes of clarification of non attainment new source review (NSR) permitting requirements and this Title V renewal permitting action, the permittee shall only employ non-VOC based cleanup materials. No cleanup materials with VOC as defined in OAC rule 3745-21-01 shall be employed. The emission of non-VOC based cleanup materials does not count towards the Synthetic Minor Determination to avoid the Emission Offset Policy for VOC established in PTI 14-05196.

b. The following organic HAP emission limitations shall not be exceeded based on a 12-month rolling average.

Operation Type	Organic HAP Emission Limit
Corrosion Resistant/Highs Strength (CR/HS)	113 lbs/ton
Non-CR/HS	88 lbs/ton
Tooling	254 lbs/ton
Low flame spread/low smoke products	497 lbs/ton
Shrinkage Controlled Resin	354 lbs/ton

c. On February 1, 2008, OAC rule 3745-17-11 was revised to include paragraph (C), pertaining to control requirements for particulate emissions from surface coating processes. These control requirements and the associated operational restrictions, monitoring, record keeping, and reporting requirements contained in this permit shall become federally enforceable on the date the U.S. EPA approves paragraph (C) of OAC rule 3745-17-11 as a revision to the Ohio State Implementation Plan.

d. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP); however, until the U.S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio.

e. This emissions unit is subject to the requirements of 40 CFR Part 63 Subpart WWWW - National Emissions Standards for Hazardous Air Pollutants for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. The permittee shall comply with the applicable emission limitations and operational restrictions specified in 40 CFR Part 63.5780 – 63.5930. The complete MACT requirements, including the MACT General Provisions may be accessed via the internet from the Electronic Code of Federal Regulations (e-CFR) website <http://ecfr.gpoaccess.gov> or by contacting the appropriate Ohio EPA District Office or local air agency.

c) Operational Restrictions

- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 0.5 gallon per day and 150 gallons per year.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (2) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 lbs of OC/gallon.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (3) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1), 3745-31-05(A)(3) and 3745-21-07(G)(2)]

- (4) The permittee shall operate the dry filtration system for the control of particulate emissions whenever this emissions unit is in operation and shall maintain the dry particulate filter in accordance with the manufacturer's recommendations, instructions, and/or operating manual(s), with any modifications deemed necessary by the permittee.

In the event the particulate filter system is not operating in accordance with the manufacturer's recommendations, instructions, or operating manual, with any modifications deemed necessary by the permittee, the control device shall be expeditiously repaired or otherwise returned to these documented operating conditions.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (5) The permittee shall employ only non-HAP-containing cleanup materials in each emissions unit, except that styrene may be used as a cleaner in closed systems, and organic HAP containing cleaners may be used to clean cured resin from application equipment. Application equipment includes any equipment that directly contacts resin.

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR Part 63, Subpart WWWW Table 4]

- (6) The permittee shall keep containers that store HAP-containing coating materials and cleanup materials closed or covered, except during the addition or removal of materials. Bulk HAP-containing materials storage tanks may be vented as necessary for safety.

[Authority for term: OAC rules 3745-77-07(A)(1) and 40 CFR Part 63, Subpart WWWW Table 4]

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall collect and record the following information each day this emissions unit is in operation:

- a. company identification for each coating material (resin and/or gel coat) and cleanup material applied;

Effective Date: To be entered upon final issuance

- b. number of pounds of each coating material (resin and/or gel coat) applied;
- c. the HAP content, recorded in percent by weight, of each coating material (resin and/or gel coat) employed in this emissions unit;
- d. calculated OC (assumed equal to the organic HAP) emission factor using the equations to calculate organic HAP emission factors from Table 1 of 40 CFR Part 63, Subpart WWWW, in pounds of OC per ton of coating material (resin and/or gel coat) applied;
- e. total daily OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per day $[d)(1)b./2000 \times d)(1)d.]$;
- f. number of hours the emissions unit was in operation;
- g. average hourly OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per hour $[d)(1)e. \text{ divided by } d)(1)f.]$.
- h. total number of gallons of cleanup material applied;
- i. OC content of the cleanup material employed, in pounds per gallon;
- j. daily OC emissions from the cleanup material employed, in pounds $[d)(1)h. \times d)(1)i.]$;
- k. total PE/PM10 emission rate for all coatings employed, in pounds per day $[\text{summation of } d)(1)b. \times (1 - \text{HAP content, percent by weight}) \times 0.25 \text{ (25\% overspray)} \times (1 - 0.985, \text{ the control efficiency of the dry filtration system})]**$;
- l. average hourly PE/PM10 emission rate for all coatings employed, in pounds/hour $[d)(1)k. \text{ divided by } d)(1)f.]$;
- m. a determination whether or not each cleanup material employed is a photochemically reactive material, as defined in OAC rule 3745-21-05(C)(5); and
- n. a determination whether or not each cleanup material employed is a non-HAP material, as identified in Section 112(b) of the Clean Air Act.

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit].

** The 25% overspray and 98.5% control efficiency were used to establish the PE/PM10 emission rates established in PTI 14-05196 and are based on conservative engineering assumptions.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D), 3745-21-07(G)(2), and 40 CFR Part 63 Subpart WWWW]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:

Effective Date: To be entered upon final issuance

- a. total OC emissions from all the coatings (resins and/or gel coat) employed, in tons [summation of d)(1)e. for all days of the calendar month, and divided by 2000 pounds per ton];
- b. updated rolling, 12-month summation of OC emission from all the coatings (resins and/or gel coats) employed, in tons [this shall include the total for the current month's OC emissions, plus the total for the preceding eleven calendar months];
- c. rolling, 12-month summation of OC emissions from all the coatings (resins and/or gel coats) employed, in tons;
- d. total PE/PM10 emissions for all coatings employed, in tons [summation of the data from d)(1)k. for all days of the calendar month divided by 2000 pounds per ton]; and
- e. rolling, 12-month summation of PE/PM10 emissions from all coatings employed, in tons [this shall include the total for the current month's PE/PM10 emissions, plus the total for the preceding eleven calendar months].

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and 3745-31-05(D)]

- (3) The permittee shall maintain annual records of the following information for this emissions unit:
 - a. total number of gallons of cleanup material employed [summation of d)(1)h. for all days the emissions unit was in operation]; and
 - b. total OC emissions from cleanup materials employed, in pounds [summation of d)(1)j. for all days of the emissions unit was in operation].

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) The permittee shall operate and maintain metering equipment to measure the amount of all resins and gel coats used in each emissions unit. The permittee shall calibrate the metering equipment to measure the amount, in weight or volume, of all resins and gel coats used in each emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the metering equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the metering equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the metering equipment, the permittee shall perform calibration and accuracy tests on the metering equipment on a monthly basis during the first six months of operation of the meters. The permittee calibration and accuracy tests for the metering equipment shall include two resins (the highest and lowest density resins) and two gel coats (the highest and lowest density gel coats). After completing six months of calibration and accuracy tests of the metering equipment and upon approval from the Hamilton County



Effective Date: To be entered upon final issuance

Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (5) The permittee shall operate and maintain measuring equipment to measure the amount of cleanup materials employed in this emissions unit. The permittee shall calibrate the measuring equipment to measure the amount, in weight or volume, of all cleanup materials employed in this emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the measuring equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the measuring equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the measuring equipment, the permittee shall perform calibration and accuracy tests on the measuring equipment on a monthly basis during the first six months of operation of the measuring equipment. The permittee calibration and accuracy tests for the measuring equipment shall include the cleanup material employed by the permittee. After completing six months of calibration and accuracy tests of the measuring equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (6) The permittee shall utilize one or more compliance options, as specified in 40 CFR 63.5810 to demonstrate compliance with the emission standards for open molding in Table 3 of this subpart, as described in the following sections:

63.5810(a)	individual resin or gel coat compliance demonstration
63.5810(b)	average individual organic HAP emissions limit compliance demonstration for all operations and application methods
63.5810(c)	weighted average emission limit compliance demonstration
63.5810(d)	organic HAP emission limit compliance demonstration for one resin type and application method

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR 63.5810]

- (7) The permittee is currently demonstrating compliance through the option specified in 63.5810(a). The permittee shall comply with the following data collection, emission calculation, and record keeping requirements, in addition to those listed in d)(8) below:
 - a. Calculate your actual organic HAP emissions factor for each different process stream within this emissions unit. A process stream is defined as each individual combination of resin or gel coat, application technique, and control

technique. Process streams within operations types are considered different from each other if any of the following four characteristics vary: the neat resin plus or neat gel coat plus organic HAP content, the gel coat type, the application technique, or the control technique. You must calculate organic HAP emissions factors for each different process stream by using the appropriate equations in Table 1 of 40 CFR Part 63 Subpart WWWW for open molding and for centrifugal casting, or site-specific organic HAP emissions factors discussed in §63.5796. The emission factor calculation should include any and all emission reduction techniques used. If you are using vapor suppressants to reduce HAP emissions, you must determine the vapor suppressant effectiveness (VSE) by conducting testing according to the procedures specified in appendix A to subpart WWWW of 40 CFR part 63.

Should the permittee choose to demonstrate compliance with the emission limitations listed in b)(2)b. by one of the alternative compliance demonstrations specified in d)(6), the permittee shall collect and record the information specified in 40 CFR 63.5810(b),(c), or (d), as appropriate.

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR 63.5810]

- (8) The permittee shall comply with the applicable monitoring and record keeping requirements under 40 CFR Part 63, Subpart WWWW, including the following sections:

63.5895(c) - (d)	records of resin and gel coat use, organic HAP content, operation and application method(s)
63.5915(a)	copy of compliance notification(s) and report(s)
63.5915(c)	records of all calculations and data used to determine organic HAP emissions factors or average organic HAP contents for operations and application methods as specified under 63.5810
63.5915(d)	certified statement of compliance with work practice requirements
63.5920(a) – (d)	record keeping format and retention requirements

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (9) The permittee shall maintain documentation of the manufacturer's recommendations, instructions, or operating manuals for the dry particulate filter, along with documentation of any modifications deemed necessary by the permittee. These documents shall be maintained at the facility and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (10) The permittee shall conduct periodic inspections of the dry particulate filter to determine whether it is operating in accordance with the manufacturer's recommendations, instructions, or operating manuals with any modifications deemed necessary by the

permittee or operator. These inspections shall be performed at a frequency that shall be based upon the recommendation of the manufacturer and the permittee shall maintain a copy of the manufacturer's recommended inspection frequency and it shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (11) In addition to the recommended periodic inspections, not less than once each calendar year the permittee shall conduct a comprehensive inspection of the dry particulate filter while the emissions unit is shut down and perform any needed maintenance and repair to ensure that it is operated in accordance with the manufacturer's recommendations.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (12) The permittee shall document each inspection (periodic and annual) of the dry particulate filter system and shall maintain the following information:
- a. the date of the inspection;
 - b. a description of each/any problem identified and the date it was corrected;
 - c. a description of any maintenance and repairs performed; and
 - d. the name of person who performed the inspection.

These records shall be maintained at the facility for not less than five years from the date the inspection and any necessary maintenance or repairs were completed and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (13) The permittee shall maintain records that document any time periods when the dry particulate filter was not in service when the emissions unit(s) was/were in operation, as well as, a record of all operations during which the dry particulate filter was not operated according to the manufacturer's recommendations with any documented modifications made by the permittee. These records shall be maintained for a period of not less than five years and shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (14) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05196: d)(1) through d)(13). The monitoring and recordkeeping requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
- a. daily cleanup material usage restriction;

Effective Date: To be entered upon final issuance

- b. OC content limitation for the cleanup material;
- c. daily OC emission limitation for the cleanup material;
- d. hourly OC emission limitation for coatings;
- e. daily OC emission limitation for coatings;
- f. hourly PE/PM10 emission limitation;
- g. daily PE/PM10 emission limitation;
- h. rolling 12-month emission limitation for PE/PM10;
- i. rolling 12-month OC emission limitation; and
- j. any daily record showing that the dry particulate filter system was not in service or not operated according to manufacturer's recommendations (with any documented modifications made by the permittee) when the emissions unit(s) was/were in operation.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

- (2) The permittee shall submit annual reports to the Hamilton County Department of Environmental Services that specify the following:
- a. total amount, in gallons, of cleanup material employed for the calendar year;
 - b. total OC emissions from the cleanup material employed, in tons, for the calendar year; and
 - c. rolling, 12-month summation of OC emissions from this emissions unit for each calendar month.

This report shall be submitted by January 31 of each year and cover the previous calendar year.

[Authority for term: OAC rules 3745-77-07(C)(1)].

- (3) The permittee shall notify the Hamilton County Department of Environmental Services in writing of each day during which any photochemically reactive cleanup material [as defined in OAC rule 3745-21-01(C)(5)] was employed in this emissions unit. The notification shall include a copy of such record and shall be sent to the Hamilton County Department of Environmental Services within 45 days after the exceedance occurs.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) Upon replacement and/or initial operation of any metering or measuring equipment as specified in d)(4) and d)(5) of this permit, the permittee shall provide the Hamilton County Department of Environmental Services the following information: the name of the manufacturer of the metering/measuring equipment, the make and model of the



Effective Date: To be entered upon final issuance

metering/measuring equipment, calibration data (e.g., volume of coating per pump stroke), a copy of the manufacturer's specifications and warranty for the accuracy of the metering/measuring equipment and the actual accuracy of the material measurements (by weight or by volume) recorded for the metering/measuring equipment.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (5) The permittee shall submit calibration and accuracy test results for the metering equipment and measuring equipment specified in d)(4) and d)(5) of the terms and conditions of this permit. The calibration and accuracy tests results shall be submitted to the Hamilton County Department of Environmental Services by January 30 and July 30 of each calendar year, and shall cover the previous six-month period.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (6) The permittee shall submit semi-annual reports and such other notifications and reports to the Hamilton County Department of Environmental Services as are required in 40 CFR Part 63, Subpart WWWW, pursuant to the following sections:

63.5905(b)	15-day notification of change(s)
63.5910(a) - (b) and Table 14	semi-annual compliance reports
63.5910(c) - (i) and Table 14	content of semi-annual compliance reports

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (7) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05196: e)(1) through e)(6). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.

f) Testing Requirements

- (1) Compliance with the emission limitations and material usage restrictions specified in b) and c) shall be determined by the following methods:

a. Emission Limitations:

OC emissions shall not exceed 2 pounds per hour from coatings (resin and gel coat);

OC emissions shall not exceed 40 pounds per day from coatings (resin and gel coat); and

OC emissions shall not exceed 0.5 ton per year (TPY) from coatings (resins and gel coats) based on a rolling, 12-month summation of the coating emissions.

Applicable Compliance Method:

Compliance with the hourly OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly OC emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 – 4, 18 and 25.

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), OAC rule 3745-31-05(A)(3), 3745-31-05(D), and 3745-21-07(G)(2)].

b. Emission Limitations:

OC emissions shall not exceed 3.3 pounds per day from cleanup materials

OC emissions shall not exceed 0.495 ton per year from cleanup materials

Applicable Compliance Method:

Compliance with the daily OC emission limitation from cleanup materials shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation from cleanup material shall be determined by the record keeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)].

c. Emission Limitation:

The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.

Applicable Compliance Method:

Compliance with the OC content limitation shall be determined by the record keeping requirements specified in d)(1). Formulation data or US EPA Method 24 shall be used to determine the OC content of any cleanup material employed in this emissions unit.

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

d. Material Usage Restriction:

The maximum amount of all cleanup material employed in this emissions unit shall not exceed 0.5 gallon per day and 150 gallons per year.



Effective Date: To be entered upon final issuance

Applicable Compliance Method:

Compliance with the daily cleanup material usage restriction shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual cleanup material usage restriction shall be determined by the recordkeeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

e. Emission Limitation:

See the organic HAP emission limitations noted in b)(2)b.

Applicable Compliance Method:

Compliance with the organic HAP emission limitation shall be based upon the information collected and recorded in d)(6) - d)(8) of this permit.

[Authority for term: OAC rules 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

f. Emission Limitations:

PE/PM-10 emissions shall not exceed 0.814 pound per hour;

PE/PM-10 emissions shall not exceed 4.07 pounds per day; and

PE/PM-10 emissions shall not exceed 0.05 ton per year, based on a rolling, 12-month summation.

Applicable Compliance Method:

Compliance with the hourly PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly PE/PM10 emission limitation through emission tests performed in accordance with 40 CFR, Part 60, Appendix A, Methods 1-5.

Compliance with the daily PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and OAC 3745-31-05(D)].

(2) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05196: f)(1)a. through f)(1)f. The testing requirements contained in the above-



Effective Date: To be entered upon final issuance

referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.

g) Miscellaneous Requirements

- (1) None.



12. P039, Tooling Layup

Operations, Property and/or Equipment Description:

Tooling Layup

- a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (1) None.
- b) Applicable Emissions Limitations and/or Control Requirements
 - (1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05196)	The Organic Compound (OC) emissions from resin application shall not exceed 2 pounds per hour and 40 lbs/day. OC emissions (acetone) shall not exceed 3.3 pounds per day from cleanup materials. OC emissions (acetone) shall not exceed 0.495 ton per year from cleanup materials. The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(D) See c)(1) - c)(3).
b.	OAC rule 3745-31-05(D) Synthetic Minor Determination to avoid the Emission Offset Policy for VOC.	See b)(2)a.
c.	OAC rule 3745-21-07(G)(2)	The emission limitations specified by this rule are the same as or less stringent than emission limitation established pursuant to OAC rule 3745-31-05(A)(3). See b)(2)c.



Effective Date: To be entered upon final issuance

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
d.	40 CFR Part 63, Subpart WWWW (40 CFR 63.5780-5935) [In accordance with 63.5805(b), this emissions unit is an open molding using manual resin application at an existing reinforced plastic composites production facility subject to the emission limitations and work practices specified in 40 CFR 63.5805(b)]	Table 3 to 40 CFR Part 63, Subpart WWWW – Organic Hazardous Air Pollutant (HAP) Emission Limits for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. See b)(2)b. and d. Table 4 to 40 CFR Part 63, Subpart WWWW – Applicable Work Practice Standards. See c)(4) and c)(5).
e.	40 CFR 63.1-15, Subpart A (40 CFR 63.5925)	Table 15 to 40 CFR Part 63, Subpart WWWW – Applicability of General Provisions (Subpart A) to Subpart WWWW shows which parts of the General Provisions in 40 CFR Part 63.1 – 15 apply.

(2) Additional Terms and Conditions

- a. The annual OC emissions, for the coatings employed in this emissions unit shall not exceed 0.2 TPY, based on a rolling, 12-month summation. For purposes of clarification of non attainment new source review (NSR) permitting requirements and this Title V renewal permitting action, the permittee shall only employ non-VOC based cleanup materials. No cleanup materials with VOC as defined in OAC rule 3745-21-01 shall be employed. The emission of non-VOC based cleanup materials does not count towards the Synthetic Minor Determination to avoid the Emission Offset Policy for VOC established in PTI 14-05196.
- b. The following organic HAP emission limitations shall not be exceeded based on a 12-month rolling average.

Operation Type	Organic HAP Emission Limit
Corrosion Resistant/Highs Strength (CR/HS)	123 lbs/ton
Non-CR/HS	87 lbs/ton
Tooling	157 lbs/ton
Low flame spread/low smoke products	238 lbs/ton
Shrinkage Controlled Resin	180 lbs/ton

- c. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the



U.S. EPA as a revision to Ohio's State Implementation Plan (SIP); however, until the U.S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio.

- d. This emissions unit is subject to the requirements of 40 CFR Part 63 Subpart WWWW - National Emissions Standards for Hazardous Air Pollutants for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. The permittee shall comply with the applicable emission limitations and operational restrictions specified in 40 CFR Part 63.5780 – 63.5930. The complete MACT requirements, including the MACT General Provisions may be accessed via the internet from the Electronic Code of Federal Regulations (e-CFR) website <http://ecfr.gpoaccess.gov> or by contacting the appropriate Ohio EPA District Office or local air agency.

c) Operational Restrictions

- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 0.5 gallon per day and 150.0 gallons per year.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (2) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 lbs of OC/gallon.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (3) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1), 3745-31-05(A)(3) and 3745-21-07(G)(2)]

- (4) The permittee shall employ only non-HAP-containing cleanup materials in each emissions unit, except that styrene may be used as a cleaner in closed systems, and organic HAP containing cleaners may be used to clean cured resin from application equipment. Application equipment includes any equipment that directly contacts resin.

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR Part 63, Subpart WWWW Table 4]

- (5) The permittee shall keep containers that store HAP-containing coating materials and cleanup materials closed or covered, except during the addition or removal of materials. Bulk HAP-containing materials storage tanks may be vented as necessary for safety.

[Authority for term: OAC rules 3745-77-07(A)(1) and 40 CFR Part 63, Subpart WWWW Table 4]

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall collect and record the following information each day this emissions unit is in operation:

Effective Date: To be entered upon final issuance

- a. company identification for each coating material (resin and/or gel coat) and cleanup material applied;
- b. number of pounds of each coating material (resin and/or gel coat) applied;
- c. the HAP content, recorded in percent by weight, of each coating material (resin and/or gel coat) employed in this emissions unit;
- d. calculated OC (assumed equal to the organic HAP) emission factor using the equations to calculate organic HAP emission factors from Table 1 of 40 CFR Part 63, Subpart WWWW, in pounds of OC per ton of coating material (resin and/or gel coat) applied;
- e. total daily OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per day $[d)(1)b./2000 \times d)(1)d]$;
- f. number of hours the emissions unit was in operation;
- g. average hourly OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per hour $[d)(1)e. \text{ divided by } d)(1)f.]$;
- h. total number of gallons of cleanup material applied;
- i. OC content of the cleanup material employed, in pounds per gallon;
- j. daily OC emissions from the cleanup material employed, in pounds $[d)(1)h. \times d)(1)i.]$;
- k. a determination whether or not each cleanup material employed is a photochemically reactive material, as defined in OAC rule 3745-21-05(C)(5); and
- l. a determination whether or not each cleanup material employed is a non-HAP material, as identified in Section 112(b) of the Clean Air Act.

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit].

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D), 3745-21-07(G)(2), and 40 CFR Part 63 Subpart WWWW]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:
 - a. total OC emissions from all the coatings (resins and/or gel coat) employed, in tons $[\text{summation of } d)(1)e. \text{ for all days of the calendar month, and divided by } 2000 \text{ pounds per ton}]$; and
 - b. updated rolling, 12-month summation of OC emission from all the coatings (resins and/or gel coats) employed, in tons $[\text{this shall include the total for the current month's OC emissions, plus the total for the preceding eleven calendar months}]$.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and 3745-31-05(D)]

- (3) The permittee shall maintain annual records of the following information for this emissions unit:
- a. total number of gallons of cleanup material employed [summation of d)(1)h. for all days the emissions unit was in operation]; and
 - b. total OC emissions from cleanup materials employed, in pounds [summation of d)(1)j. for all days of the emissions unit was in operation].

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) The permittee shall operate and maintain metering equipment to measure the amount of all resins and gel coats used in each emissions unit. The permittee shall calibrate the metering equipment to measure the amount, in weight or volume, of all resins and gel coats used in each emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the metering equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the metering equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the metering equipment, the permittee shall perform calibration and accuracy tests on the metering equipment on a monthly basis during the first six months of operation of the meters. The permittee calibration and accuracy tests for the metering equipment shall include two resins (the highest and lowest density resins) and two gel coats (the highest and lowest density gel coats). After completing six months of calibration and accuracy tests of the metering equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (5) The permittee shall operate and maintain measuring equipment to measure the amount of cleanup materials employed in this emissions unit. The permittee shall calibrate the measuring equipment to measure the amount, in weight or volume, of all cleanup materials employed in this emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the measuring equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the measuring equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the measuring equipment, the permittee shall perform calibration and accuracy tests on the measuring equipment on a monthly basis during the first six months of operation of the measuring equipment. The permittee calibration and accuracy tests for the measuring equipment shall include the cleanup material employed by the permittee. After completing six months of calibration and accuracy tests of the measuring equipment and

upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (6) The permittee shall utilize one or more compliance options, as specified in 40 CFR 63.5810 to demonstrate compliance with the emission standards for open molding in Table 3 of this subpart, as described in the following sections:

63.5810(a)	individual resin or gel coat compliance demonstration
63.5810(b)	average individual organic HAP emissions limit compliance demonstration for all operations and application methods
63.5810(c)	weighted average emission limit compliance demonstration
63.5810(d)	organic HAP emission limit compliance demonstration for one resin type and application method

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR 63.5810]

- (7) The permittee is currently demonstrating compliance through the option specified in 63.5810(a). The permittee shall comply with the following data collection, emission calculation, and record keeping requirements, in addition to those listed in d)(8) below:

- a. Calculate your actual organic HAP emissions factor for each different process stream within this emissions unit. A process stream is defined as each individual combination of resin or gel coat, application technique, and control technique. Process streams within operations types are considered different from each other if any of the following four characteristics vary: the neat resin plus or neat gel coat plus organic HAP content, the gel coat type, the application technique, or the control technique. You must calculate organic HAP emissions factors for each different process stream by using the appropriate equations in Table 1 of 40 CFR Part 63 Subpart WWWW for open molding and for centrifugal casting, or site-specific organic HAP emissions factors discussed in §63.5796. The emission factor calculation should include any and all emission reduction techniques used. If you are using vapor suppressants to reduce HAP emissions, you must determine the vapor suppressant effectiveness (VSE) by conducting testing according to the procedures specified in appendix A to subpart WWWW of 40 CFR part 63.

Should the permittee choose to demonstrate compliance with the emission limitations listed in b)(2)b. by one of the alternative compliance demonstrations specified in d)(6), the permittee shall collect and record the information specified in 40 CFR 63.5810(b),(c), or (d), as appropriate.

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR 63.5810]



Effective Date: To be entered upon final issuance

- (8) The permittee shall comply with the applicable monitoring and record keeping requirements under 40 CFR Part 63, Subpart WWWW, including the following sections:

63.5895(c) - (d)	records of resin and gel coat use, organic HAP content, operation and application method(s)
63.5915(a)	copy of compliance notification(s) and report(s)
63.5915(c)	records of all calculations and data used to determine organic HAP emissions factors or average organic HAP contents for operations and application methods as specified under 63.5810
63.5915(d)	certified statement of compliance with work practice requirements
63.5920(a) – (d)	record keeping format and retention requirements

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (9) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05196: d)(1) through d)(8). The monitoring and recordkeeping requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
 - a. daily cleanup material usage restriction;
 - b. OC content limitation for the cleanup material;
 - c. daily OC emission limitation for the cleanup material;
 - d. hourly OC emission limitation for coatings;
 - e. daily OC emission limitation for coatings; and
 - f. any daily record showing that the dry particulate filter system was not in service or not operated according to manufacturer’s recommendations (with any documented modifications made by the permittee) when the emissions unit(s) was/were in operation.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

- (2) The permittee shall submit annual reports to the Hamilton County Department of Environmental Services that specify the following:



Effective Date: To be entered upon final issuance

- a. total amount, in gallons, of cleanup material employed for the calendar year;
- b. total OC emissions from the cleanup material employed, in tons, for the calendar year; and
- c. rolling, 12-month summation of OC emissions from this emissions unit, for each calendar month.

This report shall be submitted by January 31 of each year and cover the previous calendar year.

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)].

- (3) The permittee shall notify the Hamilton County Department of Environmental Services in writing of each day during which any photochemically reactive cleanup material [as defined in OAC rule 3745-21-01(C)(5)] was employed in this emissions unit. The notification shall include a copy of such record and shall be sent to the Hamilton County Department of Environmental Services within 45 days after the exceedance occurs.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) Upon replacement and/or initial operation of any metering or measuring equipment as specified in d)(4) and d)(5) of this permit, the permittee shall provide the Hamilton County Department of Environmental Services the following information: the name of the manufacturer of the metering/measuring equipment, the make and model of the metering/measuring equipment, calibration data (e.g., volume of coating per pump stroke), a copy of the manufacturer's specifications and warranty for the accuracy of the metering/measuring equipment and the actual accuracy of the material measurements (by weight or by volume) recorded for the metering/measuring equipment.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (5) The permittee shall submit calibration and accuracy test results for the metering equipment and measuring equipment specified in d)(4) and d)(5) of the terms and conditions of this permit. The calibration and accuracy tests results shall be submitted to the Hamilton County Department of Environmental Services by January 30 and July 30 of each calendar year, and shall cover the previous six-month period.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (6) The permittee shall submit semi-annual reports and such other notifications and reports to the Hamilton County Department of Environmental Services as are required in 40 CFR Part 63, Subpart WWWW, pursuant to the following sections:

63.5905(b)	15-day notification of change(s)
63.5910(a) - (b) and Table 14	semi-annual compliance reports
63.5910(c) - (i) and Table 14	content of semi-annual compliance reports

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (7) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05196: e)(1) through e)(6). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.
- f) Testing Requirements
- (1) Compliance with the emission limitations and material usage restrictions specified in b) and c) shall be determined by the following methods:
- a. Emission Limitations:
- OC emissions shall not exceed 2 pounds per hour from coatings (resin and gel coat);
- OC emissions shall not exceed 40 pounds per day from coatings (resin and gel coat); and
- OC emissions shall not exceed 0.2 ton per year (TPY) from coatings (resins and gel coats) based on a rolling, 12-month summation of the coating emissions.
- Applicable Compliance Method:
- Compliance with the hourly OC emission limitation shall be determined by the record keeping requirements specified in d)(1).
- If required, the permittee shall demonstrate compliance with the hourly OC emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 – 4, 18 and 25.
- Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).
- Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).
- [Authority for term: OAC rules 3745-77-07(C)(1), OAC rule 3745-31-05(A)(3), 3745-31-05(D), and 3745-21-07(G)(2)].
- b. Emission Limitations:
- OC emissions shall not exceed 3.3 pounds per day from cleanup materials
- OC emissions shall not exceed 0.495 ton per year from cleanup materials
- Applicable Compliance Method:
- Compliance with the daily OC emission limitation from cleanup materials shall be determined by the record keeping requirements specified in d)(1).



Compliance with the annual OC emission limitation from cleanup material shall be determined by the record keeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)].

c. Emission Limitation:

The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.

Applicable Compliance Method:

Compliance with the OC content limitation shall be determined by the record keeping requirements specified in d)(1). Formulation data or US EPA Method 24 shall be used to determine the OC content of any cleanup material employed in this emissions unit.

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

d. Material Usage Restriction:

The maximum amount of all cleanup material employed in this emissions unit shall not exceed 0.5 gallon per day and 150 gallons per year.

Applicable Compliance Method:

Compliance with the daily cleanup material usage restriction shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual cleanup material usage restriction shall be determined by the recordkeeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

e. Emission Limitation:

See the organic HAP emission limitations noted in b)(2)b.

Applicable Compliance Method:

Compliance with the organic HAP emission limitation shall be based upon the information collected and recorded in d)(6) - d)(8) of this permit.

[Authority for term: OAC rules 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (2) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05196: f)(1)a. through f)(1)e. The testing requirements contained in the above-referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.

Effective Date: To be entered upon final issuance

- g) Miscellaneous Requirements
 - (1) None.



13. Emissions Unit Group - Gel Coat: P026, P029,

EU ID	Operations, Property and/or Equipment Description
P026	Service Gel Coat 3 Building B
P029	Service Gel Coat 4 Building B

- a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (1) None.
- b) Applicable Emissions Limitations and/or Control Requirements
 - (1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05338)	<p>The Organic Compound (OC) emissions from resin application shall not exceed 8 pounds per hour and 40 lbs/day.</p> <p>OC emissions (acetone) shall not exceed 19.8 pounds per day from cleanup materials.</p> <p>OC emissions (acetone) shall not exceed 2.97 tons per year from cleanup materials.</p> <p>Particulate emissions (PE) and Particulate matter with a diameter of 10 microns or less (PM-10) shall not exceed 0.28 pound per hour.</p> <p>PE/PM10 emissions shall not exceed 1.38 pounds per day.</p> <p>PE/PM10 emissions shall not exceed 0.24 ton per year based on a rolling, 12-month summation.</p> <p>The emission of organic HAP from Clear Production gel coat shall not exceed 504 lbs per ton.</p>

Draft Title V Permit

Core Composites Cincinnati, LLC

Permit Number: P0104748**Facility ID:** 1413020248**Effective Date:** To be entered upon final issuance

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		<p>The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(D), and 3745-17-07(A)(1).</p> <p>See c)(1) - c)(4).</p>
b.	<p>OAC rule 3745-31-05(D)</p> <p>Synthetic Minor Determination to avoid the Emission Offset Policy for VOC.</p>	See b)(2)a.
c.	OAC rule 3745-17-07(A)(1)	Visible particulate emissions from any stack shall not exceed 20% opacity, as a six minute average, except as specified by rule.
d.	OAC rule 3745-17-11(B)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
e.	OAC rule 3745-17-11(C)(3)	<p>The Permit to Install for this emissions unit was issued July 9, 2002 (post January 1, 1990). Therefore, the emissions unit is exempt from the requirements of OAC rule 3745-17-11(C)(1) and (2).</p> <p>See b)(2)c.</p>
f.	OAC rule 3745-21-07(G)(2)	<p>The emission limitations specified by this rule are the same as the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).</p> <p>See b)(2)d.</p>
g.	<p>40 CFR Part 63, Subpart WWWW (40 CFR 63.5780-5935)</p> <p>[In accordance with 63.5805(b), this emissions unit is an open molding gel coating application at an existing reinforced plastic composites production facility subject to the emission limitations and work practices specified in 40 CFR 63.5805(b)]</p>	<p>Table 3 to 40 CFR Part 63, Subpart WWWW – Organic Hazardous Air Pollutant (HAP) Emission Limits for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations.</p> <p>See b)(2)b. and e.</p> <p>Table 4 to 40 CFR Part 63, Subpart WWWW – Applicable Work Practice Standards.</p> <p>See c)(5) and c)(6).</p>

Effective Date: To be entered upon final issuance

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
h.	40 CFR 63.1-15, Subpart A (40 CFR 63.5925)	Table 15 to 40 CFR Part 63, Subpart WWWW – Applicability of General Provisions (Subpart A) to Subpart WWWW shows which parts of the General Provisions in 40 CFR Part 63.1 – 15 apply.

(2) Additional Terms and Conditions

- a. The annual OC emission limit, for the coatings, employed in emissions units P026, P029, P040, and P041, combined shall not exceed 28.0 TPY, based on a rolling, 12-month summation. For purposes of clarification of non attainment new source review (NSR) permitting requirements and this Title V renewal permitting action, the permittee shall only employ non-VOC based cleanup materials. No cleanup materials with VOC as defined in OAC rule 3745-21-01 shall be employed. The emission of non-VOC based cleanup materials does not count towards the Synthetic Minor Determination to avoid the Emission Offset Policy for VOC established in PTI 14-05338.
- b. The following organic HAP emission limitations shall not be exceeded based on a 12-month rolling average.

Gel Coat Type	Organic HAP Emission Limit
Tooling gel coating	440 lbs/ton
White/off white pigmented gel coating	267 lbs/ton
All other pigmented gel coating	377 lbs/ton
CR/HS or high performance gel coating	605 lbs/ton
Fire retardant gel coat	854 lbs/ton
Clear Production gel coat	A more stringent emission limitation was established under OAC 3745-31-05(A)(3). See b)(1)a. above.

- c. On February 1, 2008, OAC rule 3745-17-11 was revised to include paragraph (C), pertaining to control requirements for particulate emissions from surface coating processes. These control requirements and the associated operational restrictions, monitoring, record keeping, and reporting requirements contained in this permit shall become federally enforceable on the date the U.S. EPA approves paragraph (C) of OAC rule 3745-17-11 as a revision to the Ohio State Implementation Plan.
- d. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the U.S. EPA as a revision to Ohio’s State Implementation Plan (SIP); however,

Effective Date: To be entered upon final issuance

until the U.S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio.

- e. This emissions unit is subject to the requirements of 40 CFR Part 63 Subpart WWWW - National Emissions Standards for Hazardous Air Pollutants for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. The permittee shall comply with the applicable emission limitations and operational restrictions specified in 40 CFR Part 63.5780 – 63.5930. The complete MACT requirements, including the MACT General Provisions may be accessed via the internet from the Electronic Code of Federal Regulations (e-CFR) website <http://ecfr.gpoaccess.gov> or by contacting the appropriate Ohio EPA District Office or local air agency.

c) Operational Restrictions

- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3 gallons per day and 900 gallons per year.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (2) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 lbs of OC/gallon.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (3) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1), 3745-31-05(A)(3) and 3745-21-07(G)(2)]

- (4) The permittee shall operate the dry filtration system for the control of particulate emissions whenever this emissions unit is in operation and shall maintain the dry particulate filter in accordance with the manufacturer's recommendations, instructions, and/or operating manual(s), with any modifications deemed necessary by the permittee.

In the event the particulate filter system is not operating in accordance with the manufacturer's recommendations, instructions, or operating manual, with any modifications deemed necessary by the permittee, the control device shall be expeditiously repaired or otherwise returned to these documented operating conditions.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (5) The permittee shall employ only non-HAP-containing cleanup materials in each emissions unit, except that styrene may be used as a cleaner in closed systems, and organic HAP containing cleaners may be used to clean cured resin from application equipment. Application equipment includes any equipment that directly contacts resin.

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR Part 63, Subpart WWWW Table 4]

Effective Date: To be entered upon final issuance

- (6) The permittee shall keep containers that store HAP-containing coating materials and cleanup materials closed or covered, except during the addition or removal of materials. Bulk HAP-containing materials storage tanks may be vented as necessary for safety.

[Authority for term: OAC rules 3745-77-07(A)(1) and 40 CFR Part 63, Subpart WWWW Table 4]

d) **Monitoring and/or Recordkeeping Requirements**

- (1) The permittee shall collect and record the following information each day this emissions unit is in operation:
- a. company identification for each coating material (resin and/or gel coat) and cleanup material applied;
 - b. number of pounds of each coating material (resin and/or gel coat) applied;
 - c. the HAP content, recorded in percent by weight, of each coating material (resin and/or gel coat) employed in this emissions unit;
 - d. calculated OC (assumed equal to the organic HAP) emission factor using the equations to calculate organic HAP emission factors from Table 1 of 40 CFR Part 63, Subpart WWWW, in pounds of OC per ton of coating material (resin and/or gel coat) applied;
 - e. total daily OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per day $[d)(1)b./2000 \times d)(1)d.]$;
 - f. number of hours the emissions unit was in operation;
 - g. average hourly OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per hour $[d)(1)e. \text{ divided by } d)(1)f.]$.
 - h. total number of gallons of cleanup material applied;
 - i. OC content of the cleanup material employed, in pounds per gallon;
 - j. daily OC emissions from the cleanup material employed, in pounds $[d)(1)h. \times d)(1)i.]$;
 - k. total PE/PM10 emission rate for all coatings employed, in pounds per day $[\text{summation of } d)(1)b. \times (1 - \text{HAP content, percent by weight}) \times 0.25 \text{ (25\% overspray)} \times (1 - 0.985, \text{ the control efficiency of the dry filtration system})]**$;
 - l. average hourly PE/PM10 emission rate for all coatings employed, in pounds/hour $[d)(1)k \text{ divided by } d)(1)f.]$;
 - m. a determination whether or not each cleanup material employed is a photochemically reactive material, as defined in OAC rule 3745-21-05(C)(5); and

- n. a determination whether or not each cleanup material employed is a non-HAP material, as identified in Section 112(b) of the Clean Air Act.

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit].

** The 25% overspray and 98.5% control efficiency were used to establish the PE/PM10 emission rates established in PTI 14-05338 and are based on conservative engineering assumptions.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D), 3745-21-07(G)(2), and 40 CFR Part 63 Subpart WWWW]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:

- a. total OC emissions from all the coatings (resins and/or gel coat) employed, in tons [summation of d)(1)e. for all days of the calendar month, and divided by 2000 pounds per ton];
- b. updated rolling, 12-month summation of OC emission from all the coatings (resins and/or gel coats) employed, in tons [this shall include the total for the current month's OC emissions, plus the total for the preceding eleven calendar months];
- c. rolling, 12-month summation of OC emissions from all the coatings (resins and/or gel coats) employed, in tons, for emissions units P026, P029, P040, and P041;
- d. total PE/PM10 emissions for all coatings employed, in tons [summation of the data from d)(1)k. for all days of the calendar month divided by 2000 pounds per ton]; and
- e. rolling, 12-month summation of PE/PM10 emissions from all coatings employed, in tons [this shall include the total for the current month's PE/PM10 emissions, plus the total for the preceding eleven calendar months].

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and 3745-31-05(D)]

- (3) The permittee shall maintain annual records of the following information for this emissions unit:

- a. total number of gallons of cleanup material employed [summation of d)(1)h. for all days the emissions unit was in operation]; and
- b. total OC emissions from cleanup materials employed, in pounds [summation of d)(1)j. for all days of the emissions unit was in operation].

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) The permittee shall operate and maintain metering equipment to measure the amount of all resins and gel coats used in each emissions unit. The permittee shall calibrate the

Effective Date: To be entered upon final issuance

metering equipment to measure the amount, in weight or volume, of all resins and gel coats used in each emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the metering equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the metering equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the metering equipment, the permittee shall perform calibration and accuracy tests on the metering equipment on a monthly basis during the first six months of operation of the meters. The permittee calibration and accuracy tests for the metering equipment shall include two resins (the highest and lowest density resins) and two gel coats (the highest and lowest density gel coats). After completing six months of calibration and accuracy tests of the metering equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (5) The permittee shall operate and maintain measuring equipment to measure the amount of cleanup materials employed in this emissions unit. The permittee shall calibrate the measuring equipment to measure the amount, in weight or volume, of all cleanup materials employed in this emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the measuring equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the measuring equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the measuring equipment, the permittee shall perform calibration and accuracy tests on the measuring equipment on a monthly basis during the first six months of operation of the measuring equipment. The permittee calibration and accuracy tests for the measuring equipment shall include the cleanup material employed by the permittee. After completing six months of calibration and accuracy tests of the measuring equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (6) The permittee shall utilize one or more compliance options, as specified in 40 CFR 63.5810 to demonstrate compliance with the emission standards for open molding in Table 3 of this subpart, as described in the following sections:

63.5810(a)	individual resin or gel coat compliance demonstration
63.5810(b)	average individual organic HAP emissions limit compliance demonstration for all operations and application methods

Effective Date: To be entered upon final issuance

63.5810(c)	weighted average emission limit compliance demonstration
63.5810(d)	organic HAP emission limit compliance demonstration for one resin type and application method

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR 63.5810]

(7) The permittee is currently demonstrating compliance through the option specified in 63.5810(a). The permittee shall comply with the following data collection, emission calculation, and record keeping requirements, in addition to those listed in d)(8) below:

- a. Calculate your actual organic HAP emissions factor for each different process stream within this emissions unit. A process stream is defined as each individual combination of resin or gel coat, application technique, and control technique. Process streams within operations types are considered different from each other if any of the following four characteristics vary: the neat resin plus or neat gel coat plus organic HAP content, the gel coat type, the application technique, or the control technique. You must calculate organic HAP emissions factors for each different process stream by using the appropriate equations in Table 1 of 40 CFR Part 63 Subpart WWWW for open molding and for centrifugal casting, or site-specific organic HAP emissions factors discussed in §63.5796. The emission factor calculation should include any and all emission reduction techniques used. If you are using vapor suppressants to reduce HAP emissions, you must determine the vapor suppressant effectiveness (VSE) by conducting testing according to the procedures specified in appendix A to subpart WWWW of 40 CFR part 63.

Should the permittee choose to demonstrate compliance with the emission limitations listed in b)(2)b. by one of the alternative compliance demonstrations specified in d)(6), the permittee shall collect and record the information specified in 40 CFR 63.5810(b),(c), or (d), as appropriate.

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR 63.5810]

(8) The permittee shall comply with the applicable monitoring and record keeping requirements under 40 CFR Part 63, Subpart WWWW, including the following sections:

63.5895(c) - (d)	records of resin and gel coat use, organic HAP content, operation and application method(s)
63.5915(a)	copy of compliance notification(s) and report(s)
63.5915(c)	records of all calculations and data used to determine organic HAP emissions factors or average organic HAP contents for operations and application methods as specified under 63.5810
63.5915(d)	certified statement of compliance with work practice requirements

63.5920(a) – (d)	record keeping format and retention requirements
------------------	--

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (9) The permittee shall maintain documentation of the manufacturer's recommendations, instructions, or operating manuals for the dry particulate filter, along with documentation of any modifications deemed necessary by the permittee. These documents shall be maintained at the facility and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (10) The permittee shall conduct periodic inspections of the dry particulate filter to determine whether it is operating in accordance with the manufacturer's recommendations, instructions, or operating manuals with any modifications deemed necessary by the permittee or operator. These inspections shall be performed at a frequency that shall be based upon the recommendation of the manufacturer and the permittee shall maintain a copy of the manufacturer's recommended inspection frequency and it shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (11) In addition to the recommended periodic inspections, not less than once each calendar year the permittee shall conduct a comprehensive inspection of the dry particulate filter while the emissions unit is shut down and perform any needed maintenance and repair to ensure that it is operated in accordance with the manufacturer's recommendations.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (12) The permittee shall document each inspection (periodic and annual) of the dry particulate filter system and shall maintain the following information:
 - a. the date of the inspection;
 - b. a description of each/any problem identified and the date it was corrected;
 - c. a description of any maintenance and repairs performed; and
 - d. the name of person who performed the inspection.

These records shall be maintained at the facility for not less than five years from the date the inspection and any necessary maintenance or repairs were completed and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (13) The permittee shall maintain records that document any time periods when the dry particulate filter was not in service when the emissions unit(s) was/were in operation, as well as, a record of all operations during which the dry particulate filter was not operated according to the manufacturer's recommendations with any documented modifications made by the permittee. These records shall be maintained for a period of not less than five years and shall be made available to the Ohio EPA upon request.

Effective Date: To be entered upon final issuance

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (14) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05338: d)(1) through d)(13). The monitoring and recordkeeping requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
- a. daily cleanup material usage restriction;
 - b. OC content limitation for the cleanup material;
 - c. daily OC emission limitation for the cleanup material;
 - d. hourly OC emission limitation for coatings;
 - e. daily OC emission limitation for coatings;
 - f. hourly PE/PM10 emission limitation;
 - g. daily PE/PM10 emission limitation;
 - h. rolling 12-month emission limitation for PE/PM10;
 - i. rolling 12-month combined OC emission limitation for P026, P029, P040, and P041; and
 - j. any daily record showing that the dry particulate filter system was not in service or not operated according to manufacturer's recommendations (with any documented modifications made by the permittee) when the emissions unit(s) was/were in operation.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

- (2) The permittee shall submit annual reports to the Hamilton County Department of Environmental Services that specify the following:
- a. total amount, in gallons, of cleanup material employed for the calendar year;
 - b. total OC emissions from the cleanup material employed, in tons, for the calendar year; and
 - c. rolling, 12-month summation of OC emissions from emissions units P026, P029, P040, and P041, combined, for each calendar month.

Effective Date: To be entered upon final issuance

This report shall be submitted by January 31 of each year and cover the previous calendar year.

[Authority for term: OAC rules 3745-77-07(C)(1)].

- (3) The permittee shall notify the Hamilton County Department of Environmental Services in writing of each day during which any photochemically reactive cleanup material [as defined in OAC rule 3745-21-01(C)(5)] was employed in this emissions unit. The notification shall include a copy of such record and shall be sent to the Hamilton County Department of Environmental Services within 45 days after the exceedance occurs.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) Upon replacement and/or initial operation of any metering or measuring equipment as specified in d)(4) and d)(5) of this permit, the permittee shall provide the Hamilton County Department of Environmental Services the following information: the name of the manufacturer of the metering/measuring equipment, the make and model of the metering/measuring equipment, calibration data (e.g., volume of coating per pump stroke), a copy of the manufacturer's specifications and warranty for the accuracy of the metering/measuring equipment and the actual accuracy of the material measurements (by weight or by volume) recorded for the metering/measuring equipment.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (5) The permittee shall submit calibration and accuracy test results for the metering equipment and measuring equipment specified in d)(4) and d)(5) of the terms and conditions of this permit. The calibration and accuracy tests results shall be submitted to the Hamilton County Department of Environmental Services by January 30 and July 30 of each calendar year, and shall cover the previous six-month period.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (6) The permittee shall submit semi-annual reports and such other notifications and reports to the Hamilton County Department of Environmental Services as are required in 40 CFR Part 63, Subpart WWWW, pursuant to the following sections:

63.5905(b)	15-day notification of change(s)
63.5910(a) - (b) and Table 14	semi-annual compliance reports
63.5910(c) - (i) and Table 14	content of semi-annual compliance reports

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (7) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05338: e)(1) through e)(6). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.

f) Testing Requirements

(1) Compliance with the emission limitations and material usage restrictions specified in b) and c) shall be determined by the following methods:

a. Emission Limitations:

OC emissions shall not exceed 8 pounds per hour from coatings (resin and gel coat);

OC emissions shall not exceed 40 pounds per day from coatings (resin and gel coat); and

OC emissions shall not exceed 28.0 tons per year (TPY) from coatings (resins and gel coats) for emissions units P026, P029, P040, and P041, combined, based on a rolling, 12-month summation of the coating emissions.

Applicable Compliance Method:

Compliance with the hourly OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly OC emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 – 4, 18 and 25.

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), OAC rule 3745-31-05(A)(3), 3745-31-05(D), and 3745-21-07(G)(2)].

b. Emission Limitations:

OC emissions shall not exceed 19.8 pounds per day from cleanup materials

OC emissions shall not exceed 2.97 tons per year from cleanup materials

Applicable Compliance Method:

Compliance with the daily OC emission limitation from cleanup materials shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation from cleanup material shall be determined by the record keeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)].

c. Emission Limitation:

The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.

Applicable Compliance Method:

Compliance with the OC content limitation shall be determined by the record keeping requirements specified in d)(1). Formulation data or US EPA Method 24 shall be used to determine the OC content of any cleanup material employed in this emissions unit.

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

d. Material Usage Restriction:

The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3 gallons per day and 900 gallons per year.

Applicable Compliance Method:

Compliance with the daily cleanup material usage restriction shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual cleanup material usage restriction shall be determined by the recordkeeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

e. Emission Limitation:

See the organic HAP emission limitations noted in b)(2)b.

Applicable Compliance Method:

Compliance with the organic HAP emission limitation shall be based upon the information collected and recorded in d)(6) - d)(8) of this permit.

[Authority for term: OAC rules 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

f. Emission Limitations:

PE/PM-10 emissions shall not exceed 0.28 pound per hour;

PE/PM-10 emissions shall not exceed 1.38 pounds per day; and

PE/PM-10 emissions shall not exceed 0.24 ton per year, based on a rolling, 12-month summation.

Effective Date: To be entered upon final issuance

Applicable Compliance Method:

Compliance with the hourly PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly PE/PM10 emission limitation through emission tests performed in accordance with 40 CFR, Part 60, Appendix A, Methods 1-5.

Compliance with the daily PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and OAC 3745-31-05(D)].

- (2) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05338: f)(1)a. through f)(1)f. The testing requirements contained in the above-referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.

g) Miscellaneous Requirements

- (1) None.

Effective Date: To be entered upon final issuance

14. Emissions Unit Group - Open Molding Manual: P018, P019,

EU ID	Operations, Property and/or Equipment Description
P018	Manual Spray Chop Booth 1 Modification
P019	Manual Spray Chop Booth 2 Modification

- a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.
- (1) None.
- b) Applicable Emissions Limitations and/or Control Requirements
- (1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05196)	The Organic Compound (OC) emissions from resin application shall not exceed 8 pounds per hour and 40 lbs/day. OC emissions (acetone) shall not exceed 9.9 pounds per day from cleanup materials. OC emissions (acetone) shall not exceed 1.8 tons per year from cleanup materials. Particulate emissions (PE) and Particulate matter with a diameter of 10 microns or less (PM-10) shall not exceed 0.81 pound per hour. PE/PM10 emissions shall not exceed 4.1 pounds per day. The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(D) and 3745-17-07(A)(1). See c)(1) - c)(4).
b.	OAC rule 3745-31-05(D) Synthetic Minor Determination to	See b)(2)a. PE/PM10 emissions shall not exceed

Draft Title V Permit

Core Composites Cincinnati, LLC

Permit Number: P0104748**Facility ID:** 1413020248**Effective Date:** To be entered upon final issuance

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
	avoid the Emission Offset Policy for VOC.	0.51 ton per year based on a rolling, 12-month summation.
c.	OAC rule 3745-17-07(A)(1)	Visible particulate emissions from any stack shall not exceed 20% opacity, as a six minute average, except as specified by rule.
d.	OAC rule 3745-17-11(B)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
e.	OAC rule 3745-17-11(C)(3)	The Permit to Install for this emissions unit was issued July 9, 2002 (post January 1, 1990). Therefore, the emissions unit is exempt from the requirements of OAC rule 3745-17-11(C)(1) and (2). See b)(2)c.
f.	OAC rule 3745-21-07(G)(2)	The emission limitations specified by this rule are the same as the emission limitation established pursuant to OAC rule 3745-31-05(A)(3). See b)(2)d.
g.	40 CFR Part 63, Subpart WWWW (40 CFR 63.5780-5935) [In accordance with 63.5805(b), this emissions unit is an open molding using mechanical resin application at an existing reinforced plastic composites production facility subject to the emission limitations and work practices specified in 40 CFR 63.5805(b)]	Table 3 to 40 CFR Part 63, Subpart WWWW – Organic Hazardous Air Pollutant (HAP) Emission Limits for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. See b)(2)b and e. Table 4 to 40 CFR Part 63, Subpart WWWW – Applicable Work Practice Standards. See c)(5) and c)(6).
h.	40 CFR 63.1-15, Subpart A (40 CFR 63.5925)	Table 15 to 40 CFR Part 63, Subpart WWWW – Applicability of General Provisions (Subpart A) to Subpart WWWW shows which parts of the General Provisions in 40 CFR Part 63.1 – 15 apply.

Effective Date: To be entered upon final issuance

(2) Additional Terms and Conditions

a. The annual OC emission limit, for the coatings, employed in emissions units P018 through P020, combined shall not exceed 15.0 TPY, based on a rolling, 12-month summation. For purposes of clarification of non attainment new source review (NSR) permitting requirements and this Title V renewal permitting action, the permittee shall only employ non-VOC based cleanup materials. No cleanup materials with VOC as defined in OAC rule 3745-21-01 shall be employed. The emission of non-VOC based cleanup materials does not count towards the Synthetic Minor Determination to avoid the Emission Offset Policy for VOC established in PTI 14-05196.

b. The following organic HAP emission limitations shall not be exceeded based on a 12-month rolling average.

Operation Type	Organic HAP Emission Limit
Corrosion Resistant/Highs Strength (CR/HS)	113 lbs/ton
Non-CR/HS	88 lbs/ton
Tooling	254 lbs/ton
Low flame spread/low smoke products	497 lbs/ton
Shrinkage Controlled Resin	354 lbs/ton

c. On February 1, 2008, OAC rule 3745-17-11 was revised to include paragraph (C), pertaining to control requirements for particulate emissions from surface coating processes. These control requirements and the associated operational restrictions, monitoring, record keeping, and reporting requirements contained in this permit shall become federally enforceable on the date the U.S. EPA approves paragraph (C) of OAC rule 3745-17-11 as a revision to the Ohio State Implementation Plan.

d. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP); however, until the U.S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio.

e. This emissions unit is subject to the requirements of 40 CFR Part 63 Subpart WWWW - National Emissions Standards for Hazardous Air Pollutants for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. The permittee shall comply with the applicable emission limitations and operational restrictions specified in 40 CFR Part 63.5780 – 63.5930. The complete MACT requirements, including the MACT General Provisions may be accessed via the internet from the Electronic Code of Federal Regulations (e-CFR) website <http://ecfr.gpoaccess.gov> or by contacting the appropriate Ohio EPA District Office or local air agency.

Effective Date: To be entered upon final issuance

c) Operational Restrictions

- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 1.5 gallons per day and 550 gallons per year.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (2) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 lbs of OC/gallon.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (3) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1), 3745-31-05(A)(3) and 3745-21-07(G)(2)]

- (4) The permittee shall operate the dry filtration system for the control of particulate emissions whenever this emissions unit is in operation and shall maintain the dry particulate filter in accordance with the manufacturer's recommendations, instructions, and/or operating manual(s), with any modifications deemed necessary by the permittee.

In the event the particulate filter system is not operating in accordance with the manufacturer's recommendations, instructions, or operating manual, with any modifications deemed necessary by the permittee, the control device shall be expeditiously repaired or otherwise returned to these documented operating conditions.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (5) The permittee shall employ only non-HAP-containing cleanup materials in each emissions unit, except that styrene may be used as a cleaner in closed systems, and organic HAP containing cleaners may be used to clean cured resin from application equipment. Application equipment includes any equipment that directly contacts resin.

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR Part 63, Subpart WWWW Table 4]

- (6) The permittee shall keep containers that store HAP-containing coating materials and cleanup materials closed or covered, except during the addition or removal of materials. Bulk HAP-containing materials storage tanks may be vented as necessary for safety.

[Authority for term: OAC rules 3745-77-07(A)(1) and 40 CFR Part 63, Subpart WWWW Table 4]

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall collect and record the following information each day this emissions unit is in operation:

- a. company identification for each coating material (resin and/or gel coat) and cleanup material applied;

Effective Date: To be entered upon final issuance

- b. number of pounds of each coating material (resin and/or gel coat) applied;
- c. the HAP content, recorded in percent by weight, of each coating material (resin and/or gel coat) employed in this emissions unit;
- d. calculated OC (assumed equal to the organic HAP) emission factor using the equations to calculate organic HAP emission factors from Table 1 of 40 CFR Part 63, Subpart WWWW, in pounds of OC per ton of coating material (resin and/or gel coat) applied;
- e. total daily OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per day $[d)(1)b./2000 \times d)(1)d.]$;
- f. number of hours the emissions unit was in operation;
- g. average hourly OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per hour $[d)(1)e. \text{ divided by } d)(1)f.]$.
- h. total number of gallons of cleanup material applied;
- i. OC content of the cleanup material employed, in pounds per gallon;
- j. daily OC emissions from the cleanup material employed, in pounds $[d)(1)h. \times d)(1)i.]$;
- k. total PE/PM10 emission rate for all coatings employed, in pounds per day $[\text{summation of } d)(1)b. \times (1 - \text{HAP content, percent by weight}) \times 0.25 \text{ (25\% overspray)} \times (1 - 0.985, \text{ the control efficiency of the dry filtration system})]**$;
- l. average hourly PE/PM10 emission rate for all coatings employed, in pounds/hour $[d)(1)k. \text{ divided by } d)(1)f.]$;
- m. a determination whether or not each cleanup material employed is a photochemically reactive material, as defined in OAC rule 3745-21-05(C)(5); and
- n. a determination whether or not each cleanup material employed is a non-HAP material, as identified in Section 112(b) of the Clean Air Act.

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit].

** The 25% overspray and 98.5% control efficiency were used to establish the PE/PM10 emission rates established in PTI 14-05196 and are based on conservative engineering assumptions.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D), 3745-21-07(G)(2), and 40 CFR Part 63 Subpart WWWW]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:

- a. total OC emissions from all the coatings (resins and/or gel coat) employed, in tons [summation of d)(1)e. for all days of the calendar month, and divided by 2000 pounds per ton];
- b. updated rolling, 12-month summation of OC emission from all the coatings (resins and/or gel coats) employed, in tons [this shall include the total for the current month's OC emissions, plus the total for the preceding eleven calendar months];
- c. rolling, 12-month summation of OC emissions from all the coatings (resins and/or gel coats) employed, in tons, for emissions units P018 through P020;
- d. total PE/PM10 emissions for all coatings employed, in tons [summation of the data from d)(1)k. for all days of the calendar month divided by 2000 pounds per ton]; and
- e. rolling, 12-month summation of PE/PM10 emissions from all coatings employed, in tons [this shall include the total for the current month's PE/PM10 emissions, plus the total for the preceding eleven calendar months].

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and 3745-31-05(D)]

- (3) The permittee shall maintain annual records of the following information for this emissions unit:
 - a. total number of gallons of cleanup material employed [summation of d)(1)h. for all days the emissions unit was in operation]; and
 - b. total OC emissions from cleanup materials employed, in pounds [summation of d)(1)j. for all days of the emissions unit was in operation].

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) The permittee shall operate and maintain metering equipment to measure the amount of all resins and gel coats used in each emissions unit. The permittee shall calibrate the metering equipment to measure the amount, in weight or volume, of all resins and gel coats used in each emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the metering equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the metering equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the metering equipment, the permittee shall perform calibration and accuracy tests on the metering equipment on a monthly basis during the first six months of operation of the meters. The permittee calibration and accuracy tests for the metering equipment shall include two resins (the highest and lowest density resins) and two gel coats (the highest and lowest density gel coats). After completing six months of calibration and accuracy tests of the metering equipment and upon approval from the Hamilton County

Effective Date: To be entered upon final issuance

Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (5) The permittee shall operate and maintain measuring equipment to measure the amount of cleanup materials employed in this emissions unit. The permittee shall calibrate the measuring equipment to measure the amount, in weight or volume, of all cleanup materials employed in this emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the measuring equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the measuring equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the measuring equipment, the permittee shall perform calibration and accuracy tests on the measuring equipment on a monthly basis during the first six months of operation of the measuring equipment. The permittee calibration and accuracy tests for the measuring equipment shall include the cleanup material employed by the permittee. After completing six months of calibration and accuracy tests of the measuring equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (6) The permittee shall utilize one or more compliance options, as specified in 40 CFR 63.5810 to demonstrate compliance with the emission standards for open molding in Table 3 of this subpart, as described in the following sections:

63.5810(a)	individual resin or gel coat compliance demonstration
63.5810(b)	average individual organic HAP emissions limit compliance demonstration for all operations and application methods
63.5810(c)	weighted average emission limit compliance demonstration
63.5810(d)	organic HAP emission limit compliance demonstration for one resin type and application method

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR 63.5810]

- (7) The permittee is currently demonstrating compliance through the option specified in 63.5810(a). The permittee shall comply with the following data collection, emission calculation, and record keeping requirements, in addition to those listed in d)(8) below:
- a. Calculate your actual organic HAP emissions factor for each different process stream within this emissions unit. A process stream is defined as each individual combination of resin or gel coat, application technique, and control

Effective Date: To be entered upon final issuance

technique. Process streams within operations types are considered different from each other if any of the following four characteristics vary: the neat resin plus or neat gel coat plus organic HAP content, the gel coat type, the application technique, or the control technique. You must calculate organic HAP emissions factors for each different process stream by using the appropriate equations in Table 1 of 40 CFR Part 63 Subpart WWWW for open molding and for centrifugal casting, or site-specific organic HAP emissions factors discussed in §63.5796. The emission factor calculation should include any and all emission reduction techniques used. If you are using vapor suppressants to reduce HAP emissions, you must determine the vapor suppressant effectiveness (VSE) by conducting testing according to the procedures specified in appendix A to subpart WWWW of 40 CFR part 63.

Should the permittee choose to demonstrate compliance with the emission limitations listed in b)(2)b. by one of the alternative compliance demonstrations specified in d)(6), the permittee shall collect and record the information specified in 40 CFR 63.5810(b),(c), or (d), as appropriate.

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR 63.5810]

- (8) The permittee shall comply with the applicable monitoring and record keeping requirements under 40 CFR Part 63, Subpart WWWW, including the following sections:

63.5895(c) - (d)	records of resin and gel coat use, organic HAP content, operation and application method(s)
63.5915(a)	copy of compliance notification(s) and report(s)
63.5915(c)	records of all calculations and data used to determine organic HAP emissions factors or average organic HAP contents for operations and application methods as specified under 63.5810
63.5915(d)	certified statement of compliance with work practice requirements
63.5920(a) – (d)	record keeping format and retention requirements

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (9) The permittee shall maintain documentation of the manufacturer's recommendations, instructions, or operating manuals for the dry particulate filter, along with documentation of any modifications deemed necessary by the permittee. These documents shall be maintained at the facility and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (10) The permittee shall conduct periodic inspections of the dry particulate filter to determine whether it is operating in accordance with the manufacturer's recommendations, instructions, or operating manuals with any modifications deemed necessary by the

Effective Date: To be entered upon final issuance

permittee or operator. These inspections shall be performed at a frequency that shall be based upon the recommendation of the manufacturer and the permittee shall maintain a copy of the manufacturer's recommended inspection frequency and it shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (11) In addition to the recommended periodic inspections, not less than once each calendar year the permittee shall conduct a comprehensive inspection of the dry particulate filter while the emissions unit is shut down and perform any needed maintenance and repair to ensure that it is operated in accordance with the manufacturer's recommendations.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (12) The permittee shall document each inspection (periodic and annual) of the dry particulate filter system and shall maintain the following information:
- a. the date of the inspection;
 - b. a description of each/any problem identified and the date it was corrected;
 - c. a description of any maintenance and repairs performed; and
 - d. the name of person who performed the inspection.

These records shall be maintained at the facility for not less than five years from the date the inspection and any necessary maintenance or repairs were completed and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (13) The permittee shall maintain records that document any time periods when the dry particulate filter was not in service when the emissions unit(s) was/were in operation, as well as, a record of all operations during which the dry particulate filter was not operated according to the manufacturer's recommendations with any documented modifications made by the permittee. These records shall be maintained for a period of not less than five years and shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (14) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05196: d)(1) through d)(13). The monitoring and recordkeeping requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
- a. daily cleanup material usage restriction;

Effective Date: To be entered upon final issuance

- b. OC content limitation for the cleanup material;
- c. daily OC emission limitation for the cleanup material;
- d. hourly OC emission limitation for coatings;
- e. daily OC emission limitation for coatings;
- f. hourly PE/PM10 emission limitation;
- g. daily PE/PM10 emission limitation;
- h. rolling 12-month emission limitation for PE/PM10;
- i. rolling 12-month combined OC emission limitation for P018-P020; and
- j. any daily record showing that the dry particulate filter system was not in service or not operated according to manufacturer's recommendations (with any documented modifications made by the permittee) when the emissions unit(s) was/were in operation.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

- (2) The permittee shall submit annual reports to the Hamilton County Department of Environmental Services that specify the following:
- a. total amount, in gallons, of cleanup material employed for the calendar year;
 - b. total OC emissions from the cleanup material employed, in tons, for the calendar year; and
 - c. rolling, 12-month summation of OC emissions from emissions units P018 through P020, combined, for each calendar month.

This report shall be submitted by January 31 of each year and cover the previous calendar year.

[Authority for term: OAC rules 3745-77-07(C)(1)].

- (3) The permittee shall notify the Hamilton County Department of Environmental Services in writing of each day during which any photochemically reactive cleanup material [as defined in OAC rule 3745-21-01(C)(5)] was employed in this emissions unit. The notification shall include a copy of such record and shall be sent to the Hamilton County Department of Environmental Services within 45 days after the exceedance occurs.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) Upon replacement and/or initial operation of any metering or measuring equipment as specified in d)(4) and d)(5) of this permit, the permittee shall provide the Hamilton County Department of Environmental Services the following information: the name of the manufacturer of the metering/measuring equipment, the make and model of the

Effective Date: To be entered upon final issuance

metering/measuring equipment, calibration data (e.g., volume of coating per pump stroke), a copy of the manufacturer's specifications and warranty for the accuracy of the metering/measuring equipment and the actual accuracy of the material measurements (by weight or by volume) recorded for the metering/measuring equipment.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (5) The permittee shall submit calibration and accuracy test results for the metering equipment and measuring equipment specified in d)(4) and d)(5) of the terms and conditions of this permit. The calibration and accuracy tests results shall be submitted to the Hamilton County Department of Environmental Services by January 30 and July 30 of each calendar year, and shall cover the previous six-month period.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (6) The permittee shall submit semi-annual reports and such other notifications and reports to the Hamilton County Department of Environmental Services as are required in 40 CFR Part 63, Subpart WWWW, pursuant to the following sections:

63.5905(b)	15-day notification of change(s)
63.5910(a) - (b) and Table 14	semi-annual compliance reports
63.5910(c) - (i) and Table 14	content of semi-annual compliance reports

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (7) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05196: e)(1) through e)(6). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.

f) **Testing Requirements**

- (1) Compliance with the emission limitations and material usage restrictions specified in b) and c) shall be determined by the following methods:

- a. **Emission Limitations:**

OC emissions shall not exceed 8 pounds per hour from coatings (resin and gel coat);

OC emissions shall not exceed 40 pounds per day from coatings (resin and gel coat);

OC emissions shall not exceed 15.0 tons per year (TPY) from coatings (resins and gel coats) for emissions units P018 through P020, combined, based on a rolling, 12-month summation of the coating emissions.

Effective Date: To be entered upon final issuance

Applicable Compliance Method:

Compliance with the hourly OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly OC emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 – 4, 18 and 25.

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), OAC rule 3745-31-05(A)(3), 3745-31-05(D), and 3745-21-07(G)(2)].

b. Emission Limitations:

OC emissions shall not exceed 9.9 pounds per day from cleanup materials.

OC emissions shall not exceed 1.8 tons per year from cleanup materials.

Applicable Compliance Method:

Compliance with the daily OC emission limitation from cleanup materials shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation from cleanup material shall be determined by the record keeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)].

c. Emission Limitation:

The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.

Applicable Compliance Method:

Compliance with the OC content limitation shall be determined by the record keeping requirements specified in d)(1). Formulation data or US EPA Method 24 shall be used to determine the OC content of any cleanup material employed in this emissions unit.

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

d. Material Usage Restriction:

The maximum amount of all cleanup material employed in this emissions unit shall not exceed 1.5 gallons per day and 550 gallons per year.

Effective Date: To be entered upon final issuance

Applicable Compliance Method:

Compliance with the daily cleanup material usage restriction shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual cleanup material usage restriction shall be determined by the recordkeeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

e. Emission Limitation:

See the organic HAP emission limitations noted in b)(2)b.

Applicable Compliance Method:

Compliance with the organic HAP emission limitation shall be based upon the information collected and recorded in d)(6) - d)(8) of this permit.

[Authority for term: OAC rules 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

f. Emission Limitations:

PE/PM-10 emissions shall not exceed 0.81 pound per hour;

PE/PM-10 emissions shall not exceed 4.1 pounds per day; and

PE/PM-10 emissions shall not exceed 0.51 ton per year, based on a rolling, 12-month summation.

Applicable Compliance Method:

Compliance with the hourly PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly PE/PM10 emission limitation through emission tests performed in accordance with 40 CFR, Part 60, Appendix A, Methods 1-5.

Compliance with the daily PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and OAC 3745-31-05(D)].

- (2) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05196: f)(1)a. through f)(1)f. The testing requirements contained in the above-

Draft Title V Permit

Core Composites Cincinnati, LLC

Permit Number: P0104748

Facility ID: 1413020248

Effective Date: To be entered upon final issuance

referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.

g) Miscellaneous Requirements

(1) None.

Effective Date: To be entered upon final issuance

15. Emissions Unit Group - Open Molding Mechanical: P023, P024,

EU ID	Operations, Property and/or Equipment Description
P023	Robotic Spray Chop Booth 1
P024	Robotic Spray Chop Booth 2

- a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.
- (1) None.
- b) Applicable Emissions Limitations and/or Control Requirements
- (1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05223)	Particulate emissions (PE) and Particulate matter with a diameter of 10 microns or less (PM-10) shall not exceed 2.05 pounds per hour. PE/PM10 emissions shall not exceed 22.9 pounds per day. PE/PM10 emissions shall not exceed 2.77 TPY. The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(D), 3745-21-07(G)(9)(g), and 3745-17-07(A)(1). See c)(1) - c)(8).
b.	OAC rule 3745-31-05(D) Synthetic Minor Determination to avoid the Emission Offset Policy for VOC.	See b)(2)a.
c.	OAC rule 3745-17-07(A)(1)	Visible particulate emissions from any stack shall not exceed 20% opacity, as a six minute average, except as specified by rule.
d.	OAC rule 3745-17-11(B)	The emission limitation specified by this

Draft Title V Permit

Core Composites Cincinnati, LLC

Permit Number: P0104748**Facility ID:** 1413020248**Effective Date:** To be entered upon final issuance

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
e.	OAC rule 3745-17-11(C)(3)	The Permit to Install for this emissions unit was issued July 9, 2002 (post January 1, 1990). Therefore, the emissions unit is exempt from the requirements of OAC rule 3745-17-11(C)(1) and (2). See b)(2)c.
f.	OAC rule 3745-21-07(G)(9)(g)	The Organic Compound (OC) emissions from resin application shall not exceed 18.5 pounds per hour and 208 lbs/day. OC (acetone) emissions shall not exceed 13.2 pounds per day from cleanup materials. OC (acetone) emissions shall not exceed 1.16 tons per year from cleanup materials. See b)(2)d.
g.	40 CFR Part 63, Subpart WWWW (40 CFR 63.5780-5935) [In accordance with 63.5805(b), this emissions unit is an open molding using mechanical resin application at an existing reinforced plastic composites production facility subject to the emission limitations and work practices specified in 40 CFR 63.5805(b)]	Table 3 to 40 CFR Part 63, Subpart WWWW – Organic Hazardous Air Pollutant (HAP) Emission Limits for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. See b)(2)b. and e. Table 4 to 40 CFR Part 63, Subpart WWWW – Applicable Work Practice Standards. See c)(10) and c)(11).
h.	40 CFR 63.1-15, Subpart A (40 CFR 63.5925)	Table 15 to 40 CFR Part 63, Subpart WWWW – Applicability of General Provisions (Subpart A) to Subpart WWWW shows which parts of the General Provisions in 40 CFR Part 63.1 – 15 apply.

Effective Date: To be entered upon final issuance

(2) Additional Terms and Conditions

a. Organic Compound (OC) emissions shall not exceed 25.0 TPY from coatings, based on a rolling 12-month summation. For purposes of clarification of non attainment new source review (NSR) permitting requirements and this Title V renewal permitting action, the permittee shall only employ non-VOC based cleanup materials. No cleanup materials with VOC as defined in OAC rule 3745-21-01 shall be employed. The emission of non-VOC based cleanup materials does not count towards the Synthetic Minor Determination to avoid the Emission Offset Policy for VOC established in PTI 14-05223.

b. The following organic HAP emission limitations shall not be exceeded based on a 12-month rolling average.

Operation Type	Organic HAP Emission Limit
Corrosion Resistant/Highs Strength (CR/HS)	113 lbs/ton
Non-CR/HS	88 lbs/ton
Tooling	254 lbs/ton
Low flame spread/low smoke products	497 lbs/ton
Shrinkage Controlled Resin	354 lbs/ton

c. On February 1, 2008, OAC rule 3745-17-11 was revised to include paragraph (C), pertaining to control requirements for particulate emissions from surface coating processes. These control requirements and the associated operational restrictions, monitoring, record keeping, and reporting requirements contained in this permit shall become federally enforceable on the date the U.S. EPA approves paragraph (C) of OAC rule 3745-17-11 as a revision to the Ohio State Implementation Plan.

d. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP); however, until the U.S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio. The requirements of OAC 3745-21-07(G)(9)(g) have been carried over into 3745-21-07(M)(5)(e). Therefore, no change in emission limitations or terms and conditions will take place after the SIP is modified.

e. This emissions unit is subject to the requirements of 40 CFR Part 63 Subpart WWWW - National Emissions Standards for Hazardous Air Pollutants for Specific Open Molding, Centrifugal Casting, Pultrusion, and Continuous Lamination/Casting Operations. The permittee shall comply with the applicable emission limitations and operational restrictions specified in 40 CFR Part 63.5780 – 63.5930. The complete MACT requirements, including the MACT General Provisions may be accessed via the internet from the Electronic Code of Federal Regulations (e-CFR) website <http://ecfr.gpoaccess.gov> or by contacting the appropriate Ohio EPA District Office or local air agency.

c) Operational Restrictions

- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 2.0 gallons per day and 350 gallons per year.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (2) The styrene content of the neat resins shall not exceed the following limitations:

- a. 48%, by weight, as applied for each corrosion resistant material (Corrosion resistant materials are polyester resin materials used to make products for corrosion retardant applications such as tooling, fuel or chemical tanks and boat hulls.);
- b. 42%, by weight, as applied for each fire retardant material (Fire retardant materials are polyester resin materials used to make products resistant to flame or fire.); and
- c. 38%, by weight, as applied for all other materials.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (3) The amount of coatings (resins) employed in this emissions unit shall not exceed 840.9 pounds per hour, 9,412 pounds per day and 1,135 tons per year. The tons per year limitation is based upon a rolling, 12-month summation.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (4) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (5) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01, in this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (6) The permittee shall operate the dry filtration system for the control of particulate emissions whenever this emissions unit is in operation and shall maintain the dry particulate filter in accordance with the manufacturer's recommendations, instructions, and/or operating manual(s), with any modifications deemed necessary by the permittee.

In the event the particulate filter system is not operating in accordance with the manufacturer's recommendations, instructions, or operating manual, with any modifications deemed necessary by the permittee, the control device shall be expeditiously repaired or otherwise returned to these documented operating conditions.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (7) The permittee shall electronically monitor the amount of coating pumped by this emissions unit.

Effective Date: To be entered upon final issuance

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (8) The permittee shall only utilize robotic application equipment in this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (9) The permittee shall employ only non-HAP-containing cleanup materials in each emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3), and 40 CFR Part 63, Subpart WWWW Table 4]

- (10) The permittee shall keep containers that store HAP-containing coating materials and cleanup materials closed or covered, except during the addition or removal of materials.

[Authority for term: OAC rules 3745-77-07(A)(1), 3745-31-05(A)(3), and 40 CFR Part 63, Subpart WWWW Table 4]

d) **Monitoring and/or Recordkeeping Requirements**

- (1) The permittee shall collect and record the following information each day this emissions unit is in operation:

- a. company identification for each coating material (resin and/or gel coat) and cleanup material applied;
- b. number of pounds of each coating material (resin and/or gel coat) applied;
- c. the HAP content, recorded in percent by weight, of each coating material (resin and/or gel coat) employed in this emissions unit;
- d. calculated OC (assumed equal to the organic HAP) emission factor using the equations to calculate organic HAP emission factors from Table 1 of 40 CFR Part 63, Subpart WWWW, in pounds of OC per ton of coating material (resin and/or gel coat) applied;
- e. total daily OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per day $[d)(1)b./2000 \times d)(1)d.]$;
- f. number of hours the emissions unit was in operation;
- g. average hourly OC emission rate for all coatings (resins and/or gel coats) applied, in pounds per hour $[d)(1)e. \text{ divided by } d)(1)f.]$.
- h. total number of gallons of cleanup material applied;
- i. OC content of the cleanup material employed, in pounds per gallon;
- j. daily OC emissions from the cleanup material employed, in pounds $[d)(1)h. \times d)(1)i.]$;

Draft Title V Permit

Core Composites Cincinnati, LLC

Permit Number: P0104748

Facility ID: 1413020248

Effective Date: To be entered upon final issuance

- k. total PE/PM10 emission rate for all coatings employed, in pounds per day [summation of d)(1)b. x (1 - HAP content, percent by weight) x 0.25 (25% overspray) x (1 - 0.985, the control efficiency of the dry filtration system)]**;
- l. average hourly PE/PM10 emission rate for all coatings employed, in pounds/hour [d)(1)k. divided by d)(1)f.];
- m. a determination whether or not each cleanup material employed is a photochemically reactive material, as defined in OAC rule 3745-21-05(C)(5); and
- n. a determination whether or not each cleanup material employed is a non-HAP material, as identified in Section 112(b) of the Clean Air Act.

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit].

** The 25% overspray and 98.5% control efficiency were used to establish the PE/PM10 emission rates established in PTI 14-05223 and are based on conservative engineering assumptions.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D), 3745-21-07(G)(2), and 40 CFR Part 63 Subpart WWWW]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:
 - a. total OC emissions from all the coatings (resins and/or gel coat) employed, in tons [summation of d)(1)e. for all days of the calendar month, and divided by 2000 pounds per ton];
 - b. updated rolling, 12-month summation of OC emission from all the coatings (resins and/or gel coats) employed, in tons [this shall include the total for the current month's OC emissions, plus the total for the preceding eleven calendar months];
 - c. total PE/PM10 emissions for all coatings employed, in tons [summation of the data from d)(1)k. for all days of the calendar month divided by 2000 pounds per ton]; and
 - d. rolling, 12-month summation of PE/PM10 emissions from all coatings employed, in tons [this shall include the total for the current month's PE/PM10 emissions, plus the total for the preceding eleven calendar months]; and
 - e. rolling, 12-month summation all coatings employed, in tons [this shall include the total for the current months, plus the total for the preceding eleven calendar months].

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and 3745-31-05(D)]

- (3) The permittee shall maintain annual records of the following information for this emissions unit:
- a. total number of gallons of cleanup material employed [summation of d)(1)h. for all days the emissions unit was in operation]; and
 - b. total OC emissions from cleanup materials employed, in pounds [summation of d)(1)j. for all days of the emissions unit was in operation].

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) The permittee shall operate and maintain metering equipment to measure the amount of all resins and gel coats used in each emissions unit. The permittee shall calibrate the metering equipment to measure the amount, in weight or volume, of all resins and gel coats used in each emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the metering equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the metering equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the metering equipment, the permittee shall perform calibration and accuracy tests on the metering equipment on a monthly basis during the first six months of operation of the meters. The permittee calibration and accuracy tests for the metering equipment shall include two resins (the highest and lowest density resins) and two gel coats (the highest and lowest density gel coats). After completing six months of calibration and accuracy tests of the metering equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (5) The permittee shall operate and maintain measuring equipment to measure the amount of cleanup materials employed in this emissions unit. The permittee shall calibrate the measuring equipment to measure the amount, in weight or volume, of all cleanup materials employed in this emissions unit as necessary or appropriate to maintain the accuracy of the measurements guaranteed or specified by the manufacturer of the measuring equipment, or to an accuracy of within plus or minus five percent (5%) of the true value, whichever is more stringent.

Calibration and accuracy tests consistent with the measuring equipment manufacturer specifications shall be conducted semi-annually. If the manufacturer does not warrant or specify the calibration data or the accuracy of the material measurements for the measuring equipment, the permittee shall perform calibration and accuracy tests on the measuring equipment on a monthly basis during the first six months of operation of the measuring equipment. The permittee calibration and accuracy tests for the measuring equipment shall include the cleanup material employed by the permittee. After completing six months of calibration and accuracy tests of the measuring equipment and upon approval from the Hamilton County Department of Environmental Services, the permittee shall conduct calibration and accuracy tests semi-annually.

Effective Date: To be entered upon final issuance

[Authority for term: OAC rule 3745-77-07(C)(1)]

- (6) The permittee shall utilize one or more compliance options, as specified in 40 CFR 63.5810 to demonstrate compliance with the emission standards for open molding in Table 3 of this subpart, as described in the following sections:

63.5810(a)	individual resin or gel coat compliance demonstration
63.5810(b)	average individual organic HAP emissions limit compliance demonstration for all operations and application methods
63.5810(c)	weighted average emission limit compliance demonstration
63.5810(d)	organic HAP emission limit compliance demonstration for one resin type and application method

[Authority for term: OAC rule 3745-77-07(A)(1) and 40 CFR 63.5810]

- (7) The permittee is currently demonstrating compliance through the option specified in 63.5810(a). The permittee shall comply with the following data collection, emission calculation, and record keeping requirements, in addition to those listed in d)(8) below:

- a. Calculate your actual organic HAP emissions factor for each different process stream within this emissions unit. A process stream is defined as each individual combination of resin or gel coat, application technique, and control technique. Process streams within operations types are considered different from each other if any of the following four characteristics vary: the neat resin plus or neat gel coat plus organic HAP content, the gel coat type, the application technique, or the control technique. You must calculate organic HAP emissions factors for each different process stream by using the appropriate equations in Table 1 of 40 CFR Part 63 Subpart WWWW for open molding and for centrifugal casting, or site-specific organic HAP emissions factors discussed in §63.5796. The emission factor calculation should include any and all emission reduction techniques used. If you are using vapor suppressants to reduce HAP emissions, you must determine the vapor suppressant effectiveness (VSE) by conducting testing according to the procedures specified in appendix A to subpart WWWW of 40 CFR part 63.

Should the permittee choose to demonstrate compliance with the emission limitations listed in b)(2)b. by one of the alternative compliance demonstrations specified in d)(6), the permittee shall collect and record the information specified in 40 CFR 63.5810(b),(c), or (d), as appropriate.

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR 63.5810]

- (8) The permittee shall comply with the applicable monitoring and record keeping requirements under 40 CFR Part 63, Subpart WWWW, including the following sections:

Effective Date: To be entered upon final issuance

63.5895(c) - (d)	records of resin and gel coat use, organic HAP content, operation and application method(s)
63.5915(a)	copy of compliance notification(s) and report(s)
63.5915(c)	records of all calculations and data used to determine organic HAP emissions factors or average organic HAP contents for operations and application methods as specified under 63.5810
63.5915(d)	certified statement of compliance with work practice requirements
63.5920(a) – (d)	record keeping format and retention requirements

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

- (9) The permittee shall maintain documentation of the manufacturer's recommendations, instructions, or operating manuals for the dry particulate filter, along with documentation of any modifications deemed necessary by the permittee. These documents shall be maintained at the facility and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (10) The permittee shall conduct periodic inspections of the dry particulate filter to determine whether it is operating in accordance with the manufacturer's recommendations, instructions, or operating manuals with any modifications deemed necessary by the permittee or operator. These inspections shall be performed at a frequency that shall be based upon the recommendation of the manufacturer and the permittee shall maintain a copy of the manufacturer's recommended inspection frequency and it shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (11) In addition to the recommended periodic inspections, not less than once each calendar year the permittee shall conduct a comprehensive inspection of the dry particulate filter while the emissions unit is shut down and perform any needed maintenance and repair to ensure that it is operated in accordance with the manufacturer's recommendations.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (12) The permittee shall document each inspection (periodic and annual) of the dry particulate filter system and shall maintain the following information:
- a. the date of the inspection;
 - b. a description of each/any problem identified and the date it was corrected;
 - c. a description of any maintenance and repairs performed; and
 - d. the name of person who performed the inspection.

These records shall be maintained at the facility for not less than five years from the date the inspection and any necessary maintenance or repairs were completed and shall be

Effective Date: To be entered upon final issuance

made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (13) The permittee shall maintain records that document any time periods when the dry particulate filter was not in service when the emissions unit(s) was/were in operation, as well as, a record of all operations during which the dry particulate filter was not operated according to the manufacturer's recommendations with any documented modifications made by the permittee. These records shall be maintained for a period of not less than five years and shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (14) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05223: d)(1) through d)(13). The monitoring and recordkeeping requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
- a. daily cleanup material usage restriction;
 - b. OC content limitation for the cleanup material;
 - c. daily OC emission limitation for the cleanup material;
 - d. hourly OC emission limitation for coatings;
 - e. daily OC emission limitation for coatings;
 - f. hourly PE/PM10 emission limitation;
 - g. daily PE/PM10 emission limitation;
 - h. rolling 12-month emission limitation for PE/PM10;
 - i. hourly usage limitation;
 - j. daily usage limitation; and
 - k. rolling 12-month usage limitation.
 - l. any daily record showing that the dry particulate filter system was not in service or not operated according to manufacturer's recommendations (with any

Effective Date: To be entered upon final issuance

documented modifications made by the permittee) when the emissions unit(s) was/were in operation.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

- (2) The permittee shall submit annual reports to the Hamilton County Department of Environmental Services that specify the following:
- a. total amount, in gallons, of cleanup material employed for the calendar year;
 - b. total OC emissions from the cleanup material employed, in tons, for the calendar year; and
 - c. rolling, 12-month summation of OC emissions from this emissions unit, for each calendar month.

This report shall be submitted by January 31 of each year and cover the previous calendar year.

[Authority for term: OAC rules 3745-77-07(C)(1)].

- (3) The permittee shall notify the Hamilton County Department of Environmental Services in writing of each day during which any photochemically reactive cleanup material [as defined in OAC rule 3745-21-01(C)(5)] was employed in this emissions unit. The notification shall include a copy of such record and shall be sent to the Hamilton County Department of Environmental Services within 45 days after the exceedance occurs.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) Upon replacement and/or initial operation of any metering or measuring equipment as specified in d)(4) and d)(5) of this permit, the permittee shall provide the Hamilton County Department of Environmental Services the following information: the name of the manufacturer of the metering/measuring equipment, the make and model of the metering/measuring equipment, calibration data (e.g., volume of coating per pump stroke), a copy of the manufacturer's specifications and warranty for the accuracy of the metering/measuring equipment and the actual accuracy of the material measurements (by weight or by volume) recorded for the metering/measuring equipment.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (5) The permittee shall submit calibration and accuracy test results for the metering equipment and measuring equipment specified in d)(4) and d)(5) of the terms and conditions of this permit. The calibration and accuracy tests results shall be submitted to the Hamilton County Department of Environmental Services by January 30 and July 30 of each calendar year, and shall cover the previous six-month period.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (6) The permittee shall submit semi-annual reports and such other notifications and reports to the Hamilton County Department of Environmental Services as are required in 40 CFR Part 63, Subpart WWWW, pursuant to the following sections:

Effective Date: To be entered upon final issuance

63.5905(b)	15-day notification of change(s)
63.5910(a) - (b) and Table 14	semi-annual compliance reports
63.5910(c) - (i) and Table 14	content of semi-annual compliance reports

[Authority for term: OAC rule 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

(7) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05223: e)(1) through e)(6). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.

f) Testing Requirements

(1) Compliance with the emission limitations and material usage restrictions specified in b) and c) shall be determined by the following methods:

a. Emission Limitations:

OC emissions shall not exceed 18.5 pounds per hour from coatings (resin and gel coat);

OC emissions shall not exceed 208 pounds per day from coatings (resin and gel coat); and

OC emissions shall not exceed 25.0 tons per year (TPY) from coatings (resins and gel coats) for this emissions units, based on a rolling, 12-month summation of the coating emissions.

Applicable Compliance Method:

Compliance with the hourly OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly OC emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 – 4, 18 and 25.

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), OAC rule 3745-31-05(A)(3), 3745-31-05(D), and 3745-21-07(G)(2)].

b. Emission Limitations:

OC emissions shall not exceed 13.2 pounds per day from cleanup materials.

OC emissions shall not exceed 1.16 tons per year from cleanup materials.

Applicable Compliance Method:

Compliance with the daily OC emission limitation from cleanup materials shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation from cleanup material shall be determined by the record keeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)].

c. Emission Limitation:

The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.

Applicable Compliance Method:

Compliance with the OC content limitation shall be determined by the record keeping requirements specified in d)(1). Formulation data or US EPA Method 24 shall be used to determine the OC content of any cleanup material employed in this emissions unit.

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

d. Material Usage Restriction:

The maximum amount of all cleanup material employed in this emissions unit shall not exceed 2 gallons per day and 350 gallons per year.

Applicable Compliance Method:

Compliance with the daily cleanup material usage restriction shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual cleanup material usage restriction shall be determined by the recordkeeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

e. Emission Limitation:

See the organic HAP emission limitations noted in b)(2)b.

Applicable Compliance Method:

Compliance with the organic HAP emission limitation shall be based upon the information collected and recorded in d)(6) - d)(8) of this permit.

Effective Date: To be entered upon final issuance

[Authority for term: OAC rules 3745-77-07(C)(1) and 40 CFR Part 63, Subpart WWWW]

f. Emission Limitations:

PE/PM-10 emissions shall not exceed 2.05 pounds per hour;

PE/PM-10 emissions shall not exceed 22.9 pounds per day; and

PE/PM-10 emissions shall not exceed 2.77 tons per year.

Applicable Compliance Method:

Compliance with the hourly PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).

If required, the permittee shall demonstrate compliance with the hourly PE/PM10 emission limitation through emission tests performed in accordance with 40 CFR, Part 60, Appendix A, Methods 1-5.

Compliance with the daily PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual PE/PM10 emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and OAC 3745-31-05(D)].

- (2) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05223: f)(1)a. through f)(1)f. The testing requirements contained in the above-referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.

g) Miscellaneous Requirements

- (1) None.

Effective Date: To be entered upon final issuance

16. Emissions Unit Group - Primer Booths: R001, R002,

EU ID	Operations, Property and/or Equipment Description
R001	Primer Booth 1 Modification
R002	Primer Booth 2 Modification

- a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.
- (1) See d)(4) and d)(5).
- b) Applicable Emissions Limitations and/or Control Requirements
- (1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05253)	<p>The Organic Compound (OC) emissions from resin application shall not exceed 8 pounds per hour and 40 lbs/day.</p> <p>OC emissions shall not exceed 7.0 pounds per day from cleanup materials.</p> <p>Particulate emissions (PE) and Particulate matter with a diameter of 10 microns or less (PM-10) shall not exceed 0.17 pound per hour.*</p> <p>PE/PM10 emissions shall not exceed 0.73 ton per year.*</p> <p>The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(D) and 3745-17-07(A)(1).</p> <p>See c)(1) - c)(6).</p> <p>The PE/PM10 emission limitations are based on the emissions unit's potential to emit. Therefore, no records are required to demonstrate compliance with these limits.</p>
b.	OAC rule 3745-31-05(D)	See b)(2)a.

Effective Date: To be entered upon final issuance

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
	(PTI 14-05253) Synthetic Minor Determination to avoid the Emission Offset Policy for VOC.	
c.	OAC rule 3745-17-07(A)(1)	Visible PE from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.
d.	OAC rule 3745-17-11(B)	The PE limitation specified by this rule is less stringent than the PE limitation established pursuant to OAC rule 3745-31-05(A)(3).
e.	OAC rule 3745-17-11(C)(3)	The Permit to Install for this emissions unit was issued October 24, 2002 (post January 1, 1990). Therefore, the emissions unit is exempt from the requirements of OAC rule 3745-17-11(C)(1) and (2). See b)(2)c.
f.	OAC rule 3745-21-07(G)(2)	The emission limitations specified by this rule are the same as the emission limitation established pursuant to OAC rule 3745-31-05(A)(3). See b)(2)(b).

(2) Additional Terms and Conditions

- a. OC emissions shall not exceed 5.0 tons per year from all coatings and cleanup materials employed, based on a rolling, 12- month summation.
- b. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP); however, until the U. S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio.
- c. On February 1, 2008, OAC rule 3745-17-11 was revised to include paragraph (C), pertaining to control requirements for particulate emissions from surface coating processes. These control requirements and the associated operational restrictions, monitoring, record keeping, and reporting requirements contained in this permit shall become federally enforceable on the date the U.S. EPA

approves paragraph (C) of OAC rule 3745-17-11 as a revision to the Ohio State Implementation Plan.

c) Operational Restrictions

- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 0.936 gallon per day and 220 gallons per year, based upon a rolling, 12-month summation of the cleanup material usage.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (2) The maximum coating usage for this emissions unit shall not exceed 13.3 gallons/day and 2,820 gallons/year based upon a rolling, 12-month summation of the coating usage.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (3) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 7.0 lbs of OC/gallon.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (4) The maximum OC content of each coating employed in this emissions unit shall not exceed 3.0 lbs of OC/gallon, including water and exempt solvents, as applied.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (5) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01, in this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1), 3745-31-05(A)(3) and 3745-21-07(G)(2)]

- (6) The permittee shall operate the dry filtration system for the control of particulate emissions whenever this emissions unit is in operation and shall maintain the dry particulate filter in accordance with the manufacturer's recommendations, instructions, and/or operating manual(s), with any modifications deemed necessary by the permittee.

In the event the particulate filter system is not operating in accordance with the manufacturer's recommendations, instructions, or operating manual, with any modifications deemed necessary by the permittee, the control device shall be expeditiously repaired or otherwise returned to these documented operating conditions.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall collect and record the following information each day this emissions unit is in operation:

- a. company identification for each coating and cleanup material employed;
- b. number of gallons of each coating employed;

- c. OC content of each coating employed in this emissions unit, in pounds of OC per gallon;
- d. number of gallons of each cleanup material employed;
- e. OC content of each cleanup material, in pounds of OC per gallon;
- f. daily OC emissions for all coatings, in pounds (the summation of line d)(1)b. x d)(1)c. for all coatings employed);
- g. daily OC emissions from all cleanup materials employed, in pounds (the summation of line d)(1)d. x d)(1)e. for all cleanup materials employed);
- h. total number of hours this emissions unit was in operation;
- i. average hourly OC emission rate for all coatings, in pounds per hour [d)(1)f./d)(1)h.];
- j. total number of gallons of all coatings employed [summation of d)(1)b for all coatings employed];
- k. total number of gallons of all cleanup material employed [summation of d)(1)e. for all cleanup materials]; and
- l. documentation on whether or not each cleanup material employed is a photochemically reactive material as defined in OAC rule 3745-21-01(C)(5).

The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit. Also, the definitions of "photochemically reactive" is based upon OAC rule 3745-21-01(C)(5).

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3) and 3745-21-07(G)(2)]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:
 - a. the total number of gallons of coatings and cleanup materials employed during the calendar month [the summation of d)(1)b. for all coatings employed during the calendar month and the summation of d)(1)d. for all cleanup materials employed during the calendar month];
 - b. the updated rolling, 12-month summation of the coating and cleanup material usage figures, in gallons. The updated rolling, 12-month summation shall be calculated by adding the current monthly usage totals recorded in d)(2)a. to the previous 11-months usage totals recorded in d)(2)a.
 - c. the total monthly OC emissions from all coatings and cleanup materials employed, in tons [the summation of the daily OC emission totals recorded in d)(1)f., plus d)(1)g. for each day during the month this emissions unit was in operation, divided by 2,000 pounds per ton]; and

- d. the updated rolling, 12-month summation of the OC emissions from all coatings and cleanup materials, in tons. The updated rolling, 12-month summation shall be calculated by adding the current monthly OC emission totals recorded in line d)(2)c. to the previous 11- months' OC emission totals recorded in d)(2)c.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(D)]

- (3) The permit to install for this emissions unit was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Methyl Amyl Ketone

TLV (mg/m3): 233,000

Maximum Hourly Emission Rate (lbs/hr): 15.2

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 1,358

MAGLC (ug/m3): 5,547.6

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (5) The permittee shall maintain documentation of the manufacturer's recommendations, instructions, or operating manuals for the dry particulate filter, along with documentation of any modifications deemed necessary by the permittee. These documents shall be maintained at the facility and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (6) The permittee shall conduct periodic inspections of the dry particulate filter to determine whether it is operating in accordance with the manufacturer's recommendations, instructions, or operating manuals with any modifications deemed necessary by the permittee or operator. These inspections shall be performed at a frequency that shall be based upon the recommendation of the manufacturer and the permittee shall maintain a copy of the manufacturer's recommended inspection frequency and it shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (7) In addition to the recommended periodic inspections, not less than once each calendar year the permittee shall conduct a comprehensive inspection of the dry particulate filter while the emissions unit is shut down and perform any needed maintenance and repair to ensure that it is operated in accordance with the manufacturer's recommendations.

[Authority for term: OAC rules 3745-77-07(C)(1)]

Effective Date: To be entered upon final issuance

- (8) The permittee shall document each inspection (periodic and annual) of the dry particulate filter system and shall maintain the following information:
- a. the date of the inspection;
 - b. a description of each/any problem identified and the date it was corrected;
 - c. a description of any maintenance and repairs performed; and
 - d. the name of person who performed the inspection.

These records shall be maintained at the facility for not less than five years from the date the inspection and any necessary maintenance or repairs were completed and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (9) The permittee shall maintain records that document any time periods when the dry particulate filter was not in service when the emissions unit(s) was/were in operation, as well as, a record of all operations during which the dry particulate filter was not operated according to the manufacturer's recommendations with any documented modifications made by the permittee. These records shall be maintained for a period of not less than five years and shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (10) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05253: d)(1) through d)(9). The monitoring and recordkeeping requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
- a. daily cleanup material usage restriction;
 - b. daily coating usage restriction;
 - c. OC content limitation for the cleanup material;
 - d. OC content limitation for the coating material;
 - e. hourly OC emission limitation for the coating;
 - f. daily OC emission limitation for the cleanup material;
 - g. daily OC emission limitation for the coating;
 - h. rolling, 12-month OC emission limitation;

Effective Date: To be entered upon final issuance

- i. rolling, 12-month coating usage restriction;
- j. rolling, 12-month cleanup material usage restriction; and
- k. any daily record showing that the dry particulate filter system was not in service or not operated according to manufacturer's recommendations (with any documented modifications made by the permittee) when the emissions unit(s) was/were in operation.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D), and 3745-21-07(G)(2)].

- (2) The permittee shall notify the Hamilton County Department of Environmental Services in writing of each day during which any photochemically reactive cleanup material [as defined in OAC rule 3745-21-01(C)(5)] was employed in this emissions unit. The notification shall include a copy of such record and shall be sent to the Hamilton County Department of Environmental Services within 45 days after the exceedance occurs.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (3) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05253: e)(1) through e)(2). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.

f) **Testing Requirements**

- (1) Compliance with the emission limitations, OC content restrictions and material usage restrictions specified in b) and c) shall be determined in accordance with the following methods:

- a. **Emission Limitations:**

OC emissions shall not exceed 8.0 pounds per hour from coatings employed.

OC emissions shall not exceed 40.0 pounds per day from coatings employed.

OC emissions shall not exceed 7.0 pounds per day from cleanup materials employed.

OC emissions shall not exceed 5.0 tons per year from coatings and cleanup materials combined, based on a rolling, 12-month summation.

Applicable Compliance Method:

Compliance with the hourly and daily OC emission limitations shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).

Effective Date: To be entered upon final issuance

[Authority for term: OAC rules 3745-77-07(A)(1), 3745-31-05(A)(3), 3745-21-07(G)(2) and 3745-31-05(D)].

b. Emission Limitations:

3.0 pounds of OC per gallon for coatings.

7.0 pounds of OC per gallon for cleanup materials.

Applicable Compliance Method:

Compliance with the OC content limitations shall be determined by the record keeping requirements specified in d)(1). Formulation data or U.S. EPA Method 24 shall be used to determine the OC contents of coatings and cleanup materials employed in this emissions unit.

[Authority for term: OAC rules 3745-77-07(A)(1) and 3745-31-05(A)(3)].

c. Material Usage Restrictions:

The maximum cleanup material usage for this emissions unit shall not exceed 0.936 gallon per day and 220 gallons per year based upon a rolling, 12-month summation.

The maximum coating usage for this emissions unit shall not exceed 13.3 gallons per day and 2,820 gallons per year based upon a rolling, 12-month summation.

Applicable Compliance Method:

Compliance with the daily material usage restrictions shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual material usage restrictions shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(A)(1) and 3745-31-05(A)(3)].

d. Emission Limitations:

Particulate emissions (PE)/Particulate matter with a diameter of 10 microns or less (PM10) shall not exceed 0.17 pound per hour.

Particulate emissions (PE)/Particulate matter with a diameter of 10 microns or less (PM10) shall not exceed 0.73 ton per year.

Applicable Compliance Method:

The hourly PE/PM10 emission limitations based upon the emissions unit's potential to emit as was established by the following methodology:

lbs/hour of PE/PM10 emissions = (maximum gallons of coating/hour (1.89 gallons/hour)) x (10.16 lbs/gallon) x (1 - volatile content (42.45%), in percent by

Draft Title V Permit

Core Composites Cincinnati, LLC

Permit Number: P0104748

Facility ID: 1413020248

Effective Date: To be entered upon final issuance

weight) x (1 - 0.50 overspray control) x (1 - 0.97 (97% control efficiency of the overspray)).

The annual PE/PM10 emission limitation was determined by multiplying the hourly PE/PM10 emission limitation (0.17 lb/hr) by 8,760 hour/year and dividing by 2,000 lbs/ton. Therefore, compliance with the hourly PE/PM10 emission limitation ensures compliance with the annual PE/PM10 emission limitation.

The 50% overspray and 97% control efficiency were used to establish the PE/PM10 emission rates established in PTI 14-05253 and are based on conservative engineering assumptions.

If required, the permittee shall demonstrate compliance with the hourly PE/PM10 emission limitation through emission tests performed in accordance with 40 CFR, Part 60, Appendix A, Methods 1-5.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and OAC 3745-31-05(D)].

e. Emission Limitation:

Visible PE shall not exceed 20 percent opacity, as a six-minute average, except as provided by the rule.

Applicable Compliance Method:

If required, compliance shall be determined through visible emissions observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9, and the procedures specified in OAC rule 3745-17-03(B)(1).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-17-07(A)(1)].

- (2) Pursuant to OAC Rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05253: f(1)a through f(1)e. The testing requirements contained in the above-referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.

g) Miscellaneous Requirements

- (1) None.

Effective Date: To be entered upon final issuance

17. Emissions Unit Group - Primer Booths: R003, R004,

EU ID	Operations, Property and/or Equipment Description
R003	Primer Booth 3 Modification
R004	Primer Booth 4 Modification

- a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.
- (1) See d)(4) and d)(5).
- b) Applicable Emissions Limitations and/or Control Requirements
- (1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05253)	<p>The Organic Compound (OC) emissions from resin application shall not exceed 8 pounds per hour and 40 lbs/day.</p> <p>OC emissions shall not exceed 7.0 pounds per day from cleanup materials.</p> <p>Particulate emissions (PE) and Particulate matter with a diameter of 10 microns or less (PM-10) shall not exceed 0.17 pound per hour.*</p> <p>PE/PM10 emissions shall not exceed 0.73 ton per year.*</p> <p>The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(D) and 3745-17-07(A)(1).</p> <p>See c)(1) - c)(6).</p> <p>The PE/PM10 emission limitations are based on the emissions unit's potential to emit. Therefore, no records are required to demonstrate compliance with these limits.</p>
b.	OAC rule 3745-31-05(D)	See b)(2)a.

Effective Date: To be entered upon final issuance

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
	(PTI 14-05253) Synthetic Minor Determination to avoid the Emission Offset Policy for VOC.	
c.	OAC rule 3745-17-07(A)(1)	Visible PE from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.
d.	OAC rule 3745-17-11(B)	The PE limitation specified by this rule is less stringent than the PE limitation established pursuant to OAC rule 3745-31-05(A)(3).
e.	OAC rule 3745-17-11(C)(3)	The Permit to Install for this emissions unit was issued October 24, 2002 (post January 1, 1990). Therefore, the emissions unit is exempt from the requirements of OAC rule 3745-17-11(C)(1) and (2). See b)(2)c.
f.	OAC rule 3745-21-07(G)(2)	The emission limitations specified by this rule are the same as the emission limitation established pursuant to OAC rule 3745-31-05(A)(3). See b)(2)(b).

(2) Additional Terms and Conditions

- a. OC emissions shall not exceed 7.75 tons per year from all coatings and cleanup materials employed, based on a rolling, 12- month summation.
- b. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP); however, until the U. S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio.
- c. On February 1, 2008, OAC rule 3745-17-11 was revised to include paragraph (C), pertaining to control requirements for particulate emissions from surface coating processes. These control requirements and the associated operational restrictions, monitoring, record keeping, and reporting requirements contained in this permit shall become federally enforceable on the date the U.S. EPA

approves paragraph (C) of OAC rule 3745-17-11 as a revision to the Ohio State Implementation Plan.

c) Operational Restrictions

- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 0.936 gallon per day and 220 gallons per year, based upon a rolling, 12-month summation of the cleanup material usage.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (2) The maximum coating usage for this emissions unit shall not exceed 13.3 gallons/day and 2,820 gallons/year based upon a rolling, 12-month summation of the coating usage.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (3) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 7.0 lbs of OC/gallon.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (4) The maximum OC content of each coating employed in this emissions unit shall not exceed 3.0 lbs of OC/gallon, including water and exempt solvents, as applied.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

- (5) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01, in this emissions unit.

[Authority for term: OAC rule 3745-77-07(A)(1), 3745-31-05(A)(3) and 3745-21-07(G)(2)]

- (6) The permittee shall operate the dry filtration system for the control of particulate emissions whenever this emissions unit is in operation and shall maintain the dry particulate filter in accordance with the manufacturer's recommendations, instructions, and/or operating manual(s), with any modifications deemed necessary by the permittee.

In the event the particulate filter system is not operating in accordance with the manufacturer's recommendations, instructions, or operating manual, with any modifications deemed necessary by the permittee, the control device shall be expeditiously repaired or otherwise returned to these documented operating conditions.

[Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall collect and record the following information each day this emissions unit is in operation:

- a. company identification for each coating and cleanup material employed;
- b. number of gallons of each coating employed;

Effective Date: To be entered upon final issuance

- c. OC content of each coating employed in this emissions unit, in pounds of OC per gallon;
- d. number of gallons of each cleanup material employed;
- e. OC content of each cleanup material, in pounds of OC per gallon;
- f. daily OC emissions for all coatings, in pounds (the summation of line d)(1)b. x d)(1)c. for all coatings employed);
- g. daily OC emissions from all cleanup materials employed, in pounds (the summation of line d)(1)d. x d)(1)e. for all cleanup materials employed);
- h. total number of hours this emissions unit was in operation;
- i. average hourly OC emission rate for all coatings, in pounds per hour [d)(1)f./d.(1)h.];
- j. total number of gallons of all coatings employed [summation of d)(1)b. for all coatings employed];
- k. total number of gallons of all cleanup material employed [summation of d)(1)e. for all cleanup materials]; and
- l. documentation on whether or not each cleanup material employed is a photochemically reactive material as defined in OAC rule 3745-21-01(C)(5).

The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit. Also, the definitions of "photochemically reactive" is based upon OAC rule 3745-21-01(C)(5).

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3) and 3745-21-07(G)(2)]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:
 - a. the total number of gallons of coatings and cleanup materials employed during the calendar month [the summation of d)(1)b. for all coatings employed during the calendar month and the summation of d)(1)d. for all cleanup materials employed during the calendar month];
 - b. the updated rolling, 12-month summation of the coating and cleanup material usage figures, in gallons. The updated rolling, 12-month summation shall be calculated by adding the current monthly usage totals recorded in d)(2)a. to the previous 11-months usage totals recorded in d)(2)a.
 - c. the total monthly OC emissions from all coatings and cleanup materials employed, in tons [the summation of the daily OC emission totals recorded in d)(1)f., plus d)(1)g. for each day during the month this emissions unit was in operation, divided by 2,000 pounds per ton]; and

- d. the updated rolling, 12-month summation of the OC emissions from all coatings and cleanup materials, in tons. The updated rolling, 12-month summation shall be calculated by adding the current monthly OC emission totals recorded in line d)(2)c. to the previous 11-months OC emission totals recorded in d)(2)c.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(D)]

- (3) The permit to install for this emissions unit was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Methyl Amyl Ketone

TLV (mg/m³): 233,000

Maximum Hourly Emission Rate (lbs/hr): 15.2

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 1,061

MAGLC (ug/m³): 5,547.6

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (4) If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (5) The permittee shall maintain documentation of the manufacturer's recommendations, instructions, or operating manuals for the dry particulate filter, along with documentation of any modifications deemed necessary by the permittee. These documents shall be maintained at the facility and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (6) The permittee shall conduct periodic inspections of the dry particulate filter to determine whether it is operating in accordance with the manufacturer's recommendations, instructions, or operating manuals with any modifications deemed necessary by the permittee or operator. These inspections shall be performed at a frequency that shall be based upon the recommendation of the manufacturer and the permittee shall maintain a copy of the manufacturer's recommended inspection frequency and it shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (7) In addition to the recommended periodic inspections, not less than once each calendar year the permittee shall conduct a comprehensive inspection of the dry particulate filter while the emissions unit is shut down and perform any needed maintenance and repair to ensure that it is operated in accordance with the manufacturer's recommendations.

[Authority for term: OAC rules 3745-77-07(C)(1)]

Effective Date: To be entered upon final issuance

- (8) The permittee shall document each inspection (periodic and annual) of the dry particulate filter system and shall maintain the following information:
- a. the date of the inspection;
 - b. a description of each/any problem identified and the date it was corrected;
 - c. a description of any maintenance and repairs performed; and
 - d. the name of person who performed the inspection.

These records shall be maintained at the facility for not less than five years from the date the inspection and any necessary maintenance or repairs were completed and shall be made available to the appropriate Ohio EPA District Office or local air agency upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (9) The permittee shall maintain records that document any time periods when the dry particulate filter was not in service when the emissions unit(s) was/were in operation, as well as, a record of all operations during which the dry particulate filter was not operated according to the manufacturer's recommendations with any documented modifications made by the permittee. These records shall be maintained for a period of not less than five years and shall be made available to the Ohio EPA upon request.

[Authority for term: OAC rules 3745-77-07(C)(1)]

- (10) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05253: d)(1) through d)(9). The monitoring and recordkeeping requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
- a. daily cleanup material usage restriction;
 - b. daily coating usage restriction;
 - c. OC content limitation for the cleanup material;
 - d. OC content limitation for the coating material;
 - e. hourly OC emission limitation for the coating;
 - f. daily OC emission limitation for the cleanup material;
 - g. daily OC emission limitation for the coating;
 - h. rolling, 12-month OC emission limitation;

Effective Date: To be entered upon final issuance

- i. rolling, 12-month coating usage restriction;
- j. rolling, 12-month cleanup material usage restriction; and
- k. any daily record showing that the dry particulate filter system was not in service or not operated according to manufacturer's recommendations (with any documented modifications made by the permittee) when the emissions unit(s) was/were in operation.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D), and 3745-21-07(G)(2)].

- (2) The permittee shall notify the Hamilton County Department of Environmental Services in writing of each day during which any photochemically reactive cleanup material [as defined in OAC rule 3745-21-01(C)(5)] was employed in this emissions unit. The notification shall include a copy of such record and shall be sent to the Hamilton County Department of Environmental Services within 45 days after the exceedance occurs.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (3) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05253: e)(1) through e)(2). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.

f) **Testing Requirements**

- (1) Compliance with the emission limitations, OC content restrictions and material usage restrictions specified in b) and c) shall be determined in accordance with the following methods:

- a. **Emission Limitations:**

OC emissions shall not exceed 8.0 pounds per hour from coatings employed.

OC emissions shall not exceed 40.0 pounds per day from coatings employed.

OC emissions shall not exceed 7.0 pounds per day from cleanup materials employed.

OC emissions shall not exceed 7.75 tons per year from coatings and cleanup materials combined, based on a rolling, 12-month summation.

Applicable Compliance Method:

Compliance with the hourly and daily OC emission limitations shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).

Effective Date: To be entered upon final issuance

[Authority for term: OAC rules 3745-77-07(A)(1), 3745-31-05(A)(3), 3745-21-07(G)(2) and 3745-31-05(D)].

b. Emission Limitations:

3.0 pounds of OC per gallon for coatings.

7.0 pounds of OC per gallon for cleanup materials.

Applicable Compliance Method:

Compliance with the OC content limitations shall be determined by the record keeping requirements specified in d)(1). Formulation data or U.S. EPA Method 24 shall be used to determine the OC contents of coatings and cleanup materials employed in this emissions unit.

[Authority for term: OAC rules 3745-77-07(A)(1) and 3745-31-05(A)(3)].

c. Material Usage Restrictions:

The maximum cleanup material usage for this emissions unit shall not exceed 0.936 gallon per day and 220 gallons per year based upon a rolling, 12-month summation.

The maximum coating usage for this emissions unit shall not exceed 13.3 gallons per day and 2,820 gallons per year based upon a rolling, 12-month summation.

Applicable Compliance Method:

Compliance with the daily material usage restrictions shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual material usage restrictions shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(A)(1) and 3745-31-05(A)(3)].

d. Emission Limitations:

Particulate emissions (PE)/Particulate matter with a diameter of 10 microns or less (PM10) shall not exceed 0.17 pound per hour.

Particulate emissions (PE)/Particulate matter with a diameter of 10 microns or less (PM10) shall not exceed 0.73 ton per year.

Applicable Compliance Method:

The hourly PE/PM10 emission limitations based upon the emissions unit's potential to emit as was established by the following methodology:

lbs/hour of PE/PM10 emissions = (maximum gallons of coating/hour (1.89 gallons/hour)) x (10.16 lbs/gallon) x (1 - volatile content (42.45%), in percent by

Draft Title V Permit

Core Composites Cincinnati, LLC

Permit Number: P0104748

Facility ID: 1413020248

Effective Date: To be entered upon final issuance

weight) x (1 - 0.50 overspray control) x (1 - 0.97 (97% control efficiency of the overspray)).

The annual PE/PM10 emission limitation was determined by multiplying the hourly PE/PM10 emission limitation (0.17 lb/hr) by 8,760 hour/year and dividing by 2,000 lbs/ton. Therefore, compliance with the hourly PE/PM10 emission limitation ensures compliance with the annual PE/PM10 emission limitation.

The 50% overspray and 97% control efficiency were used to establish the PE/PM10 emission rates established in PTI 14-05253 and are based on conservative engineering assumptions.

If required, the permittee shall demonstrate compliance with the hourly PE/PM10 emission limitation through emission tests performed in accordance with 40 CFR, Part 60, Appendix A, Methods 1-5.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and OAC 3745-31-05(D)].

e. Emission Limitation:

Visible PE shall not exceed 20 percent opacity, as a six-minute average, except as provided by the rule.

Applicable Compliance Method:

If required, compliance shall be determined through visible emissions observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9, and the procedures specified in OAC rule 3745-17-03(B)(1).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-17-07(A)(1)].

- (2) Pursuant to OAC Rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05253: f)(1)a. through f)(1)e. The testing requirements contained in the above-referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.

g) Miscellaneous Requirements

- (1) None.

Effective Date: To be entered upon final issuance

18. Emissions Unit Group - RTM Units: P040, P041,

EU ID	Operations, Property and/or Equipment Description
P040	RTM Pump 5 Building B
P041	RTM Pump 6 Building B

- a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.
- (1) See d)(4) and d)(5).
- b) Applicable Emissions Limitations and/or Control Requirements
- (1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05338)	Organic compound (OC) emissions shall not exceed 5 pounds per hour and 40 pounds per day from coating materials (resins and gel coat). OC emissions (Acetone) shall not exceed 19.8 pounds per day from cleanup materials. OC emissions (Acetone) shall not exceed 2.97 tons per year (TPY) from cleanup materials. See c)(1) through c)(3). Compliance with this rule also includes compliance with the requirements of OAC rules 3745-31-05(D) and OAC rule 3745-31-28.
b.	OAC rule 3745-31-05(D) (PTI 14-05338) Synthetic Minor Determination to avoid the Emission Offset Policy for VOC.	See b)(2)a.
c.	OAC rule 3745-21-07(G)(2)	The emission limitations specified by this rule are the same as or less stringent

Effective Date: To be entered upon final issuance

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		then the emission limitation established pursuant to OAC rule 3745-31-05(A)(3). See b)(2)b.
d.	OAC rule 3745-31-28	The requirements of this rule are satisfied by the requirements established in accordance with OAC rule 3745-31-05(A)(3).

(2) Additional Terms and Conditions

- a. The annual OC emission limitation, for the coatings employed in emissions units P026, P029, P040, and P041, combined, shall not exceed 28.0 tons per year, based on a rolling, 12-month summation of the coating emissions. For purposes of clarification of non attainment new source review (NSR) permitting requirements and this Title V renewal permitting action, the permittee shall only employ non-VOC based cleanup materials. No cleanup materials with VOC as defined in OAC rule 3745-21-01 shall be employed. The emission of non-VOC based cleanup materials does not count towards the Synthetic Minor Determination to avoid the Emission Offset Policy for VOC established in PTI 14-05338.
- b. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP); however, until the U. S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio.

c) Operational Restrictions

- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3.0 gallons per day and 900 gallons per year.
 [Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]
- (2) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.
 [Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]
- (3) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.
 [Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

Effective Date: To be entered upon final issuance

- (4) The permittee shall not employ volatile organic compound (VOC) cleanup materials as VOC is defined in OAC rule 3745-21-01.

[Authority for term: OAC rule 3745-77-07(A)(1)]

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall collect and record the following information for each day for this emissions unit:

- a. company identification for each coating (resin) and cleanup material employed;
- b. number of pounds of each coating material employed;
- c. the OC (styrene) content, recorded in percent by weight, of each coating employed in this emissions unit;
- d. total number of gallons of cleanup material employed;
- e. OC content of the cleanup material employed, in pounds per gallon;
- f. daily OC emissions from the cleanup material employed, in pounds [d)(1)d. multiplied by d)(1)e.];
- g. daily OC emissions from all coatings employed, in pounds [the summation d)(1)b. X d)(1)c. X 0.02* for all coatings employed during the day];
- h. number of hours this emissions unit was in operation;
- i. average hourly OC emission rate from all coatings, in pounds per hour [d)(1)g./ d)(1)h.];
- j. a determination whether or not each cleanup material employed is a photochemically reactive material, as defined in OAC rule 3745-21-05(C)(5); and
- k. a determination whether or not each cleanup material employed is a volatile organic compound, as defined in OAC rule 3745-21-01.

[Note: The coating information must be for the coatings, as employed, including any thinning solvents added at the emissions unit].

* The 2% evaporation loss is the worst case emission factor for closed mold vapor suppressed resins specified in AP-42, Fifth Edition, Chapter 4.4, Polyester Resin Plastic Products Fabrication, Table 4.4-2, published January 1995.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:

Draft Title V Permit

Core Composites Cincinnati, LLC

Permit Number: P0104748

Facility ID: 1413020248

Effective Date: To be entered upon final issuance

- a. total OC emissions from all the coatings employed, in tons [summation of d)(1)g. for all days of the calendar month, and divided by 2000 pounds per ton];
- b. updated rolling, 12-month summation of OC emission from all the coatings employed, in tons [this shall include the total for the current month, plus the total for the preceding eleven calendar months]; and
- c. rolling, 12-month summation of OC emissions from all the coatings employed, in tons, for emissions units P026, P029, P040, and P041 combined.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)]

- (3) The permittee shall maintain monthly records of the following information for this emissions unit:

- a. total number of gallons of cleanup material employed [summation of d)(1)d. for all days of the calendar month];
- b. total OC emissions from the cleanup material employed, in pounds [summation of d)(1)f. for all days of the calendar month];
- c. the year-to-date total number of gallons of cleanup material employed [summation of the data from d)(3)a. for all months of the calendar year]; and
- d. the year-to-date total OC emissions from the cleanup materials, in tons [summation of the data from d)(3)b. for all months of the calendar year, divided by 2000 pounds per ton].

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and 3745-21-07(G)(2)]

- (4) The permit to install for this emissions unit was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Styrene

TLV (mg/m³): 85,000

Maximum Hourly Emission Rate (lbs/hr): 26

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 820.8

MAGLC (ug/m³): 2,029

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (5) If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

Effective Date: To be entered upon final issuance

- (6) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05338: d)(1) through d)(5). The monitoring and recordkeeping requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
- a. daily cleanup material usage restriction;
 - b. OC content limitation for the cleanup material;
 - c. daily OC emission limitation for the cleanup material;
 - d. hourly OC emission limitation for coatings;
 - e. daily OC emission limitation for coatings; and
 - f. rolling, 12-month summation of OC emissions for emissions units P026, P029, P040, and P041 combined.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

- (2) The permittee shall submit annual reports to the Hamilton County Department of Environmental Services that specify the rolling, 12-month summation of OC emissions for emissions units P026, P029, P040, and P041 combined recorded in tons.

The reports shall be submitted by January 31 of each year and cover the previous calendar year.

[Authority for term: OAC rules 3745-77-07(C)(1)].

- (3) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05338: e)(1) through e)(2). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.

f) Testing Requirements

- (1) Compliance with the emission limitations and material usage restrictions specified in b) and c) shall be determined by the following methods:
- a. Emission Limitations:

Effective Date: To be entered upon final issuance

OC emissions shall not exceed 5 pounds per hour from coatings (resin);

OC emissions shall not exceed 40 pounds per day from coatings (resin); and

OC emissions shall not exceed 20 tons per year (TPY) from coatings for emissions units P026, P029, P040, and P041 combined, based on a rolling, 12-month summation of the coating emissions.

Applicable Compliance Method:

Compliance with the hourly OC emission limitation shall be determined by the record keeping requirements specified in d)(1). If required, the permittee shall demonstrate compliance with the hourly OC emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 – 4, 18 and 25.

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

b. Emission Limitations:

OC emissions shall not exceed 19.8 pounds per day from cleanup material.

OC emissions shall not exceed 2.97 tons per year from cleanup material.

Applicable Compliance Method:

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

c. Emission Limitation:

The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.

Applicable Compliance Method:

Compliance with the OC content limitation shall be determined by the record keeping requirements specified in d)(1). Formulation data or US EPA Method 24 shall be used to determine the OC content of any cleanup material employed in this emissions unit.

Effective Date: To be entered upon final issuance

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

d. **Material Usage Restrictions:**

The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3.0 gallons per day and 900 gallons per year.

Nonphotochemically reactive cleanup materials shall be employed.

Non-VOC based cleanup materials shall be employed.

Applicable Compliance Method:

Compliance with the daily cleanup material usage and content restrictions shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual cleanup material usage restriction shall be determined by the recordkeeping requirements specified in d)(3).

Compliance with the Nonphotochemically reactive and Non-VOC cleanup material limitations shall be employed shall be determined by the recordkeeping requirements specified in d).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

- (2) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05338: f)(1)a. through f)(1)d. The testing requirements contained in the above-referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.

g) **Miscellaneous Requirements**

- (1) None.

Effective Date: To be entered upon final issuance

19. Emissions Unit Group - RTM Units: P015, P016, P017,

EU ID	Operations, Property and/or Equipment Description
P015	Clam Shell Mold 1
P016	Clam Shell Mold 2
P017	Cold Molding Area

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) See d)(4) and d)(5).

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05196)	Organic compound (OC) emissions shall not exceed 2.0 pounds per hour and 40 pounds per day from coating materials (resins and gel coat). OC emissions (Acetone) shall not exceed 19.8 pounds per day from cleanup materials. OC emissions (Acetone) shall not exceed 2.97 tons per year (TPY) from cleanup materials. See c)(1) through c)(3). Compliance with this rule also include compliance with the requirements of OAC rules 3745-31-05(D) and OAC rule 3745-31-28.
b.	OAC rule 3745-31-05(D) (PTI 14-05196) Synthetic Minor Determination to avoid the Emission Offset Policy for VOC.	See b)(2)a.
c.	OAC rule 3745-21-07(G)(2)	The emission limitations specified by this

Effective Date: To be entered upon final issuance

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		rule are the same as or less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3). See b)(2)b.
d.	OAC rule 3745-31-28	The requirements of this rule are satisfied by the requirements established in accordance with OAC rule 3745-31-05(A)(3).

(2) Additional Terms and Conditions

- a. The annual OC emission limitation, for the coatings employed in emissions units P006, P013 through P017, P021, P027, P028, P032 and P035, combined, shall not exceed 20.0 tons per year, based on a rolling, 12-month summation of the coating emissions. For purposes of clarification of non attainment new source review (NSR) permitting requirements and this Title V renewal permitting action, the permittee shall only employ non-VOC based cleanup materials. No cleanup materials with VOC as defined in OAC rule 3745-21-01 shall be employed. The emission of non-VOC based cleanup materials does not count towards the Synthetic Minor Determination to avoid the Emission Offset Policy for VOC established in PTI 14-05196.
- b. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP); however, until the U. S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio.

c) Operational Restrictions

- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3.0 gallons per day and 900 gallons per year.
 [Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]
- (2) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.
 [Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]
- (3) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.
 [Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

Effective Date: To be entered upon final issuance

- (4) The permittee shall not employ volatile organic compound (VOC) cleanup materials as VOC is defined in OAC rule 3745-21-01.

[Authority for term: OAC rule 3745-77-07(A)(1)]

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall collect and record the following information for each day for this emissions unit:

- a. company identification for each coating (resin) and cleanup material employed;
- b. number of pounds of each coating material employed;
- c. the OC (styrene) content, recorded in percent by weight, of each coating employed in this emissions unit;
- d. total number of gallons of cleanup material employed;
- e. OC content of the cleanup material employed, in pounds per gallon;
- f. daily OC emissions from the cleanup material employed, in pounds [d)(1)d. multiplied by d)(1)e.];
- g. daily OC emissions from all coatings employed, in pounds [the summation d)(1)b. X d)(1)c. X 0.02* for all coatings employed during the day];
- h. number of hours this emissions unit was in operation;
- i. average hourly OC emission rate from all coatings, in pounds per hour [d)(1)g./ d)(1)h.];
- j. a determination whether or not each cleanup material employed is a photochemically reactive material, as defined in OAC rule 3745-21-05(C)(5); and
- k. a determination whether or not each cleanup material employed is a volatile organic compound, as defined in OAC rule 3745-21-01.

[Note: The coating information must be for the coatings, as employed, including any thinning solvents added at the emissions unit].

* The 2% evaporation loss is the worst case emission factor for closed mold vapor suppressed resins specified in AP-42, Fifth Edition, Chapter 4.4, Polyester Resin Plastic Products Fabrication, Table 4.4-2, published January 1995.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:

Draft Title V Permit

Core Composites Cincinnati, LLC

Permit Number: P0104748

Facility ID: 1413020248

Effective Date: To be entered upon final issuance

- a. total OC emissions from all the coatings employed, in tons [summation of d)(1)g. for all days of the calendar month, and divided by 2000 pounds per ton];
- b. updated rolling, 12-month summation of OC emission from all the coatings employed, in tons [this shall include the total for the current month, plus the total for the preceding eleven calendar months]; and
- c. rolling, 12-month summation of OC emissions from all the coatings employed, in tons, for emissions units P006, P013 through P017, P021, P027, P028, P032 and P035 combined.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)]

- (3) The permittee shall maintain monthly records of the following information for this emissions unit:

- a. total number of gallons of cleanup material employed [summation of d)(1)d. for all days of the calendar month];
- b. total OC emissions from the cleanup material employed, in pounds [summation of d)(1)f. for all days of the calendar month];
- c. the year-to-date total number of gallons of cleanup material employed [summation of the data from d)(3)a. for all months of the calendar year]; and
- d. the year-to-date total OC emissions from the cleanup materials, in tons [summation of the data from d)(3)b. for all months of the calendar year, divided by 2000 pounds per ton].

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and 3745-21-07(G)(2)]

- (4) The permit to install for this emissions unit was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Styrene

TLV (mg/m³): 85,000

Maximum Hourly Emission Rate (lbs/hr): 125.5

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 1,857

MAGLC (ug/m³): 2,029

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (5) If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

Effective Date: To be entered upon final issuance

- (6) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05196: d)(1) through d)(5). The monitoring and recordkeeping requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
- a. daily cleanup material usage restriction;
 - b. OC content limitation for the cleanup material;
 - c. daily OC emission limitation for the cleanup material;
 - d. hourly OC emission limitation for coatings;
 - e. daily OC emission limitation for coatings; and
 - f. rolling, 12-month summation of OC emissions for emissions units P006, P013 through P017, P021, P027, P028, P032 and P035 combined.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

- (2) The permittee shall submit annual reports to the Hamilton County Department of Environmental Services that specify the rolling, 12-month summation of OC emissions for emissions units P006, P013 through P017, P021, P027, P028, P032 and P035 combined recorded in tons.

The reports shall be submitted by January 31 of each year and cover the previous calendar year.

[Authority for term: OAC rules 3745-77-07(C)(1)].

- (3) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05196: e)(1) through e)(2). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.

f) Testing Requirements

- (1) Compliance with the emission limitations and material usage restrictions specified in b) and c) shall be determined by the following methods:
- a. Emission Limitations:

Effective Date: To be entered upon final issuance

OC emissions shall not exceed 2.0 pounds per hour from coatings (resin);

OC emissions shall not exceed 40 pounds per day from coatings (resin); and

OC emissions shall not exceed 20 tons per year (TPY) from coatings for emissions units P006, P013 through P017, P021, P027, P028, P032 and P035 combined, based on a rolling, 12-month summation of the coating emissions.

Applicable Compliance Method:

Compliance with the hourly OC emission limitation shall be determined by the record keeping requirements specified in d)(1). If required, the permittee shall demonstrate compliance with the hourly OC emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 – 4, 18 and 25.

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

b. Emission Limitations:

OC emissions shall not exceed 19.8 pounds per day from cleanup material.

OC emissions shall not exceed 2.97 tons per year from cleanup material.

Applicable Compliance Method:

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

c. Emission Limitation:

The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.

Applicable Compliance Method:

Compliance with the OC content limitation shall be determined by the record keeping requirements specified in d)(1). Formulation data or US EPA Method 24 shall be used to determine the OC content of any cleanup material employed in this emissions unit.

Effective Date: To be entered upon final issuance

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

d. **Material Usage Restrictions:**

The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3.0 gallons per day and 900 gallons per year.

Nonphotochemically reactive cleanup materials shall be employed.

Non-VOC based cleanup materials shall be employed.

Applicable Compliance Method:

Compliance with the daily cleanup material usage and content restrictions shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual cleanup material usage restriction shall be determined by the recordkeeping requirements specified in d)(3).

Compliance with the Nonphotochemically reactive and Non-VOC cleanup material limitations shall be employed shall be determined by the recordkeeping requirements specified in d).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

- (2) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05196: f)(1)a. through f)(1)d. The testing requirements contained in the above-referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.

g) **Miscellaneous Requirements**

- (1) None.

Effective Date: To be entered upon final issuance

20. Emissions Unit Group - RTM Units: P002, P003, P004, P005,

EU ID	Operations, Property and/or Equipment Description
P002	RTM Pump 1 Bldg B
P003	RTM Pump 2 Bldg B
P004	RTM Pump 3 Bldg B
P005	RTM Pump 4 Bldg B

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) See d)(4) and d)(5).

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05196)	Organic compound (OC) emissions shall not exceed 5 pounds per hour and 40 pounds per day from coating materials (resins and gel coat). OC emissions (Acetone) shall not exceed 19.8 pounds per day from cleanup materials. OC emissions (Acetone) shall not exceed 2.97 tons per year (TPY) from cleanup materials. See c)(1) through c)(3). Compliance with this rule also include compliance with the requirements of OAC rules 3745-31-05(D) and OAC rule 3745-31-28.
b.	OAC rule 3745-31-05(D) (PTI 14-05196) Synthetic Minor Determination to avoid the Emission Offset Policy for VOC.	See b)(2)a.

Effective Date: To be entered upon final issuance

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
c.	OAC rule 3745-21-07(G)(2)	The emission limitations specified by this rule are the same as or less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3). See b)(2)b.
d.	OAC rule 3745-31-28	The requirements of this rule are satisfied by the requirements established in accordance with OAC rule 3745-31-05(A)(3).

(2) Additional Terms and Conditions

- a. The annual OC emission limitation, for the coatings employed in emissions units P002 through P005, P030, P031, P033 and P034, combined, shall not exceed 25.0 tons per year, based on a rolling, 12-month summation of the coating emissions. For purposes of clarification of non attainment new source review (NSR) permitting requirements and this Title V renewal permitting action, the permittee shall only employ non-VOC based cleanup materials. No cleanup materials with VOC as defined in OAC rule 3745-21-01 shall be employed. The emission of non-VOC based cleanup materials does not count towards the Synthetic Minor Determination to avoid the Emission Offset Policy for VOC established in PTI 14-05196.
- b. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP); however, until the U. S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio.

c) Operational Restrictions

- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3.0 gallons per day and 900 gallons per year.
 [Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]
- (2) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.
 [Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]
- (3) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.
 [Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

Effective Date: To be entered upon final issuance

- (4) The permittee shall not employ volatile organic compound (VOC) cleanup materials as VOC is defined in OAC rule 3745-21-01.

[Authority for term: OAC rule 3745-77-07(A)(1)]

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall collect and record the following information for each day for this emissions unit:

- a. company identification for each coating (resin) and cleanup material employed;
- b. number of pounds of each coating material employed;
- c. the OC (styrene) content, recorded in percent by weight, of each coating employed in this emissions unit;
- d. total number of gallons of cleanup material employed;
- e. OC content of the cleanup material employed, in pounds per gallon;
- f. daily OC emissions from the cleanup material employed, in pounds [d)(1)d. multiplied by d)(1)e.];
- g. daily OC emissions from all coatings employed, in pounds [the summation d)(1)b. X d.))(1)c. X 0.02* for all coatings employed during the day];
- h. number of hours this emissions unit was in operation;

average hourly OC emission rate from all coatings, in pounds per hour [d)(1)g./d)(1)h.];
- i. a determination whether or not each cleanup material employed is a photochemically reactive material, as defined in OAC rule 3745-21-05(C)(5); and
- j. a determination whether or not each cleanup material employed is a volatile organic compound, as defined in OAC rule 3745-21-01.

[Note: The coating information must be for the coatings, as employed, including any thinning solvents added at the emissions unit].

* The 2% evaporation loss is the worst case emission factor for closed mold vapor suppressed resins specified in AP-42, Fifth Edition, Chapter 4.4, Polyester Resin Plastic Products Fabrication, Table 4.4-2, published January 1995.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:

Draft Title V Permit

Core Composites Cincinnati, LLC

Permit Number: P0104748

Facility ID: 1413020248

Effective Date: To be entered upon final issuance

- a. total OC emissions from all the coatings employed, in tons [summation of d)(1)g. for all days of the calendar month, and divided by 2000 pounds per ton];
- b. updated rolling, 12-month summation of OC emission from all the coatings employed, in tons [this shall include the total for the current month, plus the total for the preceding eleven calendar months]; and
- c. rolling, 12-month summation of OC emissions from all the coatings employed, in tons, for emissions units P002 through P005, P030, P031, P033 and P034, combined.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)]

- (3) The permittee shall maintain monthly records of the following information for this emissions unit:

- a. total number of gallons of cleanup material employed [summation of d)(1)d. for all days of the calendar month];
- b. total OC emissions from the cleanup material employed, in pounds [summation of d)(1)f. for all days of the calendar month];
- c. the year-to-date total number of gallons of cleanup material employed [summation of the data from d)(3)a. for all months of the calendar year]; and
- d. the year-to-date total OC emissions from the cleanup materials, in tons [summation of the data from d)(3)b. for all months of the calendar year, divided by 2000 pounds per ton].

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and 3745-21-07(G)(2)]

- (4) The permit to install for this emissions unit was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Styrene

TLV (mg/m³): 85,000

Maximum Hourly Emission Rate (lbs/hr): 125.5

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 1,857

MAGLC (ug/m³): 2,029

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (5) If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

Effective Date: To be entered upon final issuance

- (6) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05196: d)(1) through d)(5). The monitoring and recordkeeping requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
- a. daily cleanup material usage restriction;
 - b. OC content limitation for the cleanup material;
 - c. daily OC emission limitation for the cleanup material;
 - d. hourly OC emission limitation for coatings;
 - e. daily OC emission limitation for coatings; and
 - f. rolling, 12-month summation of OC emissions for emissions units P002 through P005, P030, P031, P033 and P034 combined.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

- (2) The permittee shall submit annual reports to the Hamilton County Department of Environmental Services that specify the rolling, 12-month summation of OC emissions for emissions units P002 through P005, P030, P031, P033 and P034 combined recorded in tons.

The reports shall be submitted by January 31 of each year and cover the previous calendar year.

[Authority for term: OAC rules 3745-77-07(C)(1)].

- (3) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05196: e)(1) through e)(2). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.

f) Testing Requirements

- (1) Compliance with the emission limitations and material usage restrictions specified in b) and c) shall be determined by the following methods:
- a. Emission Limitations:

Effective Date: To be entered upon final issuance

OC emissions shall not exceed 5 pounds per hour from coatings (resin);

OC emissions shall not exceed 40 pounds per day from coatings (resin);

OC emissions shall not exceed 25 tons per year (TPY) from coatings for emissions units P002 through P005, P030, P031, P033 and P034, combined, based on a rolling, 12-month summation of the coating emissions.

Applicable Compliance Method:

Compliance with the hourly OC emission limitation shall be determined by the record keeping requirements specified in d)(1). If required, the permittee shall demonstrate compliance with the hourly OC emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 – 4, 18 and 25.

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

b. Emission Limitations:

OC emissions shall not exceed 19.8 pounds per day from cleanup material.

OC emissions shall not exceed 2.97 tons per year from cleanup material.

Applicable Compliance Method:

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

c. Emission Limitation:

The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.

Applicable Compliance Method:

Compliance with the OC content limitation shall be determined by the record keeping requirements specified in d)(1). Formulation data or US EPA Method 24 shall be used to determine the OC content of any cleanup material employed in this emissions unit.

Effective Date: To be entered upon final issuance

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

d. **Material Usage Restrictions:**

The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3.0 gallons per day and 900 gallons per year.

Nonphotochemically reactive cleanup materials shall be employed.

Non-VOC based cleanup materials shall be employed.

Applicable Compliance Method:

Compliance with the daily cleanup material usage and content restrictions shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual cleanup material usage restriction shall be determined by the recordkeeping requirements specified in d)(3).

Compliance with the Nonphotochemically reactive and Non-VOC cleanup material limitations shall be employed shall be determined by the recordkeeping requirements specified in d).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

- (2) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05196: f)(1)a. through f)(1)d. The testing requirements contained in the above-referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.

g) **Miscellaneous Requirements**

- (1) None.

Effective Date: To be entered upon final issuance

21. Emissions Unit Group - RTM Units: P033, P034,

EU ID	Operations, Property and/or Equipment Description
P033	RTM Pump 7 Bldg B
P034	RTM Pump 8 Bldg B

- a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.
- (1) See d)(4) and d)(5).
- b) Applicable Emissions Limitations and/or Control Requirements
- (1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05196)	Organic compound (OC) emissions shall not exceed 3 pounds per hour and 40 pounds per day from coating materials (resins and gel coat). OC emissions (Acetone) shall not exceed 19.8 pounds per day from cleanup materials. OC emissions (Acetone) shall not exceed 2.97 tons per year (TPY) from cleanup materials. See c)(1) through c)(3). Compliance with this rule also include compliance with the requirements of OAC rules 3745-31-05(D) and 3745-31-28.
b.	OAC rule 3745-31-05(D) (PTI 14-05196) Synthetic Minor Determination to avoid the Emission Offset Policy for VOC.	See b)(2)a.
c.	OAC rule 3745-21-07(G)(2)	The emission limitations specified by this rule are less stringent than the emission limitation established pursuant to OAC

Effective Date: To be entered upon final issuance

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		rule 3745-31-05(A)(3). See b)(2)b.
d.	OAC rule 3745-31-28	The requirements of this rule are satisfied by the requirements established in accordance with OAC rule 3745-31-05(A)(3).

(2) Additional Terms and Conditions

- a. The annual OC emission limitation, for the coatings employed in emissions units P002 through P005, P030, P031, P033 and P034, combined, shall not exceed 25.0 tons per year, based on a rolling, 12-month summation of the coating emissions. For purposes of clarification of non attainment new source review (NSR) permitting requirements and this Title V renewal permitting action, the permittee shall only employ non-VOC based cleanup materials. No cleanup materials with VOC as defined in OAC rule 3745-21-01 shall be employed. The emission of non-VOC based cleanup materials does not count towards the Synthetic Minor Determination to avoid the Emission Offset Policy for VOC established in PTI 14-05196.
- b. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP); however, until the U. S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio.

c) Operational Restrictions

- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3.0 gallons per day and 900 gallons per year.
 [Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]
- (2) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.
 [Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]
- (3) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.
 [Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]
- (4) The permittee shall not employ volatile organic compound (VOC) cleanup materials as VOC is defined in OAC rule 3745-21-01.

Effective Date: To be entered upon final issuance

[Authority for term: OAC rule 3745-77-07(A)(1)]

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall collect and record the following information for each day for this emissions unit:
- a. company identification for each coating (resin) and cleanup material employed;
 - b. number of pounds of each coating material employed;
 - c. the OC (styrene) content, recorded in percent by weight, of each coating employed in this emissions unit;
 - d. total number of gallons of cleanup material employed;
 - e. OC content of the cleanup material employed, in pounds per gallon;
 - f. daily OC emissions from the cleanup material employed, in pounds [d)(1)d. multiplied by d)(1)e.];
 - g. daily OC emissions from all coatings employed, in pounds [the summation d)(1)b. X d)(1)c. X 0.02* for all coatings employed during the day];
 - h. number of hours this emissions unit was in operation;
 - i. average hourly OC emission rate from all coatings, in pounds per hour [d)(1)g./ d)(1)h.];
 - j. a determination whether or not each cleanup material employed is a photochemically reactive material, as defined in OAC rule 3745-21-05(C)(5); and
 - k. a determination whether or not each cleanup material employed is a volatile organic compound, as defined in OAC rule 3745-21-01.

[Note: The coating information must be for the coatings, as employed, including any thinning solvents added at the emissions unit].

* The 2% evaporation loss is the worst case emission factor for closed mold vapor suppressed resins specified in AP-42, Fifth Edition, Chapter 4.4, Polyester Resin Plastic Products Fabrication, Table 4.4-2, published January 1995.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:
- a. total OC emissions from all the coatings employed, in tons [summation of d)(1)g. for all days of the calendar month, and divided by 2000 pounds per ton];

- b. updated rolling, 12-month summation of OC emission from all the coatings employed, in tons [this shall include the total for the current month, plus the total for the preceding eleven calendar months]; and
- c. rolling, 12-month summation of OC emissions from all the coatings employed, in tons, for emissions units P002 through P005, P030, P031, P033 and P034, combined.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)]

- (3) The permittee shall maintain monthly records of the following information for this emissions unit:
 - a. total number of gallons of cleanup material employed [summation of d)(1)d. for all days of the calendar month];
 - b. total OC emissions from the cleanup material employed, in pounds [summation of d)(1)f. for all days of the calendar month];
 - c. the year-to-date total number of gallons of cleanup material employed [summation of the data from d)(3)a. for all months of the calendar year]; and
 - d. the year-to-date total OC emissions from the cleanup materials, in tons [summation of the data from d)(3)b. for all months of the calendar year, divided by 2000 pounds per ton].

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and 3745-21-07(G)(2)]

- (4) The permit to install for this emissions unit was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Styrene

TLV (mg/m³): 85,000

Maximum Hourly Emission Rate (lbs/hr): 125.5

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 1,857

MAGLC (ug/m³): 2,029

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not

the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (5) If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy."

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (6) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05196: d)(1) through d)(5). The

Effective Date: To be entered upon final issuance

monitoring and recordkeeping requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
 - a. daily cleanup material usage restriction;
 - b. OC content limitation for the cleanup material;
 - c. daily OC emission limitation for the cleanup material;
 - d. hourly OC emission limitation for coatings;
 - e. daily OC emission limitation for coatings; and
 - f. rolling, 12-month summation of OC emissions for emissions units P002 through P005, P030, P031, P033 and P034 combined.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

- (2) The permittee shall submit annual reports to the Hamilton County Department of Environmental Services that specify the rolling, 12-month summation of OC emissions for emissions units P002 through P005, P030, P031, P033 and P034 combined recorded in tons.

The reports shall be submitted by January 31 of each year and cover the previous calendar year.

[Authority for term: OAC rules 3745-77-07(C)(1)].

- (3) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05196: e)(1) through e)(2). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.

f) Testing Requirements

- (1) Compliance with the emission limitations and material usage restrictions specified in b) and c) shall be determined by the following methods:
 - a. Emission Limitations:
OC emissions shall not exceed 5 pounds per hour from coatings (resin);

Effective Date: To be entered upon final issuance

OC emissions shall not exceed 40 pounds per day from coatings (resin);

OC emissions shall not exceed 25 tons per year (TPY) from coatings for emissions units P002 through P005, P030, P031, P033 and P034, combined, based on a rolling, 12-month summation of the coating emissions.

Applicable Compliance Method:

Compliance with the hourly OC emission limitation shall be determined by the record keeping requirements specified in d)(1). If required, the permittee shall demonstrate compliance with the hourly OC emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 – 4, 18 and 25.

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

b. Emission Limitations:

OC emissions shall not exceed 19.8 pounds per day from cleanup material.

OC emissions shall not exceed 2.97 tons per year from cleanup material.

Applicable Compliance Method:

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

c. Emission Limitation:

The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.

Applicable Compliance Method:

Compliance with the OC content limitation shall be determined by the record keeping requirements specified in d)(1). Formulation data or US EPA Method 24 shall be used to determine the OC content of any cleanup material employed in this emissions unit.

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

d. **Material Usage Restrictions:**

The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3.0 gallons per day and 900 gallons per year.

Nonphotochemically reactive cleanup materials shall be employed.

Non-VOC based cleanup materials shall be employed.

Applicable Compliance Method:

Compliance with the daily cleanup material usage and content restrictions shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual cleanup material usage restriction shall be determined by the recordkeeping requirements specified in d)(3).

Compliance with the Nonphotochemically reactive and Non-VOC cleanup material limitations shall be employed shall be determined by the recordkeeping requirements specified in d).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

- (2) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05196: f)(1)a. through f)(1)d. The testing requirements contained in the above-referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.

g) **Miscellaneous Requirements**

- (1) None.

Effective Date: To be entered upon final issuance

22. Emissions Unit Group - RTM Units: P006, P013, P035,

EU ID	Operations, Property and/or Equipment Description
P006	RTM Pump 1 Main Bldg
P013	RTM Pump 2 Main Bldg
P035	RTM Pump 8 Main Bldg

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) See d)(4) and d)(5).

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05196)	Organic compound (OC) emissions shall not exceed 5 pounds per hour and 40 pounds per day from coating materials (resins and gel coat). OC emissions (Acetone) shall not exceed 19.8 pounds per day from cleanup materials. OC emissions (Acetone) shall not exceed 2.97 tons per year (TPY) from cleanup materials. See c)(1) through c)(3). Compliance with this rule also include compliance with the requirements of OAC rules 3745-31-05(D) and 3745-31-28.
b.	OAC rule 3745-31-05(D) (PTI 14-05196) Synthetic Minor Determination to avoid the Emission Offset Policy for VOC.	See b)(2)a.
c.	OAC rule 3745-21-07(G)(2)	The emission limitations specified by this rule are less stringent than the emission

Effective Date: To be entered upon final issuance

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		limitation established pursuant to OAC rule 3745-31-05(A)(3). See b)(2)b.
d.	OAC rule 3745-31-28	The requirements of this rule are satisfied by the requirements established in accordance with OAC rule 3745-31-05(A)(3).

(2) Additional Terms and Conditions

- a. The annual OC emission limitation, for the coatings employed in emissions units P006, P013 through P017, P021, P027, P028, P032 and P035, combined, shall not exceed 20.0 tons per year, based on a rolling, 12-month summation of the coating emissions. For purposes of clarification of non attainment new source review (NSR) permitting requirements and this Title V renewal permitting action, the permittee shall only employ non-VOC based cleanup materials. No cleanup materials with VOC as defined in OAC rule 3745-21-01 shall be employed. The emission of non-VOC based cleanup materials does not count towards the Synthetic Minor Determination to avoid the Emission Offset Policy for VOC established in PTI 14-05196.
- b. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP); however, until the U. S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio.

c) Operational Restrictions

- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3.0 gallons per day and 900 gallons per year.
 [Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]
- (2) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.
 [Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]
- (3) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.
 [Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]

Effective Date: To be entered upon final issuance

- (4) The permittee shall not employ volatile organic compound (VOC) cleanup materials as VOC is defined in OAC rule 3745-21-01.

[Authority for term: OAC rule 3745-77-07(A)(1)]

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall collect and record the following information for each day for this emissions unit:

- a. company identification for each coating (resin) and cleanup material employed;
- b. number of pounds of each coating material employed;
- c. the OC (styrene) content, recorded in percent by weight, of each coating employed in this emissions unit;
- d. total number of gallons of cleanup material employed;
- e. OC content of the cleanup material employed, in pounds per gallon;
- f. daily OC emissions from the cleanup material employed, in pounds [d)(1)d. multiplied by d)(1)e.];
- g. daily OC emissions from all coatings employed, in pounds [the summation d)(1)b. X d)(1)c. X 0.02* for all coatings employed during the day];
- h. number of hours this emissions unit was in operation;
- i. average hourly OC emission rate from all coatings, in pounds per hour [d)(1)g./ d)(1)h.];
- j. a determination whether or not each cleanup material employed is a photochemically reactive material, as defined in OAC rule 3745-21-05(C)(5); and
- k. a determination whether or not each cleanup material employed is a volatile organic compound, as defined in OAC rule 3745-21-01.

[Note: The coating information must be for the coatings, as employed, including any thinning solvents added at the emissions unit].

* The 2% evaporation loss is the worst case emission factor for closed mold vapor suppressed resins specified in AP-42, Fifth Edition, Chapter 4.4, Polyester Resin Plastic Products Fabrication, Table 4.4-2, published January 1995.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:

Draft Title V Permit

Core Composites Cincinnati, LLC

Permit Number: P0104748

Facility ID: 1413020248

Effective Date: To be entered upon final issuance

- a. total OC emissions from all the coatings employed, in tons [summation of d)(1)g. for all days of the calendar month, and divided by 2000 pounds per ton];
- b. updated rolling, 12-month summation of OC emission from all the coatings employed, in tons [this shall include the total for the current month, plus the total for the preceding eleven calendar months]; and
- c. rolling, 12-month summation of OC emissions from all the coatings employed, in tons, for emissions units P006, P013 through P017, P021, P027, P028, P032 and P035 combined.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)]

- (3) The permittee shall maintain monthly records of the following information for this emissions unit:

- a. total number of gallons of cleanup material employed [summation of d)(1)d. for all days of the calendar month];
- b. total OC emissions from the cleanup material employed, in pounds [summation of d)(1)f. for all days of the calendar month];
- c. the year-to-date total number of gallons of cleanup material employed [summation of the data from d)(3)a. for all months of the calendar year]; and
- d. the year-to-date total OC emissions from the cleanup materials, in tons [summation of the data from d)(3)b. for all months of the calendar year, divided by 2000 pounds per ton].

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and 3745-21-07(G)(2)]

- (4) The permit to install for this emissions unit was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Styrene

TLV (mg/m³): 85,000

Maximum Hourly Emission Rate (lbs/hr): 125.5

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 1,857

MAGLC (ug/m³): 2,029

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (5) If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

Effective Date: To be entered upon final issuance

- (6) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05196: d)(1) through d)(5). The monitoring and recordkeeping requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
- a. daily cleanup material usage restriction;
 - b. OC content limitation for the cleanup material;
 - c. daily OC emission limitation for the cleanup material;
 - d. hourly OC emission limitation for coatings;
 - e. daily OC emission limitation for coatings; and
 - f. rolling, 12-month summation of OC emissions for emissions units P006, P013 through P017, P021, P027, P028, P032 and P035 combined.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

- (2) The permittee shall submit annual reports to the Hamilton County Department of Environmental Services that specify the rolling, 12-month summation of OC emissions for emissions units P006, P013 through P017, P021, P027, P028, P032 and P035 combined recorded in tons.

The reports shall be submitted by January 31 of each year and cover the previous calendar year.

[Authority for term: OAC rules 3745-77-07(C)(1)].

- (3) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05196: e)(1) through e)(2). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.

f) Testing Requirements

- (1) Compliance with the emission limitations and material usage restrictions specified in b) and c) shall be determined by the following methods:
- a. Emission Limitations:

Effective Date: To be entered upon final issuance

OC emissions shall not exceed 5 pounds per hour from coatings (resin);

OC emissions shall not exceed 40 pounds per day from coatings (resin);

OC emissions shall not exceed 20 tons per year (TPY) from coatings for emissions units P006, P013 through P017, P021, P027, P028, P032 and P035 combined, based on a rolling, 12-month summation of the coating emissions.

Applicable Compliance Method:

Compliance with the hourly OC emission limitation shall be determined by the record keeping requirements specified in d)(1). If required, the permittee shall demonstrate compliance with the hourly OC emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 – 4, 18 and 25.

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

b. Emission Limitations:

OC emissions shall not exceed 19.8 pounds per day from cleanup material.

OC emissions shall not exceed 2.97 tons per year from cleanup material.

Applicable Compliance Method:

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

c. Emission Limitation:

The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.

Applicable Compliance Method:

Compliance with the OC content limitation shall be determined by the record keeping requirements specified in d)(1). Formulation data or US EPA Method 24 shall be used to determine the OC content of any cleanup material employed in this emissions unit.

Effective Date: To be entered upon final issuance

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

d. **Material Usage Restrictions:**

The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3.0 gallons per day and 900 gallons per year.

Nonphotochemically reactive cleanup materials shall be employed.

Non-VOC based cleanup materials shall be employed.

Applicable Compliance Method:

Compliance with the daily cleanup material usage and content restrictions shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual cleanup material usage restriction shall be determined by the recordkeeping requirements specified in d)(3).

Compliance with the Nonphotochemically reactive and Non-VOC cleanup material limitations shall be employed shall be determined by the recordkeeping requirements specified in d).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

- (2) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05196: f)(1)a. through f)(1)d. The testing requirements contained in the above-referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.

g) **Miscellaneous Requirements**

- (1) None.

Effective Date: To be entered upon final issuance

23. Emissions Unit Group - RTM Units: P021, P032,

EU ID	Operations, Property and/or Equipment Description
P021	RTM Pump 7 Main Bldg
P032	RTM Pump 4 Main Bldg

- a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (1) See d)(4) and d)(5).
- b) Applicable Emissions Limitations and/or Control Requirements
 - (1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 14-05196)	Organic compound (OC) emissions shall not exceed 3 pounds per hour and 40 pounds per day from coating materials (resins and gel coat). OC emissions (Acetone) shall not exceed 19.8 pounds per day from cleanup materials. OC emissions (Acetone) shall not exceed 2.97 tons per year (TPY) from cleanup materials. See c)(1) through c)(3). Compliance with this rule also include compliance with the requirements of OAC rules 3745-31-05(D) and 3745-31-28.
b.	OAC rule 3745-31-05(D) (PTI 14-05196) Synthetic Minor Determination to avoid the Emission Offset Policy for VOC.	See b)(2)a.
c.	OAC rule 3745-21-07(G)(2)	The emission limitations specified by this rule are less stringent than the emission limitation established pursuant to OAC

Effective Date: To be entered upon final issuance

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		rule 3745-31-05(A)(3). See b)(2)b.
d.	OAC rule 3745-31-28	The requirements of this rule are satisfied by the requirements established in accordance with OAC rule 3745-31-05(A)(3).

(2) Additional Terms and Conditions

- a. The annual OC emission limitation, for the coatings employed in emissions units P006, P013 through P017, P021, P027, P028, P032 and P035, combined, shall not exceed 20.0 tons per year, based on a rolling, 12-month summation of the coating emissions. For purposes of clarification of non attainment new source review (NSR) permitting requirements and this Title V renewal permitting action, the permittee shall only employ non-VOC based cleanup materials. No cleanup materials with VOC as defined in OAC rule 3745-21-01 shall be employed. The emission of non-VOC based cleanup materials does not count towards the Synthetic Minor Determination to avoid the Emission Offset Policy for VOC established in PTI 14-05196.
- b. On February 18, 2008, OAC rule 3745-21-07 was revised in its entirety; therefore, the 21-07 rule that was in effect prior to this date is no longer part of the State regulations. On April 4, 2008, the rule revision was submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP); however, until the U. S. EPA approves the revision to OAC rule 3745-21-07, the requirement to comply with the previous 21-07 rule provisions still exists as part of the federally-approved SIP for Ohio.

c) Operational Restrictions

- (1) The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3.0 gallons per day and 900 gallons per year.
 [Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]
- (2) The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.
 [Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]
- (3) The permittee shall not employ any photochemically reactive cleanup material, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.
 [Authority for term: OAC rule 3745-77-07(A)(1) and 3745-31-05(A)(3)]
- (4) The permittee shall not employ volatile organic compound (VOC) cleanup materials as VOC is defined in OAC rule 3745-21-01.

Effective Date: To be entered upon final issuance

[Authority for term: OAC rule 3745-77-07(A)(1)]

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall collect and record the following information for each day for this emissions unit:
- a. company identification for each coating (resin) and cleanup material employed;
 - b. number of pounds of each coating material employed;
 - c. the OC (styrene) content, recorded in percent by weight, of each coating employed in this emissions unit;
 - d. total number of gallons of cleanup material employed;
 - e. OC content of the cleanup material employed, in pounds per gallon;
 - f. daily OC emissions from the cleanup material employed, in pounds [d)(1)d. multiplied by d)(1)e.];
 - g. daily OC emissions from all coatings employed, in pounds [the summation d)(1)b. X d)(1)c. X 0.02* for all coatings employed during the day];
 - h. number of hours this emissions unit was in operation;
 - i. average hourly OC emission rate from all coatings, in pounds per hour [d)(1)g./ d)(1)h.];
 - j. a determination whether or not each cleanup material employed is a photochemically reactive material, as defined in OAC rule 3745-21-05(C)(5); and
 - k. a determination whether or not each cleanup material employed is a volatile organic compound, as defined in OAC rule 3745-21-01.

[Note: The coating information must be for the coatings, as employed, including any thinning solvents added at the emissions unit].

* The 2% evaporation loss is the worst case emission factor for closed mold vapor suppressed resins specified in AP-42, Fifth Edition, Chapter 4.4, Polyester Resin Plastic Products Fabrication, Table 4.4-2, published January 1995.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)]

- (2) The permittee shall collect and record the following information for each month for this emissions unit:
- a. total OC emissions from all the coatings employed, in tons [summation of d)(1)g. for all days of the calendar month, and divided by 2000 pounds per ton];

Draft Title V Permit

Core Composites Cincinnati, LLC

Permit Number: P0104748

Facility ID: 1413020248

Effective Date: To be entered upon final issuance

- b. updated rolling, 12-month summation of OC emission from all the coatings employed, in tons [this shall include the total for the current month, plus the total for the preceding eleven calendar months]; and
- c. rolling, 12-month summation of OC emissions from all the coatings employed, in tons, for emissions units P006, P013 through P017, P021, P027, P028, P032 and P035 combined.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)]

- (3) The permittee shall maintain monthly records of the following information for this emissions unit:

- a. total number of gallons of cleanup material employed [summation of d)(1)d. for all days of the calendar month];
- b. total OC emissions from the cleanup material employed, in pounds [summation of d)(1)f. for all days of the calendar month];
- c. the year-to-date total number of gallons of cleanup material employed [summation of the data from d)(3)a. for all months of the calendar year]; and
- d. the year-to-date total OC emissions from the cleanup materials, in tons [summation of the data from d)(3)b. for all months of the calendar year, divided by 2000 pounds per ton].

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), and 3745-21-07(G)(2)]

- (4) The permit to install for this emissions unit was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Styrene

TLV (mg/m³): 85,000

Maximum Hourly Emission Rate (lbs/hr): 125.5

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 1,857

MAGLC (ug/m³): 2,029

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not

the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (5) If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy."

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

[Authority for term: OAC rules 3745-77-07(C)(1) and 3745-31-05(A)(3)]

- (6) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following monitoring and recordkeeping requirements are as stringent as or more stringent than the monitoring and recordkeeping contained in Permit to Install PTI 14-05196: d)(1) through d)(5). The

Effective Date: To be entered upon final issuance

monitoring and recordkeeping requirements contained in the above-referenced Permit to Install are subsumed into the monitoring and recordkeeping requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying monitoring and recordkeeping requirements in the Permit to Install.

e) Reporting Requirements

- (1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
 - a. daily cleanup material usage restriction;
 - b. OC content limitation for the cleanup material;
 - c. daily OC emission limitation for the cleanup material;
 - d. hourly OC emission limitation for coatings;
 - e. daily OC emission limitation for coatings; and
 - f. rolling, 12-month summation of OC emissions for emissions units P006, P013 through P017, P021, P027, P028, P032 and P035 combined.

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

- (2) The permittee shall submit annual reports to the Hamilton County Department of Environmental Services that specify the rolling, 12-month summation of OC emissions for emissions units P006, P013 through P017, P021, P027, P028, P032 and P035 combined recorded in tons.

The reports shall be submitted by January 31 of each year and cover the previous calendar year.

[Authority for term: OAC rules 3745-77-07(C)(1)].

- (3) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following reporting requirements are as stringent as or more stringent than the reporting requirements contained in Permit to Install PTI 14-05196: e)(1) through e)(2). The reporting requirements contained in the above-referenced Permit to Install are subsumed into the reporting requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying reporting requirements in the Permit to Install.

f) Testing Requirements

- (1) Compliance with the emission limitations and material usage restrictions specified in b) and c) shall be determined by the following methods:
 - a. Emission Limitations:
OC emissions shall not exceed 3 pounds per hour from coatings (resin);

Effective Date: To be entered upon final issuance

OC emissions shall not exceed 40 pounds per day from coatings (resin);

OC emissions shall not exceed 20 tons per year (TPY) from coatings for emissions units P006, P013 through P017, P021, P027, P028, P032 and P035 combined, based on a rolling, 12-month summation of the coating emissions.

Applicable Compliance Method:

Compliance with the hourly OC emission limitation shall be determined by the record keeping requirements specified in d)(1). If required, the permittee shall demonstrate compliance with the hourly OC emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 – 4, 18 and 25.

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(2).

[Authority for term: OAC rules 3745-77-07(C)(1), 3745-31-05(A)(3), 3745-31-05(D) and 3745-21-07(G)(2)].

b. Emission Limitations:

OC emissions shall not exceed 19.8 pounds per day from cleanup material.

OC emissions shall not exceed 2.97 tons per year from cleanup material.

Applicable Compliance Method:

Compliance with the daily OC emission limitation shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual OC emission limitation shall be determined by the record keeping requirements specified in d)(3).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

c. Emission Limitation:

The maximum OC content of the cleanup material employed in this emissions unit shall not exceed 6.6 pounds of OC per gallon of cleanup material.

Applicable Compliance Method:

Compliance with the OC content limitation shall be determined by the record keeping requirements specified in d)(1). Formulation data or US EPA Method 24 shall be used to determine the OC content of any cleanup material employed in this emissions unit.

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

d. **Material Usage Restrictions:**

The maximum amount of all cleanup material employed in this emissions unit shall not exceed 3.0 gallons per day and 900 gallons per year.

Nonphotochemically reactive cleanup materials shall be employed.

Non-VOC based cleanup materials shall be employed.

Applicable Compliance Method:

Compliance with the daily cleanup material usage and content restrictions shall be determined by the record keeping requirements specified in d)(1).

Compliance with the annual cleanup material usage restriction shall be determined by the recordkeeping requirements specified in d)(3).

Compliance with the Nonphotochemically reactive and Non-VOC cleanup material limitations shall be employed shall be determined by the recordkeeping requirements specified in d).

[Authority for term: OAC rules 3745-77-07(C)(1), and 3745-31-05(A)(3)]

- (2) Pursuant to OAC rule 3745-77-07(A)(3)(a)(ii), the following testing requirements are as stringent as or more stringent than the testing requirements contained in Permit to Install PTI 14-05196: f)(1)a. through f)(1)d. The testing requirements contained in the above-referenced Permit to Install are subsumed into the testing requirements of this operating permit, so that compliance with these requirements constitutes compliance with the underlying testing requirements in the Permit to Install.

g) **Miscellaneous Requirements**

- (1) None.