



State of Ohio Environmental Protection Agency

**RE: DRAFT PERMIT TO INSTALL CERTIFIED MAIL**  
**ASHTABULA COUNTY**

Street Address:

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov.  
Center

**Application No: 02-19429**

**DATE: 8/3/2004**

Glastic Corp  
Robert Sedlatschek  
400 East Erie Ave  
Jefferson, OH 44047

You are hereby notified that the Ohio Environmental Protection Agency has made a draft action recommending that the Director issue a Permit to Install for the air contaminant source(s) [emissions unit(s)] shown on the enclosed draft permit. This draft action is not an authorization to begin construction or modification of your emissions unit(s). The purpose of this draft is to solicit public comments on the proposed installation. A public notice concerning the draft permit will appear in the Ohio EPA Weekly Review and the newspaper in the county where the facility will be located. Public comments will be accepted by the field office within 30 days of the date of publication in the newspaper. Any comments you have on the draft permit should be directed to the appropriate field office within the comment period. A copy of your comments should also be mailed to Robert Hodanbosi, Division of Air Pollution Control, Ohio EPA, P.O. Box 1049, Columbus, OH, 43266-0149.

A Permit to Install may be issued in proposed or final form based on the draft action, any written public comments received within 30 days of the public notice, or record of a public meeting if one is held. You will be notified in writing of a scheduled public meeting. Upon issuance of a final Permit to Install a fee of **\$3000** will be due. Please do not submit any payment now.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469. If you have any questions about this draft permit, please contact the field office where you submitted your application, or Mike Ahern, Field Operations & Permit Section at (614) 644-3631.

Very truly yours,

Michael W. Ahern, Supervisor  
Field Operations and Permit Section  
Division of Air Pollution Control

CC: USEPA

NEDO

Eastgate Dev. & Trans. Study

NY

PA

**ASHTABULA  
COUNTY**

**PUBLIC NOTICE  
ISSUANCE OF DRAFT PERMIT TO INSTALL 02-19429 FOR AN AIR CONTAMINANT SOURCE FOR  
GLASTIC CORP**

On 8/3/2004 the Director of the Ohio Environmental Protection Agency issued a draft action of a Permit To Install an air contaminant source for **Glastic Corp**, located at **400 East Erie St, Jefferson, Ohio**.

Installation of the air contaminant source identified below may proceed upon final issuance of Permit To Install 02-19429:

**five compression molding presses.**

Comments concerning this draft action, or a request for a public meeting, must be sent in writing to the address identified below no later than thirty (30) days from the date this notice is published. All inquiries concerning this draft action may be directed to the contact identified below.

Dennis Bush, Ohio EPA, Northeast District Office, 2110 East Aurora Road, Twinsburg, OH 44087  
[(330)425-9171]



**Permit To Install  
Terms and  
Conditions**

**Issue Date: To be entered upon final issuance  
Effective Date: To be entered upon final issuance**

**DRAFT PERMIT TO INSTALL 02-19429**

Application Number: 02-19429  
APS Premise Number: 0204000293  
Permit Fee: **To be entered upon final issuance**  
Name of Facility: Glastic Corp  
Person to Contact: Robert Sedlatschek  
Address: 400 East Erie Ave  
Jefferson, OH 44047

Location of proposed air contaminant source(s) [emissions unit(s)]:  
**400 East Erie St  
Jefferson, Ohio**

Description of proposed emissions unit(s):  
**Five compression molding presses.**

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Glastic Corp

Facility ID: 0204000293

PTI Application: 02-19429

Issued: To be entered upon final issuance

Part I - GENERAL TERMS AND CONDITIONS

**A. State and Federally Enforceable Permit To Install General Terms and Conditions**

**1. Monitoring and Related Recordkeeping and Reporting Requirements**

- a. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:
  - i. The date, place (as defined in the permit), and time of sampling or measurements.
  - ii. The date(s) analyses were performed.
  - iii. The company or entity that performed the analyses.
  - iv. The analytical techniques or methods used.
  - v. The results of such analyses.
  - vi. The operating conditions existing at the time of sampling or measurement.
- b. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.
- c. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall submit required reports in the following manner:
  - i. Reports of any required monitoring and/or recordkeeping of federally enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
  - ii. Quarterly written reports of (i) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, excluding deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06, that have been detected by the testing, monitoring and recordkeeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures taken, shall be made to the appropriate Ohio EPA District Office or local air agency. The written reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. See B.9 below if no deviations occurred during the quarter.

Glastic Corp

Facility ID: 0204000293

PTI Application: 02-19429

Issued: To be entered upon final issuance

- iii. Written reports, which identify any deviations from the federally enforceable monitoring, recordkeeping, and reporting requirements contained in this permit shall be submitted to the appropriate Ohio EPA District Office or local air agency every six months, i.e., by January 31 and July 31 of each year for the previous six calendar months. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report, which states that no deviations occurred during that period.
- iv. Each written report shall be signed by a responsible official certifying that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.

## **2. Scheduled Maintenance/Malfunction Reporting**

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction, i.e., upset, of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. (The definition of an upset condition shall be the same as that used in OAC rule 3745-15-06(B)(1) for a malfunction.) The verbal and written reports shall be submitted pursuant to OAC rule 3745-15-06.

Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emission unit(s) that is (are) served by such control system(s).

## **3. Risk Management Plans**

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. 7401 et seq. ("Act"), the permittee shall comply with the requirement to register such a plan.

## **4. Title IV Provisions**

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

## **5. Severability Clause**

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition declared invalid.

**Glastic Corp**

**Facility ID: 0204000293**

**PTI Application: 02-19429**

**Issued: To be entered upon final issuance**

**6. General Requirements**

- a. The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and reissuance, or modification, or for denial of a permit renewal application.
- b. It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.
- c. This permit may be modified, reopened, revoked, or revoked and reissued, for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.
- d. This permit does not convey any property rights of any sort, or any exclusive privilege.
- e. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

**7. Fees**

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit To Install fees within 30 days after the issuance of this Permit To Install.

**8. Federal and State Enforceability**

Only those terms and conditions designated in this permit as federally enforceable, that are required under the Act, or any of its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA, the State, and citizens under the Act. All other terms and conditions of this permit shall not be federally enforceable and shall be enforceable under State law only.

**9. Compliance Requirements**

- a. Any document (including reports) required to be submitted and required by a federally

Glastic Corp

Facility ID: 0204000293

PTI Application: 02-19429

Issued: To be entered upon final issuance

applicable requirement in this permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.

- b. Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:
  - i. At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.
  - ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with ORC section 3704.08.
  - iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.
  - iv. As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.
- c. The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually, or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:
  - i. Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
  - ii. An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

## 10. Permit To Operate Application

- a. If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule

**Glastic Corp**

**Facility ID: 0204000293**

**PTI Application: 02-19429**

**Issued: To be entered upon final issuance**

3745-77-08(C)(3)(d).

- b. If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35, the source(s) identified in this Permit To Install is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the source(s) covered by this permit.

**11. Best Available Technology**

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

**12. Air Pollution Nuisance**

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

**Glastic Corp**

**Facility ID: 0204000293**

**PTI Application: 02-19429**

**Issued: To be entered upon final issuance**

**B. State Only Enforceable Permit To Install General Terms and Conditions**

**1. Compliance Requirements**

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

**2. Reporting Requirements**

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping of state-only enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from state-only required emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

**3. Permit Transfers**

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

**4. Termination of Permit To Install**

This permit to install shall terminate within eighteen months of the effective date of the permit to install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may

**Glastic Corp****Facility ID: 0204000293****PTI Application: 02-19429****Issued: To be entered upon final issuance**

be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

## **5. Construction of New Sources(s)**

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

## **6. Public Disclosure**

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

## **7. Applicability**

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

## **8. Construction Compliance Certification**

If applicable, the applicant shall provide Ohio EPA with a written certification (see enclosed form

Glastic Corp

Facility ID: 0204000293

PTI Application: 02-19429

**Issued: To be entered upon final issuance**

if applicable) that the facility has been constructed in accordance with the Permit To Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

**9. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations (See Section A of This Permit)**

If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.

**C. Permit To Install Summary of Allowable Emissions**

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)

**TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<b><u>Pollutant</u></b>	<b><u>Tons Per Year</u></b>
OC (processes)	43.8
OC (cleanup material)	0.5

12

**Glastic Corp**

**PTI Application: 02-19429**

**Issued: To be entered upon final issuance**

**Facility ID: 0204000293**

**Glastic Corp**  
**PTI Application: 02-10420**  
**Issued**

**Facility ID: 0204000293**

Emissions Unit ID: P047

**Part II - FACILITY SPECIFIC TERMS AND CONDITIONS**

**A. State and Federally Enforceable Permit To Install Facility Specific Terms and Conditions**

None

**B. State Only Enforceable Permit To Install Facility Specific Terms and Conditions**

None

**Issued: To be entered upon final issuance**

**Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. State and Federally Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P047 - Compression Mold Press, Stokes 50 Ton Press, Press 14 C	OAC rule 3745-31-05(A)(3)	Organic compound (OC) emissions shall not exceed 2.38 lbs/hr, 40.0 lbs/day, and 7.3 tpy from this emissions unit.  Cleanup materials: Total OC emissions shall not exceed 0.5 tons per year as combined OC emissions from emissions units P047, P048, P049, P050, P051 and P052. See Section A.2.a.
	OAC rule 3745-21-07(G)(2)	The requirements of this rule are less stringent than the requirements of OAC rule 3745-31-05(A)(3).
	40 CFR Part 63, Subpart WWWW Reinforced Plastic Composites Production	See Section A.I.2.b.

**2. Additional Terms and Conditions**

- 2.a The permittee shall not employ any cleanup material in this emissions unit which is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).
- 2.b This facility is subject to 40 CFR Part 63, Subpart WWWW, National Emission Standards for Hazardous Air Pollutants: Reinforced Plastic Composites Production. The permittee

**Issued: To be entered upon final issuance**

shall comply with all applicable requirements of 40 CFR Part 63, Subpart WWWW. The permittee shall also comply with all applicable requirements of 40 CFR Part 63, Subpart A (General Provisions) as identified in Table 15 of 40 CFR Part 63, Subpart WWWW. Compliance with all applicable requirements shall be achieved by the dates set forth in 40 CFR Part 63, Subpart WWWW and Subpart A.

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information for each day for this emissions unit:
  - a. the company identification for each mold compound employed;
  - b. the number of pounds of each mold compound employed;
  - c. the total OC emission rate for all mold compound, in pounds;
  - d. the actual number of hours that the emissions unit was in operation; and
  - e. the average hourly OC emission rate for all mold compound, i.e., (c) divided by (d), in pounds per hour (average).
2. The permittee shall collect and record the following information each week for the following emissions units P047, P048, P049, P050, P051 and P052:
  - a. the name and identification number of each cleanup material employed;
  - b. the number of gallons of each cleanup material employed, in gallons per week;
  - c. the OC content of each cleanup material employed, in pounds of OC per gallon; and
  - d. the total OC emission rate for all cleanup materials employed, i.e., the sum of (b) x (c), in pounds per week.

**IV. Reporting Requirements**

1. The permittee shall submit quarterly deviation (excursion) reports which include the following

information:

- a. an identification of each day during which the average hourly OC emissions from the mold compounds exceeded 2.38 pounds per hour, and the actual average hourly OC emissions for each such day;
  - b. an identification of each day during which the OC emissions from the mold compounds exceeded 40 pounds per day, and the actual OC emissions for each such day;
  - c. an identification of each calendar year during which the OC emissions from the mold compounds exceeded 7.3 tons per year and the actual OC emissions for each such year; and
  - d. an identification of each calendar year during which the OC emissions from the cleanup materials exceeded 0.5 tons per year and the actual OC emissions for each such year.
2. The permittee shall submit annual reports which specify the total OC emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

**V. Testing Requirements**

1. Compliance with the allowable emission limitations in section A.I.1. of these terms and conditions shall be determined in accordance with the following methods:

**1.a** Emission Limitation: 2.38 lbs OC/hr

Applicable Compliance Method: Compliance shall be demonstrated in accordance with the record keeping requirements specified in section A.III.1.e. If required, the permittee shall demonstrate compliance with this emission limitation through emission tests, performed in accordance with 40 CFR Part 60, Appendix A, Method 18, 25 or 25A, as appropriate.

**1.b** Emission Limitation: 40 lbs OC/day

Applicable Compliance Method: Compliance shall be determined in accordance with the following method:

$$EOC(\text{lbs/day}) = \text{Summation of } P_i \times E_{Fi}$$

where:

EOC(lbs/day) = the organic compound emissions from mold operations, in pounds per day.

P<sub>i</sub> = the production rate of mold compound i, in pounds per day.

E<sub>Fi</sub> = emission factor of mold compound i, in pound OC per pound of mold

**Issued: To be entered upon final issuance**

compound:

- i. 0.00134 lb OC (styrene) per pound of mold compound, as determined from a Society of Plastics Industry report, "Styrene Emissions during the Charging and Molding Cycle".
- ii. 0.000576 lb OC (vinyl toluene) per pound of mold compound, vinyl toluene emissions are based on the relative evaporative rate as compare to styrene. Vinyl toluene emissions were estimated to be 43% of styrene emissions.
- iii. 0.0005 lb OC (phenol) per pound of phenolic mold compound, as determined from manufacturer Plastic Engineering Corporation
- iv. 0.000025 lb OC (formaldehyde) per phenolic mold compound, as determined from manufacturer Durez

**1.c** Emission Limitation: 7.3 tpy OC

Applicable Compliance Method: To determine annual OC emissions from all molding compound materials, compliance shall be based on the sum of the daily OC emission rates from mold compound, as specified in section A.V.1.b. of this permit for the calendar year, divided by 2000 pounds/ton.

Any determination of OC content (percent by weight), solids content, or density of a material shall be based on the material as employed, including the addition of any monomer to the material. The permittee shall determine the composition of the material by formulation data supplied by the manufacturer or from data determined by an analysis of each material, as employed, by U.S. EPA Reference Method 24 as referenced in 40 CFR Part 60, Appendix A. If formulation data is employed, the Ohio EPA may require the permittee to have a Reference Method 24 analysis or an equivalent, alternative method (as approved by Ohio EPA) performed on the material(s).

**1.d** Emission Limitation: 0.5 tpy OC cleanup materials as combined OC emissions from emissions units P047, P048, P049, P050, P051 and P052.

Applicable Compliance Method: To determine annual OC emissions from all cleanup materials, compliance shall be based on the sum of the weekly OC emission rates from cleanup materials, as specified in section A.III.2.d. of this permit for the calendar year, divided by 2000 pounds/ton.

**VI. Miscellaneous Requirements**

18

**Glastic Corp**

**PTI Application: 02-10420**

**Issued**

**Facility ID: 0204000293**

Emissions Unit ID: P047

None

**Issued: To be entered upon final issuance**

**B. State Only Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P047 - Compression Mold Press, Stokes 50 Ton Press, Press 14 C		Compliance with the Air Toxic Policy as specified in sections B.III.1. to B.III.4.

**2. Additional Terms and Conditions**

2.a None

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
  - a. A description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
  - b. Documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
  - c. Where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.
2. The permit-to-install for this emissions unit was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the

**Issued: To be entered upon final issuance**

permit-to-install application. Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit-to-install application and the SCREEN3 model. The predicted 1-hour maximum ground-level concentration from the use of the dispersion models was compared to the maximum acceptable ground-level concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

<b>AIR TOXIC ANALYSIS</b>					
<b>Emission Unit(s) ID</b>	<b>Pollutant</b>	<b>Threshold Limit Value (TLV) (<math>\mu\text{g}/\text{m}^3</math>)</b>	<b>Maximum Hourly Emission Rate (lbs/hr)</b>	<b>Predicted 1 Hour Maximum Ground Level Concentration (<math>\mu\text{g}/\text{m}^3</math>)</b>	<b>Maximum Acceptable Ground Level Concentration (MAGLC), (<math>\mu\text{g}/\text{m}^3</math>)</b>
P047 through P052	Styrene	85,202	10.0	1,128	2,028
P047 through P052	Vinyl Toluene	241,677	4.3	485	5,754
P047 through P051	Ammonia	17,413	0.65	73	415
P047 through P051	Phenol	19,245	0.94	106	458

3. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
  - a. Changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower threshold limit value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV previously modeled;
  - b. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

**Glastic Corp**

**PTI Application: 02-10420**

**Issued**

**Facility ID: 0204000293**

Emissions Unit ID: P047

- c. Physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
4. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit-to-install will not be required. If the

**Glasti**

**PTI A**

Emissions Unit ID: P047

**Issued: To be entered upon final issuance**

change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit-to-install prior to the change.

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P048 - Compression Mold Press, Martin 400 Ton Press, Press 29 C	OAC rule 3745-31-05(A)(3)	Organic compound (OC) emissions shall not exceed 2.38 lbs/hr, 40.0 lbs/day, and 7.3 tpy from this emissions unit.
	OAC rule 3745-21-07(G)(2)	Cleanup materials: Total OC emissions shall not exceed 0.5 tons per year as combined OC emissions from emissions units P047, P048, P049, P050, P051 and P052. See Section A.2.a.
	40 CFR Part 63, Subpart WWWW Reinforced Plastic Composites Production	The requirements of this rule are less stringent than the requirements of OAC rule 3745-31-05(A)(3).  See Section A.I.2.b.

2. Additional Terms and Conditions

- 2.a The permittee shall not employ any cleanup material in this emissions unit which is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).
- 2.b This facility is subject to 40 CFR Part 63, Subpart WWWW, National Emission Standards for Hazardous Air Pollutants: Reinforced Plastic Composites Production. The permittee

**Issued: To be entered upon final issuance**

shall comply with all applicable requirements of 40 CFR Part 63, Subpart WWWW. The permittee shall also comply with all applicable requirements of 40 CFR Part 63, Subpart A (General Provisions) as identified in Table 15 of 40 CFR Part 63, Subpart WWWW. Compliance with all applicable requirements shall be achieved by the dates set forth in 40 CFR Part 63, Subpart WWWW and Subpart A.

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information for each day for this emissions unit:
  - a. the company identification for each mold compound employed;
  - b. the number of pounds of each mold compound employed;
  - c. the total OC emission rate for all mold compound, in pounds;
  - d. the actual number of hours that the emissions unit was in operation; and
  - e. the average hourly OC emission rate for all mold compound, i.e., (c) divided by (d), in pounds per hour (average).
2. The permittee shall collect and record the following information each week for the following emissions units P047, P048, P049, P050, P051 and P052:
  - a. the name and identification number of each cleanup material employed;
  - b. the number of gallons of each cleanup material employed, in gallons per week;
  - c. the OC content of each cleanup material employed, in pounds of OC per gallon; and
  - d. the total OC emission rate for all cleanup materials employed, i.e., the sum of (b) x (c), in pounds per week.

**IV. Reporting Requirements**

1. The permittee shall submit quarterly deviation (excursion) reports which include the following

information:

- a. an identification of each day during which the average hourly OC emissions from the mold compounds exceeded 2.38 pounds per hour, and the actual average hourly OC emissions for each such day;
  - b. an identification of each day during which the OC emissions from the mold compounds exceeded 40 pounds per day, and the actual OC emissions for each such day;
  - c. an identification of each calendar year during which the OC emissions from the mold compounds exceeded 7.3 tons per year and the actual OC emissions for each such year; and
  - d. an identification of each calendar year during which the OC emissions from the cleanup materials exceeded 0.5 tons per year and the actual OC emissions for each such year.
2. The permittee shall submit annual reports which specify the total OC emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

## **V. Testing Requirements**

1. Compliance with the allowable emission limitations in section A.I.1. of these terms and conditions shall be determined in accordance with the following methods:

### **1.a Emission Limitation: 2.38 lbs OC/hr**

Applicable Compliance Method: Compliance shall be demonstrated in accordance with the record keeping requirements specified in section A.III.1.e. If required, the permittee shall demonstrate compliance with this emission limitation through emission tests, performed in accordance with 40 CFR Part 60, Appendix A, Method 18, 25 or 25A, as appropriate.

### **1.b Emission Limitation: 40 lbs OC/day**

Applicable Compliance Method: Compliance shall be determined in accordance with the following method:

$$\text{EOC}(\text{lbs/day}) = \text{Summation of } P_i \times E_{Fi}$$

where:

EOC(lbs/day) = the organic compound emissions from mold operations, in pounds per day.

$P_i$  = the production rate of mold compound  $i$ , in pounds per day.

$E_{Fi}$  = emission factor of mold compound  $i$ , in pound OC per pound of mold

**Issued: To be entered upon final issuance**  
compound:

- i. 0.00134 lb OC (styrene) per pound of mold compound, as determined from a Society of Plastics Industry report, "Styrene Emissions during the Charging and Molding Cycle".
- ii. 0.000576 lb OC (vinyl toluene) per pound of mold compound, vinyl toluene emissions are based on the relative evaporative rate as compare to styrene. Vinyl toluene emissions were estimated to be 43% of styrene emissions.
- iii. 0.0005 lb OC (phenol) per pound of phenolic mold compound, as determined from manufacturer Plastic Engineering Corporation
- iv. 0.000025 lb OC (formaldehyde) per phenolic mold compound, as determined from manufacturer Durez

**Issued: To be entered upon final issuance****1.c** Emission Limitation: 7.3 tpy OC

Applicable Compliance Method: To determine annual OC emissions from all molding compound materials, compliance shall be based on the sum of the daily OC emission rates from mold compounds, as specified in section A.V.1.b. of this permit for the calendar year, divided by 2000 pounds/ton.

Any determination of OC content (percent by weight), solids content, or density of a material shall be based on the material as employed, including the addition of any monomer to the material. The permittee shall determine the composition of the material by formulation data supplied by the manufacturer or from data determined by an analysis of each material, as employed, by U.S. EPA Reference Method 24 as referenced in 40 CFR Part 60, Appendix A. If formulation data is employed, the Ohio EPA may require the permittee to have a Reference Method 24 analysis or an equivalent, alternative method (as approved by Ohio EPA) performed on the material(s).

**1.d** Emission Limitation: 0.5 tpy OC cleanup materials as combined OC emissions from emissions units P047, P048, P049, P050, P051 and P052.

Applicable Compliance Method: To determine annual OC emissions from all cleanup materials, compliance shall be based on the sum of the weekly OC emission rates from cleanup materials, as specified in section A.III.2.d. of this permit for the calendar year, divided by 2000 pounds/ton.

**VI. Miscellaneous Requirements**

None

## B. State Only Enforceable Section

### I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P048 - Compression Mold Press, Martin 400 Ton Press, Press 29 C		Compliance with the Air Toxic Policy as specified in sections B.III.1. to B.III.4.

#### 2. Additional Terms and Conditions

##### 2.a None

### II. Operational Restrictions

None

### III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":
  - a. A description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
  - b. Documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
  - c. Where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.
2. The permit-to-install for this emissions unit was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit-to-install application. Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit-to-install application and the SCREEN3 model. The predicted 1-hour maximum ground-level concentration from the use of the dispersion models was compared to the maximum acceptable ground-level concentration (MAGLC). The following summarizes the

**Issued: To be entered upon final issuance**

results of the modeling for the "worst case" pollutant(s):

<b>AIR TOXIC ANALYSIS</b>					
<b>Emission Unit(s) ID</b>	<b>Pollutant</b>	<b>Threshold Limit Value (TLV) (<math>\mu\text{g}/\text{m}^3</math>)</b>	<b>Maximum Hourly Emission Rate (lbs/hr)</b>	<b>Predicted 1 Hour Maximum Ground Level Concentration (<math>\mu\text{g}/\text{m}^3</math>)</b>	<b>Maximum Acceptable Ground Level Concentration (MAGLC), (<math>\mu\text{g}/\text{m}^3</math>)</b>
P047 through P052	Styrene	85,202	10.0	1,128	2,028
P047 through P052	Vinyl Toluene	241,677	4.3	485	5,754
P047 through P051	Ammonia	17,413	0.65	73	415
P047 through P051	Phenol	19,245	0.94	106	458

3. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
  - a. Changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower threshold limit value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV previously modeled;
  - b. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
  - c. Physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
4. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes,

**Glastic Corp**

**PTI Application: 02-10420**

**Issued**

**Facility ID: 0204000293**

Emissions Unit ID: P048

Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit-to-install will not be required.  
If the

**Glasti**

**PTI A**

Emissions Unit ID: P048

**Issued: To be entered upon final issuance**

change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit-to-install prior to the change.

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None

Issued: To be entered upon final issuance

**Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. State and Federally Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P049 - Compression Mold Press, Hull 150 Ton Press, Press 7 C	OAC rule 3745-31-05(A)(3)	Organic compound (OC) emissions shall not exceed 2.38 lbs/hr, 40.0 lbs/day, and 7.3 tpy from this emissions unit.  Cleanup materials: Total OC emissions shall not exceed 0.5 tons per year as combined OC emissions from emissions units P047, P048, P049, P050, P051 and P052. See Section A.2.a.
	OAC rule 3745-21-07(G)(2)	The requirements of this rule are less stringent than the requirements of OAC rule 3745-31-05(A)(3).
	40 CFR Part 63, Subpart WWWW Reinforced Plastic Composites Production	See Section A.I.2.b.

**2. Additional Terms and Conditions**

- 2.a** The permittee shall not employ any cleanup material in this emissions unit which is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).
- 2.b** This facility is subject to 40 CFR Part 63, Subpart WWWW, National Emission Standards for Hazardous Air Pollutants: Reinforced Plastic Composites Production. The permittee

**Issued: To be entered upon final issuance**

shall comply with all applicable requirements of 40 CFR Part 63, Subpart WWWW. The permittee shall also comply with all applicable requirements of 40 CFR Part 63, Subpart A (General Provisions) as identified in Table 15 of 40 CFR Part 63, Subpart WWWW. Compliance with all applicable requirements shall be achieved by the dates set forth in 40 CFR Part 63, Subpart WWWW and Subpart A.

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information for each day for this emissions unit:
  - a. the company identification for each mold compound employed;
  - b. the number of pounds of each mold compound employed;
  - c. the total OC emission rate for all mold compound, in pounds;
  - d. the actual number of hours that the emissions unit was in operation; and
  - e. the average hourly OC emission rate for all mold compound, i.e., (c) divided by (d), in pounds per hour (average).
2. The permittee shall collect and record the following information each week for the following emissions units P047, P048, P049, P050, P051 and P052:
  - a. the name and identification number of each cleanup material employed;
  - b. the number of gallons of each cleanup material employed, in gallons per week;
  - c. the OC content of each cleanup material employed, in pounds of OC per gallon; and
  - d. the total OC emission rate for all cleanup materials employed, i.e., the sum of (b) x (c), in pounds per week.

**IV. Reporting Requirements**

1. The permittee shall submit quarterly deviation (excursion) reports which include the following

information:

- a. an identification of each day during which the average hourly OC emissions from the mold compounds exceeded 2.38 pounds per hour, and the actual average hourly OC emissions for each such day;
  - b. an identification of each day during which the OC emissions from the mold compounds exceeded 40 pounds per day, and the actual OC emissions for each such day;
  - c. an identification of each calendar year during which the OC emissions from the mold compounds exceeded 7.3 tons per year and the actual OC emissions for each such year; and
  - d. an identification of each calendar year during which the OC emissions from the cleanup materials exceeded 0.5 tons per year and the actual OC emissions for each such year.
2. The permittee shall submit annual reports which specify the total OC emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

## **V. Testing Requirements**

1. Compliance with the allowable emission limitations in section A.I.1. of these terms and conditions shall be determined in accordance with the following methods:

- 1.a Emission Limitation: 2.38 lbs OC/hr

Applicable Compliance Method: Compliance shall be demonstrated in accordance with the record keeping requirements specified in section A.III.1.e. If required, the permittee shall demonstrate compliance with this emission limitation through emission tests, performed in accordance with 40 CFR Part 60, Appendix A, Method 18, 25 or 25A, as appropriate.

- 1.b Emission Limitation: 40 lbs OC/day

Applicable Compliance Method: Compliance shall be determined in accordance with the following method:

$$EOC(\text{lbs/day}) = \text{Summation of } P_i \times E_{Fi}$$

where:

EOC(lbs/day) = the organic compound emissions from mold operations, in pounds per day.

$P_i$  = the production rate of mold compound  $i$ , in pounds per day.

$E_{Fi}$  = emission factor of mold compound  $i$ , in pound OC per pound of mold

**Issued: To be entered upon final issuance**  
compound:

- i. 0.00134 lb OC (styrene) per pound of mold compound, as determined from a Society of Plastics Industry report, "Styrene Emissions during the Charging and Molding Cycle".
- ii. 0.000576 lb OC (vinyl toluene) per pound of mold compound, vinyl toluene emissions are based on the relative evaporative rate as compare to styrene. Vinyl toluene emissions were estimated to be 43% of styrene emissions.
- iii. 0.0005 lb OC (phenol) per pound of phenolic mold compound, as determined from manufacturer Plastic Engineering Corporation
- iv. 0.000025 lb OC (formaldehyde) per phenolic mold compound, as determined from manufacturer Durez

**Issued: To be entered upon final issuance**

- 1.c Emission Limitation: 7.3 tpy OC

Applicable Compliance Method: To determine annual OC emissions from all molding compound materials, compliance shall be based on the sum of the daily OC emission rates from mold compound, as specified in section A.V.1.b. of this permit for the calendar year, divided by 2000 pounds/ton.

Any determination of OC content (percent by weight), solids content, or density of a material shall be based on the material as employed, including the addition of any monomer to the material. The permittee shall determine the composition of the material by formulation data supplied by the manufacturer or from data determined by an analysis of each material, as employed, by U.S. EPA Reference Method 24 as referenced in 40 CFR Part 60, Appendix A. If formulation data is employed, the Ohio EPA may require the permittee to have a Reference Method 24 analysis or an equivalent, alternative method (as approved by Ohio EPA) performed on the material(s).

- 1.d Emission Limitation: 0.5 tpy OC cleanup materials as combined OC emissions from emissions units P047, P048, P049, P050, P051 and P052.

Applicable Compliance Method: To determine annual OC emissions from all cleanup materials, compliance shall be based on the sum of the weekly OC emission rates from cleanup materials, as specified in section A.III.2.d. of this permit for the calendar year, divided by 2000 pounds/ton.

**VI. Miscellaneous Requirements**

None

## B. State Only Enforceable Section

### I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P049 - Compression Mold Press, Hull 150 Ton Press, Press 7 C		Compliance with the Air Toxic Policy as specified in sections B.III.1. to B.III.4.

#### 2. Additional Terms and Conditions

2.a None

### II. Operational Restrictions

None

### III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":
  - a. A description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
  - b. Documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
  - c. Where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.
2. The permit-to-install for this emissions unit was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit-to-install application. Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit-to-install application and the SCREEN3 model. The predicted 1-hour maximum ground-level concentration from the use of the dispersion models was compared to the maximum acceptable ground-level concentration (MAGLC). The following summarizes the

**Issued: To be entered upon final issuance**

results of the modeling for the "worst case" pollutant(s):

<b>AIR TOXIC ANALYSIS</b>					
<b>Emission Unit(s) ID</b>	<b>Pollutant</b>	<b>Threshold Limit Value (TLV) (<math>\mu\text{g}/\text{m}^3</math>)</b>	<b>Maximum Hourly Emission Rate (lbs/hr)</b>	<b>Predicted 1 Hour Maximum Ground Level Concentration (<math>\mu\text{g}/\text{m}^3</math>)</b>	<b>Maximum Acceptable Ground Level Concentration (MAGLC), (<math>\mu\text{g}/\text{m}^3</math>)</b>
P047 through P052	Styrene	85,202	10.0	1,128	2,028
P047 through P052	Vinyl Toluene	241,677	4.3	485	5,754
P047 through P051	Ammonia	17,413	0.65	73	415
P047 through P051	Phenol	19,245	0.93	105	458

3. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
  - a. Changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower threshold limit value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV previously modeled;
  - b. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
  - c. Physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
4. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes,

**Glastic Corp**

**PTI Application: 02-10420**

**Issued**

**Facility ID: 0204000293**

Emissions Unit ID: P049

Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit-to-install will not be required.

If the

**Glasti**

**PTI A**

Emissions Unit ID: P049

**Issued: To be entered upon final issuance**

change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit-to-install prior to the change.

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P050 - Compression Mold Press, Stokes 200 Ton Press, Press 19 C	OAC rule 3745-31-05(A)(3)	Organic compound (OC) emissions shall not exceed 2.38 lbs/hr, 40.0 lbs/day, and 7.3 tpy from this emissions unit.  Cleanup materials: Total OC emissions shall not exceed 0.5 tons per year as combined OC emissions from emissions units P047, P048, P049, P050, P051 and P052. See Section A.2.a.
	OAC rule 3745-21-07(G)(2)	The requirements of this rule are less stringent than the requirements of OAC rule 3745-31-05(A)(3).
	40 CFR Part 63, Subpart WWWW Reinforced Plastic Composites Production	See Section A.I.2.b.

2. Additional Terms and Conditions

- 2.a The permittee shall not employ any cleanup material in this emissions unit which is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).
- 2.b This facility is subject to 40 CFR Part 63, Subpart WWWW, National Emission Standards for Hazardous Air Pollutants: Reinforced Plastic Composites Production. The permittee

**Issued: To be entered upon final issuance**

shall comply with all applicable requirements of 40 CFR Part 63, Subpart WWWW. The permittee shall also comply with all applicable requirements of 40 CFR Part 63, Subpart A (General Provisions) as identified in Table 15 of 40 CFR Part 63, Subpart WWWW. Compliance with all applicable requirements shall be achieved by the dates set forth in 40 CFR Part 63, Subpart WWWW and Subpart A.

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information for each day for this emissions unit:
  - a. the company identification for each mold compound employed;
  - b. the number of pounds of each mold compound employed;
  - c. the total OC emission rate for all mold compound, in pounds;
  - d. the actual number of hours that the emissions unit was in operation; and
  - e. the average hourly OC emission rate for all mold compound, i.e., (c) divided by (d), in pounds per hour (average).
2. The permittee shall collect and record the following information each week for the following emissions units P047, P048, P049, P050, P051 and P052:
  - a. the name and identification number of each cleanup material employed;
  - b. the number of gallons of each cleanup material employed, in gallons per week;
  - c. the OC content of each cleanup material employed, in pounds of OC per gallon; and
  - d. the total OC emission rate for all cleanup materials employed, i.e., the sum of (b) x (c), in pounds per week.

**IV. Reporting Requirements**

1. The permittee shall submit quarterly deviation (excursion) reports which include the following

**Issued: To be entered upon final issuance**

information:

- a. an identification of each day during which the average hourly OC emissions from the mold compounds exceeded 2.38 pounds per hour, and the actual average hourly OC emissions for each such day;
  - b. an identification of each day during which the OC emissions from the mold compounds exceeded 40 pounds per day, and the actual OC emissions for each such day;
  - c. an identification of each calendar year during which the OC emissions from the mold compounds exceeded 7.3 tons per year and the actual OC emissions for each such year; and
  - d. an identification of each calendar year during which the OC emissions from the cleanup materials exceeded 0.5 tons per year and the actual OC emissions for each such year.
2. The permittee shall submit annual reports which specify the total OC emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

**V. Testing Requirements**

1. Compliance with the allowable emission limitations in section A.I.1. of these terms and conditions shall be determined in accordance with the following methods:

- 1.a Emission Limitation: 2.38 lbs OC/hr

Applicable Compliance Method: Compliance shall be demonstrated in accordance with the record keeping requirements specified in section A.III.1.e. If required, the permittee shall demonstrate compliance with this emission limitation through emission tests, performed in accordance with 40 CFR Part 60, Appendix A, Method 18, 25 or 25A, as appropriate.

- 1.b Emission Limitation: 40 lbs OC/day

Applicable Compliance Method: Compliance shall be determined in accordance with the following method:

$$EOC(\text{lbs/day}) = \text{Summation of } P_i \times EFi.$$

where:

Emissions Unit ID: P050

EOC(lbs/day) = the organic compound emissions from mold operations, in pounds per day.

P<sub>i</sub> = the production rate of mold compound i, in pounds per day.

E<sub>F<sub>i</sub></sub> = emission factor of mold compound i, in pound OC per pound of mold compound:

- i. 0.00134 lb OC (styrene) per pound of mold compound, as determined from a Society of Plastics Industry report, "Styrene Emissions during the Charging and Molding Cycle".
- ii. 0.000576 lb OC (vinyl toluene) per pound of mold compound, vinyl toluene emissions are based on the relative evaporative rate as compare to styrene. Vinyl toluene emissions were estimated to be 43% of styrene emissions.
- iii. 0.0005 lb OC (phenol) per pound of phenolic mold compound, as determined from manufacturer Plastic Engineering Corporation
- iv. 0.000025 lb OC (formaldehyde) per phenolic mold compound, as determined from manufacturer Durez

**Issued: To be entered upon final issuance**

- 1.c Emission Limitation: 7.3 tpy OC

Applicable Compliance Method: To determine annual OC emissions from all molding compound materials, compliance shall be based on the sum of the daily OC emission rates from mold compound, as specified in section A.V.1.b. of this permit for the calendar year, divided by 2000 pounds/ton.

Any determination of OC content (percent by weight), solids content, or density of a material shall be based on the material as employed, including the addition of any monomer to the material. The permittee shall determine the composition of the material by formulation data supplied by the manufacturer or from data determined by an analysis of each material, as employed, by U.S. EPA Reference Method 24 as referenced in 40 CFR Part 60, Appendix A. If formulation data is employed, the Ohio EPA may require the permittee to have a Reference Method 24 analysis or an equivalent, alternative method (as approved by Ohio EPA) performed on the material(s).

- 1.d Emission Limitation: 0.5 tpy OC cleanup materials as combined OC emissions from emissions units P047, P048, P049, P050, P051 and P052.

Applicable Compliance Method: To determine annual OC emissions from all cleanup materials, compliance shall be based on the sum of the weekly OC emission rates from cleanup materials, as specified in section A.III.2.d. of this permit for the calendar year, divided by 2000 pounds/ton.

**VI. Miscellaneous Requirements**

None

**Issued: To be entered upon final issuance**

**B. State Only Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P050 - Compression Mold Press, Stokes 200 Ton Press, Press 19 C		Compliance with the Air Toxic Policy as specified in sections B.III.1. to B.III.4.

**2. Additional Terms and Conditions**

2.a None

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

- 1. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
  - a. A description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
  - b. Documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
  - c. Where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.
- 2. The permit-to-install for this emissions unit was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the

Emissions Unit ID: P050

permit-to-install application. Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit-to-install application and the SCREEN3 model. The predicted 1-hour maximum ground-level concentration from the use of the dispersion models was compared to the maximum acceptable ground-level concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

AIR TOXIC ANALYSIS					
Emission Unit(s) ID	Pollutant	Threshold Limit Value (TLV) ( $\mu\text{g}/\text{m}^3$ )	Maximum Hourly Emission Rate (lbs/hr)	Predicted 1 Hour Maximum Ground Level Concentration ( $\mu\text{g}/\text{m}^3$ )	Maximum Acceptable Ground Level Concentration (MAGLC), ( $\mu\text{g}/\text{m}^3$ )
P047 through P052	Styrene	85,202	10.0	1,128	2,028
P047 through P052	Vinyl Toluene	241,677	4.3	485	5,754
P047 through P051	Ammonia	17,413	0.65	73	415
P047 through P051	Phenol	19,245	0.93	105	458

3. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
  - a. Changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower threshold limit value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV previously modeled;
  - b. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
  - c. Physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
4. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes,

**Glasti**

**PTI A**

Emissions Unit ID: P050

**Issued: To be entered upon final issuance**

Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit-to-install will not be required.  
If the

**Glasti**

**PTI A**

Emissions Unit ID: P050

**Issued: To be entered upon final issuance**

change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit-to-install prior to the change.

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None

### Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

#### A. State and Federally Enforceable Section

##### I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P051 - Compression Mold Press, Martin 400 Ton Press, Press 40 C	OAC rule 3745-31-05(A)(3)	Organic compound (OC) emissions shall not exceed 2.38 lbs/hr, 40.0 lbs/day, and 7.3 tpy from this emissions unit.
	OAC rule 3745-21-07(G)(2)	Cleanup materials: Total OC emissions shall not exceed 0.5 tons per year as combined OC emissions from emissions units P047, P048, P049, P050, P051 and P052. See Section A.2.a.
	40 CFR Part 63, Subpart WWWW Reinforced Plastic Composites Production	The requirements of this rule are less stringent than the requirements of OAC rule 3745-31-05(A)(3).
		See Section A.I.2.b.

##### 2. Additional Terms and Conditions

- 2.a The permittee shall not employ any cleanup material in this emissions unit which is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).
- 2.b This facility is subject to 40 CFR Part 63, Subpart WWWW, National Emission Standards for Hazardous Air Pollutants: Reinforced Plastic Composites Production. The permittee shall comply with all applicable requirements of 40 CFR Part 63, Subpart WWWW. The permittee shall also comply with all applicable requirements of 40 CFR Part 63, Subpart A (General Provisions) as identified in Table 15 of 40 CFR Part 63, Subpart WWWW. Compliance with all applicable requirements shall be achieved by the dates set forth in 40 CFR Part 63, Subpart WWWW and Subpart A.

**Issued: To be entered upon final issuance**

## **II. Operational Restrictions**

None

## **III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information for each day for this emissions unit:
  - a. the company identification for each mold compound employed;
  - b. the number of pounds of each mold compound employed;
  - c. the total OC emission rate for all mold compound, in pounds;
  - d. the actual number of hours that the emissions unit was in operation; and
  - e. the average hourly OC emission rate for all mold compound, i.e., (c) divided by (d), in pounds per hour (average).
2. The permittee shall collect and record the following information each week for the following emissions units P047, P048, P049, P050, P051 and P052:
  - a. the name and identification number of each cleanup material employed;
  - b. the number of gallons of each cleanup material employed, in gallons per week;
  - c. the OC content of each cleanup material employed, in pounds of OC per gallon; and
  - d. the total OC emission rate for all cleanup materials employed, i.e., the sum of (b) x (c), in pounds per week.

## **IV. Reporting Requirements**

1. The permittee shall submit quarterly deviation (excursion) reports which include the following information:
  - a. an identification of each day during which the average hourly OC emissions from the mold compounds exceeded 2.38 pounds per hour, and the actual average hourly OC emissions for

**Issued: To be entered upon final issuance**

- each such day;
- b. an identification of each day during which the OC emissions from the mold compounds exceeded 40 pounds per day, and the actual OC emissions for each such day;
  - c. an identification of each calendar year during which the OC emissions from the mold compounds exceeded 7.3 tons per year and the actual OC emissions for each such year; and
  - d. an identification of each calendar year during which the OC emissions from the cleanup materials exceeded 0.5 tons per year and the actual OC emissions for each such year.
2. The permittee shall submit annual reports which specify the total OC emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

**V. Testing Requirements**

1. Compliance with the allowable emission limitations in section A.I.1. of these terms and conditions shall be determined in accordance with the following methods:
  - 1.a Emission Limitation: 2.38 lbs OC/hr

Applicable Compliance Method: Compliance shall be demonstrated in accordance with the record keeping requirements specified in section A.III.1.e. If required, the permittee shall demonstrate compliance with this emission limitation through emission tests, performed in accordance with 40 CFR Part 60, Appendix A, Method 18, 25 or 25A, as appropriate.

- 1.b Emission Limitation: 40 lbs OC/day

Applicable Compliance Method: Compliance shall be determined in accordance with the following method:

$$\text{EOC}(\text{lbs/day}) = \text{Summation of } P_i \times \text{EF}_i$$

where:

$\text{EOC}(\text{lbs/day})$  = the organic compound emissions from mold operations, in pounds per day.

$P_i$  = the production rate of mold compound  $i$ , in pounds per day.

$\text{EF}_i$  = emission factor of mold compound  $i$ , in pound OC per pound of mold

compound:

- i. 0.00134 lb OC (styrene) per pound of mold compound, as determined from a Society of Plastics Industry report, "Styrene Emissions during the Charging and Molding Cycle".
- ii. 0.000576 lb OC (vinyl toluene) per pound of mold compound, vinyl toluene emissions are based on the relative evaporative rate as compare to styrene. Vinyl toluene emissions were estimated to be 43% of styrene emissions.
- iii. 0.0005 lb OC (phenol) per pound of phenolic mold compound, as determined from manufacturer Plastic Engineering Corporation
- iv. 0.000025 lb OC (formaldehyde) per phenolic mold compound, as determined from manufacturer Durez

**Issued: To be entered upon final issuance**

- 1.c Emission Limitation: 7.3 tpy OC

Applicable Compliance Method: To determine annual OC emissions from all molding compound materials, compliance shall be based on the sum of the daily OC emission rates from mold compound, as specified in section A.V.1.b. of this permit for the calendar year, divided by 2000 pounds/ton.

Any determination of OC content (percent by weight), solids content, or density of a material shall be based on the material as employed, including the addition of any monomer to the material. The permittee shall determine the composition of the material by formulation data supplied by the manufacturer or from data determined by an analysis of each material, as employed, by U.S. EPA Reference Method 24 as referenced in 40 CFR Part 60, Appendix A. If formulation data is employed, the Ohio EPA may require the permittee to have a Reference Method 24 analysis or an equivalent, alternative method (as approved by Ohio EPA) performed on the material(s).

- 1.d Emission Limitation: 0.5 tpy OC cleanup materials as combined OC emissions from emissions units P047, P048, P049, P050, P051 and P052.

Applicable Compliance Method: To determine annual OC emissions from all cleanup materials, compliance shall be based on the sum of the weekly OC emission rates from cleanup materials, as specified in section A.III.2.d. of this permit for the calendar year, divided by 2000 pounds/ton.

**VI. Miscellaneous Requirements**

None

**Issued: To be entered upon final issuance**

**B. State Only Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P051 - Compression Mold Press, Martin 400 Ton Press, Press 40 C		Compliance with the Air Toxic Policy as specified in sections B.III.1. to B.III.4.

**2. Additional Terms and Conditions**

2.a None

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
  - a. A description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
  - b. Documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
  - c. Where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.
2. The permit-to-install for this emissions unit was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the

Emissions Unit ID: P051

permit-to-install application. Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit-to-install application and the SCREEN3 model. The predicted 1-hour maximum ground-level concentration from the use of the dispersion models was compared to the maximum acceptable ground-level concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

AIR TOXIC ANALYSIS					
Emission Unit(s) ID	Pollutant	Threshold Limit Value (TLV) ( $\mu\text{g}/\text{m}^3$ )	Maximum Hourly Emission Rate (lbs/hr)	Predicted 1 Hour Maximum Ground Level Concentration ( $\mu\text{g}/\text{m}^3$ )	Maximum Acceptable Ground Level Concentration (MAGLC), ( $\mu\text{g}/\text{m}^3$ )
P047 through P052	Styrene	85,202	10.0	1,128	2,028
P047 through P052	Vinyl Toluene	241,677	4.3	485	5,754
P047 through P051	Ammonia	17,413	0.65	73	415
P047 through P051	Phenol	19,245	0.94	105	458

3. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
  - a. Changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower threshold limit value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV previously modeled;
  - b. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
  - c. Physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
4. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes,

57

**Glasti**

**PTI A**

Emissions Unit ID: P051

**Issued: To be entered upon final issuance**

Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit-to-install will not be required.  
If the

**Glasti**

**PTI A**

Emissions Unit ID: P051

**Issued: To be entered upon final issuance**

change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit-to-install prior to the change.

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None

**Issued: To be entered upon final issuance**

**Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. State and Federally Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P052 - Compression Mold Press, Wabash 200 Ton Press, Press 23 C	OAC rule 3745-31-05(A)(3)	Organic compound (OC) emissions shall not exceed 2.38 lbs/hr, 40.0 lbs/day, and 7.3 tpy from this emissions unit.  Cleanup materials: Total OC emissions shall not exceed 0.5 tons per year as combined OC emissions from emissions units P047, P048, P049, P050, P051 and P052. See Section A.2.a.
	OAC rule 3745-21-07(G)(2)	The requirements of this rule are less stringent than the requirements of OAC rule 3745-31-05(A)(3).
	40 CFR Part 63, Subpart WWWW Reinforced Plastic Composites Production	See Section A.I.2.b.

**2. Additional Terms and Conditions**

- 2.a** The permittee shall not employ any cleanup material in this emissions unit which is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).
- 2.b** This facility is subject to 40 CFR Part 63, Subpart WWWW, National Emission Standards for Hazardous Air Pollutants: Reinforced Plastic Composites Production. The permittee

Emissions Unit ID: P052

shall comply with all applicable requirements of 40 CFR Part 63, Subpart WWWW. The permittee shall also comply with all applicable requirements of 40 CFR Part 63, Subpart A (General Provisions) as identified in Table 15 of 40 CFR Part 63, Subpart WWWW. Compliance with all applicable requirements shall be achieved by the dates set forth in 40 CFR Part 63, Subpart WWWW and Subpart A.

## **II. Operational Restrictions**

None

## **III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information for each day for this emissions unit:
  - a. the company identification for each mold compound employed;
  - b. the number of pounds of each mold compound employed;
  - c. the total OC emission rate for all mold compound, in pounds;
  - d. the actual number of hours that the emissions unit was in operation; and
  - e. the average hourly OC emission rate for all mold compound, i.e., (c) divided by (d), in pounds per hour (average).
2. The permittee shall collect and record the following information each week for the following emissions units P047, P048, P049, P050, P051 and P052:
  - a. the name and identification number of each cleanup material employed;
  - b. the number of gallons of each cleanup material employed, in gallons per week;
  - c. the OC content of each cleanup material employed, in pounds of OC per gallon; and
  - d. the total OC emission rate for all cleanup materials employed, i.e., the sum of (b) x (c), in pounds per week.

## **IV. Reporting Requirements**

1. The permittee shall submit quarterly deviation (excursion) reports which include the following information:
  - a. an identification of each day during which the average hourly OC emissions from the mold compounds exceeded 2.38 pounds per hour, and the actual average hourly OC emissions for

**Issued: To be entered upon final issuance**

- each such day;
- b. an identification of each day during which the OC emissions from the mold compounds exceeded 40 pounds per day, and the actual OC emissions for each such day;
  - c. an identification of each calendar year during which the OC emissions from the mold compounds exceeded 7.3 tons per year and the actual OC emissions for each such year; and
  - d. an identification of each calendar year during which the OC emissions from the cleanup materials exceeded 0.5 tons per year and the actual OC emissions for each such year.
2. The permittee shall submit annual reports which specify the total OC emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

**V. Testing Requirements**

1. Compliance with the allowable emission limitations in section A.I.1. of these terms and conditions shall be determined in accordance with the following methods:

- 1.a Emission Limitation: 2.38 lbs OC/hr

Applicable Compliance Method: Compliance shall be demonstrated in accordance with the record keeping requirements specified in section A.III.1.e. If required, the permittee shall demonstrate compliance with this emission limitation through emission tests, performed in accordance with 40 CFR Part 60, Appendix A, Method 18, 25 or 25A, as appropriate.

- 1.b Emission Limitation: 40 lbs OC/day

Applicable Compliance Method: Compliance shall be determined in accordance with the following method:

$$EOC(\text{lbs/day}) = \text{Summation of } P_i \times EFi.$$

where:

$EOC(\text{lbs/day})$  = the organic compound emissions from mold operations, in pounds per day.

$P_i$  = the production rate of mold compound  $i$ , in pounds per day.

$EF_i$  = emission factor of mold compound  $i$ , in pound OC per pound of mold

Emissions Unit ID: P052

compound:

- i. 0.00134 lb OC (styrene) per pound of mold compound, as determined from a Society of Plastics Industry report, "Styrene Emissions during the Charging and Molding Cycle".
- ii. 0.000576 lb OC (vinyl toluene) per pound of mold compound, vinyl toluene emissions are based on the relative evaporative rate as compare to styrene. Vinyl toluene emissions were estimated to be 43% of styrene emissions.

1.c Emission Limitation: 7.3 tpy OC

Applicable Compliance Method: To determine annual OC emissions from all molding compound materials, compliance shall be based on the sum of the daily OC emission rates from mold compound, as specified in section A.V.1.b. of this permit for the calendar year, divided by 2000 pounds/ton.

Any determination of OC content (percent by weight), solids content, or density of a material shall be based on the material as employed, including the addition of any monomer to the material. The permittee shall determine the composition of the material by formulation data supplied by the manufacturer or from data determined by an analysis of each material, as employed, by U.S. EPA Reference Method 24 as referenced in 40 CFR Part 60, Appendix A. If formulation data is employed, the Ohio EPA may require the permittee to have a Reference Method 24 analysis or an equivalent, alternative method (as approved by Ohio EPA) performed on the material(s).

1.d Emission Limitation: 0.5 tpy OC cleanup materials as combined OC emissions from emissions units P047, P048, P049, P050, P051 and P052.

Applicable Compliance Method: To determine annual OC emissions from all cleanup materials, compliance shall be based on the sum of the weekly OC emission rates from cleanup materials, as specified in section A.III.2.d. of this permit for the calendar year, divided by 2000 pounds/ton.

## **VI. Miscellaneous Requirements**

None

**Issued: To be entered upon final issuance****B. State Only Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P052 - Compression Mold Press, Wabash 200 Ton Press, Press 23 C		Compliance with the Air Toxic Policy as specified in sections B.III.1. to B.III.4.

**2. Additional Terms and Conditions**

2.a None

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
  - a. A description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
  - b. Documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
  - c. Where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.
2. The permit-to-install for this emissions unit was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the

Emissions Unit ID: P052

permit-to-install application. Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit-to-install application and the SCREEN3 model. The predicted 1-hour maximum ground-level concentration from the use of the dispersion models was compared to the maximum acceptable ground-level concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

AIR TOXIC ANALYSIS					
Emission Unit(s) ID	Pollutant	Threshold Limit Value (TLV) ( $\mu\text{g}/\text{m}^3$ )	Maximum Hourly Emission Rate (lbs/hr)	Predicted 1 Hour Maximum Ground Level Concentration ( $\mu\text{g}/\text{m}^3$ )	Maximum Acceptable Ground Level Concentration (MAGLC), ( $\mu\text{g}/\text{m}^3$ )
P047 through P052	Styrene	85,202	10.0	1,128	2,028
P047 through P052	Vinyl Toluene	241,677	4.3	485	5,754
P047 through P051	Ammonia	17,413	0.65	73	415
P047 through P051	Phenol	19,245	0.93	105	458

3. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
  - a. Changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower threshold limit value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV previously modeled;
  - b. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
  - c. Physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
4. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes,

65

**Glasti**

**PTI A**

Emissions Unit ID: P052

**Issued: To be entered upon final issuance**

Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit-to-install will not be required.  
If the

**Glasti**

**PTI A**

Emissions Unit ID: P052

**Issued: To be entered upon final issuance**

change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit-to-install prior to the change.

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None