



State of Ohio Environmental Protection Agency

Street Address:

Mailing Address:

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Lazarus Gov.
Center

RE: PERMIT TO INSTALL MODIFICATION
ASHTABULA COUNTY
Application No: 02-11131

CERTIFIED MAIL

DATE: 9/21/2000

MFG Premier Molding Company
Matthew Narducci
PO Box 1000 4401 Benefit Ave
Ashtabula, OH 44003

Enclosed Please find a modification to the Ohio EPA Permit To Install referenced above which will modify the terms and conditions.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
236 East Town Street, Room 300
Columbus, Ohio 43215

Very truly yours,

Thomas G. Rigo, Manager
Field Operations and Permit Section
Division of Air Pollution Control

CC: USEPA

NEDO



**Permit To Install
Terms and Conditions**

**Issue Date: 9/21/2000
Effective Date: 9/21/2000**

ADMINISTRATIVE MODIFICATION OF PERMIT TO INSTALL 02-11131

Application Number: **02-11131**
APS Premise Number: **0204010173**
Permit Fee: **\$1400**
Name of Facility: **MFG Premier Molding Company**
Person to Contact: **Matthew Narducci**
Address: **PO Box 1000 4401 Benefit Ave
Ashtabula, OH 44003**

Location of proposed air contaminant source(s) [emissions unit(s)]:
**4401 Benefit Ave
Ashtabula, OHIO**

Description of modification:

Modification for PTI 02-1131, issued 11/5/97, to increase the OC, NO_x, CO & PM limits due to re-vised emissions factors & inclusion of PM emissions from spray-up operation at P001 & P007-P009.

The above named entity is hereby granted a modification to the permit to install described above pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this modification does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described source(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans included in the application, the above described source(s) of pollutants will be granted the necessary operating permits.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency


Director

MFG Premier Molding Company

Facility ID: **0204010173**

PTI Application: 02-11131

Modification Issued: 9/21/2000

GENERAL PERMIT CONDITIONS

TERMINATION OF PERMIT TO INSTALL

Substantial construction for installation must take place within 18 months of the effective date of this permit. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

NOTICE OF INSPECTION

The Director of the Ohio Environmental Protection Agency, or his authorized representatives, may enter upon the premises of the above-named applicant during construction and operation at any reasonable time for the purpose of making inspections, conducting tests, or to examine records or reports pertaining to the construction, modification or installation of the source(s) of environmental pollutants identified within this permit.

CONSTRUCTION OF NEW SOURCES

The proposed source(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources are inadequate or cannot meet applicable standards.

If the construction of the proposed source(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of Ohio Administrative Code (OAC) Rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet applicable standards.

PERMIT TO INSTALL FEE

In accordance with Ohio Revised Code 3745.11, the specified Permit to Install fee must be remitted within 30 days of the effective date of this permit to install.

PUBLIC DISCLOSURE

MFG Premier Molding Company
PTI Application: 02-11131
Modification Issued: 9/21/2000

Facility ID: **0204010173**

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC Rule 3745-49-03.

APPLICABILITY

This Permit to Install is applicable only to the contaminant sources identified. Separate application must be made to the Director for the installation or modification of any other contaminant sources.

BEST AVAILABLE TECHNOLOGY

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

PERMIT TO OPERATE APPLICATION

A Permit to Operate application must be submitted to the appropriate field office for each air contaminant source in this Permit to Install. In accordance with OAC Rule 3745-35-02, the application shall be filed no later than thirty days after commencement of operation.

SOURCE OPERATION AFTER COMPLETION OF CONSTRUCTION

This facility is permitted to operate each source described by this permit to install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws and regulations.

5

MFG Premier Molding Company
PTI Application: 02-11131
Modification Issued: 9/21/2000

Facility ID: **0204010173**

MFG Premier Molding Company
PTI Application: 02-11131
Modification Issued: 9/21/2000

Facility ID: **0204010173**

| <u>Ohio EPA Source Number</u> | <u>Source Identification Number</u> | <u>BAT Determination</u> | <u>Applicable Federal & OAC Rules</u> | <u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u> |
|-------------------------------|-------------------------------------|--------------------------|---|--|
|-------------------------------|-------------------------------------|--------------------------|---|--|

AIR EMISSION SUMMARY

The air contaminant sources listed below comprise the Permit to Install for **MFG Premier Molding Company** located in **ASHTABULA** County. The sources listed below shall not exceed the emission limits/control requirements contained in the table. This condition in no way limits the applicability of any other state or federal regulations. Additionally, this condition does not limit the applicability of additional special terms and conditions of this permit.

Ohio EPA Source Number

P009
Cont'd

P001

P007

P008

P009

P008
Cont'd

P010

P011

MFG Premier Molding Company
PTI Application: 02-11131
Modification Issued: 9/21/2000

Facility ID: **0204010173**

| <u>Ohio EPA Source Number</u> | <u>Source Identification Number</u> | <u>BAT Determination</u> Number 3 | <u>Applicable Federal & OAC Rules</u> | <u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u> |
|-------------------------------|---|--------------------------------------|---|--|
| P012 | <u>Source Identification Description</u> 48" Preform/Oven Number 1 | | | Wet Resin Mixer Number 1 |
| | | | 80" Preform/Oven | Wet Resin Mixer Number 2 |
| | | 48" Preform/Oven Number 4 | | Wet Resin Mixer Number 3 |
| | 48" Preform/Oven | | | |

MFG Premier Molding Company
PTI Application: 02-11131
Modification Issued: 9/21/2000

Facility ID: **0204010173**

| <u>Ohio EPA Source Number</u> | <u>Source Identification Number</u> | <u>BAT Determination</u> | <u>Applicable Federal & OAC Rules</u> | <u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u> |
|-------------------------------|-------------------------------------|--------------------------|---|--|
|-------------------------------|-------------------------------------|--------------------------|---|--|

BAT Determination

Use of non-photochemically reactive binder solution. Use of natural gas as the fuel.

Use of non-photochemically reactive binder solution. Use of natural gas as the fuel.

Use of non-photochemically reactive binder solution. Use of natural gas as the fuel.

Use of non-photochemically reactive binder solution. Use of natural gas as the fuel.

Use of a dust control device.

Use of a dust control device.

Use of a dust control device.

MFG Premier Molding Company
PTI Application: 02-11131
Modification Issued: 9/21/2000

Facility ID: **0204010173**

| <u>Ohio EPA Source Number</u> | <u>Source Identification Number</u> | <u>BAT Determination</u> | <u>Applicable Federal & OAC Rules</u> | <u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u> |
|---------------------------------------|-------------------------------------|--------------------------|---|--|
| | | | | 3745-31-05 |
| | | | | 3745-17-11 |
| | | | | 3745-21-07 (G)(2) |
| Applicable Federal & <u>OAC Rules</u> | | | 3745-31-05 | |
| | | | 3745-17-07(A) | |
| | | | 3745-17-11 | |
| | | 3745-31-05 | 3745-21-07(G)(1) | |
| | | 3745-17-07(A) | 3745-21-08 | 3745-31-05 |
| | | 3745-17-11 | 3745-23-06 | 3745-17-11 |
| 3745-31-05 | 3745-31-05 | 3745-21-07(G)(1) | | 3745-21-07 (G)(2) |
| 3745-17-07(A) | 3745-17-07(A) | 3745-21-08 | | |
| 3745-17-11 | 3745-17-11 | 3745-23-06 | | |
| 3745-17-11 | 3745-21-07(G)(1) | | | |
| 3745-21-07(G)(1) | 3745-21-08 | | | 3745-31-05 |
| 3745-21-08 | 3745-23-06 | | | 3745-17-11 |
| 3745-23-06 | | | | 3745-21-07 (G)(2) |

MFG Premier Molding Company
PTI Application: 02-11131
Modification Issued: 9/21/2000

Facility ID: **0204010173**

| <u>Ohio EPA Source Number</u> | <u>Source Identification Number</u> | <u>BAT Determination</u> | <u>Applicable Federal & OAC Rules</u> | <u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u> |
|--|--|--|--|---|
| Permit Allowable Mass Emissions and/or Control/Usage Requirements | the spray-up operation. 2.84 TPY of total PM emissions from spray-up and fuel combustion. 6.9 pounds/day OC from binder usage at sprayup; 3 pounds/ hour and 15 pounds/ day OC from binder usage at the oven; and | emissions from the spray-up operation. 2.84 TPY of total PM emissions from spray-up and fuel combustion. 6.9 pounds/day OC from binder usage at sprayup; 3 pounds/ hour and 15 pounds/ day OC from binder usage at the oven; and 4.09 TPY from all operations of OC emissions. 0.09 lb/hr and 0.39 TPY of CO emissions from fuel combustion at the oven. | operations of OC emissions. 0.09 lb/hr and 0.39 TPY of CO emissions from fuel combustion at the oven. 0.10 lb/hr and 0.44 TPY of NO _x emissions from fuel combustion at the oven. | fuel combustion at the oven. 0.39 lb/hr and 1.71 TPY of NO _x emissions from fuel combustion at the oven. |
| Visible particulate emissions from this emissions unit shall not exceed 20% opacity as a 6-minute average, except as specified by rule. 0.629 lb/hr of PM emissions from | 4.09 TPY from all operations of OC emissions. 0.09 lb/hr and 0.39 TPY of CO emissions from fuel combustion at the oven. 0.10 lb/hr and 0.44 TPY of NO _x emissions from fuel combustion at the oven. Visible particulate emissions from this emissions unit shall not exceed 20% opacity as a 6-minute average, except as specified by rule. 0.629 lb/hr of PM | Visible particulate emissions from this emissions unit shall not exceed 20% opacity as a 6-minute average, except as specified by rule. 0.629 lb/hr of PM emissions from the spray-up operation. 2.84 TPY of total PM emissions from spray-up and fuel combustion. 6.9 pounds/day OC from binder usage at sprayup; 3 pounds/ hour and 15 pounds/ day OC from binder usage at the oven; and 4.09 TPY from all | Visible particulate emissions from this emissions unit shall not exceed 20% opacity as a 6-minute average, except as specified by rule. 1.83 lbs/hr of PM emissions from the spray-up operation. 8.36 TPY of total PM emissions from spray-up and fuel combustion. 6.9 pounds/day OC from binder usage at sprayup; 3 pounds/ hour and 15 pounds/day OC from binder usage at the oven; and 4.18 TPY from all operations of OC emissions. 0.39 lb/hr and 1.71 TPY of CO emissions from | 1.05 pounds/hour and 4.60 TPY of PM emissions. 8 pounds/hour, 40 pounds/day and 7.3 TPY of OC emissions. |
| | | | | 1.05 pounds/hour and 4.60 TPY of PM emissions. 8 pounds/hour, 40 pounds/day and 7.3 TPY of OC emissions. |

MFG Premier Molding Company
PTI Application: 02-11131
Modification Issued: 9/21/2000

Facility ID: **0204010173**

SUMMARY
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

| <u>Pollutant</u> | <u>Tons/Year</u> |
|------------------|------------------|
| PM | 30.68 |
| OC | 49.39 |
| CO | 1.55 |
| NO _x | 4.36 |

RECORD(S) RETENTION AND AVAILABILITY

All records required by this Permit to Install shall be retained on file for a period of not less than three years unless otherwise indicated by Ohio Environmental Protection Agency. All records shall be made available to the Director, or any representative of the Director, for review during normal business hours.

REPORTING REQUIREMENTS

Unless otherwise specified, reports required by the Permit to Install need only be submitted to OEPA Northwest District Office - DAPC, 2110 East Aurora Road, Twinsburg, Ohio 44087.

WASTE DISPOSAL

The owner/operator shall comply with any applicable state and federal requirements governing the storage, treatment, transport and disposal of any waste material generated by the operation of the sources.

MAINTENANCE OF EQUIPMENT

This source and its associated air pollution control system(s) shall be maintained regularly in accordance with good engineering practices and the recommendations of the respective manufacturers in order to minimize air contaminant emissions.

MALFUNCTION/ABATEMENT

In accordance with OAC RULE 3745-15-06, any malfunction of the source(s) or associated air pollution control

MFG Premier Molding Company
PTI Application: 02-11131
Modification Issued: 9/21/2000

Facility ID: **0204010173**

system(s) shall be reported immediately to the OEPA Northwest District Office - DAPC, 2110 East Aurora Road, Twinsburg, Ohio 44087.

Except as provided by OAC Rule 3745-15-06(A)(3), scheduled maintenance of air pollution control equipment that requires the shutdown or bypassing of air pollution control system(s) must be accompanied by the shutdown of the associated air pollution sources.

AIR POLLUTION NUISANCES PROHIBITED

The air contaminant source(s) identified in this permit may not cause a public nuisance in violation of OAC Rule 3745-15-07.

ADDITIONAL SPECIAL TERMS AND CONDITIONS

A. INTRODUCTION

The company manufactures fiber glass reinforced plastic parts. This permit is for four preform/ovens (P001, P007, P008 and P009) and three mixers for wet resin mix (P010, P011 and P012).

B. EMISSION LIMITATIONS

1. The emissions from each of emissions units P001, P007, and P008 shall not exceed the following limits:
 - a. 6.9 pounds/day of organic compound (OC) emissions from binder usage at the sprayup operation;
 - b. 3 pounds/hour and 15 pounds/day of OC emissions from binder usage at the oven operation;
 - c. 4.09 TPY of OC emissions from all operations, including emissions from combustion of fuel;
 - d. 0.629 lb/hr of PM emissions from the sprayup operation. 2.84 TPY of total PM emissions from sprayup and fuel combustion.
 - e. 0.10 pound/hour and 0.44 TPY of nitrogen oxide compounds (NO_x) emissions; and,

MFG Premier Molding Company
PTI Application: 02-11131
Modification Issued: 9/21/2000

Facility ID: **0204010173**

- f. 0.09 pound/hour and 0.39 TPY of carbon monoxide (CO) emissions.
2. The emissions from emissions unit P009 shall not exceed the following limits:
 - a. 6.9 pounds/day of OC emissions from binder usage at the sprayup operation;
 - b. 3 pounds/hour and 15 pounds/day of OC emissions from binder usage at the oven operation;
 - c. 4.18 TPY of OC emissions from all operations, including emissions from combustion of fuel;
 - d. 1.83 pounds/hour of PM emissions from the sprayup operation. 8.36 TPY of total PM emissions from sprayup and fuel combustion.
 - e. 0.39 pound/hour and 1.71 TPY of NO_x emissions; and,
 - f. 0.39 pound/hour and 1.71 TPY of carbon monoxide (CO) emissions.
3. The emissions from each of emissions units P010, P011 and P012 shall not exceed the following limits:
 - a. 1.05 pounds/hour and 4.60 TPY of PM emissions; and,
 - b. 8 pounds/hour, 40 pounds/day and 7.3 TPY of OC emissions.

C. OPERATIONAL RESTRICTIONS

1. Only non-photochemically reactive materials shall be employed at the preform/ovens (P001, P007, P008 and P009).
2. Natural gas shall be employed as the fuel in a burner with a rated capacity of no more than 1 MMBTU/hour at each of the 48" preform/ovens (P001, P007, and P008).
3. Natural gas shall be employed as the fuel in a burner with a rated capacity of no more than 4 MMBTU/hour at the 80" preform/oven (P009).
4. The settling chamber installed on the wet resin mixers (P010, P011 and P012) for the control of particulate matter shall be operated and maintained in accordance with the manufacturer's

MFG Premier Molding Company
PTI Application: 02-11131
Modification Issued: 9/21/2000

Facility ID: **0204010173**

specifications, instructions and operating manual(s).

5. This permit allows for the use of the materials specified by the permittee in the application for a Permit to Install. In conjunction with the best available technology requirements of OAC rule 3745-31-05, the organic compound emission limitations specified in this permit were established in accordance with the Ohio EPA's "Air Toxics Policy" and are based on both the material formulation data and the design parameters of the emissions unit's exhaust system, as specified in the application. Compliance with the Ohio EPA's "Air Toxics Policy" was demonstrated for each pollutant based on the TSCREEN model and a comparison of the predicted 1 hour maximum ground-level concentration to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling of each pollutant:

| Pollutant from P010, P011 & P012, combined Styrene | Threshold Limit Value (TLV) ($\mu\text{g}/\text{m}^3$) | Maximum Hourly Emission Rate (lbs/hr) | Predicted 1 Hour Maximum Ground Level Concentration at the fence line ($\mu\text{g}/\text{m}^3$) | Maximum Acceptable Ground Level Concentration (MAGLC), ($\mu\text{g}/\text{m}^3$) |
|--|---|---|---|--|
| | 213,000 | 24 | 2,460 | 5,071 |

Any of the following changes may be deemed as "modification" to the emissions unit(s) and, as such, prior notification to and approval from the Ohio EPA are required:

- a. any changes in the composition of the materials, or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value specified in the above table;
- b. any change to the emissions unit(s) or its exhaust parameters (e.g., increased emission rate, reduction of exhaust gas flow rate, and decreased stack height) that would result in an exceedance of any MAGLC specified in the above table: and,
- c. any change to the emissions unit(s) or its method of operation that would either require an increase in the emission limitation(s) established by this permit or would otherwise be considered a "modification" as defined in OAC rule 3745-31-01.

D. MONITORING AND/OR RECORDKEEPING REQUIREMENTS

1. The permittee shall collect and record the following information for each day for each of the preform/ovens (P001, P007, P008 and P009):
 - a. the company identification for each binder solution employed;
 - b. the number of pounds of each binder solution employed;

MFG Premier Molding Company
PTI Application: 02-11131
Modification Issued: 9/21/2000

Facility ID: **0204010173**

- c. the organic compound content of each binder solution, in percent by weight;
 - d. the total available (prior to applying the sprayup/oven "split") daily organic compound emission rate for all binder solutions, in pounds per day;
 - e. the total number of hours the emissions unit was in operation;
 - f. the total organic compound emission rate for all binder solutions at the sprayup operation (after applying the sprayup/oven "split"), in pounds per day;
 - g. the total organic compound emission rate for all binder solutions at the oven operation (after applying the sprayup/oven "split"), in pounds per day; and,
 - h. the average hourly organic compound emission rate for all binder solutions at the oven operations, i.e., (g)/(e), in pounds per hour (average).
2. The permittee shall collect and record the following information for each day for the each of the wet resin mixers (P010, P011 and P012):
- a. the company identification for each mix manufactured;
 - b. the number of pounds of each mix manufactured;
 - c. the solids content of each mix, in percent by weight;
 - d. the organic compound content of each mix, in percent by weight;
 - e. the total number of hours the emissions unit was in operation;
 - f. the total organic compound emission rate from all mixes, in pounds per day;
 - g. the average hourly organic compound emission rate, i.e., (f)/(e), in pounds per hour (average); and,
 - h. the average hourly PM emission rate, in pounds per hour (average).

E. REPORTING REQUIREMENTS

1. The permittee shall submit deviation (excursion) reports to the Ohio EPA Northeast District Office

MFG Premier Molding Company
PTI Application: 02-11131
Modification Issued: 9/21/2000

Facility ID: **0204010173**

which identify all exceedances. The reports shall include the following information:

- a. statement(s) noting the allowable limit(s) as specified in term B;
- b. an identification of each day during which the total organic compound emissions from the sprayup operation at any of the preform/ovens (P001, P007, P008 or P009) exceeded 6.9 pounds per day, and the actual organic compound emissions from the sprayup operation for each such day;
- c. an identification of each day during which the total organic compound emissions from the oven operation at any of the preform/ovens (P001, P007, P008 or P009) exceeded 15 pounds per day, and the actual organic compound emissions from the sprayup operation for each such day;
- d. an identification of each day during which the average hourly organic compound emission rate from the oven operation at any of the preform/ovens (P001, P007, P008 or P009) exceeded 3 pounds per hour, and the actual average hourly organic compound emission rate from the oven for each such day;
- e. an identification of each day during which the total organic compound emissions at any of the wet resin mixers (P010, P011 or P012) exceeded 40 pounds per day, and the actual organic compound emissions for each such day;
- f. an identification of each day during which the average hourly organic compound emission rate at any of the wet resin mixers (P010, P011 or P012) exceeded 8 pounds per hour, and the actual average hourly organic compound emission rate for each such day;
- g. an identification of each day during which the average hourly PM emission rate at any of the wet resin mixers (P010, P011 or P012) exceeded 1.05 pounds per hour, and the actual average hourly organic compound emission rate for each such day; and,
- h. a description of any corrective actions taken to address any exceedance of any emission limitation.

The excursion reports shall be submitted quarterly, i.e., by January 31, April 30, July 31 and October 31 of each year and shall cover the previous calendar quarters. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC Rule 3745-15-06.)

2. The permittee shall submit annual reports to the Ohio EPA Northeast District Office which include the following information:
 - a. the total organic compound and PM emissions from each emissions unit for the previous calendar year in tons per year.

MFG Premier Molding Company
PTI Application: 02-11131
Modification Issued: 9/21/2000

Facility ID: **0204010173**

These reports shall be submitted by April 15 of each year.

F. TESTING REQUIREMENTS

1. For purposes of calculating the organic compound emission rates for the oven operation at the preform/ovens (P001, P007, P008 and P009) and each associated sprayup operation, the permittee shall utilize a value of 32 percent as the maximum percentage of the organic compounds employed in the sprayup operation that are emitted uncontrolled from the sprayup operation. The remaining 68 percent of the organic compounds employed in the sprayup operation shall be considered to be the uncontrolled emissions for the oven operation. This split of organic compound emissions between the oven operation and the associated sprayup operation is based upon in-house testing, conducted on October 18, 1994, on a similar emissions unit, (P027) 128" Preform/Oven at Plant 2 (0204010230).

2. To calculate organic compound emissions from sprayup and oven operations at the preform/ovens (P001, P007, P008 and P009) for purposes of determining compliance with the applicable emission limitations of this permit, the permittee shall employ the following:

- a. determination of total, available, daily organic compound content for all binder solutions:

$$\sum AOE = \sum (W_i \times OC_i)$$

$\sum AOE$ = the total, available, daily organic compound content for all binder solutions, in pounds.

W_i = the weight of binder solution "a" employed, in pounds per day.

OC_i = the volatile organic compound content of binder solution "a", in percent by weight.

- b. to calculate emissions from sprayup or oven operations for purposes of determining compliance with the daily organic compound emission limitations of this permit, the permittee shall employ the following:

$$E = \sum AOE \times SR$$

E = total, daily, organic compound emissions, in pounds per day.

SR = split ratio. 0.32 for sprayup operations and 0.68 for oven operations.

3. To calculate organic compound emissions from the wet resin mixers (P010, P011 and P012) for purposes of determining compliance with the applicable emission limitations of this permit, the permittee shall employ the following:

- a. determination of total, available, daily organic compound content for all mixes:

$$\sum AOE = \sum (W_i \times OC_i)$$

$\sum AOE$ = the total, available, daily volatile organic compound emissions for all mixes, in pounds.

W_i = the weight of mix "a" employed, in pounds per day.

OC_i = the volatile organic compound content of mix "a", in percent by weight.

- b. to calculate emissions from mix operations for purposes of determining compliance with the daily organic compound emission limitations of this permit, the permittee shall employ the following:

$$E = \sum AOE \times EF$$

E = total, daily, organic compound emissions, in pounds per day.

EF = the emission factor for organic compound emissions, which is 0.01 pound per pound of available organic compound emissions, as noted in section 5.10 of AP-42.

4. To calculate PM emissions from the wet resin mixers (P010, P011 and P012) for purposes of determining compliance with the applicable emission limitations of this permit, the permittee shall employ the following:

- a. determination of total, available, daily PM content for all mixes:

$$\sum ASE = \sum (W_i \times SC_i)$$

$\sum ASE$ = the total, available, daily PM content for all mixes, in pounds per day.

W_i = the weight of mix "a" employed, in pounds per day.

SC_i = the dry solids content of mix "a", in percent by weight.

- b. to calculate emissions from mix operations for purposes of determining compliance with the hourly, PM emission limitations of this permit, the permittee shall employ the following:

MFG Premier Molding Company
PTI Application: 02-11131
Modification Issued: 9/21/2000

Facility ID: **0204010173**

$$E = \{ \sum ASE \times EF \times (1 - CE) \} / HR$$

E = total, average, hourly, PM emissions, in pounds per hour.

EF = the emission factor for PM emissions, which is 0.01 pound per pound of available PM emissions, as noted in section 5.10 of AP-42.

CE = control efficiency of PM control device.

HR = the total number of hours the emissions unit was in operation.

5. Any determination of organic compound content (percent by weight), solids content, or density of a material shall be based on the material as employed, including the addition of any thinner or viscosity reducer to the material. The permittee shall determine the composition of the material by formulation data supplied by the manufacturer or from data determined by an analysis of each material, as received, by U.S. EPA Reference Method 24 as referenced in 40 CFR Part 60, Appendix A. If formulation data is employed, the Ohio EPA may require the permittee to have a Reference Method 24 analysis or an equivalent, alternative method (as approved by Ohio EPA) performed on the material(s).

G. MISCELLANEOUS REQUIREMENTS

None.