



State of Ohio Environmental Protection Agency

Street Address:

Lazarus Gov. Center
122 S. Front Street
Columbus, OH 43215

TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049
Columbus, OH 43216-1049

07/12/02

CERTIFIED MAIL

RE: Final Title V Chapter 3745-77 permit

03-35-01-0053
Silgan Can Company
Matthew Witte Mr.
5701 Frontier Road
Oconomowoc, WI 53066

Dear Matthew Witte:

Enclosed is the Title V permit that allows you to operate the facility in the manner indicated in the permit. Because this permit may contain several conditions and restrictions, we urge you to read it carefully.

The Ohio EPA is encouraging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action of the Director is final and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed with the Environmental Review Appeals Commission within thirty (30) days after notice of the Director's action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. It is also requested by the Director that a copy of the appeal be served upon the Environmental Enforcement Section of the Office of the Attorney General. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
236 East Town Street
Room 300
Columbus, Ohio 43215

If you have any questions, please contact Northwest District Office.

Very truly yours,

Thomas G. Rigo, Manager
Field Operations and Permit Section
Division of Air Pollution Control

cc: Northwest District Office
File, DAPC PMU



State of Ohio Environmental Protection Agency

FINAL TITLE V PERMIT

Issue Date: 07/12/02	Effective Date: 07/12/02	Expiration Date: 07/12/07
-----------------------------	---------------------------------	----------------------------------

This document constitutes issuance of a Title V permit for Facility ID: 03-35-01-0053 to:

Silgan Can Company
Maumee Avenue, State Route 110 East
Napoleon, OH 43545

Emissions Unit ID (Company ID)/Emissions Unit Activity Description


K005 (COATING LINE 1) SHEET COATING LINE 1 (APPLICATION AND OVEN)	K013 (WELDED LINE 4) WELDED LINE 4 (APPLICATION AND OVEN)	END PRESS 7 (APPLICATION)
K006 (COATING LINE 2) SHEET COATING LINE 2 (APPLICATION AND OVEN)	K014 (WELDED LINE 3) WELDED LINE 3 (APPLICATION AND OVEN)	K022 (END PRESS 8) END PRESS 8 (APPLICATION)
K008 (WELDED LINE) WELDED LINE V8 (APPLICATION AND OVEN)	K015 (END PRESS 1) END PRESS 1 (APPLICATION)	K023 (END PRESS 9) can end sealing liner - end press #9
K009 (WELDED LINE 2) WELDED LINE 2 (APPLICATION AND OVEN)	K016 (END PRESS 2) END PRESS 2 (APPLICATION)	K024 (END PRESS 10) END PRESS 10 (APPLICATION)
K010 (D&I LINE) DRAWN & IRONED 2-PIECE FOOD CAN LINE (MAIN PLANT)	K017 (END PRESS 3) END PRESS 3 (APPLICATION)	K025 (END PRESS 11) END PRESS 11 (APPLICATION)
K011 (WELDED LINE 6) side seam coater - welded line #6	K018 (END PRESS 4) can end sealing liner - end press #4	K026 (END PRESS 12) END PRESS 12 (APPLICATION)
K012 (WELDED LINE 7) WELDED LINE 7 (APPLICATION AND OVEN)	K019 (END PRESS 5) END PRESS 5 (APPLICATION)	K027 (END PRESS 13) END PRESS 13 (APPLICATION)
	K020 (END PRESS 6) END PRESS 6 (APPLICATION)	K028 (END PRESS 14) END PRESS 14 (APPLICATION)
	K021 (END PRESS 7)	

You will be contacted approximately eighteen (18) months prior to the expiration date regarding the renewal of this permit. If you are not contacted, please contact the appropriate Ohio EPA District Office or local air agency listed below. This permit and the authorization to operate the air contaminant sources (emissions units) at this facility shall expire at midnight on the expiration date shown above. If a renewal permit is not issued prior to the expiration date, the permittee may continue to operate pursuant to OAC rule 3745-77-08(E) and in accordance with the terms of this permit beyond the expiration date, provided that a complete renewal application is submitted no earlier than eighteen (18) months and no later than one-hundred eighty (180) days prior to the expiration date.

Described below is the current Ohio EPA District Office or local air agency that is responsible for processing and administering your Title V permit:

Northwest District Office
347 North Dunbridge Road
Bowling Green, OH 43402
(419) 352-8461

OHIO ENVIRONMENTAL PROTECTION AGENCY

A handwritten signature in black ink, appearing to read "Christopher Jones", is written over a solid black horizontal line.

Christopher Jones
Director

PART I - GENERAL TERMS AND CONDITIONS

A. *State and Federally Enforceable Section*

1. **Monitoring and Related Record Keeping and Reporting Requirements**

- a. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:
 - i. The date, place (as defined in the permit), and time of sampling or measurements.
 - ii. The date(s) analyses were performed.
 - iii. The company or entity that performed the analyses.
 - iv. The analytical techniques or methods used.
 - v. The results of such analyses.
 - vi. The operating conditions existing at the time of sampling or measurement.
(Authority for term: OAC rule 3745-77-07(A)(3)(b)(i))
- b. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.
(Authority for term: OAC rule 3745-77-07(A)(3)(b)(ii))
- c. The permittee shall submit required reports in the following manner:
 - i. Reports of any required monitoring and/or record keeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
(Authority for term: OAC rule 3745-77-07(A)(3)(c))
 - ii. **For emission limitations, operational restrictions, and control device operating parameter limitations:**
 - (a) Written reports of (i) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring and record keeping requirements specified in this permit; (ii) the probable cause of such deviations; and (iii) any corrective actions or preventive measures taken, shall be promptly made to the appropriate Ohio EPA District Office or local air agency. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, i.e., in Part III of this Title V permit, the written reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year, and shall cover the previous calendar quarters. In identifying each deviation, the permittee shall specify the applicable requirement for which the

deviation occurred, describe each deviation, and provide the magnitude and duration of each deviation. These written reports shall satisfy the requirements (in part) of OAC rule 3745-77-07(A)(3)(c)(i) and (ii) pertaining to the submission of monitoring reports every six months and the requirements (in part) of OAC rule 3745-77-07(A)(3)(c)(iii) pertaining to the prompt reporting of all deviations. See B.6 below if no deviations occurred during the quarter.

(Authority for term: OAC rules 3745-77-07(A)(3)(c)(i) ,(ii) and (iii))

- (b) Any malfunction, as defined in OAC rule 3745-15-06(B)(1), shall be promptly reported to the Ohio EPA in accordance with OAC rule 3745-15-06. In addition, to fulfill the deviation reporting requirements for this Title V permit, written reports that identify each malfunction that occurred during each calendar quarter shall be submitted, at a minimum, quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year, and shall cover the previous calendar quarters.

In identifying each deviation caused by a malfunction, the permittee shall specify the applicable requirement for which the deviation occurred, describe each deviation, and provide the magnitude and duration of each deviation. For a specific malfunction, if this information has been provided in a written report that was submitted in accordance with OAC rule 3745-15-06, the permittee may simply reference that written report to identify the deviation. Also, if a deviation caused by a malfunction is identified in a written report submitted pursuant to paragraph (a) above, a separate report is not required for that malfunction pursuant to this paragraph. Nevertheless, all malfunctions, including those reported only verbally in accordance with OAC rule 3745-15-06, must be reported in writing, at a minimum, on a quarterly basis.

Any scheduled maintenance, as defined in OAC rule 3745-15-06(A)(1), that results in a deviation from a federally enforceable emission limitation, operational restriction, and control device operating parameter limitation shall be reported in the same manner as described above for malfunctions. These written reports for malfunctions (and scheduled maintenance projects, if appropriate) shall satisfy the requirements (in part) of OAC rule 3745-77-07(A)(3)(c)(iii) pertaining to the prompt reporting of all deviations.

(Authority for term: OAC rules 3745-77-07(A)(3)(c)(iii))

iii. **For monitoring, record keeping, and reporting requirements:**

Written reports that identify any deviations from the federally enforceable monitoring, record keeping, and reporting requirements contained in this permit shall be submitted to the appropriate Ohio EPA District Office or local air agency every six months, i.e., by January 31 and July 31 of each year, for the previous six calendar months. In identifying each deviation, the permittee shall specify the applicable requirement for which the deviation occurred, describe each deviation, and provide the magnitude and duration of each deviation. These semi-annual written reports shall satisfy the requirements of OAC rule 3745-77-07(A)(3)(c)(i) and (ii) pertaining to the reporting of any deviations related to the monitoring, record keeping, and

reporting requirements. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report which states that no deviations occurred during that period.

(Authority for term: OAC rules 3745-77-07(A)(3)(c)(i) and (ii))

- iv. Each written report shall be signed by a responsible official certifying that, "based on information and belief formed after reasonable inquiry, the statements and information in the report (including any written malfunction reports required by OAC rule 3745-15-06 that are referenced in the deviation reports) are true, accurate, and complete."

(Authority for term: OAC rule 3745-77-07(A)(3)(c)(iv))

2. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions unit(s) or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in OAC rule 3745-15-06, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

(Authority for term: OAC rule 3745-77-07(A)(3)(c)(iii))

3. Risk Management Plans

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. 7401 et seq. ("Act"), the permittee shall comply with the requirement to register such a plan.

(Authority for term: OAC rule 3745-77-07(A)(4))

4. Title IV Provisions

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

(Authority for term: OAC rule 3745-77-07(A)(5))

5. Severability Clause

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition declared invalid.

(Authority for term: OAC rule 3745-77-07(A)(6))

6. General Requirements

- a. The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and reissuance, or modification, or for denial of a permit renewal application.

- b. It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.
- c. This permit may be modified, reopened, revoked, or revoked and reissued, for cause, in accordance with A.10 below. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.
- d. This permit does not convey any property rights of any sort, or any exclusive privilege.
- e. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

(Authority for term: OAC rule 3745-77-07(A)(7))

7. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78.

(Authority for term: OAC rule 3745-77-07(A)(8))

8. Marketable Permit Programs

No revision of this permit is required under any approved economic incentive, marketable permits, emissions trading, and other similar programs or processes for changes that are provided for in this permit.

(Authority for term: OAC rule 3745-77-07(A)(9))

9. Reasonably Anticipated Operating Scenarios

The permittee is hereby authorized to make changes among operating scenarios authorized in this permit without notice to the Ohio EPA, but, contemporaneous with making a change from one operating scenario to another, the permittee must record in a log at the permitted facility the scenario under which the permittee is operating. The permit shield provided in these general terms and conditions shall apply to all operating scenarios authorized in this permit.

(Authority for term: OAC rule 3745-77-07(A)(10))

10. Reopening for Cause

This Title V permit will be reopened prior to its expiration date under the following conditions:

- a. Additional applicable requirements under the Act become applicable to one or more emissions units covered by this permit, and this permit has a remaining term of three or more years. Such a reopening shall be completed not later than eighteen (18) months after promulgation of the applicable requirement. No such reopening is required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions has been extended pursuant to paragraph (E)(1) of OAC rule 3745-77-08.
- b. This permit is issued to an affected source under the acid rain program and additional requirements (including excess emissions requirements) become applicable. Upon approval by the Administrator, excess emissions offset plans shall be deemed to be incorporated into the permit, and shall not require a reopening of this permit.
- c. The Director of the Ohio EPA or the Administrator of the U.S. EPA determines that the federally applicable requirements in this permit are based on a material mistake, or that inaccurate statements were made in establishing the emissions standards or other terms and conditions of this permit related to such federally applicable requirements.
- d. The Administrator of the U.S. EPA or the Director of the Ohio EPA determines that this permit must be revised or revoked to assure compliance with the applicable requirements.
(Authority for term: OAC rules 3745-77-07(A)(12) and 3745-77-08(D))

11. Federal and State Enforceability

Only those terms and conditions designated in this permit as federally enforceable, that are required under the Act, or any of its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA, the State, and citizens under the Act. All other terms and conditions of this permit shall not be federally enforceable and shall be enforceable under State law only.

(Authority for term: OAC rule 3745-77-07(B))

12. Compliance Requirements

- a. Any document (including reports) required to be submitted and required by a federally applicable requirement in this Title V permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.
- b. Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:

- i. At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.
 - ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with paragraph (E) of OAC rule 3745-77-03.
 - iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.
 - iv. As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.
- c. The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually, or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:
- i. Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
 - ii. An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.
- d. Compliance certifications concerning the terms and conditions contained in this permit that are federally enforceable emission limitations, standards, or work practices, shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) and the Administrator of the U.S. EPA in the following manner and with the following content:
- i. Compliance certifications shall be submitted annually on a calendar year basis. The annual certification shall be submitted on or before April 30th of each year during the permit term.
 - ii. Compliance certifications shall include the following:
 - (a) An identification of each term or condition of this permit that is the basis of the certification.
 - (b) The permittee's current compliance status.
 - (c) Whether compliance was continuous or intermittent.
 - (d) The method(s) used for determining the compliance status of the source currently and over the required reporting period.
 - (e) Such other facts as the Director of the Ohio EPA may require in the permit to determine the compliance status of the source.
 - iii. Compliance certifications shall contain such additional requirements as may be specified pursuant to sections 114(a)(3) and 504(b) of the Act.

(Authority for term: OAC rules 3745-77-07(C)(1),(2),(4) and (5) and ORC section 3704.03(L))

13. Permit Shield

- a. Compliance with the terms and conditions of this permit (including terms and conditions established for alternate operating scenarios, emissions trading, and emissions averaging, but excluding terms and conditions for which the permit shield is expressly prohibited under OAC rule 3745-77-07) shall be deemed compliance with the applicable requirements identified and addressed in this permit as of the date of permit issuance.
- b. This permit shield provision shall apply to any requirement identified in this permit pursuant to OAC rule 3745-77-07(F)(2), as a requirement that does not apply to the source or to one or more emissions units within the source.

(Authority for term: OAC rule 3745-77-07(F))

14. Operational Flexibility

The permittee is authorized to make the changes identified in OAC rule 3745-77-07(H)(1)(a) to (H)(1)(c) within the permitted stationary source without obtaining a permit revision, if such change is not a modification under any provision of Title I of the Act [as defined in OAC rule 3745-77-01(JJ)], and does not result in an exceedance of the emissions allowed under this permit (whether expressed therein as a rate of emissions or in terms of total emissions), and the permittee provides the Administrator of the U.S. EPA and the appropriate Ohio EPA District Office or local air agency with written notification within a minimum of seven days in advance of the proposed changes, unless the change is associated with, or in response to, emergency conditions. If less than seven days notice is provided because of a need to respond more quickly to such emergency conditions, the permittee shall provide notice to the Administrator of the U.S. EPA and the appropriate District Office of the Ohio EPA or local air agency as soon as possible after learning of the need to make the change. The notification shall contain the items required under OAC rule 3745-77-07(H)(2)(d).

(Authority for term: OAC rules 3745-77-07(H)(1) and (2))

15. Emergencies

The permittee shall have an affirmative defense of emergency to an action brought for noncompliance with technology-based emission limitations if the conditions of OAC rule 3745-77-07(G)(3) are met. This emergency defense provision is in addition to any emergency or upset provision contained in any applicable requirement.

(Authority for term: OAC rule 3745-77-07(G))

16. Off-Permit Changes

The owner or operator of a Title V source may make any change in its operations or emissions at the source that is not specifically addressed or prohibited in the Title V permit, without obtaining an amendment or modification of the permit, provided that the following conditions are met:

- a. The change does not result in conditions that violate any applicable requirements or that violate any existing federally enforceable permit term or condition.
- b. The permittee provides contemporaneous written notice of the change to the Director and the Administrator of the U.S. EPA, except that no such notice shall be required for changes that qualify as

insignificant emission levels or activities as defined in OAC rule 3745-77-01(U). Such written notice shall describe each such change, the date of such change, any change in emissions or pollutants emitted, and any federally applicable requirement that would apply as a result of the change.

- c. The change shall not qualify for the permit shield under OAC rule 3745-77-07(F).
- d. The permittee shall keep a record describing all changes made at the source that result in emissions of a regulated air pollutant subject to an applicable requirement, but not otherwise regulated under the permit, and the emissions resulting from those changes.
- e. The change is not subject to any applicable requirement under Title IV of the Act or is not a modification under any provision of Title I of the Act.

Paragraph (I) of rule 3745-77-07 of the Administrative Code applies only to modification or amendment of the permittee's Title V permit. The change made may require a permit to install under Chapter 3745-31 of the Administrative Code if the change constitutes a modification as defined in that Chapter. Nothing in paragraph (I) of rule 3745-77-07 of the Administrative Code shall affect any applicable obligation under Chapter 3745-31 of the Administrative Code.

(For purposes of clarification, the permittee can refer to Engineering Guide #63 that is available in the STARSHIP software package.)
(*Authority for term: OAC rule 3745-77-07(I)*)

17. Compliance Method Requirements

Nothing in this permit shall alter or affect the ability of any person to establish compliance with, or a violation of, any applicable requirement through the use of credible evidence to the extent authorized by law. Nothing in this permit shall be construed to waive any defenses otherwise available to the permittee, including but not limited to, any challenge to the Credible Evidence Rule (see 62 Fed. Reg. 8314, Feb. 24, 1997), in the context of any future proceeding.

(*This term is provided for informational purposes only.*)

18. Insignificant Activities

Each insignificant activity that has one or more applicable requirements shall comply with those applicable requirements.

(*Authority for term: OAC rule 3745-77-07(A)(1)*)

19. Permit to Install Requirement

Prior to the "installation" or "modification" of any "air contaminant source," as those terms are defined in OAC rule 3745-31-01, a permit to install must be obtained from the Ohio EPA pursuant to OAC Chapter 3745-31.

(*Authority for term: OAC rule 3745-77-07(A)(1)*)

20. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

(Authority for term: OAC rule 3745-77-07(A)(1))

B. State Only Enforceable Section

1. Reporting Requirements Related to Monitoring and Record Keeping Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or record keeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (i) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and record keeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. In identifying each deviation, the permittee shall specify the applicable requirement for which the deviation occurred, describe each deviation, and provide the magnitude and duration of each deviation. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

2. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

3. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee

shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

4. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

5. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

6. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations (See Section A of This Permit)

If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.

Part II - Specific Facility Terms and Conditions

A. State and Federally Enforcable Section

None

B. State Only Enforceable Section

1. The following insignificant emissions units are located at this facility:

can assembly solvent clean tank, emissions unit L001;
press room solvent clean tank, emissions unit L002;
machine shop solvent clean tank, emissions unit L003;
machine shop (caustic solution) solvent clean tank, emissions unit L004;
D&I department solvent clean tank, emissions unit L005;
press room portable solvent clean tank, emissions unit L006;
can shipping portable solvent clean tank, emissions unit L007;
coating department portable solvent clean tank, emissions unit L008;
D&I-V8 portable solvent clean tank, emissions unit L009;
solvent clean tank, emissions unit L010;
distillation unit (including piping and tanks), emissions unit P006;
coating storage tank, emissions unit Z001;
interior spray storage tank, emissions unit Z002;
washcoat storage tank, emissions unit Z003;
end compound tank #1, emissions unit Z004;
end compound tank #2, emissions unit Z005;
interior spray storage tank (V8), emissions unit Z006;
video marking units, emissions unit Z007;
can shredder/bailer, emissions unit Z010;
can bailer, emissions unit Z011;
UV coating line, emissions unit Z012; and
pizza ovens, emissions unit Z023.

Each insignificant emissions unit at this facility must comply with all applicable State and federal regulations, as well as any emission limitations and/or control requirements contained within a Permit to Install (PTI) for the emissions unit.

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: COATING LINE 1 (K005)
Activity Description: SHEET COATING LINE 1 (APPLICATION AND OVEN)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
sheet coating line #1, with thermal incinerator	OAC rule 3745-21-09(D)(2)(a)	4.5 lbs volatile organic compounds (VOC)/gallon of coating solids

2. Additional Terms and Conditions

None

II. Operational Restrictions

- The average combustion temperature within the thermal incinerator, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the thermal incinerator when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

The permittee shall collect and record the following information for each day for the coating line and control equipment:

- a. The name and identification number of each coating, as applied.
- b. The pounds of VOC per gallon of coating solids, as applied, the volume solids content, as applied, and the volume, as applied, of each coating.
- c. The maximum VOC content (in pounds of VOC per gallon of coating solids, as applied) of all the coatings.
- d. The calculated, controlled VOC emission rate, in pounds of VOC per gallon of coating solids, as applied. The controlled VOC emission rate shall be calculated using (i) the maximum VOC content and (ii) the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the emissions unit was in compliance.
- e. A log of the downtime for the capture (collection) system, control device and monitoring equipment when the associated emissions unit was in operation.
- f. All 3-hour blocks of time during which the average combustion temperature within the thermal incinerator, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated that the emissions unit was in compliance.

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the calculated, controlled VOC emission rate exceeded the applicable pounds of VOC per gallon of solids limitation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.
2. The permittee shall submit quarterly temperature deviation (excursion) reports that identify all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated that the emissions unit was in compliance.
3. The permittee shall submit quarterly summaries that include a log of the downtime for the capture (collection) system, control device and monitoring equipment when this emissions unit was in operation.
4. All of the quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

V. Testing Requirements

1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - 1.a The emission testing shall be conducted within 3 months after issuance of the permit and within 6 months prior to permit expiration.
 - 1.b The emission testing shall be conducted to determine the overall mass emission rate of 4.5 lbs VOC/gallon of coating solids.

V. Testing Requirements (continued)

- 1.c** The test method(s) which must be employed to demonstrate compliance with the overall control efficiency limitation for VOC are specified below.

The capture efficiency shall be determined using Methods 204 through 204F, as specified in 40 CFR Part 51, Appendix M, or the permittee may request to use an alternative method or procedure for the determination of capture efficiency in accordance with the USEPA's "Guidelines for Determining Capture Efficiency," dated January 9, 1995. (The Ohio EPA will consider the request, including an evaluation of the applicability, necessity, and validity of the alternative, and may approve the use of the alternative if such approval does not contravene any other applicable requirement.) The control efficiency (i.e. percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in OAC rule 3745-21-10. The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases.

- 1.d** The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity, unless otherwise specified or approved by the appropriate Ohio EPA District Office or local air agency.
- 2.** Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the appropriate Ohio EPA District Office or local air agency. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA District Office's or local air agency's refusal to accept the results of the emission test(s).

Personnel from the appropriate Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office or local air agency within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the appropriate Ohio EPA District Office or local air agency.

- 3.** Compliance with the emission limitation in this permit shall be determined in accordance with the following method:

Emission Limitation: 4.5 lbs VOC/gallon of coating solids

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit and also on the results of emission testing conducted in accordance with the methods and procedures outlined in section V.1 of this permit

- 4.** Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: COATING LINE 2 (K006)
Activity Description: SHEET COATING LINE 2 (APPLICATION AND OVEN)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
sheet coating line #2, with thermal incinerator	OAC rule 3745-21-09(D)(2)(a)	4.5 lbs volatile organic compounds (VOC)/gallon of coating solids

2. Additional Terms and Conditions

None

II. Operational Restrictions

- The average combustion temperature within the thermal incinerator, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the thermal incinerator when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

The permittee shall collect and record the following information for each day for the coating line and control equipment:

- a. The name and identification number of each coating, as applied.
- b. The pounds of VOC per gallon of coating solids, as applied, the volume solids content, as applied, and the volume, as applied, of each coating.
- c. The maximum VOC content (in pounds of VOC per gallon of coating solids, as applied) of all the coatings.
- d. The calculated, controlled VOC emission rate, in pounds of VOC per gallon of coating solids, as applied. The controlled VOC emission rate shall be calculated using (i) the maximum VOC content and (ii) the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the emissions unit was in compliance.
- e. A log of the downtime for the capture (collection) system control device and monitoring equipment, when the associated emissions unit was in operation.
- f. All 3-hour blocks of time during which the average combustion temperature within the thermal incinerator, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated that the emissions unit was in compliance.

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the calculated, controlled VOC emission rate exceeded the applicable pounds of VOC per gallon of solids limitation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.
2. The permittee shall submit quarterly temperature deviation (excursion) reports that identify all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated that the emissions unit was in compliance.
3. The permittee shall submit quarterly summaries that include a log of the downtime for the capture (collection) system, control device and monitoring equipment when this emissions unit was in operation.
4. All of the quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

V. Testing Requirements

1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - 1.a The emission testing shall be conducted within 3 months after issuance of the permit and within 6 months prior to permit expiration.
 - 1.b The emission testing shall be conducted to determine the overall mass emission rate of 4.5 lbs VOC/gallon of coating solids.

V. Testing Requirements (continued)

- 1.c** The test method(s) which must be employed to demonstrate compliance with the overall control efficiency limitation for VOC are specified below.

The capture efficiency shall be determined using Methods 204 through 204F, as specified in 40 CFR Part 51, Appendix M, or the permittee may request to use an alternative method or procedure for the determination of capture efficiency in accordance with the USEPA's "Guidelines for Determining Capture Efficiency," dated January 9, 1995. (The Ohio EPA will consider the request, including an evaluation of the applicability, necessity, and validity of the alternative, and may approve the use of the alternative if such approval does not contravene any other applicable requirement.) The control efficiency (i.e. percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in OAC rule 3745-21-10. The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases.

- 1.d** The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity, unless otherwise specified or approved by the appropriate Ohio EPA District Office or local air agency.
- 2.** Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the appropriate Ohio EPA District Office or local air agency. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA District Office's or local air agency's refusal to accept the results of the emission test(s).

Personnel from the appropriate Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office or local air agency within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the appropriate Ohio EPA District Office or local air agency.

- 3.** Compliance with the emission limitation in this permit shall be determined in accordance with the following method:

Emission Limitation: 4.5 lbs VOC/gallon of coating solids

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit and also on the results of emission testing conducted in accordance with the methods and procedures outlined in section V.1 of this permit

- 4.** Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: WELDED LINE (K008)
Activity Description: WELDED LINE V8 (APPLICATION AND OVEN)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
side seam coater - welded line V8	OAC rule 3745-21-09(D)(2)(d)	5.5 lbs volatile organic compounds (VOC)/gallon of coating, excluding water and exempt solvents
	OAC rule 3745-17-11(B)	0.551 lb particulate emissions (PE)/hr
	OAC rule 3745-17-07(A)	Visible PE shall not exceed 20% opacity, as a six-minute average, except as provided by rule.
	OAC rule 3745-31-05(A)(3) (PTI No. 03-2521)	The requirements established pursuant to this rule are equivalent to the requirements of OAC rules 3745-21-09(D)(2)(d), 3745-17-11(B) and 3745-17-07(A).

2. Additional Terms and Conditions

None

II. Operational Restrictions

1. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for the line:
 - 1.a the name and identification number of each coating employed; and
 - 1.b the VOC content of each coating employed (in lbs/gallon, excluding water and exempt solvents), as applied.

(This information does not have to be kept on a line-by-line basis, unless one or more of the lines is a new emissions unit and subject to specific "gallons/year" and "tons/year" limitations, or just a "tons/year" limitation in a Permit to Install. In such cases, for each such new emissions unit only, the above-mentioned information must be maintained separately for that line. Also, if the permittee mixes complying coatings at a line, it is not necessary to record the VOC content of the resulting mixture.)

III. Monitoring and/or Record Keeping Requirements (continued)

2. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC content). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.
2. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.

V. Testing Requirements

1. Compliance with the emission limitations in this permit shall be determined in accordance with the following methods:

- 1.a Emission Limitation: 5.5 lbs VOC/gallon of coating, excluding water and exempt solvents

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit.

- 1.b Emission Limitation: 0.551 lb PE/hr

Applicable Compliance Method:

To determine the actual worst case PE rate (E), the following equation may be used for the paint spraying operations:

$$E = \text{PE rate (lbs/hr)}$$

$$E = (\text{maximum coating solids usage rate, in pounds per hour}) \times (1-TE) \times (1-CE)$$

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

If required, the permittee shall demonstrate compliance with the emission limit above pursuant to OAC rule 3745-17-03(B)(10).

- 1.c Emission Limitation:
Visible PE shall not exceed 20% opacity, as a six-minute average, except as provided by rule

Applicable Compliance Method:

If required, the permittee shall demonstrate compliance with the VE limitation above pursuant to OAC rule 3745-17-03(B)(1).

2. Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings.

VI. Miscellaneous Requirements

None

Facility Name: **Silgan Can Company**
Facility ID: **03-35-01-0053**
Emissions Unit: **WELDED LINE (K008)**

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: WELDED LINE 2 (K009)
Activity Description: WELDED LINE 2 (APPLICATION AND OVEN)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
side seam coater - welded line #2	OAC rule 3745-21-09(D)(2)(d)	5.5 lbs volatile organic compounds (VOC)/gallon of coating, excluding water and exempt solvents
	OAC rule 3745-17-11(B)	0.551 lb particulate emissions (PE)/hr
	OAC rule 3745-17-07(A)	Visible PE shall not exceed 20% opacity, as a six-minute average, except as provided by rule.
	OAC rule 3745-31-05(A)(3) (PTI No. 03-2521)	The requirements established pursuant to this rule are equivalent to the requirements of OAC rules 3745-21-09(D)(2)(d), 3745-17-11(B) and 3745-17-07(A).

2. Additional Terms and Conditions

None

II. Operational Restrictions

1. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for the line:
 - 1.a the name and identification number of each coating employed; and
 - 1.b the VOC content of each coating employed (in lbs/gallon, excluding water and exempt solvents), as applied.

(This information does not have to be kept on a line-by-line basis, unless one or more of the lines is a new emissions unit and subject to specific "gallons/year" and "tons/year" limitations, or just a "tons/year" limitation in a Permit to Install. In such cases, for each such new emissions unit only, the above-mentioned information must be maintained separately for that line. Also, if the permittee mixes complying coatings at a line, it is not necessary to record the VOC content of the resulting mixture.)

III. Monitoring and/or Record Keeping Requirements (continued)

2. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC content). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.
2. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.

V. Testing Requirements

1. Compliance with the emission limitations in this permit shall be determined in accordance with the following methods:

- 1.a Emission Limitation: 5.5 lbs VOC/gallon of coating, excluding water and exempt solvents

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit.

- 1.b Emission Limitation: 0.551 lb PE/hr

Applicable Compliance Method:

To determine the actual worst case PE rate (E), the following equation may be used for the paint spraying operations:

$$E = \text{PE rate (lbs/hr)}$$

$$E = (\text{maximum coating solids usage rate, in pounds per hour}) \times (1-TE) \times (1-CE)$$

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

If required, the permittee shall demonstrate compliance with the emission limit above pursuant to OAC rule 3745-17-03(B)(10).

- 1.c Emission Limitation:
Visible PE shall not exceed 20% opacity as a six-minute average, except as provided by rule

Applicable Compliance Method:

If required, the permittee shall demonstrate compliance with the VE limitation above pursuant to OAC rule 3745-17-03(B)(1).

2. Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings.

VI. Miscellaneous Requirements

None

Facility Name: **Silgan Can Company**
Facility ID: **03-35-01-0053**
Emissions Unit: **WELDED LINE 2 (K009)**

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: D&I LINE (K010)
Activity Description: DRAWN & IRONED 2-PIECE FOOD CAN LINE (MAIN PLANT)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
drawn & ironed 2-piece food can line (main plant), with thermal oxidizer	OAC rule 3745-31-05 (PTI 03-6720)	223.92 lbs volatile organic compounds (VOC)/day (including cleanup materials) 1.74 lbs nitrogen oxides (NOx)/hr See A.II.1 & 2. The requirements of this rule also include compliance with the requirements of OAC rules 3745-21-09(D)(1)(b) & (c), 3745-17-11(B) and 3745-17-07(A).
	OAC rule 3745-21-09(D)(1)(b)	4.5 lbs VOC/gallon of coating solids (for overvarnish coatings)
	OAC rule 3745-21-09(D)(1)(c)	9.8 lbs VOC/gallon of coating solids (for interior body coatings)
	OAC rule 3745-17-11(B)	0.98 lb particulate emissions (PE)/hr
	OAC rule 3745-17-07(A)	Visible PE shall not exceed 20% opacity, as a six-minute average, except as provided by rule.

2. Additional Terms and Conditions

- The permittee shall operate a thermal oxidizer that has capture and destruction efficiencies for VOC sufficient to comply with the emission limitations above.

II. Operational Restrictions

- The maximum annual number of hours of operation for this emissions unit shall not exceed 8,400 hours, based upon a rolling, 365-day summation of the daily numbers of operating hours.
- The average combustion temperature within the thermal oxidizer, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.

II. Operational Restrictions (continued)

3. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the thermal oxidizer when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

The permittee shall collect and record the following information for each day:

- a. All 3-hour blocks of time during which the average combustion temperature within the thermal oxidizer, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
 - b. A log of the downtime for the capture (collection) system, control device and monitoring equipment when the associated emissions unit was in operation.
2. The permittee shall record and maintain each day the following information for this emissions unit:
 - a. the number of hours the emissions unit was in operation; and
 - b. the rolling, 365-day summation of the daily numbers of hours of operation.
 3. The permittee shall collect and record the following information each day for the overvarnish coating operation associated with this emissions unit:
 - a. the name and identification number of each coating, as applied;
 - b. the pounds of VOC per gallon of coating solids, as applied, the volume solids content, as applied, and the volume, as applied, of each coating;
 - c. the maximum VOC content (in pounds of VOC per gallon of coating solids, as applied) or the daily volume-weighted average VOC content (in pounds of VOC per gallon of coating solids, as applied) of all the coatings;
 - d. the calculated, controlled VOC emission rate, in pounds of VOC per gallon of coating solids, as applied (the controlled VOC emission rate shall be calculated using (i) either the maximum VOC content or the daily volume-weighted VOC content recorded in accordance with paragraph (c) above and (ii) the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the emissions unit was in compliance);
 - e. the uncontrolled amount of VOCs emitted from each coating employed (this is calculated, for each coating, by multiplying the lbs of VOC/gallon of solids by the volume solids content, and then multiplying by the number of gallons of each coating), in pounds;
 - f. the uncontrolled amount of VOC emitted from all the coatings employed (summation of 2.e for all coatings), in pounds; and
 - g. the calculated, controlled VOC emissions, in tons $[2.f \times (1 - \text{the overall control efficiency of the thermal oxidizer as determined during the most recent compliance test that demonstrated the emissions unit was in compliance}) \div 2000]$.

III. Monitoring and/or Record Keeping Requirements (continued)

4. The permittee shall collect and record the following information each day for the interior body coating operation associated with this emissions unit:
 - a. the name and identification number of each coating, as applied;
 - b. the pounds of VOC per gallon of coating solids, as applied, the volume solids content, as applied, and the volume, as applied, of each coating;
 - c. the maximum VOC content (in pounds of VOC per gallon of coating solids, as applied) or the daily volume-weighted average VOC content (in pounds of VOC per gallon of coating solids, as applied) of all the coatings;
 - d. the calculated, controlled VOC emission rate, in pounds of VOC per gallon of coating solids, as applied (the controlled VOC emission rate shall be calculated using (i) either the maximum VOC content or the daily volume-weighted VOC content recorded in accordance with paragraph (c) above and (ii) the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the emissions unit was in compliance);
 - e. the uncontrolled amount of VOCs emitted from each coating employed (this is calculated, for each coating, by multiplying the lbs of VOC/gallon of solids by the volume solids content, and then multiplying by the number of gallons of each coating), in pounds;
 - f. the uncontrolled amount of VOC emitted from all the coatings employed (summation of 2.e for all coatings), in pounds; and
 - g. the calculated, controlled VOC emissions, in tons $[2.f \times (1 - \text{the overall control efficiency of the thermal oxidizer as determined during the most recent compliance test that demonstrated the emissions unit was in compliance}) \div 2000]$.
5. The permittee shall collect and record the following information each day for the cleanup materials employed in this emissions unit:
 - a. The name and identification number for each cleanup material employed.
 - b. The volume, in gallons, of each cleanup material employed.
 - c. The VOC content, in pounds/gallon, for each cleanup material employed.
 - d. The amount of VOC emitted from each cleanup material employed (5.b x 5.c), in pounds.
 - e. The total amount of VOC emitted from all the cleanup materials employed (summation of d. for all cleanup materials), in pounds.
6. The permittee shall calculate and record, each day, the total VOC emissions, in pounds, from all the coatings and cleanup materials employed. The total VOC emissions shall be calculated as follows:

total VOC emissions (lbs/day) = VOC emissions from section 3.g + VOC emissions from section 4.g + VOC emissions from section 5.e

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify the following:
 - a. All exceedances of the rolling, 365-day limitation of 8,400 hours of operation.
 - b. All exceedances of the daily VOC emission limitation of 223.92 pounds.
 - c. All 3-hour blocks of time during which the average combustion temperature within the thermal oxidizer, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated that the emissions unit was in compliance.

These quarterly reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC contents). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.
3. The permittee shall submit quarterly summaries that include a log of the downtime for the capture (collection) system, control device and monitoring equipment when this emissions unit was in operation.

V. Testing Requirements

1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - 1.a The emission testing shall be conducted within 3 months after issuance of the permit and within 6 months prior to permit expiration.
 - 1.b The emission testing shall be conducted to determine the overall control efficiency for VOC and the overall mass emission limitations of 4.5 lbs VOC/gallon of overvarnish coating solids and 9.8 lbs VOC/gallon of interior body coating solids.
 - 1.c The test method(s) which must be employed to demonstrate compliance with the overall control efficiency limitation for VOC are specified below.

The capture efficiency shall be determined using Methods 204 through 204F, as specified in 40 CFR Part 51, Appendix M, or the permittee may request to use an alternative method or procedure for the determination of capture efficiency in accordance with the USEPA's "Guidelines for Determining Capture Efficiency," dated January 9, 1995. (The Ohio EPA will consider the request, including an evaluation of the applicability, necessity, and validity of the alternative, and may approve the use of the alternative if such approval does not contravene any other applicable requirement.) The control efficiency (i.e. percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in OAC rule 3745-21-10. The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases.

- 1.d The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity, unless otherwise specified or approved by the appropriate Ohio EPA District Office or local air agency.

V. Testing Requirements (continued)

2. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the appropriate Ohio EPA District Office or local air agency. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA District Office's or local air agency's refusal to accept the results of the emission test(s).

Personnel from the appropriate Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office or local air agency within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the appropriate Ohio EPA District Office or local air agency.

3. Compliance with the emission limitations in this permit shall be determined in accordance with the following methods:

3.a Emission limitation: 223.92 lbs VOC/day

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.3, 4, 5 and 6 of this permit.

3.b Emission Limitation: 9.8 lbs VOC/gallon of coating solids (for interior body coatings)

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.4 of this permit and also on the results of emission testing conducted in accordance with the methods and procedures outlined in section V.1 of this permit.

3.c Emission Limitation: 4.5 lbs VOC/gallon of coating solids (for overvarnish coatings)

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.3 of this permit and also on the results of emission testing conducted in accordance with the methods and procedures outlined in section V.1 of this permit.

3.d Emission Limitation: 1.74 lbs NO_x/hour

Applicable Compliance Method: Compliance with the hourly limitation above may be determined by multiplying the maximum natural gas consumption rate (mm cu. ft/hr) by the AP-42, Table 1.4-1 (revised 1/95) emission factor of 100 lbs NO_x/mm cu. ft of natural gas.

If required, the permittee shall demonstrate compliance with the hourly emission limitation pursuant to Methods 1 through 4 and 7 of 40 CFR, Part 60, Appendix A.

V. Testing Requirements (continued)

3.e Emission Limitation: 0.98 lb PE/hr

Applicable Compliance Method:

To determine the actual worst case PE rate (E), the following equation may be used for the paint spraying operations:

$E = \text{PE rate (lbs/hr)}$

$E = (\text{maximum coating solids usage rate, in pounds per hour}) \times (1-TE) \times (1-CE)$

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

If required, the permittee shall demonstrate compliance with the emission limit above pursuant to OAC rule 3745-17-03(B)(10).

3.f Emission Limitation: Visible PE shall not exceed 20% opacity, as a six-minute average, except as provided by rule.

Applicable Compliance Method: If required, the permittee shall demonstrate compliance with the Visible PE limit pursuant to OAC rule 3745-17-03(B)(1).

4. Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings and cleanup materials.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: WELDED LINE 6 (K011)
Activity Description: side seam coater - welded line #6

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
side seam coater - welded line #6	OAC rule 3745-31-05 (PTI No. 03-6946)	1,850 lbs volatile organic compounds (VOC)/month (including cleanup materials)
		The requirements of this rule also include compliance with the requirements of OAC rules 3745-21-09(D)(2)(d), 3745-17-11(B) and 3745-17-07(A).
	OAC rule 3745-21-09(D)(2)(d)	5.5 lbs VOC/gallon of coating, excluding water and exempt solvents
	OAC rule 3745-17-11(B)	0.551 lb particulate emissions (PE)/hr
	OAC rule 3745-17-07(A)	Visible PE shall not exceed 20% opacity, as a six-minute average, except as provided by rule.

2. Additional Terms and Conditions

2. Each coating employed in this emissions unit shall comply with the VOC content in section A.I.1 on an "as applied" basis.

II. Operational Restrictions

1. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for this emissions unit:
 - 1.a the name and identification number of each coating and cleanup material employed, as applied;
 - 1.b the VOC content of each coating employed (in lbs/gallon, excluding water and exempt solvents), as applied;
 - 1.c the VOC content of each coating and cleanup material employed, in pounds per gallon, as applied;

III. Monitoring and/or Record Keeping Requirements (continued)

- 1.d the volume, in gallons, of each coating and cleanup material employed;
- 1.e the amount of VOC emitted from each coating employed (1.c x 1.d), in pounds;
- 1.f the amount of VOC emitted from each cleanup material employed (1.c x 1.d), in pounds; and
- 1.g the amount of VOC emitted from all the coatings and cleanup materials employed [(summation of 1.e) for all coatings + (summation of 1.f) for all cleanup materials)], in pounds.
- 2. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.

IV. Reporting Requirements

- 1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the monthly VOC limitation of 1,850 pounds. All of the quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.
- 2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC content). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.
- 3. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.

V. Testing Requirements

- 1. Compliance with the emission limitations in this permit shall be determined in accordance with the following methods:
 - 1.a Emission Limitation: 1,850 lbs VOC/month

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit.
 - 1.b Emission Limitation: 5.5 lbs VOC/gallon of coating, excluding water and exempt solvents

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit.

V. Testing Requirements (continued)

1.c Emission Limitation: 0.551 lb PE/hr

Applicable Compliance Method:

To determine the actual worst case PE rate (E), the following equation shall be used for the paint spraying operations:

$E = \text{PE rate (lbs/hr)}$

$E = (\text{maximum coating solids usage rate, in pounds per hour}) \times (1-TE) \times (1-CE)$

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

If required, the permittee shall demonstrate compliance with the emission limit above pursuant to OAC rule 3745-17-03(B)(10).

1.d Emission Limitation: Visible PE shall not exceed 20% opacity, as a six-minute average, except as provided by rule.

Applicable Compliance Method: If required, the permittee shall demonstrate compliance with the visible PE limit above pursuant to OAC rule 3745-17-03(B)(1).

2. Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings and cleanup materials.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: WELDED LINE 7 (K012)
Activity Description: WELDED LINE 7 (APPLICATION AND OVEN)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
side seam coater - welded line #7	OAC rule 3745-31-05 (PTI No. 03-6946)	1,850 lbs volatile organic compounds (VOC)/month (including cleanup materials)
		The requirements of this rule also include compliance with the requirements of OAC rules 3745-21-09(D)(2)(d), 3745-17-11(B) and 3745-17-07(A).
	OAC rule 3745-21-09(D)(2)(d)	5.5 lbs VOC/gallon of coating, excluding water and exempt solvents
	OAC rule 3745-17-11(B)	0.551 lb particulate emissions (PE)/hr
	OAC rule 3745-17-07(A)	Visible PE shall not exceed 20% opacity, as a six-minute average, except as provided by rule.

2. Additional Terms and Conditions

2. Each coating employed in this emissions unit shall comply with the VOC content in section A.I.1 on an "as applied" basis.

II. Operational Restrictions

1. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for this emissions unit:
 - 1.a the name and identification number of each coating and cleanup material employed, as applied;
 - 1.b the VOC content of each coating employed (in lbs/gallon, excluding water and exempt solvents), as applied;
 - 1.c the VOC content of each coating and cleanup material employed, in pounds per gallon, as applied;

III. Monitoring and/or Record Keeping Requirements (continued)

- 1.d the volume, in gallons, of each coating and cleanup material employed;
- 1.e the amount of VOC emitted from each coating employed (1.c x 1.d), in pounds;
- 1.f the amount of VOC emitted from each cleanup material employed (1.c x 1.d), in pounds; and
- 1.g the amount of VOC emitted from all the coatings and cleanup materials employed [(summation of 1.e) for all coatings + (summation of 1.f) for all cleanup materials)], in pounds.
- 2. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.

IV. Reporting Requirements

- 1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the monthly VOC limitation of 1,850 pounds. All of the quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.
- 2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC content). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.
- 3. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.

V. Testing Requirements

- 1. Compliance with the emission limitations in this permit shall be determined in accordance with the following methods:
 - 1.a Emission Limitation: 1,850 lbs VOC/month

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit.
 - 1.b Emission Limitation: 5.5 lbs VOC/gallon of coating, excluding water and exempt solvents

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit.

V. Testing Requirements (continued)

1.c Emission Limitation: 0.551 lb PE/hr

Applicable Compliance Method:

To determine the actual worst case PE rate (E), the following equation shall be used for the paint spraying operations:

$$E = PE \text{ (lbs/hr)}$$

$$E = (\text{maximum coating solids usage rate, in pounds per hour}) \times (1-TE) \times (1-CE)$$

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

If required, the permittee shall demonstrate compliance with the emission limit above pursuant to OAC rule 3745-17-03(B)(10).

1.d Emission Limitation: Visible PE shall not exceed 20% opacity as a six-minute average, except as provided by rule

Applicable Compliance Method: If required, the permittee shall demonstrate compliance with the visible PE limit above pursuant to OAC rule 3745-17-03(B)(1).

2. Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings and cleanup materials.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: WELDED LINE 4 (K013)
Activity Description: WELDED LINE 4 (APPLICATION AND OVEN)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
side seam coater - welded line #4	OAC rule 3745-31-05 (PTI No. 03-2521)	The requirements established pursuant to this rule are equivalent to the requirements of OAC rules 3745-21-09(D)(2)(d), 3745-17-11(B) and 3745-17-07(A).
	OAC rule 3745-21-09(D)(2)(d)	5.5 lbs VOC/gallon of coating, excluding water and exempt solvents
	OAC rule 3745-17-11(B)	0.551 lb particulate emissions (PE)/hr
	OAC rule 3745-17-07(A)	Visible PE shall not exceed 20% opacity, as a six-minute average, except as provided by rule.

2. Additional Terms and Conditions

None

II. Operational Restrictions

1. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for this emissions unit:
 - 1.a the name and identification number of each coating employed;
 - 1.b the VOC content of each coating employed (in lbs/gallon, excluding water and exempt solvents), as applied.

(This information does not have to be kept on a line-by-line basis, unless one or more of the lines is a new emissions unit and subject to specific "gallons/year" and "tons/year" limitations, or just a "tons/year" limitation in a Permit to Install. In such cases, for each such new emissions unit only, the above-mentioned information must be maintained separately for that line. Also, if the permittee mixes complying coatings at a line, it is not necessary to record the VOC content of the resulting mixture.)

III. Monitoring and/or Record Keeping Requirements (continued)

2. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC content). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.
2. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.

V. Testing Requirements

1. Compliance with the emission limitations in this permit shall be determined in accordance with the following methods:

- 1.a Emission Limitation: 5.5 lbs VOC/gallon of coating, excluding water and exempt solvents

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit.

- 1.b Emission Limitation: 0.551 lb PE/hr

Applicable Compliance Method:

To determine the actual worst case PE rate (E), the following equation may be used for the paint spraying operations:

$$E = \text{PE rate (lbs/hr)}$$

$$E = (\text{maximum coating solids usage rate, in pounds per hour}) \times (1-TE) \times (1-CE)$$

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

If required, the permittee shall demonstrate compliance with the emission limit above pursuant to OAC rule 3745-17-03(B)(10).

- 1.c Emission Limitation: Visible PE shall not exceed 20% opacity, as a six-minute average, except as provided by rule.

Applicable Compliance Method: If required, the permittee shall demonstrate compliance with the above emission limit pursuant to OAC rule 3745-17-03(B)(1).

2. Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: WELDED LINE 3 (K014)
Activity Description: WELDED LINE 3 (APPLICATION AND OVEN)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
side seam coater - welded line #3	OAC rule 3745-31-05 (PTI No. 03-2521)	The requirements established pursuant to this rule are equivalent to the requirements of OAC rules 3745-21-09(D)(2)(d), 3745-17-11(B) and 3745-17-07(A).
	OAC rule 3745-21-09(D)(2)(d)	5.5 lbs VOC/gallon of coating, excluding water and exempt solvents
	OAC rule 3745-17-11(B)	0.551 lb particulate emissions (PE)/hr
	OAC rule 3745-17-07(A)	Visible PE shall not exceed 20% opacity, as a six-minute average, except as provided by rule.

2. Additional Terms and Conditions

None

II. Operational Restrictions

1. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for this emissions unit:
 - 1.a the name and identification number of each coating employed;
 - 1.b the VOC content of each coating employed (in lbs/gallon, excluding water and exempt solvents), as applied.

(This information does not have to be kept on a line-by-line basis, unless one or more of the lines is a new emissions unit and subject to specific "gallons/year" and "tons/year" limitations, or just a "tons/year" limitation in a Permit to Install. In such cases, for each such new emissions unit only, the above-mentioned information must be maintained separately for that line. Also, if the permittee mixes complying coatings at a line, it is not necessary to record the VOC content of the resulting mixture.)

III. Monitoring and/or Record Keeping Requirements (continued)

2. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC content). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.
2. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.

V. Testing Requirements

1. Compliance with the emission limitations in this permit shall be determined in accordance with the following methods:

- 1.a Emission Limitation: 5.5 lbs VOC/gallon of coating, excluding water and exempt solvents

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit.

- 1.b Emission Limitation: 0.551 lb PE/hr

Applicable Compliance Method:

To determine the actual worst case PE rate (E), the following equation may be used for the paint spraying operations:

$$E = \text{PE rate (lbs/hr)}$$

$$E = (\text{maximum coating solids usage rate, in pounds per hour}) \times (1-TE) \times (1-CE)$$

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

If required, the permittee shall demonstrate compliance with the emission limit above pursuant to OAC rule 3745-17-03(B)(10).

- 1.c Emission Limitation: Visible PE shall not exceed 20% opacity as a six-minute average, except as provided by rule.

Applicable Compliance Method: If required, the permittee shall demonstrate compliance with the above emission limit pursuant to OAC rule 3745-17-03(B)(1).

2. Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: END PRESS 1 (K015)
Activity Description: END PRESS 1 (APPLICATION)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
can end sealing liner - end press #1	OAC rule 3745-21-09(D)(2)(e)	3.7 lbs VOC/gallon of coating, excluding water and exempt solvents

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for the line:
 - 1.a the name and identification number of each coating employed; and
 - 1.b the VOC content of each coating employed (lbs/gallon, excluding water and exempt solvents), as applied.

(This information does not have to be kept on a line-by-line basis, unless one or more of the lines is a new emissions unit and subject to specific "gallons/year" and "tons/year" limitations, or just a "tons/year" limitation in a Permit to Install. In such cases, for each such new emissions unit only, the above-mentioned information must be maintained separately for that line. Also, if the permittee mixes complying coatings at a line, it is not necessary to record the VOC content of the resulting mixture.)

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC content). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.
2. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.

V. Testing Requirements

1. Compliance with the emission limitation(s) in this permit shall be determined in accordance with the following method(s):

1.a Emission Limitation: 3.7 lbs VOC per gallon of coating, excluding water and exempt solvents

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit.

2. Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: END PRESS 2 (K016)
Activity Description: END PRESS 2 (APPLICATION)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
can end sealing liner - end press #2	OAC rule 3745-21-09(D)(2)(e)	3.7 lbs VOC/gallon of coating, excluding water and exempt solvents

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for the line:
 - 1.a the name and identification number of each coating employed; and
 - 1.b the VOC content of each coating employed (lbs/gallon, excluding water and exempt solvents), as applied.

(This information does not have to be kept on a line-by-line basis, unless one or more of the lines is a new emissions unit and subject to specific "gallons/year" and "tons/year" limitations, or just a "tons/year" limitation in a Permit to Install. In such cases, for each such new emissions unit only, the above-mentioned information must be maintained separately for that line. Also, if the permittee mixes complying coatings at a line, it is not necessary to record the VOC content of the resulting mixture.)

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC content). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.
2. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.

V. Testing Requirements

1. Compliance with the emission limitation(s) in this permit shall be determined in accordance with the following method(s):

1.a Emission Limitation: 3.7 lbs VOC per gallon of coating, excluding water and exempt solvents

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit.

2. Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: END PRESS 3 (K017)
Activity Description: END PRESS 3 (APPLICATION)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
can end sealing liner - end press #3	OAC rule 3745-21-09(D)(2)(e)	3.7 lbs VOC/gallon of coating, excluding water and exempt solvents

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for the line:
 - 1.a the name and identification number of each coating employed; and
 - 1.b the VOC content of each coating employed (lbs/gallon, excluding water and exempt solvents), as applied.

(This information does not have to be kept on a line-by-line basis, unless one or more of the lines is a new emissions unit and subject to specific "gallons/year" and "tons/year" limitations, or just a "tons/year" limitation in a Permit to Install. In such cases, for each such new emissions unit only, the above-mentioned information must be maintained separately for that line. Also, if the permittee mixes complying coatings at a line, it is not necessary to record the VOC content of the resulting mixture.)

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC content). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.

V. Testing Requirements

1. Compliance with the emission limitation(s) in this permit shall be determined in accordance with the following method(s):

V. Testing Requirements (continued)

- 1.a** Emission Limitation: 3.7 lbs VOC per gallon of coating, excluding water and exempt solvents

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit.

- 2.** Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: END PRESS 4 (K018)

Activity Description: can end sealing liner - end press #4

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
can end sealing liner - end press #4	OAC rule 3745-21-09(D)(2)(e)	3.7 lbs VOC/gallon of coating, excluding water and exempt solvents

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for the line:
 - 1.a the name and identification number of each coating employed; and
 - 1.b the VOC content of each coating employed (lbs/gallon, excluding water and exempt solvents), as applied.

(This information does not have to be kept on a line-by-line basis, unless one or more of the lines is a new emissions unit and subject to specific "gallons/year" and "tons/year" limitations, or just a "tons/year" limitation in a Permit to Install. In such cases, for each such new emissions unit only, the above-mentioned information must be maintained separately for that line. Also, if the permittee mixes complying coatings at a line, it is not necessary to record the VOC content of the resulting mixture.)

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC content). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.

V. Testing Requirements

1. Compliance with the emission limitation(s) in this permit shall be determined in accordance with the following method(s):

V. Testing Requirements (continued)

- 1.a** Emission Limitation: 3.7 lbs VOC per gallon of coating, excluding water and exempt solvents

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit.

- 2.** Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: END PRESS 5 (K019)
Activity Description: END PRESS 5 (APPLICATION)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
can end sealing liner - end press #5	OAC rule 3745-21-09(D)(2)(e)	3.7 lbs VOC/gallon of coating, excluding water and exempt solvents

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for the line:
 - 1.a the name and identification number of each coating employed; and
 - 1.b the VOC content of each coating employed (lbs/gallon, excluding water and exempt solvents), as applied.

(This information does not have to be kept on a line-by-line basis, unless one or more of the lines is a new emissions unit and subject to specific "gallons/year" and "tons/year" limitations, or just a "tons/year" limitation in a Permit to Install. In such cases, for each such new emissions unit only, the above-mentioned information must be maintained separately for that line. Also, if the permittee mixes complying coatings at a line, it is not necessary to record the VOC content of the resulting mixture.)

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC content). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.

V. Testing Requirements

1. Compliance with the emission limitation(s) in this permit shall be determined in accordance with the following method(s):

V. Testing Requirements (continued)

- 1.a** Emission Limitation: 3.7 lbs VOC per gallon of coating, excluding water and exempt solvents

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit.

- 2.** Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: END PRESS 6 (K020)
Activity Description: END PRESS 6 (APPLICATION)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
can end sealing liner - end press #6	OAC rule 3745-21-09(D)(2)(e)	3.7 lbs VOC/gallon of coating, excluding water and exempt solvents

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for the line:
 - 1.a the name and identification number of each coating employed; and
 - 1.b the VOC content of each coating employed (lbs/gallon, excluding water and exempt solvents), as applied.

(This information does not have to be kept on a line-by-line basis, unless one or more of the lines is a new emissions unit and subject to specific "gallons/year" and "tons/year" limitations, or just a "tons/year" limitation in a Permit to Install. In such cases, for each such new emissions unit only, the above-mentioned information must be maintained separately for that line. Also, if the permittee mixes complying coatings at a line, it is not necessary to record the VOC content of the resulting mixture.)

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC content). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.

V. Testing Requirements

1. Compliance with the emission limitation(s) in this permit shall be determined in accordance with the following method(s):

V. Testing Requirements (continued)

- 1.a** Emission Limitation: 3.7 lbs VOC per gallon of coating, excluding water and exempt solvents

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit.

- 2.** Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: END PRESS 7 (K021)
Activity Description: END PRESS 7 (APPLICATION)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
can end sealing liner - end press #7	OAC rule 3745-21-09(D)(2)(e)	3.7 lbs VOC/gallon of coating, excluding water and exempt solvents

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for the line:
 - 1.a the name and identification number of each coating employed; and
 - 1.b the VOC content of each coating employed (lbs/gallon, excluding water and exempt solvents), as applied.

(This information does not have to be kept on a line-by-line basis, unless one or more of the lines is a new emissions unit and subject to specific "gallons/year" and "tons/year" limitations, or just a "tons/year" limitation in a Permit to Install. In such cases, for each such new emissions unit only, the above-mentioned information must be maintained separately for that line. Also, if the permittee mixes complying coatings at a line, it is not necessary to record the VOC content of the resulting mixture.)

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC content). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.

V. Testing Requirements

1. Compliance with the emission limitation(s) in this permit shall be determined in accordance with the following method(s):

V. Testing Requirements (continued)

- 1.a** Emission Limitation: 3.7 lbs VOC per gallon of coating, excluding water and exempt solvents

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit.

- 2.** Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: END PRESS 8 (K022)
Activity Description: END PRESS 8 (APPLICATION)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
can end sealing liner - end press #8	OAC rule 3745-21-09(D)(2)(e)	3.7 lbs VOC/gallon of coating, excluding water and exempt solvents

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for the line:
 - 1.a the name and identification number of each coating employed; and
 - 1.b the VOC content of each coating employed (lbs/gallon, excluding water and exempt solvents), as applied.

(This information does not have to be kept on a line-by-line basis, unless one or more of the lines is a new emissions unit and subject to specific "gallons/year" and "tons/year" limitations, or just a "tons/year" limitation in a Permit to Install. In such cases, for each such new emissions unit only, the above-mentioned information must be maintained separately for that line. Also, if the permittee mixes complying coatings at a line, it is not necessary to record the VOC content of the resulting mixture.)

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC content). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.

V. Testing Requirements

1. Compliance with the emission limitation(s) in this permit shall be determined in accordance with the following method(s):

Facility Name: **Silgan Can Company**

Facility ID: **03-35-01-0053**

Emissions Unit: **END PRESS 8 (K022)**

V. Testing Requirements (continued)

1.a Emission Limitation: 3.7 lbs VOC per gallon of coating, excluding water and exempt solvents

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit.

2. Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: END PRESS 9 (K023)
Activity Description: can end sealing liner - end press #9

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
can end sealing liner - end press #9	OAC rule 3745-21-09(D)(2)(e)	3.7 lbs VOC/gallon of coating, excluding water and exempt solvents

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for the line:
 - 1.a the name and identification number of each coating employed; and
 - 1.b the VOC content of each coating employed (lbs/gallon, excluding water and exempt solvents), as applied.

(This information does not have to be kept on a line-by-line basis, unless one or more of the lines is a new emissions unit and subject to specific "gallons/year" and "tons/year" limitations, or just a "tons/year" limitation in a Permit to Install. In such cases, for each such new emissions unit only, the above-mentioned information must be maintained separately for that line. Also, if the permittee mixes complying coatings at a line, it is not necessary to record the VOC content of the resulting mixture.)

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC content). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.

V. Testing Requirements

1. Compliance with the emission limitation(s) in this permit shall be determined in accordance with the following method(s):

V. Testing Requirements (continued)

- 1.a** Emission Limitation: 3.7 lbs VOC per gallon of coating, excluding water and exempt solvents

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit.

- 2.** Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: END PRESS 10 (K024)
Activity Description: END PRESS 10 (APPLICATION)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
can end sealing liner - end press #10	OAC rule 3745-21-09(D)(2)(e)	3.7 lbs VOC/gallon of coating, excluding water and exempt solvents

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for the line:
 - 1.a the name and identification number of each coating employed; and
 - 1.b the VOC content of each coating employed (lbs/gallon, excluding water and exempt solvents), as applied.

(This information does not have to be kept on a line-by-line basis, unless one or more of the lines is a new emissions unit and subject to specific "gallons/year" and "tons/year" limitations, or just a "tons/year" limitation in a Permit to Install. In such cases, for each such new emissions unit only, the above-mentioned information must be maintained separately for that line. Also, if the permittee mixes complying coatings at a line, it is not necessary to record the VOC content of the resulting mixture.)

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC content). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.

V. Testing Requirements

1. Compliance with the emission limitation(s) in this permit shall be determined in accordance with the following method(s):

V. Testing Requirements (continued)

- 1.a** Emission Limitation: 3.7 lbs VOC per gallon of coating, excluding water and exempt solvents

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit.

- 2.** Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: END PRESS 11 (K025)
Activity Description: END PRESS 11 (APPLICATION)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
can end sealing liner - end press #11	OAC rule 3745-21-09(D)(2)(e)	3.7 lbs VOC/gallon of coating, excluding water and exempt solvents

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for the line:
 - 1.a the name and identification number of each coating employed; and
 - 1.b the VOC content of each coating employed (lbs/gallon, excluding water and exempt solvents), as applied.

(This information does not have to be kept on a line-by-line basis, unless one or more of the lines is a new emissions unit and subject to specific "gallons/year" and "tons/year" limitations, or just a "tons/year" limitation in a Permit to Install. In such cases, for each such new emissions unit only, the above-mentioned information must be maintained separately for that line. Also, if the permittee mixes complying coatings at a line, it is not necessary to record the VOC content of the resulting mixture.)

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC content). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.

V. Testing Requirements

1. Compliance with the emission limitation(s) in this permit shall be determined in accordance with the following method(s):

Facility Name: **Silgan Can Company**

Facility ID: **03-35-01-0053**

Emissions Unit: **END PRESS 11 (K025)**

V. Testing Requirements (continued)

1.a Emission Limitation: 3.7 lbs VOC per gallon of coating, excluding water and exempt solvents

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit.

2. Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: END PRESS 12 (K026)
Activity Description: END PRESS 12 (APPLICATION)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
can end sealing liner - end press #12	OAC rule 3745-21-09(D)(2)(e)	3.7 lbs VOC/gallon of coating, excluding water and exempt solvents

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for the line:
 - 1.a the name and identification number of each coating employed; and
 - 1.b the VOC content of each coating employed (lbs/gallon, excluding water and exempt solvents), as applied.

(This information does not have to be kept on a line-by-line basis, unless one or more of the lines is a new emissions unit and subject to specific "gallons/year" and "tons/year" limitations, or just a "tons/year" limitation in a Permit to Install. In such cases, for each such new emissions unit only, the above-mentioned information must be maintained separately for that line. Also, if the permittee mixes complying coatings at a line, it is not necessary to record the VOC content of the resulting mixture.)

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC content). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.

V. Testing Requirements

1. Compliance with the emission limitation(s) in this permit shall be determined in accordance with the following method(s):

V. Testing Requirements (continued)

- 1.a** Emission Limitation: 3.7 lbs VOC per gallon of coating, excluding water and exempt solvents

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit.

- 2.** Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: END PRESS 13 (K027)
Activity Description: END PRESS 13 (APPLICATION)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
can end sealing liner - end press #13	OAC rule 3745-21-09(D)(2)(e)	3.7 lbs VOC/gallon of coating, excluding water and exempt solvents

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for the line:
 - 1.a the name and identification number of each coating employed; and
 - 1.b the VOC content of each coating employed (lbs/gallon, excluding water and exempt solvents), as applied.

(This information does not have to be kept on a line-by-line basis, unless one or more of the lines is a new emissions unit and subject to specific "gallons/year" and "tons/year" limitations, or just a "tons/year" limitation in a Permit to Install. In such cases, for each such new emissions unit only, the above-mentioned information must be maintained separately for that line. Also, if the permittee mixes complying coatings at a line, it is not necessary to record the VOC content of the resulting mixture.)

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC content). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.

V. Testing Requirements

1. Compliance with the emission limitation(s) in this permit shall be determined in accordance with the following method(s):

V. Testing Requirements (continued)

- 1.a** Emission Limitation: 3.7 lbs VOC per gallon of coating, excluding water and exempt solvents

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit.

- 2.** Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: END PRESS 14 (K028)
Activity Description: END PRESS 14 (APPLICATION)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
can end sealing liner - end press #14	OAC rule 3745-21-09(D)(2)(e)	3.7 lbs VOC/gallon of coating, excluding water and exempt solvents

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for the line:
 - 1.a the name and identification number of each coating employed; and
 - 1.b the VOC content of each coating employed (lbs/gallon, excluding water and exempt solvents), as applied.

(This information does not have to be kept on a line-by-line basis, unless one or more of the lines is a new emissions unit and subject to specific "gallons/year" and "tons/year" limitations, or just a "tons/year" limitation in a Permit to Install. In such cases, for each such new emissions unit only, the above-mentioned information must be maintained separately for that line. Also, if the permittee mixes complying coatings at a line, it is not necessary to record the VOC content of the resulting mixture.)

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings (i.e., for VOC content). The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.

V. Testing Requirements

1. Compliance with the emission limitation(s) in this permit shall be determined in accordance with the following method(s):

V. Testing Requirements (continued)

- 1.a** Emission Limitation: 3.7 lbs VOC per gallon of coating, excluding water and exempt solvents

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of this permit.

- 2.** Formulation data or USEPA Method 24 shall be used to determine the VOC contents of all the coatings.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

THIS IS THE LAST PAGE OF THE PERMIT
