

Facility ID: 0247090986 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

\*\*\*THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION\*\*\*

Facility ID: 0247090986 Emissions Unit ID: K001 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

**Part II - Special Terms and Conditions**

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
  - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
  - (a) None.

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K001 - Paint Booth for Auto Body shop	OAC rule 3745-31-05(A)(3) PTI 02-16279	55.43 pounds per day and 10.2 tons per year of Volatile Organic Compound (VOC) emissions from all coatings, including cleanup materials.

See below A.2.2.a.

OAC rule 3745-21-09(U)(2)(c)

2. **Additional Terms and Conditions**
  - (a) The requirements of OAC rule 3745-21-09(U)(1) shall not apply to the repainting (refinishing) of used motor vehicles and trailers, in accordance with OAC rule 3745-21-09(U)(2)(c).

**B. Operational Restrictions**

1. A dry filtration system for the paint spray booth (K001) shall be used while the booth is in operation.

**C. Monitoring and/or Record Keeping Requirements**

1. The permittee shall collect and record the following information daily for the paint spray booth (K001):
  - a. The name and identification number of each coating, as applied.
  - b. The VOC content of each coating, as applied (excluding water and exempt solvents).
  - c. The number of gallons of each coating employed.
  - d. The name and identification of each cleanup material employed.
  - e. The VOC content of each cleanup material, in pounds per gallon (excluding water and exempt solvents).
  - f. The number of gallons of each cleanup material employed.
  - g. The total VOC emission rate for all coatings and cleanup materials, in pounds per day.

The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit.
2. The permittee shall maintain daily records that document any time periods when the dry filters were not in service when the emissions unit was in operation.
3. The permit to install for this emissions unit K001 was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Xylenes  
 TLV (mg/m3): 434  
 Maximum Hourly Emission Rate (lbs/hr): 2.13  
 Predicted 1-Hour Maximum Ground-Level  
 Concentration (ug/m3): 119.5  
 MAGLC (ug/m3): 10,338

Pollutant: Ethyl Benzene  
 TLV (mg/m3): 434  
 Maximum Hourly Emission Rate (lbs/hr): 0.81  
 Predicted 1-Hour Maximum Ground-Level  
 Concentration (ug/m3): 44.27  
 MAGLC (ug/m3): 10,338

Pollutant: Propylene glycol monomethyl ether (PGME)  
 TLV (mg/m3): 369  
 Maximum Hourly Emission Rate (lbs/hr): 0.92  
 Predicted 1-Hour Maximum Ground-Level  
 Concentration (ug/m3): 53.12  
 MAGLC (ug/m3): 8,776

Pollutant: N-Butanol  
 TLV (mg/m3): 36.85  
 Maximum Hourly Emission Rate (lbs/hr): 0.55  
 Predicted 1-Hour Maximum Ground-Level  
 Concentration (ug/m3): 30.55  
 MAGLC (ug/m3): 877.38

Pollutant: VM&P Naphtha  
 TLV (mg/m3): 1,400  
 Maximum Hourly Emission Rate (lbs/hr): 0.42  
 Predicted 1-Hour Maximum Ground-Level  
 Concentration (ug/m3): 23.46  
 MAGLC (ug/m3): 33,304  
 Pollutant: N-Butyl Acetate  
 TLV (mg/m3): 713  
 Maximum Hourly Emission Rate (lbs/hr): 2.26  
 Predicted 1-Hour Maximum Ground-Level  
 Concentration (ug/m3): 124  
 MAGLC (ug/m3): 17,000

Pollutant: Toluene  
 TLV (mg/m3): 188  
 Maximum Hourly Emission Rate (lbs/hr): 2.43  
 Predicted 1-Hour Maximum Ground-Level  
 Concentration (ug/m3): 137.2  
 MAGLC (ug/m3): 4,480  
 Pollutant: IsoButyl Acetate  
 TLV (mg/m3): 713  
 Maximum Hourly Emission Rate (lbs/hr): 0.69  
 Predicted 1-Hour Maximum Ground-Level  
 Concentration (ug/m3): 38.52  
 MAGLC (ug/m3): 17,000

Pollutant: Methyl Ethyl Ketone (MEK)  
 TLV (mg/m3): 590  
 Maximum Hourly Emission Rate (lbs/hr): 0.70  
 Predicted 1-Hour Maximum Ground-Level  
 Concentration (ug/m3): 38.69  
 MAGLC (ug/m3): 14,000

4. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
- changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
  - changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
  - physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

5. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
  - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
  - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
  - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.
- D. **Reporting Requirements**
  1. The permittee shall submit deviation (excursion) reports which identify each day during which the total VOC emissions exceeded 55.43 lbs/day and the actual VOC emissions for each such day.
  2. The permittee shall submit annual reports which specify the total VOC emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.
  3. The permittee shall notify the Director (Ohio EPA, Northeast District Office) in writing of any daily record showing that the dry filters were not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (Ohio EPA, Northeast District Office) within 30 days after the event occurs.
- E. **Testing Requirements**
  1. Emission Limitation:  
55.43 pounds per day of VOC emissions from all coatings, including cleanup materials  
  
Applicable Compliance Method:  
Compliance shall be based upon the Monitoring and/or Record Keeping requirements specified in Section C.
  2. Emission Limitation:  
10.2 tons per year of VOC emissions from all coatings, including cleanup materials  
  
Applicable Compliance Method:  
Compliance shall be based upon the Monitoring and/or Record Keeping requirements specified in Section C.
- F. **Miscellaneous Requirements**
  1. None