



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL
HOLMES COUNTY**

CERTIFIED MAIL

Street Address:

50 West Town Street, Suite 700

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049

Application No: 02-22720

Fac ID: 0238000165

DATE: 8/21/2007

Schlabach Woodworks
David Schlabach
6660 State Rte 241
Millersburg, OH 44654

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action of the Director is final and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. The appeal must be filed with the Commission within thirty (30) days after notice of the Director's action. The appeal must be accompanied by a filing fee of \$70.00 which the Commission, in its discretion, may reduce if by affidavit you demonstrate that payment of the full amount of the fee would cause extreme hardship. Notice of the filing of the appeal shall be filed with the Director within three (3) days of filing with the Commission. Ohio EPA requests that a copy of the appeal be served upon the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, OH 43215

Sincerely,

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: USEPA

NEDO



**Permit To Install
Terms and Conditions**

**Issue Date: 8/21/2007
Effective Date: 8/21/2007**

FINAL PERMIT TO INSTALL 02-22720

Application Number: 02-22720
Facility ID: 0238000165
Permit Fee: **\$800**
Name of Facility: Schlabach Woodworks
Person to Contact: David Schlabach
Address: 6660 State Rte 241
Millersburg, OH 44654

Location of proposed air contaminant source(s) [emissions unit(s)]:
**6660 State Rte 241
Millersburg, Ohio**

Description of proposed emissions unit(s):
2 diesel fired engines.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Chris Korleski
Director

Schlabach Woodworks
PTI Application: 02-22720
Issued: 8/21/2007

Facility ID: 0238000165

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted (i.e., postmarked) quarterly by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon

Schlabach Woodworks
PTI Application: 02-22720
Issued: 8/21/2007

Facility ID: 0238000165

the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

Schlabach Woodworks
PTI Application: 02-22720
Issued: 8/21/2007

Facility ID: 0238000165

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

Schlabach Woodworks
 PTI Application: 02-22720
 Issued: 8/21/2007

Facility ID: 0238000165

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
 TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
NOx	24.99
CO	5.39
SOx	1.65
OC	2.01
PE	1.77

7

Schlabach Woodworks
PTI Application: 02-22720
Issued: 8/21/2007

Facility ID: 0238000165

Issued: 8/21/2007

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P003) - 160 HP Perkins stationary diesel engine

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(A)(3)	<p>0.35 lb/hr and 0.66 TPY of particulate emissions (PE)/PM less than 10 microns in diameter (PM-10).</p> <p>0.33 lb/hr and 0.62 TPY of sulfur dioxide (SO₂). Also includes B.1 below.</p> <p>4.96 lbs/hr of nitrogen dioxides (NO_x).</p> <p>0.40 lb/hr and 0.75 TPY of organic compounds (OC).</p> <p>1.07 lb/hr and 2.01 TPY of carbon monoxide (CO).</p> <p>Visible particulate emissions from the stack serving this emissions unit shall not exceed 10% opacity, as a six-minute average.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-11(B)(5)(a).</p>
OAC rule 3745-17-11(B)(5)(a)	0.310 lb/mmBtu of particulate emissions.
OAC rule 3745-17-07(A)(1)	The opacity limitation specified in this rule is less stringent than the limit established pursuant to OAC rule 3745-31-05(A)(3).
OAC rule 3745-18-06(G)	This emissions unit is exempt from the requirements of OAC rule 3745-18-06 pursuant to OAC rule 3745-18-06(B).
OAC rule 3745-31-05(C) (State Synthetic Minor to avoid modeling)	<p>9.30 TPY of nitrogen dioxides (NO_x).</p> <p>See B.2 below.</p>

Issued: 8/21/2007

2. Additional Terms and Conditions

- 2.a** In accordance with OAC rule 3745-31-05(A)(3), best available technology for this emissions unit includes the emission limitations and fuel sulfur content restriction.

B. Operational Restrictions

1. The permittee shall use only diesel fuel/number 2 fuel oil with a maximum sulfur content of 0.5 percent, by weight, for combustion in this emissions unit.
2. The maximum operating hours for this emissions unit shall not exceed 72.1 hours per week and 3750 hours per year.

C. Monitoring and/or Recordkeeping Requirements

1. For each day during which the permittee burns a fuel other than diesel fuel, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.
2. The permittee shall maintain documentation of the sulfur content of all fuels received.
3. The permittee shall maintain weekly records of the operating hours for this emissions unit.

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify each day during which a fuel other than diesel fuel with a maximum sulfur content of 0.5 percent by weight was burned in this emissions unit and any corrective action(s) that were taken. Each report shall be submitted to the Ohio EPA Northeast District Office within 30 days of the deviation.
2. The permittee shall submit annual reports by January 31 of each year that include the total annual operating hours for the previous calendar year, as a summation of the weekly records kept according to C.3 above.

The reports contained in this permit shall be submitted in accordance with the reporting requirements specified in Part 1 - General Terms and Conditions, Section A of this permit.

Emissions Unit ID: P003

E. Testing Requirements

1. Compliance with the emission limitations specified in section A.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation:
0.35 lb/hr of PM/PM-10

Applicable Compliance Method:

If required, compliance shall be demonstrated based upon an emission test performed in accordance with the procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 5.

- b. Emission Limitation:
0.66 TPY of PM/PM-10

Applicable Compliance Method:

The ton per year (tpy) emission limitation was developed by multiplying the short-term allowable particulate emission limitation (0.35 lb/hr) by the maximum allowable hours of operation (3,750 hours), and then dividing by 2,000 lbs per ton. Therefore, if compliance is shown with the short-term allowable emission limitation, compliance shall also be shown with the annual emission limitation.

- c. Emission Limitation:
0.33 lb/hr of SO₂

Applicable Compliance Method:

Compliance with the hourly emission limitation above shall be determined by multiplying 0.00205 lb/hp-hr, emission factor for SO_x emission from AP-42, Table 3.3-1 (10/96), by 160 hp, the power output rating of this unit.

- d. Emission Limitation:
0.62 TPY of SO₂

Applicable Compliance Method:

The tpy emission limitation was developed by multiplying the short-term allowable SO₂ emission limitation (0.33 lb/hr) by the maximum allowable hours of operation (3,750 hours), and then dividing by 2,000 lbs per ton. Therefore, if compliance is shown with the short-term allowable emission limitation,

Emissions Unit ID: P003

compliance shall also be shown with the annual emission limitation.

- e. Emission Limitation:
4.96 lbs/hr of NO_x

Applicable Compliance Method:

Compliance with the hourly emission limitation above shall be determined by multiplying 0.031 lb/hp-hr, emission factor for NO_x emission from AP-42, Table 3.3-1 (10/96), by 160 hp, the power output rating of this unit.

- f. Emission Limitation:
9.30 TPY of NO_x

Applicable Compliance Method:

The tpy emission limitation was developed by multiplying the short-term allowable NO_x emission limitation (4.96 lbs/hr) by the maximum allowable hours of operation (3,750 hours), and then dividing by 2,000 lbs per ton. Therefore, if compliance is shown with the short-term allowable emission limitation, compliance shall also be shown with the annual emission limitation.

- g. Emission Limitation:
0.40 lb/hr of OC

Applicable Compliance Method:

Compliance with the hourly emission limitation above shall be determined by multiplying 0.00251 lb/hp-hr, the emission factor from AP-42, Table 3.3-1 (10/96), by 160 hp, the power output rating of this unit.

- h. Emission Limitation:
0.75 TPY of OC

Applicable Compliance Method:

The tpy emission limitation was developed by multiplying the short-term allowable OC emission limitation (0.31 lb/hr) by the maximum allowable hours of operation (3,750 hours), and then dividing by 2,000 lbs per ton. Therefore, if compliance is shown with the short-term allowable emission limitation, compliance shall also be shown with the annual emission limitation.

- i. Emission Limitation:
1.07 lb/hr of CO

Issued: 8/21/2007

Applicable Compliance Method:

Compliance with the hourly emission limitation above shall be determined by multiplying 0.00668 lb/hp-hr, the emission factor from AP-42, Table 3.3-1 (10/96), by 160 hp, the power output rating of this unit.

- j. Emission Limitation:
2.01 TPY of CO

Applicable Compliance Method:

The tpy emission limitation was developed by multiplying the short-term allowable OC emission limitation (1.07 lb/hr) by the maximum allowable hours of operation (3,750 hours), and then dividing by 2,000 lbs per ton. Therefore, if compliance is shown with the short-term allowable emission limitation, compliance shall also be shown with the annual emission limitation.

- k. Emission Limitation:
10% opacity, as a 6-minute average

Applicable Compliance Method:

If required, compliance with the visible particulate emission limitation shall be demonstrated based upon the visible emission observations performed in accordance with the procedures specified in 40 CFR Part 60, Appendix A, Method 9.

- l. Emission Limitation:
0.310 lb/mmBtu of particulate emissions

Emissions Unit ID: P003

Applicable Compliance Method:

Compliance with the short term emission limitation above may be determined by the following equation:

$$(0.0022 \text{ lb/hp-hr}) / (\text{hp-hr}/7000 \text{ Btu}) * (10^6 \text{ Btu/mmBtu})$$

where:

0.0022 lb/hp-hr, the emission factor from AP-42, Table 3.3-1 (10/96).

If required, compliance shall be demonstrated based upon an emission test performed in accordance with the procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 5.

F. Miscellaneous Requirements

None

Issued: 8/21/2007

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P004) - 270 HP Detron stationary diesel engine

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(A)(3)	<p>0.59 lb/hr and 1.11 TPY of particulate emissions (PE)/PM less than 10 microns in diameter (PM-10).</p> <p>0.55 lb/hr and 1.03 TPY of sulfur dioxide (SO₂). Also includes B.1 below.</p> <p>8.37 lbs/hr of nitrogen dioxides (NO_x).</p> <p>0.67 lb/hr and 1.26 TPY of organic compounds (OC).</p> <p>1.80 lb/hr and 3.38 TPY of carbon monoxide (CO).</p> <p>Visible particulate emissions from the stack serving this emissions unit shall not exceed 10% opacity, as a six-minute average.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-11(B)(5)(a).</p>
OAC rule 3745-17-11(B)(5)(a)	0.310 lb/mmBtu of particulate emissions.
OAC rule 3745-17-07(A)(1)	The opacity limitation specified in this rule is less stringent than the limit established pursuant to OAC rule 3745-31-05(A)(3).
OAC rule 3745-18-06(G)	This emissions unit is exempt from the requirements of OAC rule 3745-18-06 pursuant to OAC rule 3745-18-06(B).
OAC rule 3745-31-05(C) (State Synthetic Minor to avoid modeling)	<p>15.69 TPY of nitrogen dioxides (NO_x).</p> <p>See B.2 below.</p>

Issued: 8/21/2007

2. Additional Terms and Conditions

2.a In accordance with OAC rule 3745-31-05(A)(3), best available technology for this emissions unit includes the emission limitations and fuel sulfur content restriction.

B. Operational Restrictions

1. The permittee shall use only diesel fuel/number 2 fuel oil with a maximum sulfur content of 0.5 percent, by weight, for combustion in this emissions unit.
2. The maximum operating hours for this emissions unit shall not exceed 72.1 hours per week and 3,750 hours per year.

C. Monitoring and/or Recordkeeping Requirements

1. For each day during which the permittee burns a fuel other than diesel fuel, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.
2. The permittee shall maintain documentation of the sulfur content of all fuels received.
3. The permittee shall maintain weekly records of the operating hours for this emissions unit.

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify each day during which a fuel other than diesel fuel with a maximum sulfur content of 0.5 percent by weight was burned in this emissions unit and any corrective action(s) that were taken. Each report shall be submitted to the Ohio EPA Northeast District Office within 30 days of the deviation.
2. The permittee shall submit annual reports by January 31 of each year that include the total annual operating hours for the previous calendar year, as a summation of the weekly records kept according to C.3 above.

The reports contained in this permit shall be submitted in accordance with the reporting requirements specified in Part 1 - General Terms and Conditions, Section A of this permit.

E. Testing Requirements

1. Compliance with the emission limitations specified in section A.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation:
0.59 lb/hr of PM/PM-10

Applicable Compliance Method:

If required, compliance shall be demonstrated based upon an emission test performed in accordance with the procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 5.

- b. Emission Limitation:
1.11 TPY of PM/PM-10

Applicable Compliance Method:

The tpy emission limitation was developed by multiplying the short-term allowable particulate emission limitation (0.59 lb/hr) by the maximum allowable hours of operation (3,750 hours), and then dividing by 2,000 lbs per ton. Therefore, if compliance is shown with the short-term allowable emission limitation, compliance shall also be shown with the annual emission limitation.

- c. Emission Limitation:
0.55 lb/hr of SO₂

Applicable Compliance Method:

Compliance with the hourly emission limitation above shall be determined by multiplying 0.00205 lb/hp-hr, emission factor for SO_x emission from AP-42, Table 3.3-1 (10/96), by 270 hp, the power output rating of this unit.

- d. Emission Limitation:
1.03 TPY of SO₂

Applicable Compliance Method:

The tpy emission limitation was developed by multiplying the short-term allowable SO₂ emission limitation (0.0.55 lb/hr) by the maximum allowable hours of operation (3,750 hours), and then dividing by 2,000 lbs per ton. Therefore, if compliance is shown with the short-term allowable emission

Emissions Unit ID: **P004**

limitation, compliance shall also be shown with the annual emission limitation.

- e. Emission Limitation:
8.37 lbs/hr of NO_x

Applicable Compliance Method:

Compliance with the hourly emission limitation above shall be determined by multiplying 0.031 lb/hp-hr, emission factor for NO_x emission from AP-42, Table 3.3-1 (10/96), by 270 hp, the power output rating of this unit.

- f. Emission Limitation:
15.69 TPY of NO_x

Applicable Compliance Method:

The tpy emission limitation was developed by multiplying the short-term allowable NO_x emission limitation (8.37 lbs/hr) by the maximum allowable hours of operation (3,750 hours), and then dividing by 2,000 lbs per ton. Therefore, if compliance is shown with the short-term allowable emission limitation, compliance shall also be shown with the annual emission limitation.

- g. Emission Limitation:
0.67 lb/hr of OC

Applicable Compliance Method:

Compliance with the hourly emission limitation above shall be determined by multiplying 0.00251 lb/hp-hr, the emission factor from AP-42, Table 3.3-1 (10/96), by 270 hp, the power output rating of this unit.

- h. Emission Limitation:
1.26 TPY of OC

Applicable Compliance Method:

The tpy emission limitation was developed by multiplying the short-term allowable OC emission limitation (0.31 lb/hr) by the maximum allowable hours of operation (3,750 hours), and then dividing by 2,000 lbs per ton. Therefore, if compliance is shown with the short-term allowable emission limitation, compliance shall also be shown with the annual emission limitation.

- i. Emission Limitation:
1.80 lb/hr of CO

Issued: 8/21/2007

Applicable Compliance Method:

Compliance with the hourly emission limitation above shall be determined by multiplying 0.00668 lb/hp-hr, the emission factor from AP-42, Table 3.3-1 (10/96), by 270 hp, the power output rating of this unit.

- j. Emission Limitation:
3.38 TPY of CO

Applicable Compliance Method:

The tpy emission limitation was developed by multiplying the short-term allowable OC emission limitation (1.80 lb/hr) by the maximum allowable hours of operation (3,750 hours), and then dividing by 2,000 lbs per ton. Therefore, if compliance is shown with the short-term allowable emission limitation, compliance shall also be shown with the annual emission limitation.

- k. Emission Limitation:
10% opacity, as a 6-minute average from the stack

Applicable Compliance Method:

If required, compliance with the visible particulate emission limitation shall be demonstrated based upon the visible emission observations performed in accordance with the procedures specified in 40 CFR Part 60, Appendix A, Method 9.

- l. Emission Limitation:
0.310 lb/mmBtu of particulate emissions

Schlabach Woodworks

DTI Application: 02-22720

Facility ID: 0238000165Emissions Unit ID: **P004**

Applicable Compliance Method:

Compliance with the short term emission limitation above may be determined by the following equation:

$$(0.0022 \text{ lb/hp-hr}) / (\text{hp-hr}/7000 \text{ Btu}) * (10^6 \text{ Btu/mmBtu})$$

where:

0.0022 lb/hp-hr, the emission factor from AP-42, Table 3.3-1 (10/96).

If required, compliance shall be demonstrated based upon an emission test performed in accordance with the procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 5.

F. Miscellaneous Requirements

None

Emissions Unit ID: P004

SIC CODE 2541 SCC CODE 20200102 EMISSIONS UNIT ID P003
 EMISSIONS UNIT DESCRIPTION 160 HP Perkins stationary diesel engine
 DATE INSTALLED 7/96

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	Attainment	0.35 lb/hr	0.5 tpy	0.31 lb/MMBtu 0.35 lb/hr	0.66 tpy
PM ₁₀	Attainment	0.35 lb/hr	0.5 tpy	0.31 lb/MMBtu 0.35 lb/hr	0.66 tpy
Sulfur Dioxide	attainment	0.33 lb/hr	0.5 tpy	0.33 lb/hr	0.62 tpy
Organic Compounds	attainment	0.40 lb/hr	0.75 tpy	0.40 lb/hr	0.75 tpy
Nitrogen Oxides	attainment	4.96 lbs/hr	7.7 tpy	4.96 lbs/hr	9.30 tpy
Carbon Monoxide	attainment	1.07 lb/hr	1.7 tpy	1.07 lb/hr	2.01 tpy
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? _____ NESHAP? _____ PSD? _____ OFFSET POLICY? _____

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

**0.31 lb/MMBtu PE/PM-10 - basis compliance with 17-11
 4.96 lbs/hr NOx, 1.07 lb/hr & 2.01 tpy CO; 0.35 lb/hr & 0.66 tpy PE; 0.33 lb/hr & 0.62 tpy SOx; 0.40 lb/hr & 0.75 tpy VOC - basis 3750 hrs/yr operation of source times AP-42 factors**

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? no
 OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ _____

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES _____ NO

IDENTIFY THE AIR CONTAMINANTS: _____

Schlabach Woodworks
PTI Application: 02-22720
Issued: 8/21/2007

Facility ID: 0238000165

Emissions Unit ID: **P004**

SIC CODE 2541 SCC CODE 20200102 EMISSIONS UNIT ID P004
 EMISSIONS UNIT DESCRIPTION 270 HP Detron stationary diesel engine
 DATE INSTALLED 7/98

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	Attainment	0.59 lb/hr	1.11 tpy	0.31 lb/MMBtu 0.59 lb/hr	1.11 tpy
PM ₁₀	Attainment	0.59 lb/hr	1.11 tpy	0.31 lb/MMBtu 0.59 lb/hr	1.11 tpy
Sulfur Dioxide	attainment	0.55 lb/hr	0.85 tpy	0.55 lb/hr	1.03 tpy
Organic Compounds	attainment	0.67 lb/hr	1.04 tpy	0.67 lb/hr	1.26 tpy
Nitrogen Oxides	attainment	8.37 lb/hr	13.0 tpy	8.37 lbs/hr	15.69 tpy
Carbon Monoxide	attainment	1.80 lb/hr	2.8 tpy	1.80 lb/hr	3.38 tpy
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? _____ NESHAP? _____ PSD? _____ OFFSET POLICY? _____

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

0.31 lb/MMBtu PE/PM-10 - basis compliance with 17-11
8.37 lb/hr NOx; 1.80 lb/hr & 3.38 tpy CO; 0.59 lb/hr & 1.11 tpy PE; 0.55 lb/hr & 1.03tpy SOx; 0.67 lb/hr & 1.26 tpy OC - basis 3750 hrs/yr operation of source times AP-42 factors

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? no
 OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ _____

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES _____ NO

IDENTIFY THE AIR CONTAMINANTS: _____