



Environmental Protection Agency

John R. Kasich, Governor
Mary Taylor, Lt. Governor
Scott J. Nally, Director

4/28/2011

Beth Mowrey
Shelly Materials Plant #92
The Shelly Company
PO Box 266
Thornville, OH 43076

RE: FINAL AIR POLLUTION PERMIT-TO-INSTALL AND OPERATE

Facility ID: 0125041880
Permit Number: P0107956
Permit Type: Renewal
County: Franklin

Certified Mail

No	TOXIC REVIEW
No	PSD
No	SYNTHETIC MINOR TO AVOID MAJOR NSR
No	CEMS
No	MACT/GACT
No	NSPS
No	NESHAPS
No	NETTING
No	MAJOR NON-ATTAINMENT
No	MODELING SUBMITTED
Yes	SYNTHETIC MINOR TO AVOID TITLE V
Yes	FEDERALLY ENFORCABLE PTIO (FEPTIO)

Dear Permit Holder:

Enclosed please find a final Air Pollution Permit-to-Install and Operate (PTIO) which will allow you to install, modify, and/or operate the described emissions unit(s) in the manner indicated in the permit. Because this permit contains conditions and restrictions, please read it very carefully. Please complete a survey at www.epa.ohio.gov/dapc/permitsurvey.aspx and give us feedback on your permitting experience. We value your opinion.

The issuance of this PTI is a final action of the Director and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. The appeal must be filed with the Commission within thirty (30) days after notice of the Director's action. The appeal must be accompanied by a filing fee of \$70.00, made payable to "Ohio Treasurer Josh Mandel," which the Commission, in its discretion, may reduce if by affidavit you demonstrate that payment of the full amount of the fee would cause extreme hardship. Notice of the filing of the appeal shall be filed with the Director within three (3) days of filing with the Commission. Ohio EPA requests that a copy of the appeal be served upon the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, OH 43215

If you have any questions, please contact Ohio EPA DAPC, Central District Office at (614)728-3778 or the Office of Compliance Assistance and Pollution Prevention at (614) 644-3469. This permit can be accessed electronically on the DAPC Web page, www.epa.ohio.gov/dapc, by clicking the "Issued Air Pollution Control Permits" link.

Sincerely,

Michael W. Ahern, Manager

Permit Issuance and Data Management Section, DAPC

Cc: Ohio EPA-CDO



FINAL

**Division of Air Pollution Control
Permit-to-Install and Operate
for
Shelly Materials Plant #92**

Facility ID:	0125041880
Permit Number:	P0107956
Permit Type:	Renewal
Issued:	4/28/2011
Effective:	4/28/2011
Expiration:	4/28/2016



Division of Air Pollution Control
Permit-to-Install and Operate
for
Shelly Materials Plant #92

Table of Contents

Authorization 1
A. Standard Terms and Conditions 3
1. What does this permit-to-install and operate ("PTIO") allow me to do?..... 4
2. Who is responsible for complying with this permit? 4
3. What records must I keep under this permit? 4
4. What are my permit fees and when do I pay them?..... 4
5. When does my PTIO expire, and when do I need to submit my renewal application? 4
6. What happens to this permit if my project is delayed or I do not install or modify my source? 5
7. What reports must I submit under this permit? 5
8. If I am required to obtain a Title V operating permit in the future, what happens to the operating provisions and PER obligations under this permit? 5
9. What are my obligations when I perform scheduled maintenance on air pollution control equipment? ... 5
10. Do I have to report malfunctions of emissions units or air pollution control equipment? If so, how must I report? 6
11. Can Ohio EPA or my local air agency inspect the facility where the emission unit(s) is/are located? 6
12. What happens if one or more emissions units operated under this permit is/are shut down permanently? 6
13. Can I transfer this permit to a new owner or operator?..... 7
14. Does compliance with this permit constitute compliance with OAC rule 3745-15-07, "air pollution nuisance"? 7
15. What happens if a portion of this permit is determined to be invalid? 7
B. Facility-Wide Terms and Conditions..... 8
C. Emissions Unit Terms and Conditions 10
1. P901, Plant #92 11

Authorization

Facility ID: 0125041880
Application Number(s): M0001218
Permit Number: P0107956
Permit Description: Admin mod to allow the use of shingles
Permit Type: Renewal
Permit Fee: \$0.00
Issue Date: 4/28/2011
Effective Date: 4/28/2011
Expiration Date: 4/28/2016
Permit Evaluation Report (PER) Annual Date: July 1 - June 30, Due Aug 15

This document constitutes issuance to:

Shelly Materials Plant #92
2280 Dublin Road
Columbus, OH 43228

of a Permit-to-Install and Operate for the emissions unit(s) identified on the following page.


Ohio EPA District Office or local air agency responsible for processing and administering your permit:

Ohio EPA DAPC, Central District Office
50 West Town Street, 6th Floor
P.O. Box 1049
Columbus, OH 43216-1049
(614)728-3778

The above named entity is hereby granted this Permit-to-Install and Operate for the air contaminant source(s) (emissions unit(s)) listed in this section pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the described emissions unit(s) will operate in compliance with applicable State and federal laws and regulations.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency


Scott J. Nally
Director

Authorization (continued)

Permit Number: P0107956
Permit Description: Admin mod to allow the use of shingles

Permits for the following Emissions Unit(s) or groups of Emissions Units are in this document as indicated below:

Emissions Unit ID:	P901
Company Equipment ID:	Plant #92 Batch Plt
Superseded Permit Number:	01-01342
General Permit Category and Type:	Not Applicable

A. Standard Terms and Conditions

1. What does this permit-to-install and operate ("PTIO") allow me to do?

This permit allows you to install and operate the emissions unit(s) identified in this PTIO. You must install and operate the unit(s) in accordance with the application you submitted and all the terms and conditions contained in this PTIO, including emission limits and those terms that ensure compliance with the emission limits (for example, operating, recordkeeping and monitoring requirements).

2. Who is responsible for complying with this permit?

The person identified on the "Authorization" page, above, is responsible for complying with this permit until the permit is revoked, terminated, or transferred. "Person" means a person, firm, corporation, association, or partnership. The words "you," "your," or "permittee" refer to the "person" identified on the "Authorization" page above.

The permit applies only to the emissions unit(s) identified in the permit. If you install or modify any other equipment that requires an air permit, you must apply for an additional PTIO(s) for these sources.

3. What records must I keep under this permit?

You must keep all records required by this permit, including monitoring data, test results, strip-chart recordings, calibration data, maintenance records, and any other record required by this permit for five years from the date the record was created. You can keep these records electronically, provided they can be made available to Ohio EPA during an inspection at the facility. Failure to make requested records available to Ohio EPA upon request is a violation of this permit requirement.

4. What are my permit fees and when do I pay them?

There are two fees associated with permitted air contaminant sources in Ohio:

- PTIO fee. This one-time fee is based on a fee schedule in accordance with Ohio Revised Code (ORC) section 3745.11, or based on a time and materials charge for permit application review and permit processing if required by the Director.

You will be sent an invoice for this fee after you receive this PTIO and payment is due within 30 days of the invoice date. You are required to pay the fee for this PTIO even if you do not install or modify your operations as authorized by this permit.

- Annual emissions fee. Ohio EPA will assess a separate fee based on the total annual emissions from your facility. You self-report your emissions in accordance with Ohio Administrative Code (OAC) Chapter 3745-78. This fee assessed is based on a fee schedule in ORC section 3745.11 and funds Ohio EPA's permit compliance oversight activities. Unless otherwise specified, facilities subject to one or more synthetic minor restrictions must use Ohio EPA's "Air Services" to submit annual emissions associated with this permit requirement. Ohio EPA will notify you when it is time to report your emissions and to pay your annual emission fees.

5. When does my PTIO expire, and when do I need to submit my renewal application?

This permit expires on the date identified at the beginning of this permit document (see "Authorization" page above) and you must submit a renewal application to renew the permit. Ohio EPA will send a renewal notice to you approximately six months prior to the expiration date of this permit. However, it is

very important that you submit a complete renewal permit application (postmarked prior to expiration of this permit) even if you do not receive the renewal notice.

If a complete renewal application is submitted before the expiration date, Ohio EPA considers this a timely application for purposes of ORC section 119.06, and you are authorized to continue operating the emissions unit(s) covered by this permit beyond the expiration date of this permit until final action is taken by Ohio EPA on the renewal application.

6. What happens to this permit if my project is delayed or I do not install or modify my source?

This PTIO expires 18 months after the issue date identified on the "Authorization" page above unless otherwise specified if you have not (1) started constructing the new or modified emission sources identified in this permit, or (2) entered into a binding contract to undertake such construction. This deadline can be extended by up to 12 months, provided you apply to Ohio EPA for this extension within a reasonable time before the 18-month period has ended and you can show good cause for any such extension.

7. What reports must I submit under this permit?

An annual permit evaluation report (PER) is required in addition to any malfunction reporting required by OAC rule 3745-15-06 or other specific rule-based reporting requirement identified in this permit. Your PER due date is identified in the Authorization section of this permit.

8. If I am required to obtain a Title V operating permit in the future, what happens to the operating provisions and PER obligations under this permit?

If you are required to obtain a Title V permit under OAC Chapter 3745-77 in the future, the permit-to-operate portion of this permit will be superseded by the issued Title V permit. From the effective date of the Title V permit forward, this PTIO will effectively become a PTI (permit-to-install) in accordance with OAC rule 3745-31-02(B). The following terms and conditions will no longer be applicable after issuance of the Title V permit: Section B, Term 1.b) and Section C, for each emissions unit, Term a)(2).

The PER requirements in this permit remain effective until the date the Title V permit is issued and is effective, and cease to apply after the effective date of the Title V permit. The final PER obligation will cover operations up to the effective date of the Title V permit and must be submitted on or before the submission deadline identified in this permit on the last day prior to the effective date of the Title V permit.

9. What are my obligations when I perform scheduled maintenance on air pollution control equipment?

You must perform scheduled maintenance of air pollution control equipment in accordance with OAC rule 3745-15-06(A). If scheduled maintenance requires shutting down or bypassing any air pollution control equipment, you must also shut down the emissions unit(s) served by the air pollution control equipment during maintenance, unless the conditions of OAC rule 3745-15-06(A)(3) are met. Any emissions that exceed permitted amount(s) under this permit (unless specifically exempted by rule) must be reported as deviations in the annual permit evaluation report (PER), including nonexempt excess emissions that occur during approved scheduled maintenance.

10. Do I have to report malfunctions of emissions units or air pollution control equipment? If so, how must I report?

If you have a reportable malfunction of any emissions unit(s) or any associated air pollution control system, you must report this to the Ohio EPA DAPC, Central District Office in accordance with OAC rule 3745-15-06(B). Malfunctions that must be reported are those that result in emissions that exceed permitted emission levels. It is your responsibility to evaluate control equipment breakdowns and operational upsets to determine if a reportable malfunction has occurred.

If you have a malfunction, but determine that it is not a reportable malfunction under OAC rule 3745-15-06(B), it is recommended that you maintain records associated with control equipment breakdown or process upsets. Although it is not a requirement of this permit, Ohio EPA recommends that you maintain records for non-reportable malfunctions.

11. Can Ohio EPA or my local air agency inspect the facility where the emission unit(s) is/are located?

Yes. Under Ohio law, the Director or his authorized representative may inspect the facility, conduct tests, examine records or reports to determine compliance with air pollution laws and regulations and the terms and conditions of this permit. You must provide, within a reasonable time, any information Ohio EPA requests either verbally or in writing.

12. What happens if one or more emissions units operated under this permit is/are shut down permanently?

Ohio EPA can terminate the permit terms associated with any permanently shut down emissions unit. "Shut down" means the emissions unit has been physically removed from service or has been altered in such a way that it can no longer operate without a subsequent "modification" or "installation" as defined in OAC Chapter 3745-31.

You should notify Ohio EPA of any emissions unit that is permanently shut down by submitting¹ a certification that identifies the date on which the emissions unit was permanently shut down. The certification must be submitted by an authorized official from the facility. You cannot continue to operate an emissions unit once the certification has been submitted to Ohio EPA by the authorized official.

You must comply with all recordkeeping and reporting for any permanently shut down emissions unit in accordance with the provisions of the permit, regulations or laws that were enforceable during the period of operation, such as the requirement to submit a PER, air fee emission report, or malfunction report. You must also keep all records relating to any permanently shutdown emissions unit, generated while the emissions unit was in operation, for at least five years from the date the record was generated.

Again, you cannot resume operation of any emissions unit certified by the authorized official as being permanently shut down without first applying for and obtaining a permit pursuant to OAC Chapter 3745-31.

¹Permittees that use Ohio EPA's "Air Services" can mark the affected emissions unit(s) as "permanently shutdown" in the facility profile along with the date the emissions unit(s) was permanently removed and/or disabled. Submitting the facility profile update will constitute notifying of the permanent shutdown of the affected emissions unit(s).

13. Can I transfer this permit to a new owner or operator?

You can transfer this permit to a new owner or operator. If you transfer the permit, you must follow the procedures in OAC Chapter 3745-31, including notifying Ohio EPA or the local air agency of the change in ownership or operator. Any transferee of this permit must assume the responsibilities of the transferor permit holder.

14. Does compliance with this permit constitute compliance with OAC rule 3745-15-07, "air pollution nuisance"?

This permit and OAC rule 3745-15-07 prohibit operation of the air contaminant source(s) regulated under this permit in a manner that causes a nuisance. Ohio EPA can require additional controls or modification of the requirements of this permit through enforcement orders or judicial enforcement action if, upon investigation, Ohio EPA determines existing operations are causing a nuisance.

15. What happens if a portion of this permit is determined to be invalid?

If a portion of this permit is determined to be invalid, the remainder of the terms and conditions remain valid and enforceable. The exception is where the enforceability of terms and conditions are dependent on the term or condition that was declared invalid.

B. Facility-Wide Terms and Conditions

1. This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).
 - a) For the purpose of a permit-to-install document, the facility-wide terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (1) None.
 - b) For the purpose of a permit-to-operate document, the facility-wide terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (1) None.

C. Emissions Unit Terms and Conditions



1. P901, Plant #92

Operations, Property and/or Equipment Description:

480 TPH Batch plant controlled by a baghouse

a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

(1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. None.

(2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

a. None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3)	<p>Carbon monoxide (CO) emissions from burning natural gas, on-spec used oil, number 2 fuel oil, number 4 fuel oil or number 6 fuel oil shall not exceed 90.0lbs/hr.</p> <p>Nitrogen Oxide (NO_x) emissions from burning on-spec used oil, number 2 fuel oil, number 4 fuel oil or number 6 fuel oil shall not exceed 21.6lbs/hr.</p> <p>NO_x emissions from burning natural gas shall not exceed 28.8lbs/hr.</p> <p>Sulfur Dioxide (SO₂) emissions from burning on-spec used oil or number 2 fuel oil shall not exceed 27.14lbs/hr.</p> <p>Sulfur Dioxide (SO₂) emissions from</p>



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		<p>burning number 4 fuel oil shall not exceed 43.43lbs/hr.</p> <p>Sulfur Dioxide (SO₂) emissions from burning number 6 fuel oil shall not exceed 54.28lbs/hr.</p> <p>SO₂ emissions from burning natural gas shall not exceed 1.66lbs/hr.</p> <p>Volatile Organic Compound (VOC) emissions from burning on-spec used oil, number 2 fuel oil, number 4 fuel oil, number 6 fuel oil or natural gas shall not exceed 16.78lbs/hr.</p> <p>Emissions of fugitive PM₁₀ shall not exceed 6.39 pound per hour.</p> <p>Fugitive particulate emissions shall not exceed 16.74 pounds per hour.</p> <p>Arsenic, cadmium, chromium, and lead emissions are limited by the fuel specifications in b)(2)b below</p> <p>Visible particulate emissions from the stack shall not exceed 20% opacity, as a 3-minute average.</p> <p>Bestavailable control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust .See section b)(2)a.</p> <p>No visible emissions of fugitive dust from the enclosures for the hot aggregate elevator.</p> <p>Visible emissions of fugitive dust (from areas other than the enclosures for the hot aggregate elevator) shall be less than or equal to 10% opacity, as a 3-minute average.</p> <p>The drop height of the front end loader bucket shall be minimized to the extent</p>



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		<p>possible in order to minimize or eliminate visible emissions of fugitive dust from the aggregate storage bins.</p> <p>The aggregate loaded into the storage bins shall have a moisture content sufficient to minimize the visible emissions of fugitive dust from conveyors and all transfer points to the dryer.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(D) and 40CFR Part 60, Subpart I.</p> <p>See b)(2)c-f below.</p>
b.	OAC rule 3745-31-05(C)	<p>Particulate emissions (PE) from the stack shall not exceed 9.14 tons per rolling 12-month period.</p> <p>PM₁₀ emissions from the stack shall not exceed 9.14 tons per rolling 12-month period.</p> <p>Fugitive PE shall not exceed 16.74 tons per rolling 12-month period.</p> <p>Fugitive PM₁₀ emissions shall not exceed 6.39 tons per rolling 12-month period.</p> <p>CO emissions shall not exceed 50.0 tons per rolling 12-month period.</p> <p>VOC emissions shall not exceed 30.0 tons per rolling 12-month period.</p> <p>SO₂ emissions shall not exceed 30.1 tons per rolling 12-month period.</p> <p>NO_x emissions shall not exceed 16.0 tons per rolling 12-month period.</p> <p>Fugitive emissions from drum mix load out operations (hot side) shall not exceed 0.83 ton VOC per rolling 12-month period and 0.27 ton CO per rolling 12-month period.</p>



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		Fugitive emissions from the silo filling operations (hot side) shall not exceed 2.44 tons VOC per rolling 12-month period and 0.24 ton CO per rolling 12-month period.
c.	OAC rule 3745-17-07(A)(1) OAC rule 3745-17-11(B)(1) OAC rule 3745-18-06(E)	The emissions limitations specified by these rules are less stringent than the emission limitations established pursuant to OAC rule 3745-31-05(A)(3).
d.	40 CFR Part 60, Subpart I	PE from the stack shall not exceed 0.04 gr/dscf when burning on-spec used oil, number 2 fuel oil, or natural gas.

(2) Additional Terms and Conditions

- a. The permittee shall ensure that the baghouse is operated with sufficient air volume to minimize or eliminate visible fugitive emissions from the rotary drum.
- b. All used oil burned in this emissions unit shall be “on-specification” (on-spec) oil and must meet the used oil fuel specifications contained in OAC rule 3745-279-11, which restricts the used oil to the following limitations:

Contaminant/Property	Allowable Specifications
arsenic	5 ppm, maximum
cadmium	2 ppm, maximum
chromium	10 ppm, maximum
total halogens	4,000 ppm maximum
lead	100 ppm, maximum
flash point	100°F, minimum

and shall also not exceed the following maximum PCB and mercury limitations nor fall below the following heating value:

heat content	135,000 Btu/gallon, minimum
PCB's	50 ppm, maximum



mercury	1 ppm, maximum
---------	----------------

Used oil containing 1,000 ppm or greater total halogens is presumed to be a hazardous waste under the rebuttable presumption provided under paragraph (B)(1) of rule 3745-279-10 of the Administrative Code. The permittee may receive and burn used oil equaling or exceeding 1,000 ppm total halogens, but less than 4,000 ppm, only if the permittee has successfully demonstrated, pursuant to OAC rule 3745-279-63, that the used oil does not contain a listed hazardous waste, by either acquiring and maintaining source process information which demonstrates that the used oil was contaminated by halogenated constituents that would not be listed hazardous waste or by demonstrating that the used oil does not contain significant concentrations of halogens by acquiring and maintaining representative analytical data. Acceptable analytical test protocols that can be used to analyze used oil for halogenated hazardous constituents include SW-846 Test Methods 9075, 9076, and 9077.*

If analytical results demonstrate that used oil containing 1,000 ppm or more total halogens, but less than 4,000 total halogens, does not contain greater than 100 ppm of any individual halogenated hazardous constituent found in the F001 and F002 listings in OAC rule 3745-51-31 and there is no information suggesting that any other halogenated hazardous constituent (e.g., chlorinated pesticides) has come in contact with the oil, then the presumption that the oil contains hazardous waste has been successfully rebutted.** The rebuttable presumption does not apply to either metal working oils/fluids containing chlorinated paraffins, if processed through a tolling arrangement as described in OAC rule 3745-279-24(C), or used oils contaminated with chlorofluorocarbons removed from refrigeration units.

The burning of used oil not meeting the above limitations is prohibited in this emissions unit and the fuel oil analyses shall document compliance with each limitation before it is burned. The management and burning of used oil is subject to the Standards for the Management of Used Oil, OAC Chapter 3745-279, and the permittee shall document and assure that used oils burned in this emissions unit meet all of the applicable requirements of this Chapter. If the used oil analyses shows total halogens of 1,000 ppm or greater, the permittee shall obtain and maintain all the necessary records to successfully rebut the presumption that the used oil contains or has been mixed with a listed hazardous waste in accordance with this permit.

*EPA publication SW-846, 3rd (or most current) edition, is available from the Government Printing Office, P.O. Box 371954, Pittsburgh, PA 15250-7954; 202/512-1800, document number 955-001-00000-1.

**DHWM policy documented in "Used Oil Burners - New Guidance for Rebuttable Presumption", published April 2008 or most current policy

- c. All number 2 and on-spec used oil burned in this emission unit shall have a sulfur content equal to or less than 0.5%.

- d. All number 4 oil burned in this emission unit shall have a sulfur content equal to or less than 0.8%.
 - e. All number 6 oil burned in this emission unit shall have a sulfur content equal to or less than 1.0%.
 - f. The following material handling operations are covered by this permit and subject to the above-mentioned requirements: vibrating screens, conveyor transferpoints, elevators, storage bin and weigh hopper loading, silo filling, and drum mix load-out operations.
- c) Operational Restrictions
- (1) The pressure drop across the fabric filter shall be maintained within the range of 1 to 8 inches of water while the emissions unit is in operation.
 - (2) The permittee may not receive or burn any on-spec used oil which does not meet the specifications listed in b)(2)b of this permit without first obtaining a permit to install that authorizes the burning of such off-specification used oil. The burning of off-specification used oil is subject to OAC rule 3745-279-60 through 67.
 - (3) The maximum annual asphalt production rate for this emissions unit shall not exceed 400,000 tons per year, based upon a rolling, 12-month summation of the production rates. The company has existing records for the current operational location such that the applicant does not need to be restricted to first year monthly asphalt production.
 - (4) The permittee shall operate and maintain the fuel burner in accordance with the manufacturer's recommendations to ensure efficient combustion of the fuel(s) and to ensure compliance with the applicable emission limitations for VOC, CO and NOx. The permittee shall submit a copy of all *Burner Tuning Reporting Form for Asphalt Concrete Plants* forms produced during the past calendar year to the appropriate Ohio EPA District Office or local air agency responsible for the permitting of the facility with the PER.
 - (5) The permittee may substitute reclaimed asphalt pavement (RAP) or shingles in the raw material feed mix in amounts not to exceed 50 percent of all aggregate materials.
 - (6) Asphalt shingles removed from buildings (tear-off material) may be used but only if has been determined that they do not contain asbestos. Verification that the shingles do not contain asbestos can either be done by actual testing of a representative sample of the shingles, or by verification from the shingle supplier that the shingles do not contain asbestos. Records shall be kept documenting the asbestos verification of any shingles used in the feed mix consistent with the language requirements in the standard terms and conditions.
 - (7) The permittee shall only burn natural gas, #2 fuel oil, #4 fuel oil, #6 fuel oil and/or on-spec used oil in this emissions unit. In order to use a fuel on an ongoing basis, the permittee shall complete the emissions testing for that fuel as specified in this PTIO.

d) **Monitoring and/or Recordkeeping Requirements**

- (1) The permittee shall receive and maintain the chemical analyses from the supplier/marketer for each shipment of used oil burned in this emissions unit, which shall contain the following information:
- a. the date the used oil was received at the facility;
 - b. the name, address, and U.S. EPA identification number (if applicable) of the generator, transporter, processor/re-finer, supplier, and/or marketer;
 - c. the results of the chemical analyses demonstrating the used oil meets the standards in OAC rule 3745-279-11, including:
 - i. arsenic content, in ppm;
 - ii. the cadmium content, in ppm;
 - iii. the chromium content, in ppm;
 - iv. the lead content, in ppm;
 - v. total halogens, in ppm; and
 - vi. the flash point
 - d. the analysis demonstrating that the used oil has a total halogen content below 1,000 ppm, or below 4,000 ppm with the demonstration for the rebuttal of the presumption that the oil is hazardous waste or has been mixed with hazardous waste, as described in OAC paragraph 3745-279-63(B); and
 - e. the results of the analyses demonstrating that the used oil meets the heating value and mercury and PCB limitations contained in this permit.

The metal contents for arsenic, cadmium, chromium, lead, and mercury shall be analyzed using a "Totals Analysis" or Total Metals" testing methodology, Chapter Two of "Testing Methods for Evaluating Solid Waste, Physical/Chemical Methods (SW-846)" should be referenced to for selecting appropriate test methods for the used oil analyses. Under no circumstances shall the metal contents of the used oil be analyzed using "TCLP", "EP-TOC", or other similar testing procedures, since these tests were developed to gauge leachate mobility from a landfill, of which is an irrelevant property of the used oil burned for energy recovery.

Each analysis shall be kept in a readily accessible location for a period of not less than 5 years following the receipt of each shipment of used oil and shall be made available to the Ohio EPA Division of Hazardous Waste Management and/or the Division of Air Pollution Control (the appropriate Ohio EPA District Office or local air agency) upon verbal or written request. Any authorized representative of the Ohio EPA may sample or require sampling of any used oil shipments received, stored, or burned by/at this facility for periodic detailed chemical analyses, through an independent laboratory.

(2) The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the fabric filter while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the fabric filter on daily basis.

(3) The permittee shall maintain monthly records of the following information:

- a. The asphalt production for each month;
- b. The rolling, 12-month summation of the asphalt production; and
- c. The maximum percentage RAP used for any mix.

(4) For each shipment of number 2 fuel oil, number 4 fuel oil, number 6 fuel oil and on-spec used oil received for burning in this emissions unit, the permittee shall maintain records of the total quantity of oil received and the permittees or oil supplier's analyses for sulfur content and heat content.

(5) The permittee shall perform daily visible emission checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the enclosures for the hot aggregate elevator, vibrating screens and weigh hopper servicing this emissions unit. If visible particulate emissions are observed, the permittee shall note the following in the operation log:

- a. The color of the visible particulate emissions;
- b. The cause of the visible particulate emissions;
- c. The total duration of the visible particulate emission incident; and
- d. Corrective actions taken to eliminate the visible particulate emissions.

The permittee may, upon receipt of written approval from the Ohio EPA, Central District Office, modify the above-mentioned visible particulate emissions check frequency if operating experience indicates that less frequent checks would be sufficient to ensure compliance with the visible particulate emissions requirements.

(6) The permittee shall perform daily visible emission checks, when the emissions unit is in operation and when the weather conditions allow, for any abnormal visible particulate emissions from the stack, aggregate storage bins and cold aggregate elevator/conveyor serving this emissions unit. If abnormal visible emissions are observed, the permittee shall note the following in the operation log:

- a. The color of the abnormal visible particulate emissions;
- b. The cause of the abnormal visible particulate emissions;

- c. The total duration of any abnormal visible particulate emissions incident; and
- d. Any corrective actions taken to eliminate the abnormal visible particulate emissions.

The permittee may, upon receipt of written approval from the Ohio EPA, Central District Office modify the above-mentioned visible particulate emissions check frequency if operating experience indicates that less frequent checks would be sufficient to ensure compliance with the visible particulate emissions requirements.

- (7) While performing each burner tuning, the permittee shall record the results of the burner tuning using the *Burner Tuning Reporting Form for Asphalt Concrete Plants* form (as found in g)(3)). An alternative form may be used upon approval of the Ohio EPA, Central District Office.
 - (8) For each day during which the permittee uses any raw material that is not specifically identified in the EAC form submitted on April 25th, 2011 without prior approval from Ohio EPA, the permittee shall maintain a record of the type and quantity of raw material employed in this emissions unit.
 - (9) The permittee shall maintain documentation verifying that any shingles employed do not contain asbestos as described in c)(6).
 - (10) Modeling to demonstrate compliance with, the "Toxic Air Contaminant Statute", ORC 3704.03(F)(4)(b), was not necessary because the emissions unit's maximum annual emissions for each toxic air contaminant, as defined in OAC rule 3745-114-01, will be less than 1.0 ton per year. OAC Chapter 3745-31 requires permittees to apply for and obtain a new or modified PTIO prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that changes in the composition of the material, or use of new materials, that would cause the emissions of any toxic air contaminant to increase to above 1.0 ton per year may require the permittee to apply for and obtain a new PTIO.
- e) Reporting Requirements
- (1) The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above. These reports are due by the date described in Part A Standard Terms and Conditions of this permit.
 - (2) The permittee shall submit quarterly deviation (excursion) reports which identify all exceedances of the rolling 12-month asphalt production limitation. These reports are due by the date described in Part A Standard Terms and Conditions of this permit.
 - (3) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the RAP/shingle limitation specified above. These reports are due by the date described in Part A Standard Terms and Conditions of this permit.

- (4) The permittee shall submit annual reports which specify the total PM, SO₂, NO_x, VOC and CO emissions from this emissions unit for the previous calendar year. These reports shall be submitted by April 15 of each year.
- (5) The permittee shall submit quarterly reports that identify the following information concerning the quality of used oil burned in this emissions unit:
- any exceedance of the used oil standards in OAC rule 3745-279-11;
 - any occasion where used oil containing 1,000 ppm or more total halogens was burned prior to receiving information demonstrating a successful rebuttal of the presumption that the used oil contains or has been mixed with a listed hazardous waste;
 - any exceedance of the limitations for mercury and/or PCBs; and
 - any deviation from the minimum heat content of 135,000 Btu/gallon.

These reports are due by the date described in Part A Standard Terms and Conditions of this permit.

- (6) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the sulfur content limit specified above. These reports are due by the date described in Part A Standard Terms and Conditions of this permit.
- (7) The permittee shall submit quarterly deviation (excursion) reports that identify any of the following occurrences:
- Identify all days during which any abnormal visible particulate emissions were observed from the stack, aggregate storage bins and cold aggregate elevator/conveyors serving this emissions unit;
 - Identify all days during which any visible fugitive particulate emissions were observed from the enclosures for the hot aggregate elevator, vibrating screens, weigh hopper;
 - Describe any corrective actions taken to eliminate the abnormal visible particulate emissions.

These reports are due by the date described in Part A Standard Terms and Conditions of this permit.

- (8) Annual Permit Evaluation Report (PER) forms will be mailed to the permittee at the end of the reporting period specified in the Authorization section of this permit. The permittee shall submit the PER in the form and manner provided by the director by the due date identified in the Authorization section of this permit. The permit evaluation report shall cover a reporting period of no more than twelve-months for each air contaminant source identified in this permit.

f) Testing Requirements

(1) Compliance with the emission limitations specified in Section b)1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitations: Carbon monoxide (CO) emissions from burning on-spec used oil, number 2 fuel oil, number 4 fuel oil, number 6 fuel oil or natural gas shall not exceed 90.0lbs/hr; Nitrogen Oxide (NO_x) emissions from burning on-spec used oil, number 2 fuel oil, number 4 fuel oil or number 6 fuel oil shall not exceed 21.6lbs/hr; NO_x emissions from burning natural gas shall not exceed 28.8lbs/hr; Sulfur Dioxide (SO₂) emissions from burning on-spec used oil or number 2 fuel oil shall not exceed 27.14lbs/hr; SO₂ emissions from burning natural gas shall not exceed 1.66 lbs/hr; Sulfur Dioxide (SO₂) emissions from burning number 4 fuel oil shall not exceed 43.43lbs/hr; Sulfur Dioxide (SO₂) emissions from burning number 6 fuel oil shall not exceed 54.28lbs/hr; Volatile Organic Compound (VOC) emissions from burning on-spec used oil, number 2 fuel oil, number 4 fuel oil, number 6 fuel oil or natural gas shall not exceed 16.78lbs/hr; PE from the stack shall not exceed 0.04 gr/dscf.

Applicable Compliance Method: The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:

- i. The emission testing shall be conducted within 3 months after issuance of this permit and within 6 months prior to permit renewal.
- ii. The emission testing shall be conducted to demonstrate compliance with the allowable mass emission rate(s) for PE, CO, NO_x, SO₂, and VOC in the appropriate averaging period(s).
- iii. The following test method(s) shall be employed to demonstrate compliance with the allowable mass emission rate(s) for:

PE, Methods 1-5 of 40 CFR Part 60, Appendix A.

NO_x, Methods 1-4 and 7 or 7E of 40 CFR Part 60, Appendix A.

SO₂, Methods 1-4 and 6 or 6C of 40 CFR Part 60, Appendix A

CO, Methods 1-4 and 10 of 40 CFR Part 60, Appendix A

VOC, Methods 1-4 and 25 and/or 18 of 40 CFR Part 60, Appendix A

The VOC pounds per hour emission rate observed during the emissions test shall be calculated in accordance with OAC paragraph 3745-21-10(C)(7) where the average molecular weight of the VOC emissions equals 16. i.e., the VOC as carbon emission rate observed during testing shall be converted to the appropriate units by multiplying the VOC as carbon emission rate observed during testing by 16 and dividing by 12.

Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA.

- iv. The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity and burning on spec used oil for PE, CO, NO_x, SO₂ and VOC and employing RAP to verify VOC emissions, unless otherwise specified or approved by the Ohio EPA, CDO.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, Central District Office. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, Central District Office's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA, Central District Office shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA, Central District Office within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, Central District Office.

- b. Emissions Limitation: PE emissions shall not exceed 9.14 tons per rolling 12-month period.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of PE per ton of asphalt produced, by the actual rolling 12 month summation of asphalt produced, in tons per rolling 12-month period, (as derived from the records required by term and condition d)(3) above) and dividing by 2000.

- c. Emission Limitation: VOC emissions shall not exceed 30.0 tons per rolling 12-month period.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of VOC per ton of asphalt produced, by the actual rolling 12 month summation of asphalt produced, in tons per rolling 12-month period, (as derived from the records required by term and condition d)(3) above) and dividing by 2000.

- d. Emission Limitation: CO emissions shall not exceed 50.0 tons per rolling 12-month period.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of CO per ton of asphalt produced, by the actual rolling 12 month summation of asphalt produced, in tons per rolling 12-month period, (as derived from the records required by term and condition d)(3) above) and dividing by 2000.

- e. Emission Limitation: SO₂ emissions shall not exceed 30.1 tons per rolling 12-month period.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of SO₂ per ton of asphalt produced, by the actual rolling 12 month summation of asphalt produced, in tons per rolling 12-month period, (as derived from the records required by term and condition d)(3) above) and dividing by 2000.

- f. Emission Limitation: NO_x emissions shall not exceed 16.0 tons per rolling 12-month period.

Applicable Compliance Method: Method: Compliance with the annual emissions limitation shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of NO_x per ton of asphalt produced, by the actual rolling 12 month summation of asphalt produced, in tons per rolling 12-month period, (as derived from the records required by term and condition d)(3) above) and dividing by 2000.

- g. Emission Limitations: Arsenic, cadmium, chromium, and lead emissions are limited by the fuel specifications in b)(2)b.

Applicable Compliance Method: Compliance with the emissions limitation for arsenic, cadmium and lead shall be demonstrated by the monitoring and record keeping required by term and condition d)(1) of this permit.

- h. Emission Limitation: Visible particulate emissions from the stack shall not exceed 20% opacity as a 3-minute average.

Applicable Compliance Method: Compliance shall be determined using Method 9 as set forth in 40 CFR Part 60 Appendix A, as such appendix existed on July 1, 1996 and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

- i. Emission Limitation: No visible emissions of fugitive dust from the enclosures for the hot aggregate elevator.

Applicable Compliance Method: Compliance with the limitations on visible emissions of fugitive dust found in Section b)1 of this permit shall be demonstrated by the monitoring and record keeping required by term and condition d)(5).

- j. Emission Limitation: Visible emissions of fugitive dust (from areas other than the enclosures for the hot aggregate elevator) shall be less than or equal to 10% opacity, as a 3-minute average.

Applicable Compliance Method: Compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

- k. Emissions Limitation: PM-10 emissions from the stack shall not exceed 9.14 tons per rolling 12-month period.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be assumed as long as compliance is maintained with the rolling 12-month emissions limitation for particulate emissions.

- l. Emissions Limitation: Fugitive PM₁₀ emissions shall not exceed 6.39 tons per rolling 12-month period.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be assumed based upon the following worst case calculations:

Total fugitive emissions equal the summation of the fugitives from the cold end and the hot end of the plant operations.

Fugitives emissions from the cold end are calculated as follows:

Material Loading (AP-42, Fifth edition, Table 11.12-2, 10/01):

$((400,000 \text{ tons of material/year} \times 0.0024 \text{ lb PM-10/ton of material}) + (200,000 \text{ tons of aggregate/year} \times 0.0033 \text{ lb PM-10/ton of aggregate}) + (200,000 \text{ tons of sand/year} \times 0.00099 \text{ lb PM-10/ton of sand})) \times (1 \text{ ton}/2000 \text{ pounds}) = 0.909 \text{ ton of PM-10/year}$

Screening (AP-42, Fifth edition, Table 11.19.2-2, 08/04):

$(400,000 \text{ tons of material/year}) \times (0.0087 \text{ lb PM-10/ton of material}) = 1.74 \text{ tons PM-10/year}$

Transfer Points (AP-42, Fifth edition, Table 11.19.2-2, 08/04):

$(400,000 \text{ tons of material/year}) \times (16 \text{ transfer points}) \times (0.0011 \text{ lb PM-10/ton of material}) = 3.52 \text{ tons of PM-10/year}$

Fugitives emissions from the hot end are calculated as follows:

Drum Mix Load-out (AP-42, Fifth edition, Table 11.1-14, 03/04):

Emission factor = $0.000181 + 0.00141(-V)e^{((0.0251)(T+460) - 20.43)}$ = 0.000522 lb/ton asphalt

where,

V = asphalt volatility (- 0.5)*

T = HMA temperature (325°F)*

* Default values listed in AP-42

(400,000 tons of asphalt produced X 0.000522 lb of PM-10/ton of asphalt produced) X (1 ton/2000 pounds) = 0.10 ton of PM-10/ year

Silo Filling (AP-42, Fifth edition, Table 11.1-14, 03/04):

Emission factor = $0.000332 + 0.00105(-V)e^{((0.0251)(T+460) - 20.43)}$ = 0.000586 lb/ton asphalt

where,

V = asphalt volatility (- 0.5)*

T = HMA temperature (325°F)*

* Default values listed in AP-42

(400,000 tons of asphalt produced X 0.000586 lb of PM-10/ton of asphalt produced) X (1 ton/2000 pounds) = 0.117 ton of PM-10/year

Total fugitive emissions are therefore 6.39 tons of PM-10/year

- m. Emissions Limitation: Fugitive PM emissions shall not exceed 16.74 tons per rolling 12-month period.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be assumed based upon the following worst case calculations:

Total fugitive emissions equal the summation of the fugitives from the cold end and the hot end of the plant operations.

Fugitives emissions from the cold end are calculated as follows:

Material Loading (AP-42, Fifth edition, Table 11.12-2, 10/01):

((400,000 tons of material/year X 0.0051 lb PM/ton of material) + (200,000 tons of aggregate/year X 0.0069lb PM/ton of aggregate) + (200,000 tons of

sand/year X 0.0021 lb PM/ton of sand)) X (1 ton/2000 pounds) = 1.92 tons of PM/year

Screening (AP-42, Fifth edition, Table 11.19.2-2, 08/04):

(400,000 tons of material/year) X (0.025 lb PM/ton of material) = 5.0 tons PM/year

Transfer Points (AP-42, Fifth edition, Table 11.19.2-2, 08/04):

(400,000 tons of material/year) X (16 transfer points) X (0.0030 lb PM/ton of material) = 9.6 tons of PM/year

Fugitives emissions from the hot end are calculated as follows:

Drum Mix Load-out (AP-42, Fifth edition, Table 11.1-14, 03/04):

Emission factor = $0.000181 + 0.00141(-V)e^{((0.0251)(T+460) - 20.43)}$ = 0.000522 lb/ton asphalt

where,

V = asphalt volatility (- 0.5)*

T = HMA temperature (325°F)*

* Default values listed in AP-42

(400,000 tons of asphalt produced X 0.000522lb of PM/ton of asphalt produced) X (1 ton/2000 pounds) = 0.10 ton of PM.

Silo Filling (AP-42, Fifth edition, Table 11.1-14, 03/04):

Emission factor = $0.000332 + 0.00105(-V)e^{((0.0251)(T+460) - 20.43)}$ = 0.000586 lb/ton asphalt

where,

V = asphalt volatility (- 0.5)*

T = HMA temperature (325°F)*

* Default values listed in AP-42

(400,000 tons of asphalt produced X 0.000586 lb of PM/ton of asphalt produced) X (1 ton/2000 pounds) = 0.117 ton of PM/year

Total fugitive emissions are therefore 16.74 tons of PM/year.

- n. Emission Limitations: Emissions of fugitive PM-10 shall not exceed 6.39 pounds per hour.

Applicable Compliance Method: Compliance with this emissions limitation shall be assumed as long as compliance is maintained with the rolling 12-month operational restriction.

- o. Emission Limitations: Emissions of fugitive PM shall not exceed 16.74 pounds per hour.

Applicable Compliance Method: Compliance with this emissions limitation shall be assumed as long as compliance is maintained with the rolling 12-month operational restriction.

- p. Emission Limitations: Fugitive emissions from drum mix load out operations (hot side) shall not exceed 0.83 ton VOC per rolling 12-month period and 0.27 ton CO per rolling 12-month period. Fugitive emissions from the silo filling operations (hot side) shall not exceed 2.44 tons VOC per rolling 12-month period and 0.24 ton CO per rolling 12-month period.

Applicable Compliance Method: Compliance with this emissions limitation shall be assumed based upon the following worst case calculations.

Fugitive emissions from the hot side load out and silo filling operations are calculated based on the following emission factors from AP-42, Fifth edition, Table 11.1-14, 03/04:

<u>Activity</u>	<u>Pollutant</u>	<u>Predictive Emission Factor Equation (lb/ton)</u>
Load-out	VOC**	$EF = 0.0172 (-V)e^{((0.251)(T+460) - 20.43)}$
Silo Filling	VOC**	$EF = 0.0504 (-V)e^{((0.251)(T+460) - 20.43)}$
Load-out	CO	$EF = 0.00558 (-V)e^{((0.251)(T+460) - 20.43)}$
Silo Filling	CO	$EF = 0.00488 (-V)e^{((0.251)(T+460) - 20.43)}$

where,

V = asphalt volatility (- 0.5)*

T = HMA temperature (325°F)*

* Default values listed in AP

** Assumes VOC = TOC

Based on the above information, the emission factors and emissions are as follows:

<u>Activity</u>	<u>Pollutant</u>	<u>EF, in lb/ton</u>	<u>tons/year (at 400,000 tons/yr production)</u>
Load-out	VOC*	4.16×10^{-3}	0.83
Silo Filling	VOC*	1.22×10^{-2}	2.44
Load-out	CO	1.35×10^{-3}	0.27
Silo Filling	CO	1.18×10^{-3}	0.24

(2) Burner Tuning

a. Introduction

The permittee is required to conduct periodic tuning of the asphalt plant burner. The purpose of this tuning is to ensure that the burner is adjusted properly so that air pollution emissions remain in compliance with allowable emissions rates and are minimized.

b. Qualifications for Burner Tuning

Technicians who conduct the burner tuning must be qualified to perform the expected tasks. The permittee is required to provide training to the technicians who perform the burner tuning procedure. Technicians who are qualified shall, at a minimum, have passed manufacturer's training concerning burner tuning, or have been trained by someone who has completed the manufacturer's training concerning burner tuning.

c. Portable Monitor Requirements

The permittee shall properly operate and maintain portable device(s) to monitor the concentration of NO_x, O₂ and CO in the stack exhaust gases from this emissions unit. The monitor(s) shall be capable of measuring the expected concentrations of the measured gases. The monitoring equipment shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall maintain records of each portable monitoring device's calibration.

d. Burner Tuning Procedure

The first steps concerning burner tuning involve setting the pollutant baseline levels (concentrations) utilizing the portable monitor. These baselines shall be set during the initial U.S. EPA approved emissions testing that demonstrated the emissions unit was in compliance with all applicable emissions limitations as described in f)(1). The baselines shall be determined for NO_x, and CO. Sampling should measure the exhaust gas values exiting the dryer or the baghouse. The duration of each sample shall follow the portable monitor manufacture's recommendations. Record these values on the Burner Tuning Reporting Form for Asphalt Concrete Plants form (as found in g)(3)) in the "Recent Stack Test Basis Values" column.

Once the pollutant baseline levels are set, the burner shall be next tuned based on the frequency described in f)(1) The general procedure for tuning the burner involves the following steps:

- i. Review the plant operations to ensure the plant is operating normally.
- ii. Confirm that the portable monitor is calibrated per the manufacture's specifications.

- iii. Using the calibrated monitor and the monitor manufacturer's recommended sampling duration, measure the stack exhaust gas values for O₂, NO_x, and CO. These measurements shall be taken at the same location as the location where the baseline samples were taken. Record the values in the "Pre Tuning" results column on the Burner Tuning Reporting Form for Asphalt Concrete Plants form.
- iv. Compare the measured stack exhaust gas values with the pollutant baseline values. If all of the measured stack exhaust gas values are equal to or less than 115 per cent of the pollutant baseline values, then it is not necessary to tune the burner. Go on to Section v. below.

The permittee shall have the burners tuned within two calendar weeks of any measured stack exhaust values greater than 115 per cent of the baseline values. Make any necessary adjustments and repairs. Repeat Sections iii. and iv. until the measured stack exhaust gas values are equal to or less than 115 per cent of the pollutant baseline values.

- v. Once all of the measured stack exhaust gas values are within the 115 per cent of the pollutant baseline values, record the measured stack exhaust gas values in the "Post Tuning" results column on the Burner Tuning Reporting Form for Asphalt Concrete Plants form.
 - vi. By January 31 of each year, submit a copy of all Burner Tuning Reporting Form for Asphalt Concrete Plants forms produced during the past calendar year to the appropriate Ohio EPA District Office or local air agency responsible for the permitting of the facility.
- e. Burner Tuning Frequency

The permittee shall conduct the burner tuning procedure within 20 production days after commencement of the production season in the State of Ohio. The permittee shall conduct another burner tuning procedure within 10 production days before or after June 1st of each year and within 10 production days before or after September 1st of each year. For purposes of this permit, the production season is defined as the time period between the date the first ton of asphalt is produced and the date that the last ton of asphalt is produced during the same calendar year. A burner tuning is not required if the production season ends prior to the associated tuning due date. If the baseline level testing or the initial season tuning is done within 30 days prior to June 1 or September 1, the tuning associated with that due date is not required.

- (2) In addition to the burner tuning procedure required above, the permittee shall conduct the burner tuning procedure within 20 production days from the date the facility switches to a fuel that is different than the fuel burned during the initial emissions tests that establish the pollutant baseline levels or the fuel burned during the most recent burner tuning procedure, whichever is later.

g) Miscellaneous Requirements

- (1) The following source is subject to the applicable provision of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR part 60. *

Source Number	Source Description	NSPS Regulation (Subpart)
P901	480 tph asphalt plant	Subpart I

The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

Pursuant to NSPS, the source owner/operator is hereby advised of the requirement to report the following at the appropriate times:

- a. Construction date (no later than 30 days after such date);
- b. Actual start-up date (within 15 days after such date); and
- c. Date of performance testing (If required, at least 30 days prior to testing).

Reports are to be sent to:

Ohio Environmental Protection Agency
DAPC- Air Quality Modeling and Planning
P.O. Box 1049
Columbus, OH 43216-1049

and

Central District Office
Division of Air Pollution Control
50 West Town Street Suite 700
Columbus, OH 43215

*The Permittee has already satisfied this requirement

- (2) This permit replaces PTI number 01-01342, as issued on April 25, 2006.
- (3) Burner Tuning Form (See next page)



BURNER TUNING REPORTING FORM FOR ASPHALT CONCRETE PLANTS	
Facility ID:	Tuning Date:
Legal Name:	Other Company Name (if different than legal name):
Mailing Address:	Other Company Site Address: (if different than mailing address):
City, State, Zip Code:	Other Company City, County, Zip Code:
Site Contact Person:	Site Contact Telephone Number:
Site Contact Title:	Site Contact Fax Number:
Name of company performing tuning:	Name of company performing emission monitoring:
Type of plant (ie: batch, drum mix, etc.):	Calibration date for analyzers:

Reason for Tuning: Season Initial Tuning June Tuning September Tuning Fuel Switch
 Other (describe)

Fuel employed during tuning: Natural Gas Propane # 2 Fuel Oil # 4 Fuel Oil Used Oil
 Other(describe)

Tuning Results:

Parameter	Recent Stack Test Pollutant Baseline Levels ¹	Results	
		Pre Tuning	Post Tuning ³
Fuel flow to the burner (gallon/hr) (for fuel oil and on-spec used oil)			
Fuel pressure (psi)			
For burners that require compressed air for proper operation, pressure at the burner (psi)			
Carbon Monoxide (CO) concentrations (ppm) ²			
NOx concentrations (ppm) ²			
Oxygen concentrations (per cent) ²			
Asphalt Production (tons/hr)			

¹These values are based on the results of the most recent Ohio EPA approved emissions test.

² Specify whether on a dry or wet basis.

³ If the burner did not require adjusting, please record N/A in the post tuning column.

Describe in detail a list of adjustments and/or repairs made to bring the operating parameters into conformance with the manufacturers specifications. Use additional paper if necessary.

Authorized Signature: This signature shall constitute personal affirmation that all statements or assertions of facts made in this form are true and complete, comply fully with applicable state requirements, and shall subject the signatory to liability under applicable state laws forbidding false or misleading statements.

Name of Official (Printed or Typed):	Title of Official and Phone Number:
Signature of Official:	Date: