



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL
LAKE COUNTY**

CERTIFIED MAIL

Street Address:

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:
Lazarus Gov.
Center

Application No: 02-13738

DATE: 6/14/00

Component Repair Technologies Inc
Michael Lasco
8597 Tyler Blvd
Mentor, OH 44060

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Director's action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
236 East Town Street, Room 300
Columbus, Ohio 43215

Very truly yours,

Thomas G. Rigo
Field Operations and Permit Section
Division of Air Pollution Control

CC: USEPA

NEDO



STATE OF OHIO ENVIRONMENTAL PROTECTION AGENCY

**Permit To Install
Terms and Conditions**

**Issue Date: June 14, 2000
Effective Date: June 14, 2000**

FINAL PERMIT TO INSTALL 02-13738

Application Number: 02-13738
APS Premise Number: 0243081158
Permit Fee: **\$200**
Name of Facility: Component Repair Technologies Inc
Person to Contact: Michael Lasco
Address: 8597 Tyler Blvd
Mentor, OH 44060

Location of proposed air contaminant source(s) [emissions unit(s)]:
8507 Tyler Blvd
Mentor, Ohio

Description of proposed emissions unit(s):
Detrex vapor degreaser.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS**A. State and Federally Enforceable Permit To Install General Terms and Conditions****1. Monitoring and Related Recordkeeping and Reporting Requirements**

- a. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:
 - i. The date, place (as defined in the permit), and time of sampling or measurements.
 - ii. The date(s) analyses were performed.
 - iii. The company or entity that performed the analyses.
 - iv. The analytical techniques or methods used.
 - v. The results of such analyses.
 - vi. The operating conditions existing at the time of sampling or measurement.
- b. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.
- c. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall submit required reports in the following manner:
 - i. Reports of any required monitoring and/or recordkeeping of federally enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
 - ii. Quarterly written reports of (i) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, excluding deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06, that have been detected by the testing, monitoring and recordkeeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures taken, shall be made to the appropriate Ohio EPA District Office or local air agency. The written reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. See B.11 below if no deviations occurred during the quarter.

- iii. Written reports, which identify any deviations from the federally enforceable monitoring, recordkeeping, and reporting requirements contained in this permit shall be submitted to the appropriate Ohio EPA District Office or local air agency every six months, i.e., by January 31 and July 31 of each year for the previous six calendar months. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report, which states that no deviations occurred during that period.
- iv. Each written report shall be signed by a responsible official certifying that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.

2. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction, i.e., upset, of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. (The definition of an upset condition shall be the same as that used in OAC rule 3745-15-06(B)(1) for a malfunction.) The verbal and written reports shall be submitted pursuant to OAC rule 3745-15-06.

Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emission unit(s) that is (are) served by such control system(s).

3. Risk Management Plans

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. 7401 et seq. ("Act"), the permittee shall comply with the requirement to register such a plan.

4. Title IV Provisions

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

5. Severability Clause

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition declared invalid.

6. General Requirements

- a. The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and reissuance, or modification, or for denial of a permit renewal application.
- b. It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.
- c. This permit may be modified, reopened, revoked, or revoked and reissued, for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.
- d. This permit does not convey any property rights of any sort, or any exclusive privilege.
- e. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

7. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit To Install fees within 30 days after the issuance of this Permit To Install.

8. Federal and State Enforceability

Only those terms and conditions designated in this permit as federally enforceable, that are required under the Act, or any of its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA, the State, and citizens under the Act. All other terms and conditions of this permit shall not be federally enforceable and shall be enforceable under State law only.

9. Compliance Requirements

- a. Any document (including reports) required to be submitted and required by a federally

Component Repair Technologies Inc

PTI Application: 02-13738

Issued: June 14, 2000

Facility ID: 0243081158

applicable requirement in this permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.

- b. Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:
 - i. At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.
 - ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with ORC section 3704.08.
 - iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.
 - iv. As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.
- c. The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually, or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:
 - i. Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
 - ii. An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

10. Permit To Operate Application

- a. If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete

Component Repair Technologies Inc

Facility ID: 0243081158

PTI Application: 02-13738

Issued: June 14, 2000

Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).

- b. If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35 , the source(s) identified in this Permit To Install is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within thirty (30) days after commencing operation of the source(s) covered by this permit.

Component Repair Technologies Inc

Facility ID: 0243081158

PTI Application: 02-13738

Issued: June 14, 2000

B. State Only Enforceable Permit To Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping of state-only enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from state-only required emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

4. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

5. Termination of Permit To Install

This permit to install shall terminate within eighteen months of the effective date of the permit to install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

6. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources are inadequate or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities prove to be inadequate or cannot meet applicable standards.

7. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

8. Applicability

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

9. Best Available Technology

Component Repair Technologies Inc
PTI Application: 02-13738
Issued: June 14, 2000

Facility ID: 0243081158

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

10. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit To Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

11. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations (See Section A of This Permit)

If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.

C. Permit To Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
OC	9.9

Component Repair Technologies Inc

Facility ID: 0243081158

PTI Application: 02-13738

Issued: June 14, 2000

Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

A. State and Federally Enforceable Permit To Install Facility Specific Terms and Conditions

None.

B. State Only Enforceable Permit To Install Facility Specific Terms and Conditions

None.

Comp
PTI A

Emissions Unit ID: L003

Issued: June 14, 2000

Part III -

SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
L003 - Detrex Trichloroethylene Batch, Open Top, Vapor Degreaser	40 CFR Part 63, subpart T OAC rule 3745-21-09 (O) OAC rule 3745-31-05 (A)(3)	See sections A.I.2.a, A.II.1 - A.II.4 of these terms and conditions. In accordance with paragraph (O)(6)(b) of OAC rule 3745-21-09, the requirements of OAC rule 3745-21-09 (O)(4) shall not apply to this emissions unit. Volatile Organic compound (OC) emissions generated from this emissions unit shall not exceed 9.9 tons per year.

2. Additional Terms and Conditions

- 2.a The permittee shall ensure that the solvent cleaning machine conforms to the following design requirements:
 - i. The solvent cleaning machine shall be designed or operated to meet the following control equipment or technique requirements:
 - aa. Use of reduced room draft that ensures that the flow or movement across the top of the freeboard area of the solvent cleaning machine or within the solvent cleaning machine enclosure does not exceed 15.2 meters per minute (50 feet per minute)

at any time measured using the procedure described in section A.III.5 of these terms and conditions. The permittee shall establish and maintain the operating conditions under which the wind speed was demonstrated to be 15.2 meters per minute (50 feet per minute) or less as described in section A.III.5 of these terms and conditions.

- ii. The solvent cleaning machine shall have a freeboard ratio of 0.75 or greater.
 - iii. The solvent cleaning machine shall have an automated parts handling system capable of moving parts or parts baskets at a speed of 3.4 meters per minute (11 feet per minute) or less from the initial loading of parts through removal of cleaned parts.
 - iv. The solvent cleaning machine shall be equipped with a device that shuts off the sump heat if the sump liquid solvent level drops to the sump heater coils.
 - v. The solvent cleaning machine shall be equipped with a vapor level control device that shuts off sump heat if the vapor level in the vapor cleaning machine rises above the height of the primary condenser.
 - vi. The solvent cleaning machine shall have a primary condenser.
- 2.b** The permittee shall ensure that the chilled air blanket temperature (in °F or °C), measured at the center of the air blanket, is no greater than 30 percent of the solvent's boiling point.
- 2.c** The permittee shall comply with the following requirements:
- i. Ensure that the flow or movement of air across the top of the freeboard area of the solvent cleaning machine does not exceed 15.2 meters per minute (50 feet per minute) at any time as measured using the procedures outlined in section A.III.5 of these terms and conditions.
 - ii. Establish and maintain the operating conditions under which the wind speed was demonstrated to be 15.2 meters per minute (50 feet per minute) or less.
- 2.d** The permittee shall maintain a freeboard with the a freeboard ratio equal to 1.0 or greater.

II. Operational Restrictions

1. The permittee shall meet all of the following required work and operational practices:
 - a. Control air disturbances across the solvent cleaning machine opening(s) by incorporating the following control equipment or techniques:
 - i. The permittee shall employ a reduced room draft that ensures that the flow or movement of air across the top of the freeboard area of the solvent cleaning machine or within the solvent cleaning machine enclosure does not exceed 15.2 meters per minute (50 feet per minute) at any time as measured using the procedures described in section A.III.5 of these terms and conditions. The permittee shall also establish and maintain the operating conditions under which the wind speed was demonstrated to be 15.2 meters per minute (50 feet per minute) or less as described in the "Monitoring and/or Recordkeeping Requirements" section of this permit.
 - b. The parts baskets or the parts being cleaned in solvent cleaning machine shall not occupy more than 50 percent of the solvent/air interface area unless the parts baskets or parts are introduced at a speed of 0.9 meter per minute (3 feet per minute) or less.
 - c. Any spraying operations shall be done within the vapor zone or within a section of the solvent cleaning machine that is not directly exposed to the ambient air (i.e., a baffled or enclosed area of the solvent cleaning machine).
 - d. Parts shall be oriented so that the solvent drains from them freely. Parts having cavities or blind holes must be tipped or rotated before being removed from the solvent cleaning machine unless an equally effective approach has been approved by the Director (appropriate field Office or local air agency).
 - e. Parts baskets or parts shall not be removed from the solvent cleaning machine until dripping has stopped.
 - f. During startup of the solvent cleaning machine, the primary condensers shall be turned on before the sump heater.
 - g. During shutdown of the solvent cleaning machine, the sump heater shall be turned off and the solvent vapor layer allowed to collapse before the primary condenser is turned off.
 - h. When solvent is added or drained from the solvent cleaning machine, the solvent shall be transferred using threaded or other leakproof couplings and the end of the pipe in the solvent sump shall be located beneath the liquid solvent surface.
 - i. The solvent cleaning machine and its associated controls shall be maintained as recommended by the manufacturers of the equipment or using alternative maintenance practices that have been demonstrated to the satisfaction of the Director (appropriate field Office or local air agency) to achieve the same or better results as those recommended by

Issued: June 14, 2000

the manufacturer.

- j. The permittee shall complete and pass the applicable sections of the test of solvent cleaning operating procedures in 40 CFR Part 63, Appendix B if requested during an inspection by the Director (appropriate field Office or local air agency).
- k. Waste solvent, still bottoms, and sump bottoms shall be collected and stored in closed containers. The closed containers may contain a device that would allow pressure relief, but must not allow liquid solvent to drain from the container.
- l. Sponges, fabric, wood, and paper products shall not be cleaned.

III. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall monitor the hoist speed as described below:
 - a. The permittee shall determine the hoist speed by measuring the time it takes for the hoist to travel a measured distance. The speed is equal to the distance in meters divided by the time in minutes (meters per minute).
 - b. The permittee shall conduct monthly monitoring of the hoist speed. If after the first year, no exceedances of the hoist speed are measured, the permittee may begin monitoring the hoist speed quarterly.
 - c. If an exceedance of the hoist speed occurs during quarterly monitoring, the permittee shall return to a monthly monitoring frequency until another year of compliance without an exceedance is demonstrated.
 - d. If the permittee can demonstrate to the satisfaction of the Director (appropriate District Office or local air agency) in the initial compliance report that the hoist speed cannot exceed a speed of 3.4 meters per minute (11 feet per minute), the required monitoring frequency is quarterly, including during the first year of compliance.
- 2. The permittee shall maintain the following records in written or electronic form for the lifetime of the solvent cleaning machine:
 - a. Owner's manuals, or if not available, written maintenance and operating procedures for the solvent cleaning machine and control equipment.
 - b. The date of installation for the solvent cleaning machine and all of its control devices.

Emissions Unit ID: L003

- c. Records of the halogenated HAP solvent content for the solvent used in the solvent cleaning machine.
3. The permittee shall maintain the following records in written or electronic form for a period of five years for the solvent cleaning machine:
 - a. The results of control device monitoring required in this section of the permit.
 - b. Information on the actions taken to comply with 40 CFR 63.463 (e) and (f), including records of written or verbal orders for replacement parts, a description of the repair made, and additional monitoring conducted to demonstrate that monitored parameters have returned to acceptable levels.
 - c. Estimates of annual trichloroethylene consumption for the solvent cleaning machine.
4. The permittee shall conduct monitoring and record the results on a weekly basis for the freeboard refrigeration device by using a thermometer or thermocouple to measure the temperature at the center of the air blanket during the idling mode.
5. The permittee shall conduct an initial monitoring test of the wind speed and of room parameters, quarterly monitoring of wind speed, and weekly monitoring of room parameters as specified below:
 - a. Measure the wind speed within 6 inches above the top of the freeboard area of the solvent cleaning machine as follows:
 - i. Determine the direction of the wind current by slowly rotating a velometer or similar device until the maximum speed is located.
 - ii. Orient a velometer in the direction of the wind current at each of the four corners of the machine.
 - iii. Record the reading for each corner.
 - iv. Average the values obtained at each corner and record the average wind speed.
 - b. Monitor on a weekly basis the room parameters established during the initial compliance test that are used to achieve the reduced room draft.
6. The permittee shall keep the following information for this emissions unit every year:
 - a. The name and company identification of each solvent employed in this emissions unit.
 - b. The amount of each cleaning solvent employed, to be defined as "L_{Si}", in gallons per year.
 - c. The density of each solvent, to be defined as "D_i", in pounds per gallon.

Issued: June 14, 2000

- d. The amount of each cleaning solvent sent off-site as waste, defined as " L_{wi} ", in gallons per year.
- e. The amount of VOC emitted, to be defined as "MOC", in tons per year. MOC shall be calculated as follows:

MOC = the sum, $i = 1$ to $i = n$, of $[(L_s - L_w) \times D]_i$, divided by 2000 pounds per ton

IV. Reporting Requirements

1. The permittee shall submit an initial notification report as soon as practicable before the construction or reconstruction is planned to commence. This report shall include all of the information required in 40 CF 63.5 (d)(1) of subpart A, with the following revisions and additions:
 - a. The report shall include a brief description of the solvent cleaning machine type (batch vapor, batch cold, vapor in-line, or cold in-line), solvent/air interface area, and existing controls.
 - b. The report shall include the anticipated compliance approach for the solvent cleaning machine.
 - c. The report shall include an estimate of the trichloroethylene consumption for the solvent cleaning machine in lieu of the requirements of 40 CFR 63.5 (d)(1)(ii)(H), subpart A.
2. The permittee shall submit an initial statement of compliance no later than 150 days after startup. Each initial statement of compliance shall contain the following:
 - a. The name and address of the permittee.
 - b. The address (i.e., physical location) of the solvent cleaning machine.
 - c. A list of the control equipment used to achieve compliance.
 - d. A list of the parameters that are monitored and the values of these parameters measured on or during the first month after the compliance date for each piece of control equipment required to be monitored.
 - e. Conditions to maintain the wind speed requirements as described in the "Additional Terms and Conditions" section of this permit.
3. The permittee shall submit an annual report by February 1 of each year for the preceding year.

Each annual report shall contain the following:

- a. A signed statement from the facility owner or their designee stating that, "All operators of solvent cleaning machines have received training on the proper operation of solvent cleaning machines and their control devices sufficient to pass the test required pursuant to 40 CFR 60.463 (d) (10)."
 - b. An estimate of solvent consumption during the reporting period.
4. The permittee shall submit an exceedance report on a semiannual basis. If no operation conditions were established under which the wind speed was demonstrated to be 15.2 meters per minute (50 feet per minute) and/or if the flow of air across the top of the freeboard area of the cleaning machine or within the solvent cleaning machine enclosure exceeded 15.2 meters/minute and no correction was made within 15 days of detection, and if the temperature of the chilled air blanket, measured at the center of the air blanket, was greater than 30% of the solvent's boiling point and no correction was made within 15 days of detection, the permittee shall begin to submit a quarterly report until such time that the permittee requests and receives approval of a less frequent reporting frequency from the Director (appropriate District Office or local air agency). The permittee may receive approval of less frequent reporting if the following conditions are met: (1) The emissions unit has demonstrated a full year of compliance without an exceedance, (2) the permittee continues to comply with all relevant recordkeeping and monitoring requirements specified in 40 CFR 63.1, General Provisions, and (3) the Director (appropriate District Office or local air agency) does not object to a reduced frequency of reporting for the affected emissions unit as provided in paragraph (e) (3) (iii) of subpart A, 40 CFR 63.1, General Provisions. Each exceedance report shall be delivered or post marked by the 30th day following the reporting period. Each exceedance report shall contain the following:
- a. The reason and a description of the exceedance and action(s) taken to comply with 40 CFR 63.463 (e) and (f) including written or verbal orders for replacement parts, a description of the repairs made, and additional monitoring conducted to demonstrate that monitored parameters have returned to acceptable levels.
 - b. If no exceedance has occurred, a statement to that effect shall be submitted.

Written reports shall be submitted to the appropriate Ohio EPA District Office or local air agency every six months, i.e., by January 31 and July 31 of each year for the previous six calendar months. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report, which states that no deviations occurred during that period.

5. The permittee shall submit an annual solvent usage report. The report shall be submitted to the appropriate Ohio EPA District Office or local air agency by January 31 of each year, and shall cover previous calendar year.

V. Testing Requirements

Issued: June 14, 2000

1. The permittee shall conduct an initial test of the wind speed and of room parameters using the following procedures:
 - a. Determine and measure the maximum wind speed within 6 inches above the top of the freeboard area of the solvent cleaning machine by slowly rotating a velometer or similar device until the maximum speed is located.
 - b. Orient the velometer or similar device in the direction of the wind current at each of the four corners of the machine and perform the following:
 - i. Record the reading for each corner.
 - ii. Average the values obtained at each corner and record the average wind speed.

2. The permittee shall determine the facility's potential to emit (PTE) from all solvent cleaning operations. A facility's total PTE is the sum of the HAP emissions from all solvent cleaning operations plus all HAP emissions from other emissions units from within the facility. The potential to emit shall be determined in accordance with the following procedures:

- a. Determine the potential to emit for each individual solvent cleaning machine using the following equation:

$$PTE_i = H_i \times W_i \times SAI_i$$

Where:

PTE_i = the potential to emit for the solvent cleaning machine i (kilograms solvent per year).

H_i = hours of operation for solvent cleaning machine i (hours per year).

= 8760 hours per year, unless otherwise restricted by a federally enforceable requirement.

W_i = the working mode uncontrolled emission rate (kilograms per square meter per hour).

= 1.95 kilograms per square meter per hour for batch vapor and cold cleaning machines.

SAI_i = solvent/air interface area of solvent cleaning machine i (square meters). Section

Emissions Unit ID: L003

63.461 defines the solvent/air interface area for those machines that have a solvent/air interface. Cleaning machines that do not have a solvent area interface shall calculate a solvent/air interface area using the procedure in paragraph (b) below.

- b. Cleaning machines that do not have a solvent/air interface shall calculate a solvent/air interface area using the following equation:

$$SAI = 2.2 * (Vol)^{0.6}$$

Where:

SAI = the solvent/air interface area (square meters).

Vol = the cleaning capacity of the solvent cleaning machine (cubic meters).

- c. Sum the PTE_i for all solvent cleaning operations to obtain the total potential to emit for solvent cleaning operations at the facility.
3. Compliance with the emission limitation in section A.I.1 of these terms and conditions shall be determined in accordance with the following method:
- a. Emission Limitation:
9.9 tons per year of OC

Applicable Compliance Method:

Compliance shall be determined based upon recordkeeping requirements specified in section A.III.6 of these terms and conditions.

VI. Miscellaneous Requirements

None.

Issued: June 14, 2000

B. State Only Enforceable Section**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
L003 - Detrex Trichloroethylene Vapor Degreaser		

2. Additional Terms and Conditions

2.a None.

II. Operational Restrictions

None.

III. Monitoring and/or Recordkeeping Requirements

None.

IV. Reporting Requirements

None.

V. Testing Requirements

None.

VI. Miscellaneous Requirements

None.

NEW SOURCE REVIEW FORM B

PTI Number: 02-13738 Facility ID: 0243081158

FACILITY NAME Component Repair Technologies Inc

FACILITY DESCRIPTION Detrex vapor degreaser CITY/TWP Mentor

SIC CODE 3742 SCC CODE 4-01-002-05 EMISSIONS UNIT ID L003

EMISSIONS UNIT DESCRIPTION Detrex Trichloroethylene Vapor Degreaser

DATE INSTALLED

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter					
PM ₁₀					
Sulfur Dioxide					
Organic Compounds	Attainment		2.44		9.9
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? **subpart T**

NESHAP?

PSD?

OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination The BAT determination is compliance with MACT requirements, and 9.9 tons per year of organic compound emissions. The basis for the determination is knowledge of process, engineering analysis, and regulation governing this emissions unit.

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? No - Exempt

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT?

\$

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES X NO

IDENTIFY THE AIR CONTAMINANTS: _____

NEW SOURCE REVIEW FORM B

PTI Number: 02-13738 Facility ID: 0243081158

FACILITY NAME Component Repair Technologies Inc

FACILITY DESCRIPTION Detrex vapor degreaser CITY/TWP Mentor

Please describe any hard copy information is being submitted with this recommendation (Please send hard copy information to Pam McGraner, DAPC Central Office - Air Quality Modeling and Planning):

NONE

Please provide any additional permit specific notes as you deem necessary:

PREMISE No. 02 43 08 1158 EU No. L003
PTI No. 02-13738

AIR EMISSION CALCULATION FORM

1. Facility Name: Component Repair Technologies, Inc.
2. Source Description: Detrex Trichloroethylene Vapor Degreaser
3. Source Inspection: Yes/ No Date:
Operating: Yes/ No
4. Calculation:
Information: Operating Schedule: Actual: 20 hours/day and 6344 hours/year
Maximum: 24 hours/day and 7488 hours/year
Tank Dimensions: 3 ft x 6 ft = (18 ft²)(0.3048 m/ft)² = 1.672 m²
Maximum trichloroethylene usage = 750 gallons per year
Minimum solvent waste disposed = 350 gallons per year

$$\text{Actual} = (750 \text{ gal/year} - 350 \text{ gal/year}) \times (1.462 \times 8.34 \text{ lbs/gal}) / (2000 \text{ lbs/ton})$$

$$= 2.44 \text{ tons/yr}$$

$$\text{Potential} = (8760 \text{ hours/year})(1.95 \text{ kg/hr/m}^2)(1.672 \text{ m}^2) = 28561.104 \text{ kg/yr}$$

$$= (28561.104 \text{ kg/yr})(2.20462 \text{ lb/kg}) = 62966.3811 \text{ lb/yr} = 31.48 \text{ tons/yr}$$

(Equation in MACT rule, subpart T)

$$\text{Allowable} = 9.9 \text{ tons/yr}$$

(BAT determination, OAC rule 3745-31-05 (A)(3))

Air Toxic Policy: Exempt, - Compliance with MACT requirements

5. EMISSIONS (TONS/YEAR):

Pollutant	Actual*	Potential**	Allowable**
OC	2.44	31.48	9.9

NEW SOURCE REVIEW FORM B

PTI Number: 02-13738 Facility ID: 0243081158

FACILITY NAME Component Repair Technologies Inc

FACILITY DESCRIPTION Detrex vapor degreaser CITY/TWP Mentor

Source classification: Major Minor

Other

Source Recommendation: Approval T - Status

Denial Revoke

Examiner: Chaoxia Gu

Date:

* Based upon actual operating hours.
days/yr

** Based upon 24 hrs/day and 365

Permit To Install Synthetic Minor Write-Up

NONE

Please fill in the following for this permit:

TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

Pollutant

Tons Per Year

OC

9.9