



Street Address:

State of Ohio Environmental Protection Agency
Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov.
Center

**RE: FINAL PERMIT TO INSTALL
LORAIN COUNTY
Application No: 02-14213**

CERTIFIED MAIL

DATE: 11/2/2000

Western Enterprises
Robert Wisner
33672 Pin Oak Parkway
Avon Lake, OH 44012

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Director's action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
236 East Town Street, Room 300
Columbus, Ohio 43215

Very truly yours,

Thomas G. Rigo, Manager
Field Operations and Permit Section
Division of Air Pollution Control

CC: USEPA

NEDO



STATE OF OHIO ENVIRONMENTAL PROTECTION AGENCY

**Permit To Install
Terms and Conditions**

**Issue Date: November 2, 2000
Effective Date: November 2, 2000**

FINAL PERMIT TO INSTALL 02-14213

Application Number: 02-14213
APS Premise Number: 0247030559
Permit Fee: **\$200**
Name of Facility: Western Enterprises
Person to Contact: Robert Wisner
Address: 33672 Pin Oak Parkway
Avon Lake, OH 44012

Location of proposed air contaminant source(s) [emissions unit(s)]:
**33672 Pin Oak Parkway
Avon Lake, Ohio**

Description of proposed emissions unit(s):
Ultrasonic vapor degreaser using trichloroethylene.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Western Enterprises
PTI Application: 02-14213
Issued: November 2, 2000

Facility ID: 0247030559

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any

Western Enterprises
PTI Application: 02-14213
Issued: November 2, 2000

Facility ID: 0247030559

information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional

Western Enterprises
PTI Application: 02-14213
Issued: November 2, 2000

Facility ID: 0247030559

facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources are inadequate or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities prove to be inadequate or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit to Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within thirty (30) days after commencing operation of the emissions unit(s) covered by this permit.

Western Enterprises
 PTI Application: 02-14213
 Issued: November 2, 2000

Facility ID: 0247030559

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)
 TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
volatile organic compounds (trichloroethylene)	5.1 TPY

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
L003 - Ultrasonic open top vapor degreaser using trichloroethylene	OAC rule 3745-31-05(A)(3)	The requirements established pursuant to this rule are equivalent to the requirements of 40 CFR Part 63, Subpart T and OAC rule 3745-35-07(B).
	OAC rule 3745-35-07(B)	Emissions of volatile organic compounds (trichloroethylene) shall not exceed 5.1 tons per rolling 12-month period.
	OAC rule 3745-21-09(O)	In accordance with paragraph (O)(6)(b) of OAC rule 3745-21-09, the requirements of OAC rule 3745-21-09(3) shall not apply to this emissions unit.
	40 CFR Part 63, Subpart T	See Additional Terms and Conditions 2.a, 2.b, and 2.c.

2. Additional Terms and Conditions

- 2.a The permittee shall ensure that the chilled air blanket temperature (in degrees F), measured at the center of the air blanket, is no greater than 30 percent of the solvent's boiling point.
- 2.b The permittee shall maintain a freeboard with a freeboard ratio equal to 1.0 or greater.

Western Enterprises
PTI Application 02-14212
Issue

Facility ID: 0247030559

Emissions Unit ID: L003

- 2.c** The permittee shall ensure that the solvent cleaning machine conforms to the following design requirements:

- i. use of an idling and downtime mode cover that shall be in place during the idling mode, and during the downtime mode unless either the solvent has been removed from the machine or maintenance or monitoring is being performed that requires the cover(s) to not be in place. The cover must be able to be readily opened or closed, must completely cover the cleaning machine openings when in place, and must be free of cracks, holes and other defects;
- ii. the solvent cleaning machine shall have a freeboard ratio of 1.0 or greater;
- iii. the solvent cleaning machine shall have an automated parts handling system capable of moving parts or parts baskets at a speed of 3.4 meters per minute (11 feet per minute) or less from the initial loading of parts through removal of cleaned parts;
- iv. the solvent cleaning machine shall be equipped with a device that shuts off the sump heat if the sump liquid solvent level drops to the sump heater coils;
- v. the solvent cleaning machine shall be equipped with a vapor level control device that shuts off sump heat if the vapor level in the vapor cleaning machine rises above the height of the primary condenser; and,
- vi. the solvent cleaning machine shall have a primary condenser.

B. Operational Restrictions

1. The permittee shall meet all of the following required work and operational practices:
 - a. control air disturbances across the solvent cleaning machine opening(s) by incorporating the following control equipment or techniques: cover(s) for the solvent cleaning machine shall be in place during the idling mode and during the downtime mode unless either the solvent has been removed from the machine or maintenance or monitoring is being performed that requires the cover(s) to not be in place;
 - b. the parts basket or the parts being cleaned in the solvent cleaning machine shall not occupy more than 50 percent of the solvent/air interface area unless the parts baskets or parts are introduced at a speed of 0.9 meter per minute (3 feet per minute) or less;
 - c. any spraying operations shall be done within the vapor zone or within a section of the solvent cleaning machine that is not directly exposed to the ambient air (i.e., a baffled or enclosed area of the solvent cleaning machine);

- d. parts shall be oriented so that the solvent drains from them freely. Parts having cavities or blind holes must be tipped or rotated before being removed from the solvent cleaning machine unless an equally effective approach has been approved by the Ohio EPA Northeast District Office;
 - e. parts baskets or parts shall not be removed from the solvent cleaning machine until dripping has stopped;
 - f. during startup of the solvent cleaning machine, the primary condensers shall be turned on before the sump heater;
 - g. during shutdown of the solvent cleaning machine, the sump heater shall be turned off and the solvent vapor layer allowed to collapse before the primary condenser is turned off;
 - h. when solvent is added or drained from the solvent cleaning machine, the solvent shall be transferred using threaded or other leakproof couplings and the end of the pipe in the solvent sump shall be located beneath the liquid solvent surface;
 - i. the solvent cleaning machine and its associated controls shall be maintained as recommended by the manufacturers of the equipment or using alternative maintenance practices that have been demonstrated to the satisfaction of the Ohio EPA Northeast District Office to achieve the same or better results as those recommended by the manufacturer;
 - j. the permittee shall complete and pass the applicable sections of the test of solvent cleaning operating procedures in 40 CFR Part 63, Appendix B if requested during an inspection by the Ohio EPA Northeast District Office;
 - k. waste solvent, still bottoms, and sump bottoms shall be collected and stored in closed containers. The closed containers may contain a device that would allow pressure relief, but must not allow liquid solvent to drain from the container; and,
 - l. sponges, fabric, wood, and paper products shall not be cleaned.
2. The maximum annual solvent (trichloroethylene) usage for this emissions unit shall not exceed 840 gallons, based upon a rolling, 12-month summation of the solvent usage figures.

To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed the solvent usage levels specified in the following table:

Western Enterprises
 PTI A-111111-02-11111
 Issue

Facility ID: 0247030559

Emissions Unit ID: L003

<u>Month(s)</u>	<u>Maximum Allowable Cumulative Solvent Usage</u>
1	70 gallons
2	140 gallons
3	210 gallons
4	280 gallons
5	350 gallons
6	420 gallons
7	490 gallons
8	560 gallons
9	630 gallons
10	700 gallons
11	770 gallons
12	840 gallons

After the first 12 calendar months of operation following the issuance of this permit, compliance with the annual solvent usage limitation shall be based upon a rolling, 12-month summation of the solvent usage figures.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall monitor the hoist speed as described below:
 - a. the permittee shall determine the hoist speed by measuring the time it takes for the hoist to travel a measured distance. The speed is equal to the distance in meters divided by the time in minutes (meters per minute);
 - b. the permittee shall conduct monthly monitoring of the hoist speed. If after the first year, no exceedances of the hoist speed are measured, the permittee may begin monitoring the hoist speed quarterly;
 - c. if an exceedance of the hoist speed occurs during quarterly monitoring, the permittee shall return to a monthly monitoring frequency until another year of compliance without an exceedance is demonstrated; and,
 - d. if the permittee can demonstrate to the satisfaction of the Ohio EPA Northeast District Office in the initial compliance report that the hoist speed cannot exceed a speed of 3.4 meters per minute (11 feet per minute), the required monitoring frequency is quarterly, including during the first year of compliance.

2. The permittee shall maintain the following records in written or electronic form for the lifetime of the solvent cleaning machine:
 - a. owner's manuals, or if not available, written maintenance and operating procedures for the solvent cleaning machine and control equipment;
 - b. the date of installation for the solvent cleaning machine and all of its control devices. If the exact date for the installation is not known, a letter certifying that the cleaning machine and its control devices were installed prior to, or on, November 29, 1993, or after November 29, 1993, may be substituted; and,
 - c. records of the halogenated HAP solvent content for the solvent used in the solvent cleaning machine.
3. The permittee shall maintain the following records in written or electronic form for a period of five years for the solvent cleaning machine:
 - a. the results of control device monitoring required in this section of the permit;
 - b. information on the actions taken to comply with 40 CFR 63.463 (e) and (f), including records of written or verbal orders for replacement parts, a description of the repair made, and additional monitoring conducted to demonstrate that monitored parameters have returned to acceptable levels;
 - c. estimates of annual trichloroethylene consumption for the solvent cleaning machine; and,
 - d. estimates of annual trichloroethylene waste removed from the solvent cleaning machine.
4. The permittee shall conduct monitoring and record the results on a weekly basis for the freeboard refrigeration device by using a thermometer or thermocouple to measure the temperature at the center of the air blanket during the idling mode.
5. The permittee shall maintain monthly records of the following information:
 - a. The solvent usage for each month.
 - b. Beginning after the first 12 calendar months of operation following the issuance of this permit, the rolling 12-month summation of the solvent usage figures.

Also, during the first 12 calendar months of operation following the issuance of this permit, the permittee shall record the cumulative solvent usage for each calendar month.

D. Reporting Requirements

1. The permittee shall submit an initial statement of compliance no later than 150 days of startup. Each initial statement of compliance shall contain the following:
 - a. The name and address of the permittee.
 - b. The address (i.e., physical location) of the solvent cleaning machine.
 - c. A brief description of the solvent cleaning machine type, solvent/air interface area, and existing controls.
 - d. The date of installation for each solvent cleaning machine or a letter certifying that the solvent cleaning machine and its control devices were installed prior to, or after, November 2, 1993.
 - e. The anticipated compliance approach for the solvent cleaning machine.
 - f. An estimate of the annual trichloroethylene consumption for the solvent cleaning machine.
2. The permittee shall submit an initial notification report as soon as practicable before the construction or reconstruction is planned to commence. This report shall include all of the information required in 40 CFR 63.5(d)(1) of subpart A, with the following revisions and additions:
 - a. The report shall include a brief description of the solvent cleaning machine type (batch vapor, batch cold, vapor in-line, or cold in-line), solvent/air interface area, and existing controls.
 - b. The report shall include the anticipated compliance approach for the solvent cleaning machine.
 - c. The report shall include an estimate of the trichloroethylene consumption for the solvent cleaning machine in lieu of the requirements of 40 CFR 63.5(d)(1)(ii)(H), subpart A.
3. The permittee shall submit an annual report by February 1 of each year for the preceding year. Each annual report shall contain the following:

West**PTI****Issued: November 2, 2000**Emissions Unit ID: **L003**

- a. a signed statement from the facility owner or their designee stating that, "All operators of solvent cleaning machines have received training on the proper operation of solvent cleaning machines and their control devices sufficient to pass the test required pursuant to 40 CFR Part 60.463(d)(10)"; and
 - b. an estimate of solvent consumption during the reporting period.
4. The permittee shall submit an exceedance report on a semiannual basis. If the temperature of the chilled air blanket, measured at the center of the air blanket, was greater than 30% of the solvent's boiling point and no correction was made within 15 days of detection, the permittee shall begin to submit a quarterly report until such time that the permittee requests and receives approval of a less frequent reporting frequency from the Director (appropriate field office or local area agency). The permittee may receive approval of less frequent reporting if the following conditions are met: (1) The emissions unit has demonstrated a full year of compliance without an exceedance, (2) the permittee continues to comply with all relevant recordkeeping and monitoring requirements specified in 40 CFR 63.1, General Provisions, and (3) the Director (appropriate field office or local area agency) does not object to a reduce frequency of reporting for the affected emissions unit as provided in paragraph (e)(3)(iii) of subpart A, 40 CFR 63.1, General Provisions. Each exceedance report shall be delivered or post marked by the 30th day following the reporting period. Each exceedance report shall contain the following:
- a. The reason and a description of the exceedance and action(s) taken to comply with 40 CFR 63.463 (e) and (f) including written or verbal orders for replacement parts, a description of the repairs made, and additional monitoring conducted to demonstrate that monitored parameters have returned to acceptable level; and
 - b. If no exceedance has occurred, a statement to that effect shall be submitted.
5. The permittee shall submit deviation (excursion) reports which identify all exceedances of the rolling, 12-month limitation and, for the first 12 calendar months of operation following the issuance of this permit, all exceedances of the maximum allowable cumulative solvent usage levels.

E. Testing Requirements

1. Emission Limit: Emissions of volatile organic compounds (trichloroethylene) shall not exceed 5.1 tons per rolling 12-month period.

Applicable Compliance Method:

To determine the actual volatile organic compound emission rate, the following equation shall be used:

$$E = (L_s - L_w) \times D / 2000$$

Where:

E = organic compound emission rate (tons/year);

L_s = liquid volume of cleaning solvent employed each year (gallons);

L_w = liquid volume of cleaning solvent sent off-site as waste (gallons); and,

D = density of cleaning solvent (pounds/gallon).

2. It is not required that the permittee determine the potential to emit for emissions unit L003 using the equation found in 40 CFR 63.465 since this permit is limiting potential emissions to 5.1 tons VOC per rolling 12-month period.

F. Miscellaneous Requirements

1. All volatile organic compounds (VOCs) emitted from this source (emission unit L003) are hazardous air pollutants (HAPs) as defined in Section 112(b) of the Clean Air Act.

NEW SOURCE REVIEW FORM B

PTI Number: 02-14213 Facility ID: 0247030559

FACILITY NAME Western Enterprises

FACILITY DESCRIPTION Machining screw products CITY/TWP Avon Lake

SIC CODE 3451 SCC CODE 4-01-002-05 EMISSIONS UNIT ID L003

EMISSIONS UNIT DESCRIPTION Ultrasonic open top vapor degreaser using trichloroethylene or perchloroethylene

DATE INSTALLED 8/31/00

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter					
PM ₁₀					
Sulfur Dioxide					
Organic Compounds		NA	4.6 TPY	NA	5.1 TPY
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? 40 CFR Part 63 PSD? OFFSET POLICY?
 Subpart T

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination Use of a freeboard refrigeration device and maintenance of a freeboard ratio of 1.0. Compliance with equipment standards in 40 CFR Part 63, Subpart T. Control consistent with BAT database. Restriction of solvent usage.

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? No
 OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? YES X NO

IDENTIFY THE AIR CONTAMINANTS:

NEW SOURCE REVIEW FORM B

PTI Number: 02-14213 Facility ID: 0247030559

FACILITY NAME Western Enterprises

FACILITY DESCRIPTION Machining screw products CITY/TWP Avon Lake

Ohio EPA Permit to Install Information Form Please describe below any documentation which is being submitted with this recommendation (must be sent the same day). Electronic items should be submitted with the e-mail transmitting the PTI terms, and in software that CO can utilize. If mailing any hard copy, this section must be printed as a cover page. All items must be clearly labeled indicating the PTI name and number. Submit **hard copy items to Pam McGraner**, AQM&P, DAPC, Central Office, and electronic files to airpti@epa.state.oh.us

Please fill out the following. If the checkbox does not work, replace it with an 'X'

	<u>Electronic</u>	<u>Additional information File Name Convention (your PTI # plus this letter)</u>	<u>Hard Copy</u>	<u>None</u>
<u>Calculations (required)</u>	<input type="checkbox"/>	0000000c.wpd	<input checked="" type="checkbox"/>	
<u>Modeling form/results</u>	<input type="checkbox"/>	0000000s.wpd	<input type="checkbox"/>	<input checked="" type="checkbox"/>
<u>PTI Application (complete or partial)*</u>	<input type="checkbox"/>	0000000a.wpd	<input type="checkbox"/>	<input checked="" type="checkbox"/>
<u>BAT Study</u>	<input type="checkbox"/>	0000000b.wpd	<input type="checkbox"/>	<input checked="" type="checkbox"/>
<u>Other/misc.</u>	<input type="checkbox"/>	0000000t.wpd	<input type="checkbox"/>	<input checked="" type="checkbox"/>

* Mandatory for netting, PSD, nonattainment NSR, 112(g), 21-07(G)(9)(g) and 21-09(U)(2)(f) - 2 complete copies.

Please complete (see comment bubble to the left for additional instructions):

NSR Discussion

NONE

Please complete for these type permits (For PSD/NSR Permit, place mouse over this text):

Synthetic Minor Determination and/or **Netting Determination**

Permit To Install **02-14213**

- A. Source Description: Western Enterprises has applied for a permit to install an open top vapor degreaser (emissions unit L003) to replace an existing open top vapor degreaser (either emissions unit L001 or L002). The degreaser utilizes trichloroethylene as a solvent and is subject to 40 CFR Part 63 Subpart T, the MACT standard for halogenated solvent cleaning. The vapor degreaser will be installed upon final issuance of the permit to install.
- B. Facility Emissions and Attainment Status: The vapor degreaser emits trichloroethylene which is a volatile organic compound (VOC) and hazardous air pollutant (HAP). Lorain county is attainment for ozone.
- C. Source Emissions: Maximum potential VOC (trichloroethylene) emissions from L003 are 5.24 tons per year. Maximum potential VOC (trichloroethylene) emissions are 4.85 tons per year from each L001 and L002. Therefore, potential emissions of trichloroethylene from L003 in combination with potential emissions of trichloroethylene from either L001 or L002 will exceed 10 tons per year. In accordance with the definition of OAC rule 3745-77, this facility is a major source because of potential trichloroethylene emissions and is required to obtain a Title V permit. There are no other sources of trichloroethylene at the facility.

Western Enterprises has proposed to limit trichloroethylene emissions from emissions unit L003 by limiting trichloroethylene usage to 70 gallons per month and 840 cumulative gallons per year which is equivalent to 5.1 tons per

NEW SOURCE REVIEW FORM B

PTI Number: 02-14213 Facility ID: 0247030559

FACILITY NAME Western Enterprises

FACILITY DESCRIPTION Machining screw products CITY/TWP Avon Lake

year. The permit to install will contain terms and conditions to establish these limits. Potential trichloroethylene emissions from either emissions unit L001 or L002 are 4.85 tons per year. Therefore, total trichloroethylene emissions for the facility will be limited to 9.95 tons per year.

- D. Conclusion: The permit will limit emissions over a rolling 12-month period by limiting trichloroethylene usage. Western Enterprises will be required to record the monthly trichloroethylene usage. Exceedance reports will be submitted if necessary.

The allowable emission rate for trichloroethylene from emissions unit L003 will be 5.1 tons per year. The allowable emission rate for trichloroethylene from either emissions unit L001 or L002 will be 4.85 tons per year. The total allowable emission rate for trichloroethylene for the facility will be 9.95 tons per year. Therefore, this facility will not be a major source per the definition in OAC rule 3745-77 and will not be required to obtain a Title V permit.

PLEASE PROVIDE ADDITIONAL NOTES OR COMMENTS AS NECESSARY:

NONE

Please complete:

SUMMARY (for informational purposes only)	
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS	
<u>Pollutant</u>	<u>Tons Per Year</u>
volatile organic compounds (trichloroethylene)	5.1 TPY