

Facility ID: 0278050669 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0278050669 Emissions Unit ID: P002 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
blast room #2 with baghouse	OAC rule 3745-31-05(A)(3) (PTI 02-12459)	Particulate emissions (PE) shall not exceed 0.03 grain per dry standard cubic foot of exhaust gases, 5.2 pounds per hour and 22.5 tons per year.
	OAC rule 3745-17-07(A)	Visible PE from any stack shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.
	OAC rule 3745-17-11	The emission limitation required by this applicable rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. **Additional Terms and Conditions**
 - (a) None

B. Operational Restrictions

1. The pressure drop across the baghouse shall be maintained within the range of 2 to 6 inches of water while the emissions unit is in operation.

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each day for the line:
 - a. the total amount of abrasive blasting material employed; and
 - b. the total hours of operation of the blast room.

The permittee shall also determine the annual amount of abrasive blasting material employed, by summing the daily usages.
2. The permittee shall operate and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a daily basis.

D. Reporting Requirements

1. The permittee shall submit pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above.

E. Testing Requirements

1. Compliance with the emissions limitations in section A.1 of these terms and conditions shall be determined in accordance with the following methods:
Emission Limitation:
Visible PE from any stack shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.

Applicable Compliance Method:
If required, compliance shall be demonstrated based upon visible particulate emission observations performed

in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(1).

Emission Limitations:

PE shall not exceed 0.03 grain per dry standard cubic foot of exhaust gases and 5.2 pounds per hour.

Applicable Compliance Method:

To determine the actual hourly emission rate for PE, the following equation shall be used:

$$E = (0.03 \text{ lb PE/lb abrasive material}) (AB) (1 - 0.95) / (H)$$

where:

E = the average hourly emission rate of PE, in lbs/hr;

0.03 lb/lb abrasive material = the emission factor for PE, from a USEPA report "Development of Particulate Emission Factors for Uncontrolled Abrasive Blasting Operations" from MRI, April 1994;

AB = the amount of abrasive material used in this operation per day, in lbs;

H = the total hours this process operated per day; and

1-.95 = a correction for the assumed collector efficiency of 95%.

If required, compliance with the grain loading and hourly emission limitations shall be demonstrated in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 5 and the procedures specified in OAC rule 3745-17-03(B)(10).

Emission Limitation:

PE shall not exceed 22.5 tons per year.

Applicable Compliance Method:

Yearly emissions shall be calculated using the following equation:

$$E = (0.03 \text{ lb PE/lb abrasive material}) (AB) (1 - 0.95) / (2000 \text{ lbs/ton})$$

where:

E = the annual rate of PE, in tons;

0.03 lb/lb abrasive material = the emission factor for PE, from a USEPA report "Development of Particulate Emission Factors for Uncontrolled Abrasive Blasting Operations" from MRI, April 1994;

AB = the amount of abrasive material used during the calendar year, in lbs;

1-.95 = a correction for the assumed collector efficiency of 95%; and

2000 lbs/ton = the conversion factor for lbs to tons.

F. **Miscellaneous Requirements**

1. None