

Synthetic Minor Determination and/or **Netting Determination**

Permit To Install 02-19084

A. Source Description

Forest City Technologies Inc. has applied for a permit to install eleven (11) metal parts coating lines. These coating lines, along with all of the other coating lines at the facility, are subject to 40 CFR, Part 63, Subpart M, the MACT standard for miscellaneous metal parts and products based on potential facility emissions. However, see section C below for limitations. The facility is located in Lorain county.

B. Facility Emissions and Attainment Status

The eleven (11) metal parts coating lines, a vapor degreaser utilizing methylene chloride, and some of the other coating lines at the facility emit hazardous air pollutants (HAPs). The coating lines also emit volatile organic compounds (VOCs). Maximum potential single HAP and combined HAP emission for the facility exceed 10 and 25 tons per year, respectively. Lorain county is attainment for ozone.

C. Source Emissions

Forest City Technologies Inc. has proposed to limit HAP emissions facility-wide to 9.9 tons per year of each single HAP and 24.9 tons per year of combined HAPs. This permit to install will contain terms and conditions to establish these limits.

D. Conclusion

This permit to install will limit HAP emissions by limiting facility-wide HAP emissions over a rolling, 12-month period to 9.9 tons per year of each single HAP and 24.9 tons per year of combined HAPs. Forest City Technologies Inc. will be required to record the monthly facility-wide emissions of each single HAP and all combined HAPs from all of the coating lines and the vapor degreaser. Exceedance reports will be submitted if necessary. In this way, the facility will address the issue of 40CFR Part 63, subpart M by not being major for HAPs.



State of Ohio Environmental Protection Agency

**RE: DRAFT PERMIT TO INSTALL
LORAIN COUNTY**

CERTIFIED MAIL

Street Address:

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov.
Center

Application No: 02-19084
Fac ID: 0247170841

DATE: 2/15/2005

Forest City Technologies Inc Plant 2/4
Marshall Searles
PO Box 86 299 Clay St
Wellington, OH 44090

You are hereby notified that the Ohio Environmental Protection Agency has made a draft action recommending that the Director issue a Permit to Install for the air contaminant source(s) [emissions unit(s)] shown on the enclosed draft permit. This draft action is not an authorization to begin construction or modification of your emissions unit(s). The purpose of this draft is to solicit public comments on the proposed installation. A public notice concerning the draft permit will appear in the Ohio EPA Weekly Review and the newspaper in the county where the facility will be located. Public comments will be accepted by the field office within 30 days of the date of publication in the newspaper. Any comments you have on the draft permit should be directed to the appropriate field office within the comment period. A copy of your comments should also be mailed to Robert Hodanbosi, Division of Air Pollution Control, Ohio EPA, P.O. Box 1049, Columbus, OH, 43266-0149.

A Permit to Install may be issued in proposed or final form based on the draft action, any written public comments received within 30 days of the public notice, or record of a public meeting if one is held. You will be notified in writing of a scheduled public meeting. Upon issuance of a final Permit to Install a fee of **\$400** will be due. Please do not submit any payment now.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469. If you have any questions about this draft permit, please contact the field office where you submitted your application, or Mike Ahern, Field Operations & Permit Section at (614) 644-3631.

Sincerely,

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: USEPA

NEDO

LORAIN COUNTY

PUBLIC NOTICE
ISSUANCE OF DRAFT PERMIT TO INSTALL **02-19084** FOR AN AIR CONTAMINANT SOURCE FOR
Forest City Technologies Inc Plant 2/4

On 2/15/2005 the Director of the Ohio Environmental Protection Agency issued a draft action of a Permit To Install an air contaminant source for **Forest City Technologies Inc Plant 2/4**, located at **401 Maygar St, Wellington, Ohio**.

Installation of the air contaminant source identified below may proceed upon final issuance of Permit To Install 02-19084:

Chapter 31 modification to PTI 02-17168, issued on 4/3/2003 to increase the maximum material usage rates for K044 and K049.

Comments concerning this draft action, or a request for a public meeting, must be sent in writing to the address identified below no later than thirty (30) days from the date this notice is published. All inquiries concerning this draft action may be directed to the contact identified below.

Dennis Bush, Ohio EPA, Northeast District Office, 2110 East Aurora Road, Twinsburg, OH 44087
[(330)425-9171]



**Permit To Install
Terms and Conditions**

**Issue Date: To be entered upon final issuance
Effective Date: To be entered upon final issuance**

DRAFT PERMIT TO INSTALL 02-19084

Application Number: 02-19084
Facility ID: 0247170841
Permit Fee: **To be entered upon final issuance**
Name of Facility: Forest City Technologies Inc Plant 2/4
Person to Contact: Marshall Searles
Address: PO Box 86 299 Clay St
Wellington, OH 44090

Location of proposed air contaminant source(s) [emissions unit(s)]:

**401 Maygar St
Wellington, Ohio**

Description of proposed emissions unit(s):

Chapter 31 modification to PTI 02-17168, issued on 4/3/2003 to increase the maximum material usage rates for K044 and K049.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

A. State and Federally Enforceable Permit To Install General Terms and Conditions**1. Monitoring and Related Recordkeeping and Reporting Requirements**

- a. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:
 - i. The date, place (as defined in the permit), and time of sampling or measurements.
 - ii. The date(s) analyses were performed.
 - iii. The company or entity that performed the analyses.
 - iv. The analytical techniques or methods used.
 - v. The results of such analyses.
 - vi. The operating conditions existing at the time of sampling or measurement.
- b. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.
- c. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall submit required reports in the following manner:
 - i. Reports of any required monitoring and/or recordkeeping of federally enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
 - ii. Quarterly written reports of (i) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, excluding deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06, that have been detected by the testing, monitoring and recordkeeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures taken, shall be made to the appropriate Ohio EPA District Office or local air agency. The written reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. See B.9 below if no deviations occurred during the quarter.

- iii. Written reports, which identify any deviations from the federally enforceable monitoring, recordkeeping, and reporting requirements contained in this permit shall be submitted to the appropriate Ohio EPA District Office or local air agency every six months, i.e., by January 31 and July 31 of each year for the previous six calendar months. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report, which states that no deviations occurred during that period.
- iv. Each written report shall be signed by a responsible official certifying that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.

2. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction, i.e., upset, of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. (The definition of an upset condition shall be the same as that used in OAC rule 3745-15-06(B)(1) for a malfunction.) The verbal and written reports shall be submitted pursuant to OAC rule 3745-15-06.

Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emission unit(s) that is (are) served by such control system(s).

3. Risk Management Plans

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. 7401 et seq. ("Act"), the permittee shall comply with the requirement to register such a plan.

4. Title IV Provisions

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

5. Severability Clause

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition declared invalid.

Forest City Technologies Inc Plant 2/4

Facility ID: 0247170841

PTI Application: 02-19084

Issued: To be entered upon final issuance

6. General Requirements

- a. The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and reissuance, or modification, or for denial of a permit renewal application.
- b. It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.
- c. This permit may be modified, reopened, revoked, or revoked and reissued, for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.
- d. This permit does not convey any property rights of any sort, or any exclusive privilege.
- e. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

7. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit To Install fees within 30 days after the issuance of this Permit To Install.

8. Federal and State Enforceability

Only those terms and conditions designated in this permit as federally enforceable, that are required under the Act, or any of its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA, the State, and citizens under the Act. All other terms and conditions of this permit

shall not be federally enforceable and shall be enforceable under State law only.

9. Compliance Requirements

- a. Any document (including reports) required to be submitted and required by a federally applicable requirement in this permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.
- b. Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:
 - i. At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.
 - ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with ORC section 3704.08.
 - iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.
 - iv. As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.
- c. The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually, or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:
 - i. Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
 - ii. An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

10. Permit To Operate Application

- a. If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete

Issued: To be entered upon final issuance

Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).

- b. If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35, the source(s) identified in this Permit To Install is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the source(s) covered by this permit.

11. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

12. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

Forest City Technologies Inc Plant 2/4

Facility ID: 0247170841

PTI Application: 02-19084

Issued: To be entered upon final issuance

B. State Only Enforceable Permit To Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping of state-only enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from state-only required emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

4. Termination of Permit To Install

This permit to install shall terminate within eighteen months of the effective date of the permit to install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may

Issued: To be entered upon final issuance

be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

5. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

6. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

7. Applicability

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate application must be made to the Director for the installation or modification of any other

Forest City Technologies Inc Plant 2/4

Facility ID: 0247170841

PTI Application: 02-19084

Issued: To be entered upon final issuance

emissions unit(s).

8. Construction Compliance Certification

If applicable, the applicant shall provide Ohio EPA with a written certification (see enclosed form if applicable) that the facility has been constructed in accordance with the Permit To Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

9. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations (See Section A of This Permit)

If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.

C. Permit To Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)

TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
VOC	10.04
Single HAP	9.9
Combined HAP	24.9

Forest City Technologies Inc Plant 2/4

PTI Application: 02-19084

Issued: To be entered upon final issuance

Facility ID: 0247170841

Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

A. State and Federally Enforceable Permit To Install Facility Specific Terms and Conditions

None

B. State Only Enforceable Permit To Install Facility Specific Terms and Conditions

None

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K039 - Grip Line 1: Coater and natural gas oven no. 1 equipped with a catalytic oxidizer	OAC rule 3745-31-05(A)(3)	The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09(B)(6).
Terms in this permit supercede those identified in PTI 02-17168 issued 04/03/03.	OAC rule 3745-21-09(B)(6)	VOC emissions shall not exceed 8.51 pounds per day.
	OAC rule 3745-21-09(U)	VOC emissions shall not exceed 10.04 tons per year. See A.I.2.a below.
	OAC rule 3745-21-09(B)(3)(l)	81 percent overall reduction of VOCs by weight and 90 percent destruction for all solvent based coatings.
	OAC rule 3745-21-09(B)(3)(m)	In lieu of complying with the requirements of this rule, the permittee has opted to comply with the requirements of OAC rule 3745-21-09(B).
	OAC rule 3745-21-09(B)(3)(n)	See A.III.2.a, A.III.2b, and A.III.2.c below.
	OAC rule 3745-35-07	See A.IV.2.a, A.IV.2.b, and A.IV.2.c below.
		See A.III.1, A.V.1.c, and A.V.2 below.
		See A.I.2.b and A.I.2.c below.

Issued: To be entered upon final issuance**2. Additional Terms and Conditions**

- 2.a** The emission limitation of 10.04 tons VOC per year is based on the combined annual emissions from this emissions unit (K039) and emissions units K040, K041, K042, K043, K044, K045, K046, K047, K048, and K049.
- 2.b** The emissions of each single hazardous air pollutant (HAP) from all emissions units at the facility shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation. The permittee shall use existing records to determine compliance with the rolling 12-month restrictions upon issuance of this permit. Therefore, it is not necessary to establish federally enforceable restrictions for the first 12 months of operation under the provisions of this permit.
- 2.c** The emissions of the combined HAPs from all emissions units at the facility shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation. The permittee shall use existing records to determine compliance with the rolling 12-month restrictions upon issuance of this permit. Therefore, it is not necessary to establish federally enforceable restrictions for the first 12 months of operation under the provisions of this permit.

II. Operational Restrictions

1. Exhaust gases from operation of the emissions unit shall be vented to the catalytic oxidizer.
2. The average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below 652 degrees Fahrenheit, the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance. In the event that future emission tests are conducted, the average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
3. The catalytic oxidizer shall be operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manuals. The VOC conversion efficiency of the catalyst in the catalytic oxidizer, as determined by the catalyst activity testing, shall be at least 90% at a test temperature that is representative of the normal temperature at the catalyst bed inlet. Solvent loading during catalyst analysis shall be consistent with the test laboratory's normal testing protocol.
4. All ventilation fans associated with this emissions unit and the catalytic oxidizer shall be in

operation at all times when this emissions unit is in operation.

5. When employing the catalytic oxidizer, all bypass dampers, actuator pins, and associated motors shall be in the correct position and in good operating condition at all times when this emissions unit is in operation to ensure that all captured VOC emissions are vented to the catalytic oxidizer. Also, all the hooding and ductwork comprising the VOC emission capture system for this emissions unit shall be free of leaks and holes that would permit the escape of the captured VOC emissions.
6. The average, total exhaust flow rate from this emissions unit to the catalytic oxidizer shall be within 25% of 1700 feet per minute (fpm), the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation. In the event that future emission tests are conducted, the average, total exhaust flow rate from this emissions unit to the catalytic oxidizer shall be within 25% of the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain continuous monitors and recorder(s) which measure and record the temperature immediately upstream and downstream of the incinerator's catalyst bed when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitors and recorder(s) shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.
2. The permittee shall collect and record the following information each day:
 - a. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
 - b. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance. The permittee may use the oxidizer's temperature chart to determine the temperature differential across the catalyst bed.
 - c. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation. The permittee may use the current temperature chart as the log documenting that the monitoring equipment and control device are operating. Each bypass of the collection system and/or control device shall be logged as to the date and time.

Issued: To be entered upon final issuance

3. The permittee shall perform an inspection of the catalytic oxidizer, including the catalyst bed, at least once each calendar year. Each inspection shall consist of internal and visual inspections in accordance with the manufacturer's recommendations and shall include a physical inspection of the unit and checks of associated equipment, including but not limited to burners, controls, dampers, valves, and monitoring and recording equipment. Repair and replacement of equipment shall be performed as determined by the inspection. In accordance with the testing schedule in section A.V, a sample of catalyst material shall be collected from the catalyst bed to perform the catalyst activity tests required in section A.V.
4. The permittee shall maintain a record of the results of each annual inspection of the catalytic oxidizer, as well as the results of each catalyst activity test required in section A.V.
5. The permittee shall operate and maintain a flow meter at the inlet to the catalytic oxidizer to ensure that the exhaust from the coating room and the emissions units in the coating room are being directed to the catalytic oxidizer. The permittee shall collect and record the flow rate at the inlet to the catalytic oxidizer on a daily basis.
6. Each calendar month, the permittee shall inspect the operational condition and integrity of each ventilation fan comprising the capture system. Ventilation fan observations shall include visual inspections of the fan wheel, belts, and bearings. Lubrication of bearings and replacement of parts shall occur as necessary. The permittee shall document the results of all monthly inspections, including any corrective actions taken.
7. Each calendar month, the permittee shall inspect the operational condition and integrity of all hooding, ductwork, and bypass dampers comprising the capture system. Hooding and ductwork observations shall include visual inspections to verify that the damper setting is in the correct position (i.e., to oxidizer or to atmosphere) and visual inspections of the actuator and motor to verify that the actuator pin and the motor are operating properly. The permittee shall document the results of all monthly inspections, including any corrective actions taken.
8. The permittee shall collect and record the following information each day for this coating line (K039):
 - a. The name and identification number of each coating, as applied;
 - b. The volume in gallons of each coating, as applied;
 - c. The VOC content of each coating, as applied, in pounds per gallon; and
 - d. The total VOC emissions from all coatings employed [summation of (b x c) for all coatings multiplied by the overall control efficiency for the control equipment as

Emissions Unit ID: K039

determined during the most recent emission test that demonstrated that the source was in compliance].

9. The permittee shall collect and record the following information each month for all coating lines at the facility:
 - a. The name and identification number of each coating, as applied;
 - b. The volume in gallons of each coating, as applied;
 - c. The HAP content of each coating, as applied, in pounds per gallon;

Issued: To be entered upon final issuance

- d. The total HAP emissions for all emissions units of each single HAP [summation of (b x c) for all coatings multiplied by the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the source was in compliance]; and
- e. The total combined HAP emissions for all emissions units [summation of (d) for all HAPs emitted by the coating lines plus the monthly HAP emissions from the vapor degreaser (L001)].

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and was not vented to the catalytic oxidizer.
2. The permittee shall submit quarterly summaries of the following records:
 - a. a log of operating time for the capture (collection) system, control device, monitoring equipment, and the associated emissions unit;
 - b. all 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed (as determined by the continuous temperature monitor) did not comply with the temperature limitation specified above; and
 - c. all 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed (as determined by the continuous temperature monitor) was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance.

NOTE: Information submitted pursuant to section A.IV.2.c is not relevant for determining compliance with any operational restriction contained in section A.II. As long as the permittee performs the monitoring, record keeping, and reporting specified in sections A.III.2.b and A.IV.2.c of these terms and conditions, an average temperature difference across the catalyst bed of less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance shall not constitute a violation of any operational restriction or be considered a deviation.

3. The permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and the daily average air flow rate in the inlet stack to the catalytic

Emissions Unit ID: K039

oxidizer was more than 25% less than 1700 feet per minute (fpm), the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation. In the event that future emission tests are conducted, the permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and the daily average air flow rate in the inlet stack to the catalytic oxidizer was more than 25% less than the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation.

4. The permittee shall submit deviation (excursion) reports which identify each day where the daily VOC emission rate exceeded 8.51 pounds per day for this emissions unit (K039). The notification shall include a copy of such record and shall be sent to the Ohio EPA Northeast District Office within 30 days after the exceedance occurs.
5. The permittee shall submit deviation (excursion) reports which identify each month during which the rolling, 12-month emissions of any single HAP from all emissions units at the facility exceeded 9.9 tons per year, and the actual rolling, 12-month emissions of each such single HAP for each such month.
6. The permittee shall submit deviation (excursion) reports which identify each month during which the rolling, 12-month emissions of combined HAPs from all emissions units at the facility exceeded 24.9 tons per year, and the actual rolling, 12-month emissions of combined HAPs for each such month.
7. The permittee shall submit annual reports which specify the actual annual VOC emissions for the emissions unit (K039) and emissions units K040, K041, K042, K043, K044, K045, K046, K047, K048, and K049; combined. The reports shall be submitted by January 31 of each year and cover the previous calendar year.
8. The permittee shall submit annual reports which summarize the facility-wide emissions of each single HAP and combined HAPs from all emissions units at the facility. The reports shall include the emission calculations, be submitted by January 31 of each year, and cover the previous calendar year.
9. The permittee shall submit annual reports which summarize the results of the annual inspections conducted on the catalytic oxidizer by the manufacturer's representative. The reports shall describe any maintenance conducted on the catalytic oxidizer as a direct result of the inspections by manufacturer's representative. The reports shall be submitted by January 31 of each year and cover the previous calendar year.
10. The permittee shall submit reports that include the results of the catalyst activity tests required in section A.V. These reports shall be submitted within 45 days after each catalyst activity test is performed.

V. Testing Requirements

Issued: To be entered upon final issuance

1. Compliance with the emission limitations in Section A.I.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation:

VOC emissions shall not exceed 8.51 pounds per day.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in section A.III. 8 of these terms and conditions.
 - b. Emission Limitation:

VOC emissions shall not exceed 10.04 tons per year.

Applicable Compliance Method:

Compliance with the annual emission limitation is shown as long as compliance with the daily emission limitations for this emissions unit (K039) and emissions units K040, K041, K042, K043, K044, K045, K046, K047, K048, and K049, are maintained (the annual emission limitation was calculated by multiplying the sum of the daily emission limitations for this emissions unit (K039) and emissions units K040, K041, K042, K043, K044, K045, K046, K047, K048, and K049, by 365 and dividing by 2000).
 - c. Emission Limitation:

81 percent overall reduction of VOCs by weight and 90 percent destruction for all solvent based coatings.

Applicable Compliance Method:

If required by the Ohio EPA Northeast District Office, compliance shall be demonstrated in accordance with 40 CFR Part 60, Appendix A, Methods 25, 25A, and 40 CFR Part 51, Appendix M, Method 204. Performance testing shall be in accordance with OAC rule 3745-21-10(C).
 - d. Emission Limitation:

The emissions of each single hazardous air pollutant (HAP) from all emissions units at the facility shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation.

Forest City Technologies Inc Plant 2/4
PTI Application: 02-10084
Issued

Facility ID: 0247170841

Emissions Unit ID: K039

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in section A.III. 9 of these terms and conditions.

e. Emission Limitation:

The emissions of the combined HAPs from all emissions units at the facility shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation.

Issued: To be entered upon final issuance

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in section A.III. 9 of these terms and conditions.

2. Emission testing demonstrating compliance with the overall control efficiency limitation for VOC of 81 percent, the destruction efficiency limitation for VOC of 90 percent, and capture efficiency was conducted on January 8, 2004, as required by PTI 02-17168 issued 04/03/03.
3. US EPA Method 24 shall be used to determine the VOC contents of all the coatings employed in this emissions unit.
4. The permittee shall conduct, or have conducted, catalyst activity testing using the catalyst sample collected during the annual inspection described in section A.III. An intent to test notification shall not be required for the testing noted in this term. The procedures for the catalyst activity test shall be in accordance with the manufacturer's recommendations.

VI. Miscellaneous Requirements

None

Forest
PTI A

Emissions Unit ID: K039

Issued: To be entered upon final issuance

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K039 - Grip Line 1: Coater and natural gas oven no. 1 equipped with a catalytic oxidizer Terms in this permit supercede those identified in PTI 02-17168 issued 04/03/03.	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit (K039) was evaluated based on the actual materials (coatings) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant potentially emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the

Issued: To be entered upon final issuance

modeling for the "worst case" pollutant(s):

Pollutant: toluene

TLV (ug/m3): 188,400

Maximum Hourly Emission Rate (lbs/hr): 3.31

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 250.5

MAGLC (ug/m3): 4476

Physical changes to or changes in the method of operation of the emissions unit after its installation could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

28

Forest

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: K039

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Forest
PTI A

Emissions Unit ID: K040

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	OAC rule 3745-35-07
K040 - Grip Line 2: Coater and natural gas oven no. 2 equipped with a catalytic oxidizer	OAC rule 3745-31-05(A)(3)	
Terms in this permit supercede those identified in PTI 02-17168 issued 04/03/03.	OAC rule 3745-21-09(B)(6)	
	OAC rule 3745-21-09(U)	
	OAC rule 3745-21-09(B)(3)(l)	
	OAC rule 3745-21-09(B)(3)(m)	
	OAC rule 3745-21-09(B)(3)(n)	

Forest

PTI A

Emissions Unit ID: K040

Issued: To be entered upon final issuance

Applicable Emissions
Limitations/Control
Measures

The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09(B)(6).

VOC emissions shall not exceed 8.51 pounds per day.

VOC emissions shall not exceed 10.04 tons per year.
See A.I.2.a below.

81 percent overall reduction of VOCs by weight and 90 percent destruction for all solvent based coatings.

In lieu of complying with the requirements of this rule, the permittee has opted to comply with the requirements of OAC rule 3745-21-09(B).

See A.III.2.a, A.III.2b, and A.III.2.c below.

See A.IV.2.a, A.IV.2.b, and A.IV.2.c below.

See A.III.1, A.V.1.c, and A.V.2 below.

See A.I.2.b and A.I.2.c below.

Issued: To be entered upon final issuance**2. Additional Terms and Conditions**

- 2.a** The emission limitation of 10.04 tons VOC per year is based on the combined annual emissions from this emissions unit (K040) and emissions units K039, K041, K042, K043, K044, K045, K046, K047, K048, and K049.
- 2.b** The emissions of each single hazardous air pollutant (HAP) from all emissions units at the facility shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation. The permittee shall use existing records to determine compliance with the rolling 12-month restrictions upon issuance of this permit. Therefore, it is not necessary to establish federally enforceable restrictions for the first 12 months of operation under the provisions of this permit.
- 2.c** The emissions of the combined HAPs from all emissions units at the facility shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation. The permittee shall use existing records to determine compliance with the rolling 12-month restrictions upon issuance of this permit. Therefore, it is not necessary to establish federally enforceable restrictions for the first 12 months of operation under the provisions of this permit.

II. Operational Restrictions

1. Exhaust gases from operation of the emissions unit shall be vented to the catalytic oxidizer.
2. The average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below 652 degrees Fahrenheit, the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance. In the event that future emission tests are conducted, the average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
3. The catalytic oxidizer shall be operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manuals. The VOC conversion efficiency of the catalyst in the catalytic oxidizer, as determined by the catalyst activity testing, shall be at least 90% at a test temperature that is representative of the normal temperature at the catalyst bed inlet. Solvent loading during catalyst analysis shall be consistent with the test laboratory's normal testing protocol.
4. All ventilation fans associated with this emissions unit and the catalytic oxidizer shall be in

operation at all times when this emissions unit is in operation.

5. When employing the catalytic oxidizer, all bypass dampers, actuator pins, and associated motors shall be in the correct position and in good operating condition at all times when this emissions unit is in operation to ensure that all captured VOC emissions are vented to the catalytic oxidizer. Also, all the hooding and ductwork comprising the VOC emission capture system for this emissions unit shall be free of leaks and holes that would permit the escape of the captured VOC emissions.
6. The average, total exhaust flow rate from this emissions unit to the catalytic oxidizer shall be within 25% of 1700 feet per minute (fpm), the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation. In the event that future emission tests are conducted, the average, total exhaust flow rate from this emissions unit to the catalytic oxidizer shall be within 25% of the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain continuous monitors and recorder(s) which measure and record the temperature immediately upstream and downstream of the incinerator's catalyst bed when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitors and recorder(s) shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.
2. The permittee shall collect and record the following information each day:
 - a. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
 - b. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance. The permittee may use the oxidizer's temperature chart to determine the temperature differential across the catalyst bed.
 - c. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation. The permittee may use the current temperature chart as the log documenting that the monitoring equipment and control device are operating. Each bypass of the collection system and/or control device shall be logged as to the date and time.

Issued

Emissions Unit ID: K040

3. The permittee shall perform an inspection of the catalytic oxidizer, including the catalyst bed, at least once each calendar year. Each inspection shall consist of internal and visual inspections in accordance with the manufacturer's recommendations and shall include a physical inspection of the unit and checks of associated equipment, including but not limited to burners, controls, dampers, valves, and monitoring and recording equipment. Repair and replacement of equipment shall be performed as determined by the inspection. In accordance with the testing schedule in section A.V, a sample of catalyst material shall be collected from the catalyst bed to perform the catalyst activity tests required in section A.V.
4. The permittee shall maintain a record of the results of each annual inspection of the catalytic oxidizer, as well as the results of each catalyst activity test required in section A.V.
5. The permittee shall operate and maintain a flow meter at the inlet to the catalytic oxidizer to ensure that the exhaust from the coating room and the emissions units in the coating room are being directed to the catalytic oxidizer. The permittee shall collect and record the flow rate at the inlet to the catalytic oxidizer on a daily basis.
6. Each calendar month, the permittee shall inspect the operational condition and integrity of each ventilation fan comprising the capture system. Ventilation fan observations shall include visual inspections of the fan wheel, belts, and bearings. Lubrication of bearings and replacement of parts shall occur as necessary. The permittee shall document the results of all monthly inspections, including any corrective actions taken.
7. Each calendar month, the permittee shall inspect the operational condition and integrity of all hooding, ductwork, and bypass dampers comprising the capture system. Hooding and ductwork observations shall include visual inspections to verify that the damper setting is in the correct position (i.e., to oxidizer or to atmosphere) and visual inspections of the actuator and motor to verify that the actuator pin and the motor are operating properly. The permittee shall document the results of all monthly inspections, including any corrective actions taken.
8. The permittee shall collect and record the following information each day for this coating line (K040):
 - a. The name and identification number of each coating, as applied;
 - b. The volume in gallons of each coating, as applied;
 - c. The VOC content of each coating, as applied, in pounds per gallon; and
 - d. The total VOC emissions from all coatings employed [summation of (b x c) for all coatings multiplied by the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the source was in compliance].
9. The permittee shall collect and record the following information each month for all coating lines at the facility:

Issued: To be entered upon final issuance

- a. The name and identification number of each coating, as applied;
- b. The volume in gallons of each coating, as applied;
- c. The HAP content of each coating, as applied, in pounds per gallon;
- d. The total HAP emissions for all emissions units of each single HAP [summation of (b x c) for all coatings multiplied by the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the source was in compliance]; and
- e. The total combined HAP emissions for all emissions units [summation of (d) for all HAPs emitted by the coating lines plus the monthly HAP emissions from the vapor degreaser (L001)].

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and was not vented to the catalytic oxidizer.
2. The permittee shall submit quarterly summaries of the following records:
 - a. a log of operating time for the capture (collection) system, control device, monitoring equipment, and the associated emissions unit;
 - b. all 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed (as determined by the continuous temperature monitor) did not comply with the temperature limitation specified above; and
 - c. all 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed (as determined by the continuous temperature monitor) was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance.

NOTE: Information submitted pursuant to section A.IV.2.c is not relevant for determining compliance with any operational restriction contained in section A.II. As long as the permittee performs the monitoring, record keeping, and reporting specified in sections A.III.2.b and A.IV.2.c of these terms and conditions, an average temperature difference across the catalyst bed

Emissions Unit ID: K040

of less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance shall not constitute a violation of any operational restriction or be considered a deviation.

3. The permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and the daily average air flow rate in the inlet stack to the catalytic oxidizer was more than 25% less than 1700 feet per minute (fpm), the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation. In the event that future emission tests are conducted, the permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and the daily average air flow rate in the inlet stack to the catalytic oxidizer was more than 25% less than the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation.
4. The permittee shall submit deviation (excursion) reports which identify each day where the daily VOC emission rate exceeded 8.51 pounds per day for this emissions unit (K040). The notification shall include a copy of such record and shall be sent to the Ohio EPA Northeast District Office within 30 days after the exceedance occurs.
5. The permittee shall submit deviation (excursion) reports which identify each month during which the rolling, 12-month emissions of any single HAP from all emissions units at the facility exceeded 9.9 tons per year, and the actual rolling, 12-month emissions of each such single HAP for each such month.
6. The permittee shall submit deviation (excursion) reports which identify each month during which the rolling, 12-month emissions of combined HAPs from all emissions units at the facility exceeded 24.9 tons per year, and the actual rolling, 12-month emissions of combined HAPs for each such month.
7. The permittee shall submit annual reports which specify the actual annual VOC emissions for the emissions unit (K040) and emissions units K039, K041, K042, K043, K044, K045, K046, K047, K048, and K049; combined. The reports shall be submitted by January 31 of each year and cover the previous calendar year.
8. The permittee shall submit annual reports which summarize the facility-wide emissions of each single HAP and combined HAPs from all emissions units at the facility. The reports shall include the emission calculations, be submitted by January 31 of each year, and cover the previous calendar year.
9. The permittee shall submit annual reports which summarize the results of the annual inspections conducted on the catalytic oxidizer by the manufacturer's representative. The reports shall describe any maintenance conducted on the catalytic oxidizer as a direct result of the inspections by manufacturer's representative. The reports shall be submitted by January 31 of each year and cover the previous calendar year.

Issued

Emissions Unit ID: K040

10. The permittee shall submit reports that include the results of the catalyst activity tests required in section A.V. These reports shall be submitted within 45 days after each catalyst activity test is performed.

V. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation:

VOC emissions shall not exceed 8.51 pounds per day.

Issued: To be entered upon final issuance

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 8 of these terms and conditions.

b. Emission Limitation:

VOC emissions shall not exceed 10.04 tons per year.

Applicable Compliance Method:

Compliance with the annual emission limitation is shown as long as compliance with the daily emission limitations for this emissions unit (K040) and emissions units K039, K041, K042, K043, K044, K045, K046, K047, K048, and K049, are maintained (the annual emission limitation was calculated by multiplying the sum of the daily emission limitations for this emissions unit (K040) and emissions units K039, K041, K042, K043, K044, K045, K046, K047, K048, and K049, by 365 and dividing by 2000).

c. Emission Limitation:

81 percent overall reduction of VOCs by weight and 90 percent destruction for all solvent based coatings.

Applicable Compliance Method:

If required by the Ohio EPA Northeast District Office, compliance shall be demonstrated in accordance with 40 CFR Part 60, Appendix A, Methods 25, 25A, and 40 CFR Part 51, Appendix M, Method 204. Performance testing shall be in accordance with OAC rule 3745-21-10(C).

d. Emission Limitation:

The emissions of each single hazardous air pollutant (HAP) from all emissions units at the facility shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 9 of these terms and conditions.

Forest

PTI A

Emissions Unit ID: K040

Issued: To be entered upon final issuance

e. Emission Limitation:

The emissions of the combined HAPs from all emissions units at the facility shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation.

Issued: To be entered upon final issuance

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 9 of these terms and conditions.

2. Emission testing demonstrating compliance with the overall control efficiency limitation for VOC of 81 percent, the destruction efficiency limitation for VOC of 90 percent, and capture efficiency was conducted on January 8, 2004, as required by PTI 02-17168 issued 04/03/03.
3. US EPA Method 24 shall be used to determine the VOC contents of all the coatings employed in this emissions unit.
4. The permittee shall conduct, or have conducted, catalyst activity testing using the catalyst sample collected during the annual inspection described in section A.III. An intent to test notification shall not be required for the testing noted in this term. The procedures for the catalyst activity test shall be in accordance with the manufacturer's recommendations.

VI. Miscellaneous Requirements

None

**Forest
PTI A**

Emissions Unit ID: K040

Issued: To be entered upon final issuance

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K040 - Grip Line 2: Coater and natural gas oven no. 2 equipped with a catalytic oxidizer Terms in this permit supercede those identified in PTI 02-17168 issued 04/03/03.	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit (K040) was evaluated based on the actual materials (coatings) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant potentially emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the

modeling for the "worst case" pollutant(s):

Pollutant: toluene

TLV (ug/m3): 188,400

Maximum Hourly Emission Rate (lbs/hr): 3.31

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 250.5

MAGLC (ug/m3): 4476

Physical changes to or changes in the method of operation of the emissions unit after its installation could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that

Forest

PTI A

Emissions Unit ID: K040

Issued: To be entered upon final issuance

show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Forest
PTI A

Emissions Unit ID: K041

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	OAC rule 3745-35-07
K041 - Grip Line 3: Coater and natural gas oven no. 3 equipped with a catalytic oxidizer	OAC rule 3745-31-05(A)(3)	
Terms in this permit supercede those identified in PTI 02-17168 issued 04/03/03.	OAC rule 3745-21-09(B)(6)	
	OAC rule 3745-21-09(U)	
	OAC rule 3745-21-09(B)(3)(l)	
	OAC rule 3745-21-09(B)(3)(m)	
	OAC rule 3745-21-09(B)(3)(n)	

Applicable Emissions
Limitations/Control
Measures

The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09(B)(6).

VOC emissions shall not exceed 9.56 pounds per day.

VOC emissions shall not exceed 10.04 tons per year. See A.I.2.a below.

81 percent overall reduction of VOCs by weight and 90 percent destruction for all solvent based coatings.

In lieu of complying with the requirements of this rule, the permittee has opted to comply with the requirements of OAC rule 3745-21-09(B).

See A.III.2.a, A.III.2.b, and A.III.2.c below.

See A.IV.2.a, A.IV.2.b, and A.IV.2.c below.

See A.III.1, A.V.1.c, and A.V.2 below.

See A.I.2.b and A.I.2.c below.

Issued: To be entered upon final issuance**2. Additional Terms and Conditions**

- 2.a** The emission limitation of 10.04 tons VOC per year is based on the combined annual emissions from this emissions unit (K041) and emissions units K039, K040, K042, K043, K044, K045, K046, K047, K048, and K049.
- 2.b** The emissions of each single hazardous air pollutant (HAP) from all emissions units at the facility shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation. The permittee shall use existing records to determine compliance with the rolling 12-month restrictions upon issuance of this permit. Therefore, it is not necessary to establish federally enforceable restrictions for the first 12 months of operation under the provisions of this permit.
- 2.c** The emissions of the combined HAPs from all emissions units at the facility shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation. The permittee shall use existing records to determine compliance with the rolling 12-month restrictions upon issuance of this permit. Therefore, it is not necessary to establish federally enforceable restrictions for the first 12 months of operation under the provisions of this permit.

II. Operational Restrictions

1. Exhaust gases from operation of the emissions unit shall be vented to the catalytic oxidizer.
2. The average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below 652 degrees Fahrenheit, the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance. In the event that future emission tests are conducted, the average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
3. The catalytic oxidizer shall be operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manuals. The VOC conversion efficiency of the catalyst in the catalytic oxidizer, as determined by the catalyst activity testing, shall be at least 90% at a test temperature that is representative of the normal temperature at the catalyst bed inlet. Solvent loading during catalyst analysis shall be consistent with the test laboratory's normal testing protocol.
4. All ventilation fans associated with this emissions unit and the catalytic oxidizer shall be in

operation at all times when this emissions unit is in operation.

5. When employing the catalytic oxidizer, all bypass dampers, actuator pins, and associated motors shall be in the correct position and in good operating condition at all times when this emissions unit is in operation to ensure that all captured VOC emissions are vented to the catalytic oxidizer. Also, all the hooding and ductwork comprising the VOC emission capture system for this emissions unit shall be free of leaks and holes that would permit the escape of the captured VOC emissions.
6. The average, total exhaust flow rate from this emissions unit to the catalytic oxidizer shall be within 25% of 1700 feet per minute (fpm), the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation. In the event that future emission tests are conducted, the average, total exhaust flow rate from this emissions unit to the catalytic oxidizer shall be within 25% of the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain continuous monitors and recorder(s) which measure and record the temperature immediately upstream and downstream of the incinerator's catalyst bed when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitors and recorder(s) shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.
2. The permittee shall collect and record the following information each day:
 - a. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
 - b. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance. The permittee may use the oxidizer's temperature chart to determine the temperature differential across the catalyst bed.
 - c. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation. The permittee may use the current temperature chart as the log documenting that the monitoring equipment and control device are operating. Each bypass of the collection system and/or control device shall be logged as to the date and time.

Issued: To be entered upon final issuance

3. The permittee shall perform an inspection of the catalytic oxidizer, including the catalyst bed, at least once each calendar year. Each inspection shall consist of internal and visual inspections in accordance with the manufacturer's recommendations and shall include a physical inspection of the unit and checks of associated equipment, including but not limited to burners, controls, dampers, valves, and monitoring and recording equipment. Repair and replacement of equipment shall be performed as determined by the inspection. In accordance with the testing schedule in section A.V, a sample of catalyst material shall be collected from the catalyst bed to perform the catalyst activity tests required in section A.V.
4. The permittee shall maintain a record of the results of each annual inspection of the catalytic oxidizer, as well as the results of each catalyst activity test required in section A.V.
5. The permittee shall operate and maintain a flow meter at the inlet to the catalytic oxidizer to ensure that the exhaust from the coating room and the emissions units in the coating room are being directed to the catalytic oxidizer. The permittee shall collect and record the flow rate at the inlet to the catalytic oxidizer on a daily basis.
6. Each calendar month, the permittee shall inspect the operational condition and integrity of each ventilation fan comprising the capture system. Ventilation fan observations shall include visual inspections of the fan wheel, belts, and bearings. Lubrication of bearings and replacement of parts shall occur as necessary. The permittee shall document the results of all monthly inspections, including any corrective actions taken.
7. Each calendar month, the permittee shall inspect the operational condition and integrity of all hooding, ductwork, and bypass dampers comprising the capture system. Hooding and ductwork observations shall include visual inspections to verify that the damper setting is in the correct position (i.e., to oxidizer or to atmosphere) and visual inspections of the actuator and motor to verify that the actuator pin and the motor are operating properly. The permittee shall document the results of all monthly inspections, including any corrective actions taken.
8. The permittee shall collect and record the following information each day for this coating line (K041):
 - a. The name and identification number of each coating, as applied;
 - b. The volume in gallons of each coating, as applied;
 - c. The VOC content of each coating, as applied, in pounds per gallon; and
 - d. The total VOC emissions from all coatings employed [summation of (b x c) for all coatings multiplied by the overall control efficiency for the control equipment as

Emissions Unit ID: K041

determined during the most recent emission test that demonstrated that the source was in compliance].

9. The permittee shall collect and record the following information each month for all coating lines at the facility:
 - a. The name and identification number of each coating, as applied;
 - b. The volume in gallons of each coating, as applied;
 - c. The HAP content of each coating, as applied, in pounds per gallon;

Issued: To be entered upon final issuance

- d. The total HAP emissions for all emissions units of each single HAP [summation of (b x c) for all coatings multiplied by the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the source was in compliance]; and
- e. The total combined HAP emissions for all emissions units [summation of (d) for all HAPs emitted by the coating lines plus the monthly HAP emissions from the vapor degreaser (L001)].

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and was not vented to the catalytic oxidizer.
2. The permittee shall submit quarterly summaries of the following records:
 - a. a log of operating time for the capture (collection) system, control device, monitoring equipment, and the associated emissions unit;
 - b. all 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed (as determined by the continuous temperature monitor) did not comply with the temperature limitation specified above; and
 - c. all 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed (as determined by the continuous temperature monitor) was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance.

NOTE: Information submitted pursuant to section A.IV.2.c is not relevant for determining compliance with any operational restriction contained in section A.II. As long as the permittee performs the monitoring, record keeping, and reporting specified in sections A.III.2.b and A.IV.2.c of these terms and conditions, an average temperature difference across the catalyst bed of less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance shall not constitute a violation of any operational restriction or be considered a deviation.

3. The permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and the daily average air flow rate in the inlet stack to the catalytic

Emissions Unit ID: K041

oxidizer was more than 25% less than 1700 feet per minute (fpm), the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation. In the event that future emission tests are conducted, the permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and the daily average air flow rate in the inlet stack to the catalytic oxidizer was more than 25% less than the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation.

4. The permittee shall submit deviation (excursion) reports which identify each day where the daily VOC emission rate exceeded 9.56 pounds per day for this emissions unit (K041). The notification shall include a copy of such record and shall be sent to the Ohio EPA Northeast District Office within 30 days after the exceedance occurs.
5. The permittee shall submit deviation (excursion) reports which identify each month during which the rolling, 12-month emissions of any single HAP from all emissions units at the facility exceeded 9.9 tons per year, and the actual rolling, 12-month emissions of each such single HAP for each such month.
6. The permittee shall submit deviation (excursion) reports which identify each month during which the rolling, 12-month emissions of combined HAPs from all emissions units at the facility exceeded 24.9 tons per year, and the actual rolling, 12-month emissions of combined HAPs for each such month.
7. The permittee shall submit annual reports which specify the actual annual VOC emissions for the emissions unit (K041) and emissions units K039, K040, K042, K043, K044, K045, K046, K047, K048, and K049; combined. The reports shall be submitted by January 31 of each year and cover the previous calendar year.
8. The permittee shall submit annual reports which summarize the facility-wide emissions of each single HAP and combined HAPs from all emissions units at the facility. The reports shall include the emission calculations, be submitted by January 31 of each year, and cover the previous calendar year.
9. The permittee shall submit annual reports which summarize the results of the annual inspections conducted on the catalytic oxidizer by the manufacturer's representative. The reports shall describe any maintenance conducted on the catalytic oxidizer as a direct result of the inspections by manufacturer's representative. The reports shall be submitted by January 31 of each year and cover the previous calendar year.
10. The permittee shall submit reports that include the results of the catalyst activity tests required in section A.V. These reports shall be submitted within 45 days after each catalyst activity test is performed.

V. Testing Requirements

Issued: To be entered upon final issuance

1. Compliance with the emission limitations in Section A.I.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation:

VOC emissions shall not exceed 9.56 pounds per day.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 8 of these terms and conditions.
 - b. Emission Limitation:

VOC emissions shall not exceed 10.04 tons per year.

Applicable Compliance Method:

Compliance with the annual emission limitation is shown as long as compliance with the daily emission limitations for this emissions unit (K041) and emissions units K039, K040, K042, K043, K044, K045, K046, K047, K048, and K049, are maintained (the annual emission limitation was calculated by multiplying the sum of the daily emission limitations for this emissions unit (K041) and emissions units K039, K040, K042, K043, K044, K045, K046, K047, K048, and K049, by 365 and dividing by 2000).
 - c. Emission Limitation:

81 percent overall reduction of VOCs by weight and 90 percent destruction for all solvent based coatings.

Applicable Compliance Method:

If required by the Ohio EPA Northeast District Office, compliance shall be demonstrated in accordance with 40 CFR Part 60, Appendix A, Methods 25, 25A, and 40 CFR Part 51, Appendix M, Method 204. Performance testing shall be in accordance with OAC rule 3745-21-10(C).
 - d. Emission Limitation:

The emissions of each single hazardous air pollutant (HAP) from all emissions units at the facility shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 9 of these terms and conditions.

e. Emission Limitation:

The emissions of the combined HAPs from all emissions units at the facility shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation.

Issued: To be entered upon final issuance

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 9 of these terms and conditions.

2. Emission testing demonstrating compliance with the overall control efficiency limitation for VOC of 81 percent, the destruction efficiency limitation for VOC of 90 percent, and capture efficiency was conducted on January 8, 2004, as required by PTI 02-17168 issued 04/03/03.
3. US EPA Method 24 shall be used to determine the VOC contents of all the coatings employed in this emissions unit.
4. The permittee shall conduct, or have conducted, catalyst activity testing using the catalyst sample collected during the annual inspection described in section A.III. An intent to test notification shall not be required for the testing noted in this term. The procedures for the catalyst activity test shall be in accordance with the manufacturer's recommendations.

VI. Miscellaneous Requirements

None

Forest

PTI A

Emissions Unit ID: K041

Issued: To be entered upon final issuance**B. State Only Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K041 - Grip Line 3: Coater and natural gas oven no. 3 equipped with a catalytic oxidizer	None	None
Terms in this permit supercede those identified in PTI 02-17168 issued 04/03/03.		

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit (K041) was evaluated based on the actual materials (coatings) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant potentially emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the

55

Forest

PTI A

Emissions Unit ID: K041

Issued: To be entered upon final issuance

modeling for the "worst case" pollutant(s):

Pollutant: toluene

TLV (ug/m3): 188,400

Maximum Hourly Emission Rate (lbs/hr): 3.31

Issued: To be entered upon final issuance

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 250.5
MAGLC (ug/m3): 4476

Physical changes to or changes in the method of operation of the emissions unit after its installation could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

Emissions Unit ID: K041

- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Forest
PTI A

Emissions Unit ID: K042

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	OAC rule 3745-35-07
K042 - Grip Line 4: Coater and electric oven equipped with a catalytic oxidizer	OAC rule 3745-31-05(A)(3)	
Terms in this permit supercede those identified in PTI 02-17168 issued 04/03/03.		
	OAC rule 3745-21-09(B)(6)	
	OAC rule 3745-21-09(U)	
	OAC rule 3745-21-09(B)(3)(l)	
	OAC rule 3745-21-09(B)(3)(m)	
	OAC rule 3745-21-09(B)(3)(n)	

Forest**PTI A**

Emissions Unit ID: K042

Issued: To be entered upon final issuance

Applicable Emissions
Limitations/Control
Measures

The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09(B)(6).

VOC emissions shall not exceed 8.51 pounds per day.

VOC emissions shall not exceed 10.04 tons per year.
See A.I.2.a below.

81 percent overall reduction of VOCs by weight and 90 percent destruction for all solvent based coatings.

In lieu of complying with the requirements of this rule, the permittee has opted to comply with the requirements of OAC rule 3745-21-09(B).

See A.III.2.a, A.III.2.b, and A.III.2.c below.

See A.IV.2.a, A.IV.2.b, and A.IV.2.c below.

See A.III.1, A.V.1.c, and A.V.2 below.

See A.I.2.b and A.I.2.c below.

Issued: To be entered upon final issuance**2. Additional Terms and Conditions**

- 2.a** The emission limitation of 10.04 tons VOC per year is based on the combined annual emissions from this emissions unit (K042) and emissions units K039, K040, K041, K043, K044, K045, K046, K047, K048, and K049.
- 2.b** The emissions of each single hazardous air pollutant (HAP) from all emissions units at the facility shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation. The permittee shall use existing records to determine compliance with the rolling 12-month restrictions upon issuance of this permit. Therefore, it is not necessary to establish federally enforceable restrictions for the first 12 months of operation under the provisions of this permit.
- 2.c** The emissions of the combined HAPs from all emissions units at the facility shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation. The permittee shall use existing records to determine compliance with the rolling 12-month restrictions upon issuance of this permit. Therefore, it is not necessary to establish federally enforceable restrictions for the first 12 months of operation under the provisions of this permit.

II. Operational Restrictions

1. Exhaust gases from operation of the emissions unit shall be vented to the catalytic oxidizer.
2. The average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below 652 degrees Fahrenheit, the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance. In the event that future emission tests are conducted, the average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
3. The catalytic oxidizer shall be operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manuals. The VOC conversion efficiency of the catalyst in the catalytic oxidizer, as determined by the catalyst activity testing, shall be at least 90% at a test temperature that is representative of the normal temperature at the catalyst bed inlet. Solvent loading during catalyst analysis shall be consistent with the test laboratory's normal testing protocol.
4. All ventilation fans associated with this emissions unit and the catalytic oxidizer shall be in

operation at all times when this emissions unit is in operation.

5. When employing the catalytic oxidizer, all bypass dampers, actuator pins, and associated motors shall be in the correct position and in good operating condition at all times when this emissions unit is in operation to ensure that all captured VOC emissions are vented to the catalytic oxidizer. Also, all the hooding and ductwork comprising the VOC emission capture system for this emissions unit shall be free of leaks and holes that would permit the escape of the captured VOC emissions.
6. The average, total exhaust flow rate from this emissions unit to the catalytic oxidizer shall be within 25% of 1700 feet per minute (fpm), the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation. In the event that future emission tests are conducted, the average, total exhaust flow rate from this emissions unit to the catalytic oxidizer shall be within 25% of the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain continuous monitors and recorder(s) which measure and record the temperature immediately upstream and downstream of the incinerator's catalyst bed when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitors and recorder(s) shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.
2. The permittee shall collect and record the following information each day:
 - a. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
 - b. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance. The permittee may use the oxidizer's temperature chart to determine the temperature differential across the catalyst bed.
 - c. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation. The permittee may use the current temperature chart as the log documenting that the monitoring equipment and control device are operating. Each bypass of the collection system and/or control device shall be logged as to the date and time.

Issued

Emissions Unit ID: K042

3. The permittee shall perform an inspection of the catalytic oxidizer, including the catalyst bed, at least once each calendar year. Each inspection shall consist of internal and visual inspections in accordance with the manufacturer's recommendations and shall include a physical inspection of the unit and checks of associated equipment, including but not limited to burners, controls, dampers, valves, and monitoring and recording equipment. Repair and replacement of equipment shall be performed as determined by the inspection. In accordance with the testing schedule in section A.V, a sample of catalyst material shall be collected from the catalyst bed to perform the catalyst activity tests required in section A.V.
4. The permittee shall maintain a record of the results of each annual inspection of the catalytic oxidizer, as well as the results of each catalyst activity test required in section A.V.
5. The permittee shall operate and maintain a flow meter at the inlet to the catalytic oxidizer to ensure that the exhaust from the coating room and the emissions units in the coating room are being directed to the catalytic oxidizer. The permittee shall collect and record the flow rate at the inlet to the catalytic oxidizer on a daily basis.
6. Each calendar month, the permittee shall inspect the operational condition and integrity of each ventilation fan comprising the capture system. Ventilation fan observations shall include visual inspections of the fan wheel, belts, and bearings. Lubrication of bearings and replacement of parts shall occur as necessary. The permittee shall document the results of all monthly inspections, including any corrective actions taken.
7. Each calendar month, the permittee shall inspect the operational condition and integrity of all hooding, ductwork, and bypass dampers comprising the capture system. Hooding and ductwork observations shall include visual inspections to verify that the damper setting is in the correct position (i.e., to oxidizer or to atmosphere) and visual inspections of the actuator and motor to verify that the actuator pin and the motor are operating properly. The permittee shall document the results of all monthly inspections, including any corrective actions taken.
8. The permittee shall collect and record the following information each day for this coating line (K042):
 - a. The name and identification number of each coating, as applied;
 - b. The volume in gallons of each coating, as applied;
 - c. The VOC content of each coating, as applied, in pounds per gallon; and
 - d. The total VOC emissions from all coatings employed [summation of (b x c) for all coatings multiplied by the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the source was in compliance].
9. The permittee shall collect and record the following information each month for all coating lines at the facility:

Issued: To be entered upon final issuance

- a. The name and identification number of each coating, as applied;
- b. The volume in gallons of each coating, as applied;
- c. The HAP content of each coating, as applied, in pounds per gallon;
- d. The total HAP emissions for all emissions units of each single HAP [summation of (b x c) for all coatings multiplied by the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the source was in compliance]; and
- e. The total combined HAP emissions for all emissions units [summation of (d) for all HAPs emitted by the coating lines plus the monthly HAP emissions from the vapor degreaser (L001)].

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and was not vented to the catalytic oxidizer.
2. The permittee shall submit quarterly summaries of the following records:
 - a. a log of operating time for the capture (collection) system, control device, monitoring equipment, and the associated emissions unit;
 - b. all 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed (as determined by the continuous temperature monitor) did not comply with the temperature limitation specified above; and
 - c. all 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed (as determined by the continuous temperature monitor) was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance.

NOTE: Information submitted pursuant to section A.IV.2.c is not relevant for determining compliance with any operational restriction contained in section A.II. As long as the permittee performs the monitoring, record keeping, and reporting specified in sections A.III.2.b and A.IV.2.c of these terms and conditions, an average temperature difference across the catalyst bed

Emissions Unit ID: K042

of less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance shall not constitute a violation of any operational restriction or be considered a deviation.

3. The permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and the daily average air flow rate in the inlet stack to the catalytic oxidizer was more than 25% less than 1700 feet per minute (fpm), the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation. In the event that future emission tests are conducted, the permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and the daily average air flow rate in the inlet stack to the catalytic oxidizer was more than 25% less than the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation.
4. The permittee shall submit deviation (excursion) reports which identify each day where the daily VOC emission rate exceeded 8.51 pounds per day for this emissions unit (K042). The notification shall include a copy of such record and shall be sent to the Ohio EPA Northeast District Office within 30 days after the exceedance occurs.
5. The permittee shall submit deviation (excursion) reports which identify each month during which the rolling, 12-month emissions of any single HAP from all emissions units at the facility exceeded 9.9 tons per year, and the actual rolling, 12-month emissions of each such single HAP for each such month.
6. The permittee shall submit deviation (excursion) reports which identify each month during which the rolling, 12-month emissions of combined HAPs from all emissions units at the facility exceeded 24.9 tons per year, and the actual rolling, 12-month emissions of combined HAPs for each such month.
7. The permittee shall submit annual reports which specify the actual annual VOC emissions for the emissions unit (K042) and emissions units K039, K040, K041, K043, K044, K045, K046, K047, K048, and K049; combined. The reports shall be submitted by January 31 of each year and cover the previous calendar year.
8. The permittee shall submit annual reports which summarize the facility-wide emissions of each single HAP and combined HAPs from all emissions units at the facility. The reports shall include the emission calculations, be submitted by January 31 of each year, and cover the previous calendar year.
9. The permittee shall submit annual reports which summarize the results of the annual inspections conducted on the catalytic oxidizer by the manufacturer's representative. The reports shall describe any maintenance conducted on the catalytic oxidizer as a direct result of the inspections by manufacturer's representative. The reports shall be submitted by January 31 of each year and cover the previous calendar year.

Issued

Emissions Unit ID: K042

10. The permittee shall submit reports that include the results of the catalyst activity tests required in section A.V. These reports shall be submitted within 45 days after each catalyst activity test is performed.

V. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1 of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation:

VOC emissions shall not exceed 8.51 pounds per day.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 8 of these terms and conditions.

- b. Emission Limitation:

VOC emissions shall not exceed 10.04 tons per year.

Applicable Compliance Method:

Compliance with the annual emission limitation is shown as long as compliance with the daily emission limitations for this emissions unit (K042) and emissions units K039, K040, K041, K043, K044, K045, K046, K047, K048, and K049, are maintained (the annual emission limitation was calculated by multiplying the sum of the daily emission limitations for this emissions unit (K042) and emissions units K039, K040, K041, K043, K044, K045, K046, K047, K048, and K049, by 365 and dividing by 2000).

- c. Emission Limitation:

81 percent overall reduction of VOCs by weight and 90 percent destruction for all solvent based coatings.

Applicable Compliance Method:

If required by the Ohio EPA Northeast District Office, compliance shall be demonstrated in accordance with 40 CFR Part 60, Appendix A, Methods 25, 25A, and 40 CFR Part 51, Appendix M, Method 204. Performance testing shall be in accordance with OAC rule 3745-21-10(C).

- d. Emission Limitation:

The emissions of each single hazardous air pollutant (HAP) from all emissions units at the

Issued: To be entered upon final issuance

facility shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 9 of these terms and conditions.

e. Emission Limitation:

The emissions of the combined HAPs from all emissions units at the facility shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 9 of these terms and conditions.

2. Emission testing demonstrating compliance with the overall control efficiency limitation for VOC of 81 percent, the destruction efficiency limitation for VOC of 90 percent, and capture efficiency was conducted on January 8, 2004, as required by PTI 02-17168 issued 04/03/03.
3. US EPA Method 24 shall be used to determine the VOC contents of all the coatings employed in this emissions unit.
4. The permittee shall conduct, or have conducted, catalyst activity testing using the catalyst sample collected during the annual inspection described in section A.III. An intent to test notification shall not be required for the testing noted in this term. The procedures for the catalyst activity test shall be in accordance with the manufacturer's recommendations.

VI. Miscellaneous Requirements

None

Forest
PTI A

Emissions Unit ID: K042

Issued: To be entered upon final issuance

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K042 - Grip Line 4: Coater and electric oven equipped with a catalytic oxidizer Terms in this permit supercede those identified in PTI 02-17168 issued 04/03/03.	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit (K042) was evaluated based on the actual materials (coatings) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant potentially emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: toluene

TLV (ug/m3): 188,400

Maximum Hourly Emission Rate (lbs/hr): 3.31

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 250.5

MAGLC (ug/m3): 4476

Physical changes to or changes in the method of operation of the emissions unit after its installation could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

69

Forest

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: K042

IV. Reporting Requirements

None

70

Forest

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: K042

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	OAC rule 3745-35-07
K043 - Patch coater 1 and electric oven equipped with a catalytic oxidizer	OAC rule 3745-31-05(A)(3)	
Terms in this permit supercede those identified in PTI 02-17168 issued 04/03/03.	OAC rule 3745-21-09(B)(6)	
	OAC rule 3745-21-09(U)	
	OAC rule 3745-21-09(B)(3)(l)	
	OAC rule 3745-21-09(B)(3)(m)	
	OAC rule 3745-21-09(B)(3)(n)	

Issued

Applicable Emissions
Limitations/Control
Measures

The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09(B)(6).

VOC emissions shall not exceed 8.51 pounds per day.

VOC emissions shall not exceed 10.04 tons per year. See A.I.2.a below.

81 percent overall reduction of VOCs by weight and 90 percent destruction for all solvent based coatings.

In lieu of complying with the requirements of this rule, the permittee has opted to comply with the requirements of OAC rule 3745-21-09(B).

See A.III.2.a, A.III.2.b, and A.III.2.c below.

See A.IV.2.a, A.IV.2.b, and A.IV.2.c below.

See A.III.1, A.V.1.c, and A.V.2 below.

See A.I.2.b and A.I.2.c below.

Issued: To be entered upon final issuance**2. Additional Terms and Conditions**

- 2.a** The emission limitation of 10.04 tons VOC per year is based on the combined annual emissions from this emissions unit (K043) and emissions units K039, K040, K041, K042, K044, K045, K046, K047, K048, and K049.
- 2.b** The emissions of each single hazardous air pollutant (HAP) from all emissions units at the facility shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation. The permittee shall use existing records to determine compliance with the rolling 12-month restrictions upon issuance of this permit. Therefore, it is not necessary to establish federally enforceable restrictions for the first 12 months of operation under the provisions of this permit.
- 2.c** The emissions of the combined HAPs from all emissions units at the facility shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation. The permittee shall use existing records to determine compliance with the rolling 12-month restrictions upon issuance of this permit. Therefore, it is not necessary to establish federally enforceable restrictions for the first 12 months of operation under the provisions of this permit.

II. Operational Restrictions

1. Exhaust gases from operation of the emissions unit shall be vented to the catalytic oxidizer.
2. The average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below 652 degrees Fahrenheit, the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance. In the event that future emission tests are conducted, the average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
3. The catalytic oxidizer shall be operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manuals. The VOC conversion efficiency of the catalyst in the catalytic oxidizer, as determined by the catalyst activity testing, shall be at least 90% at a test temperature that is representative of the normal temperature at the catalyst bed inlet. Solvent loading during catalyst analysis shall be consistent with the test laboratory's normal testing protocol.
4. All ventilation fans associated with this emissions unit and the catalytic oxidizer shall be in

operation at all times when this emissions unit is in operation.

5. When employing the catalytic oxidizer, all bypass dampers, actuator pins, and associated motors shall be in the correct position and in good operating condition at all times when this emissions unit is in operation to ensure that all captured VOC emissions are vented to the catalytic oxidizer. Also, all the hooding and ductwork comprising the VOC emission capture system for this emissions unit shall be free of leaks and holes that would permit the escape of the captured VOC emissions.
6. The average, total exhaust flow rate from this emissions unit to the catalytic oxidizer shall be within 25% of 1700 feet per minute (fpm), the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation. In the event that future emission tests are conducted, the average, total exhaust flow rate from this emissions unit to the catalytic oxidizer shall be within 25% of the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain continuous monitors and recorder(s) which measure and record the temperature immediately upstream and downstream of the incinerator's catalyst bed when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitors and recorder(s) shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.
2. The permittee shall collect and record the following information each day:
 - a. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
 - b. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance. The permittee may use the oxidizer's temperature chart to determine the temperature differential across the catalyst bed.
 - c. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation. The permittee may use the current temperature chart as the log documenting that the monitoring equipment and control device are operating. Each bypass of the collection system and/or control device shall be logged as to the date and time.

Issued: To be entered upon final issuance

3. The permittee shall perform an inspection of the catalytic oxidizer, including the catalyst bed, at least once each calendar year. Each inspection shall consist of internal and visual inspections in accordance with the manufacturer's recommendations and shall include a physical inspection of the unit and checks of associated equipment, including but not limited to burners, controls, dampers, valves, and monitoring and recording equipment. Repair and replacement of equipment shall be performed as determined by the inspection. In accordance with the testing schedule in section A.V, a sample of catalyst material shall be collected from the catalyst bed to perform the catalyst activity tests required in section A.V.
4. The permittee shall maintain a record of the results of each annual inspection of the catalytic oxidizer, as well as the results of each catalyst activity test required in section A.V.
5. The permittee shall operate and maintain a flow meter at the inlet to the catalytic oxidizer to ensure that the exhaust from the coating room and the emissions units in the coating room are being directed to the catalytic oxidizer. The permittee shall collect and record the flow rate at the inlet to the catalytic oxidizer on a daily basis.
6. Each calendar month, the permittee shall inspect the operational condition and integrity of each ventilation fan comprising the capture system. Ventilation fan observations shall include visual inspections of the fan wheel, belts, and bearings. Lubrication of bearings and replacement of parts shall occur as necessary. The permittee shall document the results of all monthly inspections, including any corrective actions taken.
7. Each calendar month, the permittee shall inspect the operational condition and integrity of all hooding, ductwork, and bypass dampers comprising the capture system. Hooding and ductwork observations shall include visual inspections to verify that the damper setting is in the correct position (i.e., to oxidizer or to atmosphere) and visual inspections of the actuator and motor to verify that the actuator pin and the motor are operating properly. The permittee shall document the results of all monthly inspections, including any corrective actions taken.
8. The permittee shall collect and record the following information each day for this coating line (K043):
 - a. The name and identification number of each coating, as applied;
 - b. The volume in gallons of each coating, as applied;
 - c. The VOC content of each coating, as applied, in pounds per gallon; and
 - d. The total VOC emissions from all coatings employed [summation of (b x c) for all coatings multiplied by the overall control efficiency for the control equipment as

Emissions Unit ID: K043

determined during the most recent emission test that demonstrated that the source was in compliance].

9. The permittee shall collect and record the following information each month for all coating lines at the facility:
 - a. The name and identification number of each coating, as applied;
 - b. The volume in gallons of each coating, as applied;
 - c. The HAP content of each coating, as applied, in pounds per gallon;
 - d. The total HAP emissions for all emissions units of each single HAP [summation of (b x c) for all coatings multiplied by the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the source was in compliance]; and
 - e. The total combined HAP emissions for all emissions units [summation of (d) for all HAPs emitted by the coating lines plus the monthly HAP emissions from the vapor degreaser (L001)].

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and was not vented to the catalytic oxidizer.
2. The permittee shall submit quarterly summaries of the following records:
 - a. a log of operating time for the capture (collection) system, control device, monitoring equipment, and the associated emissions unit;
 - b. all 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed (as determined by the continuous temperature monitor) did not comply with the temperature limitation specified above; and
 - c. all 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed (as determined by the continuous temperature monitor) was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance.

NOTE: Information submitted pursuant to section A.IV.2.c is not relevant for determining compliance with any operational restriction contained in section A.II. As long as the permittee performs the monitoring, record keeping, and reporting specified in sections A.III.2.b and A.IV.2.c of these terms and conditions, an average temperature difference across the catalyst bed

Issued: To be entered upon final issuance

of less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance shall not constitute a violation of any operational restriction or be considered a deviation.

3. The permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and the daily average air flow rate in the inlet stack to the catalytic oxidizer was more than 25% less than 1700 feet per minute (fpm), the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation. In the event that future emission tests are conducted, the permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and the daily average air flow rate in the inlet stack to the catalytic oxidizer was more than 25% less than the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation.
4. The permittee shall submit deviation (excursion) reports which identify each day where the daily VOC emission rate exceeded 8.51 pounds per day for this emissions unit (K043). The notification shall include a copy of such record and shall be sent to the Ohio EPA Northeast District Office within 30 days after the exceedance occurs.
5. The permittee shall submit deviation (excursion) reports which identify each month during which the rolling, 12-month emissions of any single HAP from all emissions units at the facility exceeded 9.9 tons per year, and the actual rolling, 12-month emissions of each such single HAP for each such month.
6. The permittee shall submit deviation (excursion) reports which identify each month during which the rolling, 12-month emissions of combined HAPs from all emissions units at the facility exceeded 24.9 tons per year, and the actual rolling, 12-month emissions of combined HAPs for each such month.
7. The permittee shall submit annual reports which specify the actual annual VOC emissions for the emissions unit (K043) and emissions units K039, K040, K041, K042, K044, K045, K046, K047, K048, and K049; combined. The reports shall be submitted by January 31 of each year and cover the previous calendar year.
8. The permittee shall submit annual reports which summarize the facility-wide emissions of each single HAP and combined HAPs from all emissions units at the facility. The reports shall include the emission calculations, be submitted by January 31 of each year, and cover the previous calendar year.
9. The permittee shall submit annual reports which summarize the results of the annual inspections

Emissions Unit ID: K043

conducted on the catalytic oxidizer by the manufacturer's representative. The reports shall describe any maintenance conducted on the catalytic oxidizer as a direct result of the inspections by manufacturer's representative. The reports shall be submitted by January 31 of each year and cover the previous calendar year.

10. The permittee shall submit reports that include the results of the catalyst activity tests required in section A.V. These reports shall be submitted within 45 days after each catalyst activity test is performed.

V. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1 of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation:

VOC emissions shall not exceed 8.51 pounds per day.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 8 of these terms and conditions.

- b. Emission Limitation:

VOC emissions shall not exceed 10.04 tons per year.

Applicable Compliance Method:

Compliance with the annual emission limitation is shown as long as compliance with the daily emission limitations for this emissions unit (K043) and emissions units K039, K040, K041, K042, K044, K045, K046, K047, K048, and K049, are maintained (the annual emission limitation was calculated by multiplying the sum of the daily emission limitations for this emissions unit (K043) and emissions units K039, K040, K041, K042, K044, K045, K046, K047, K048, and K049, by 365 and dividing by 2000).

- c. Emission Limitation:

81 percent overall reduction of VOCs by weight and 90 percent destruction for all solvent based coatings.

Applicable Compliance Method:

If required by the Ohio EPA Northeast District Office, compliance shall be demonstrated in accordance with 40 CFR Part 60, Appendix A, Methods 25, 25A, and 40 CFR Part 51, Appendix M, Method 204. Performance testing shall be in accordance with OAC rule

3745-21-10(C).

d. Emission Limitation:

The emissions of each single hazardous air pollutant (HAP) from all emissions units at the facility shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 9 of these terms and conditions.

e. Emission Limitation:

The emissions of the combined HAPs from all emissions units at the facility shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 9 of these terms and conditions.

2. Emission testing demonstrating compliance with the overall control efficiency limitation for VOC of 81 percent, the destruction efficiency limitation for VOC of 90 percent, and capture efficiency was conducted on January 8, 2004, as required by PTI 02-17168 issued 04/03/03.
3. US EPA Method 24 shall be used to determine the VOC contents of all the coatings employed in this emissions unit.
4. The permittee shall conduct, or have conducted, catalyst activity testing using the catalyst sample collected during the annual inspection described in section A.III. An intent to test notification shall not be required for the testing noted in this term. The procedures for the catalyst activity test shall be in accordance with the manufacturer's recommendations.

VI. Miscellaneous Requirements

None

**Forest
PTI A**

Emissions Unit ID: K043

Issued: To be entered upon final issuance

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K043 - Patch coater 1 and electric oven equipped with a catalytic oxidizer Terms in this permit supercede those identified in PTI 02-17168 issued 04/03/03.	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit (K043) was evaluated based on the actual materials (coatings) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant potentially emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Issued: To be entered upon final issuance

Pollutant: toluene

TLV (ug/m3): 188,400

Maximum Hourly Emission Rate (lbs/hr): 3.31

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 250.5

MAGLC (ug/m3): 4476

Physical changes to or changes in the method of operation of the emissions unit after its installation could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

Issued

Emissions Unit ID: K043

- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

83

Forest

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: K043

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Forest
PTI A

Emissions Unit ID: K044

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
K044 - Rail coater and electric oven equipped with a catalytic oxidizer	OAC rule 3745-31-05(A)(3)	OAC rule 3745-21-09(B)(3)(n)
Terms in this permit supercede those identified in PTI 02-17168 issued 04/03/03.		OAC rule 3745-35-07
	OAC rule 3745-21-09(B)(6)	
	OAC rule 3745-21-09(U)	
	OAC rule 3745-21-09(B)(3)(l)	
	OAC rule 3745-21-09(B)(3)(m)	

Forest

PTI A

Issued: To be entered upon final issuance

Applicable Emissions
Limitations/Control
Measures

See A.I.2.b and A.I.2.c below.

The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09(B)(6).

VOC emissions shall not exceed **2.2** pounds per day.

VOC emissions shall not exceed 10.04 tons per year. See A.I.2.a below.

90 percent overall reduction of VOCs by weight.

The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

In lieu of complying with the requirements of this rule, the permittee has opted to comply with the requirements of OAC rule 3745-21-09(B).

See A.III.2.a, A.III.2.b, and A.III.2.c below.

See A.IV.2.a, A.IV.2.b, and A.IV.2.c below.

See A.III.1, A.V.1.c, and A.V.2 below.

Issued: To be entered upon final issuance**2. Additional Terms and Conditions**

- 2.a** The emission limitation of 10.04 tons VOC per year is based on the combined annual emissions from this emissions unit (K044) and emissions units K039, K040, K041, K042, K043, K045, K046, K047, K048, and K049.
- 2.b** The emissions of each single hazardous air pollutant (HAP) from all emissions units at the facility shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation. The permittee shall use existing records to determine compliance with the rolling 12-month restrictions upon issuance of this permit. Therefore, it is not necessary to establish federally enforceable restrictions for the first 12 months of operation under the provisions of this permit.
- 2.c** The emissions of the combined HAPs from all emissions units at the facility shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation. The permittee shall use existing records to determine compliance with the rolling 12-month restrictions upon issuance of this permit. Therefore, it is not necessary to establish federally enforceable restrictions for the first 12 months of operation under the provisions of this permit.

II. Operational Restrictions

1. Exhaust gases from operation of the emissions unit shall be vented to the catalytic oxidizer.
2. The average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below 652 degrees Fahrenheit, the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance. In the event that future emission tests are conducted, the average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
3. The catalytic oxidizer shall be operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manuals. The VOC conversion efficiency of the catalyst in the catalytic oxidizer, as determined by the catalyst activity testing, shall be at least 90% at a test temperature that is representative of the normal temperature at the catalyst bed inlet. Solvent loading during catalyst analysis shall be consistent with the test laboratory's normal testing protocol.
4. All ventilation fans associated with this emissions unit and the catalytic oxidizer shall be in

operation at all times when this emissions unit is in operation.

5. When employing the catalytic oxidizer, all bypass dampers, actuator pins, and associated motors shall be in the correct position and in good operating condition at all times when this emissions unit is in operation to ensure that all captured VOC emissions are vented to the catalytic oxidizer. Also, all the hooding and ductwork comprising the VOC emission capture system for this emissions unit shall be free of leaks and holes that would permit the escape of the captured VOC emissions.
6. The average, total exhaust flow rate from this emissions unit to the catalytic oxidizer shall be within 25% of 1700 feet per minute (fpm), the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation. In the event that future emission tests are conducted, the average, total exhaust flow rate from this emissions unit to the catalytic oxidizer shall be within 25% of the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain continuous monitors and recorder(s) which measure and record the temperature immediately upstream and downstream of the incinerator's catalyst bed when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitors and recorder(s) shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.
2. The permittee shall collect and record the following information each day:
 - a. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
 - b. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance. The permittee may use the oxidizer's temperature chart to determine the temperature differential across the catalyst bed.
 - c. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation. The permittee may use the current temperature chart as the log documenting that the monitoring equipment and control device are operating. Each bypass of the collection system and/or control device shall be logged as to the date and time.

Issued

Emissions Unit ID: K044

3. The permittee shall perform an inspection of the catalytic oxidizer, including the catalyst bed, at least once each calendar year. Each inspection shall consist of internal and visual inspections in accordance with the manufacturer's recommendations and shall include a physical inspection of the unit and checks of associated equipment, including but not limited to burners, controls, dampers, valves, and monitoring and recording equipment. Repair and replacement of equipment shall be performed as determined by the inspection. In accordance with the testing schedule in section A.V, a sample of catalyst material shall be collected from the catalyst bed to perform the catalyst activity tests required in section A.V.
4. The permittee shall maintain a record of the results of each annual inspection of the catalytic oxidizer, as well as the results of each catalyst activity test required in section A.V.
5. The permittee shall operate and maintain a flow meter at the inlet to the catalytic oxidizer to ensure that the exhaust from the coating room and the emissions units in the coating room are being directed to the catalytic oxidizer. The permittee shall collect and record the flow rate at the inlet to the catalytic oxidizer on a daily basis.
6. Each calendar month, the permittee shall inspect the operational condition and integrity of each ventilation fan comprising the capture system. Ventilation fan observations shall include visual inspections of the fan wheel, belts, and bearings. Lubrication of bearings and replacement of parts shall occur as necessary. The permittee shall document the results of all monthly inspections, including any corrective actions taken.
7. Each calendar month, the permittee shall inspect the operational condition and integrity of all hooding, ductwork, and bypass dampers comprising the capture system. Hooding and ductwork observations shall include visual inspections to verify that the damper setting is in the correct position (i.e., to oxidizer or to atmosphere) and visual inspections of the actuator and motor to verify that the actuator pin and the motor are operating properly. The permittee shall document the results of all monthly inspections, including any corrective actions taken.
8. The permittee shall collect and record the following information each day for this coating line (K044):
 - a. The name and identification number of each coating, as applied;
 - b. The volume in gallons of each coating, as applied;
 - c. The VOC content of each coating, as applied, in pounds per gallon; and
 - d. The total VOC emissions from all coatings employed [summation of (b x c) for all coatings multiplied by the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the source was in compliance].
9. The permittee shall collect and record the following information each month for all coating lines at the facility:

- a. The name and identification number of each coating, as applied;
- b. The volume in gallons of each coating, as applied;
- c. The HAP content of each coating, as applied, in pounds per gallon;
- d. The total HAP emissions for all emissions units of each single HAP [summation of (b x c) for all coatings multiplied by the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the source was in compliance]; and
- e. The total combined HAP emissions for all emissions units [summation of (d) for all HAPs emitted by the coating lines plus the monthly HAP emissions from the vapor degreaser (L001)].

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and was not vented to the catalytic oxidizer.
2. The permittee shall submit quarterly summaries of the following records:
 - a. a log of operating time for the capture (collection) system, control device, monitoring equipment, and the associated emissions unit;
 - b. all 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed (as determined by the continuous temperature monitor) did not comply with the temperature limitation specified above; and
 - c. all 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed (as determined by the continuous temperature monitor) was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance.

NOTE: Information submitted pursuant to section A.IV.2.c is not relevant for determining compliance with any operational restriction contained in section A.II. As long as the permittee performs the monitoring, record keeping, and reporting specified in sections A.III.2.b and A.IV.2.c of these terms and conditions, an average temperature difference across the catalyst bed of less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance shall not constitute a violation of any operational restriction or be considered a deviation.

3. The permittee shall submit deviation (excursion) reports that identify all periods of time when the

Emissions Unit ID: K044

emissions unit was in operation and the daily average air flow rate in the inlet stack to the catalytic oxidizer was more than 25% less than 1700 feet per minute (fpm), the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation. In the event that future emission tests are conducted, the permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and the daily average air flow rate in the inlet stack to the catalytic oxidizer was more than 25% less than the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation.

4. The permittee shall submit deviation (excursion) reports which identify each day where the daily VOC emission rate exceeded 2.2 pounds per day for this emissions unit (K044). The notification shall include a copy of such record and shall be sent to the Ohio EPA Northeast District Office within 30 days after the exceedance occurs.
5. The permittee shall submit deviation (excursion) reports which identify each month during which the rolling, 12-month emissions of any single HAP from all emissions units at the facility exceeded 9.9 tons per year, and the actual rolling, 12-month emissions of each such single HAP for each such month.
6. The permittee shall submit deviation (excursion) reports which identify each month during which the rolling, 12-month emissions of combined HAPs from all emissions units at the facility exceeded 24.9 tons per year, and the actual rolling, 12-month emissions of combined HAPs for each such month.
7. The permittee shall submit annual reports which specify the actual annual VOC emissions for the emissions unit (K044) and emissions units K039, K040, K041, K042, K043, K045, K046, K047, K048, and K049; combined. The reports shall be submitted by January 31 of each year and cover the previous calendar year.
8. The permittee shall submit annual reports which summarize the facility-wide emissions of each single HAP and combined HAPs from all emissions units at the facility. The reports shall include the emission calculations, be submitted by January 31 of each year, and cover the previous calendar year.
9. The permittee shall submit annual reports which summarize the results of the annual inspections conducted on the catalytic oxidizer by the manufacturer's representative. The reports shall describe any maintenance conducted on the catalytic oxidizer as a direct result of the inspections by manufacturer's representative. The reports shall be submitted by January 31 of each year and cover the previous calendar year.
10. The permittee shall submit reports that include the results of the catalyst activity tests required in section A.V. These reports shall be submitted within 45 days after each catalyst activity test is performed.

V. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1 of these terms and conditions shall be determined in accordance with the following method(s):

Issued: To be entered upon final issuance

a. Emission Limitation:

VOC emissions shall not exceed 2.2 pounds per day.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 8 of these terms and conditions.

b. Emission Limitation:

VOC emissions shall not exceed 10.04 tons per year.

Applicable Compliance Method:

Compliance with the annual emission limitation is shown as long as compliance with the daily emission limitations for this emissions unit (K044) and emissions units K039, K040, K041, K042, K043, K045, K046, K047, K048, and K049, are maintained (the annual emission limitation was calculated by multiplying the sum of the daily emission limitations for this emissions unit (K044) and emissions units K039, K040, K041, K042, K043, K045, K046, K047, K048, and K049, by 365 and dividing by 2000).

c. Emission Limitation:

90 percent overall reduction of VOCs by weight.

Applicable Compliance Method:

If required by the Ohio EPA Northeast District Office, compliance shall be demonstrated in accordance with 40 CFR Part 60, Appendix A, Methods 25, 25A, and 40 CFR Part 51, Appendix M, Method 204. Performance testing shall be in accordance with OAC rule 3745-21-10(C).

d. Emission Limitation:

The emissions of each single hazardous air pollutant (HAP) from all emissions units at the facility shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 9 of these

Issued: To be entered upon final issuance

terms and conditions.

e. Emission Limitation:

The emissions of the combined HAPs from all emissions units at the facility shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 9 of these terms and conditions.

2. Emission testing demonstrating compliance with the overall control efficiency limitation for VOC of 81 percent, the destruction efficiency limitation for VOC of 90 percent, and capture efficiency was conducted on January 8, 2004, as required by PTI 02-17168 issued 04/03/03. Emission testing conducted on January 8, 2004, also demonstrated that the permittee was in compliance with the emission limitation of 90 percent overall reduction of VOCs by weight for this emissions unit (K044).
3. US EPA Method 24 shall be used to determine the VOC contents of all the coatings employed in this emissions unit.
4. The permittee shall conduct, or have conducted, catalyst activity testing using the catalyst sample collected during the annual inspection described in section A.III. An intent to test notification shall not be required for the testing noted in this term. The procedures for the catalyst activity test shall be in accordance with the manufacturer's recommendations.

VI. Miscellaneous Requirements

None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K044 - Rail coater and electric oven equipped with a catalytic oxidizer Terms in this permit supercede those identified in PTI 02-17168 issued 04/03/03.	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit (K044) was evaluated based on the actual materials (coatings) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant potentially emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: toluene
 TLV (ug/m3): 188,400
 Maximum Hourly Emission Rate (lbs/hr): 3.31
 Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 250.5

Issued: To be entered upon final issuance

MAGLC (ug/m3): 4476

Physical changes to or changes in the method of operation of the emissions unit after its installation could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

Forest City Technologies Inc Plant 2/4

PTI Application: 02 10084

Issued

Facility ID: 0247170841

Emissions Unit ID: K044

IV. Reporting Requirements

None

97

Forest

PTI A

Emissions Unit ID: K044

Issued: To be entered upon final issuance

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Forest
PTI A

Emissions Unit ID: K045

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	OAC rule 3745-35-07
K045 - Nut coater 1 equipped with a catalytic oxidizer Terms in this permit supercede those identified in PTI 02-17168 issued 04/03/03.	OAC rule 3745-31-05(A)(3)	
	OAC rule 3745-21-09(B)(6)	
	OAC rule 3745-21-09(U)	
	OAC rule 3745-21-09(B)(3)(l)	
	OAC rule 3745-21-09(B)(3)(m)	
	OAC rule 3745-21-09(B)(3)(n)	

Forest**PTI A**

Emissions Unit ID: K045

Issued: To be entered upon final issuance

Applicable Emissions
Limitations/Control
Measures

The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09(B)(6).

VOC emissions shall not exceed 2.07 pounds per day.

VOC emissions shall not exceed 10.04 tons per year.
See A.I.2.a below.

81 percent overall reduction of VOCs by weight and 90 percent destruction for all solvent based coatings.

In lieu of complying with the requirements of this rule, the permittee has opted to comply with the requirements of OAC rule 3745-21-09(B).

See A.III.2.a, A.III.2.b, and A.III.2.c below.

See A.IV.2.a, A.IV.2.b, and A.IV.2.c below.

See A.III.1, A.V.1.c, and A.V.2 below.

See A.I.2.b and A.I.2.c below.

Issued: To be entered upon final issuance**2. Additional Terms and Conditions**

- 2.a** The emission limitation of 10.04 tons VOC per year is based on the combined annual emissions from this emissions unit (K045) and emissions units K039, K040, K041, K042, K043, K044, K046, K047, K048, and K049.
- 2.b** The emissions of each single hazardous air pollutant (HAP) from all emissions units at the facility shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation. The permittee shall use existing records to determine compliance with the rolling 12-month restrictions upon issuance of this permit. Therefore, it is not necessary to establish federally enforceable restrictions for the first 12 months of operation under the provisions of this permit.
- 2.c** The emissions of the combined HAPs from all emissions units at the facility shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation. The permittee shall use existing records to determine compliance with the rolling 12-month restrictions upon issuance of this permit. Therefore, it is not necessary to establish federally enforceable restrictions for the first 12 months of operation under the provisions of this permit.

II. Operational Restrictions

1. Exhaust gases from operation of the emissions unit shall be vented to the catalytic oxidizer.
2. The average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below 652 degrees Fahrenheit, the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance. In the event that future emission tests are conducted, the average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
3. The catalytic oxidizer shall be operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manuals. The VOC conversion efficiency of the catalyst in the catalytic oxidizer, as determined by the catalyst activity testing, shall be at least 90% at a test temperature that is representative of the normal temperature at the catalyst bed inlet. Solvent loading during catalyst analysis shall be consistent with the test laboratory's normal testing protocol.
4. All ventilation fans associated with this emissions unit and the catalytic oxidizer shall be in

operation at all times when this emissions unit is in operation.

5. When employing the catalytic oxidizer, all bypass dampers, actuator pins, and associated motors shall be in the correct position and in good operating condition at all times when this emissions unit is in operation to ensure that all captured VOC emissions are vented to the catalytic oxidizer. Also, all the hooding and ductwork comprising the VOC emission capture system for this emissions unit shall be free of leaks and holes that would permit the escape of the captured VOC emissions.
6. The average, total exhaust flow rate from this emissions unit to the catalytic oxidizer shall be within 25% of 1700 feet per minute (fpm), the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation. In the event that future emission tests are conducted, the average, total exhaust flow rate from this emissions unit to the catalytic oxidizer shall be within 25% of the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain continuous monitors and recorder(s) which measure and record the temperature immediately upstream and downstream of the incinerator's catalyst bed when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitors and recorder(s) shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.
2. The permittee shall collect and record the following information each day:
 - a. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
 - b. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance. The permittee may use the oxidizer's temperature chart to determine the temperature differential across the catalyst bed.
 - c. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation. The permittee may use the current temperature chart as the log documenting that the monitoring equipment and control device are operating. Each bypass of the collection system and/or control device shall be logged as to the date and time.

Issued: To be entered upon final issuance

3. The permittee shall perform an inspection of the catalytic oxidizer, including the catalyst bed, at least once each calendar year. Each inspection shall consist of internal and visual inspections in accordance with the manufacturer's recommendations and shall include a physical inspection of the unit and checks of associated equipment, including but not limited to burners, controls, dampers, valves, and monitoring and recording equipment. Repair and replacement of equipment shall be performed as determined by the inspection. In accordance with the testing schedule in section A.V, a sample of catalyst material shall be collected from the catalyst bed to perform the catalyst activity tests required in section A.V.
4. The permittee shall maintain a record of the results of each annual inspection of the catalytic oxidizer, as well as the results of each catalyst activity test required in section A.V.
5. The permittee shall operate and maintain a flow meter at the inlet to the catalytic oxidizer to ensure that the exhaust from the coating room and the emissions units in the coating room are being directed to the catalytic oxidizer. The permittee shall collect and record the flow rate at the inlet to the catalytic oxidizer on a daily basis.
6. Each calendar month, the permittee shall inspect the operational condition and integrity of each ventilation fan comprising the capture system. Ventilation fan observations shall include visual inspections of the fan wheel, belts, and bearings. Lubrication of bearings and replacement of parts shall occur as necessary. The permittee shall document the results of all monthly inspections, including any corrective actions taken.
7. Each calendar month, the permittee shall inspect the operational condition and integrity of all hooding, ductwork, and bypass dampers comprising the capture system. Hooding and ductwork observations shall include visual inspections to verify that the damper setting is in the correct position (i.e., to oxidizer or to atmosphere) and visual inspections of the actuator and motor to verify that the actuator pin and the motor are operating properly. The permittee shall document the results of all monthly inspections, including any corrective actions taken.
8. The permittee shall collect and record the following information each day for this coating line (K045):
 - a. The name and identification number of each coating, as applied;
 - b. The volume in gallons of each coating, as applied;
 - c. The VOC content of each coating, as applied, in pounds per gallon; and
 - d. The total VOC emissions from all coatings employed [summation of (b x c) for all coatings multiplied by the overall control efficiency for the control equipment as

Emissions Unit ID: K045

determined during the most recent emission test that demonstrated that the source was in compliance].

9. The permittee shall collect and record the following information each month for all coating lines at the facility:
 - a. The name and identification number of each coating, as applied;
 - b. The volume in gallons of each coating, as applied;
 - c. The HAP content of each coating, as applied, in pounds per gallon;
 - d. The total HAP emissions for all emissions units of each single HAP [summation of (b x c) for all coatings multiplied by the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the source was in compliance]; and
 - e. The total combined HAP emissions for all emissions units [summation of (d) for all HAPs emitted by the coating lines plus the monthly HAP emissions from the vapor degreaser (L001)].

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and was not vented to the catalytic oxidizer.
2. The permittee shall submit quarterly summaries of the following records:
 - a. a log of operating time for the capture (collection) system, control device, monitoring equipment, and the associated emissions unit;
 - b. all 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed (as determined by the continuous temperature monitor) did not comply with the temperature limitation specified above; and
 - c. all 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed (as determined by the continuous temperature monitor) was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance.

NOTE: Information submitted pursuant to section A.IV.2.c is not relevant for determining compliance with any operational restriction contained in section A.II. As long as the permittee performs the monitoring, record keeping, and reporting specified in sections A.III.2.b and A.IV.2.c of these terms and conditions, an average temperature difference across the catalyst bed

Issued: To be entered upon final issuance

- of less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance shall not constitute a violation of any operational restriction or be considered a deviation.
3. The permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and the daily average air flow rate in the inlet stack to the catalytic oxidizer was more than 25% less than 1700 feet per minute (fpm), the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation. In the event that future emission tests are conducted, the permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and the daily average air flow rate in the inlet stack to the catalytic oxidizer was more than 25% less than the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation.
 4. The permittee shall submit deviation (excursion) reports which identify each day where the daily VOC emission rate exceeded 2.07 pounds per day for this emissions unit (K045). The notification shall include a copy of such record and shall be sent to the Ohio EPA Northeast District Office within 30 days after the exceedance occurs.
 5. The permittee shall submit deviation (excursion) reports which identify each month during which the rolling, 12-month emissions of any single HAP from all emissions units at the facility exceeded 9.9 tons per year, and the actual rolling, 12-month emissions of each such single HAP for each such month.
 6. The permittee shall submit deviation (excursion) reports which identify each month during which the rolling, 12-month emissions of combined HAPs from all emissions units at the facility exceeded 24.9 tons per year, and the actual rolling, 12-month emissions of combined HAPs for each such month.
 7. The permittee shall submit annual reports which specify the actual annual VOC emissions for the emissions unit (K045) and emissions units K039, K040, K041, K042, K043, K044, K046, K047, K048, and K049; combined. The reports shall be submitted by January 31 of each year and cover the previous calendar year.
 8. The permittee shall submit annual reports which summarize the facility-wide emissions of each single HAP and combined HAPs from all emissions units at the facility. The reports shall include the emission calculations, be submitted by January 31 of each year, and cover the previous calendar year.
 9. The permittee shall submit annual reports which summarize the results of the annual inspections

Issued

Emissions Unit ID: K045

conducted on the catalytic oxidizer by the manufacturer's representative. The reports shall describe any maintenance conducted on the catalytic oxidizer as a direct result of the inspections by manufacturer's representative. The reports shall be submitted by January 31 of each year and cover the previous calendar year.

10. The permittee shall submit reports that include the results of the catalyst activity tests required in section A.V. These reports shall be submitted within 45 days after each catalyst activity test is performed.

V. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1 of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation:

VOC emissions shall not exceed 2.07 pounds per day.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 8 of these terms and conditions.

- b. Emission Limitation:

VOC emissions shall not exceed 10.04 tons per year.

Applicable Compliance Method:

Compliance with the annual emission limitation is shown as long as compliance with the daily emission limitations for this emissions unit (K045) and emissions units K039, K040, K041, K042, K043, K044, K046, K047, K048, and K049, are maintained (the annual emission limitation was calculated by multiplying the sum of the daily emission limitations for this emissions unit (K045) and emissions units K039, K040, K041, K042, K043, K044, K046, K047, K048, and K049, by 365 and dividing by 2000).

- c. Emission Limitation:

81 percent overall reduction of VOCs by weight and 90 percent destruction for all solvent based coatings.

Applicable Compliance Method:

If required by the Ohio EPA Northeast District Office, compliance shall be demonstrated in accordance with 40 CFR Part 60, Appendix A, Methods 25, 25A, and 40 CFR Part 51, Appendix M, Method 204. Performance testing shall be in accordance with OAC rule

3745-21-10(C).

d. Emission Limitation:

The emissions of each single hazardous air pollutant (HAP) from all emissions units at the facility shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 9 of these terms and conditions.

e. Emission Limitation:

The emissions of the combined HAPs from all emissions units at the facility shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 9 of these terms and conditions.

2. Emission testing demonstrating compliance with the overall control efficiency limitation for VOC of 81 percent, the destruction efficiency limitation for VOC of 90 percent, and capture efficiency was conducted on January 8, 2004, as required by PTI 02-17168 issued 04/03/03.
3. US EPA Method 24 shall be used to determine the VOC contents of all the coatings employed in this emissions unit.
4. The permittee shall conduct, or have conducted, catalyst activity testing using the catalyst sample collected during the annual inspection described in section A.III. An intent to test notification shall not be required for the testing noted in this term. The procedures for the catalyst activity test shall be in accordance with the manufacturer's recommendations.

VI. Miscellaneous Requirements

None

**Forest
PTI A**

Emissions Unit ID: K045

Issued: To be entered upon final issuance

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K045 - Nut coater 1 equipped with a catalytic oxidizer Terms in this permit supercede those identified in PTI 02-17168 issued 04/03/03.	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit (K045) was evaluated based on the actual materials (coatings) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant potentially emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Issued: To be entered upon final issuance

Pollutant: toluene

TLV (ug/m3): 188,400

Maximum Hourly Emission Rate (lbs/hr): 3.31

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 250.5

MAGLC (ug/m3): 4476

Physical changes to or changes in the method of operation of the emissions unit after its installation could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

Issued

Emissions Unit ID: K045

- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

110

Forest

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: K045

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Forest
PTI A

Emissions Unit ID: K046

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	OAC rule 3745-35-07
K046 - Nut coater 2 equipped with a catalytic oxidizer	OAC rule 3745-31-05(A)(3)	
Terms in this permit supercede those identified in PTI 02-17168 issued 04/03/03.	OAC rule 3745-21-09(B)(6)	
	OAC rule 3745-21-09(U)	
	OAC rule 3745-21-09(B)(3)(l)	
	OAC rule 3745-21-09(B)(3)(m)	
	OAC rule 3745-21-09(B)(3)(n)	

Forest**PTI A**

Emissions Unit ID: K046

Issued: To be entered upon final issuance

Applicable Emissions
Limitations/Control
Measures

The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09(B)(6).

VOC emissions shall not exceed 2.07 pounds per day.

VOC emissions shall not exceed 10.04 tons per year.
See A.I.2.a below.

81 percent overall reduction of VOCs by weight and 90 percent destruction for all solvent based coatings.

In lieu of complying with the requirements of this rule, the permittee has opted to comply with the requirements of OAC rule 3745-21-09(B).

See A.III.2.a, A.III.2.b, and A.III.2.c below.

See A.IV.2.a, A.IV.2.b, and A.IV.2.c below.

See A.III.1, A.V.1.c, and A.V.2 below.

See A.I.2.b and A.I.2.c below.

Issued: To be entered upon final issuance**2. Additional Terms and Conditions**

- 2.a** The emission limitation of 10.04 tons VOC per year is based on the combined annual emissions from this emissions unit (K046) and emissions units K039, K040, K041, K042, K043, K044, K045, K047, K048, and K049.
- 2.b** The emissions of each single hazardous air pollutant (HAP) from all emissions units at the facility shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation. The permittee shall use existing records to determine compliance with the rolling 12-month restrictions upon issuance of this permit. Therefore, it is not necessary to establish federally enforceable restrictions for the first 12 months of operation under the provisions of this permit.
- 2.c** The emissions of the combined HAPs from all emissions units at the facility shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation. The permittee shall use existing records to determine compliance with the rolling 12-month restrictions upon issuance of this permit. Therefore, it is not necessary to establish federally enforceable restrictions for the first 12 months of operation under the provisions of this permit.

II. Operational Restrictions

1. Exhaust gases from operation of the emissions unit shall be vented to the catalytic oxidizer.
2. The average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below 652 degrees Fahrenheit, the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance. In the event that future emission tests are conducted, the average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
3. The catalytic oxidizer shall be operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manuals. The VOC conversion efficiency of the catalyst in the catalytic oxidizer, as determined by the catalyst activity testing, shall be at least 90% at a test temperature that is representative of the normal temperature at the catalyst bed inlet. Solvent loading during catalyst analysis shall be consistent with the test laboratory's normal testing protocol.
4. All ventilation fans associated with this emissions unit and the catalytic oxidizer shall be in

operation at all times when this emissions unit is in operation.

5. When employing the catalytic oxidizer, all bypass dampers, actuator pins, and associated motors shall be in the correct position and in good operating condition at all times when this emissions unit is in operation to ensure that all captured VOC emissions are vented to the catalytic oxidizer. Also, all the hooding and ductwork comprising the VOC emission capture system for this emissions unit shall be free of leaks and holes that would permit the escape of the captured VOC emissions.
6. The average, total exhaust flow rate from this emissions unit to the catalytic oxidizer shall be within 25% of 1700 feet per minute (fpm), the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation. In the event that future emission tests are conducted, the average, total exhaust flow rate from this emissions unit to the catalytic oxidizer shall be within 25% of the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain continuous monitors and recorder(s) which measure and record the temperature immediately upstream and downstream of the incinerator's catalyst bed when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitors and recorder(s) shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.
2. The permittee shall collect and record the following information each day:
 - a. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
 - b. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance. The permittee may use the oxidizer's temperature chart to determine the temperature differential across the catalyst bed.
 - c. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation. The permittee may use the current temperature chart as the log documenting that the monitoring equipment and control device are operating. Each bypass of the collection system and/or control device shall be logged as to the date and time.

Issued

Emissions Unit ID: K046

3. The permittee shall perform an inspection of the catalytic oxidizer, including the catalyst bed, at least once each calendar year. Each inspection shall consist of internal and visual inspections in accordance with the manufacturer's recommendations and shall include a physical inspection of the unit and checks of associated equipment, including but not limited to burners, controls, dampers, valves, and monitoring and recording equipment. Repair and replacement of equipment shall be performed as determined by the inspection. In accordance with the testing schedule in section A.V, a sample of catalyst material shall be collected from the catalyst bed to perform the catalyst activity tests required in section A.V.
4. The permittee shall maintain a record of the results of each annual inspection of the catalytic oxidizer, as well as the results of each catalyst activity test required in section A.V.
5. The permittee shall operate and maintain a flow meter at the inlet to the catalytic oxidizer to ensure that the exhaust from the coating room and the emissions units in the coating room are being directed to the catalytic oxidizer. The permittee shall collect and record the flow rate at the inlet to the catalytic oxidizer on a daily basis.
6. Each calendar month, the permittee shall inspect the operational condition and integrity of each ventilation fan comprising the capture system. Ventilation fan observations shall include visual inspections of the fan wheel, belts, and bearings. Lubrication of bearings and replacement of parts shall occur as necessary. The permittee shall document the results of all monthly inspections, including any corrective actions taken.
7. Each calendar month, the permittee shall inspect the operational condition and integrity of all hooding, ductwork, and bypass dampers comprising the capture system. Hooding and ductwork observations shall include visual inspections to verify that the damper setting is in the correct position (i.e., to oxidizer or to atmosphere) and visual inspections of the actuator and motor to verify that the actuator pin and the motor are operating properly. The permittee shall document the results of all monthly inspections, including any corrective actions taken.
8. The permittee shall collect and record the following information each day for this coating line (K046):
 - a. The name and identification number of each coating, as applied;
 - b. The volume in gallons of each coating, as applied;
 - c. The VOC content of each coating, as applied, in pounds per gallon; and
 - d. The total VOC emissions from all coatings employed [summation of (b x c) for all coatings multiplied by the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the source was in compliance].
9. The permittee shall collect and record the following information each month for all coating lines at the facility:

Issued: To be entered upon final issuance

- a. The name and identification number of each coating, as applied;
- b. The volume in gallons of each coating, as applied;
- c. The HAP content of each coating, as applied, in pounds per gallon;
- d. The total HAP emissions for all emissions units of each single HAP [summation of (b x c) for all coatings multiplied by the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the source was in compliance]; and
- e. The total combined HAP emissions for all emissions units [summation of (d) for all HAPs emitted by the coating lines plus the monthly HAP emissions from the vapor degreaser (L001)].

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and was not vented to the catalytic oxidizer.
2. The permittee shall submit quarterly summaries of the following records:
 - a. a log of operating time for the capture (collection) system, control device, monitoring equipment, and the associated emissions unit;
 - b. all 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed (as determined by the continuous temperature monitor) did not comply with the temperature limitation specified above; and
 - c. all 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed (as determined by the continuous temperature monitor) was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance.

NOTE: Information submitted pursuant to section A.IV.2.c is not relevant for determining compliance with any operational restriction contained in section A.II. As long as the permittee performs the monitoring, record keeping, and reporting specified in sections A.III.2.b and A.IV.2.c of these terms and conditions, an average temperature difference across the catalyst bed

Emissions Unit ID: K046

of less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance shall not constitute a violation of any operational restriction or be considered a deviation.

3. The permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and the daily average air flow rate in the inlet stack to the catalytic oxidizer was more than 25% less than 1700 feet per minute (fpm), the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation. In the event that future emission tests are conducted, the permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and the daily average air flow rate in the inlet stack to the catalytic oxidizer was more than 25% less than the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation.
4. The permittee shall submit deviation (excursion) reports which identify each day where the daily VOC emission rate exceeded 2.07 pounds per day for this emissions unit (K046). The notification shall include a copy of such record and shall be sent to the Ohio EPA Northeast District Office within 30 days after the exceedance occurs.
5. The permittee shall submit deviation (excursion) reports which identify each month during which the rolling, 12-month emissions of any single HAP from all emissions units at the facility exceeded 9.9 tons per year, and the actual rolling, 12-month emissions of each such single HAP for each such month.
6. The permittee shall submit deviation (excursion) reports which identify each month during which the rolling, 12-month emissions of combined HAPs from all emissions units at the facility exceeded 24.9 tons per year, and the actual rolling, 12-month emissions of combined HAPs for each such month.
7. The permittee shall submit annual reports which specify the actual annual VOC emissions for the emissions unit (K046) and emissions units K039, K040, K041, K042, K043, K044, K045, K047, K048, and K049; combined. The reports shall be submitted by January 31 of each year and cover the previous calendar year.
8. The permittee shall submit annual reports which summarize the facility-wide emissions of each single HAP and combined HAPs from all emissions units at the facility. The reports shall include the emission calculations, be submitted by January 31 of each year, and cover the previous calendar year.
9. The permittee shall submit annual reports which summarize the results of the annual inspections conducted on the catalytic oxidizer by the manufacturer's representative. The reports shall describe any maintenance conducted on the catalytic oxidizer as a direct result of the inspections by manufacturer's representative. The reports shall be submitted by January 31 of each year and cover the previous calendar year.

Issued

Emissions Unit ID: K046

10. The permittee shall submit reports that include the results of the catalyst activity tests required in section A.V. These reports shall be submitted within 45 days after each catalyst activity test is performed.

V. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1 of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation:

VOC emissions shall not exceed 2.07 pounds per day.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 8 of these terms and conditions.

- b. Emission Limitation:

VOC emissions shall not exceed 10.04 tons per year.

Applicable Compliance Method:

Compliance with the annual emission limitation is shown as long as compliance with the daily emission limitations for this emissions unit (K046) and emissions units K039, K040, K041, K042, K043, K044, K045, K047, K048, and K049, are maintained (the annual emission limitation was calculated by multiplying the sum of the daily emission limitations for this emissions unit (K046) and emissions units K039, K040, K041, K042, K043, K044, K045, K047, K048, and K049, by 365 and dividing by 2000).

- c. Emission Limitation:

81 percent overall reduction of VOCs by weight and 90 percent destruction for all solvent based coatings.

Applicable Compliance Method:

If required by the Ohio EPA Northeast District Office, compliance shall be demonstrated in accordance with 40 CFR Part 60, Appendix A, Methods 25, 25A, and 40 CFR Part 51, Appendix M, Method 204. Performance testing shall be in accordance with OAC rule 3745-21-10(C).

- d. Emission Limitation:

The emissions of each single hazardous air pollutant (HAP) from all emissions units at the

Issued: To be entered upon final issuance

facility shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 9 of these terms and conditions.

e. Emission Limitation:

The emissions of the combined HAPs from all emissions units at the facility shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 9 of these terms and conditions.

2. Emission testing demonstrating compliance with the overall control efficiency limitation for VOC of 81 percent, the destruction efficiency limitation for VOC of 90 percent, and capture efficiency was conducted on January 8, 2004, as required by PTI 02-17168 issued 04/03/03.
3. US EPA Method 24 shall be used to determine the VOC contents of all the coatings employed in this emissions unit.
4. The permittee shall conduct, or have conducted, catalyst activity testing using the catalyst sample collected during the annual inspection described in section A.III. An intent to test notification shall not be required for the testing noted in this term. The procedures for the catalyst activity test shall be in accordance with the manufacturer's recommendations.

VI. Miscellaneous Requirements

None

**Forest
PTI A**

Emissions Unit ID: K046

Issued: To be entered upon final issuance

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K046 - Nut coater 2 equipped with a catalytic oxidizer Terms in this permit supercede those identified in PTI 02-17168 issued 04/03/03.	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit (K046) was evaluated based on the actual materials (coatings) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant potentially emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: toluene

TLV (ug/m3): 188,400

Maximum Hourly Emission Rate (lbs/hr): 3.31

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 250.5

MAGLC (ug/m3): 4476

Physical changes to or changes in the method of operation of the emissions unit after its installation could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

122

Forest

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: K046

IV. Reporting Requirements

None

123

Forest

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: K046

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Forest
PTI A

Emissions Unit ID: K047

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	OAC rule 3745-35-07
K047 - Nut coater 3 equipped with a catalytic oxidizer	OAC rule 3745-31-05(A)(3)	
Terms in this permit supercede those identified in PTI 02-17168 issued 04/03/03.	OAC rule 3745-21-09(B)(6)	
	OAC rule 3745-21-09(U)	
	OAC rule 3745-21-09(B)(3)(l)	
	OAC rule 3745-21-09(B)(3)(m)	
	OAC rule 3745-21-09(B)(3)(n)	

Applicable Emissions
Limitations/Control
Measures

The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09(B)(6).

VOC emissions shall not exceed 2.07 pounds per day.

VOC emissions shall not exceed 10.04 tons per year.
See A.I.2.a below.

81 percent overall reduction of VOCs by weight and 90 percent destruction for all solvent based coatings.

In lieu of complying with the requirements of this rule, the permittee has opted to comply with the requirements of OAC rule 3745-21-09(B).

See A.III.2.a, A.III.2.b, and A.III.2.c below.

See A.IV.2.a, A.IV.2.b, and A.IV.2.c below.

See A.III.1, A.V.1.c, and A.V.2 below.

See A.I.2.b and A.I.2.c below.

Issued: To be entered upon final issuance**2. Additional Terms and Conditions**

- 2.a** The emission limitation of 10.04 tons VOC per year is based on the combined annual emissions from this emissions unit (K047) and emissions units K039, K040, K041, K042, K043, K044, K045, K046, K048, and K049.
- 2.b** The emissions of each single hazardous air pollutant (HAP) from all emissions units at the facility shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation. The permittee shall use existing records to determine compliance with the rolling 12-month restrictions upon issuance of this permit. Therefore, it is not necessary to establish federally enforceable restrictions for the first 12 months of operation under the provisions of this permit.
- 2.c** The emissions of the combined HAPs from all emissions units at the facility shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation. The permittee shall use existing records to determine compliance with the rolling 12-month restrictions upon issuance of this permit. Therefore, it is not necessary to establish federally enforceable restrictions for the first 12 months of operation under the provisions of this permit.

II. Operational Restrictions

1. Exhaust gases from operation of the emissions unit shall be vented to the catalytic oxidizer.
2. The average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below 652 degrees Fahrenheit, the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance. In the event that future emission tests are conducted, the average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
3. The catalytic oxidizer shall be operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manuals. The VOC conversion efficiency of the catalyst in the catalytic oxidizer, as determined by the catalyst activity testing, shall be at least 90% at a test temperature that is representative of the normal temperature at the catalyst bed inlet. Solvent loading during catalyst analysis shall be consistent with the test laboratory's normal testing protocol.
4. All ventilation fans associated with this emissions unit and the catalytic oxidizer shall be in

operation at all times when this emissions unit is in operation.

5. When employing the catalytic oxidizer, all bypass dampers, actuator pins, and associated motors shall be in the correct position and in good operating condition at all times when this emissions unit is in operation to ensure that all captured VOC emissions are vented to the catalytic oxidizer. Also, all the hooding and ductwork comprising the VOC emission capture system for this emissions unit shall be free of leaks and holes that would permit the escape of the captured VOC emissions.
6. The average, total exhaust flow rate from this emissions unit to the catalytic oxidizer shall be within 25% of 1700 feet per minute (fpm), the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation. In the event that future emission tests are conducted, the average, total exhaust flow rate from this emissions unit to the catalytic oxidizer shall be within 25% of the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain continuous monitors and recorder(s) which measure and record the temperature immediately upstream and downstream of the incinerator's catalyst bed when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitors and recorder(s) shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.
2. The permittee shall collect and record the following information each day:
 - a. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
 - b. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance. The permittee may use the oxidizer's temperature chart to determine the temperature differential across the catalyst bed.
 - c. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation. The permittee may use the current temperature chart as the log documenting that the monitoring equipment and control device are operating. Each bypass of the collection system and/or control device shall be logged as to the date and time.

Issued: To be entered upon final issuance

3. The permittee shall perform an inspection of the catalytic oxidizer, including the catalyst bed, at least once each calendar year. Each inspection shall consist of internal and visual inspections in accordance with the manufacturer's recommendations and shall include a physical inspection of the unit and checks of associated equipment, including but not limited to burners, controls, dampers, valves, and monitoring and recording equipment. Repair and replacement of equipment shall be performed as determined by the inspection. In accordance with the testing schedule in section A.V, a sample of catalyst material shall be collected from the catalyst bed to perform the catalyst activity tests required in section A.V.
4. The permittee shall maintain a record of the results of each annual inspection of the catalytic oxidizer, as well as the results of each catalyst activity test required in section A.V.
5. The permittee shall operate and maintain a flow meter at the inlet to the catalytic oxidizer to ensure that the exhaust from the coating room and the emissions units in the coating room are being directed to the catalytic oxidizer. The permittee shall collect and record the flow rate at the inlet to the catalytic oxidizer on a daily basis.
6. Each calendar month, the permittee shall inspect the operational condition and integrity of each ventilation fan comprising the capture system. Ventilation fan observations shall include visual inspections of the fan wheel, belts, and bearings. Lubrication of bearings and replacement of parts shall occur as necessary. The permittee shall document the results of all monthly inspections, including any corrective actions taken.
7. Each calendar month, the permittee shall inspect the operational condition and integrity of all hooding, ductwork, and bypass dampers comprising the capture system. Hooding and ductwork observations shall include visual inspections to verify that the damper setting is in the correct position (i.e., to oxidizer or to atmosphere) and visual inspections of the actuator and motor to verify that the actuator pin and the motor are operating properly. The permittee shall document the results of all monthly inspections, including any corrective actions taken.
8. The permittee shall collect and record the following information each day for this coating line (K047):
 - a. The name and identification number of each coating, as applied;
 - b. The volume in gallons of each coating, as applied;
 - c. The VOC content of each coating, as applied, in pounds per gallon; and
 - d. The total VOC emissions from all coatings employed [summation of (b x c) for all coatings multiplied by the overall control efficiency for the control equipment as

Emissions Unit ID: K047

determined during the most recent emission test that demonstrated that the source was in compliance].

9. The permittee shall collect and record the following information each month for all coating lines at the facility:
 - a. The name and identification number of each coating, as applied;
 - b. The volume in gallons of each coating, as applied;
 - c. The HAP content of each coating, as applied, in pounds per gallon;
 - d. The total HAP emissions for all emissions units of each single HAP [summation of (b x c) for all coatings multiplied by the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the source was in compliance]; and
 - e. The total combined HAP emissions for all emissions units [summation of (d) for all HAPs emitted by the coating lines plus the monthly HAP emissions from the vapor degreaser (L001)].

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and was not vented to the catalytic oxidizer.
2. The permittee shall submit quarterly summaries of the following records:
 - a. a log of operating time for the capture (collection) system, control device, monitoring equipment, and the associated emissions unit;
 - b. all 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed (as determined by the continuous temperature monitor) did not comply with the temperature limitation specified above; and
 - c. all 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed (as determined by the continuous temperature monitor) was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance.

NOTE: Information submitted pursuant to section A.IV.2.c is not relevant for determining compliance with any operational restriction contained in section A.II. As long as the permittee performs the monitoring, record keeping, and reporting specified in sections A.III.2.b and A.IV.2.c of these terms and conditions, an average temperature difference across the catalyst bed

Issued: To be entered upon final issuance

of less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance shall not constitute a violation of any operational restriction or be considered a deviation.

3. The permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and the daily average air flow rate in the inlet stack to the catalytic oxidizer was more than 25% less than 1700 feet per minute (fpm), the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation. In the event that future emission tests are conducted, the permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and the daily average air flow rate in the inlet stack to the catalytic oxidizer was more than 25% less than the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation.
4. The permittee shall submit deviation (excursion) reports which identify each day where the daily VOC emission rate exceeded 2.07 pounds per day for this emissions unit (K047). The notification shall include a copy of such record and shall be sent to the Ohio EPA Northeast District Office within 30 days after the exceedance occurs.
5. The permittee shall submit deviation (excursion) reports which identify each month during which the rolling, 12-month emissions of any single HAP from all emissions units at the facility exceeded 9.9 tons per year, and the actual rolling, 12-month emissions of each such single HAP for each such month.
6. The permittee shall submit deviation (excursion) reports which identify each month during which the rolling, 12-month emissions of combined HAPs from all emissions units at the facility exceeded 24.9 tons per year, and the actual rolling, 12-month emissions of combined HAPs for each such month.
7. The permittee shall submit annual reports which specify the actual annual VOC emissions for the emissions unit (K047) and emissions units K039, K040, K041, K042, K043, K044, K045, K046, K048, and K049; combined. The reports shall be submitted by January 31 of each year and cover the previous calendar year.
8. The permittee shall submit annual reports which summarize the facility-wide emissions of each single HAP and combined HAPs from all emissions units at the facility. The reports shall include the emission calculations, be submitted by January 31 of each year, and cover the previous calendar year.
9. The permittee shall submit annual reports which summarize the results of the annual inspections

Emissions Unit ID: K047

conducted on the catalytic oxidizer by the manufacturer's representative. The reports shall describe any maintenance conducted on the catalytic oxidizer as a direct result of the inspections by manufacturer's representative. The reports shall be submitted by January 31 of each year and cover the previous calendar year.

10. The permittee shall submit reports that include the results of the catalyst activity tests required in section A.V. These reports shall be submitted within 45 days after each catalyst activity test is performed.

V. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1 of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation:

VOC emissions shall not exceed 2.07 pounds per day.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 8 of these terms and conditions.

- b. Emission Limitation:

VOC emissions shall not exceed 10.04 tons per year.

Applicable Compliance Method:

Compliance with the annual emission limitation is shown as long as compliance with the daily emission limitations for this emissions unit (K047) and emissions units K039, K040, K041, K042, K043, K044, K045, K046, K048, and K049, are maintained (the annual emission limitation was calculated by multiplying the sum of the daily emission limitations for this emissions unit (K047) and emissions units K039, K040, K041, K042, K043, K044, K045, K046, K048, and K049, by 365 and dividing by 2000).

- c. Emission Limitation:

81 percent overall reduction of VOCs by weight and 90 percent destruction for all solvent based coatings.

Applicable Compliance Method:

If required by the Ohio EPA Northeast District Office, compliance shall be demonstrated in accordance with 40 CFR Part 60, Appendix A, Methods 25, 25A, and 40 CFR Part 51, Appendix M, Method 204. Performance testing shall be in accordance with OAC rule

3745-21-10(C).

d. Emission Limitation:

The emissions of each single hazardous air pollutant (HAP) from all emissions units at the facility shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 9 of these terms and conditions.

e. Emission Limitation:

The emissions of the combined HAPs from all emissions units at the facility shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 9 of these terms and conditions.

2. Emission testing demonstrating compliance with the overall control efficiency limitation for VOC of 81 percent, the destruction efficiency limitation for VOC of 90 percent, and capture efficiency was conducted on January 8, 2004, as required by PTI 02-17168 issued 04/03/03.
3. US EPA Method 24 shall be used to determine the VOC contents of all the coatings employed in this emissions unit.
4. The permittee shall conduct, or have conducted, catalyst activity testing using the catalyst sample collected during the annual inspection described in section A.III. An intent to test notification shall not be required for the testing noted in this term. The procedures for the catalyst activity test shall be in accordance with the manufacturer's recommendations.

VI. Miscellaneous Requirements

None

**Forest
PTI A**

Emissions Unit ID: K047

Issued: To be entered upon final issuance

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K047 - Nut coater 3 equipped with a catalytic oxidizer Terms in this permit supercede those identified in PTI 02-17168 issued 04/03/03.	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit (K047) was evaluated based on the actual materials (coatings) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant potentially emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Issued: To be entered upon final issuance

Pollutant: toluene

TLV (ug/m3): 188,400

Maximum Hourly Emission Rate (lbs/hr): 3.31

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 250.5

MAGLC (ug/m3): 4476

Physical changes to or changes in the method of operation of the emissions unit after its installation could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

Issued

Emissions Unit ID: K047

- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

136

Forest

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: K047

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Forest
PTI A

Emissions Unit ID: K048

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	OAC rule 3745-35-07
K048 - Nut coater 4 (hand) equipped with a catalytic oxidizer	OAC rule 3745-31-05(A)(3)	
Terms in this permit supercede those identified in PTI 02-17168 issued 04/03/03.	OAC rule 3745-21-09(B)(6)	
	OAC rule 3745-21-09(U)	
	OAC rule 3745-21-09(B)(3)(l)	
	OAC rule 3745-21-09(B)(3)(m)	
	OAC rule 3745-21-09(B)(3)(n)	

Forest**PTI A**

Emissions Unit ID: K048

Issued: To be entered upon final issuance

Applicable Emissions
Limitations/Control
Measures

The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09(B)(6).

VOC emissions shall not exceed 1.03 pounds per day.

VOC emissions shall not exceed 10.04 tons per year.
See A.I.2.a below.

81 percent overall reduction of VOCs by weight and 90 percent destruction for all solvent based coatings.

In lieu of complying with the requirements of this rule, the permittee has opted to comply with the requirements of OAC rule 3745-21-09(B).

See A.III.2.a, A.III.2.b, and A.III.2.c below.

See A.IV.2.a, A.IV.2.b, and A.IV.2.c below.

See A.III.1, A.V.1.c, and A.V.2 below.

See A.I.2.b and A.I.2.c below.

Issued: To be entered upon final issuance**2. Additional Terms and Conditions**

- 2.a** The emission limitation of 10.04 tons VOC per year is based on the combined annual emissions from this emissions unit (K048) and emissions units K039, K040, K041, K042, K043, K044, K045, K046, K047, and K049.
- 2.b** The emissions of each single hazardous air pollutant (HAP) from all emissions units at the facility shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation. The permittee shall use existing records to determine compliance with the rolling 12-month restrictions upon issuance of this permit. Therefore, it is not necessary to establish federally enforceable restrictions for the first 12 months of operation under the provisions of this permit.
- 2.c** The emissions of the combined HAPs from all emissions units at the facility shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation. The permittee shall use existing records to determine compliance with the rolling 12-month restrictions upon issuance of this permit. Therefore, it is not necessary to establish federally enforceable restrictions for the first 12 months of operation under the provisions of this permit.

II. Operational Restrictions

1. Exhaust gases from operation of the emissions unit shall be vented to the catalytic oxidizer.
2. The average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below 652 degrees Fahrenheit, the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance. In the event that future emission tests are conducted, the average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
3. The catalytic oxidizer shall be operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manuals. The VOC conversion efficiency of the catalyst in the catalytic oxidizer, as determined by the catalyst activity testing, shall be at least 90% at a test temperature that is representative of the normal temperature at the catalyst bed inlet. Solvent loading during catalyst analysis shall be consistent with the test laboratory's normal testing protocol.
4. All ventilation fans associated with this emissions unit and the catalytic oxidizer shall be in

operation at all times when this emissions unit is in operation.

5. When employing the catalytic oxidizer, all bypass dampers, actuator pins, and associated motors shall be in the correct position and in good operating condition at all times when this emissions unit is in operation to ensure that all captured VOC emissions are vented to the catalytic oxidizer. Also, all the hooding and ductwork comprising the VOC emission capture system for this emissions unit shall be free of leaks and holes that would permit the escape of the captured VOC emissions.
6. The average, total exhaust flow rate from this emissions unit to the catalytic oxidizer shall be within 25% of 1700 feet per minute (fpm), the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation. In the event that future emission tests are conducted, the average, total exhaust flow rate from this emissions unit to the catalytic oxidizer shall be within 25% of the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain continuous monitors and recorder(s) which measure and record the temperature immediately upstream and downstream of the incinerator's catalyst bed when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitors and recorder(s) shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.
2. The permittee shall collect and record the following information each day:
 - a. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
 - b. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance. The permittee may use the oxidizer's temperature chart to determine the temperature differential across the catalyst bed.
 - c. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation. The permittee may use the current temperature chart as the log documenting that the monitoring equipment and control device are operating. Each bypass of the collection system and/or control device shall be logged as to the date and time.

Issued

Emissions Unit ID: K048

3. The permittee shall perform an inspection of the catalytic oxidizer, including the catalyst bed, at least once each calendar year. Each inspection shall consist of internal and visual inspections in accordance with the manufacturer's recommendations and shall include a physical inspection of the unit and checks of associated equipment, including but not limited to burners, controls, dampers, valves, and monitoring and recording equipment. Repair and replacement of equipment shall be performed as determined by the inspection. In accordance with the testing schedule in section A.V, a sample of catalyst material shall be collected from the catalyst bed to perform the catalyst activity tests required in section A.V.
4. The permittee shall maintain a record of the results of each annual inspection of the catalytic oxidizer, as well as the results of each catalyst activity test required in section A.V.
5. The permittee shall operate and maintain a flow meter at the inlet to the catalytic oxidizer to ensure that the exhaust from the coating room and the emissions units in the coating room are being directed to the catalytic oxidizer. The permittee shall collect and record the flow rate at the inlet to the catalytic oxidizer on a daily basis.
6. Each calendar month, the permittee shall inspect the operational condition and integrity of each ventilation fan comprising the capture system. Ventilation fan observations shall include visual inspections of the fan wheel, belts, and bearings. Lubrication of bearings and replacement of parts shall occur as necessary. The permittee shall document the results of all monthly inspections, including any corrective actions taken.
7. Each calendar month, the permittee shall inspect the operational condition and integrity of all hooding, ductwork, and bypass dampers comprising the capture system. Hooding and ductwork observations shall include visual inspections to verify that the damper setting is in the correct position (i.e., to oxidizer or to atmosphere) and visual inspections of the actuator and motor to verify that the actuator pin and the motor are operating properly. The permittee shall document the results of all monthly inspections, including any corrective actions taken.
8. The permittee shall collect and record the following information each day for this coating line (K048):
 - a. The name and identification number of each coating, as applied;
 - b. The volume in gallons of each coating, as applied;
 - c. The VOC content of each coating, as applied, in pounds per gallon; and
 - d. The total VOC emissions from all coatings employed [summation of (b x c) for all coatings multiplied by the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the source was in compliance].
9. The permittee shall collect and record the following information each month for all coating lines at the facility:

Issued: To be entered upon final issuance

- a. The name and identification number of each coating, as applied;
- b. The volume in gallons of each coating, as applied;
- c. The HAP content of each coating, as applied, in pounds per gallon;
- d. The total HAP emissions for all emissions units of each single HAP [summation of (b x c) for all coatings multiplied by the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the source was in compliance]; and
- e. The total combined HAP emissions for all emissions units [summation of (d) for all HAPs emitted by the coating lines plus the monthly HAP emissions from the vapor degreaser (L001)].

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and was not vented to the catalytic oxidizer.
2. The permittee shall submit quarterly summaries of the following records:
 - a. a log of operating time for the capture (collection) system, control device, monitoring equipment, and the associated emissions unit;
 - b. all 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed (as determined by the continuous temperature monitor) did not comply with the temperature limitation specified above; and
 - c. all 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed (as determined by the continuous temperature monitor) was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance.

NOTE: Information submitted pursuant to section A.IV.2.c is not relevant for determining compliance with any operational restriction contained in section A.II. As long as the permittee performs the monitoring, record keeping, and reporting specified in sections A.III.2.b and A.IV.2.c of these terms and conditions, an average temperature difference across the catalyst bed

Emissions Unit ID: K048

of less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance shall not constitute a violation of any operational restriction or be considered a deviation.

3. The permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and the daily average air flow rate in the inlet stack to the catalytic oxidizer was more than 25% less than 1700 feet per minute (fpm), the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation. In the event that future emission tests are conducted, the permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and the daily average air flow rate in the inlet stack to the catalytic oxidizer was more than 25% less than the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation.
4. The permittee shall submit deviation (excursion) reports which identify each day where the daily VOC emission rate exceeded 1.03 pounds per day for this emissions unit (K048). The notification shall include a copy of such record and shall be sent to the Ohio EPA Northeast District Office within 30 days after the exceedance occurs.
5. The permittee shall submit deviation (excursion) reports which identify each month during which the rolling, 12-month emissions of any single HAP from all emissions units at the facility exceeded 9.9 tons per year, and the actual rolling, 12-month emissions of each such single HAP for each such month.
6. The permittee shall submit deviation (excursion) reports which identify each month during which the rolling, 12-month emissions of combined HAPs from all emissions units at the facility exceeded 24.9 tons per year, and the actual rolling, 12-month emissions of combined HAPs for each such month.
7. The permittee shall submit annual reports which specify the actual annual VOC emissions for the emissions unit (K048) and emissions units K039, K040, K041, K042, K043, K044, K045, K046, K047, and K049; combined. The reports shall be submitted by January 31 of each year and cover the previous calendar year.
8. The permittee shall submit annual reports which summarize the facility-wide emissions of each single HAP and combined HAPs from all emissions units at the facility. The reports shall include the emission calculations, be submitted by January 31 of each year, and cover the previous calendar year.
9. The permittee shall submit annual reports which summarize the results of the annual inspections conducted on the catalytic oxidizer by the manufacturer's representative. The reports shall describe any maintenance conducted on the catalytic oxidizer as a direct result of the inspections by manufacturer's representative. The reports shall be submitted by January 31 of each year and cover the previous calendar year.

Issued

Emissions Unit ID: K048

10. The permittee shall submit reports that include the results of the catalyst activity tests required in section A.V. These reports shall be submitted within 45 days after each catalyst activity test is performed.

V. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1 of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation:

VOC emissions shall not exceed 1.03 pounds per day.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 8 of these terms and conditions.

- b. Emission Limitation:

VOC emissions shall not exceed 10.04 tons per year.

Applicable Compliance Method:

Compliance with the annual emission limitation is shown as long as compliance with the daily emission limitations for this emissions unit (K048) and emissions units K039, K040, K041, K042, K043, K044, K045, K046, K047, and K049, are maintained (the annual emission limitation was calculated by multiplying the sum of the daily emission limitations for this emissions unit (K048) and emissions units K039, K040, K041, K042, K043, K044, K045, K046, K047, and K049, by 365 and dividing by 2000).

- c. Emission Limitation:

81 percent overall reduction of VOCs by weight and 90 percent destruction for all solvent based coatings.

Applicable Compliance Method:

If required by the Ohio EPA Northeast District Office, compliance shall be demonstrated in accordance with 40 CFR Part 60, Appendix A, Methods 25, 25A, and 40 CFR Part 51, Appendix M, Method 204. Performance testing shall be in accordance with OAC rule 3745-21-10(C).

- d. Emission Limitation:

The emissions of each single hazardous air pollutant (HAP) from all emissions units at the

Issued: To be entered upon final issuance

facility shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 9 of these terms and conditions.

e. Emission Limitation:

The emissions of the combined HAPs from all emissions units at the facility shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 9 of these terms and conditions.

2. Emission testing demonstrating compliance with the overall control efficiency limitation for VOC of 81 percent, the destruction efficiency limitation for VOC of 90 percent, and capture efficiency was conducted on January 8, 2004, as required by PTI 02-17168 issued 04/03/03.
3. US EPA Method 24 shall be used to determine the VOC contents of all the coatings employed in this emissions unit.
4. The permittee shall conduct, or have conducted, catalyst activity testing using the catalyst sample collected during the annual inspection described in section A.III. An intent to test notification shall not be required for the testing noted in this term. The procedures for the catalyst activity test shall be in accordance with the manufacturer's recommendations.

VI. Miscellaneous Requirements

None

Forest

PTI A

Emissions Unit ID: K048

Issued: To be entered upon final issuance

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K048 - Nut coater 4 (hand) equipped with a catalytic oxidizer Terms in this permit supercede those identified in PTI 02-17168 issued 04/03/03.	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit (K048) was evaluated based on the actual materials (coatings) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant potentially emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: toluene

TLV (ug/m3): 188,400

Maximum Hourly Emission Rate (lbs/hr): 3.31

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 250.5

MAGLC (ug/m3): 4476

Physical changes to or changes in the method of operation of the emissions unit after its installation could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

148

Forest

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: K048

IV. Reporting Requirements

None

149

Forest

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: K048

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Forest
PTI A

Emissions Unit ID: K049

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
K049 - Nut coater 5 equipped with a catalytic oxidizer	OAC rule 3745-31-05(A)(3)	OAC rule 3745-21-09(B)(3)(n)
Terms in this permit supercede those in PTI 02-17168 issued 04/03/03.	OAC rule 3745-21-09(B)(6)	OAC rule 3745-35-07
	OAC rule 3745-21-09(U)	
	OAC rule 3745-21-09(B)(3)(l)	
	OAC rule 3745-21-09(B)(3)(m)	

Applicable Emissions
Limitations/Control
Measures

The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09(B)(6).

VOC emissions shall not exceed **1.77** pounds per day.

VOC emissions shall not exceed 10.04 tons per year. See A.I.2.a below.

90 percent overall reduction of VOCs by weight.

The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

In lieu of complying with the requirements of this rule, the permittee has opted to comply with the requirements of OAC rule 3745-21-09(B).

See A.III.2.a, A.III.2.b, and A.III.2.c below.

See A.IV.2.a, A.IV.2.b, and A.IV.2.c below.

See A.III.1, A.V.1.c, and A.V.2 below.

See A.I.2.b and A.I.2.c below.

2. Additional Terms and Conditions

Issued: To be entered upon final issuance

- 2.a** The emission limitation of 10.04 tons VOC per year is based on the combined annual emissions from this emissions unit (K049) and emissions units K039, K040, K041, K042, K043, K044, K045, K046, K047, and K048.
- 2.b** The emissions of each single hazardous air pollutant (HAP) from all emissions units at the facility shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation. The permittee shall use existing records to determine compliance with the rolling 12-month restrictions upon issuance of this permit. Therefore, it is not necessary to establish federally enforceable restrictions for the first 12 months of operation under the provisions of this permit.
- 2.c** The emissions of the combined HAPs from all emissions units at the facility shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation. The permittee shall use existing records to determine compliance with the rolling 12-month restrictions upon issuance of this permit. Therefore, it is not necessary to establish federally enforceable restrictions for the first 12 months of operation under the provisions of this permit.

II. Operational Restrictions

1. Exhaust gases from operation of the emissions unit shall be vented to the catalytic oxidizer.
2. The average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below 652 degrees Fahrenheit, the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance. In the event that future emission tests are conducted, the average temperature of the exhaust gases immediately before the catalyst bed, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
3. The catalytic oxidizer shall be operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manuals. The VOC conversion efficiency of the catalyst in the catalytic oxidizer, as determined by the catalyst activity testing, shall be at least 90% at a test temperature that is representative of the normal temperature at the catalyst bed inlet. Solvent loading during catalyst analysis shall be consistent with the test laboratory's normal testing protocol.
4. All ventilation fans associated with this emissions unit and the catalytic oxidizer shall be in operation at all times when this emissions unit is in operation.

5. When employing the catalytic oxidizer, all bypass dampers, actuator pins, and associated motors shall be in the correct position and in good operating condition at all times when this emissions unit is in operation to ensure that all captured VOC emissions are vented to the catalytic oxidizer. Also, all the hooding and ductwork comprising the VOC emission capture system for this emissions unit shall be free of leaks and holes that would permit the escape of the captured VOC emissions.
6. The average, total exhaust flow rate from this emissions unit to the catalytic oxidizer shall be within 25% of 1700 feet per minute (fpm), the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation. In the event that future emission tests are conducted, the average, total exhaust flow rate from this emissions unit to the catalytic oxidizer shall be within 25% of the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain continuous monitors and recorder(s) which measure and record the temperature immediately upstream and downstream of the incinerator's catalyst bed when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitors and recorder(s) shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.
2. The permittee shall collect and record the following information each day:
 - a. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
 - b. All 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance. The permittee may use the oxidizer's temperature chart to determine the temperature differential across the catalyst bed.
 - c. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation. The permittee may use the current temperature chart as the log documenting that the monitoring equipment and control device are operating. Each bypass of the collection system and/or control device shall be logged as to the date and time.
3. The permittee shall perform an inspection of the catalytic oxidizer, including the catalyst bed, at

Issued: To be entered upon final issuance

least once each calendar year. Each inspection shall consist of internal and visual inspections in accordance with the manufacturer's recommendations and shall include a physical inspection of the unit and checks of associated equipment, including but not limited to burners, controls, dampers, valves, and monitoring and recording equipment. Repair and replacement of equipment shall be performed as determined by the inspection. In accordance with the testing schedule in section A.V, a sample of catalyst material shall be collected from the catalyst bed to perform the catalyst activity tests required in section A.V.

4. The permittee shall maintain a record of the results of each annual inspection of the catalytic oxidizer, as well as the results of each catalyst activity test required in section A.V.
5. The permittee shall operate and maintain a flow meter at the inlet to the catalytic oxidizer to ensure that the exhaust from the coating room and the emissions units in the coating room are being directed to the catalytic oxidizer. The permittee shall collect and record the flow rate at the inlet to the catalytic oxidizer on a daily basis.
6. Each calendar month, the permittee shall inspect the operational condition and integrity of each ventilation fan comprising the capture system. Ventilation fan observations shall include visual inspections of the fan wheel, belts, and bearings. Lubrication of bearings and replacement of parts shall occur as necessary. The permittee shall document the results of all monthly inspections, including any corrective actions taken.
7. Each calendar month, the permittee shall inspect the operational condition and integrity of all hooding, ductwork, and bypass dampers comprising the capture system. Hooding and ductwork observations shall include visual inspections to verify that the damper setting is in the correct position (i.e., to oxidizer or to atmosphere) and visual inspections of the actuator and motor to verify that the actuator pin and the motor are operating properly. The permittee shall document the results of all monthly inspections, including any corrective actions taken.
8. The permittee shall collect and record the following information each day for this coating line (K049):
 - a. The name and identification number of each coating, as applied;
 - b. The volume in gallons of each coating, as applied;
 - c. The VOC content of each coating, as applied, in pounds per gallon; and
 - d. The total VOC emissions from all coatings employed [summation of (b x c) for all coatings multiplied by the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the source was in

compliance].

9. The permittee shall collect and record the following information each month for all coating lines at the facility:
 - a. The name and identification number of each coating, as applied;
 - b. The volume in gallons of each coating, as applied;
 - c. The HAP content of each coating, as applied, in pounds per gallon;
 - d. The total HAP emissions for all emissions units of each single HAP [summation of (b x c) for all coatings multiplied by the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the source was in compliance]; and
 - e. The total combined HAP emissions for all emissions units [summation of (d) for all HAPs emitted by the coating lines plus the monthly HAP emissions from the vapor degreaser (L001)].

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and was not vented to the catalytic oxidizer.
2. The permittee shall submit quarterly summaries of the following records:
 - a. a log of operating time for the capture (collection) system, control device, monitoring equipment, and the associated emissions unit;
 - b. all 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature of the exhaust gases immediately before the catalyst bed (as determined by the continuous temperature monitor) did not comply with the temperature limitation specified above; and
 - c. all 3-hour blocks of time (when the emissions unit was in operation) during which the average temperature difference across the catalyst bed (as determined by the continuous temperature monitor) was less than 80 percent of the average temperature difference during the most recent emission test that demonstrated the emissions unit was in compliance.

NOTE: Information submitted pursuant to section A.IV.2.c is not relevant for determining compliance with any operational restriction contained in section A.II. As long as the permittee performs the monitoring, record keeping, and reporting specified in sections A.III.2.b and A.IV.2.c of these terms and conditions, an average temperature difference across the catalyst bed of less than 80 percent of the average temperature difference during the most recent emission test

Issued: To be entered upon final issuance

that demonstrated the emissions unit was in compliance shall not constitute a violation of any operational restriction or be considered a deviation.

3. The permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and the daily average air flow rate in the inlet stack to the catalytic oxidizer was more than 25% less than 1700 feet per minute (fpm), the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation. In the event that future emission tests are conducted, the permittee shall submit deviation (excursion) reports that identify all periods of time when the emissions unit was in operation and the daily average air flow rate in the inlet stack to the catalytic oxidizer was more than 25% less than the mean average stack gas velocity during the most recent compliance test that demonstrated the emissions unit was in compliance with the applicable capture efficiency limitation.
4. The permittee shall submit deviation (excursion) reports which identify each day where the daily VOC emission rate exceeded 1.77 pounds per day for this emissions unit (K049). The notification shall include a copy of such record and shall be sent to the Ohio EPA Northeast District Office within 30 days after the exceedance occurs.
5. The permittee shall submit deviation (excursion) reports which identify each month during which the rolling, 12-month emissions of any single HAP from all emissions units at the facility exceeded 9.9 tons per year, and the actual rolling, 12-month emissions of each such single HAP for each such month.
6. The permittee shall submit deviation (excursion) reports which identify each month during which the rolling, 12-month emissions of combined HAPs from all emissions units at the facility exceeded 24.9 tons per year, and the actual rolling, 12-month emissions of combined HAPs for each such month.
7. The permittee shall submit annual reports which specify the actual annual VOC emissions for the emissions unit (K049) and emissions units K039, K040, K041, K042, K043, K044, K045, K046, K047, and K048; combined. The reports shall be submitted by January 31 of each year and cover the previous calendar year.
8. The permittee shall submit annual reports which summarize the facility-wide emissions of each single HAP and combined HAPs from all emissions units at the facility. The reports shall include the emission calculations, be submitted by January 31 of each year, and cover the previous calendar year.
9. The permittee shall submit annual reports which summarize the results of the annual inspections conducted on the catalytic oxidizer by the manufacturer's representative. The reports shall

Issued

Emissions Unit ID: K049

describe any maintenance conducted on the catalytic oxidizer as a direct result of the inspections by manufacturer's representative. The reports shall be submitted by January 31 of each year and cover the previous calendar year.

10. The permittee shall submit reports that include the results of the catalyst activity tests required in section A.V. These reports shall be submitted within 45 days after each catalyst activity test is performed.

V. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1 of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation:

VOC emissions shall not exceed 1.77 pounds per day.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 8 of these terms and conditions.

- b. Emission Limitation:

VOC emissions shall not exceed 10.04 tons per year.

Applicable Compliance Method:

Compliance with the annual emission limitation is shown as long as compliance with the daily emission limitations for this emissions unit (K049) and emissions units K039, K040, K041, K042, K043, K044, K045, K046, K047, and K048, are maintained (the annual emission limitation was calculated by multiplying the sum of the daily emission limitations for this emissions unit (K049) and emissions units K039, K040, K041, K042, K043, K044, K045, K046, K047, and K048, by 365 and dividing by 2000).

- c. Emission Limitation:

90 percent overall reduction of VOCs by weight.

Applicable Compliance Method:

If required by the Ohio EPA Northeast District Office, compliance shall be demonstrated in accordance with 40 CFR Part 60, Appendix A, Methods 25, 25A, and 40 CFR Part 51, Appendix M, Method 204. Performance testing shall be in accordance with OAC rule 3745-21-10(C).

d. Emission Limitation:

The emissions of each single hazardous air pollutant (HAP) from all emissions units at the facility shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 9 of these terms and conditions.

e. Emission Limitation:

The emissions of the combined HAPs from all emissions units at the facility shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation.

Applicable Compliance Method:

Compliance shall be based upon the record keeping specified in Section A.III. 9 of these terms and conditions.

2. Emission testing demonstrating compliance with the overall control efficiency limitation for VOC of 81 percent, the destruction efficiency limitation for VOC of 90 percent, and capture efficiency was conducted on January 8, 2004, as required by PTI 02-17168 issued 04/03/03. Emission testing conducted on January 8, 2004, also demonstrated that the permittee was in compliance with the emission limitation of 90 percent overall reduction of VOCs by weight for this emissions unit (K049).
3. S EPA Method 24 shall be used to determine the VOC contents of all the coatings employed in this emissions unit.
4. The permittee shall conduct, or have conducted, catalyst activity testing using the catalyst sample collected during the annual inspection described in section A.III. An intent to test notification shall not be required for the testing noted in this term. The procedures for the catalyst activity test shall be in accordance with the manufacturer's recommendations.

VI. Miscellaneous Requirements

None

**Forest
PTI A**

Emissions Unit ID: K049

Issued: To be entered upon final issuance

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K049 - Nut coater 5 equipped with a catalytic oxidizer Terms in this permit supercede those in PTI 02-17168 issued 04/03/03.	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit (K049) was evaluated based on the actual materials (coatings) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant potentially emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Issued: To be entered upon final issuance

Pollutant: toluene

TLV (ug/m3): 188,400

Maximum Hourly Emission Rate (lbs/hr): 3.31

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 250.5

MAGLC (ug/m3): 4476

Physical changes to or changes in the method of operation of the emissions unit after its installation could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still

satisfies the "Air Toxic Policy"; and

- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

162

Forest

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: K049

V. Testing Requirements

None

VI. Miscellaneous Requirements

None