



State of Ohio Environmental Protection Agency

Street Address:

Lazarus Gov. Center
50 West Town Street, Suite 700
Columbus, OH 43215

TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049
Columbus, OH 43216-1049

RE: FINAL PERMIT TO INSTALL

BUTLER COUNTY

Application No: 14-06011

Fac ID: 1409011026

DATE: 2/8/2008

Midwest Service
Donald Brown
PO Box 44-919 605 Clark Street
Middletown, OH 45042

CERTIFIED MAIL

	TOXIC REVIEW
	PSD
	SYNTHETIC MINOR
	CEMS
	MACT
	NSPS
	NESHAPS
	NETTING
	MAJOR NON-ATTAINMENT
	MODELING SUBMITTED
	GASOLINE DISPENSING FACILITY

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action of the Director is final and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. The appeal must be filed with the Commission within thirty (30) days after notice of the Director's action. The appeal must be accompanied by a filing fee of \$70.00 which the Commission, in its discretion, may reduce if by affidavit you demonstrate that payment of the full amount of the fee would cause extreme hardship. Notice of the filing of the appeal shall be filed with the Director within three (3) days of filing with the Commission. Ohio EPA requests that a copy of the appeal be served upon the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, OH 43215

Sincerely,

Michael W. Ahern 

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: USEPA

HCDES



Permit To Install
Terms and Conditions

Issue Date: 2/8/2008
Effective Date: 2/8/2008

FINAL PERMIT TO INSTALL 14-06011

Application Number: 14-06011
Facility ID: 1409011026
Permit Fee: **\$900**
Name of Facility: Midwest Service
Person to Contact: Donald Brown
Address: PO Box 44-919 605 Clark Street
Middletown, OH 45042

Location of proposed air contaminant source(s) [emissions unit(s)]:
**605 Clark Street
Middletown, Ohio**

Description of proposed emissions unit(s):
Application of rubber to steel rollers and associated processes.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Chris Korleski
Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted (i.e., postmarked) quarterly by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air

contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental

Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
VOC	7.34
PE	0.88

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment -(K001) - Paint spray booth

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-21-09(U)(2)(e)(ii)	See term and condition A.2.a below.
OAC rule 3745-31-05(A)(3)(b)	See term and condition A.2.b below.
OAC rule 3745-31-05(c)	See term and condition A.2.c below.

2. Additional Terms and Conditions

- 2.a The permittee shall not use more than 3 gallons of coating material per day for the coating of miscellaneous metal parts.
- 2.b The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the volatile organic compounds (VOC) from this air contaminant source since the calculated annual emission rates for volatile organic compound are less than ten tons per year taking into account the federally enforceable rule limitation of 3 gallons of coating material per day as derived from OAC rule 3745-21-09(U)(2)(e)(ii).
- 2.c Permit to Install 14-06011 for this air contaminant source takes into account the following voluntary restrictions as proposed by the permittee for the purpose of avoiding Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) for VOC emissions:
 - i. the maximum annual cleanup solvent use shall not exceed 55 gallons per year; and
 - ii. the maximum VOC content of solvent used for cleanup shall not exceed 7.2 pounds of VOC per gallon of solvent.

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each day for this emissions unit:
 - a. the name and identification number of each coating employed;
 - b. the number of gallons of each coating employed; and
 - c. the total number of gallons of all the coatings employed.

2. The permittee shall collect and record the following information each month for this emissions unit:
 - a. the name and identification number of each coating employed;
 - b. the number of gallons of each coating employed; and
 - c. the total number of gallons of all the coatings employed.
 - d. the name, identification number and VOC content of each cleanup solvent employed;
 - e. the number of gallons of each cleanup solvent employed; and
 - f. the total number of gallons of all the cleanup solvents employed.

3. The permittee shall collect and record the following information annually on a calendar basis for this emissions unit:
 - a. the total number of gallons of all the cleanup solvents employed.

D. Reporting Requirements

1. The permittee shall notify the Hamilton County Department of Environmental Services in writing of any daily record showing that this emissions unit employed more than the applicable maximum usage limit of 3 gallons of coating material per day. The notification shall include a copy of such record and shall be sent to the Hamilton County Department of Environmental Services within 45 days after the exceedance occurs.

2. The permittee shall notify the Hamilton County Department of Environmental Services in writing of any monthly record showing that a cleaning solvent exceeding 7.2 pounds of VOC per gallon of solvent was employed in this emissions unit. The notification shall include a copy of such record and shall be sent to the Hamilton County Department of Environmental Services within 45 days following the month in which the exceedance occurs.
3. The permittee shall notify the Hamilton County Department of Environmental Services in writing of any annual record showing that more than 55 gallons of cleaning solvents were employed in this emissions unit in a calendar year. The notification shall include a copy of such record and shall be sent to the Hamilton County Department of Environmental Services within 45 days following the end of the calendar year in which the exceedance occurs.

E. Testing Requirements

1. Compliance with the usage limitations in Section A of these terms and conditions shall be determined in accordance with the following methods:

Usage limitation:

3 gallons per day total coating usage

Applicable compliance method:

Compliance shall be based upon the record keeping specified in term and condition C.1.

Usage limitation:

55 gallons per year total cleaning solvent usage

Applicable compliance method:

Compliance shall be based upon the record keeping specified in term and condition C.3.

2. Compliance with the VOC content limitation in Section A of these terms and conditions shall be determined in accordance with the following methods:

USEPA methods 24 and 24A shall be used to determine the VOC content for cleanup materials. If pursuant to 40 CFR Part 60, Appendix A, the permittee determines that Method 24 or 24A cannot be used for a particular cleanup material, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating or cleanup material to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

F. Miscellaneous Requirements

1. Modeling to demonstrate compliance with the Ohio EPA's "Air Toxic Policy" was not necessary because the emissions unit's maximum annual emissions for each toxic compound will be less than 1.0 ton. OAC Chapter 3745-31 requires permittees to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that changes in the composition of the materials, or use of new materials, that would cause the emissions of any pollutant that has a listed TLV to increase to above 1.0 ton per year may require the permittee to apply for and obtain a new permit to install.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment -(P001) - Shot blast booth

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(A)(3)(b)	See term and condition A.2.a.
OAC rule 3745-17-07(A)(1)	Visible particulate emissions from any stack shall not exceed 20 percent opacity, as a six-minute average.
OAC rule 3745-17-11(B)	Particulate emissions (PE) shall not exceed 4.0 lb/hour.
OAC rule 3745-17-07(B)(1)	Fugitive visible particulate emissions from any stack shall not exceed 20 percent opacity, as a three-minute average.
OAC rule 3745-17-08(B)(3)	The fabric filter serving this emissions unit shall achieve an outlet emission rate of not greater than 0.030 grain of particulate emissions per dry standard cubic foot of exhaust gases or there shall be no visible particulate emissions from the outlet.

2. Additional Terms and Conditions

- The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the particulate emissions (PE) and particulate matter emissions 10 microns and less in diameter (PM10) from this air contaminant source since the calculated annual emission rates for PE and PM10 are less than ten tons per year taking into account the federally enforceable rule limitation of OAC rule 3745-17-08(B)(3).

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

- The permittee shall properly install, operate, and maintain equipment to continuously monitor and record the pressure drop, in inches of water, across the baghouse during

operation of this emissions unit, including periods of startup and shutdown. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a daily basis.

Whenever the monitored value for the pressure drop deviates from the range specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation: the date and time the deviation began and the magnitude of the deviation at that time, the date(s) the investigation was conducted, the names of the personnel who conducted the investigation, and the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable range specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken: a description of the corrective action, the date it was completed, the date and time the deviation ended, the total period of time (in minutes) during which there was a deviation, the pressure drop reading immediately after the corrective action, and the names of the personnel who performed the work. Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

The acceptable range for the pressure drop across the baghouse shall be based upon the manufacturer's specifications until such time as any required emission testing is conducted. This range is 3 inches of water to 10 inches of water effective for the duration of this permit, unless revisions are requested by the permittee and approved in writing by the appropriate Ohio EPA District Office or local air agency.

The permittee may request revisions to the pressure drop range based upon information obtained during future particulate emission tests that demonstrate compliance with the allowable particulate emission rate for this emissions unit. In addition, approved revisions to the pressure drop range will not constitute a relaxation of the monitoring requirements of this permit and may be incorporated into this permit by means of an administrative modification.

2. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack and for any visible emissions of fugitive dust from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:

- a. the location and color of the emissions;
- b. whether the emissions are representative of normal operations;
- c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;
- d. the total duration of any visible emission incident; and
- e. any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item (d) above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

The permittee may, upon receipt of written approval from Hamilton County Department of Environmental Services, modify the above-mentioned frequencies for performing the visible emissions checks if operating experience indicates that less frequent visible emissions checks would be sufficient to ensure compliance with the above-mentioned applicable requirements.

D. Reporting Requirements

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the stack serving this emissions unit, (b) identify all days during which any visible emissions of fugitive dust were observed from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit, and (c) describe any corrective actions taken to minimize or eliminate the visible particulate emissions and/or visible fugitive dust emissions. These reports shall be submitted to the Hamilton County Department of Environmental Services by January 31 and July 31 of each year and shall cover the previous six-month periods.

E. Testing Requirements

1. Compliance with the emissions limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emissions Limitation:
Visible particulate emissions from any stack shall not exceed 20 percent opacity, as a six-minute average.

Applicable Compliance Method:

Compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002.

- b. Emissions Limitation:
PE shall not exceed 4.0 lb/hour.

Applicable Compliance Method:

If required, compliance shall be determined in accordance with Test Methods 1 - 5 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60.

- c. Emissions Limitation:
The fabric filter serving this emissions unit shall achieve an outlet emission rate of not greater than 0.030 grain of particulate emissions per dry standard cubic foot of exhaust gases or there shall be no visible particulate emissions from the outlet.

Applicable Compliance Method:

If required, the permittee shall demonstrate compliance by emission testing in accordance with the procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 5 and the procedures specified in OAC rule 3745-17-03(B)(10).

If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such appendix existed on July 1, 2002.

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment -(P002) - Roller bonding adhesive application

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
Adhesive application OAC rule 3745-21-09(U)(2)(e)(ii)	See term and condition A.2.a below.
OAC rule 3745-31-05(A)(3)(b)	See term and condition A.2.b below.
OAC rule 3745-31-05(c)	See term and condition A.2.c below.
Vulcanizing OAC rule 3745-31-05(A)(3)(b)	See term and condition A.2.d below.

2. Additional Terms and Conditions

- 2.a The permittee shall not use more than 3 gallons of coating (adhesive) material per day for the coating of miscellaneous metal parts.
- 2.b The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the volatile organic compounds (VOC) from adhesive application from this air contaminant source since the calculated annual emission rates for volatile organic compound are less than ten tons per year taking into account the federally enforceable rule limitation of 3 gallons of coating material per day as derived from OAC rule 3745-21-09(U)(2)(e)(ii).
- 2.c Permit to Install 14-06011 for this air contaminant source takes into account the following voluntary restrictions as proposed by the permittee for the purpose of avoiding Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) for VOC emissions:

- i. the maximum annual cleanup solvent use in this emissions unit shall not exceed 85 gallons per year; and
- ii. the maximum VOC content of solvent used for cleanup in this emissions unit shall not exceed 7.2 pounds of VOC per gallon of solvent.

2.d The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the volatile organic compounds (VOC) from vulcanizing in this air contaminant source since the uncontrolled potential to emit for this pollutant is less than ten tons per year.

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each day for this emissions unit:
 1. The permittee shall collect and record the following information each day for this emissions unit:
 - a. the name and identification number of each coating employed;
 - b. the number of gallons of each coating employed; and
 - c. the total number of gallons of all the coatings employed.
2. The permittee shall collect and record the following information each month for this emissions unit:
 - a. the name and identification number of each coating employed;
 - b. the number of gallons of each coating employed; and
 - c. the total number of gallons of all the coatings employed.
 - d. the name, identification number and VOC content of each cleanup solvent employed;
 - e. the number of gallons of each cleanup solvent employed; and
 - f. the total number of gallons of all the cleanup solvents employed.

3. The permittee shall collect and record the following information annually on a calendar basis for this emissions unit:
 - a. the total number of gallons of all the cleanup solvents employed.

D. Reporting Requirements

1. The permittee shall notify the Hamilton County Department of Environmental Services in writing of any daily record showing that the coating line employed more than the applicable maximum usage limit of 3 gallons of coating material per day. The notification shall include a copy of such record and shall be sent to the Hamilton County Department of Environmental Services within 45 days after the exceedance occurs.

E. Testing Requirements

1. Compliance with the usage limitation in Section A of these terms and conditions shall be determined in accordance with the following methods:

Usage limitation:

3 gallons per day total coating usage

Applicable compliance method:

Compliance shall be based upon the record keeping specified in Term and condition C.1.

F. Miscellaneous Requirements

1. Modeling to demonstrate compliance with the Ohio EPA's "Air Toxic Policy" was not necessary because the emissions unit's maximum annual emissions for each toxic compound will be less than 1.0 ton. OAC Chapter 3745-31 requires permittees to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that changes in the composition of the materials, or use of new materials, that would cause the emissions of any pollutant that has a listed TLV to increase to above 1.0 ton per year may require the permittee to apply for and obtain a new permit to install.