



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL CERTIFIED MAIL
MAHONING COUNTY**

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049

Application No: 02-15376

DATE: 10/4/2001

Buckeye Wrecking & Recycling Inc
Butch Olmstead
1800 19th Street NE
Alliance, OH 44601

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
236 East Town Street, Room 300
Columbus, Ohio 43215

Very truly yours,

Thomas G. Rigo, Manager
Field Operations and Permit Section
Division of Air Pollution Control

cc: USEPA

NEDO



**Permit To Install
Terms and
Conditions**

**Issue Date: 10/4/2001
Effective Date: 10/4/2001**

FINAL PERMIT TO INSTALL 02-15376

Application Number: 02-15376
APS Premise Number: 0250000999
Permit Fee: **\$6000**
Name of Facility: Buckeye Wrecking & Recycling Inc
Person to Contact: Butch Olmstead
Address: 1800 19th Street NE
Alliance, OH 44601

Location of proposed air contaminant source(s) [emissions unit(s)]:
**Harrisburg-Westville Rd
Smith Twp, Ohio**

Description of proposed emissions unit(s):
Roadways, storage piles, crushing and screening of recycled concrete and non-toxic foundry sand.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized

representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio

Buckeye Wrecking & Recycling Inc
PTI Application: 02-15376
Issued: 10/4/2001

Facility ID: 0250000999

Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit to Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within thirty (30) days after commencing operation of the emissions unit(s) covered by this permit.

Buckeye Wrecking & Recycling Inc
PTI Application: 02-15376
Issued: 10/4/2001

Facility ID: 0250000999

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
PE	35.04 TPY

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
load-in and load-out of storage piles (see section A.2.a for identification of storage piles)	OAC rule 3745-31-05 (A)(3)	PE: 4.08 tons per year
	OAC rule 3745-17-07	no visible emissions except for one minute in any hour
	OAC rule 3745-17-08	best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see Sections A.2.b, A.2.c and A.2.f)
	OAC rule 3745-31-05 (A)(3)	less stringent than limit from OAC rule 3745-31-05 (A)(3)
wind erosion from storage piles (see Section A.2.a for identification of storage piles)	OAC rule 3745-17-07 (B)	less stringent than limit from OAC rule 3745-31-05 (A)(3)
	OAC rule 3745-17-08 (B)	no visible emissions except for one minute in any hour
		best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see Sections A.2.d through A.2.f)
		less stringent than limit from OAC rule 3745-31-05 (A)(3)
		less stringent than limit from OAC

rule 3745-31-05 (A)(3)

2. Additional Terms and Conditions

- 2.a** The storage piles that are covered by this permit and subject to the requirements of OAC rule 3745-31-05 are listed below:
- All material storage piles
- 2.b** The permittee shall employ best available control measures on all load-in and load-out operations associated with the storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to **with water and/or any other suitable dust suppression chemicals** to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.
- 2.c** The above-mentioned control measure(s) shall be employed for each load-in and load-out operation of each storage pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) are necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measure(s) shall continue during any such operation until further observation confirms that use of the measure(s) is unnecessary.
- 2.d** The permittee shall employ best available control measures for wind erosion from the surfaces of all storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to **treat each storage pile with water and/or any other suitable dust suppression chemicals via the spray tower at sufficient treatment frequencies** to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.
- 2.e** The above-mentioned control measure(s) shall be employed for wind erosion from each pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) are necessary to ensure compliance with the above-mentioned applicable requirements. Implementation of the control measure(s) shall not be necessary for a storage pile that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements.

2.f Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the requirements of OAC rule 3745-31-05 (A)(3).

B. Operational Restrictions

1. The permittee shall not operate this emissions unit more than 10 hours per day and 3650 hours per year.
2. The permittee shall process no more than 10 ton per hour of any combination of brick, asphalt and/or concrete through this emissions unit.
3. The permittee shall process no more than 70 ton per hour of foundry sand through this emissions unit.

C. Monitoring and/or Recordkeeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform inspections of each load-in operation at each storage pile in accordance with the following frequencies:

<u>storage pile identification</u>	<u>minimum load-in inspection frequency</u>
All material storage piles	Daily

2. Except as otherwise provided in this section, the permittee shall perform inspections of each load-out operation at each storage pile in accordance with the following frequencies:

<u>storage pile identification</u>	<u>minimum load-out inspection frequency</u>
All material storage piles	Daily

3. Except as otherwise provided in this section, the permittee shall perform inspections of the wind erosion from pile surfaces associated with each storage pile in accordance with the following frequencies:

<u>storage pile identification</u>	<u>minimum wind erosion inspection frequency</u>
All material storage piles	Daily

4. No inspection shall be necessary for wind erosion from the surface of a storage pile when the pile is covered with snow and/or ice and for any storage pile activity if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above identified events shall be

performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.

5. The purpose of the inspections is to determine the need for implementing the control measures specified in this permit for load-in and load-out of a storage pile, and wind erosion from the surface of a storage pile. The inspections shall be performed during representative, normal storage pile operating conditions.
6. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.
7. The permittee shall maintain records of the following information:
 - a. the date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;
 - b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;
 - c. the dates the control measures were implemented; and
 - d. on a calendar quarter basis, the total number of days the control measures were implemented and, for wind erosion from pile surfaces, the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measure(s).

The information required in 7.d. shall be kept separately for (i) the load-in operations, (ii) the load-out operations, and (iii) the pile surfaces (wind erosion), and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

8. The permittee shall maintain records of the following information:
 - a. the daily and annual hours of operation of this emissions unit;
 - b. the hourly total combination of brick, asphalt, and/or concrete processed through this emissions unit (ton/hr); and
 - c. the hourly total of foundry sand processed through this emissions unit(ton/hr).

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify any of the following occurrences:
 - a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation;
 - b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented;
 - c. identify any exceedances of the hourly material processing rate limitations; and
 - d. identify any exceedances of the daily and/or annual operating hours limitation.
2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the emission limitations specified in section A.1. of these terms and conditions shall be determined in accordance with the following methods:
 - a. Compliance with the visible emission limitations for the storage piles identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996.
 - b. Emission Limitation:
PE: 4.08 tons per year wind erosion and load-in and load-out operations.

Applicable Compliance Method:

Compliance with the above annual particulate emission limitation shall be determined by the following equations:

from AP-42, Chapter 13.2.4 (Aggregate Handling and Storage Piles), Fifth Edition, dated 1/1995, for load -in and load-out operations,

$$EI = k \times 0.0032 \times [(U/5)^{1.3} / (M/2)^{1.4}] \times P \times H / 2,000$$

Buckeye Wrecking & Recycling Inc

PTI Application: 02-15276

Issued**Facility ID: 0250000999**Emissions Unit ID: **F001**

where:

El = annual particulate emission rate (TPY);

k = particle size multiplier (dimensionless), 0.74 for PE and 0.35 for PM-10;

U = mean wind speed, 10.0 mph;

M = material moisture content, 7.4%;

P = maximum hourly process rate, in tons/hr, 80 tons/hr; and

H = annual hours of operation.

and from USEPA's Control of Open Fugitive Dust Sources September 1988 for wind erosion from storage piles:

$$E_w = 1.7 \times (s/1.5) \times [(365-p)/235] \times (f/15) \times 365 \times A / 2,000$$

where:

Ew = total annual particulate emission rate;

s = silt content of the stored material, weight percent, 2.6 %;

p = number of days with > 0.01 inches of precipitation per year, 150 days;

f = percentage of time wind speed exceeds 12 mph, 30 %; and

A = total surface area of storage piles, 2.0.

For total particulate emissions:

$$E = [\text{sum of particulate emissions from each load-in/load-out operation (El)}] + [\text{total annual particulate emissions from wind erosion (Ew)}]$$

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Crushing, screening and material handling operations	OAC rule 3745-31-05(A)(3)	PE: 1.66 pounds/hour and 3.06 ton per year Visible particulate emissions of fugitive dust shall not exceed 10 % opacity, as a six-minute average. best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see Sections A.2.b
	OAC rule 3745-17-07(B)	less stringent than limit from OAC rule 3745-31-05 (A)(3)
	OAC rule 3745-17-08(B)	less stringent than limit from OAC rule 3745-31-05 (A)(3)
	40 CFR, Part 60, Subpart OOO	less stringent than limit from OAC rule 3745-31-05 (A)(3)

2. Additional Terms and Conditions

- 2.a The water sprays shall be operating at all times while the crusher is in operation. Also,

14

Bucke

PTI A

Issued: 10/4/2001

Emissions Unit ID: **F002**

water sprays shall be operated at all other points necessary to ensure compliance with the visible emission limitation specified above.

B. Operational Restrictions

1. The permittee shall not operate this emissions unit more than 10 hours per day and 3650 hours per year.
2. The permittee shall process no more than 10 ton per hour of any combination of brick, asphalt, and/or concrete through this emissions unit.
3. The permittee shall process no more than 70 ton per hour of foundry sand through this emissions unit.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall conduct visible emission evaluations in accordance with USEPA's Reference Method 9 of 40 CFR, Part 60, Appendix A at a minimum daily or upon relocation of the emissions unit. The visible emission evaluations shall be performed during the period of April 15 through October 15. The duration of the Method 9 observations shall be 3 hours (30 six-minute averages). However, the duration of the Method 9 observations can be reduced to 1 hour (10 six-minute averages) if the following conditions apply: (1) there are no individual readings greater than 10 % opacity and (2) there are no more than 3 readings of 10 % opacity for the one-hour period.
2. The permittee shall maintain records of the following information:
 - a. the daily and annual hours of operation of this emissions unit;
 - b. the hourly total combination of brick, asphalt, and/or concrete processed through this emissions unit; and
 - c. the hourly total of foundry sand processed through this emissions unit.

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify any of the following occurrences:
 - a. identify any time periods during which water sprays were not used;

16

Bucke

PTI A

Issued: 10/4/2001

Emissions Unit ID: **F002**

- c. identify any exceedances of the daily and/or annual operating hours limitation.
2. The permittee shall notify the Northeast District Office of Ohio EPA ("NEDO") of any Method 9 evaluation that did not demonstrate compliance with the opacity limitation specified above. The notification shall be in writing and shall include a copy of such record and shall be sent to NEDO within 30 days after the exceedance occurs.

E. Testing Requirements

1. This permittee shall conduct, or have conducted, visible emission tests at a minimum annually or upon relocation of this emissions unit in order to demonstrate compliance with the specified allowable visible emission limitation. The visible emission tests shall be conducted in accordance with USEPA's Reference Method 9 of 40 CFR, Part 60, Appendix A.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an Intent to Test notification to NEDO. The Intent to Test notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test, and the person(s) who will be conducting the test. Failure to submit such notification for review and approval prior to the test may result in NEDO's refusal to accept the results of the visible emissions test.

Personnel from NEDO shall be permitted to witness the test. The permittee shall acquire data and information regarding the emissions unit operating parameters (including, but not limited to, water flow rates of control system used to control fugitive dust at the facility).

A comprehensive written report on the results of the visible emission test (including opacity readings and the emissions unit operating parameters) shall be signed by the person(s) responsible for the test and submitted to NEDO within 30 days following the completion of the test.

2. Compliance with the emission limitations specified in section A.1. of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emission Limitation:
Visible particulate emissions of fugitive dust shall not exceed 10 % opacity, as a six-minute average.

Applicable Compliance Method:
Compliance with the above visible emission limitation shall be determined by USEPA's Reference Method 9 in 40 CFR, Part 60, Appendix A.
 - b. Emission Limitation:
PE: 1.66 pounds per hour

Applicable Compliance Method:
Compliance with the above hourly particulate emission limitation shall be determined using the emission factors for crushing, screening, and material handling operations in AP-42, Chapter 11.19.2 (Crushed Stone Processing), Fifth Edition, dated 1/1995 and for truck

Emissions Unit ID: **F002**

dumping operations in AP-42, Chapter 13.2.4 (Aggregate Handling and Storage Piles), Fifth Edition, dated 1/1995.

- c. Emission Limitation:
PE: 3.06 tons per year

Applicable Compliance Method:

Compliance with the above annual particulate emission limitation shall be determined by multiplying the hourly allowable emission rate (1.66 lbs/hr) by 3,650 hours and dividing by 2,000 lbs/ton.

F. Miscellaneous Requirements

1. Notice to Relocate a Portable or Mobile Emissions Unit

Pursuant to OAC rule 3745-31-03(A)(1)(p)(i), the permittee of a portable or mobile emissions unit

may relocate within the State of Ohio without first obtaining a PTI providing the following criteria are met:

- a. the portable emissions unit is equipped with the best available control technology for such portable emissions unit;
- b. the portable emissions unit is operating pursuant to a currently effective permit to operate (PTO);
- c. the applicant has provided proper notice of intent to relocate the portable emissions unit to NEDO and the appropriate Ohio EPA District Office or local air agency having jurisdiction over the new site within a minimum of thirty days prior to the scheduled relocation; and
- d. in NEDO's and the appropriate Ohio EPA District Office's or local air agency's judgement, the proposed site is acceptable under OAC rule 3745-15-07.

2. In the alternative, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), the permittee of a portable or mobile emissions unit may relocate within the State of Ohio without first obtaining a PTI providing the following criteria of OAC rule 3745-31-05(F) are met:

- a. the permittee of the portable emissions unit possesses an effective Ohio EPA PTI, PTO or registration status;

- b. the portable emissions unit is equipped with best available technology;
 - c. the portable emission unit owner has identified the proposed site to Ohio EPA;
 - d. Ohio EPA has determined that the portable emissions unit, at the proposed site, will have an acceptable environmental impact;
 - e. a public notice, consistent with OAC Chapter 3745-47, is published in the county where the proposed site is located;
 - f. the owner of the proposed site has provided the portable emissions unit owner with approval or equivalent declaration that it is acceptable to the site owner to move the portable emissions unit to this proposed site; and
 - g. the portable emissions unit owner has provided Ohio EPA with fifteen days written notice of the relocation.
3. Any site approvals issued by Ohio EPA, pursuant to F.2. above, shall be valid for no longer than three years and are subject to renewal.

In order for NEDO and the appropriate Ohio EPA District Office or local air agency having jurisdiction over the new site to determine compliance with all of the above criteria, the owner or operator of the portable or mobile emissions unit must file a "Notice of Intent to Relocate", within the specified time frame (30 or 15 days) prior to the relocation of the emissions unit with NEDO and the appropriate Ohio EPA District Office or local air agency having jurisdiction over the new site. Upon receipt of the notice, NEDO and/or the appropriate Ohio EPA District Office or local air agency having jurisdiction over the new site, will evaluate the request in accordance with the above criteria.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Unpaved roadways and parking areas	OAC rule 3745-31-05 (A)(3)	PE: 27.9 tons per year no visible particulate emissions except for 3 minutes during any 60-minute period best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see Sections A.2.b through A.2.g)
	OAC rule 3745-17-07 (B)	less stringent than limit from OAC rule 3745-31-05 (A)(3)
	OAC rule 3745-17-08 (B)	less stringent than limit from OAC rule 3745-31-05 (A)(3)

2. Additional Terms and Conditions

- 2.a The unpaved roadways and parking areas that are covered by this permit and subject to the above-mentioned requirements are listed below:

unpaved roadways:

All unpaved roadways

unpaved parking areas:

All unpaved parking areas

- 2.b** The permittee shall employ best available control measures on all unpaved roadways and parking areas for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to treat the unpaved roadways and parking areas with water and/or any other suitable dust suppression chemicals at sufficient treatment frequencies to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.
- 2.c** The needed frequencies of implementation of the control measures shall be determined by the permittee's inspections pursuant to the monitoring section of this permit. Implementation of the control measures shall not be necessary for an unpaved roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Implementation of any control measure may be suspended if unsafe or hazardous driving conditions would be created by its use.
- 2.d** Any unpaved roadway or parking area, which during the term of this permit is paved or takes the characteristics of a paved surface due to the application of certain types of dust suppressants, may be controlled using appropriate dust control measures for paved surfaces. Any unpaved roadway or parking area that takes the characteristics of a paved roadway or parking area due to the application of certain types of dust suppressants shall remain subject to the visible emission limitation for unpaved roadways and parking areas. Any unpaved roadway or parking area that is paved shall be subject to a visible emission limitation of no visible particulate emissions except for one minute during any 60-minute period.
- 2.e** The permittee shall promptly remove, in such a manner as to minimize or prevent resuspension, earth and/or other material from paved streets onto which such material has been deposited by trucking or earth moving equipment or erosion by water or other means.

- 2.f** Open-bodied vehicles transporting materials likely to become airborne shall have such materials covered at all times if the control measure is necessary for the materials being transported.
- 2.g** Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the best available technology requirements of OAC rule 3745-31-05 (A)(3).

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform inspections of the unpaved roadways and parking areas in accordance with the following frequencies:

<u>unpaved roadways</u>	<u>minimum inspection frequency</u>
All unpaved roadways	Daily
<u>unpaved parking areas</u>	<u>minimum inspection frequency</u>
All unpaved parking areas	Daily

2. The purpose of the inspections is to determine the need for implementing the above-mentioned control measures. The inspections shall be performed during representative, normal traffic conditions. No inspection shall be necessary for a roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above-identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.
3. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.
4. The permittee shall maintain records of the following information:
- the date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;
 - the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;
 - the dates the control measures were implemented; and

- d. on a calendar quarter basis, the total number of days the control measures were implemented and the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measures.

The information required in 4.d. shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:
 - a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and
 - b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.
2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the emission limitations specified in section A.1. of these terms and conditions shall be determined by the following methods:
 - a. Compliance with the emission limitation for the unpaved roadways and parking areas identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources,") as such Appendix existed on July 1, 1996.
 - b. Emission Limitation:
PE: 27.9 tons per year

Applicable Compliance Method:
Compliance with the above annual particulate emission limitation shall be determined by the following equation from AP-42, Chapter 13.2.2 (Unpaved Roads), Fifth Edition, dated 9/1998:

$$E = k \times (S/15) \times (s/12)^{0.8} \times (W/3)^{0.5} \times [(365-p)/365] / (M/2)^{0.4} \times \text{VMT} \times (1/2,000) \times (1-CE)$$

where:

E = annual particulate emission rate;

k = constant, 10;

S = mean vehicular speed, 15 mph;

s = silt content, 10.0 %;

W = mean vehicular weight, 25 tons (loaders) and 35 ton(trucks);

p = number of days with at least 0.1 inches of precipitation per year, 150;

M = moisture content of road material, 0.2;

VMT = 7680 vehicular miles traveled per year (3000 for 2 front-end loaders and 4680 for trucks); and

CE = fractional control efficiency.

F. Miscellaneous Requirements

None