

Facility ID: 0285000422 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

- [Go to Part II for Emissions Unit P001](#)
- [Go to Part II for Emissions Unit P002](#)
- [Go to Part II for Emissions Unit P003](#)
- [Go to Part II for Emissions Unit R001](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0285000422 Emissions Unit ID: P001 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
142 Hp Deutz diesel-fired reciprocating engine	OAC rule 3745-31-05(A)(3) (PTI 02-20672)	0.31 lb/hr and 1.36 TPY of particulate matter (PM)/PM less than 10 microns in diameter (PM10)
		0.29 lb/hr and 1.27 TPY of sulfur dioxide (SO2)
		4.40 lbs/hr and 19.27 TPY of nitrogen dioxides (NOx)
		0.95 lb/hr and 4.16 TPY of carbon monoxide (CO)
		0.36 lb/hr and 1.58 TPY of volatile organic compounds (VOC)
		Visible particulate emissions from the stack serving this emissions unit shall not exceed 10% opacity, as a six-minute average.
		The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-11(B)(5)(a).
	OAC rule 3745-17-11(B)(5)(a)	0.310 lb/mmBtu of particulate emissions
	OAC rule 3745-17-07(A)(1)	The opacity limitation specified in this rule is less stringent than the limit established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-18-06(G)	See section A.2.c.
	OAC rule 3745-21-07(B)	See section A.2.d.

2. **Additional Terms and Conditions**
 - (a) In accordance with OAC rule 3745-31-05(A)(3), best available technology for this emissions unit includes the emissions limitations and fuel sulfur content restriction. The hourly and annual emission limitations outlined above are based upon the emissions unit's potential to emit. Therefore, no records are required to be maintained to demonstrate compliance with these limitations. This emissions unit is exempt from the requirements of OAC rule 3745-18-06 pursuant to OAC rule 3745-18-06(B). The permittee has satisfied the "latest available control techniques and operating practices" required pursuant to OAC rule 3745-21-07(B) by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05(A)(3) in this permit to install.

B. Operational Restrictions

1. The permittee shall use only diesel fuel/number 2 fuel oil with a maximum sulfur content of 0.5 percent by weight

for combustion in this emissions unit.

C. Monitoring and/or Record Keeping Requirements

1. For each day during which the permittee burns a fuel other than diesel fuel, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit. The permittee shall also maintain documentation of the sulfur content of all fuels received.

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify each day during which a fuel other than diesel fuel with a maximum sulfur content of 0.5 percent by weight was burned in this emissions unit. Each report shall be submitted within 30 days of the deviation.

E. Testing Requirements

1. Compliance with the emission limitations specified in section A.1. of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:
0.31 lb/hr and 1.36 TPY of PM/PM10

0.29 lb/hr and 1.27 TPY of SO2

4.40 lbs/hr and 19.27 TPY of NOx

0.95 lb/hr and 4.16 TPY of CO

0.36 lb/hr and 1.58 TPY of VOC

Applicable Compliance Methods:

Compliance with the hourly emission limitations above shall be determined using the emission factors specified in AP-42 "Compilation of Air Pollutant Emission Factors," Table 3.3-1 (10/96) and the power output rating of this unit (142 Hp).

The annual emission limitations specified above were created by multiplying the hourly emission limitations by 8,760 hours/year and dividing by 2,000 lbs/ton; therefore, as long as compliance with the hourly emission limitations is maintained, compliance with the annual emission limitations will be assumed.

Emission Limitation:

Visible particulate emissions from the stack serving this emissions unit shall not exceed 10% opacity, as a six-minute average.

Applicable Compliance Method:

If required, compliance with the opacity limitation shall be determined using Method 9 of 40 CFR, Part 60, Appendix A.

Emission Limitation:

0.310 lb/mmBtu of particulate emissions

Applicable Compliance Method:

Compliance with the emission limitation above shall be determined using the appropriate emission factor specified in AP-42 "Compilation of Air Pollutant Emission Factors," Table 3.3-1 (10/96).

F. Miscellaneous Requirements

1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0285000422 Emissions Unit ID: P002 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

(a) None.

2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

(a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	--------------------------------------	--

81 Hp Deutz diesel-fired reciprocating engine	OAC rule 3745-31-05(A)(3) (PTI 02-20672)	0.18 lb/hr and 0.79 TPY of particulate matter (PM)/PM less than 10 microns in diameter (PM10) 0.17 lb/hr and 0.74 TPY of sulfur dioxide (SO2) 2.51 lbs/hr and 10.99 TPY of nitrogen dioxides (NOx) 0.54 lb/hr and 2.37 TPY of carbon monoxide (CO) 0.20 lb/hr and 0.88 TPY of volatile organic compounds (VOC) Visible particulate emissions from the stack serving this emissions unit shall not exceed 10% opacity, as a six-minute average. The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-11(B)5 (a).
	OAC rule 3745-17-11(B)(5)(a) OAC rule 3745-17-07(A)(1)	0.310 lb/mmBtu of particulate emissions The opacity limitation specified in this rule is less stringent than the limit established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-18-06(G)	See section A.2.c.
	OAC rule 3745-21-07(B)	See section A.2.d.

2. Additional Terms and Conditions

- (a) In accordance with OAC rule 3745-31-05(A)(3), best available technology for this emissions unit includes the emissions limitations and fuel sulfur content restriction. The hourly and annual emission limitations outlined above are based upon the emissions unit's potential to emit. Therefore, no records are required to be maintained to demonstrate compliance with these limitations. This emissions unit is exempt from the requirements of OAC rule 3745-18-06 pursuant to OAC rule 3745-18-06(B). The permittee has satisfied the "latest available control techniques and operating practices" required pursuant to OAC rule 3745-21-07(B) by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05(A)(3) in this permit to install.

B. Operational Restrictions

- 1. The permittee shall use only diesel fuel/number 2 fuel oil with a maximum sulfur content of 0.5 percent by weight for combustion in this emissions unit.

C. Monitoring and/or Record Keeping Requirements

- 1. For each day during which the permittee burns a fuel other than diesel fuel, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit. The permittee shall also maintain documentation of the sulfur content of all fuels received.

D. Reporting Requirements

- 1. The permittee shall submit deviation (excursion) reports that identify each day during which a fuel other than diesel fuel with a maximum sulfur content of 0.5 percent by weight was burned in this emissions unit. Each report shall be submitted within 30 days of the deviation.

E. Testing Requirements

- 1. Compliance with the emission limitations specified in section A.1. of these terms and conditions shall be determined in accordance with the following methods:
Emission Limitations:
0.18 lb/hr and 0.79 TPY of PM/PM10

0.17 lb/hr and 0.74 TPY of SO2

2.51 lbs/hr and 10.99 TPY of NOx

0.54 lb/hr and 2.37 TPY of CO

0.20 lb/hr and 0.88 TPY of VOC

Applicable Compliance Methods:
Compliance with the hourly emission limitations above shall be determined using the emission factors specified in AP-42 "Compilation of Air Pollutant Emission Factors," Table 3.3-1 (10/96) and the power output rating of this unit (81 Hp).

The annual emission limitations specified above were created by multiplying the hourly emission limitations by 8,760 hours/year and dividing by 2,000 lbs/ton; therefore, as long as compliance with the hourly emission limitations is maintained, compliance with the annual emission limitations will be assumed.
Emission Limitation:
Visible particulate emissions from the stack serving this emissions unit shall not exceed 10% opacity, as a six-minute average.

Applicable Compliance Method:
If required, compliance with the opacity limitation shall be determined using Method 9 of 40 CFR, Part 60, Appendix A.

Emission Limitation:
0.310 lb/mmBtu of particulate emissions

Applicable Compliance Method:
Compliance with the emission limitation above shall be determined using the appropriate emission factor specified in AP-42 "Compilation of Air Pollutant Emission Factors," Table 3.3-1 (10/96).

F. Miscellaneous Requirements

- 1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0285000422 Emissions Unit ID: P003 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

- 1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
- 2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
woodworking shop, controlled by a 7,500 cfm cyclone and return-air baghouse system, and associated loadout	OAC rule 3745-31-05(A)(3) (PTI 02-20672)	See A.2.a, A.2.b, A.2.c, B.2 and B.3 below.
	OAC rule 3745-17-07(B)	In accordance with paragraph (B)(11)(e) of OAC rule 3745-17-07, the requirements of OAC rule 3745-17-07 (B) shall not apply to this emissions unit.
	OAC rule 3745-17-08(B)	In accordance with paragraph (A)(1) of OAC rule 3745-17-08, the requirements of OAC rule 3745-17-08 (B) shall not apply to this emissions unit.
	OAC rule 3745-17-11	The emission limitation established in this rule is less stringent than the one established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-07(A)	The emission limitation specified in this rule is less stringent than the one established pursuant to OAC rule 3745-31-05(A)(3).

- 2. **Additional Terms and Conditions**
 - (a) Particulate emissions shall not exceed 0.01 grain per dscf of exhaust gas, 0.64 pound per hour and 2.80 tons per year from the dust collector system exhaust. There shall be no visible emissions from the dust collector system exhaust. Visible emissions shall not exceed 20% opacity, as a 3-minute average from fugitive particulate emissions during loadout.

B. Operational Restrictions

- 1. The pressure drop across the dust collector system shall be maintained within the manufacturer's recommended range while the emissions unit is in operation, or within the pressure drop range established during the most recent compliance inspection or stack test that determined the emissions unit was in compliance.
- 2. The dust collector system shall be operated with a sufficient volumetric flow rate to eliminate visible particulate emissions at the point(s) of capture to the extent possible with good engineering design.
- 3. During any unloading of sawdust into trucks from the cyclone dust collector hopper, every attempt shall be made to reduce or control fugitive dust emissions by minimizing the drop height to the truck, utilizing a truck with high side boards, or placing a covering over the discharge chute during the unloading process. The collection efficiency shall be considered adequate if there are no visible particulate emissions of fugitive dust from the fabric tube during wood waste load-out in excess of 20% opacity, as a 3-minute average.

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall properly operate and maintain equipment to monitor the pressure drop across the dust collector system while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the dust collector system on a weekly basis.
 2. The permittee shall perform weekly checks during times that dust collected by the cyclone is being unloaded, for any visible fugitive dust emissions from the unloading area. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. Whether the emissions are representative of normal operations;
 - b. If the emissions are not representative of normal operations, the cause of the abnormal visible emissions;
 - c. The total duration of any abnormal visible emission incident; and
 - d. Any corrective actions taken to eliminate the abnormal visible emissions.
- D. Reporting Requirements**
1. The permittee shall submit quarterly deviation (excursion) reports that identify all periods of time during which the pressure drop across the dust collector system did not comply with the allowable range specified above.

The quarterly deviations reports shall be submitted in accordance with the General Terms and Conditions. These reports shall be submitted by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.
 2. The permittee shall submit semiannual written reports that (a) identify all days during which any abnormal visible particulate emissions were observed from the area where cyclone dust is unloaded and (b) describe any corrective actions taken to eliminate the abnormal visible particulate emissions. These reports shall be submitted to the Northeast District Office of Ohio EPA by January 31 and July 31 of each year and shall cover the previous six-month period.
- E. Testing Requirements**
1. Compliance with the emission limitations in sections A.1 and A.2 of these terms and conditions shall be determined in accordance with the following methods:
Emission Limitation:
Particulate emissions shall not exceed 0.01 grain per dscf of exhaust gas, 0.64 pound per hour and 2.80 tons per year from the dust collector system exhaust.

Applicable Compliance Methods:
If required, compliance with the grain loading and hourly limits shall be determined according to OAC rule 3745-17-03(B)(10), (Method 5, 40 CFR, Part 60, Appendix A).

The annual limit was created by multiplying the hourly limit by 8,760 hrs/yr and dividing by 2,000 lbs/ton. Therefore, as long as compliance with the hourly limit is demonstrated, compliance with the annual limit is assumed.
Emission Limitation:
There shall be no visible emissions from the dust collector system exhaust.

Applicable Compliance Methods:
Compliance with the no visible emission limit for the exhaust from the dust collector system shall be determined using visible emission observations in accordance with Method 22 of 40 CFR, Part 60, Appendix A.
Emission Limitation:
Visible emissions shall not exceed 20% opacity, as a 3-minute average from fugitive particulate emissions during loadout.

Applicable Compliance Method:
If required, compliance with the visible fugitive emission limitation shall be determined by OAC rule 3745-17-03 (B)(3), in accordance with Method 9, as set forth in 40 CFR Part 60, Appendix A.
- F. Miscellaneous Requirements**
1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0285000422 Emissions Unit ID: R001 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

(a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
sealer/topcoat coating booth w/ HVLP spray gun and fabric filters	OAC rule 3745-31-05(A)(3) (PTI 02-20672)	Emissions of volatile organic compounds (VOC) shall not exceed 17.13 lbs/hr and 75.03 TPY from coatings employed in this booth. VOC emissions from cleanup materials shall not exceed 0.46 TPY.
	OAC rule 3745-21-07(G)(2)	See section A.2.a. See section A.2.b.

2. Additional Terms and Conditions

(a) The VOC content of each coating employed shall not exceed 5.71 pounds per gallon, as applied. The permittee shall not employ any liquid organic material in this emissions unit that is a photochemically reactive material, as defined in OAC rule 3745-21-01(C)(5).

B. Operational Restrictions

1. All exhaust from the spray booth shall pass through the dry filters whenever this emissions unit is in operation.

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall keep the following records for all organic materials used in this emissions unit:
 - a. An identification of each chemical compound in each organic material and its physical state; and
 - b. For any liquid organic material, whether or not the material is a photochemically reactive material, as defined in OAC rule 3745-21-01(C)(5).
2. The permittee shall collect and record the following information each day:
 - a. The name and identification number of each coating employed;
 - b. The number of gallons of each coating employed;
 - c. The VOC content of each coating employed, as applied;
 - d. The number of hours of operation for this emissions unit; and
 - e. The average hourly VOC emissions rate [summation of (b x c) / d for each coating].
3. The permittee shall collect and record the following each month for the cleanup material employed:
 - a. The name and identification number of each cleanup material employed;
 - b. The VOC content of each cleanup material, in lbs/gallon as applied;
 - c. The number of gallons of cleanup material employed;
 - d. The number of gallons of cleanup material waste recovered for disposal; and
 - e. The total VOC emissions from all cleanup materials employed using an average 95% solvent content for cleanup material waste, in lbs/month [summation of (b x c) - (b x d x 0.95) for each cleanup material].
4. The permit to install for this emissions unit, R001, was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Compound: isobutyl alcohol
 TLV (mg/m3): 154.153
 Maximum Hourly Emission Rate (lbs/hr): 2.28
 Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 278.69
 MAGLC (ug/m3): 3,608.92

5. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
 - a. Changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
 - b. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. Physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification
6. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
 - a. A description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. Documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
 - c. Where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that include the following information:
 - a. An identification of each day during which any photochemically reactive material was employed;
 - b. An identification of each day during which the VOC content of any coating exceeded 5.71 pounds per gallon, as applied in this emissions unit and the actual VOC content of each such coating employed;
 - c. An identification of each day during which more than 17.13 lbs/hr of VOC was emitted as an average for the day, and the actual average hourly VOC emission rate for each such day; and
 - d. An identification of each month during which the annual VOC emission limitation for cleanup material (0.46 TPY) was exceeded, and the actual annual VOC emission rate for the annual period.

The quarterly deviations reports shall be submitted in accordance with the General Terms and Conditions. These reports shall be submitted by January 31, April

E. Testing Requirements

1. Compliance with the emission limitations specified in section A.1. of these terms and conditions shall be determined in accordance with the following methods:
Emission Limitation:
17.13 lbs/hr of VOC and 75.03 TPY

Applicable Compliance Method:
Compliance with the hourly VOC emission limitation shall be determined by the record keeping requirements specified in section C.2. of these terms and conditions.

The annual limit was created by multiplying the hourly limit by 8,760 hrs/yr and dividing by 2,000 lbs/ton. Therefore, as long as compliance with the hourly limit is demonstrated, compliance with the annual limit is assumed.
Emission Limitation:
VOC emissions from cleanup materials shall not exceed 0.46 TPY.

Applicable Compliance Method:
Compliance with the annual VOC emission limitation shall be determined by the record keeping requirements specified in section C.3. of these terms and conditions.
Emission Limitation:
The VOC content of each coating shall not exceed 5.71 pounds per gallon, as applied.

Applicable Compliance Method:
Compliance with the VOC content restriction shall be determined by the record keeping requirements specified in section C.2. of these terms and conditions.

F. Miscellaneous Requirements

1. None