

Synthetic Minor Determination and/or Netting Determination

Permit To Install 03-13933

A. Source Description

This permit encompasses the equipment used for a drum-mix asphalt plant of 310 tons per hour maximum rated capacity.

B. Facility Emissions and Attainment Status

This facility has requested a synthetic minor because potential emissions of carbon monoxide exceed 250 TPY, potential emissions of sulfur dioxide, and nitrogen oxide exceed 100 TPY. Federally enforceable restrictions will lower potential emissions of the above mentioned pollutants to less than 100 TPY. These restrictions will keep the company from the requirements of PSD review and Title V.

C. Source Emissions

Shelly Materials has requested federally enforceable restrictions of varying monthly production limits and 400,000 production tons for the annual restriction. This limit will result in permit allowable emissions of 24.20 TPY SO₂, 90.00 TPY CO, 24.20 TPY NO_x, and 60.20 TPY VOC.

D. Conclusion

This facility has a restricted permit allowable emission limitations That will keep permit allowable emissions below the trigger levels for PSD review or Title V.



State of Ohio Environmental Protection Agency

Street Address:

Mailing Address:

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Lazarus Gov. Center

**RE: DRAFT PERMIT TO INSTALL
ALLEN COUNTY**

CERTIFIED MAIL

Application No: 03-13933

DATE: 2/27/2003

Shelly Materials
Larry Shively
8775 Blackbird Lane PO Box 266
Thornville, OH 43076

You are hereby notified that the Ohio Environmental Protection Agency has made a draft action recommending that the Director issue a Permit to Install for the air contaminant source(s) [emissions unit(s)] shown on the enclosed draft permit. This draft action is not an authorization to begin construction or modification of your emissions unit(s). The purpose of this draft is to solicit public comments on the proposed installation. A public notice concerning the draft permit will appear in the Ohio EPA Weekly Review and the newspaper in the county where the facility will be located. Public comments will be accepted by the field office within 30 days of the date of publication in the newspaper. Any comments you have on the draft permit should be directed to the appropriate field office within the comment period. A copy of your comments should also be mailed to Robert Hodanbosi, Division of Air Pollution Control, Ohio EPA, P.O. Box 1049, Columbus, OH, 43266-0149.

A Permit to Install may be issued in proposed or final form based on the draft action, any written public comments received within 30 days of the public notice, or record of a public meeting if one is held. You will be notified in writing of a scheduled public meeting. Upon issuance of a final Permit to Install a fee of **\$650** will be due. Please do not submit any payment now.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469. If you have any questions about this draft permit, please contact the field office where you submitted your application, or Mike Ahern, Field Operations & Permit Section at (614) 644-3631.

Very truly yours,

Michael W. Ahern, Supervisor
Field Operations and Permit Section
Division of Air Pollution Control

CC: USEPA

NWDO

Lima-Allen Regional Planning Commission

IN

ALLEN COUNTY

PUBLIC NOTICE

ISSUANCE OF DRAFT PERMIT TO INSTALL 03-13933 FOR AN AIR CONTAMINANT SOURCE FOR SHELLY MATERIALS

On 2/27/2003 the Director of the Ohio Environmental Protection Agency issued a draft action of a Permit To Install an air contaminant source for **Shelly Materials**, located at **600 North Sugar Street, Lima, Ohio**.

Installation of the air contaminant source identified below may proceed upon final issuance of Permit To Install 03-13933:

310 drum mix asphalt plant and aggregate storage piles. Modification to PTI 03-13548 issued on 12/27/01. Modification due to increase annual production, increased VOC emissions.

Comments concerning this draft action, or a request for a public meeting, must be sent in writing to the address identified below no later than thirty (30) days from the date this notice is published. All inquiries concerning this draft action may be directed to the contact identified below.

Don Waltermeyer, Ohio EPA, Northwest District Office, 347 North Dunbridge Road, Bowling Green, OH 43402 [(419)352-8461]



Permit To Install
Terms and Conditions

Issue Date: To be entered upon final issuance
Effective Date: To be entered upon final issuance

DRAFT PERMIT TO INSTALL 03-13933

Application Number: 03-13933
APS Premise Number: 0302020006
Permit Fee: **To be entered upon final issuance**
Name of Facility: Shelly Materials
Person to Contact: Larry Shively
Address: 8775 Blackbird Lane PO Box 266
Thornville, OH 43076

Location of proposed air contaminant source(s) [emissions unit(s)]:

**600 North Sugar Street
Lima, Ohio**

Description of proposed emissions unit(s):

**310 drum mix asphalt plant and aggregate storage piles. Modification to PTI 03-13548 issued on 12/27/01.
Modification due to increase annual production, increased VOC emissions.**

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any

Issued: To be entered upon final issuance

information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions

Shelly Materials

Facility ID: 0302020006

PTI Application: 03-13933

Issued: To be entered upon final issuance

and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

- a. If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete

Issued: To be entered upon final issuance

Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).

- b. If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35, the source(s) identified in this Permit To Install is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the source(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
PM	10.60
SO2	24.20
CO	90.00
NOx	24.20
VOC	60.20

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>
F002 - Aggregate storage piles. Modification to PTI 03-13548 issued on 12/27/01. Modification due to increase annual production.	OAC rule 3745-31-05(A)(3)
load-in and load-out of storage piles (see Section A.2.a. for identification of storage piles)	OAC rule 3745-31-05 (A) (3)
wind erosion from storage piles (see Section A.2.a. for identification of storage piles)	OAC rule 3745-31-03 (A) (3)
load-in and load-out of storage	OAC rule 3745-17-07 (B)

Shelly

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: F002

OAC rule 3745-17-08 (B)

Applicable Emissions
Limitations/Control Measures

2.00 TPY fugitive PE

No visible emissions except for a period of time not to exceed one minute during any 60-minute observation period.

Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see A.2.b., A.2.c., & A.2.f.)

No visible emissions except for a period of time not to exceed one minute during any 60-minute observation period.

Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see A.2.d. through A.2.f.)

See A.2.g.

See A.2.g.

2. Additional Terms and Conditions

Issued: To be entered upon final issuance

- 2.a** The storage piles that are covered by this permit and subject to the above-mentioned requirements are listed below:
- i. Material products storage pile
 - ii. RAP storage pile
 - iii. Concrete storage pile
 - iv. Sand storage pile
 - v. Gravel storage pile
- 2.b** The permittee shall employ best available control measures on all load-in and load-out operations associated with the storage piles for purposes of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to treat the load-in and load-out materials with water and/or any other suitable dust suppression chemicals to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.
- 2.c** The above-mentioned control measure(s) shall be employed for each load-in and load-out operation of each storage pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) are necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measure(s) shall continue during any such operation until further observation confirms that use of the measure(s) is unnecessary.
- 2.d** The permittee shall employ best available control measures for wind erosion from the surfaces of all storage piles for the propose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to treat each storage pile with water and/or any other suitable dust suppression chemicals at sufficient treatment frequencies to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.
- 2.e** The above-mentioned control measure(s) shall be employed for wind erosion from each pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) are necessary to ensure compliance with the above-mentioned applicable requirements. Implementation of the control measure(s) shall not be necessary for a storage pile that is covered with snow and/or ice if the precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements.

2.f Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the requirements of OAC rule 3745-31-05.

2.g The storage piles are associated with the portable asphalt plant P901 permitted under facility ID 0302020006 P901. The emission limitation of 2.05 TPY fugitive PE represents the maximum emissions which will be emitted from the storage piles for any proposed site for relocation of the portable asphalt plant.

The storage piles are associated with a portable source and are applicable to the requirements of OAC rule 3745-17-07 (B) and 3745-17-08 (B) when located in an "Appendix A" area as identified in OAC rule 3745-17-08. The emission limitations and control requirements established by OAC rule 3745-17-07 (B) and OAC rule 3745-17-08 (B) are less stringent than the requirements established pursuant to OAC rule 3745-31-05 (A) (3).

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform inspections of each load-in operation at each storage pile in accordance with the following frequencies:

<u>storage pile identification</u>	<u>minimum load-in inspection frequency</u>
All	Once during each day of operation

2. Except as otherwise provided in this section, the permittee shall perform inspections of the wind erosion from pile surfaces associated with each storage pile in accordance with the following frequencies:

<u>storage pile identification</u>	<u>minimum load-out inspection frequency</u>
All	Once during each day of operation

3. No inspection shall be necessary for wind erosion from the surface of a storage pile when the pile is covered with snow and/or ice and for any storage pile activity if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is

within one week.

4. The purpose of the inspections is to determine the need for implementing the control measures specified in this permit for load-in and load-out of a storage pile and wind erosion from the surface of a storage pile. The inspections shall be performed during representative, normal storage pile operating conditions.
5. The permittee may upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.
6. The permittee shall maintain records of the following information:
 - a. The date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation.
 - b. The date of each inspection where it was determined by the permittee that it was necessary to implement the control measures.
 - c. The dates the control measures were implemented.
 - d. On a calendar quarter basis, the total number of days the control measures were implemented and, for wind erosion from pile surfaces, the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measure(s).

The information required in 6.d. shall be kept separately for (i) the load-in operations, (ii) the load-out operations, and (iii) the storage pile surfaces (wind erosion), and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit deviation reports, in accordance with the reporting requirements of the General Terms and Conditions of this permit, that identify any of the following occurrences:
 - a. Each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation.
 - b. Each instance when a control measure, that was to be implemented as a result of an

inspection, was not implemented.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1. of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation: 2.00 ton per year fugitive PE

Applicable Compliance Method: This emission limitation was developed by applying a 50% control efficiency for dust suppression to a maximum potential uncontrolled emission rate of 4.00 TPY PE. The maximum potential uncontrolled emission rate was calculated using an AP-42 emission factor Section 13.2.4. (1/95) of 0.0lbs PE/ton of material loaded in and loaded out and multiplied by 400,000 tons material throughput/yr. Compliance shall be demonstrated through the monitoring and recordkeeping requirements in Section C of this permit.

- b. Emission Limitation: No visible emissions except for a period of time not to exceed 1 minute during and 60-minute observation period.

Applicable Compliance Method: Compliance with the visible emission limitations for the storage piles identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

NONE

Shelly

PTI A

Emissions Unit ID: P901

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>
P901 - 310 drum mix asphalt plant and aggregate storage piles. Modification to PTI 03-13548 issued on 12/27/01. Modification due to increase annual production, increased PE, VOC, NOx, SO2, emissions, and reduction of plant capacity from 375 TPY to 310 TPY.	OAC rule 3745-31-05(A)(3)
	40 CFR Part 60, Subpart I
	OAC Rule 3745-17-11 (B)
	OAC Rule 3745-17-07 (B)
	OAC Rule 3745-17-08 (B)
	OAC Rule 3745-18-06(E)(2)
	OAC rule 3745-31-05 (D)

Shelly

PTI A

Emissions Unit ID: P901

Issued: To be entered upon final issuance

Applicable Emissions	(See A.2.e.)
<u>Limitations/Control Measures</u>	(See A.2.f.)
Stack Emissions:	
10.23 lbs/hr PE	(See A.2.f.)
37.51 lbs/hr SO ₂	
37.51 lbs/hr NO _x	(See A.2.e.)
139.50 lbs/hr CO	
93.31 lbs/hr VOC	
Visible emission restrictions (See A.2.d)	
See A.2.a	
See A.2.g.	
6.60 Tons/PE per rolling 12-month period (See A.2.b)	
2.00 Tons fugitive PE/ per rolling 12-month period (See A.2.b)	
24.20 Tons/SO ₂ per rolling 12-month period (See A.2.b)	
24.20 Tons/NO _x per rolling 12-month period (See A.2.b)	
90.00 Tons/CO per rolling 12-month period (See A.2.b)	
60.20 Tons/VOC per rolling 12-month period (See A.2.b)	
0.04 gr PE/dscf of exhaust gas.	
Emissions from the baghouse stack shall not exhibit 20% opacity, or greater.	

Issued: To be entered upon final issuance

2. Additional Terms and Conditions

2.a "Best Available Technology" (BAT) for this emissions unit has been determined to be the following:

- i. Use of baghouse for drum mix operations;
- ii. Use of Best Available Control Measures (See A.2.c)

2.b The permittee has requested the following federally enforceable emission limitations:

24.20 tons SO₂ per rolling 12-month period
90.00 tons CO per rolling 12-month period
24.20 tons NO_x per rolling 12-month period
60.20 tons VOC per rolling 12-month period
6.60 tons PE (stack) per rolling 12-month period
1.38 tons PE (fugitive) per rolling 12-month period

The federally enforceable emission limitations are based on production restrictions (See B.1.) and are being established for purposes of avoiding Prevention of Significant Deterioration (PSD) and Title V requirements.

2.c The permittee shall employ best available control measures to minimize or eliminate visible emissions of fugitive dust from emissions unit P901. If the inherent moisture in the asphalt plant raw material is not sufficient to comply with the opacity restrictions in section A.2.d., the permittee shall install equipment to apply water or any other suitable dust suppressant, at appropriate locations on the line.

Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

- 2.d Visible fugitive emissions from material handling operations for emissions unit P901 shall not exceed the following opacity restrictions:

Emission Point (company ID)	Equipment Type	Opacity Limit as a three-Minute Average	Regulatory Basis for Limit
Material unloading into feeder bins	Transfer point	20%	OAC Rule 3745-31-05
Material transfer from feeder bin conveyor to dryer feed conveyor	Transfer point	20%	OAC Rule 3745-31-05
Material transfer from dryer feed conveyor to dryer	Transfer point	20%	OAC Rule 3745-31-05

- 2.e The emission limitation specified on this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

- 2.f This emissions unit is a portable source and is applicable to the requirements of OAC rule 3745-17-07(B) and OAC rule 3745-17-08 (B) when located in an "Appendix A" area as identified in OAC rule 3745-17-08. The emission limitations and control requirements established by OAC rule 3745-17-07 (B) and OAC rule 3745-17-08 (B) are equivalent to or less stringent than the requirements established pursuant to OAC rule 3745-31-05 and NSPS Subpart I.

When the emissions unit is not located within an "Appendix A" area as identified in OAC rule 3745-17-08, this emission unit is exempt from the requirements of OAC rule 3745-17-08(B) pursuant to OAC rule 3745-17-08(A) and is exempt from the visible particulate emission limitations specified in OAC rule 3745-17-07 (B)(1) pursuant to OAC rule 3745-17-07(B)(11)(e).

- 2.g The requirements of this rule also include compliance with CFR 40 Part 60, Subpart I and OAC rule 3745-31-05(D).

Shelly

PTI A

Emissions Unit ID: P901

Issued: To be entered upon final issuance

B. Operational Restrictions

1. Annual asphalt production from emissions unit P901 shall not exceed 400,000 tons per year, based on a rolling, 12 month summation of the monthly production rates.

To ensure enforceability during the first 12 calendar months of operation under the provisions of this permit, the permittee shall not exceed the production levels specified in the following table:

<u>(TONS)</u>	<u>MONTH(s)</u>	<u>MAXIMUM ALLOWABLE CUMULATIVE ASPHALT PRODUCTION</u>
	1	50,000
	1-2	100,000
	1-3	125,000
	1-4	150,000
	1-5	200,000
	1-6	250,000
	1-7	300,000
	1-8	350,000
	1-9	400,000
	1-10	400,000
	1-11	400,000
	1-12	400,000

After the first 12 calendar months of operation under the provisions of this permit, compliance with the annual production limitation shall be based upon a rolling, 12 month summation of the monthly production rates.

2. The permittee may substitute recycled asphalt aggregates in the raw material feed mix in amounts not to exceed 50 percent of all aggregate materials introduced at any given time.
3. The permittee shall only employ materials/fuels listed in the permit to install application. Any changes in the materials employed/combusted may be deemed a "modification" to the emissions unit and, as such will require prior notification to and approval from the Ohio EPA, Division of Air Pollution Control, Northwest District Office.

Shelly

PTI A

Emissions Unit ID: **P901**

Issued: To be entered upon final issuance

4. The pressure drop across the baghouse shall be maintained within the range of 3 to 6 inches of water while the emissions unit is in operation

Issued: To be entered upon final issuance

5. All recycled, used oil burned in emissions unit P901 shall meet the following specifications:

Contaminant/Property Allowable Specifications

arsenic	5 ppm, maximum
cadmium	2 ppm, maximum
chromium	10 ppm, maximum
lead	100 ppm, maximum
PCB's	50 ppm, maximum*
total halogens	4000 ppm maximum**
mercury	1 ppm, maximum
flash point	100 F, minimum
heat content	135,000 Btu/gallon, minimum

* If the permittee is burning used oil with any quantifiable level >2 ppm <50 ppm of PCB's, then the permittee is subject to any applicable requirements found under 40 CFR part 279, subparts G and H and 40 CFR 761.20 (e).

** Used oil containing more than 1000 ppm total halogens is presumed to be a hazardous waste under the rebuttable presumption provided under 40 CFR 279.10 (b)(1)(ii) and OAC rule 3745-279-10 (B)(1)(b). Therefore, the permittee may receive and burn used oil exceeding 1000 ppm of total halogens (but less than 4000 ppm, maximum) only if the used oil burner has demonstrated the used oil does not contain any hazardous waste pursuant to OAC rule 3745-279-63.

6. The permittee may not burn any used oil which does not meet the specifications listed in OAC rule 3745-279-11 without first obtaining an air permit to install that authorizes the burning of such used oil. The burning of used oil that does not meet specifications listed in OAC rule 3745-279-11 is subject to OAC rule 3745-279-60 through 67 and the applicable portions of 40 CFR part 761. In addition, if the permittee is burning used oil which exceed the mercury limitation and falls below the heat content limitation listed in term B.f, then this may trigger the requirement to apply for and obtain an air permit to install.
7. The burning of hazardous waste is prohibited without first complying with all applicable state and federal hazardous waste and air regulations and permits.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be

Shelly Materials
PTI A
Issued

Facility ID: 0302020006

Emissions Unit ID: **P901**

installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a daily basis.

Issued: To be entered upon final issuance

2. Except as otherwise provided in this section, the permittee shall perform inspections of the fugitive material handling operations in accordance with the following frequencies:

<u>material handling operation(s)</u>	<u>minimum inspection frequency</u>
all material unloading into feeder bins	once during each day of operation
all material transfer from feeder bin conveyor to dryer feed conveyor	once during each day of operation
all material transfer from dryer feed conveyor to dryer	once during each day of operation

3. The purpose of the inspections is to determine the need for implementing the above-mentioned control measures. The inspections shall be performed during times of asphaltic concrete production.
4. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.
5. The permittee shall maintain records of the following information:
- a. the date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;
 - b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;
 - c. the dates the control measures were implemented.
6. The permittee shall maintain monthly records of the following information:
- a. Asphalt production rate in tons per month.
 - b. Beginning after the first 12 calendar months of operation under the provisions of this permit, the rolling, 12-month summation of the monthly asphalt production rate.

Also, during the first 12 calendar months of operation under the provisions of this permit, the permittee shall record the cumulative asphalt production rate for each calendar month.

7. The permittee shall receive a chemical analysis with each shipment of used oil from the supplier. The analysis shall identify the name and address of the supplier, the supplier's USEPA identification number, and the following information:
 - a. The date of the shipment or delivery.
 - b. The quantity of used oil received.
 - c. The Btu value of the used oil, in Btu/gallon.
 - d. The flash point of the used oil, in Btu/gallon.
 - e. The arsenic content, in ppm.
 - f. The cadmium content, in ppm.
 - g. The chromium content, in ppm.
 - h. The lead content, in ppm.
 - i. The PCB content, in ppm.
 - j. The total halogen content, in ppm.
 - k. The mercury content, in ppm.

Each analysis shall be kept in a readily accessible location for at least 5 years and shall be made available to the Director (the appropriate Ohio EPA District Office or local air agency) upon verbal or written request. The Director or any authorized representative of the Director may require or may conduct periodic, detailed chemical analysis through an independent laboratory or any used oil shipment received by this facility, of any used oil stored at this facility, or of any used oil sampled at the dryer.

D. Reporting Requirements

1. The permittee shall submit pressure drop deviation (excursion) reports that identify that all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above.
2. The permittee shall submit deviation (excursion) reports which identify all exceedances of the

Issued: To be entered upon final issuance

rolling, 12-month asphalt production limitation and for the first 12 calendar months of operation under the provisions of this permit, all exceedances of the maximum allowable cumulative asphalt production levels.

3. The permittee shall submit deviation reports that identify any of the following occurrence:
 - a. each day during which an inspection was not performed by the required frequency; and
 - b. each instance when a control measure, that was to be performed as a result of an inspection, was not implemented.
4. Deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.
5. The permittee shall notify the USEPA and the Ohio EPA if any of the used oil exceeds the used oil specifications found in OAC rule 3745-279-11 and the applicable portions of 40 CFR part 761 and shall also notify Ohio EPA if any used oil exceed the mercury limitation and falls below the heat content limitation listed in term B.4 within thirty days after the exceedance occurs. If the permittee is burning used oil which exceeds the specifications found in OAC rule 3745-279-11 and the applicable portions of 40 CFR part 761, the permittee is subject to that rule and must comply with all applicable provisions of that rule(s).

E. Testing Requirements

1. Compliance with the emissions limitation(s) in section A.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation:
0.04 gr/dscf, 10.23 lbs/hr PE

Applicable Compliance Method:
Compliance shall be determined by testing requirements specified in section E.2.
 - b. Emission Limitation:
6.60 tons PE per rolling 12-month period

Applicable Compliance Method:
The permittee shall demonstrate compliance by multiplying a maximum rolling 12-month asphalt production rate of 400,000 tons by the AP-42 emission factor of 0.033 lb PE/ton of product, in Table 11.1-3 (12/00) and dividing by 2000 lbs/ton. Compliance with the

Issued: To be entered upon final issuance

rolling 12-month asphalt production rate shall be demonstrated by the monitoring and recordkeeping in Section C.6.

- c. Emission Limitation:
2.00 TPY PE per rolling 12-month period (fugitive)

Applicable Compliance Method:

The permittee shall demonstrate compliance by multiplying an AP-42 emission factor of 0.01 lb PE/ton of material loaded found in Section 13.2.4.3 (1/95) asphalt production rate multiplying by a maximum annual material handling operations throughput of 400,000 tons and dividing by 2000 lbs/ton.

- d. Emission Limitation:
37.51 lbs/hr SO₂

Applicable Compliance Method:

Compliance shall be determined by testing requirements specified in section E.2.

- e. Emission Limitation:
24.20 TPY/yr SO₂ per rolling 12-month period

Applicable Compliance Method:

The permittee shall demonstrate compliance by multiplying a maximum rolling 12-month asphalt production rate of 400,000 tons by a company supplied emission factor of 0.121 lb SO₂/ ton of product (verified by testing in Section E.2) and dividing by 2000 lbs/ton. Compliance with the rolling 12-month asphalt production rate shall be demonstrated by the monitoring and recordkeeping in Section C.6.

- f. Emissions Limitation:
37.51 lbs/hr NO_x

Applicable Compliance Method:

Compliance shall be determined by testing requirements specified in section E.2.

- g. Emissions Limitation:
24.20 tons/yr NO_x per rolling 12-month period

Applicable Compliance Method:

The permittee shall demonstrate compliance by multiplying a maximum rolling 12-month asphalt production rate of 400,000 tons by a company supplied emission factor of 0.121 lb

Emissions Unit ID: **P901**

NOx/ton of product (verified by testing in Section E.2) and dividing by 2000 lbs/ton. Compliance with the rolling 12-month asphalt production rate shall be demonstrated by the monitoring and recordkeeping in Section C.6.

- h. Emissions Limitation:
139.50 lbs/hr CO

Applicable Compliance Method:
Compliance shall be determined by testing requirements specified in section E.2

- i. Emissions Limitation:
90.00 tons/yr CO

Shelly

PTI A

Emissions Unit ID: P901

Issued: To be entered upon final issuance

Applicable Compliance Method:

The permittee shall demonstrate compliance by multiplying a maximum rolling 12-month asphalt production rate of 400,000 tons by a company supplied emission factor of 0.45 lb CO/ton of product (verified by testing in Section E.2) and dividing by 2000 lbs/ton. Compliance with the rolling 12-month asphalt production rate shall be demonstrated by the monitoring and recordkeeping in Section C.6.

- j. Emissions Limitation:
93.31 lbs/hr VOC

Applicable Compliance Method:

Compliance shall be determined by testing requirements specified in section E.2.

- k. Emissions Limitation:
60.20 tons/yr VOC per rolling 12-month period

Applicable Compliance Method:

The permittee shall demonstrate compliance by multiplying a maximum rolling 12-month asphalt production rate of 400,000 tons by a company supplied emission factor of 0.301 lb VOC/ton of product (verified by testing in Section E.2) and dividing by 2000 lbs/ton. Compliance with the rolling 12-month asphalt production rate shall be demonstrated by the monitoring and recordkeeping in Section C.6.

- l. Emissions Limitation:
20 percent opacity as a 3-minute average per material handling operation

Applicable Compliance Method:

USEPA Reference Method 9 of 40 CFR Part 60, Appendix A.

- m. Emission Limitation:
Emissions from the baghouse stack shall not exhibit 20% opacity, or greater.

Applicable Compliance Method:

USEPA Reference Method 9 of 40 CFR Part 60, Appendix A.

- 2. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. The emission testing shall be conducted within 60 days after achieving the maximum

Shelly

PTI A

Emissions Unit ID: **P901**

Issued: To be entered upon final issuance

production rate at which the emissions unit will be operated, but not later than 180 days after modification of such emissions unit.

Shelly

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: P901

- b. The emission testing shall be conducted to demonstrate compliance with the following:
 - i. 10.23 lbs/hr PE
 - ii. 0.04 gr/dscf
 - iii. 37.51 lbs/hr SO₂
 - iv. 139.50 lbs/hr CO
 - v. 93.31 lbs/hr VOC
 - vi. 37.51 lbs/hr NO_x

- c. The following test method(s) shall be employed to demonstrate compliance with the above emission limitations:
 - i. PE & gr/dscf- Method 5, of 40 CFR Part 60, Appendix A.
 - ii. SO₂- Method 6, of CFR Part 60, Appendix A.
 - iii. CO- Method 10, of CFR Part 60, Appendix A.
 - iv. NO_x- Method 20, of CFR Part 60, Appendix A.
 - v. VOC- Method 25 of CFR Part 60, Appendix A.

The emission testing shall also be conducted to verify the company supplied emission factors of:

- i. 0.121 lb SO₂/ton of product
- ii. 0.121 lb NO_x/ton of product
- iii. 0.45 lb CO/ton of product
- iv. 0.301 lb VOC/ton of product

The test(s) shall be conducted while the emissions unit is operating at its maximum

Emissions Unit ID: **P901**

capacity unless otherwise specified or approved by the appropriate Ohio EPA District or local air agency.

- d. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification. The company shall demonstrate in the "Intent to Test" what is "Worst Case" for particulate emissions. (e.g. "Virgin aggregate"/slag.) This "Worst Case" scenario shall be pre-approved by the Ohio EPA, Division of Air Pollution Control, Northwest District Office. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emission unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the field office's refusal to accept the results of the emissions test(s).
- e. Personnel from the Ohio EPA, Northwest District Office shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.
- f. A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA, Northwest District Office within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, Northwest District Office.

F. Miscellaneous Requirements

NONE