



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL  
ALLEN COUNTY**

**CERTIFIED MAIL**

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center  
P.O. Box 1049

**Application No: 03-16321**

**Fac ID: 0302950002**

**DATE: 9/13/2005**

Bluffton Stone Company  
Jim Scheub  
PO Box 607  
Napoleon, OH 43522

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission  
309 South Fourth Street, Room 222  
Columbus, Ohio 43215

Sincerely,

Michael W. Ahern, Manager  
Permit Issuance and Data Management Section  
Division of Air Pollution Control

CC: USEPA

NWDO



---

**Permit To Install  
Terms and Conditions**

**Issue Date: 9/13/2005  
Effective Date: 9/13/2005**

---

**FINAL PERMIT TO INSTALL 03-16321**

Application Number: 03-16321  
Facility ID: 0302950002  
Permit Fee: **\$1850**  
Name of Facility: Bluffton Stone Company  
Person to Contact: Jim Scheub  
Address: PO Box 607  
Napoleon, OH 43522

Location of proposed air contaminant source(s) [emissions unit(s)]:  
**310 Quarry Drive  
Bluffton, Ohio**

Description of proposed emissions unit(s):  
**Portable aggregate processing plant with crushing, screening, and material handling operations and associated storage piles, and roadways.**

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

## Part I - GENERAL TERMS AND CONDITIONS

### A. Permit to Install General Terms and Conditions

#### 1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

#### 2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

#### 3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

#### 4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon

**Bluffton Stone Company**  
**PTI Application: 03-16321**  
**Issued: 9/13/2005**

**Facility ID: 0302950002**

the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

**5. Scheduled Maintenance/Malfunction Reporting**

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

**6. Permit Transfers**

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

**7. Air Pollution Nuisance**

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

**8. Termination of Permit to Install**

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

**9. Construction of New Sources(s)**

**Bluffton Stone Company**  
**PTI Application: 03-16321**  
**Issued: 9/13/2005**

**Facility ID: 030295002**

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

#### **10. Public Disclosure**

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

#### **11. Applicability**

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

#### **12. Best Available Technology**

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

**Bluffton Stone Company**  
**PTI Application: 03-16321**  
**Issued: 9/13/2005**

**Facility ID: 030295002**

**13. Source Operation and Operating Permit Requirements After Completion of Construction**

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

**14. Construction Compliance Certification**

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

**15. Fees**

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

**B. Permit to Install Summary of Allowable Emissions**

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)  
 TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
Fugitive PE	7.31
Stack PE	1.49
NOx	13.35
CO	4.01
SO2	1.38

7

**Bluffton Stone Company**  
**PTI Application: 03-16321**  
**Issued: 9/13/2005**

**Facility ID: 0302950002**

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)****A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
F003 - Portable crushing, screening, and material handling operations	OAC rule 3745-31-05 (A) (3)	2.82 tons fugitive particulate emissions (PE)/yr
		20% opacity, as a 3-minute average from front-end loader dumping into Grizzly feeder
		Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see A.2.a through A.2.d)
		See A.2.e
		See A.2.f.
	OAC rule 3745-17-07 (B)	See A.2.g
	OAC rule 3745-17-08 (B)	See A.2.g
	40 CFR, Part 60, Subpart 000	Opacity Restrictions (See A.2.h)

**2. Additional Terms and Conditions**

- 2.a** The crushing, screening, and material handling operation(s) that are covered by

this permit and subject to the above-mentioned requirements are listed below:

Front End Loader to Grizzly Feeder  
 Grizzly Feeder to Conveyor  
 Grizzly Feeder to Conveyor  
 Conveyor to Crusher  
 Crusher  
 Crusher to Conveyor  
 Conveyor to Screen  
 Screen  
 Screen to Stacker 1  
 Screen to Stacker 2  
 Screen to Stacker 3  
 Screen to Stacker 4

- 2.b** The permittee shall employ best available control measures for the above-identified crushing, screening and material handling operations for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to perform the following control measure(s) to ensure compliance:

<u>Material Handling Operation</u>	<u>Control Measure</u>
Front End Loader to Grizzly Feeder	Minimize Freefall Distance
Grizzly Feeder to Conveyor	Water Spray
Grizzly Feeder to Conveyor	Water Spray
Conveyor to Crusher	Water Spray
Crusher	Water Spray
Crusher to Conveyor	Water Spray
Conveyor to Screen	Water Spray
Screen	Water Spray
Screen to Stacker 1	Water Spray
Screen to Stacker 2	Water Spray
Screen to Stacker 3	Water Spray
Screen to Stacker 4	Water Spray

- 2.c** For each crushing, screening, and material handling operation that is not adequately enclosed, the above-identified control measures shall be implemented if the permittee determines, as a result of the inspection conducted

pursuant to the monitoring section of this permit, that the control measures are necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measures shall continue during the operation of the material handling operations until further observation confirms that use of the control measures is unnecessary.

- 2.d** Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the requirements of OAC rule 3745-31-05.
- 2.e** The requirements of this rule also include compliance with OAC rule 3745-17-07(B), OAC rule 3745-17-08(B) and CFR 40 Part 60, Subpart 000.
- 2.f** The application and enforcement of the provisions of NSPS, as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60, are delegated to the Ohio Environmental Protection Agency. The requirements of 40 CFR Part 60 are also federally enforceable.
- 2.g** This emissions unit is a portable source and is applicable to the requirements of OAC rule 3745-17-07(B) and OAC rule 3745-17-08(B) when located in an "Appendix A" area as identified in OAC rule 3745-17-08. The emission limitations and control requirements established by OAC rule 3745-17-07(B) and OAC rule 3745-17-08(B) are equivalent to or less stringent than the requirements established pursuant to OAC rule 3745-31-05(A)(3).

When the emissions unit is not located within an "Appendix A" area as identified in OAC rule 3745-17-08, this emission unit is exempt from the requirements of OAC rule 3745-17-08(B) pursuant to OAC rule 3745-17-08(A) and is exempt from the visible particulate emission limitations specified in OAC rule 3745-17-07(B)(1) pursuant to OAC rule 3745-17-07(B)(11)(e).

- 2.h** Visible fugitive PE from the material process equipment shall not exceed the following opacity restrictions:

<b>Emission Point (Company ID)</b>	<b>Equipment Type</b>	<b>Opacity Limit as a 6-minute average, unless otherwise specified</b>	<b>Regulatory Basis for Limit</b>
Grizzly Feeder to Conveyor	Transfer Point	10%	40 CFR, Part 60 Subpart 000

Emissions Unit ID: **F003**

Grizzly Feeder to Conveyor	Transfer Point	10%	40 CFR, Part 60 Subpart OOO
Conveyor to Crusher	Transfer Point	10%	40 CFR, Part 60 Subpart OOO
Crusher	Crushing	15%	40 CFR, Part 60 Subpart OOO
Crusher to Conveyor	Transfer Point	10%	40 CFR, Part 60 Subpart OOO
Conveyor to Screen	Transfer Point	10%	40 CFR, Part 60 Subpart OOO
Screen	Screening	10%	40 CFR, Part 60 Subpart OOO
Screen to Stacker 1	Transfer Point	10%	40 CFR, Part 60 Subpart OOO
Screen to Stacker 2	Transfer Point	10%	40 CFR, Part 60 Subpart OOO
Screen to Stacker 3	Transfer Point	10%	40 CFR, Part 60 Subpart OOO
Screen to Stacker 4	Transfer Point	10%	40 CFR, Part 60 Subpart

## **B. Operational Restrictions**

1. The permittee shall not exceed 1,200,000 tons per year of aggregate processed in emissions unit F003. This restriction is based on the aggregate throughput of the primary crusher

## **C. Monitoring and/or Recordkeeping Requirements**

1. Except as otherwise provided in this section, for material handling operations that are not adequately enclosed, the permittee shall perform inspections of such operations in accordance with the following minimum frequencies:

Crushing/Screening/Material Handling  
All

Minimum Inspection Frequency  
Once During Each Day of Operation

2. The above-mentioned inspections shall be performed during representative, normal operating conditions.
3. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.

4. The permittee shall maintain records of the following information:
  - a. the date and reason any required inspection was not performed;
  - b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;
  - c. the dates the control measures were implemented; and
  - d. on a calendar quarter basis, the total number of days the control measures were implemented.

The information in 4.d. shall be kept separately for each material handling operation identified above, and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

#### **D. Reporting Requirements**

1. The permittee shall submit deviation reports that identify any of the following occurrences:
  - a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and
  - b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.

The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

2. The permittee shall submit the following information for each piece of equipment that is replaced by a piece of equipment having the same function as the existing facility:
  - a. for a crusher:
    - i. the rated capacity in tons per hour of the existing facility being replaced, and

Emissions Unit ID: **F003**

- ii. the rated capacity in tons per hour of the replacement equipment.
- b. for a screening operation:
  - i. the total surface area of the top screen of the existing screening operation being replaced and
  - ii. the total surface area of the top screen of the replacement screening operation.
- c. for a conveyor belt:
  - i. the width of the existing belt being replaced, and
  - ii. the width of the replacement conveyor belt.

The notification shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days after the equipment replacement.

3. Pursuant to the general provisions of NSPS, the source owner/operator is hereby advised of the requirement to report the following at the appropriate times for this emissions unit:
  - a. construction date (no later than 30 days after such date);
  - b. actual start-up date (within 15 days after such date); and
  - c. date of performance testing (if required, at least 30 days prior to testing).

Reports are to be sent to:

Ohio Environmental Protection Agency  
 DAPC - Permit Management Unit  
 Lazarus Government Center  
 P.O. Box 1049  
 Columbus, OH 43216-1049

and Ohio EPA, Northwest District Office  
 347 North Dunbridge Road  
 Bowling Green, OH 43402

## **E. Testing Requirements**

1. The permittee shall conduct, or have conducted, emission testing for all crushers, transfer points and screens of emissions units F003.

**Issued: 9/13/2005**

2. Testing shall be conducted in accordance with the provisions of 40 CFR Part 60, Subpart A, Section 60.8 and 40 CFR Part 60, Subpart OOO, Section 60.675.
3. The emission testing shall be conducted within 60 days after achieving the maximum production rate at which the affected facility will be operated, by not later than 180 days after initial startup of such facility and at such other times as may be required by the Ohio Environmental Protection Agency, Division of Air Pollution Control. The emission testing shall be conducted to demonstrate compliance with the allowable visible emission rates for particulate emissions.
4. The following test methods shall be employed to demonstrate compliance with the allowable visible emissions rates:
  - a. Method 9 of 40 CFR Part 60, Appendix A shall be used to determine opacity.
5. The tests shall be conducted while the emissions unit is operating at its maximum capacity, unless otherwise specified or approved by the Ohio EPA, Division of Air Pollution Control. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, Division of Air Pollution Control. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operation parameters, the times and dates of the tests, and the person(s) who will be conducting the tests. Failure to submit such notification for review and approval prior to the tests may result in the Ohio EPA District Office's air agency's refusal to accept the results of the emission tests.
6. Personnel from the Ohio EPA District Office's air agency shall be permitted to witness the test, examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions unit and /or the performance of the control equipment. A comprehensive written report on the emissions tests shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA Division of Air Pollution Control within 30 days following completion of the tests.
7. Compliance with the emissions limitations in section A.1 of these terms and conditions shall be determined in accordance with the following methods:
  - a. Emission Limitation: 2.82 tons fugitive PE/yr  
  
Applicable Compliance Method: The emission limitation is based on a maximum throughput rate of 1,200,000 tons per year and the following controlled emission

factors from AP-42: 0.00003 lb PE/ton (Section 11.19.2 -8/04) for the Front End Loader dumping into the Grizzly feeder, 0.0012 lb PE/ton (Section 11.19.2 - 8/04) for the crusher, 0.0022 lb PE/ton (Section 11.19.2 - 8/04) for the screen and 0.000014 lb PE/ton (Section 11.19.2 - 9/95) for the nine transfer points.

Therefore, provided compliance is shown with the requirements of this permit to apply best available control measures, compliance with the ton per year PE limitation will be assumed.

- b. 20% opacity, as a 3-minute average from front-end loader dumping into grizzly feeder

Applicable Compliance Method: If required, compliance shall be demonstrated using Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 (Standards of Performance for New Stationary Sources") as such Appendix existed on July 1, 2002, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

- c. Emission Limitation: 15% opacity, from the crushing operation

Applicable Compliance Method: Compliance shall be demonstrated using Method 9 of 40 CFR, Part 60, Appendix A, and the procedures in 40 CFR, Part 60, Subpart OOO as specified in sections E.1 through E.6 above.

- d. Emission Limitation: 10% opacity, from screening operations

Applicable Compliance Method: Compliance shall be demonstrated using Method 9 of 40 CFR, Part 60, Appendix A, and the procedures in 40 CFR, Part 60, Subpart OOO as specified in sections E.1 through E.6 above.

- e. Emission Limitation: 10% opacity, from the transfer points

Applicable Compliance Method: *Compliance shall be demonstrated using Method 9 of 40 CFR, Part 60, Appendix A, and the procedures in 40 CFR, Part 60, Subpart OOO as specified in sections E.1 through E.6 above.*

## **F. Miscellaneous Requirements**

1. Pursuant to Ohio Administrative Code (OAC) rule 3745-31-03(A)(1)(p)(i), the permittee of a portable or mobile emissions unit may relocate within the State of Ohio without first

obtaining a PTI providing the following criteria are met:

- a. the portable emissions unit is equipped with the best available control technology for such portable emissions unit;
  - b. the portable emissions unit is operating pursuant to a currently effective permit to install, permit to operate or registration;
  - c. the applicant has provided proper notice of intent to relocate the portable emissions unit to the Northwest District Office (NWDO) and the appropriate field office having jurisdiction over the new site within a minimum of thirty days prior to the scheduled relocation; and,
  - d. in the NWDO's and the appropriate field office's judgement, the proposed site is acceptable under the rule 3745-15-07 of the Administrative Code.
2. In the alternative, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), the permittee of a portable or mobile emissions unit may relocate within the State of Ohio without first obtaining a PTI providing the following criteria of OAC rule 3745-31-05(F) are met:
- a. the portable emissions unit permittee possesses an Ohio EPA PTI, PTO or registration status;
  - b. the portable emissions unit is equipped with best available technology;
  - c. the portable emission unit owner has identified the proposed site to Ohio EPA;
  - d. Ohio EPA has determined that the portable emissions unit, at the proposed site, will have an acceptable environmental impact;
  - e. a public notice, consistent with Chapter 3745-47 of the Administrative Code, is published in the county where the proposed site is located;
  - f. the owner of the proposed site has provided the portable emissions unit owner with approval or equivalent declaration that it is acceptable to the site owner to move the portable emissions unit to the proposed site; and,
  - g. the portable emissions unit owner has provided the Ohio EPA with fifteen days written notice of the relocation.

Any site approvals issued by the Ohio EPA, pursuant to section F.2. above, shall be valid for no longer than three years and are subject to renewal.

3. In order for the NWDO and the appropriate field office having jurisdiction over the new

**Bluffton Stone Company**  
**PTI Application: 03-16321**  
**Issued: 9/13/2005**

Emissions Unit ID: **F001**  
Facility ID: **0302950002**

site to determine compliance with all of the above criteria, the owner or operator of the portable or mobile emissions unit must file a "Notice of Intent to Relocate", within the specified time frame (30 or 15 days) prior to the relocation of the emissions unit with the NWDO (347 North Dunbridge Road, Bowling Green, OH 43402) and the appropriate office having jurisdiction over the new site. Upon receipt of the notice, the NWDO and/or the appropriate field office having jurisdiction over the new site, will evaluate the request in accordance with the above criteria.

4. The permittee should be advised that when portable emission units are located at a stationary source or at a source comprised of portable emission units, potential emissions from the portable emission units are included in the facility potential to emit calculations for Title V and PSD applicability.

The permittee shall include a potential to emit analysis of facility-wide emissions (including the portable sources) for the proposed relocation in the "Notice of Intent to Relocate".

## **PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

### **A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions

unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	OAC rule 3745-17-08(B)
F001 - Storage piles	OAC rule 3745-31-05(A)(3)	
load-in and load-out of storage piles (see Section A.2.a for identification of storage piles)	OAC rule 3745-31-05(A)(3)	
	OAC rule 3745-17-07(B)	
	OAC rule 3745-17-08(B)	
wind erosion from storage piles (see Section A.2.a for identification of storage piles)	OAC rule 3745-31-05(A)(3)	
	OAC rule 3745-17-07(B)	

**Bluff**

**PTI A**

**Issued: 9/13/2005**

Emissions Unit ID: **F001**

Applicable Emissions  
Limitations/Control Measures

0.33 ton fugitive particulate  
emissions (PE)/yr

No visible particulate emissions  
except for a period of time not  
to exceed one minute during  
any 60-minute observation  
period.

Best available control  
measures that are sufficient to  
minimize or eliminate visible  
emissions of fugitive dust (see  
A.2.b, A.2.c and A.2.f)

See A.2.g

See A.2.g

No visible particulate emissions  
except for a period of time not  
to exceed one minute during  
any 60-minute observation  
period.

Best available control  
measures that are sufficient to  
minimize or eliminate visible  
emissions of fugitive dust (see  
A.2.d through A.2.f)

See A.2.g

See A.2.g

**2. Additional Terms and Conditions**

- 2.a** The storage piles that are covered by this permit and subject to the above-mentioned requirements are listed below:
- 10's, 8's, 6's, 411, and 304
- 2.b** The permittee shall employ best available control measures on all load-in and load-out operations associated with the storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to watering and low drop heights from front end loaders to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.
- 2.c** The above-mentioned control measures shall be employed for each load-in and load-out operation of each storage pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measures are necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measures shall continue during any such operation until further observation confirms that use of the measures is unnecessary.
- 2.d** The permittee shall employ best available control measures for wind erosion from the surfaces of all storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to watering and maintenance of as low a pile height as possible to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.
- 2.e** The above-mentioned control measures shall be employed for wind erosion from each pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measures are necessary to ensure compliance with the above-mentioned applicable requirements. Implementation of the control measures shall not be necessary for a storage pile that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements.
- 2.f** Implementation of the above-mentioned control measures in accordance with the

Emissions Unit ID: **F001**

terms and conditions of this permit is appropriate and sufficient to satisfy the requirements of OAC rule 3745-31-05.

- 2.g** The storage piles are associated with the portable crushing, screening, and material handling operations (emissions unit F003) permitted under facility ID 0302950002. The emission limitation of 0.33 ton fugitive PE per year represents the maximum emissions which will be emitted from the storage piles associated with the portable crushing and screening system.

The storage piles are associated with a portable source and are applicable to the requirements of OAC rule 3745-17-07(B) and 3745-17-08(B) when located in an "Appendix A" area as identified in OAC rule 3745-17-08. The emission limitations and control requirements established by OAC rule 3745-17-07(B) and OAC rule 3745-17-08(B) are less stringent than the requirements established pursuant to OAC rule 3745-31-05(A)(3).

**B. Operational Restrictions**

None

**C. Monitoring and/or Recordkeeping Requirements**

1. Except as otherwise provided in this section, the permittee shall perform inspections of each load-in operation at each storage pile in accordance with the following frequencies:

<u>Storage Pile Identification</u>	<u>Minimum Load-In Inspection Frequency</u>
All Storage Piles	Once During Each Day of Operation

2. Except as otherwise provided in this section, the permittee shall perform inspections of each load-out operation at each storage pile in accordance with the following frequencies:

<u>Storage Pile identification</u>	<u>Minimum Load-Out Inspection Frequency</u>
All Storage Piles	Once During Each Day of Operation

3. Except as otherwise provided in this section, the permittee shall perform inspections of the wind erosion from pile surfaces associated with each storage pile in accordance with the following frequencies:

Storage Pile Identification

All Storage Piles

Minimum Wind Erosion Inspection Frequency

Once During Each Day of Operation

4. No inspection shall be necessary for wind erosion from the surface of a storage pile when the pile is covered with snow and/or ice and for any storage pile activity if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.
5. The purpose of the inspections is to determine the need for implementing the control measures specified in this permit for load-in and load-out of a storage pile, and wind erosion from the surface of a storage pile. The inspections shall be performed during representative, normal storage pile operating conditions.
6. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.
7. The permittee shall maintain records of the following information:
  - a. the date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;
  - b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;
  - c. the dates the control measures were implemented; and
  - d. on a calendar quarter basis, the total number of days the control measures were implemented and, for wind erosion from pile surfaces, the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measure(s).

The information required in 7.d. shall be kept separately for (i) the load-in operations, (ii) the load-out operations, and (iii) the pile surfaces (wind erosion), and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

**Bluffton Stone Company**  
**PTI Application: 02-16224**  
**Issue**

**Facility ID: 0302950002**

**Emissions Unit ID: F001**

#### **D. Reporting Requirements**

1. The permittee shall submit deviation reports that identify any of the following occurrences:
  - a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and
  - b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.
2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

## E. Testing Requirements

1. Compliance with the emission limitations in Section A.1. of the terms and conditions of this permit shall be determined in accordance with the following methods:

- a. Emission Limitation: 0.33 ton fugitive PE/yr

Applicable Compliance Method: The emission limitation was established by combining the emissions from load-in and load-out operations and from wind erosion from each storage pile as listed in the permittee's application and applying a 95% control efficiency for use of best available control measures. Load-in and load-out operation emissions are based on a maximum load-in and load-out rate of 1,200,000 tons per year. Wind erosion emissions are based on a maximum combined storage pile surface area of 2.5 acres as listed in the permit application:

The emission rate was determined as follows:

- i. Load-in - emissions associated with load-in operations were established by multiplying the maximum load-in rate of 1,200,000 tons per year combined from all storage piles by the appropriate emission factor from AP-42 section 13.2.4.3 (1/95) [0.005 lb PE/ton product], applying a 95% control efficiency and dividing by 2000 lbs/ton. (0.15 ton fugitive PE/yr)
- ii. Load-out - emissions associated with load-out operations were established by multiplying the maximum load-out rate of 1,200,000 tons per year combined from all storage piles by the appropriate emission factor from AP-42 section 13.2.4.3 (1/95) [0.005 lb PE/ton product], applying a 95% control efficiency and dividing by 2000 lbs/ton. (0.15 ton fugitive PE/yr)
- iii. Wind erosion - emissions were established by multiplying a maximum combined storage pile surface area of 2.5 acres by the appropriate emission factor from USEPA's Control of Open Fugitive Dust Sources (9/88) [1.17 lbs PE/day/acre, by a maximum operating schedule of 365 days per year and dividing by 2000 and applying a 95% control efficiency. (0.03 ton PE/yr)

Therefore, provided compliance is shown with the requirements of this permit to apply best available control measures, compliance with the ton per year PE limitation will be assumed.

- b. Emission Limitation: No visible particulate emissions except for a period of time not to exceed one minute during any 60-minute observation period from load-in and load-out of the storage piles

Applicable Compliance Method: If required, compliance with the visible emission limitations for the storage piles identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

- c. Emission Limitation: No visible particulate emissions except for a period of time not to exceed one minute during any 60-minute observation period from wind erosion

Applicable Compliance Method: If required, compliance with the visible emission limitations for the storage piles identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

**F. Miscellaneous Requirements**

None

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
F002 - Unpaved roadways and parking areas	OAC rule 3745-31-05(A)(3)	4.16 tons fugitive particulate emissions (PE)/yr  There shall be no visible particulate emissions from any unpaved roadway or parking area except for a period of time not to exceed three minutes during any 60-minute observation period.  Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see A.2.b through A.2.g)
	OAC rule 3745-17-07(B)	See A.2.h
	OAC rule 3745-17-08(B)	See A.2.h

**2. Additional Terms and Conditions**

- 2.a The unpaved roadways and parking areas that are covered by this permit and subject to the above-mentioned requirements are listed below:

Unpaved Roadways:

All Unpaved Roadways and Parking Areas

- 2.b** The permittee shall employ best available control measures on all unpaved roadways and parking areas for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to water at sufficient treatment frequencies to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.
- 2.c** The needed frequencies of implementation of the control measures shall be determined by the permittee's inspections pursuant to the monitoring section of this permit. Implementation of the control measures shall not be necessary for an unpaved roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Implementation of any control measure may be suspended if unsafe or hazardous driving conditions would be created by its use.
- 2.d** Any unpaved roadway or parking area, which during the term of this permit is paved or takes the characteristics of a paved surface due to the application of certain types of dust suppressants, may be controlled using appropriate dust control measures for paved surfaces. Any unpaved roadway or parking area that takes the characteristics of a paved roadway or parking area due to the application of certain types of dust suppressants shall remain subject to the visible emission limitation for unpaved roadways and parking areas. Any unpaved roadway or parking area that is paved shall be subject to a visible emission limitation of no visible particulate emissions except for one minute during any 60-minute period.
- 2.e** The permittee shall promptly remove, in such a manner as to minimize or prevent resuspension, earth and/or other material from paved streets onto which such material has been deposited by trucking or earth moving equipment or erosion by water or other means.
- 2.f** Open-bodied vehicles transporting materials likely to become airborne shall have such materials covered at all times if the control measure is necessary for the materials being transported.
- 2.g** Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the best available technology requirements of OAC rule 3745-31-05.

- 2.h** The unpaved roadways and parking areas are associated with the portable crushing, screening, and material handling operations (emissions unit F003) permitted under facility ID 0302950002. The emission limitation of 4.16 tons fugitive PE/yr represents the maximum emissions which will be emitted from the unpaved roadways and parking areas for any proposed site for relocation of the portable screening system.

The roadways are associated with a portable source and are applicable to the requirements of OAC rule 3745-17-07(B) and 3745-17-08(B) when located in an "Appendix A" area as identified in OAC rule 3745-17-08. The emission limitations and control requirements established by OAC rule 3745-17-07 (B) and OAC rule 3745-17-08(B) are less stringent than the requirements established pursuant to OAC rule 3745-31-05(A)(3).

## **B. Operational Restrictions**

None

## **C. Monitoring and/or Recordkeeping Requirements**

1. Except as otherwise provided in this section, the permittee shall perform inspections of the unpaved roadways and parking areas in accordance with the following frequencies:

Unpaved Roadways and Parking Areas

All

Minimum Inspection Frequency

Once During Each Day of Operation

2. The purpose of the inspections is to determine the need for implementing the above-mentioned control measures. The inspections shall be performed during representative, normal traffic conditions. No inspection shall be necessary for a roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above-identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.
3. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.

4. The permittee shall maintain records of the following information:
  - a. the date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;
  - b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;
  - c. the dates the control measures were implemented; and
  - d. on a calendar quarter basis, the total number of days the control measures were implemented and the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measures.

The information required in 4.d. shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

#### **D. Reporting Requirements**

1. The permittee shall submit deviation reports that identify any of the following occurrences:
  - a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and
  - b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.
2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

#### **E. Testing Requirements**

1. Compliance with the emission limitations in Section A.1. of the terms and conditions of this permit shall be determined in accordance with the following methods:
  - a. Emission Limitation: 4.16 tons fugitive PE/yr

Applicable Compliance Applicable Compliance Method: This emission limitation

was developed by applying a 95% control efficiency to a maximum potential uncontrolled emission rate of 83.24 tons per year fugitive PE. The maximum potential uncontrolled emission rate was calculated using an AP-42 emission factor from Chapter 13.2.2 (12/03) (13.44 lbs PE/VMT) and a maximum 12,387 vehicle miles traveled per year.

Therefore, provided compliance is shown with the requirements of this permit to apply best available control measures, compliance with the ton per year PE limitation will be assumed.

- b. Emission Limitation: There shall be no visible particulate emissions from any unpaved roadway or parking area except for a period of time not to exceed three minutes during any 60-minute observation period.

Applicable Compliance Method: Compliance with the visible emission limitation specified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(d) of OAC rule 3745-17-03.

#### **F. Miscellaneous Requirements**

None

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
P001 - 449 horsepower diesel engine	OAC rule 3745-31-05 (A) (3)	OAC rule 3745-18-06 (G)
		OAC rule 3745-21-07 (B)
		OAC rule 3745-23-06 (B)
		OAC rule 3745-21-08 (B)
	OAC rule 3745-31-05 (C)	
	OAc rule 3745-17-07 (A)	
	OAC rule 3745-17-11 (B) (5) (a)	

Applicable Emissions  
Limitations/Control Measures

1.49 ton PE/yr (stack  
emissions)  
(see A.2.g)

0.92 lbs sulfur dioxide (SO<sub>2</sub>)/hr  
& 1.38 tons/yr

8.90 lbs nitrogen oxides  
(NO<sub>x</sub>)/hr

2.67 lbs carbon monoxide  
(CO)/hr

Visible particulate emissions  
shall not exceed 10% opacity  
as a 6-minute average, except  
during start-up and shutdown

See A.2.h

13.35 tons NO<sub>x</sub> per rolling  
12-month period (see A.2.d)

4.01 tons CO per rolling  
12-month period (see A.2.d)

See A.2.a

0.031 lb PE/mmBtu of actual  
heat input

See A.2.b

See A.2.c

See A.2.f

See A.2.c

## **2. Additional Terms and Conditions**

- 2.a** The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05 (A) (3).
- 2.b** This emissions unit is exempt from the requirements of OAC rule 3745-18-06 (G) pursuant to OAC rule 3745-18-06 (B).
- 2.c** The permittee has satisfied the "latest available control techniques and operating practices" required pursuant to OAC rule 3745-21-07(B) and the "best available control techniques and operating practices" required pursuant to OAC rule 3745-21-08(B) by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05 (A)(3) in this permit to install.

On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the requirement to satisfy the "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

- 2.d** The emissions of NO<sub>x</sub> and CO from this emissions unit shall not exceed 13.35 tons per rolling 12-month period and 4.01 tons per rolling 12-month period based on an hours of operation restriction (See section B.1.).

The 13.35 tons of NO<sub>x</sub> per year and 4.01 tons of CO per year are federally enforceable limitations established for purposes of limiting potential to emit to avoid possible future Title V or Prevention of Significant Deterioration (PSD) applicability associated with relocation of a portable source.

- 2.e** The permittee has satisfied the "latest available control techniques and operating practices" required pursuant to OAC rule 3745-23-06(B) by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05(A)(3) in this Permit to Install.

On February 14, 2005, OAC rule 3745-23-06 was rescinded; therefore, paragraph (B) is no longer part of the State regulations. However, that rule

revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the U.S. EPA approves the revision to OAC rule 3745-23-06, the requirement to satisfy the "latest available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

- 2.f** All PE consists of particulate matter less than 10 microns in size (PM10)
- 2.g** The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05 (C) and OAC rule 3745-17-11 (B) (5) (a).

## **B. Operational Restrictions**

1. The maximum annual hours of operation for emissions unit P001 shall not exceed 3000 hours per year, based upon a rolling 12-month summation of the operating hours. To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed the levels specified in the following table:

Month(s)	Maximum Allowable Hours of Operation
1	750
1-2	954
1-3	1159
1-4	1364
1-5	1569
1-6	1774
1-7	1979
1-8	2184
1-9	2389
1-10	2594
1-11	2799
1-12	3000

After the first 12 calendar months of operation following the issuance of this permit, compliance with the annual hours of operation limitation shall be based upon a rolling, 12-month summation of the operating hours.

**Bluffton Stone Company**  
**PTI Application: 02 16221**  
**Issue**

**Facility ID: 0302950002**

**Emissions Unit ID: P001**

2. The oil combusted in this emissions unit shall only be distillate oil (fuel oil numbers 1 or 2, as defined by the American Society for Testing and Materials in ASTM D396-78, 89, 90, 92, 96, or 98, "Standard Specification for Fuel Oils"). The sulfur content of the distillate oil shall contain no more than 0.5 weight percent sulfur.

### **C. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall use records of fuel supplier certification to demonstrate compliance with the operational restriction in section B.2. Records of fuel supplier certification shall include the following information:
  - i. the name of the oil supplier; and
  - ii. a statement from the oil supplier that the oil complies with the specifications under the definition of distillate oil in B.2 above.
2. The permittee shall maintain monthly records of the following information for this emissions unit:
  - a. the hours of operation;
  - b. the rolling, 12-month summation of the hours of operation;
  - c. the calculated monthly emission rate for NO<sub>x</sub> using the following equation:  
$$\text{NO}_x \text{ emissions in tons} = (\text{hours of operation}) \times (\text{potential hourly NO}_x \text{ emissions}) \times (1 \text{ ton}/2000 \text{ lbs}) = (\text{C.2.a}) \times (8.90 \text{ lbs NO}_x/\text{hr}) (1 \text{ ton}/2000 \text{ lbs})$$
  - d. the calculated month emission rate for CO using the following equation:  
$$\text{CO emissions in tons} = (\text{hours of operation}) \times (\text{potential hourly NO}_x \text{ emissions}) \times (1 \text{ ton}/2000 \text{ lbs}) = (\text{C.2.a}) \times (2.67 \text{ lbs CO}/\text{hr}) (1 \text{ ton}/2000 \text{ lbs})$$
  - e. the rolling, 12-month summation of the emission rate for NO<sub>x</sub> & CO, in tons.

### **D. Reporting Requirements**

1. The permittee shall submit deviation (excursion) reports which identify the following exceedances:
  - a. the rolling, 12-month hours of operation limitation;
  - b. the rolling, 12-month NO<sub>x</sub> & CO emissions; and
  - c. sulfur content fuel restriction described in condition B.2.

These deviation (excursion) reports shall be submitted in accordance with the General Terms and Conditions of this permit.

2. The permittee shall submit deviation (excursion) reports that identify each day when a fuel was burned in this emissions unit which did not comply with the operational restriction in B.2. Each report shall be submitted within 30 days after the deviation occurs.

## **E. Testing Requirements**

1. Compliance with the emissions limitations in section A.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation: 1.49 ton PE/yr (stack emissions)

The annual emission limitation was established by multiplying an emission factor of 0.00220 lb PE/hp-hr from AP-42, Table 3.3-1 (revised 10/96), by the maximum horsepower of the generator (449 horsepower) by a maximum operating schedule of 3,000 hours per year and dividing by 2000 lbs/ton . Therefore provided compliance is shown with the 3,000 hours per rolling 12-month period operational restriction, compliance with the annual limitation will be assumed.

- b. Emission Limitation:  
0.92 lb SO<sub>2</sub>/hr & 1.38 tons SO<sub>2</sub>/yr

Applicable Compliance Method:

Compliance with the hourly emission limitation shall be determined by multiplying an emission factor of 0.00205 lb SO<sub>2</sub>/hp-hr from AP-42, Table 3.3-1 (revised 10/96), by the maximum horsepower of the generator (449 horsepower). If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1 - 4, and 6 of 40 CFR Part 60, Appendix A.

The annual emission limitation was established by multiplying the hourly emission limitation by a maximum operating schedule of 3,000 hours per year and dividing by 2000 lbs/ton. Therefore provided compliance is shown with the 3,000 hours per rolling 12-month period operational restriction, compliance with the annual limitation will be assumed.

- c. Emission Limitation:

Emissions Unit ID: **P001**

8.90 lbs NO<sub>x</sub>/hr & 13.35 tons NO<sub>x</sub> per rolling 12-month period.

Applicable Compliance Method:

The hourly emission limitation represents the potential to emit\* for this emissions unit. Therefore no hourly recordkeeping, deviation reporting, or compliance method calculations are required to demonstrate compliance with this limitation.

\*Potential to emit for this emissions unit was established by manufacturer's emission testing data.

If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1 - 4, and 7 of 40 CFR Part 60, Appendix A.

Compliance with the NO<sub>x</sub> per rolling 12-month period shall be demonstrated by the recordkeeping requirements in section C.2.

- d. Emission Limitation:  
2.67 lbs CO/hr & 4.01 tons CO/rolling 12-month period

Applicable Compliance Method:

The hourly emission limitation represents the potential to emit\* for this emissions unit. Therefore no hourly recordkeeping, deviation reporting, or compliance method calculations are required to demonstrate compliance with this limitation.

\*Potential to emit for this emissions unit was established by manufacturer's emission testing data.

If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1 - 4, and 10 of 40 CFR Part 60, Appendix A.

Compliance with the CO per rolling 12-month period shall be demonstrated by the recordkeeping requirements in section C.2.

- e. Emission Limitation:  
Visible PE shall not exceed 10% opacity as a 6-minute average, except during start-up and shutdown.

Applicable Compliance Method:

If required, the permittee shall demonstrate compliance by testing in accordance with Method 9 of 40 CFR Part 60, Appendix A.

- f. Emission Limitation: 0.031 lb PE/mmBTU of actual heat input

Applicable Compliance Method: The lbs PE/mmBtu emission limitation represents the potential to emit\* for this emissions unit. Therefore no hourly recordkeeping, deviation reporting, or compliance method calculations are required to demonstrate compliance with this limitation.

\*Potential to emit was determined using AP-42, Chapter 3.3, Table 3.3-1 (revised 10/96).

If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1 - 5 of 40 CFR Part 60, Appendix A.

## **F. Miscellaneous Requirements**

1. Pursuant to Ohio Administrative Code (OAC) rule 3745-31-03(A)(1)(p)(i), the permittee of a portable or mobile emissions unit may relocate within the State of Ohio without first obtaining a PTI providing the following criteria are met:
  - a. the portable emissions unit is equipped with the best available control technology for such portable emissions unit;
  - b. the portable emissions unit is operating pursuant to a currently effective permit to install, permit to operate or registration;
  - c. the applicant has provided proper notice of intent to relocate the portable emissions unit to the Northwest District Office (NWDO) and the appropriate field office having jurisdiction over the new site within a minimum of thirty days prior to the scheduled relocation; and,
  - d. in the -NWDO's and the appropriate field office's judgement, the proposed site is acceptable under the rule 3745-15-07 of the Administrative Code.
2. In the alternative, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), the permittee of a portable or mobile emissions unit may relocate within the State of Ohio without first obtaining a PTI providing the following criteria of OAC rule 3745-31-05(F) are met:
  - a. the portable emissions unit permittee possesses an Ohio EPA PTI, PTO or registration status;

- b. the portable emissions unit is equipped with best available technology;
- c. the portable emission unit owner has identified the proposed site to Ohio EPA;
- d. Ohio EPA has determined that the portable emissions unit, at the proposed site, will have an acceptable environmental impact;
- e. a public notice, consistent with Chapter 3745-47 of the Administrative Code, is published in the county where the proposed site is located;
- f. the owner of the proposed site has provided the portable emissions unit owner with approval or equivalent declaration that it is acceptable to the site owner to move the portable emissions unit to the proposed site; and,
- g. the portable emissions unit owner has provided the Ohio EPA with fifteen days written notice of the relocation.

Any site approvals issued by the Ohio EPA, pursuant to section F.2. above, shall be valid for no longer than three years and are subject to renewal.

- 3. In order for the NWDO and the appropriate field office having jurisdiction over the new site to determine compliance with all of the above criteria, the owner or operator of the portable or mobile emissions unit must file a "Notice of Intent to Relocate", within the specified time frame (30 or 15 days) prior to the relocation of the emissions unit with the NWDO (347 North Dunbridge Road, Bowling Green, OH 43402) and the appropriate office having jurisdiction over the new site. Upon receipt of the notice, the NWDO and/or the appropriate field office having jurisdiction over the new site, will evaluate the request in accordance with the above criteria.
- 4. The permittee should be advised that when portable emission units are located at a stationary source or at a source comprised of portable emission units, potential emissions from the portable emission units are included in the facility potential to emit calculations for Title V and PSD applicability.  
  
The permittee shall include a potential to emit analysis of facility-wide emissions (including the portable sources) for the proposed relocation in the "Notice of Intent to Relocate".
- 5. The following terms and conditions are federally enforceable: A.1, B.1, C.2, D.1, E.1.c

41

**Bluffton Stone Company**  
**PTI Application: 02 16221**  
**Issue**

**Facility ID: 0302950002**

**Emissions Unit ID: P001**

and E.1.d.