



State of Ohio Environmental Protection Agency

Franklin County

RE: Final Permit to Install

Street
1800 \
Column

Address:
149
16-1049

Application No: **01-7450**

DATE: February 24, 1999

**Georgia-Pacific Resins, Inc.
Greg Miller
1975 Watkins Road
Columbus, OH 43207**

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Director's action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
236 East Town Street, Room 300
Columbus, Ohio 43215

Very truly yours,

Thomas G. Rigo, Manager
Field Operations and Permit Section
Division of Air Pollution Control

cc: USEPA
Ohio EPA, Central District Office



STATE OF OHIO ENVIRONMENTAL PROTECTION AGENCY

Application Number: 01-7450

Permit
Title

APS Premise Number: 0125040904

Permit Fee: **\$1800.00**

Name of Facility: Georgia-Pacific Resins, Inc.

Person to Contact: Greg Miller

Address: 1975 Watkins Road
Columbus, OH 43207

Location of proposed air contaminant source(s) [emissions unit(s)]:

**1975 WATKINS ROAD
COLUMBUS, OHIO**

Description of proposed emissions unit(s):

REPLACEMENT OF SIX 25,000 GALLON RESIN STORAGE TANKS VENTED TO THERMAL OXIDIZER.

Date of Issuance: February 24, 1999

Issuance:

Effective Date: February 24, 1999

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon

the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources are inadequate or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities prove to be inadequate or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit to Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of

Georgia-Pacific Resins, Inc.

PTI Application 01-7450

February 24, 1999

Facility ID: 0125040904

Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within thirty (30) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
OC	1.0

Part II: Special Terms and Conditions

A. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
25,000 gallon resin storage tank C17	40CFR60 Subpart Kb OAC 3745-31-05 Consent Order 96CVH053988	See C.3. and D.1. below. See A.2. below. 98 percent destruction of organic compounds across thermal oxidizer or 20 ppm at outlet, See F.1. below.

2. Additional Terms and Conditions

- a. The permittee shall vent tank emissions to the thermal oxidizer at all times that resins are transferred and stored.

B. Operational Restrictions

- 1. The average combustion temperature within the thermal incinerator, for any 3-hour block of time when the emissions unit is in operation, shall not be less than 795 degrees Celsius.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall operate and maintain a continuous temperature monitor and

Georgia-Pacific Resins, Inc.

PTI Application 01-7450

February 24, 1999

Facility ID: **0125040904**

recorder which measures and records the combustion temperature within the thermal incinerator when the emissions unit is in operation. Units shall be in degrees Celsius. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

2. The permittee shall collect and record the following information for each day:

Georgia-Pacific Resins, Inc.

PTI Application 01-7450

February 24, 1999

Facility ID: 0125040904

- a. all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator, when the emissions unit was in operation, was less than 795 degrees Celsius; and,
 - b. a log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
3. The permittee shall maintain records of the following information.
 - a. the types of all petroleum liquids stored in the tank; and,
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.

D. Reporting Requirements

1. If the permittee places, stores, or holds in the fixed roof tank any petroleum liquid with a true vapor pressure which is greater than 1.52 pounds per square inch absolute, and such tank does not comply with the requirements of paragraph (L)(1) of OAC rule 3745-21-09, the permittee shall notify the Director (the Ohio EPA Central District Office) within 30 days of becoming aware of the occurrence.
2. The permittee shall submit deviation (excursion) reports which identify all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator does not comply with the temperature limitation specified above.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

Emission Limitation

The minimum 98 percent destruction of organic compounds across thermal oxidizer or 20 ppm at outlet shall be demonstrated by emission testing, as follows:

Applicable Compliance Method

The permittee conducted emission testing for this emissions unit in accordance with the

following requirements:

- a. the emission testing was conducted February 4, 1997;
- b. the emission testing was conducted to demonstrate compliance with the 98% OC destruction efficiency;
- c. the following test method(s) were employed to demonstrate compliance with the allowable mass emission rate(s): 40 CFR 60 Method 25a;
- d. the test(s) was conducted while the emissions unit operated at or near its maximum capacity. A comprehensive written report on the results of the emissions test(s) was signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office; and,
- e. the thermal oxidizer will be tested as scheduled for the two resin kettles that also vent to the thermal oxidizer.

F. Miscellaneous Requirements

1. Replaces storage tank identified as T001 in Consent Order 96CV05-3988.

Georgia-Pacific Resins, Inc
 PTI Application Number: **01-7450**
 February 24, 1999

Part II: Special Terms and Conditions

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
25,000 gallon resin storage tank C24	40CFR60 Subpart Kb	See C.3. and D.1. below.
	OAC 3745-31-05	See A.2. below.
	Consent 96CVH053988	Order 98 percent destruction of organic compounds across thermal oxidizer or 20 ppm at outlet, See F.1. below.

2. **Additional Terms and Conditions**

- a. The permittee shall vent tank emissions to the thermal oxidizer at all times that resins are transferred and stored.

B. Operational Restrictions

1. The average combustion temperature within the thermal incinerator, for any 3-hour block of time when the emissions unit is in operation, shall not be less than 795 degrees Celsius.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the thermal

Georgia-Pacific Resins, IncPTI Application Number: **01-7450**

February 24, 1999

- incinerator when the emissions unit is in operation. Units shall be in degrees Celsius. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.
2. The permittee shall collect and record the following information for each day:
 - a. all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator, when the emissions unit was in operation, was less than 795 degrees Celsius; and,
 - b. a log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
 3. The permittee shall maintain records of the following information.
 - a. the types of all petroleum liquids stored in the tank; and,
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.

D. Reporting Requirements

1. If the permittee places, stores, or holds in the fixed roof tank any petroleum liquid with a true vapor pressure which is greater than 1.52 pounds per square inch absolute, and such tank does not comply with the requirements of paragraph (L)(1) of OAC rule 3745-21-09, the permittee shall notify the Director (the Ohio EPA Central District Office) within 30 days of becoming aware of the occurrence.
2. The permittee shall submit deviation (excursion) reports which identify all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator does not comply with the temperature limitation specified above.

Georgia-Pacific Resins, IncPTI Application Number: **01-7450**

February 24, 1999

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

Emission Limitation

The minimum 98 percent destruction of organic compounds across thermal oxidizer or 20 ppm at outlet shall be demonstrated by emission testing, as follows:

Applicable Compliance Method

The permittee conducted emission testing for this emissions unit in accordance with the following requirements:

- a. the emission testing was conducted February 4, 1997;
- b. the emission testing was conducted to demonstrate compliance with the 98% OC destruction efficiency;
- c. the following test method(s) were employed to demonstrate compliance with the allowable mass emission rate(s): 40 CFR 60 Method 25a.;
- d. the test(s) was conducted while the emissions unit operated at or near its maximum capacity. A comprehensive written report on the results of the emissions test(s) was signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office; and,
- e. the thermal oxidizer will be tested as scheduled for the two resin kettles that also vent to the thermal oxidizer.

F. Miscellaneous Requirements

1. Replaces storage tank identified as T003 in Consent Order 96CV05-3988.

Georgia-Pacific Resins, Inc
PTI Application Number: **01-7450**
February 24, 1999

Part II: Special Terms and Conditions

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
25,000 gallon resin storage tank C20	40CFR60 Subpart Kb	See C.3. and D.1. below.
	OAC 3745-31-05	See A.2. below
	Consent 96CVH053988	Order 98 percent destruction of organic compounds across thermal oxidizer or 20 ppm at outlet, See F.1. below.

2. **Additional Terms and Conditions**

- a. The permittee shall vent tank emissions to the thermal oxidizer at all times that resins are transferred and stored.

B. Operational Restrictions

1. The average combustion temperature within the thermal incinerator, for any 3-hour block of time when the emissions unit is in operation, shall not be less than 795 degrees Celsius.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the thermal

Georgia-Pacific Resins, IncPTI Application Number: **01-7450**

February 24, 1999

- incinerator when the emissions unit is in operation. Units shall be in degrees Celsius. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.
2. The permittee shall collect and record the following information for each day:
 - a. all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator, when the emissions unit was in operation, was less than 795 degrees Celsius; and,
 - b. a log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
 3. The permittee shall maintain records of the following information.
 - a. the types of petroleum liquids stored in the tank; and,
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.

D. Reporting Requirements

1. If the permittee places, stores, or holds in the fixed roof tank any petroleum liquid with a true vapor pressure which is greater than 1.52 pounds per square inch absolute, and such tank does not comply with the requirements of paragraph (L)(1) of OAC rule 3745-21-09, the permittee shall notify the Director (the Ohio EPA Central District Office) within 30 days of becoming aware of the occurrence.
2. The permittee shall submit deviation (excursion) reports which identify all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator does not comply with the temperature limitation specified above.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

Georgia-Pacific Resins, IncPTI Application Number: **01-7450**

February 24, 1999

Emission Limitation

The minimum 98 percent destruction of organic compounds across thermal oxidizer or 20 ppm organic compounds at outlet shall be demonstrated by emission testing.

Applicable Compliance Method

The permittee conducted emission testing for this emissions unit in accordance with the following requirements:

- a. the emission testing was conducted February 4, 1997;

Georgia-Pacific Resins, IncPTI Application Number: **01-7450**

February 24, 1999

- b. the emission testing shall be conducted to demonstrate compliance with the 98% OC destruction efficiency;
- c. the following test method(s) were employed to demonstrate compliance with the allowable mass emission rate(s): 40 CFR 60 Method 25a.;
- d. the test(s) was conducted while the emissions unit operated at or near its maximum capacity. A comprehensive written report on the results of the emissions test(s) was signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office; and,
- e. the thermal oxidizer will be tested as scheduled for the two resin kettles that also vent to the thermal oxidizer.

F. Miscellaneous Requirements

1. Replaces storage tank identified as T011 in Consent Order 96CV05-3988.

Georgia-Pacific Resins, Inc
 PTI Application Number: **01-7450**
 February 24, 1999

Part II: Special Terms and Conditions

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
25,000 gallon resin storage tank C21	40CFR60 Subpart Kb	See C.3. and D.1. below.
	OAC 3745-31-05	See A.2. below
	Consent 96CVH053988	Order 98 percent destruction of organic compounds across thermal oxidizer or 20 ppm at outlet, See F.1. below.

2. **Additional Terms and Conditions**

- a. The permittee shall vent tank emissions to the thermal oxidizer at all times that resins are transferred and stored.

B. Operational Restrictions

1. The average combustion temperature within the thermal incinerator, for any 3-hour block of time when the emissions unit is in operation, shall not be less than 795 degrees Celsius.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the thermal

Georgia-Pacific Resins, IncPTI Application Number: **01-7450**

February 24, 1999

incinerator when the emissions unit is in operation. Units shall be in degrees Celsius. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

2. The permittee shall collect and record the following information for each day:
 - a. all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator, when the emissions unit was in operation, was less than 795 degrees Celsius; and,
 - b. a log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
3. The permittee shall maintain records of the following information:
 - a. the types of petroleum liquids stored in the tank; and,
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.

D. Reporting Requirements

1. If the permittee places, stores, or holds in the fixed roof tank any petroleum liquid with a true vapor pressure which is greater than 1.52 pounds per square inch absolute, and such tank does not comply with the requirements of paragraph (L)(1) of OAC rule 3745-21-09, the permittee shall notify the Director (the Ohio EPA Central District Office) within 30 days of becoming aware of the occurrence.
2. The permittee shall submit deviation (excursion) reports which identify all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator does not comply with the temperature limitation specified above.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

Georgia-Pacific Resins, IncPTI Application Number: **01-7450**

February 24, 1999

Emission Limitation

The minimum 98 percent destruction of organic compounds across thermal oxidizer or 20 ppm organic compounds at outlet shall be demonstrated by emission testing:

Applicable Compliance Method

The permittee conducted emission testing for this emissions unit in accordance with the following requirements:

- a. the emission testing was conducted 2/4/97;
- b. the emission testing shall be conducted to demonstrate compliance with the 98 percent OC destruction efficiency;
- c. the following test method(s) were employed to demonstrate compliance with the allowable mass emission rate(s): 40 CFR 60 Method 25a;
- d. the test(s) was conducted while the emissions unit operated at or near its maximum capacity. A comprehensive written report on the results of the emissions test(s) was signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office; and,
- e. the thermal oxidizer will be tested as scheduled for the two resin kettles that also vent to the thermal oxidizer.

F. Miscellaneous Requirements

1. Replaces storage tank identified as T011 in Consent Order 96CV05-3988.

Georgia-Pacific Resins, Inc
 PTI Application Number: **01-7450**
 February 24, 1999

Facility ID: **0125040904**
 Emissions Unit ID: **T061**

Part II: Special Terms and Conditions

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
25,000 gallon resin storage tank C42	40CFR60 Subpart Kb	See C.3. and D.1. below.
	OAC 3745-31-05	See A.2. below.
	Consent 96CVH053988	Order 98 percent destruction of organic compounds across thermal oxidizer or 20 ppm at outlet, See F.1. below.

2. Additional Terms and Conditions

- a. The permittee shall vent tank emissions to the thermal oxidizer at all times that resins are transferred and stored.

B. Operational Restrictions

1. The average combustion temperature within the thermal incinerator, for any 3-hour block of time when the emissions unit is in operation, shall not be less than 795 degrees Celsius.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the thermal

Georgia-Pacific Resins, IncPTI Application Number: **01-7450**

February 24, 1999

incinerator when the emissions unit is in operation. Units shall be in degrees Celsius. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

2. The permittee shall collect and record the following information for each day:
 - a. all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator, when the emissions unit was in operation, was less than 795 degrees Celsius; and,
 - b. a log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
3. The permittee shall maintain records of the following information:
 - a. the types of all petroleum liquids stored in the tank; and,
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.

D. Reporting Requirements

1. If the permittee places, stores, or holds in the fixed roof tank any petroleum liquid with a true vapor pressure which is greater than 1.52 pounds per square inch absolute, and such tank does not comply with the requirements of paragraph (L)(1) of OAC rule 3745-21-09, the permittee shall notify the Director (the Ohio EPA Central District Office) within 30 days of becoming aware of the occurrence.
2. The permittee shall submit deviation (excursion) reports which identify all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator does not comply with the temperature limitation specified above.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

Georgia-Pacific Resins, IncPTI Application Number: **01-7450**

February 24, 1999

Emission Limitation

The minimum 98 percent destruction of organic compounds across thermal oxidizer or 20 ppm at outlet shall be demonstrated by emission testing, as follows:

Applicable Compliance Method

The permittee conducted emission testing for this emissions unit in accordance with the following requirements:

- a. the emission testing was conducted 2/4/97;

Georgia-Pacific Resins, IncPTI Application Number: **01-7450**

February 24, 1999

- b. the emission testing shall be conducted to demonstrate compliance with the 98 percent destruction efficiency;
- c. the following test method(s) were employed to demonstrate compliance with the allowable mass emission rate(s): 40 CFR 60 Method 25a;
- d. the test(s) was conducted while the emissions unit operated at or near its maximum capacity, unless otherwise specified or approved by the appropriate Ohio EPA District Office or local air agency; and,
- e. a comprehensive written report on the results of the emissions test(s) was signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office or local air agency within 30 days following completion of the test(s).

F. Miscellaneous Requirements

1. Replaces storage tank identified as T012 in Consent Order 96CV05-3988.

Georgia-Pacific Resins, Inc
 PTI Application Number: **01-7450**
 February 24, 1999

Part II: Special Terms and Conditions

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
25,000 gallon resin storage tank C43	40CFR60 Subpart Kb	See C.3. and D.1. below.
	OAC 3745-31-05	See A.2. below.
	Consent 96CVH053988	Order 98 percent destruction of organic compounds across thermal oxidizer or 20 ppm at outlet, See F.1. below.

2. Additional Terms and Conditions

- a. The permittee shall vent tank emissions to the thermal oxidizer at all times that resins are transferred and stored.

B. Operational Restrictions

1. The average combustion temperature within the thermal incinerator, for any 3-hour block of time when the emissions unit is in operation, shall not be less than 795 degrees Celsius.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the thermal incinerator when the emissions unit is in operation. Units shall be in degrees Celsius.

Georgia-Pacific Resins, IncPTI Application Number: **01-7450**

February 24, 1999

The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

2. The permittee shall collect and record the following information for each day:

Georgia-Pacific Resins, IncPTI Application Number: **01-7450**

February 24, 1999

- a. all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator, when the emissions unit was in operation, was less than 795 degrees Celsius; and,
 - b. a log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
3. The permittee shall maintain records of the following information.
 - a. the types of petroleum liquids stored in the tank; and,
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.

D. Reporting Requirements

1. If the permittee places, stores, or holds in the fixed roof tank any petroleum liquid with a true vapor pressure which is greater than 1.52 pounds per square inch absolute, and such tank does not comply with the requirements of paragraph (L)(1) of OAC rule 3745-21-09, the permittee shall notify the Director (the Ohio EPA Central District Office) within 30 days of becoming aware of the occurrence.
2. The permittee shall submit deviation (excursion) reports which identify all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator does not comply with the temperature limitation specified above.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

Emission Limitation

The minimum 98 percent destruction of organic compounds across thermal oxidizer or 20 ppm at outlet shall be demonstrated by emission testing, as follows:

Applicable Compliance Method

The permittee conducted emission testing for this emissions unit in accordance with the

Georgia-Pacific Resins, IncPTI Application Number: **01-7450**

February 24, 1999

following requirements:

- a. the emission testing was conducted February 4, 1997;
- b. the emission testing was conducted to demonstrate compliance with the 98% OC destruction efficiency;
- c. the following test method(s) were employed to demonstrate compliance with the allowable mass emission rate(s): 40 CFR 60 Method 25a;
- d. the test(s) was conducted while the emissions unit operated at or near its maximum capacity, unless otherwise specified or approved by the appropriate Ohio EPA District Office. A comprehensive written report on the results of the emissions test(s) was signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office; and,
- e. the thermal oxidizer will be tested as scheduled for the two resin kettles that also vent to the thermal oxidizer.

F. Miscellaneous Requirements

1. Replaces storage tank identified as Z052 in Consent Order 96CV05-3988.