Ohio Environmental Protection Agency
John R. Kasich, Governor
Mary Taylor, Lt. Governor
Scott J. Nally, Director

Certified Mail

6/29/2012

ALORA MILLER
AKRON BRASS CO
PO BOX 86
WOOSTER, OH 44691

No	TOXIC REVIEW
No	PSD
No	SYNTHETIC MINOR TO AVOID MAJOR NSR
No	CEMS
No	MACT/GACT
No	NSPS
No	NESHAPS
No	NETTING
No	MAJOR NON-ATTAINMENT
No	MODELING SUBMITTED
No	SYNTHETIC MINOR TO AVOID TITLE V
No	FEDERALLY ENFORCABLE PTIO (FEPTIO)
No	SYNTHETIC MINOR TO AVOID MAJOR GHG

RE: FINALAIR POLLUTION PERMIT-TO-INSTALL AND OPERATE
Facility ID: 0285030223
Permit Number: P0108201
Permit Type: Renewal
County: Wayne

Dear Permit Holder:

Enclosed please find a final Air Pollution Permit-to-Install and Operate (PTIO) which will allow you to install, modify, and/or operate the described emissions unit(s) in the manner indicated in the permit. Because this permit contains conditions and restrictions, please read it very carefully. Please complete a survey at www.epa.ohio.gov/dapc/permitsurvey.aspx and give us feedback on your permitting experience. We value your opinion.

The issuance of this PTI is a final action of the Director and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. The appeal must be filed with the Commission within thirty (30) days after notice of the Director's action. The appeal must be accompanied by a filing fee of $70.00, made payable to “Ohio Treasurer Josh Mandel," which the Commission, in its discretion, may reduce if by affidavit you demonstrate that payment of the full amount of the fee would cause extreme hardship. Notice of the filing of the appeal shall be filed with the Director within three (3) days of filing with the Commission. Ohio EPA requests that a copy of the appeal be served upon the Ohio Attorney General’s Office, Environmental Enforcement Section. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, OH 43215

If you have any questions, please contact Ohio EPA DAPC, Northeast District Office at (330)425-9171or the Office of Compliance Assistance and Pollution Prevention at (614) 644-3469. This permit can be accessed electronically on the DAPCWeb page,www.epa.ohio.gov/dapc, by clicking the "Issued Air Pollution Control Permits" link.

Sincerely,

Michael W. Ahern

Michael W. Ahern, Manager
Permit Issuance and Data Management Section, DAPC

Cc: Ohio EPA-NEDO

Ohio | Environmental Protection Agency

FINAL

Division of Air Pollution Control
Permit-to-Install and Operate
for
AKRON BRASS CO

Facility ID:	0285030223
Permit Number:	P0108201
Permit Type:	Renewal
Issued:	6/29/2012
Effective:	6/29/2012
Expiration:	6/28/2022

Ohio Environmental Protection Agency

Division of Air Pollution Control
Permit-to-Install and Operate
for
AKRON BRASS CO

Table of Contents

Authorization 1

A. Standard Terms and Conditions 3

1. What does this permit-to-install and operate ("PTIO") allow me to do? 4
2. Who is responsible for complying with this permit? 4
3. What records must I keep under this permit? 4
4. What are my permit fees and when do I pay them? 4
5. When does my PTIO expire, and when do I need to submit my renewal application? 4
6. What happens to this permit if my project is delayed or I do not install or modify my source? 5
7. What reports must I submit under this permit? 5
8. If I am required to obtain a Title V operating permit in the future, what happens to the operating provisions and PER obligations under this permit? 5
9. What are my obligations when I perform scheduled maintenance on air pollution control equipment? 5
10. Do I have to report malfunctions of emissions units or air pollution control equipment? If so, how must I report? 6
11. Can Ohio EPA or my local air agency inspect the facility where the emission unit(s) is/are located? 6
12. What happens if one or more emissions units operated under this permit is/are shut down permanently? 6
13. Can I transfer this permit to a new owner or operator? 7
14. Does compliance with this permit constitute compliance with OAC rule 3745-15-07, "air pollution nuisance"? 7
15. What happens if a portion of this permit is determined to be invalid? 7

B. Facility-Wide Terms and Conditions 8

C. Emissions Unit Terms and Conditions 10

1. P003, Sand Handling System For Brass Foundry 11
2. P004, Grinding Operations 16
3. P006, Electric Induction Furnace #1 22
4. P007, Electric Induction Furnace #2 27
5. P008, East Barrel Blast Machine 32
6. P009, Pouring & Cooling Line 38
7. P010, Shakeout operations 44
8. P011, Chip Dryer 50

Authorization

Facility ID: 0285030223
Application Number(s): A0041972
Permit Number: P0108201
Permit Description: Renewal permits for misc sources at Akron Brass (brass/bronze foundry)
Permit Type: Renewal
Permit Fee: $0.00
Issue Date: 6/29/2012
Effective Date: 6/29/2012
Expiration Date: 6/28/2022
Permit Evaluation Report (PER) Annual Date: Apr 1 - Mar 31, Due May 15

This document constitutes issuance to:

AKRON BRASS CO
1415 East BOWMAN ST
Wooster, OH 44691

of a Permit-to-Install and Operate for the emissions unit(s) identified on the following page.

Ohio EPA District Office or local air agency responsible for processing and administering your permit:

Ohio EPA DAPC, Northeast District Office
2110 East Aurora Road
Twinsburg, OH 44087
(330)425-9171

The above named entity is hereby granted this Permit-to-Install and Operate for the air contaminant source(s) (emissions unit(s))listed in this section pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the described emissions unit(s) will operate in compliance with applicable State and federal laws and regulations.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Scott J. Nally
Director

Authorization (continued)

Permit Number: P0108201
Permit Description: Renewal permits for misc sources at Akron Brass (brass/bronze foundry)

Permits for the following Emissions Unit(s) or groups of Emissions Units are in this document as indicated below:

Emissions Unit ID:	**P003**
Company Equipment ID:	Sand Handling System For Brass Foundry
Superseded Permit Number:	P0086529
General Permit Category and Type:	Not Applicable
Emissions Unit ID:	**P004**
Company Equipment ID:	Grinding Operations
Superseded Permit Number:	P0086529
General Permit Category and Type:	Not Applicable
Emissions Unit ID:	**P006**
Company Equipment ID:	Electric Induction Furnace #1
Superseded Permit Number:	P0086529
General Permit Category and Type:	Not Applicable
Emissions Unit ID:	**P007**
Company Equipment ID:	Electric Induction Furnace #2
Superseded Permit Number:	P0086529
General Permit Category and Type:	Not Applicable
Emissions Unit ID:	**P008**
Company Equipment ID:	East Barrel Blast Machine
Superseded Permit Number:	P0086529
General Permit Category and Type:	Not Applicable
Emissions Unit ID:	**P009**
Company Equipment ID:	Pouring & Cooling Line
Superseded Permit Number:	P0086529
General Permit Category and Type:	Not Applicable
Emissions Unit ID:	**P010**
Company Equipment ID:	Shakeout operations
Superseded Permit Number:	P0086529
General Permit Category and Type:	Not Applicable
Emissions Unit ID:	**P011**
Company Equipment ID:	Chip Dryer
Superseded Permit Number:	P0086529
General Permit Category and Type:	Not Applicable

A. Standard Terms and Conditions

1. What does this permit-to-install and operate ("PTIO") allow me to do?

This permit allows you to install and operate the emissions unit(s) identified in this PTIO. You must install and operate the unit(s) in accordance with the application you submitted and all the terms and conditions contained in this PTIO, including emission limits and those terms that ensure compliance with the emission limits (for example, operating, recordkeeping and monitoring requirements).

2. Who is responsible for complying with this permit?

The person identified on the "Authorization" page, above, is responsible for complying with this permit until the permit is revoked, terminated, or transferred. "Person" means a person, firm, corporation, association, or partnership. The words "you," "your," or "permittee" refer to the "person" identified on the "Authorization" page above.

The permit applies only to the emissions unit(s) identified in the permit. If you install or modify any other equipment that requires an air permit, you must apply for an additional PTIO(s) for these sources.

3. What records must I keep under this permit?

You must keep all records required by this permit, including monitoring data, test results, strip-chart recordings, calibration data, maintenance records, and any other record required by this permit for five years from the date the record was created. You can keep these records electronically, provided they can be made available to Ohio EPA during an inspection at the facility. Failure to make requested records available to Ohio EPA upon request is a violation of this permit requirement.

4. What are my permit fees and when do I pay them?

There are two fees associated with permitted air contaminant sources in Ohio:

PTIO fee. This one-time fee is based on a fee schedule in accordance with Ohio Revised Code (ORC) section 3745.11, or based on a time and materials charge for permit application review and permit processing if required by the Director.

You will be sent an invoice for this fee after you receive this PTIO and payment is due within 30 days of the invoice date. You are required to pay the fee for this PTIO even if you do not install or modify your operations as authorized by this permit.

Annual emissions fee. Ohio EPA will assess a separate fee based on the total annual emissions from your facility. You self-report your emissions in accordance with Ohio Administrative Code (OAC) Chapter 3745-78. This fee assessed is based on a fee schedule in ORC section 3745.11 and funds Ohio EPA's permit compliance oversight activities. Unless otherwise specified, facilities subject to one or more synthetic minor restrictions must use Ohio EPA's "Air Services" to submit annual emissions associated with this permit requirement.Ohio EPA will notify you when it is time to report your emissions and to pay your annual emission fees.

5. When does my PTIO expire, and when do I need to submit my renewal application?

This permit expires on the date identified at the beginning of this permit document (see "Authorization" page above) and you must submit a renewal application to renew the permit. Ohio EPA will send a renewal notice to you approximately six months prior to the expiration date of this permit. However, it is

very important that you submit a complete renewal permit application (postmarked prior to expiration of this permit) even if you do not receive the renewal notice.

If a complete renewal application is submitted before the expiration date, Ohio EPA considers this a timely application for purposes of ORC section 119.06, and you are authorized to continue operating the emissions unit(s) covered by this permit beyond the expiration date of this permit until final action is takenby Ohio EPA on the renewal application.

6. What happens to this permit if my project is delayed or I do not install or modify my source?

This PTIO expires 18 months after the issue date identified on the "Authorization" page above unless otherwise specified if you have not (1) started constructing the new or modified emission sources identified in this permit, or (2) entered into a binding contract to undertake such construction. This deadline can be extended by up to 12 months, provided you apply to Ohio EPA for this extension within a reasonable time before the 18-month period has ended and you can show good cause for any such extension.

7. What reports must I submit under this permit?

An annual permit evaluation report (PER) is required in addition to any malfunction reporting required by OAC rule 3745-15-06 or other specific rule-based reporting requirement identified in this permit. Your PER due date is identified in the Authorization section of this permit.

8. If I am required to obtain a Title V operating permit in the future, what happens to the operating provisions and PER obligations under this permit?

If you are required to obtain a Title V permit under OAC Chapter 3745-77 in the future, the permit-to-operate portion of this permit will be superseded by the issued Title V permit. From the effective date of the Title V permit forward, this PTIO will effectively become a PTI (permit-to-install) in accordance with OAC rule 3745-31-02(B). The following terms and conditions will no longer be applicable after issuance of the Title V permit: Section B, Term 1.b) and Section C, for each emissions unit, Term a)(2).

The PER requirements in this permit remain effective until the date the Title V permit is issued and is effective, and cease to apply after the effective date of the Title V permit. The final PER obligation will cover operations up to the effective date of the Title V permit and must be submitted on or before the submission deadline identified in this permit on the last day prior to the effective date of the Title V permit.

9. What are my obligations when I perform scheduled maintenance on air pollution control equipment?

You must perform scheduled maintenance of air pollution control equipment in accordance with OAC rule 3745-15-06(A). If scheduled maintenance requires shutting down or bypassing any air pollution control equipment, you must also shut down the emissions unit(s) served by the air pollution control equipment during maintenance, unless the conditions of OAC rule 3745-15-06(A)(3) are met. Any emissions that exceed permitted amount(s) under this permit (unless specifically exempted by rule) must be reported as deviations in the annual permit evaluation report (PER), including nonexempt excess emissions that occur during approved scheduled maintenance.

10. Do I have to report malfunctions of emissions units or air pollution control equipment? If so, how must I report?

If you have a reportable malfunction of any emissions unit(s) or any associated air pollution control system, you must report this to the Ohio EPA DAPC, Northeast District Office in accordance with OAC rule 3745-15-06(B). Malfunctions that must be reported are those that result in emissions that exceed permitted emission levels. It is your responsibility to evaluate control equipment breakdowns and operational upsets to determine if a reportable malfunction has occurred.

If you have a malfunction, but determine that it is not a reportable malfunction under OAC rule 3745-15-06(B), it is recommended that you maintain records associated with control equipment breakdown or process upsets. Although it is not a requirement of this permit, Ohio EPA recommends that you maintain records for non-reportable malfunctions.

11. Can Ohio EPA or my local air agency inspect the facility where the emission unit(s) is/are located?

Yes. Under Ohio law, the Director or his authorized representative may inspect the facility, conduct tests, examine records or reports to determine compliance with air pollution laws and regulations and the terms and conditions of this permit. You must provide, within a reasonable time, any information Ohio EPA requests either verbally or in writing.

12. What happens if one or more emissions units operated under this permit is/are shut down permanently?

Ohio EPA can terminate the permit terms associated with any permanently shut down emissions unit. "Shut down" means the emissions unit has been physically removed from service or has been altered in such a way that it can no longer operate without a subsequent "modification" or "installation" as defined in OAC Chapter 3745-31.

You should notify Ohio EPA of any emissions unit that is permanently shut down by submitting[1] a certification that identifies the date on which the emissions unit was permanently shut down. The certification must be submitted by an authorized official from the facility. You cannot continue to operate an emissions unit once the certification has been submitted to Ohio EPA by the authorized official.

You must comply with all recordkeeping and reporting for any permanently shut down emissions unit in accordance with the provisions of the permit, regulations or laws that were enforceable during the period of operation, such as the requirement to submit a PER, air fee emission report, or malfunction report. You must also keep all records relating to any permanently shutdown emissions unit, generated while the emissions unit was in operation, for at least five years from the date the record was generated.

Again, you cannot resume operation of any emissions unit certified by the authorized official as being permanently shut down without first applying for and obtaining a permit pursuant to OAC Chapter 3745-31.

[1]Permittees that use Ohio EPA's "Air Services" can mark the affected emissions unit(s) as "permanently shutdown" in the facility profile along with the date the emissions unit(s) was permanently removed and/or disabled. Submitting the facility profile update will constitute notifying of the permanent shutdown of the affected emissions unit(s).

13. Can I transfer this permit to a new owner or operator?

You can transfer this permit to a new owner or operator. If you transfer the permit, you must follow the procedures in OAC Chapter 3745-31, including notifying Ohio EPA or the local air agency of the change in ownership or operator. Any transferee of this permit must assume the responsibilities of the transferor permit holder.

14. Does compliance with this permit constitute compliance with OAC rule 3745-15-07, "air pollution nuisance"?

This permit and OAC rule 3745-15-07 prohibit operation of the air contaminant source(s) regulated under this permit in a manner that causes a nuisance. Ohio EPA can require additional controls or modification of the requirements of this permit through enforcement orders or judicial enforcement action if, upon investigation, Ohio EPA determines existing operations are causing a nuisance.

15. What happens if a portion of this permit is determined to be invalid?

If a portion of this permit is determined to be invalid, the remainder of the terms and conditions remain valid and enforceable. The exception is where the enforceability of terms and conditions are dependent on the term or condition that was declared invalid.

B. Facility-Wide Terms and Conditions

1. This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

   a) For the purpose of a permit-to-install document, the facility-wide terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

      (1) None.

   b) For the purpose of a permit-to-operate document, the facility-wide terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

      (1) None.

C. Emissions Unit Terms and Conditions

1. P003, Sand Handling System For Brass Foundry

Operations, Property and/or Equipment Description:

Sand Muller, Sand Elevator and conveyor, vibratory screens, pushers, 40 ton hopper

a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

(1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. None.

(2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

a. None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-17-11(B)	11.60 lbs/hr of particulate emissions (PE) See section A.2.a. below.
b.	OAC rule 3745-17-07(A)(1)	Visible emissions from the stack of the baghouse serving this emissions unit shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.

(2) Additional Terms and Conditions

a. The PE limit was calculated using Figure II of OAC rule 3745-17-11(B) and a maximum uncontrolled rate of emission of 82.8 lbs/hr. This emission rate was estimated using a maximum process weight rate of 23 tons per hour and an emission factor of 3.6 lbs of PE/ton of sand processed from AP-42 "Compilation of Air Pollutant Emission Factors," Table 12.10-7.

b. All PE from the sand handling operations shall be captured and vented to the no. 1 west baghouse.

c) Operational Restrictions

(1) None.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall properly install, operate, and maintain equipment to continuously monitor and record the pressure drop, in inches of water, across the baghouse during operation of this emissions unit, including periods of startup and shutdown. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop, in inches of water, across the baghouse on a daily basis.

Whenever the monitored value for the pressure drop deviates from the range specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation:

a. the date and time the deviation began;

b. the magnitude of the deviation at that time;

c. the date(s) the investigation was conducted;

d. the names of the personnel who conducted the investigation; and

e. the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable range specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken:

f. description of the corrective action;

g. the date it was completed;

h. the date and time the deviation ended;

i. the total period of time (in minutes) during which there was a deviation;

j. the pressure drop readings immediately after the corrective action; and

k. the names of the personnel who performed the work.

Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

The acceptable range for the pressure drop across the baghouse is 2.0 to 7.0 inches of

water.

This range is effective for the duration of this permit, unless revisions are requested by the permittee and approved in writing by the appropriate Ohio EPA District Office or local air agency. The permittee may request revisions to the range based upon information obtained during future particulate emission tests that demonstrate compliance with the allowable particulate emission rate for this emissions unit. In addition, approved revisions to the range will not constitute a relaxation of the monitoring requirements of this permit and may be incorporated into this permit by means of an administrative modification.

(2) The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:

a. the color of the emissions;

b. whether the emissions are representative of normal operations;

c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;

d. the total duration of any visible emission incident; and

e. any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item d above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

e) Reporting Requirements

(1) The permittee shall identify in the annual permit evaluation report the following information concerning the operations of the baghouse during the 12-month reporting period for this/these emissions unit(s):

a. each period of time (start time and date, and end time and date) when the pressure drop across the baghouse was outside of the acceptable range;

b. any period of time (start time and date, and end time and date) when the emissions unit(s) was/were in operation and the process emissions were not vented to the baghouse;

c. each incident of deviation described in e)(1)a (above) where a prompt investigation was not conducted;

d. each incident of deviation described in e)(1)a where prompt corrective action, that would bring the pressure drop into compliance with the acceptable range, was determined to be necessary and was not taken; and

e. each incident of deviation described in e)(1)a where proper records were not maintained for the investigation and/or the corrective action(s), as identified in the monitoring and record keeping requirements of this permit.

[OAC rule 3745-15-03(B)(2) and OAC rule 3745-15-03(D)]

(3) The permittee shall identify the following information in the annual permit evaluation report in accordance with the monitoring requirements for visible emissions in term number d)(2) above:

a. all days during which any visible particulate emissions were observed from the stack serving this emissions unit; and

b. any corrective actions taken to minimize or eliminate the visible particulate emissions.

[OAC rule 3745-15-03(B)(2)] and [OAC rule 3745-15-03(D)]

(4) Annual Permit Evaluation Report (PER) forms will be mailed to the permittee at the end of the reporting period specified in the Authorization section of this permit. The permittee shall submit the PER in the form and manner provided by the director by the due date identified in the Authorization section of this permit. The PER shall cover a reporting period of no more than twelve-months for each air contaminant source identified in this permit. It is recommended that the PER is submitted electronically through the Ohio EPA's "e-Business Center: Air Services" although PERs can be submitted via U.S. postal service or can be hand delivered.

f) Testing Requirements

(1) Compliance with the Emissions Limitations and/or Control Requirements specified in section b) of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitation:

11.60 lbs/hr of PE

Applicable Compliance Method:

Compliance with the hourly PE limitation shall be determined using the following equation:
P = PxEFx(1-CE)

where:

PE = hourly emission rate, in lbs/hr;
P = maximum hourly processing rate, 23.0TPH;
EF = emission factor of 3.6 lbs/ton of sand processed, from AP-42 Table 12.10-7;and
CE = fractional control efficiency, 0.99 (manufacturer's estimate).

Compliance may also be determined by stack testing using Method 5 of 40 CFR, Part 60, Appendix A. No stack testing is specifically required by this permit; however, if visible emissions are observed from the baghouse stack, this office may request that stack testing be performed.

(2) Emission Limitation:

Visible emissions from the stack of the baghouse serving this emissions unit shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.

Applicable Compliance Method:

Compliance with the visible emission limitation shall be determined using Method 9 of 40 CFR, Part 60, Appendix A.

g) Miscellaneous Requirements

(1) None.

2. P004, Grinding Operations

Operations, Property and/or Equipment Description:

Abrasive grinding, controlled by a dust collector.

a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

(1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. None.

(2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

a. None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) PTI 02-21711 issued April 11, 2006	Particulate emissions (PE) from this emissions unit shall not exceed 0.12 lb/hr and 0.53 tpy. Lead emissions (Pb) from this emissions unit shall not exceed 0.0083 lb/hr and 0.036 tpy. Visible particulate emissions from the stack serving this emissions unit shall not exceed 0 percent (0%) opacity as a six-minute average.
b.	OAC rule 3745-17-07(A)	The emission limitation required by this applicable rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

c	OAC rule 3745-17-11(B)	The emission limitation required by this applicable rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

(2) Additional Terms and Conditions

a. All PE from the abrasive operations shall be captured and vented to the no. 3 south dust collector.

c) Operational Restrictions

(1) None.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall properly install, operate, and maintain equipment to continuously monitor and record the pressure drop, in inches of water, across the dust collector during operation of this emissions unit, including periods of startup and shutdown. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop, in inches of water, across the baghouse on a daily basis.

Whenever the monitored value for the pressure drop deviates from the range specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation:

a. the date and time the deviation began;

b. the magnitude of the deviation at that time;

c. the date(s) the investigation was conducted;

d. the names of the personnel who conducted the investigation; and

e. the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable range specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken:

f. description of the corrective action;

g. the date it was completed;

h. the date and time the deviation ended;

i. the total period of time (in minutes) during which there was a deviation;

j. the pressure drop readings immediately after the corrective action; and

k. the names of the personnel who performed the work.

Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

The acceptable range for the pressure drop across the baghouse is 4 to 7 inches of water.

This range is effective for the duration of this permit, unless revisions are requested by the permittee and approved in writing by the appropriate Ohio EPA District Office or local air agency. The permittee may request revisions to the range based upon information obtained during future particulate emission tests that demonstrate compliance with the allowable particulate emission rate for this emissions unit. In addition, approved revisions to the range will not constitute a relaxation of the monitoring requirements of this permit and may be incorporated into this permit by means of an administrative modification.

(2) The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:

a. the color of the emissions;

b. whether the emissions are representative of normal operations;

c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;

d. the total duration of any visible emission incident; and

e. any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item d above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

e) Reporting Requirements

(1) The permittee shall identify in the annual permit evaluation report the following information concerning the operations of the baghouse during the 12-month reporting period for this/these emissions unit(s):

a. each period of time (start time and date, and end time and date) when the pressure drop across the baghouse was outside of the acceptable range;

b. any period of time (start time and date, and end time and date) when the emissions unit(s) was/were in operation and the process emissions were not vented to the baghouse;

c. each incident of deviation described in e)(1)a (above) where a prompt investigation was not conducted;

d. each incident of deviation described in e)(1)a where prompt corrective action, that would bring the pressure drop into compliance with the acceptable range, was determined to be necessary and was not taken; and

e. each incident of deviation described in e)(1)a where proper records were not maintained for the investigation and/or the corrective action(s), as identified in the monitoring and record keeping requirements of this permit.

[OAC rule 3745-15-03(B)(2) and OAC rule 3745-15-03(D)]

(2) The permittee shall identify the following information in the annual permit evaluation report in accordance with the monitoring requirements for visible emissions in term number d)(2) above:

a. all days during which any visible particulate emissions were observed from the stack serving this emissions unit; and

b. any corrective actions taken to minimize or eliminate the visible particulate emissions.

[OAC rule 3745-15-03(B)(2)] and [OAC rule 3745-15-03(D)]

(3) Annual Permit Evaluation Report (PER) forms will be mailed to the permittee at the end of the reporting period specified in the Authorization section of this permit. The permittee shall submit the PER in the form and manner provided by the director by the due date identified in the Authorization section of this permit. The PER shall cover a reporting period of no more than twelve-months for each air contaminant source identified in this permit. It is recommended that the PER is submitted electronically through the Ohio EPA's "e-Business Center: Air Services" although PERs can be submitted via U.S. postal service or can be hand delivered.

f) Testing Requirements

(1) Compliance with the Emissions Limitations and/or Control Requirements specified in section b) of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitation:

0.12 lbs/hr and 0.53 tpy of PE

Applicable Compliance Method:

Compliance with the hourly PE limitation shall be determined using the following equation:

PE = PWR*EF*(1-CE)

Where:

PE = hourly emission rate, in lb/hr
PWR = maximum hourly processing rate, 0.7 tph
EF = emission factor of 17 lb/ton of material, from AP-42 Table 12.10-7
CE = fractional control efficiency, 0.99 (conservative as manufacturer estimates 0.999)

Compliance may also be determined by stack testing using Method 5 of 40 CFR, Part 60, Appendix A. No stack testing is specifically required by this permit; however, if visible emissions are observed from the dust collector stack, this office may request that stack testing be performed.

The annual limit of 0.53 tpy is based on the allowable hourly emission limit (0.12 lb/hr) multiplied by the maximum possible operating hours (8760 hrs/yr), and dividing by 2000 (lbs/ton). Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

(2) Emission Limitation:

0.0083 lb/hr and 0.036 tpy of Pb

Applicable Compliance Method:

Compliance with the hourly Pb emission rate shall be determined by multiplying the calculated PE emissions by the emission factor of 0.07 lb of lead/lb of brass.

The annual Pb limit of 0.036 tpy is based on the allowable hourly emission limit (0.0083 lb/hr) multiplied by the maximum possible operating hours (8760 hrs/yr), and dividing by 2000 (lbs/ton). Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

(3) Emission Limitation:

Visible emissions from the stack of the dust collector serving this emissions unit shall not exceed 0% opacity, as a six-minute average.

Applicable Compliance Method:

If required, compliance shall be based upon visible particulate emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9.

g) Miscellaneous Requirements

(1) None.

3. P006, Electric Induction Furnace #1

Operations, Property and/or Equipment Description:

South electric induction furnace, controlled by the no. 2 west dust collector

a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

(1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. None.

(2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

a. None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) PTI 02-5423 issued November 7, 1990	Particulate matter emissions from the stack shall not exceed 0.03 grain/dscf. Particulate matter less than 10 microns (PM_{10}) emissions from this emissions unit shall not exceed 1.05 lbs/hr. Lead emissions (Pb) from this emissions unit shall not exceed 0.065 lb/hr.
b.	OAC rule 3745-17-11(B)	The emission limitation required by this applicable rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
c.	OAC rule 3745-17-07(A)	Visible particulate emissions from the stack serving this emissions unit shall not exceed 20 percent (20%) opacity as a six-minute average.

(2) Additional Terms and Conditions

a. All PE from the abrasive operations shall be captured and vented to the no. 2 west dust collector.

c) Operational Restrictions

(1) None.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall properly install, operate, and maintain equipment to continuously monitor and record the pressure drop, in inches of water, across the dust collector during operation of this emissions unit, including periods of startup and shutdown. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop, in inches of water, across the baghouse on a daily basis.

Whenever the monitored value for the pressure drop deviates from the range specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation:

a. the date and time the deviation began;

b. the magnitude of the deviation at that time;

c. the date(s) the investigation was conducted;

d. the names of the personnel who conducted the investigation; and

e. the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable range specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken:

f. description of the corrective action;

g. the date it was completed;

h. the date and time the deviation ended;

i. the total period of time (in minutes) during which there was a deviation;

j. the pressure drop readings immediately after the corrective action; and

k. the names of the personnel who performed the work.

Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

The acceptable range for the pressure drop across the baghouse is 1.5 to 6.5 inches of water.

This range is effective for the duration of this permit, unless revisions are requested by the permittee and approved in writing by the appropriate Ohio EPA District Office or local air agency. The permittee may request revisions to the range based upon information obtained during future particulate emission tests that demonstrate compliance with the allowable particulate emission rate for this emissions unit. In addition, approved revisions to the range will not constitute a relaxation of the monitoring requirements of this permit and may be incorporated into this permit by means of an administrative modification.

(2) The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:

a. the color of the emissions;

b. whether the emissions are representative of normal operations;

c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;

d. the total duration of any visible emission incident; and

e. any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item d above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

e) Reporting Requirements

(1) The permittee shall identify in the annual permit evaluation report the following information concerning the operations of the baghouse during the 12-month reporting period for this/these emissions unit(s):

a. each period of time (start time and date, and end time and date) when the pressure drop across the baghouse was outside of the acceptable range;

b. any period of time (start time and date, and end time and date) when the emissions unit(s) was/were in operation and the process emissions were not vented to the baghouse;

c. each incident of deviation described in e)(1)a (above) where a prompt investigation was not conducted;

d. each incident of deviation described in e)(1)a where prompt corrective action, that would bring the pressure drop into compliance with the acceptable range, was determined to be necessary and was not taken; and

e. each incident of deviation described in e)(1)a where proper records were not maintained for the investigation and/or the corrective action(s), as identified in the monitoring and record keeping requirements of this permit.

[OAC rule 3745-15-03(B)(2) and OAC rule 3745-15-03(D)]

(2) The permittee shall identify the following information in the annual permit evaluation report in accordance with the monitoring requirements for visible emissions in term number d)(2) above:

a. all days during which any visible particulate emissions were observed from the stack serving this emissions unit; and

b. any corrective actions taken to minimize or eliminate the visible particulate emissions.

[OAC rule 3745-15-03(B)(2)] and [OAC rule 3745-15-03(D)]

(3) Annual Permit Evaluation Report (PER) forms will be mailed to the permittee at the end of the reporting period specified in the Authorization section of this permit. The permittee shall submit the PER in the form and manner provided by the director by the due date identified in the Authorization section of this permit. The PER shall cover a reporting period of no more than twelve-months for each air contaminant source identified in this permit. It is recommended that the PER is submitted electronically through the Ohio EPA's "e-Business Center: Air Services" although PERs can be submitted via U.S. postal service or can be hand delivered.

f) Testing Requirements

(1) Compliance with the Emissions Limitations and/or Control Requirements specified in section b) of these terms and conditions shall be determined in accordance with the following methods:

<u>Emission Limitation:</u>

0.03 grain of PE/dscf of total exhaust gases and 1.05 lbs/hr of PE

Applicable Compliance Method:

Compliance with the hourly PE limitation shall be determined using the following equation:

PE = PWR*EF*(1-CE)

Where:

PE = hourly emission rate, in lb/hr
PWR = maximum hourly processing rate, 1.05 tph
EF = emission factor of 20 lb/ton of material, from AP-42 Table 12.9-2
CE = fractional control efficiency, 0.99 (conservative as manufacturer estimates 0.999)

Compliance may also be determined by stack testing using Method 5 of 40 CFR, Part 60, Appendix A. No stack testing is specifically required by this permit; however, if visible emissions are observed from the dust collector stack, this office may request that stack testing be performed.

(2) Emission Limitation:

0.065 lbs/hr of Pb

Applicable Compliance Method:

Compliance with the hourly Pb emission rate shall be determined by multiplying the calculated PE emissions by the emission factor of 0.07 lb of lead/lb of brass.

(3) Emission Limitation:

Visible emissions from the stack of the dust collector serving this emissions unit shall not exceed 20% opacity, as a six-minute average.

Applicable Compliance Method:

If required, compliance shall be based upon visible particulate emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9.

g) Miscellaneous Requirements

(1) None.

4. P007, Electric Induction Furnace #2

Operations, Property and/or Equipment Description:

North electric induction furnace, controlled by the no. 2 west dust collector

a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

(1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. None.

(2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

a. None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) PTI 02-5423 issued November 7, 1990	Particulate matter emissions from the stack shall not exceed 0.03 grain/dscf. PE/PM10 emissions from this emissions unit shall not exceed 1.05 lbs/hr. Lead emissions (Pb) from this emissions unit shall not exceed 0.065 lb/hr.
b.	OAC rule 3745-17-11(B)	The emission limitation required by this applicable rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
c.	OAC rule 3745-17-07(A)	Visible particulate emissions from the stack serving this emissions unit shall not exceed 20 percent (20%) opacity as a six-minute average.

(2) Additional Terms and Conditions

a. All PE from the abrasive operations shall be captured and vented to the no. 2 west dust collector.

c) Operational Restrictions

(1) None.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall properly install, operate, and maintain equipment to continuously monitor and record the pressure drop, in inches of water, across the dust collector during operation of this emissions unit, including periods of startup and shutdown. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop, in inches of water, across the baghouse on a daily basis.

Whenever the monitored value for the pressure drop deviates from the range specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation:

a. the date and time the deviation began;

b. the magnitude of the deviation at that time;

c. the date(s) the investigation was conducted;

d. the names of the personnel who conducted the investigation; and

e. the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable range specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken:

f. description of the corrective action;

g. the date it was completed;

h. the date and time the deviation ended;

i. the total period of time (in minutes) during which there was a deviation;

j. the pressure drop readings immediately after the corrective action; and

k. the names of the personnel who performed the work.

Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

The acceptable range for the pressure drop across the baghouse is 1.5 to 6.5 inches of water.

This range is effective for the duration of this permit, unless revisions are requested by the permittee and approved in writing by the appropriate Ohio EPA District Office or local air agency. The permittee may request revisions to the range based upon information obtained during future particulate emission tests that demonstrate compliance with the allowable particulate emission rate for this emissions unit. In addition, approved revisions to the range will not constitute a relaxation of the monitoring requirements of this permit and may be incorporated into this permit by means of an administrative modification.

(2) The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:

a. the color of the emissions;

b. whether the emissions are representative of normal operations;

c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;

d. the total duration of any visible emission incident; and

e. any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item d above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

e) Reporting Requirements

(1) The permittee shall identify in the annual permit evaluation report the following information concerning the operations of the baghouse during the 12-month reporting period for this/these emissions unit(s):

a. each period of time (start time and date, and end time and date) when the pressure drop across the baghouse was outside of the acceptable range;

b. any period of time (start time and date, and end time and date) when the emissions unit(s) was/were in operation and the process emissions were not vented to the baghouse;

c. each incident of deviation described in e)(1)a (above) where a prompt investigation was not conducted;

d. each incident of deviation described in e)(1)a where prompt corrective action, that would bring the pressure drop into compliance with the acceptable range, was determined to be necessary and was not taken; and

e. each incident of deviation described in e)(1)a where proper records were not maintained for the investigation and/or the corrective action(s), as identified in the monitoring and record keeping requirements of this permit.

[OAC rule 3745-15-03(B)(2) and OAC rule 3745-15-03(D)]

(2) The permittee shall identify the following information in the annual permit evaluation report in accordance with the monitoring requirements for visible emissions in term number d)(2) above:

a. all days during which any visible particulate emissions were observed from the stack serving this emissions unit; and

b. any corrective actions taken to minimize or eliminate the visible particulate emissions.

[OAC rule 3745-15-03(B)(2)] and [OAC rule 3745-15-03(D)]

(3) Annual Permit Evaluation Report (PER) forms will be mailed to the permittee at the end of the reporting period specified in the Authorization section of this permit. The permittee shall submit the PER in the form and manner provided by the director by the due date identified in the Authorization section of this permit. The PER shall cover a reporting period of no more than twelve-months for each air contaminant source identified in this permit. It is recommended that the PER is submitted electronically through the Ohio EPA's "e-Business Center: Air Services" although PERs can be submitted via U.S. postal service or can be hand delivered.

f) Testing Requirements

(1) Compliance with the Emissions Limitations and/or Control Requirements specified in section b) of these terms and conditions shall be determined in accordance with the following methods:

<u>Emission Limitation:</u>

0.03 grain of PE/dscf of total exhaust gases and 1.05 lbs/hr of PE

Applicable Compliance Method:

Compliance with the hourly PE limitation shall be determined using the following equation:

PE = PWR*EF*(1-CE)

Where:

PE = hourly emission rate, in lb/hr
PWR = maximum hourly processing rate, 1.05 tph
EF = emission factor of 20 lb/ton of material, from AP-42 Table 12.9-2
CE = fractional control efficiency, 0.99 (conservative as manufacturer estimates 0.999)

Compliance may also be determined by stack testing using Method 5 of 40 CFR, Part 60, Appendix A. No stack testing is specifically required by this permit; however, if visible emissions are observed from the dust collector stack, this office may request that stack testing be performed.

(2) Emission Limitation:

0.065 lbs/hr of Pb

Applicable Compliance Method:

Compliance with the hourly Pb emission rate shall be determined by multiplying the calculated PE emissions by the emission factor of 0.07 lb of lead/lb of brass.

(3) Emission Limitation:

Visible emissions from the stack of the dust collector serving this emissions unit shall not exceed 20% opacity, as a six-minute average.

Applicable Compliance Method:

If required, compliance shall be based upon visible particulate emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9.

g) Miscellaneous Requirements

(1) None.

5. P008, East Barrel Blast Machine

Operations, Property and/or Equipment Description:

East Barrel Blast Machine

a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

(1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. None.

(2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

a. None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) PTI 02-21017 issued August 23, 2005	Particulate emissions from this emissions unit shall not exceed 0.36 lb/hr and 1.58 tpy. Lead emissions (Pb) from this emissions unit shall not exceed 0.025 lb/hr and 0.11 tpy. Visible particulate emissions from the stack serving this emissions unit shall not exceed 0 percent (0%) opacity as a six-minute average.
b.	OAC rule 3745-17-11(B)	The emission limitation required by this applicable rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

c.	OAC rule 3745-17-07(A)	The emission limitation required by this applicable rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

(2) Additional Terms and Conditions

a. The annual emission limitation specified above is based on the emissions unit's potential to emit. Therefore, no records are required to demonstrate compliance with this limitation.

c) Operational Restrictions

(1) None.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall properly install, operate, and maintain equipment to continuously monitor and record the pressure drop, in inches of water, across the dust collector during operation of this emissions unit, including periods of startup and shutdown. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop, in inches of water, across the baghouse on a daily basis.

Whenever the monitored value for the pressure drop deviates from the range specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation:

a. the date and time the deviation began;

b. the magnitude of the deviation at that time;

c. the date(s) the investigation was conducted;

d. the names of the personnel who conducted the investigation; and

e. the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable range specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken:

f. description of the corrective action;

g. the date it was completed;

h. the date and time the deviation ended;

i. the total period of time (in minutes) during which there was a deviation;

j. the pressure drop readings immediately after the corrective action; and

k. the names of the personnel who performed the work.

Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

The acceptable range for the pressure drop across the baghouse is 2 to 6 inches of water.

This range is effective for the duration of this permit, unless revisions are requested by the permittee and approved in writing by the appropriate Ohio EPA District Office or local air agency. The permittee may request revisions to the range based upon information obtained during future particulate emission tests that demonstrate compliance with the allowable particulate emission rate for this emissions unit. In addition, approved revisions to the range will not constitute a relaxation of the monitoring requirements of this permit and may be incorporated into this permit by means of an administrative modification.

(2) The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:

a. the color of the emissions;

b. whether the emissions are representative of normal operations;

c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;

d. the total duration of any visible emission incident; and

e. any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item d above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

e) Reporting Requirements

(1) The permittee shall identify in the annual permit evaluation report the following information concerning the operations of the baghouse during the 12-month reporting period for this/these emissions unit(s):

a. each period of time (start time and date, and end time and date) when the pressure drop across the baghouse was outside of the acceptable range;

b. any period of time (start time and date, and end time and date) when the emissions unit(s) was/were in operation and the process emissions were not vented to the baghouse;

c. each incident of deviation described in e)(1)a (above) where a prompt investigation was not conducted;

d. each incident of deviation described in e)(1)a where prompt corrective action, that would bring the pressure drop into compliance with the acceptable range, was determined to be necessary and was not taken; and

e. each incident of deviation described in e)(1)a where proper records were not maintained for the investigation and/or the corrective action(s), as identified in the monitoring and record keeping requirements of this permit.

[OAC rule 3745-15-03(B)(2) and OAC rule 3745-15-03(D)]

(2) The permittee shall identify the following information in the annual permit evaluation report in accordance with the monitoring requirements for visible emissions in term number d)(2) above:

a. all days during which any visible particulate emissions were observed from the stack serving this emissions unit; and

b. any corrective actions taken to minimize or eliminate the visible particulate emissions.

[OAC rule 3745-15-03(B)(2)] and [OAC rule 3745-15-03(D)]

(3) Annual Permit Evaluation Report (PER) forms will be mailed to the permittee at the end of the reporting period specified in the Authorization section of this permit. The permittee shall submit the PER in the form and manner provided by the director by the due date identified in the Authorization section of this permit. The PER shall cover a reporting period of no more than twelve-months for each air contaminant source identified in this permit. It is recommended that the PER is submitted electronically through the Ohio EPA's "e-Business Center: Air Services" although PERs can be submitted via U.S. postal service or can be hand delivered.

f) Testing Requirements

(1) Compliance with the Emissions Limitations and/or Control Requirements specified in section b) of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitation:

0.36 lb/hr and 1.58 tpy of PE

Applicable Compliance Method:

Compliance with the hourly PE limitation shall be determined using the following equation:

PE = PWR*EF*(1-CE)

Where:

PE = hourly emission rate, in lb/hr
PWR = maximum hourly processing rate, 2.11 tph
EF = emission factor of 17 lbs/ton of material, from AP-42 Table 12.10-7
CE = fractional control efficiency, 0.99 (conservative as manufacturer estimates 0.999)

The annual limit of 1.58 tpy is based on the allowable hourly emission limit (0.36 lb/hr) multiplied by the maximum possible operating hours (8760 hrs/yr), and dividing by 2000 (lbs/ton). Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Compliance may also be determined by stack testing using Method 5 of 40 CFR, Part 60, Appendix A. No stack testing is specifically required by this permit; however, if visible emissions are observed from the dust collector stack, this office may request that stack testing be performed.

(2) Emission Limitation:

0.025 lb/hr and 0.11 tpy of Pb

Applicable Compliance Method:

Compliance with the hourly Pb emission rate shall be determined by multiplying the calculated PE emissions by the lead content of 7%.

The annual Pb limit of 0.11 tpy is based on the allowable hourly emission limit (0.025 lb/hr) multiplied by the maximum possible operating hours (8760 hrs/yr), and dividing by 2000 (lbs/ton). Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

(3) Emission Limitation:

Visible emissions from the baghouse stack serving this emissions unit shall not exceed 0% opacity, as a six-minute average.

Applicable Compliance Method:

If required, compliance shall be based upon visible particulate emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9.

g) Miscellaneous Requirements

(1) None.

6. P009, Pouring & Cooling Line

Operations, Property and/or Equipment Description:

Pouring and cooling line, including mold transfer and pour pot, controlled by the no. 2 west dust collector.

a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

(1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. None.

(2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

a. None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) PTI 02-21711 issued April 11, 2006	Particulate emissions from this emissions unit shall not exceed 0.089 lb/hr and 0.39 tpy. Lead emissions (Pb) from this emissions unit shall not exceed 0.0062 lb/hr and 0.027 tpy. Visible particulate emissions from the stack serving this emissions unit shall not exceed 0 percent (0%) opacity as a six-minute average.
b.	OAC rule 3745-17-11(B)	The emission limitation required by this applicable rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
c.	OAC rule 3745-17-07(A)	The emission limitation required by this applicable rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

(2) Additional Terms and Conditions

a. All PE from the abrasive operations shall be captured and vented to the no. 2 west dust collector.

c) Operational Restrictions

(1) None.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall properly install, operate, and maintain equipment to continuously monitor and record the pressure drop, in inches of water, across the dust collector during operation of this emissions unit, including periods of startup and shutdown. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop, in inches of water, across the baghouse on a daily basis.

Whenever the monitored value for the pressure drop deviates from the range specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation:

a. the date and time the deviation began;

b. the magnitude of the deviation at that time;

c. the date(s) the investigation was conducted;

d. the names of the personnel who conducted the investigation; and

e. the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable range specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken:

f. description of the corrective action;

g. the date it was completed;

h. the date and time the deviation ended;

i. the total period of time (in minutes) during which there was a deviation;

j. the pressure drop readings immediately after the corrective action; and

k. the names of the personnel who performed the work.

Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

The acceptable range for the pressure drop across the baghouse is 1.5 to 6.5 inches of water.

This range is effective for the duration of this permit, unless revisions are requested by the permittee and approved in writing by the appropriate Ohio EPA District Office or local air agency. The permittee may request revisions to the range based upon information obtained during future particulate emission tests that demonstrate compliance with the allowable particulate emission rate for this emissions unit. In addition, approved revisions to the range will not constitute a relaxation of the monitoring requirements of this permit and may be incorporated into this permit by means of an administrative modification.

(2) The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:

a. the color of the emissions;

b. whether the emissions are representative of normal operations;

c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;

d. the total duration of any visible emission incident; and

e. any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item d above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that

no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

e) Reporting Requirements

(1) The permittee shall identify in the annual permit evaluation report the following information concerning the operations of the baghouse during the 12-month reporting period for this/these emissions unit(s):

a. each period of time (start time and date, and end time and date) when the pressure drop across the baghouse was outside of the acceptable range;

b. any period of time (start time and date, and end time and date) when the emissions unit(s) was/were in operation and the process emissions were not vented to the baghouse;

c. each incident of deviation described in e)(1)a (above) where a prompt investigation was not conducted;

d. each incident of deviation described in e)(1)a where prompt corrective action, that would bring the pressure drop into compliance with the acceptable range, was determined to be necessary and was not taken; and

e. each incident of deviation described in e)(1)a where proper records were not maintained for the investigation and/or the corrective action(s), as identified in the monitoring and record keeping requirements of this permit.

[OAC rule 3745-15-03(B)(2) and OAC rule 3745-15-03(D)]

(2) The permittee shall identify the following information in the annual permit evaluation report in accordance with the monitoring requirements for visible emissions in term number d)(2) above:

a. all days during which any visible particulate emissions were observed from the stack serving this emissions unit; and

b. any corrective actions taken to minimize or eliminate the visible particulate emissions.

[OAC rule 3745-15-03(B)(2)] and [OAC rule 3745-15-03(D)]

(3) Annual Permit Evaluation Report (PER) forms will be mailed to the permittee at the end of the reporting period specified in the Authorization section of this permit. The permittee shall submit the PER in the form and manner provided by the director by the due date identified in the Authorization section of this permit. The PER shall cover a reporting period of no more than twelve-months for each air contaminant source identified in this permit. It is recommended that the PER is submitted electronically through the Ohio EPA's "e-Business Center: Air Services" although PERs can be submitted via U.S. postal service or can be hand delivered.

f) Testing Requirements

(1) Compliance with the Emissions Limitations and/or Control Requirements specified in section b) of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitation:

0.089 lb/hr and 0.39 tpy of PE

Applicable Compliance Method:

Compliance with the hourly PE limitation shall be determined using the following equation:

PE = PWR*EF*(1-CE)

Where:

PE = hourly emission rate, in lb/hr
PWR = maximum hourly processing rate, 2.11 tph
EF = emission factor of 4.2 lbs/ton of material processed, from AP-42 Table 12.10-7
CE = fractional control efficiency, 0.99 (conservative as manufacturer estimates 0.999)

The annual limit of 0.39 tpy is based on the allowable hourly emission limit (0.089 lb/hr) multiplied by the maximum possible operating hours (8760 hrs/yr), and dividing by 2000 (lbs/ton). Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Compliance may also be determined by stack testing using Method 5 of 40 CFR, Part 60, Appendix A. No stack testing is specifically required by this permit; however, if visible emissions are observed from the dust collector stack, this office may request that stack testing be performed.

(2) Emission Limitation:

0.0062 lb/hr and 0.027 tpy of Pb

Applicable Compliance Method:

Compliance with the hourly Pb emission rate shall be determined by multiplying the calculated PE emissions by an emission factor of 0.7 lb of lead/lb of brass.

The annual Pb limit of 0.027 tpy is based on the allowable hourly emission limit (0.0062 lb/hr) multiplied by the maximum possible operating hours (8760 hrs/yr), and dividing by 2000 (lbs/ton). Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

(3) Emission Limitation:

Visible emissions from the baghouse stack serving this emissions unit shall not exceed 0% opacity, as a six-minute average.

Applicable Compliance Method:

If required, compliance shall be based upon visible particulate emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9.

g) Miscellaneous Requirements

(1) None.

7. P010, Shakeout operations

Operations, Property and/or Equipment Description:

Shakeout, including vibratory screen and vibratory conveyor, controlled by the no. 3 south dust collector.

a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

(1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. None.

(2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

a. None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) PTI 02-21711 issued April 11, 2006	Particulate emissions from this emissions unit shall not exceed 0.42 lb/hr and 1.84 tpy. Lead emissions (Pb) from this emissions unit shall not exceed 0.0022 lb/hr and 0.096 tpy. Visible particulate emissions from the stack serving this emissions unit shall not exceed 0 percent (0%) opacity as a six-minute average.
b.	OAC rule 3745-17-11(B)	The emission limitation required by this applicable rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
c.	OAC rule 3745-17-07(A)	The emission limitation required by this applicable rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

(2) Additional Terms and Conditions

a. All PE from the abrasive operations shall be captured and vented to the no. 3 south dust collector.

c) Operational Restrictions

(1) None.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall properly install, operate, and maintain equipment to continuously monitor and record the pressure drop, in inches of water, across the dust collector during operation of this emissions unit, including periods of startup and shutdown. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop, in inches of water, across the baghouse on a daily basis.

Whenever the monitored value for the pressure drop deviates from the range specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation:

a. the date and time the deviation began;

b. the magnitude of the deviation at that time;

c. the date(s) the investigation was conducted;

d. the names of the personnel who conducted the investigation; and

e. the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable range specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken:

f. description of the corrective action;

g. the date it was completed;

h. the date and time the deviation ended;

i. the total period of time (in minutes) during which there was a deviation;

j. the pressure drop readings immediately after the corrective action; and

k. the names of the personnel who performed the work.

Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

The acceptable range for the pressure drop across the baghouse is 4 to 7 inches of water.

This range is effective for the duration of this permit, unless revisions are requested by the permittee and approved in writing by the appropriate Ohio EPA District Office or local air agency. The permittee may request revisions to the range based upon information obtained during future particulate emission tests that demonstrate compliance with the allowable particulate emission rate for this emissions unit. In addition, approved revisions to the range will not constitute a relaxation of the monitoring requirements of this permit and may be incorporated into this permit by means of an administrative modification.

(2) The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:

a. the color of the emissions;

b. whether the emissions are representative of normal operations;

c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;

d. the total duration of any visible emission incident; and

e. any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item d above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that

no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

e) Reporting Requirements

(1) The permittee shall identify in the annual permit evaluation report the following information concerning the operations of the baghouse during the 12-month reporting period for this/these emissions unit(s):

a. each period of time (start time and date, and end time and date) when the pressure drop across the baghouse was outside of the acceptable range;

b. any period of time (start time and date, and end time and date) when the emissions unit(s) was/were in operation and the process emissions were not vented to the baghouse;

c. each incident of deviation described in e)(1)a (above) where a prompt investigation was not conducted;

d. each incident of deviation described in e)(1)a where prompt corrective action, that would bring the pressure drop into compliance with the acceptable range, was determined to be necessary and was not taken; and

e. each incident of deviation described in e)(1)a where proper records were not maintained for the investigation and/or the corrective action(s), as identified in the monitoring and record keeping requirements of this permit.

[OAC rule 3745-15-03(B)(2) and OAC rule 3745-15-03(D)]

(2) The permittee shall identify the following information in the annual permit evaluation report in accordance with the monitoring requirements for visible emissions in term number d)(2) above:

a. all days during which any visible particulate emissions were observed from the stack serving this emissions unit; and

b. any corrective actions taken to minimize or eliminate the visible particulate emissions.

[OAC rule 3745-15-03(B)(2)] and [OAC rule 3745-15-03(D)]

(3) Annual Permit Evaluation Report (PER) forms will be mailed to the permittee at the end of the reporting period specified in the Authorization section of this permit. The permittee shall submit the PER in the form and manner provided by the director by the due date identified in the Authorization section of this permit. The PER shall cover a reporting period of no more than twelve-months for each air contaminant source identified in this permit. It is recommended that the PER is submitted electronically through the Ohio EPA's "e-Business Center: Air Services" although PERs can be submitted via U.S. postal service or can be hand delivered.

f) Testing Requirements

(1) Compliance with the Emissions Limitations and/or Control Requirements specified in section b) of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitation:

0.42 lb/hr and 1.84 tpy of PE

Applicable Compliance Method:

Compliance with the hourly PE limitation shall be determined using the following equation:

PE = PWR*EF*(1-CE)

Where:

PE = hourly emission rate, in lb/hr
PWR = maximum hourly processing rate, 13.1 tph
EF = emission factor of 3.2 lbs/ton of material processed, from AP-42 Table 12.10-7
CE = fractional control efficiency, 0.99 (conservative as manufacturer estimates 0.999)

The annual limit of 1.84 tpy is based on the allowable hourly emission limit (0.42 lb/hr) multiplied by the maximum possible operating hours (8760 hrs/yr), and dividing by 2000 (lbs/ton). Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Compliance may also be determined by stack testing using Method 5 of 40 CFR, Part 60, Appendix A. No stack testing is specifically required by this permit; however, if visible emissions are observed from the dust collector stack, this office may request that stack testing be performed.

(2) Emission Limitation:

0.0022 lb/hr and 0.096 tpy of Pb

Applicable Compliance Method:

Compliance with the hourly Pb emission rate shall be determined by multiplying the calculated PE emissions by an emission factor of 0.00524 lb of lead/lb of sand.

The annual Pb limit of 0.096 tpy is based on the allowable hourly emission limit (0.0022 lb/hr) multiplied by the maximum possible operating hours (8760 hrs/yr), and dividing by 2000 (lbs/ton). Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

(3) Emission Limitation:

Visible emissions from the baghouse stack serving this emissions unit shall not exceed 0% opacity, as a six-minute average.

Applicable Compliance Method:

If required, compliance shall be based upon visible particulate emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9.

g) Miscellaneous Requirements

(1) None.

8. P011, Chip Dryer

Operations, Property and/or Equipment Description:

Chip dryer, controlled by an oil mist filtration unit and the no. 6 chip dryer.

a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

(1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. None.

(2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

a. None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) PTI 02-21711 issued April 11, 2006	Particulate emissions from this emissions unit shall not exceed 0.016 lb/hr and 0.07 tpy. Lead emissions (Pb) from this emissions unit shall not exceed 0.0036 lb/hr and 0.016 tpy. Visible particulate emissions from the stack serving this emissions unit shall not exceed 0 percent (0%) opacity as a six-minute average.
b.	OAC rule 3745-17-11(B)	The emission limitation required by this applicable rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

c.	OAC rule 3745-17-07(A)	The emission limitation required by this applicable rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

(2) Additional Terms and Conditions

a. All PE from the abrasive operations shall be captured and vented to the no. 6 chip dryer dust collector.

c) Operational Restrictions

(1) None.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall properly install, operate, and maintain equipment to continuously monitor and record the pressure drop, in inches of water, across the dust collector during operation of this emissions unit, including periods of startup and shutdown. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop, in inches of water, across the baghouse on a daily basis.

Whenever the monitored value for the pressure drop deviates from the range specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation:

a. the date and time the deviation began;

b. the magnitude of the deviation at that time;

c. the date(s) the investigation was conducted;

d. the names of the personnel who conducted the investigation; and

e. the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable range specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken:

f. description of the corrective action;

g. the date it was completed;

h. the date and time the deviation ended;

i. the total period of time (in minutes) during which there was a deviation;

j. the pressure drop readings immediately after the corrective action; and

k. the names of the personnel who performed the work.

Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

The acceptable range for the pressure drop across the baghouse is 2 to 7 inches of water.

This range is effective for the duration of this permit, unless revisions are requested by the permittee and approved in writing by the appropriate Ohio EPA District Office or local air agency. The permittee may request revisions to the range based upon information obtained during future particulate emission tests that demonstrate compliance with the allowable particulate emission rate for this emissions unit. In addition, approved revisions to the range will not constitute a relaxation of the monitoring requirements of this permit and may be incorporated into this permit by means of an administrative modification.

(2) The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:

a. the color of the emissions;

b. whether the emissions are representative of normal operations;

c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;

d. the total duration of any visible emission incident; and

e. any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item d above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

e) Reporting Requirements

(1) The permittee shall identify in the annual permit evaluation report the following information concerning the operations of the baghouse during the 12-month reporting period for this/these emissions unit(s):

a. each period of time (start time and date, and end time and date) when the pressure drop across the baghouse was outside of the acceptable range;

b. any period of time (start time and date, and end time and date) when the emissions unit(s) was/were in operation and the process emissions were not vented to the baghouse;

c. each incident of deviation described in e)(1)a (above) where a prompt investigation was not conducted;

d. each incident of deviation described in e)(1)a where prompt corrective action, that would bring the pressure drop into compliance with the acceptable range, was determined to be necessary and was not taken; and

e. each incident of deviation described in e)(1)a where proper records were not maintained for the investigation and/or the corrective action(s), as identified in the monitoring and record keeping requirements of this permit.

[OAC rule 3745-15-03(B)(2) and OAC rule 3745-15-03(D)]

(2) The permittee shall identify the following information in the annual permit evaluation report in accordance with the monitoring requirements for visible emissions in term number d)(2) above:

a. all days during which any visible particulate emissions were observed from the stack serving this emissions unit; and

b. any corrective actions taken to minimize or eliminate the visible particulate emissions.

[OAC rule 3745-15-03(B)(2)] and [OAC rule 3745-15-03(D)]

(3) Annual Permit Evaluation Report (PER) forms will be mailed to the permittee at the end of the reporting period specified in the Authorization section of this permit. The permittee shall submit the PER in the form and manner provided by the director by the due date identified in the Authorization section of this permit. The PER shall cover a reporting period of no more than twelve-months for each air contaminant source identified in this permit. It is recommended that the PER is submitted electronically through the Ohio EPA's "e-Business Center: Air Services" although PERs can be submitted via U.S. postal service or can be hand delivered.

f) Testing Requirements

(1) Compliance with the Emissions Limitations and/or Control Requirements specified in section b) of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitation:

0.016 lb/hr and 0.07 tpy of PE

Applicable Compliance Method:

Compliance with the hourly PE limitation shall be determined using the following equation:

PE = EF*(1-CE)

Where:

PE = hourly emission rate, in lb/hr
EF = uncontrolled mass emission rate of 1.55 lbs/hr, stack test result from compliance demonstration test conducted on March 17, 1999.
CE = fractional control efficiency, 0.99 (conservative as manufacturer estimates 0.999)

The annual limit of 0.07 tpy is based on the allowable hourly emission limit (0.016 lb/hr) multiplied by the maximum possible operating hours (8760 hrs/yr), and dividing by 2000 (lbs/ton). Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Compliance may also be determined by stack testing using Method 5 of 40 CFR, Part 60, Appendix A. No stack testing is specifically required by this permit; however, if visible emissions are observed from the dust collector stack, this office may request that stack testing be performed.

(2) Emission Limitation:

0.0036 lb/hr and 0.016 tpy of Pb

Applicable Compliance Method:

Compliance with the hourly PE limitation shall be determined using the following equation:

Pb = A*(1-CE)

Where:

Pb = hourly lead emission rate, in lb/hr
A = uncontrolled lead mass emission rate of 0.36 lb/hr, stack test result from compliance demonstration test conducted on March 17, 1999.
CE = fractional control efficiency, 0.99 (conservative as manufacturer estimates 0.999)

The annual Pb limit of 0.016 tpy is based on the allowable hourly emission limit (0.0036 lb/hr) multiplied by the maximum possible operating hours (8760 hrs/yr), and dividing by 2000 (lbs/ton). Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

(3) Emission Limitation:

Visible emissions from the baghouse stack serving this emissions unit shall not exceed 0% opacity, as a six-minute average.

Applicable Compliance Method:

If required, compliance shall be based upon visible particulate emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9.

g) Miscellaneous Requirements

(1) None.