



State of Ohio Environmental Protection Agency

STREET ADDRESS:

1800 WaterMark Drive
Columbus, OH 43215-1099

TELE: (614) 644-3020 FAX: (614) 644-2329

MAILING ADDRESS:

P.O. Box 1049
Columbus, OH 43216-1049

Re: Permit to Install
Stark County
Application No: 15-1300
TOXIC REVIEW
SYNTHETIC MINOR

CERTIFIED MAIL

August 27, 1997

SEP 8 1997

MIDWEST TANK SERVICES, INC.
JOHN IONNO
111 SECOND ST., N.W. SUITE 300
CANTON, OH 44702

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed with the Environmental Review Appeals Commission within thirty (30) days after notice of the Director's action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
236 East Town Street, Room 300
Columbus, Ohio 43215

Very truly yours,

Thomas G. Rigo, Manager
Field Operations & Permit Section
Division of Air Pollution Control

cc: US EPA
CANTON AIR POLLUTION CONTROL

George V. Voinovich, Governor
Nancy P. Hollister, Lt. Governor
Donald R. Schregardus, Director



Permit to Install Terms and Conditions

Application No. 15-1300
APS Premise No. 1576001860
Permit Fee: \$400.00

Name of Facility: MIDWEST TANK SERVICES, INC.

Person to Contact: JOHN IONNO

Address: 111 SECOND ST., N.W. SUITE 300
CANTON, OH 44702

Location of proposed source(s): 4936 SOUTHWAY STREET
PERRY TOWNSHIP, OHIO

Description of proposed source(s):
TWO PAINT SPRAY BOOTHS (MISCELLANEOUS METAL).

Date of Issuance: August 27, 1997

Effective Date: August 27, 1997

The above named entity is hereby granted a permit to install for the above described source(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described source(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described source(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

TERMINATION OF PERMIT TO INSTALL

Substantial construction for installation must take place within 18 months of the effective date of this permit. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

NOTICE OF INSPECTION

The Director of the Ohio Environmental Protection Agency, or his authorized representatives, may enter upon the premises of the above-named applicant during construction and operation at any reasonable time for the purpose of making inspections, conducting tests, or to examine records or reports pertaining to the construction, modification or installation of the source(s) of environmental pollutants identified within this permit.

CONSTRUCTION OF NEW SOURCES

The proposed source(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources are inadequate or cannot meet applicable standards.

If the construction of the proposed source(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of Ohio Administrative Code (OAC) Rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons)

MIDWEST TANK SERVICES, INC.
Application No. 15-1300
Page 3 of 17
August 27, 1997

may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet applicable standards.

PERMIT TO INSTALL FEE

In accordance with Ohio Revised Code 3745.11, the specified Permit to Install fee must be remitted within 30 days of the effective date of this permit to install.

PUBLIC DISCLOSURE

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC Rule 3745-49-03.

APPLICABILITY

This Permit to Install is applicable only to the contaminant sources identified. Separate application must be made to the Director for the installation or modification of any other contaminant sources.

BEST AVAILABLE TECHNOLOGY

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

PERMIT TO OPERATE APPLICATION

A Permit to Operate application must be submitted to the appropriate field office for each air contaminant source in this Permit to Install. In accordance with OAC Rule 3745-35-02, the application shall be filed no later than thirty days after commencement of operation.

SOURCE OPERATION AFTER COMPLETION OF CONSTRUCTION

This facility is permitted to operate each source described by this permit to install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws and regulations.

MIDWEST TANK SERVICES, INC.

Application No. 15-1300

Page 4 of 17

August 27, 1997

AIR EMISSION SUMMARY

The air contaminant sources listed below comprise the Permit to Install for MIDWEST TANK SERVICES, INC. located in Stark County. The sources listed below shall not exceed the emission limits/control requirements contained in the table. This condition in no way limits the applicability of any other state or federal regulations. Additionally, this condition does not limit the applicability of additional special terms and conditions of this permit.

<u>Ohio EPA Source Number</u>	<u>Source Identification Description</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
K001	Miscellaneous metal paint spray booth; Booth No. 1	Compliance with 3745-21-09 (U) and with terms and conditions of this permit	3745-21-09 including but not limited to 3745-21-09 (U) (1) (c) 3745-17-07 including but not limited to 3745-17-07 (A) (1) 3745-17-11 including but not limited to 3745-17-11 (B) (2) PTI 15-1300 BAT	Daily volume- weighted average VOC content of coatings of no more than 3.5 pounds/gallon Visible particulate emissions shall not exceed 20% opacity, as a six- minute average, except for a period of 6 consecutive minutes in any 60 minutes. Visible particulate emissions shall not exceed 60%, as a six-minute average, at any time. .551 lb PM/hr 128 lbs OC/day 20 tons OC/yr .17 ton PM/yr

Ohio EPA Source Number	Source Identification Description	BAT Determination	Applicable Federal & OAC Rules	Permit Allowable Mass Emissions and/or Control/Usage Requirements
K002	Miscellaneous metal paint spray booth; Booth No. 2	Compliance with 3745-21-09 (U) and with terms and conditions of this permit	3745-21-09 including but not limited to 3745-21-09 (U) (1) (c) 3745-17-07 including but not limited to 3745-17-07 (A) (1) 3745-17-11 including but not limited to 3745-17-11 (B) (2) PTI 15-1300 BAT	Daily volume- weighted average VOC content of coatings of not more than 3.5 pounds/gallon Visible particulate emissions shall not exceed 20% opacity, as a six- minute average, except for a period of 6 consecutive minutes in any 60 minute period. Visible particulate emissions shall not exceed 60%, as a six-minute average, at any time. .551 lb PM/hr
				128 lbs OC/day 20 tons OC/yr .17 ton PM/yr

SUMMARY
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons/Year</u>
OC	*35.00
PM	.34

* Although each individual emissions unit has a 20 tons/yr limit, the combined limit for both emissions units is 35 tons/yr.

RECORD(S) RETENTION AND AVAILABILITY

All records required by this Permit to Install shall be retained on file for a period of not less than three years unless otherwise indicated by Ohio Environmental Protection Agency. All records shall be made available to the Director, or any representative of the Director, for review during normal business hours.

REPORTING REQUIREMENTS

Unless otherwise specified, reports required by the Permit to Install need only be submitted to Canton Air Pollution Control, 420 Market Ave. N. , City Hall, Canton, Ohio 44702-1544.

WASTE DISPOSAL

The owner/operator shall comply with any applicable state and federal requirements governing the storage, treatment, transport and disposal of any waste material generated by the operation of the sources.

MAINTENANCE OF EQUIPMENT

This source and its associated air pollution control system(s) shall be maintained regularly in accordance with good engineering practices and the recommendations of the respective manufacturers in order to minimize air contaminant emissions.

MALFUNCTION/ABATEMENT

In accordance with OAC RULE 3745-15-06, any malfunction of the source(s) or associated air pollution control system(s) shall be reported immediately to the Canton Air Pollution Control, 420 Market Ave. N. , City Hall, Canton, Ohio 44702-1544.

Except as provided by OAC Rule 3745-15-06(A)(3), scheduled maintenance of air pollution control equipment that requires the

shutdown or bypassing of air pollution control system(s) must be accompanied by the shutdown of the associated air pollution sources.

AIR POLLUTION NUISANCES PROHIBITED

The air contaminant source(s) identified in this permit may not cause a public nuisance in violation of OAC Rule 3745-15-07.

CONSTRUCTION COMPLIANCE CERTIFICATION

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

ADDITIONAL SPECIAL TERMS AND CONDITIONS

K001

A. Operational Restrictions

1. The emissions of organic compounds from this emissions unit shall not exceed 20 tons per year, based upon a rolling, 12-month summation of the monthly emissions.

The total combined emissions of organic compounds from paint booths K001 and K002 shall not exceed 35 tons per year, based upon a rolling, 12-month summation of the monthly emissions.

The total combined emissions of any individual HAP [as defined by OAC rule 3745-77-01(BB) of hazardous air pollutants (HAPs)] from paint booths K001 and K002 shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation of the monthly emissions.

The total combined emissions of any combination of HAPs from paint booths K001 and K002 shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation of the monthly emissions.

To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed-- for the combined emissions from both booths--the emission levels specified in the following table:

Cumu- lative Months	Maximum Allowable Cumulative Emissions of Organic Compounds K001/K002 (Tons)	Maximum Allowable Cumulative Emissions of Organic Compounds K001 & K002 (Tons)	Maximum Allowable Cumulative Emissions of an Individual HAP (Tons)	Maximum Allowable Cumulative Emissions of Combined HAPs (Tons)
1	1.67	2.917	.825	2.075
1-2	3.33	5.833	1.650	4.150
1-3	5.00	8.750	2.475	6.225
1-4	6.67	11.667	3.300	8.300
1-5	8.33	14.583	4.125	10.375
1-6	10.00	17.500	4.950	12.450
1-7	11.67	20.417	5.775	14.525
1-8	13.33	23.333	6.600	16.600
1-9	15.00	26.250	7.425	18.675
1-10	16.67	29.167	8.250	20.750
1-11	18.33	32.083	9.075	22.825
1-12	20.00	35.000	9.900	24.900

After the first 12 calendar months of operation following issuance of this permit, compliance with the annual emission limitation for OC, individual HAPs, and combined HAPs shall be based upon a rolling, 12-month summation of the monthly emissions.

2. Best Available Control Technology shall be employed and consists of the following requirements:
 - a. using waterborne coatings whenever a satisfactory water-reduced finish can be found;
 - b. keeping all vessels containing VOCs tightly closed except when actually in use;
 - c. using HVLP spray equipment whenever possible;
 - d. using air assisted airless spray whenever possible;
 - e. carefully training the spray gun operators to coat the various object shapes with a minimum of overspray and wasted paint;
 - f. doing all spraying in a totally enclosed booth equipped with efficient dry filters for PM control; and,
 - g. carefully maintaining the spray booth and its filters so as to virtually eliminate PM emissions.

3. The pressure drop across the filters shall be maintained within a range which will be specified in the future permit to operate to be issued for this emissions unit.

B. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each day for the line:
 - a. the name and company identification for each coating as applied, thinning solvent, makeup solvent, and cleanup material employed;
 - b. the number of gallons of each coating as applied, thinning solvent, makeup solvent, and cleanup material employed;
 - c. the VOC content (excluding water and exempt solvents) of each coating, thinning solvent, makeup solvent and cleanup material, in pounds per gallon;
 - d. the total organic compound emission rate for this emissions unit, in pounds per day (This emissions rate includes the emissions from each coating, thinning solvent, makeup solvent and cleanup material); and,
 - e. the daily volume-weighted average VOC content of all coatings, as applied, calculated in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 of $C_{voc,2}$.

[Note: The coating information must be for the coatings **as employed**, including any thinning solvents added at the emissions unit.]

2. Beginning after the first 12-calendar months of operation following the issuance of this permit, the rolling, 12-month summation of the OC emissions in tons.
3. The permittee shall collect and record the following information each month:
 - a. the name and identification number of each coating, as applied;
 - b. the individual Hazardous Air Pollutant (HAP)¹ content for each HAP of each coating in pounds of individual HAP per gallon of coating, as applied;
 - c. the total combined Hazardous Air Pollutant (HAP) content for each HAP of each coating in pounds of combined HAPs per gallon of coating, as applied (sum of all the individual HAP contents);

- d. the number of gallons of each coating employed;
- e. the name and identification of each cleanup material employed;
- f. the individual HAP content for each HAP of each cleanup material, in pounds of individual HAP per gallon of cleanup material, as applied;
- g. the total HAP content for each HAP of each cleanup material in pounds of combined HAPs per gallon of cleanup material, as applied (sum of all the individual HAP contents);
- h. the number of gallons of each cleanup material employed;
- i. the total individual HAP emissions for each HAP from all coatings and cleanup materials employed, in tons per month and/or tons per rolling 12-month period; and,
- j. the total combined Hazardous Air Pollutant (HAP) emissions from all coatings and cleanup materials employed, in tons per month and tons per rolling 12-month period.

A listing of the Hazardous Air Pollutants (HAPs) can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting Canton Division of Air Pollution Control contact. Material Safety Data Sheets typically include a listing of the solvents contained in the coatings or cleanup materials. This information does not have to be kept on a line-by-line basis.

4. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the filters while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the filters on a daily basis.

C. Reporting Requirements

The permittee shall submit deviation (excursion) reports which include the following information:

1. an identification of all exceedances of the rolling, 12-month emission limitation for organic compounds, individual HAPs, and combined HAPs for the first 12

calendar months of operation following the issuance of this permit, all exceedances of the maximum allowable cumulative emission levels;

2. the permittee shall submit pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the filters was outside the range specified above while the spray booth was being employed;
3. an identification of all exceedances of the 128 pounds/day and 20 tons/year limit for organic compounds from this emissions unit; and,
4. an identification of any day in which the daily volume-weighted average VOC content of coatings exceeded 3.5 pounds/gallon.

D. Compliance Methods and Testing Requirements

1. Emission Limit:

3.5 pounds VOC/gallon as a daily weighted average.

Compliance Method:

To determine the OC contents of the coatings and inks, use OAC rule 3745-21-10(B).

2. Emission Limit:

Opacity Limit.

Compliance Method:

Method 9.

3. Emission Limit:

.551 pound Pm/hr

Compliance Method:

Properly installed and operated filters should easily meet compliance with this limit.

4. Emission Limit:

128 pounds OC/day.

Compliance Method: Daily recordkeeping as required in Term and Condition B.1.

5. Emission Limit: 20 tons OC/year for each booth and 35 tons OC/year as a 12-month rolling average for both booths.

Compliance Method:

Monthly recordkeeping as required by Term and Condition B.3.

6. Emission Limit: 9.9 tons of an individual HAP and 24.9 tons of combined HAPs for a rolling 12-month average.

Compliance Method: Monthly recordkeeping as required by Term and Condition B.3.

E. Miscellaneous Requirements

None.

K002

A. Operational Restrictions

1. The emissions of organic compounds from this emissions unit shall not exceed 20 tons per year, based upon a rolling, 12-month summation of the monthly emissions.

The total combined emissions of organic compounds from paint booths K001 and K002 shall not exceed 35 tons per year, based upon a rolling, 12-month summation of the monthly emissions.

The total combined emissions of any individual HAP [as defined by OAC rule 3745-77-01(BB) of hazardous air pollutants (HAPs)] from paint booths K001 and K002 shall not exceed 9.9 tons per year, based upon a rolling, 12-month summation of the monthly emissions.

The total combined emissions of any combination of HAPs from paint booths K001 and K002 shall not exceed 24.9 tons per year, based upon a rolling, 12-month summation of the monthly emissions.

To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed--for the combined emissions from both booths--the emission levels specified in the following table:

MIDWEST TANK SERVICES, INC.

Application No. 15-1300

Page 13 of 17

August 27, 1997

Cumu- lative Months	Maximum Allowable Cumulative Emissions of Organic Compounds K001/K002 (Tons)	Maximum Allowable Cumulative Emissions of Organic Compounds K001 & K002 (Tons)	Maximum Allowable Cumulative Emissions of an Individual HAP (Tons)	Maximum Allowable Cumulative Emissions of Combined HAPs (Tons)
1	1.67	2.917	.825	2.075
1-2	3.33	5.833	1.650	4.150
1-3	5.00	8.750	2.475	6.225
1-4	6.67	11.667	3.300	8.300
1-5	8.33	14.583	4.125	10.375
1-6	10.00	17.500	4.950	12.450
1-7	11.67	20.417	5.775	14.525
1-8	13.33	23.333	6.600	16.600
1-9	15.00	26.250	7.425	18.675
1-10	16.67	29.167	8.250	20.750
1-11	18.33	32.083	9.075	22.825
1-12	20.00	35.000	9.900	24.900

After the first 12 calendar months of operation following issuance of this permit, compliance with the annual emission limitation for OC, individual HAPs, and combined HAPs shall be based upon a rolling, 12-month summation of the monthly emissions.

2. Best Available Control Technology shall be employed and consists of the following requirements:
 - a. using waterborne coatings whenever a satisfactory water-reduced finish can be found;
 - b. keeping all vessels containing VOCs tightly closed except when actually in use;
 - c. using HVLP spray equipment whenever possible;
 - d. using air assisted airless spray whenever possible;
 - e. carefully training the spray gun operators to coat the various object shapes with a minimum of overspray and wasted paint;
 - f. doing all spraying in a totally enclosed booth equipped with efficient dry filters for PM control; and,
 - g. carefully maintaining the spray booth and its filters so as to virtually eliminate PM emissions.

3. The pressure drop across the filters shall be maintained within a range which will be specified in the future permit to operate to be issued for this emissions unit.

B. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each day for the line:
 - a. the name and company identification for each coating as applied, thinning solvent, makeup solvent, and cleanup material employed;
 - b. the number of gallons of each coating as applied, thinning solvent, makeup solvent, and cleanup material employed;
 - c. the VOC content (excluding water and exempt solvents) of each coating, thinning solvent, makeup solvent and cleanup material, in pounds per gallon;
 - d. the total organic compound emission rate for this emissions unit, in pounds per day (this emissions rate includes the emissions from each coating, thinning solvent, makeup solvent and cleanup material); and,
 - e. the daily volume-weighted average VOC content of all coatings, as applied, calculated in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for $C_{voc,2}$.

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit.]

2. Beginning after the first 12-calendar months of operation following the issuance of this permit, the rolling, 12-month summation of the OC emissions in tons.
3. The permittee shall collect and record the following information each month:
 - a. the name and identification number of each coating, as applied;
 - b. the individual Hazardous Air Pollutant (HAP)¹ content for each HAP of each coating in pounds of individual HAP per gallon of coating, as applied;

- c. the total combined Hazardous Air Pollutant (HAP) content for each HAP of each coating in pounds of combined HAPs per gallon of coating, as applied (sum of all the individual HAP contents);
- d. the number of gallons of each coating employed;
- e. the name and identification of each cleanup material employed;
- f. the individual HAP content for each HAP of each cleanup material in pounds of individual HAP per gallon of cleanup material, as applied;
- g. the total HAP content for each HAP of each cleanup material in pounds of combined HAPs per gallon of cleanup material, as applied (sum of all the individual HAP contents);
- h. the number of gallons of each cleanup material employed;
- i. the total individual HAP emissions for each HAP from all coatings and cleanup materials employed, in tons per month and/or tons per rolling 12-month period; and,
- j. the total combined Hazardous Air Pollutant (HAP) emissions from all coatings and cleanup materials employed, in tons per month and tons per rolling 12-month period.

A listing of the Hazardous Air Pollutants (HAPs) can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Canton Division of Air Pollution Control contact. Material Safety Data Sheets typically include a listing of the solvents contained in the coatings or cleanup materials. This information does not have to be kept on a line-by-line basis.

4. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the filters while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the filters on a daily basis.

C. Reporting Requirements

The permittee shall submit deviation (excursion) reports which include the following information:

1. an identification of all exceedances of the rolling, 12-month emission limitation for organic compounds, individual HAPs, and combined HAPs for the first 12 calendar months of operation following the issuance of this permit, all exceedances of the maximum allowable cumulative emission levels;
2. the permittee shall submit pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the filters was outside the range specified above while the spray booth was being employed;
3. an identification of all exceedances of the 128 pounds/day and 20 tons/year limit for organic compounds from this emissions unit; and,
4. an identification of any day in which the daily volume-weighted average VOC content of coatings exceeded 3.5 pounds/gallon.

D. Compliance Methods and Testing Requirements

1. Emission Limit:

3.5 pounds VOC/gallon as a daily weighted average.

Compliance Method:

To determine the OC contents of the coatings and inks, use OAC rule 3745-21-10(B).

2. Emission Limit:

Opacity Limit.

Compliance Method:

Method 9.

3. Emission Limit:

.551 pound PM/hr

Compliance Method:

Properly installed and operated filters should easily meet compliance with this limit.

4. Emission Limit:

128 pounds OC/day

Compliance Method:

Daily recordkeeping as required in Term and Condition B.1.

5. Emission Limit:

20 tons OC/year for each booth and 35 tons OC/year as a 12-month rolling average for both booths.

Compliance Method:

Monthly recordkeeping as required by Term and Condition B.3.

6. Emission Limit:

9.9 tons of an individual HAP and 24.9 tons of combined HAPs for a rolling 12-month average.

Compliance Method:

Monthly recordkeeping as required by Term and Condition B.3.

E. Miscellaneous Requirements

None.