



State of Ohio Environmental Protection Agency

Franklin County

RE: Final Permit to Install

Street
1800 \
Column

address:
149
16-1049

Application No: **01-7865**

DATE: May 12, 1999

**Kokosing Materials, Inc.
Ralph Kyanko
6187 Westerville Road
Westerville, Ohio 43081**

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Director's action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
236 East Town Street, Room 300
Columbus, Ohio 43215

Very truly yours,

Thomas G. Rigo, Manager
Field Operations and Permit Section
Division of Air Pollution Control

cc: USEPA

Ohio EPA Central District Office



STATE OF OHIO ENVIRONMENTAL PROTECTION AGENCY

Application Number: 01-7865

Permit
Title

APS Premise Number: 0125042399

Number:

Permit Fee: **\$2400**

Name of Facility: Kokosing Materials, Inc.

Person to Contact: Ralph Kyanko

Address: 6187 Westerville Road

Westerville, Ohio 43081

Location of proposed air contaminant source(s) [emissions unit(s)]:

Intersection of I-270 & State Route 3

Westerville, Ohio

Description of proposed emissions unit(s):

**COUNTERFLOW HOT MIX ASPHALT WITH BAG HOUSE, ROADWAYS, PARKING AREAS,
MATERIAL HANDLING, STORAGE PILES.**

Date of Issuance: May 12, 1999

Issuance:

Effective Date: May 12, 1999

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements

The permittee shall submit required reports in the following manner:

- a. reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency; and,
- b. except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon

the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

Kokosing Materials, Inc.

PTI 01-7865

May 12, 1999

Facility ID: 012504239

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions

and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources are inadequate or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities prove to be inadequate or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit to Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within thirty (30) days after commencing operation of the emissions unit(s) covered by this permit.

Kokosing Materials, Inc.
 PTI 01-7865
 May 12, 1999

Facility ID: 012504239

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
PM	32.47
CO	22.4
NO _x	30.0
SO ₂	22.4
OC	27.6

PART II: SPECIAL TERMS AND CONDITIONS

A. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>
400 Tons/Hour Hot Mix Asphalt Plant with bag house	OAC rule 3745-18-06(E)(1) 40 CFR 60 Subpart I (NSPS) OAC rule 3745-31-05

OAC rule 3745-17-07(A)(1)(a)

OAC rule 3745-17-07(B)(1)

OAC rule 3745-17-08(B)(3)(a)

OAC rule 3745-17-08(B)(3)(b)

OAC rule 3745-17-11

10
Kokos
PTI
May 12, 1999

Emissions Unit ID: **P901**

Applicable Emissions
Limitations/Control Measures

10.26 lbs/hr PM, 10.3 TPY PM
22.4 #/hr CO, 22.4 TPY CO;
30.0 #/hr NO_x, 30.0 TPY NO_x;
22.4 #/hr SO₂, 22.4 TPY SO₂;
27.6 #/hr OC, 27.6 TPY
OC

Visible particulate emissions from any stack shall not exceed 20% opacity, as a six-minute average, except as provided by rule

Visible emissions from any fugitive dust source shall not exceed 20% opacity, as a three-minute average.

Minimize or eliminate visible particulate emissions of fugitive dust at the point(s) of capture.

Control equipment outlet emission rate of not greater than 0.030 gr/dscf PM or no visible particulate emissions;

Less stringent than PM limits of OAC 3745-17-08

Less stringent than SO₂ limits of OAC 3745-31-05

Less stringent than PM limits of OAC 3745-17-08 and opacity limits of OAC 3745-17-07 and

OAC 3745-17-08.

2. Additional Terms and Conditions

2.a. None

B. Operational Restrictions

1. No visible emissions of fugitive dust from the enclosures for the hot aggregate elevator, vibrating screens, and weigh hopper.
2. The drop height of the front end loader bucket shall be minimized to the extent possible in order to minimize or eliminate visible emissions of fugitive dust from the elevator loading area.
3. The aggregate loaded into the storage bins shall have a moisture content sufficient to eliminate the visible emissions of fugitive dust from the elevator and the transfer point to the dryer.
4. To ensure the baghouse is operated according to the manufacturer's specifications and to maintain compliance with the allowable particulate emission rate, a negative pressure drop across the baghouse of not less than 3" or greater than 6" shall be maintained at all times.
5. In accordance with this permit to install, this emissions unit has been approved for the use of recycled asphalt products.
6. Maximum annual production of asphaltic concrete for this emissions unit shall not exceed 800,000 tons per year.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall properly operate and maintain a monitoring device capable of accurately measuring the pressure drop across the fabric filter.
2. The permittee shall check the pressure drop once a day and maintain daily records of the pressure drop readings.
3. The permittee shall record monthly asphalt production.
4. The permittee shall record monthly hours of operation.

12
Kokos
PTI
May 12, 1999

Emissions Unit ID: **P901**

D. Reporting Requirements

1. In accordance with paragraph A.2. of the General Terms and Conditions, the permittee shall submit deviation (excursion) reports which identify all exceedances of the above-mentioned allowable pressure drop range.

2. In accordance with paragraph A.2. of the General Terms and Conditions, the permittee shall submit deviation (excursion) reports which identify all exceedances of the above-mentioned allowable production rate.

E. Testing Requirements

1. Within 60 days of achieving the maximum production rate, but not later than 180 days after initial start-up, the permittee shall conduct, or have conducted, emission tests for this emissions unit in order to demonstrate compliance with the allowable mass emission rated for:

<u>Pollutant</u>	<u>Method</u>
particulates	Method 5 of 40 CFR Part 60, Appendix A
nitrogen oxides	Method 7 of 40 CFR Part 60, Appendix A
sulfur dioxide	Method 6 of 40 CFR Part 60, Appendix A
carbon monoxide	Method 10 of 40 CFR Part 60, Appendix A
organic compounds	Method 25A of 40 CFR Part 60, Appendix A

During emissions tests the unit shall be operating at or near maximum capacity and using only "virgin aggregate".

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and dates(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the field office's refusal to accept the results of the emissions test(s).

Personnel from the Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment and acquire data and information regarding the emissions unit operating parameters.

A comprehensive written report on the results of the emission test(s) shall be submitted within 30 days following completion of the test(s).

2. Emission Limitation:
0.04 gr/dscf PM

Compliance Method:

40 CFR 60.8, method 5

Sampling time and sample volume for each run shall be at least 60 minutes and 0.90 dscm (31.8 dscf)

3. Emission Limitation:
 Maximum 20% opacity

Compliance Method:
 40 CFR 60.8, method 9 and procedures in 40 CFR 60.11

4. Emission Limitation:
 30.0 #/hr NO_x, 30.0 TPY NO_x;

Compliance Method:
 Following required stack test, compliance with NO_x limits shall be determined by the following formula:

$$HN = (NEF) (MP/MHo)$$

Where:

HN = average hourly NO_x emissions, pounds per hour

NEF = NO_x emissions factor observed during the most recent compliance test in which compliance was demonstrated, pounds NO_x per ton asphalt produced

MP = monthly asphalt production, tons per month

Mho = monthly hours of operation, hours per month

The permittee shall use "NEF = 0.030 NO_x/ton asphalt" in the above formula from the data of the permit issuance until the permittee conducts the emissions testing specified below in paragraph E.7.

Annual limit compliance shall be determined by summing all monthly emissions above for the year.

5. Emission Limitation:
 22.4 #/hr SO₂, 22.4 TPY SO₂;

Compliance Method:
 Following required stack test, compliance with SO₂ limits shall be determined by the following formula:

$$HS = (SEF) (MP/MHo)$$

15
Kokos
PTI
May 12, 1999

Emissions Unit ID: **P901**

Where:

HS = average hourly SO₂ emissions, pounds per hour

SEF = SO₂ emissions factor observed during the most recent compliance test in which compliance was demonstrated, pounds SO₂ per ton asphalt produced

MP = monthly asphalt production, tons per month

Mho = monthly hours of operation, hours per month

The permittee shall use "SEF = 0.0033 SO₂/ton asphalt" in the above formula from the data of the permit issuance until the permittee conducts the emissions testing specified below in paragraph E.7.

Annual limit compliance shall be determined by summing all monthly emissions above for the year.

6. Emission Limitation:
27.6 #/hr OC, 27.6 TPY OC

Compliance Method:

Following required stack test, compliance with OC limits shall be determined by the following formula:

$$HO = (OEF) (MP/MHo)$$

Where:

HO = average hourly OC emissions, pounds per hour

OEF = OC emissions factor observed during the most recent compliance test in which compliance was demonstrated, pounds NO_x per ton asphalt produced

MP = monthly asphalt production, tons per month

Mho = monthly hours of operation, hours per month

The permittee shall use "OEF = 0.051 OC/ton asphalt" in the above formula from the data of the permit issuance until the permittee conducts the emissions testing specified below in paragraph E.7.

Annual limit compliance shall be determined by summing all monthly emissions above for the year.

F. Miscellaneous Requirements

None

PART II: SPECIAL TERMS AND CONDITIONS [Continued]

A. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
unpaved roadways and parking areas	OAC rule 3745-31-05	2.49 TPY PM no visible particulate emissions except for 3 minutes during any 60-minute period
	OAC rule 3745-17-07 (B)(5)	best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see Sections A.2.a through A.2.f)
	OAC rule 3745-17-08 (B), (B)(2)	less stringent than the above-mentioned visible emission limitation
		less stringent than the above-mentioned control measure requirements

2. Additional Terms and Conditions

- 2.a. The permittee shall employ best available control measures on all unpaved roadways and parking areas for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to treat the unpaved roadways and parking areas with water at sufficient treatment frequencies to ensure

compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

- 2.b. The needed frequencies of implementation of the control measures shall be determined by the permittee's inspections pursuant to the monitoring section of this permit. Implementation of the control measures shall not be necessary for an unpaved roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Implementation of any control measure may be suspended if unsafe or hazardous driving conditions would be created by its use.
- 2.c. Any unpaved roadway or parking area that takes the characteristics of a paved roadway or parking area due to the application of certain types of dust suppressants shall remain subject to the visible emission limitation for unpaved roadways and parking areas. Any unpaved roadway or parking area that is paved shall be subject to the visible emission limitation for paved roadways and parking areas.
- 2.d. The permittee shall promptly remove, in such a manner as to minimize or prevent resuspension, earth and/or other material from paved streets onto which such material has been deposited by trucking or earth moving equipment or erosion by water or other means.
- 2.e. Open-bodied vehicles transporting materials likely to become airborne shall have such materials covered at all times if the control measure is necessary for the materials being transported.
- 2.f. Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the best available technology requirements of OAC rule 3745-31-05.

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

- 1. Except as otherwise provided in this section, the permittee shall perform inspections of

the roadways and parking areas in accordance with the following frequencies:

<u>unpaved roadways and parking areas</u>	<u>minimum inspection frequency</u>
---	-------------------------------------

all	Daily
-----	-------

2. The purpose of the inspections is to determine the need for implementing the above-mentioned control measures. The inspections shall be performed during representative, normal traffic conditions. No inspection shall be necessary for a roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above-identified events shall be performed as soon as such event(s) has (have) ended.

Emissions Unit ID: **F001**

3. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.
4. The permittee shall maintain records of the following information:
 - a. the date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;
 - b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;
 - c. the dates the control measures were implemented; and,
 - d. on a calendar quarter basis, the total number of days the control measures were implemented and the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measures.

The information required in 4.d. shall be kept separately for the unpaved roadways and parking areas, and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:
 - a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and,
 - b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.
2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

21
Kokos
PTI
May 12, 1999

Emissions Unit ID: **F001**

1. Emissions Limitation:
No visible particulate emissions from any unpaved roadway or parking area except for a period of time not to exceed three minutes during any 60-minute observation period

22

Kokos

PTI

May 12, 1999

Emissions Unit ID: **F001**

Compliance Method:

Compliance with the emission limitation for the unpaved roadways and parking areas identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources," as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(d) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

None

PART II: SPECIAL TERMS AND CONDITIONS [Continued]

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Material Handling: front-end loader to hoppers hoppers to conveyor conveyor to conveyor storage silos to trucks 2 screens crusher w/water sprays	OAC rule 3745-31-05	9.7 TPY PM; opacity shall not exceed 20% as a three minute average
	OAC rule 3745-17-07 (B)(1)	best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see Sections A.2.b through A.2.d)
	OAC rule 3745-17-08 (B)	less stringent than, or equal in stringency to, the above-mentioned visible emission limitation
		less stringent than, or equal in stringency to, the above-mentioned control measure requirements

2. Additional Terms and Conditions

- 2.a. The material handling operation(s) that are covered by this permit and subject to the above-mentioned requirements are listed below:

24

Kokos

PTI

May 12, 1999

Emissions Unit ID: **F002**

front-end loader to 7 hoppers

7 hoppers to conveyor

6 transfer points from conveyor to conveyor

2 storage silos to trucks

2 screens

crusher w/water sprays

Emissions Unit ID: **F002**

- 2.b. The permittee shall employ best available control measures for the above-identified material handling operation(s) for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee’s permit application, the permittee has committed to perform the following control measure(s) to ensure compliance:

<u>material handling operation(s)</u>	<u>control measure(s)</u>
front-end loader to 7 hoppers of 7 hoppers to conveyor 6 transfer points from conveyor to conveyor 2 storage silos to trucks 2 screens crusher w/water sprays	minimize or eliminate visible emissions fugitive dust

Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

- 2.c. For each material handling operation that is not adequately enclosed, the above-identified control measure(s) shall be implemented if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) is (are) necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measure(s) shall continue during the operation of the material handling operation(s) until further observation confirms that use of the control measure(s) is unnecessary.
- 2.d. Implementation of the above-mentioned control measure(s) in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the requirements of OAC rules 3745-17-08 and 3745-31-05.

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

- 1. Except as otherwise provided in this section, for material handling operations that are not adequately enclosed, the permittee shall perform inspections of such operations in

26

Kokos

PTI

May 12, 1999

Emissions Unit ID: **F002**

accordance with the following minimum frequencies:

<u>material handling operation(s)</u>	<u>minimum inspection frequency</u>
---------------------------------------	-------------------------------------

All	Daily
-----	-------

2. The above-mentioned inspections shall be performed during representative, normal operating conditions.
3. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.
4. The permittee shall maintain records of the following information:
 - a. the date and reason any required inspection was not performed;
 - b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measure(s);
 - c. the dates the control measure(s) was (were) implemented; and,
 - d. on a calendar quarter basis, the total number of days the control measure(s) was (were) implemented.

The information in 4.d. shall be kept separately for each material handling operation identified above, and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:
 - a. each day during which an inspection was not performed by the required frequency; and,
 - b. each instance when a control measure, that was to be performed as a result of an inspection, was not implemented.
2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the visible emission limitation for the material handling operation(s) identified above shall be determined in accordance with *"Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources")*, as such Appendix existed on July 1, 1996.
2. Compliance with the 9.7 TPY PM emission limit will be based on the emissions factors in AP-42 Table 11.19.2-2, Edition 5, actual annual production, actual annual operating hours, and 50% control for water application.

F. Miscellaneous Requirements

None

PART II: SPECIAL TERMS AND CONDITIONS [Continued]**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
load-in and load-out of storage piles (see Section A.2.a for identification of storage piles)	OAC rule 3745-31-05	9.98 TPY PM; no visible emissions except for one minute in any hour best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see Sections A.2.b, A.2.c and A.2.f)
wind erosion from storage piles (see Section A.2.a for identification of storage piles)	OAC rule 3745-31-05	no visible emissions except for one minute in any hour best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see Sections A.2.d through A.2.f)
load-in and load-out of storage piles, and wind erosion from storage piles	OAC rule 3745-17-07 (B)(6) OAC rule 3745-17-08 (B), (B)(6)	less stringent than the above-mentioned visible emission limitation less stringent than the above-mentioned control measure requirements

2. Additional Terms and Conditions

2.a. The storage piles that are covered by this permit and subject to the above-mentioned requirements are listed below:

- 3 Limestone Piles
- 3 Gravel Piles
- 2 Sand Piles
- 4 Recycled Asphalt Piles

2.b. The permittee shall employ best available control measures on all load-in and load-out operations associated with the storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to keeping the aggregate wet and reducing drop height of front-end loader buckets to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

2.c. The above-mentioned control measure(s) shall be employed for each load-in and load-out operation of each storage pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) are necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measure(s) shall continue during any such operation until further observation confirms that use of the measure(s) is unnecessary.

2.d. The permittee shall employ best available control measures for wind erosion from the surfaces of all storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to keeping the aggregate wet to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

2.e. The above-mentioned control measure(s) shall be employed for wind erosion from each pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) are necessary to ensure compliance with the above-mentioned applicable requirements. Implementation of the control measure(s) shall not be

31
Kokos
PTI
May 12, 1999

Emissions Unit ID: **F003**

necessary for a storage pile that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements.

- 2.f. Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the requirements of OAC rules 3745-17-08 and 3745-31-05.

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform inspections of each load-in operation at each storage pile in accordance with the following frequencies:

<u>storage pile identification</u>	<u>minimum load-in inspection frequency</u>
3 Limestone Piles	Daily
3 Gravel Piles	
2 Sand Piles	
4 Recycled Asphalt Piles	

2. Except as otherwise provided in this section, the permittee shall perform inspections of each load-out operation at each storage pile in accordance with the following frequencies:

<u>storage pile identification</u>	<u>minimum load-out inspection frequency</u>
3 Limestone Piles	Daily
3 Gravel Piles	
2 Sand Piles	
4 Recycled Asphalt Piles	

3. Except as otherwise provided in this section, the permittee shall perform inspections of the wind erosion from pile surfaces associated with each storage pile in accordance with the following frequencies:

<u>storage pile identification</u>	<u>minimum wind erosion inspection frequency</u>
3 Limestone Piles	Daily
3 Gravel Piles	
2 Sand Piles	
4 Recycled Asphalt Piles	

4. No inspection shall be necessary for wind erosion from the surface of a storage pile when the pile is covered with snow and/or ice and for any storage pile activity if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one

week.

5. The purpose of the inspections is to determine the need for implementing the control measures specified in this permit for load-in and load-out of a storage pile, and wind erosion from the surface of a storage pile. The inspections shall be performed during representative, normal storage pile operating conditions.

6. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.
7. The permittee shall maintain records of the following information:
 - a. the date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;
 - b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;
 - c. the dates the control measures were implemented; and,
 - d. on a calendar quarter basis, the total number of days the control measures were implemented and, for wind erosion from pile surfaces, the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measure(s).

The information required in 7.d. shall be kept separately for (i) the load-in operations, (ii) the load-out operations, and (iii) the pile surfaces (wind erosion), and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:
 - a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and,
 - b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.
2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

35

Kokos

PTI

May 12, 1999

Emissions Unit ID: **F003**

E. Testing Requirements

1. Compliance with the visible emission limitations for the storage piles identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

Emissions Unit ID: **F003**

2. Compliance with the 9.98 TPY PM emission limitation will be based on the emission factors from RACM page 2-465, table 2.21-1: Loading onto pile - 0.04 lb/ton loaded onto pile, vehicular traffic - 0.13 lb/ton stored, wind erosion - 0.11 lb/ton stored, load out of pile = 0.05 lb/ton stored; actual amounts of tons stored and loaded in and 50% control for water application.

F. Miscellaneous Requirements

None