

Synthetic Minor Determination and/or Netting Determination

Permit To Install: 03-17224

A. Source Description

Port Clinton Biofuels, Inc. is proposing to construct a new 115.5 million gallon per year fuel ethanol production facility in the town of Port Clinton, Ohio (Ottawa County). Port Clinton will produce fuel ethanol by fermenting corn with subsequent distillation. The proposed facility is classified by USEPA as a chemical manufacturing plant, therefore the facility is one of the 28 listed source categories for PSD regulations.

B. Facility Emissions and Attainment Status

This is a new facility and is a synthetic minor. Ottawa County is classified as attainment for all pollutants. The company is requesting federally enforceable limits to avoid Title V and New source review.

C. Source Emissions

The potential emissions from the proposed installation for NOx, CO, VOC, PE and SO2 are greater than the New Source Review Prevention of Significant Deterioration significance level thresholds. The company is requesting federally enforceable limits on the emergency generator (Emissions unit P011) and the emergency water pump (Emissions unit P012) to avoid PSD regulations for NOx, CO, VOC, PE and SO2 .

This project will include the installation of the following and the annual potential to emit:

		NOX	CO	TSP	PM10	SO2	VOC
B001	Boiler #1	8.09	7.27	3.02	3.02	0.22	2.18
B002	Boiler #2	8.09	7.27	3.02	3.02	0.22	2.18
B003	Boiler #3	8.09	7.27	3.02	3.02	0.22	2.18
B004	Boiler #4	8.09	7.27	3.02	3.02	0.22	2.18
F001	Paved roadways and parking areas			32.98	6.34		
J001	ethanol loading operations (fugitive)						4.49
P001	grain handling			1.50	1.50		
P002	hammermill#1			1.13	1.13		
P003	hammer mill#2			1.13	1.13		
P004	hammer mill#3			1.13	1.13		
P005	hammer mill#4			1.13	1.13		
P006	milled corn storage			0.56	0.56		
P007	ethanol distillation and liquefaction	56.76	67.46	29.78	29.78	65.70	43.80
P008	ethanol fermentation						35.04
P009	drying & cooling #1						
P010	drying & cooling #2						
P011	cooling tower			1.66	1.66		
P012	emergency generator	2.24	0.51	0.04	0.07	0.34	0.07
P013	emergency water pump	0.5	0.17	0.07	0.03	0.06	0.07
P801	fugitive VOC leaks						3.48
P802	wetcake storage*						0
P901	grain receiving, transferring, conveying and storage						
	stack			8.63	8.63		
	fugitive			4.04	0.90		

P902	DDGS reclaim/storage						
	stack			0.38	0.38		
	fugitive			0.12	0.03		
P903	DDGS loadout						
	stack			1.13	1.13		
	fugitive			0.13	0.03		
T001	200 proof ethanol storage tank					0.25	
T002	200 proof ethanol storage tank					0.25	
T003	denaturant storage tank					0.75	
T004	denatured ethanol storage tank					0.21	
TOTAL	Synthetic Minor Total	91.04	98.46	97.62	67.65	66.98	97.27
	Total without restrictions	504.12	193.92	110.06	80.13	201.28	111.22

*emissions from the wetcake is accounted for in P007

D. Conclusion

Since the potential emissions from the installation of this facility will be less than PSD significance levels for NOx, CO, VOC, PE and SO2 the source is synthetically minored out of PSD requirements.



State of Ohio Environmental Protection Agency

**RE: DRAFT PERMIT TO INSTALL
OTTAWA COUNTY**

CERTIFIED MAIL

Street Address:

Mailing Address:

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Lazarus Gov.
Center

Application No: 03-17224

Fac ID: 0362010154

DATE: 6/12/2008

Port Clinton Biofuels, Inc.
Aruna Raj
14 Wall Street, 20th Floor
New York, NY 10005

You are hereby notified that the Ohio Environmental Protection Agency has made a draft action recommending that the Director issue a Permit to Install for the air contaminant source(s) [emissions unit(s)] shown on the enclosed draft permit. This draft action is not an authorization to begin construction or modification of your emissions unit(s). The purpose of this draft is to solicit public comments on the proposed installation. A public notice concerning the draft permit will appear in the Ohio EPA Weekly Review and the newspaper in the county where the facility will be located. Public comments will be accepted by the field office within 30 days of the date of publication in the newspaper. Any comments you have on the draft permit should be directed to the appropriate field office within the comment period. A copy of your comments should also be mailed to Robert Hodanbosi, Division of Air Pollution Control, Ohio EPA, P.O. Box 1049, Columbus, OH, 43216-1049.

A Permit to Install may be issued in proposed or final form based on the draft action, any written public comments received within 30 days of the public notice, or record of a public meeting if one is held. You will be notified in writing of a scheduled public meeting. Upon issuance of a final Permit to Install a fee of **\$21600** will be due. Please do not submit any payment now.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469. If you have any questions about this draft permit, please contact the field office where you submitted your application, or Mike Ahern, Field Operations & Permit Section at (614) 644-3631.

Sincerely,

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: USEPA

NWDO

TOLEDO METRO AREA COUNCIL OF GOVTS.

MI

OTTAWA COUNTY

PUBLIC NOTICE
OHIO ENVIRONMENTAL PROTECTION AGENCY
ISSUANCE OF DRAFT PERMIT TO INSTALL
TO PORT CLINTON BIOFUELS

Public notice is hereby given that the Ohio Environmental Protection Agency (EPA) has issued, on Tuesday, June 12, 2008, a draft action of Permit to Install (PTI) application number 03-13224 to Port Clinton Biofuels. This draft PTI is for public comment on the proposed installation of an ethanol production facility and associated support equipment. This will result in particulate (PE), sulfur dioxide (SO₂), nitrogen oxides (NO_x), carbon monoxide (CO), acetaldehyde, and volatile organic compounds (VOC) emissions. The resulting emissions in the permit are as follows:

<u>Pollutant</u>	<u>Tons Per Year</u>
NOx	91.04
CO	98.46
PE	97.66
PM10	67.65
VOC	97.27
SO2	67.40

Written comments must be received by Ohio EPA at the close of the public comment period. Comments received after this date will not be considered to be a part of the official record. Written comments may be submitted at the hearing or sent to: Elissa Hartfield, Ohio Environmental Protection Agency, Northwest District Office, 347 North Dunbridge Road, Bowling Green, Ohio 43402. The close of the public comment period will be announced in a subsequent public announcement at a later date.

Copies of the draft permit application and technical support information may be reviewed and/or copies requested of these materials by contacting Ohio EPA, Northwest District Office, 347 North Dunbridge Road, Bowling Green, Ohio 43402, telephone 419-352-8461.



**Permit To Install
Terms and Conditions**

**Issue Date: To be entered upon final issuance
Effective Date: To be entered upon final issuance**

DRAFT PERMIT TO INSTALL 03-17224

Application Number: 03-17224
Facility ID: 0362010154
Permit Fee: **To be entered upon final issuance**
Name of Facility: Port Clinton Biofuels, Inc.
Person to Contact: Aruna Raj
Address: 14 Wall Street, 20th Floor
New York, NY 10005

Location of proposed air contaminant source(s) [emissions unit(s)]:
**5801 West Lakeshore Drive
Port Clinton, Ohio**

Description of proposed emissions unit(s):
115.5 MMgal/year ethanol plant.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Chris Korleski
Director

Port Clinton Biofuels, Inc.

Facility ID: 0362010154

PTI Application: 03-17224

Issued: To be entered upon final issuance

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted (i.e., postmarked) quarterly by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections,

Port Clinton Biofuels, Inc.
PTI Application: 03-17224

Facility ID: 0362010154

Issued: To be entered upon final issuance

conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

Port Clinton Biofuels, Inc.

PTI Application: 03-17224

Issued: To be entered upon final issuance

Facility ID: 0362010154

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available

Port Clinton Biofuels, Inc.
PTI Application: 03-17224

Facility ID: 0362010154

Issued: To be entered upon final issuance

Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
 TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
NOx	91.04
CO	98.46
PE	97.66
PM10	67.65
VOC	97.27
SO2	67.40

Emissions Unit ID: B001

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (B001) - 92.4 mmBtu/hr natural gas fired boiler

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(C)	<p>The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart Dc and OAC rule 3745-17-07(A)(1).</p> <p>Nitrogen oxides (NOx) emissions shall not exceed 0.020 pound per million British thermal units (lbs/mmBtu) of actual heat input and 8.09 tons per year (TPY).</p> <p>Carbon monoxide (CO) emissions shall not exceed 1.66 lbs/hr and 7.27 TPY.</p> <p>Volatile organic compound (VOC) emissions shall not exceed 0.50 lb/hr and 2.19 TPY.</p> <p>Particulate matter equal to or less than 10 microns in size (PM10) shall not exceed 0.69 pound per hour and 3.02 TPY.</p> <p>See sections A.2.a and A.2.e.</p>
OAC rule 3745-17-07(A)(1)	Visible particulate emissions (PE) shall not exceed 20% opacity, as a six-minute average, except as provided by rule.
OAC rule 3745-17-10(B)(1)	See section A.2.b.
40 CFR Part 60, Subpart Dc	See section B.1.
OAC rule 3745-21-08(B)	See section A.2.d.
OAC rule 3745-114-01 ORC 3704.03(F)	See section C.3.

Issued: To be entered upon final issuance

2. Additional Terms and Conditions

- 2.a** The permittee has requested voluntary allowable emission limitations for NO_x, CO, VOC and PM₁₀. The short-term (lb/hour) and long-term (tons/year) emission limitations for the specified pollutants are being established as practically and legally enforceable requirements representing the potential to emit based on the physical capacity of the emissions unit and the use of natural gas.
- 2.b** The emissions limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(C).
- 2.c** This emissions unit is exempt from the requirements of OAC rule 3745-18-06 in accordance with OAC rule 3745-18-06(A).
- 2.d** The permittee has satisfied the "best available control techniques and operating practices" required pursuant to OAC rule 3745-21-08(B) by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05(A)(3) in this Permit to Install.

On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the requirement to satisfy the "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

- 2.e** For the purposes of this permit, all PE is considered to be PM₁₀.

B. Operational Restrictions

- 1. The permittee shall burn only natural gas in this emissions unit.

C. Monitoring and/or Recordkeeping Requirements

- 1. Pursuant to 40 CFR Part 60, Subpart Dc, the permittee shall record and maintain records of the amounts of each fuel combusted each day. These records shall be maintained by the permittee for a period of two years following the date of such record.

Emissions Unit ID: **B001**

2. For each day during which the permittee burns a fuel other than natural gas, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.
3. The permit to install for these emissions unit(s) J001, B001-B004, P007, P008, P009 and P010 was evaluated based on the actual materials and the design parameters of the emissions unit's(s') exhaust system, as specified by the permittee in the permit application. The "Toxic Air Contaminant Statute", ORC 3704.03(F), was applied to this/these emissions unit(s) for each toxic air contaminant listed in OAC rule 3745-114-01, using data from the permit application; and modeling was performed for each toxic air contaminant(s) emitted at over one ton per year using an air dispersion model such as SCREEN 3.0, AERMOD, or ISCST3, or other Ohio EPA approved model. The predicted 1-hour maximum ground-level concentration result(s) from the approved air dispersion model, was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC), calculated as described in the Ohio EPA guidance document entitled "Review of New Sources of Air Toxic Emissions, Option A", as follows:
 - a. the exposure limit, expressed as a time-weighted average concentration for a conventional 8-hour workday and a 40-hour workweek, for each toxic compound(s) emitted from the emissions unit(s), (as determined from the raw materials processed and/or coatings or other materials applied) has been documented from one of the following sources and in the following order of preference (TLV was and shall be used, if the chemical is listed):
 - i. threshold limit value (TLV) from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices";
or
 - ii. STEL (short term exposure limit) or the ceiling value from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices"; the STEL or ceiling value is multiplied by 0.737 to convert the 15-minute exposure limit to an equivalent 8-hour TLV.
 - b. The TLV is divided by ten to adjust the standard from the working population to the general public (TLV/10).
 - c. This standard is/was then adjusted to account for the duration of the exposure or the operating hours of the emissions unit(s), i.e., "X" hours per day and "Y" days per week, from that of 8 hours per day and 5 days per week. The resulting

Issued: To be entered upon final issuance

calculation was (and shall be) used to determine the Maximum Acceptable Ground-Level Concentration (MAGLC):

$$TLV/10 \times 8/X \times 5/Y = 4 TLV/XY = MAGLC$$

- d. The following summarizes the results of dispersion modeling for the significant toxic contaminants (emitted at 1 or more tons/year) or "worst case" toxic contaminant(s):

Pollutant: Acetaldehyde

TLV (mg/m³): 45.0

Maximum Hourly Emission Rate (lbs/hr): 2.11

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 28.38

MAGLC (ug/m³): 1071.43

Pollutant: Hexane

TLV (mg/m³): 176.24

Maximum Hourly Emission Rate (lbs/hr): 1.09

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 0.81

MAGLC (ug/m³): 4,196

Pollutant: Methanol

TLV (mg/m³): 262

Maximum Hourly Emission Rate (lbs/hr): 0.34

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 0.69

MAGLC (ug/m³): 6238

The permittee, has demonstrated that emissions of acetaldehyde, hexane and methanol, from emissions unit(s) J001, B001, B002, B003, B004, P007, P008, P009 and P010, are calculated to be less than eighty per cent of the maximum acceptable ground level concentration (MAGLC); any new raw material or processing agent shall not be applied without evaluating each component toxic air contaminant in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F).

4. Prior to making any physical changes to or changes in the method of operation of the emissions unit(s), that could impact the parameters or values that were used in the predicted 1-hour maximum ground-level concentration", the permittee shall re-model the change(s) to demonstrate that the MAGLC has not been exceeded. Changes that can affect the parameters/values used in determining the 1-hour maximum ground-level concentration include, but are not limited to, the following:

Emissions Unit ID: B001

- a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a new toxic air contaminant with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any toxic air contaminant listed in OAC rule 3745-114-01, that was modeled from the initial (or last) application; and
- c. physical changes to the emissions unit(s) or its/their exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Toxic Air Contaminant Statute" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to a non-restrictive change to a parameter or process operation, where compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), has been documented. If the change(s) meet(s) the definition of a "modification" or if a new toxic is emitted, or the modeled toxic(s) is/are expected to exceed the previous modeled level(s), then the permittee shall apply for and obtain a final permit-to-install prior to the change. The Director may consider any significant departure from the operations of the emissions unit, described in the permit-to-install application, as a modification that results in greater emissions than the emissions rate modeled to determine the ground level concentration; and may require the permittee to submit a permit-to-install application for the increased emissions.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

5. The permittee shall collect, record, and retain the following information for each toxic evaluation conducted to determine compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F):
 - a. a description of the parameters/values used in each compliance demonstration and the parameters or values changed for any re-evaluation of the toxic(s) modeled (the composition of materials, new toxic contaminants emitted, change in stack/exhaust parameters, etc.);
 - b. the Maximum Acceptable Ground-Level Concentration (MAGLC) for each significant toxic contaminant or worst-case contaminant, calculated in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F);

Issued: To be entered upon final issuance

- c. a copy of the computer model run(s), that established the predicted 1-hour maximum ground-level concentration that demonstrated the emissions unit(s) to be in compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), initially and for each change that requires re-evaluation of the toxic air contaminant emissions; and
- d. the documentation of the initial evaluation of compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), and documentation of any determination that was conducted to re-evaluate compliance due to a change made to the emissions unit(s) or the materials applied.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

- 6. The permittee shall maintain a record of any change made to a parameter or value used in the dispersion model, used to demonstrate compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration. The record shall include the date and reason(s) for the change and if the change would increase the ground-level concentration.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

Emissions Unit ID: **B001****D. Reporting Requirements**

1. The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than natural gas was burned in the emissions unit. These reports shall be submitted to Ohio EPA, Northwest District Office (NWDO) within 30 days after the deviation occurs.
2. This emissions unit is subject to the applicable provisions of Subpart Dc of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60.

The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

Pursuant to 40 CFR Part 60.7, the permittee is hereby advised of the requirement to report the following at the appropriate times:

- a. construction date (no later than 30 days after such date);
- b. actual start-up date (within 15 days after such date); and,
- c. date of performance testing (if required, at least 30 days prior to testing).

Reports are to be sent to:

Ohio Environmental Protection Agency
DAPC - Permit Management Unit
P. O. Box 163669
Columbus, Ohio 43216-3669

and

Ohio Environmental Protection Agency
Northwest District Office
Division of Air Pollution Control
347 North Dunbridge Road
Bowling Green, Ohio 43402

3. The permittee shall submit annual reports to the appropriate Ohio EPA District Office or local air agency, documenting any changes made to a parameter or value used in the dispersion model, that was used to demonstrate compliance with the "Toxic Air

Issued: To be entered upon final issuance

Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration. If no changes to the emissions unit(s) or the exhaust stack have been made, then the report shall include a statement to this effect. This report shall be postmarked or delivered no later than January 31 following the end of each calendar year.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

E. Testing Requirements

1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. The emission testing shall be conducted on at least one of the following emissions units: B001, B002, B003, or B004.
 - b. The emission testing shall be conducted within 60 days after achieving the maximum production rate at which the emissions unit will be operated but not later than 180 days after initial startup of emissions units to be tested. The emissions unit to be tested shall be either B001, B002, B003 or B004, whichever unit achieves its maximum production rate first.
 - c. The emission testing shall be conducted to demonstrate compliance with the 0.020 lb/mmBtu emission limitation for NO_x and the 1.66 lbs/hr CO emission limitation.
 - d. The following test methods shall be employed to demonstrate compliance with the above emissions limitations:
 - i. for NO_x, Methods 1-4 and 7 of 40 CFR Part 60, Appendix A; and
 - ii. for CO, Methods 1-4 and 10 of 40 CFR Part 60, Appendix A.

Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA, NWDO.
 - e. The test(s) shall be conducted while the emissions unit is operating at its maximum capacity, unless otherwise specified or approved by the Ohio EPA, NWDO.

Emissions Unit ID: **B001**

- f. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, NWDO. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, NWDO's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA, NWDO shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report of the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA, NWDO within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, NWDO.

2. Compliance with the emission limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:

- a. Emissions Limitations: 0.020 lb NOx/mmBtu; 8.09 TPY NOx

Applicable Compliance Method:

Compliance with the lb NOx/mmBtu emission limitation shall be demonstrated based on the results of emission testing conducted in accordance with Methods 1 - 4 and 7 of 40 CFR Part 60, Subpart A.

The annual emission limitation was developed by multiplying the lb NOx/mmBtu limitation by the maximum heat input capacity of 92.4 mmBtu/hr, the maximum operating schedule of 8760 hours/year, and then applying the conversion factor of 2000 lb/ton. Therefore, if compliance is shown with the lb NOx/mmBtu limitation, compliance with the annual limitation shall be assumed.

- b. Emissions Limitations: 1.66 lbs CO/hr; 7.27 TPY CO

Applicable Compliance Method:

Issued: To be entered upon final issuance

Compliance with the hourly allowable CO emission limitation shall be demonstrated based on the results of emission testing conducted in accordance with Methods 1 - 4 and 10 of 40 CFR Part 60, Subpart A.

The annual emission limitation was developed by multiplying the manufacturer's guaranteed emission factor of 0.018 lb CO/mmBtu limitation by the maximum heat input capacity of 92.4 mmBtu/hr, the maximum operating schedule of 8760 hours/year, and then applying the conversion factor of 2000 lb/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- c. Emissions Limitations: 0.50 lb VOC/hr; 2.19 TPY VOC

Applicable Compliance Method:

The hourly allowable VOC emission limitation was developed by multiplying the USEPA, AP42 emission factor of 5.5 lb/mmscf (Table 1.4-2, revised 7/98) by the maximum heat input capacity of 92.4 mmBtu/hr then dividing by the heating value of natural gas of 1020 mmscf/mmBtu.

If required, compliance with the hourly allowable emission limitation shall be determined in accordance with test Methods 1-4 and 18, 25 or 25A of 40 CFR Part 60, Appendix A.

The annual emission limitation was developed by multiplying the hourly allowable emission limitation by the maximum operating schedule of 8760 hours/year, and then applying the conversion factor of 2000 lb/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- d. Emissions Limitations: 0.69 lb PM10/hr; 3.02 TPY PM10

Applicable Compliance Method:

The hourly allowable PM10 emission limitation was developed by multiplying the USEPA, AP42 emission factor of 7.6 lb/mmscf (Table 1.4-2, revised 7/98) by the maximum heat input capacity of 92.4 mmBtu/hr then dividing by the heating value of natural gas of 1020 mmscf/mmBtu.

If required, compliance with the PM10 limitation shall be determined in

Issued: To be entered upon final issuance

accordance with the test methods and procedures specified in 40 CFR Part 51, Appendix M, Methods 201 and 202. Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA, Northwest District Office (NWDO).

The annual emission limitation was developed by multiplying the hourly allowable emission limitation by the maximum operating schedule of 8760 hours/year, and applying the conversion factor of 2000 lb/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- e. Emissions Limitation: Visible PE from the stack serving this emissions unit shall not exceed 20% opacity, as a six-minute average.

Applicable Compliance Method:

Compliance shall be demonstrated in accordance with OAC rule 3745-17-03(B)(1).

F. Miscellaneous Requirements

- 1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (B002) - 92.4 mmBtu/hr natural gas fired boiler

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(C)	<p>The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart Dc and OAC rule 3745-17-07(A)(1).</p> <p>Nitrogen oxides (NO_x) emissions shall not exceed 0.020 pound per million British thermal units (lbs/mmBtu) of actual heat input and 8.09 tons per year (TPY).</p> <p>Carbon monoxide (CO) emissions shall not exceed 1.66 lbs/hr and 7.27 TPY.</p> <p>Volatile organic compound (VOC) emissions shall not exceed 0.50 lb/hr and 2.19 TPY.</p> <p>Particulate matter equal to or less than 10 microns in size (PM₁₀) shall not exceed 0.69 pound per hour and 3.02 TPY.</p> <p>See sections A.2.a and A.2.e.</p>
OAC rule 3745-17-07(A)(1)	Visible PE shall not exceed 20% opacity, as a six-minute average, except as provided by rule.
OAC rule 3745-17-10(B)(1)	See section A.2.b.
40 CFR Part 60, Subpart Dc	See section B.1.
OAC rule 3745-21-08(B)	See section A.2.d.
OAC rule 3745-114-01 ORC 3704.03(F)	See section C.3.

Issued: To be entered upon final issuance

2. Additional Terms and Conditions

- 2.a** The permittee has requested voluntary allowable emission limitations for NO_x, CO, VOC and PM₁₀. The short-term (lb/hour) and long-term (tons/year) emission limitations for the specified pollutants are being established as practically and legally enforceable requirements representing the potential to emit based on the physical capacity of the emissions unit and the use of natural gas.
- 2.b** The emissions limitations specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(C).
- 2.c** This emissions unit is exempt from the requirements of OAC rule 3745-18-06 in accordance with OAC rule 3745-18-06(A).
- 2.d** The permittee has satisfied the "best available control techniques and operating practices" required pursuant to OAC rule 3745-21-08(B) by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05(A)(3) in this Permit to Install.

On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the requirement to satisfy the "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

- 2.e** For the purposes of this permit, all PE is considered to be PM₁₀.

B. Operational Restrictions

- 1. The permittee shall burn only natural gas in this emissions unit.

C. Monitoring and/or Recordkeeping Requirements

- 1. Pursuant to 40 CFR Part 60, Subpart Dc, the permittee shall record and maintain records of the amount of each fuel combusted each day. These records shall be maintained for a period of two years following the date of such record.

Emissions Unit ID: **B002**

2. For each day during which the permittee burns a fuel other than natural gas, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.
3. The permit to install for these emissions unit(s) J001, B001-B004, P007, P008, P009 and P010 was evaluated based on the actual materials and the design parameters of the emissions unit's(s') exhaust system, as specified by the permittee in the permit application. The "Toxic Air Contaminant Statute", ORC 3704.03(F), was applied to this/these emissions unit(s) for each toxic air contaminant listed in OAC rule 3745-114-01, using data from the permit application; and modeling was performed for each toxic air contaminant(s) emitted at over one ton per year using an air dispersion model such as SCREEN 3.0, AERMOD, or ISCST3, or other Ohio EPA approved model. The predicted 1-hour maximum ground-level concentration result(s) from the approved air dispersion model, was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC), calculated as described in the Ohio EPA guidance document entitled "Review of New Sources of Air Toxic Emissions, Option A", as follows:
 - a. the exposure limit, expressed as a time-weighted average concentration for a conventional 8-hour workday and a 40-hour workweek, for each toxic compound(s) emitted from the emissions unit(s), (as determined from the raw materials processed and/or coatings or other materials applied) has been documented from one of the following sources and in the following order of preference (TLV was and shall be used, if the chemical is listed):
 - i. threshold limit value (TLV) from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices";
or
 - ii. STEL (short term exposure limit) or the ceiling value from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices"; the STEL or ceiling value is multiplied by 0.737 to convert the 15-minute exposure limit to an equivalent 8-hour TLV.
 - b. The TLV is divided by ten to adjust the standard from the working population to the general public (TLV/10).
 - c. This standard is/was then adjusted to account for the duration of the exposure or the operating hours of the emissions unit(s), i.e., "X" hours per day and "Y" days per week, from that of 8 hours per day and 5 days per week. The resulting

Issued: To be entered upon final issuance

calculation was (and shall be) used to determine the Maximum Acceptable Ground-Level Concentration (MAGLC):

$$TLV/10 \times 8/X \times 5/Y = 4 TLV/XY = MAGLC$$

- d. The following summarizes the results of dispersion modeling for the significant toxic contaminants (emitted at 1 or more tons/year) or "worst case" toxic contaminant(s):

Pollutant: Acetaldehyde

TLV (mg/m³): 45.0

Maximum Hourly Emission Rate (lbs/hr): 2.11

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 28.38

MAGLC (ug/m³): 1071.43

Pollutant: Hexane

TLV (mg/m³): 176.24

Maximum Hourly Emission Rate (lbs/hr): 1.09

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 0.81

MAGLC (ug/m³): 4,196

Pollutant: Methanol

TLV (mg/m³): 262

Maximum Hourly Emission Rate (lbs/hr): 0.34

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 0.69

MAGLC (ug/m³): 6238

The permittee, has demonstrated that emissions of acetaldehyde, hexane and methanol, from emissions unit(s) J001, B001, B002, B003, B004, P007, P008, P009 and P010, are calculated to be less than eighty per cent of the maximum acceptable ground level concentration (MAGLC); any new raw material or processing agent shall not be applied without evaluating each component toxic air contaminant in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F).

4. Prior to making any physical changes to or changes in the method of operation of the emissions unit(s), that could impact the parameters or values that were used in the predicted 1-hour maximum ground-level concentration", the permittee shall re-model the change(s) to demonstrate that the MAGLC has not been exceeded. Changes that can affect the parameters/values used in determining the 1-hour maximum ground-level concentration include, but are not limited to, the following:

Emissions Unit ID: B002

- a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a new toxic air contaminant with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any toxic air contaminant listed in OAC rule 3745-114-01, that was modeled from the initial (or last) application; and
- c. physical changes to the emissions unit(s) or its/their exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Toxic Air Contaminant Statute" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to a non-restrictive change to a parameter or process operation, where compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), has been documented. If the change(s) meet(s) the definition of a "modification" or if a new toxic is emitted, or the modeled toxic(s) is/are expected to exceed the previous modeled level(s), then the permittee shall apply for and obtain a final permit-to-install prior to the change. The Director may consider any significant departure from the operations of the emissions unit, described in the permit-to-install application, as a modification that results in greater emissions than the emissions rate modeled to determine the ground level concentration; and may require the permittee to submit a permit-to-install application for the increased emissions.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

5. The permittee shall collect, record, and retain the following information for each toxic evaluation conducted to determine compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F):
 - a. a description of the parameters/values used in each compliance demonstration and the parameters or values changed for any re-evaluation of the toxic(s) modeled (the composition of materials, new toxic contaminants emitted, change in stack/exhaust parameters, etc.);
 - b. the Maximum Acceptable Ground-Level Concentration (MAGLC) for each significant toxic contaminant or worst-case contaminant, calculated in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F);

Issued: To be entered upon final issuance

- c. a copy of the computer model run(s), that established the predicted 1-hour maximum ground-level concentration that demonstrated the emissions unit(s) to be in compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), initially and for each change that requires re-evaluation of the toxic air contaminant emissions; and
- d. the documentation of the initial evaluation of compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), and documentation of any determination that was conducted to re-evaluate compliance due to a change made to the emissions unit(s) or the materials applied.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

- 6. The permittee shall maintain a record of any change made to a parameter or value used in the dispersion model, used to demonstrate compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration. The record shall include the date and reason(s) for the change and if the change would increase the ground-level concentration.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

Emissions Unit ID: B002

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than natural gas was burned in the emissions unit. These reports shall be submitted to Ohio EPA, Northwest District Office (NWDO) within 30 days after the deviation occurs.
2. This emissions unit is subject to the applicable provisions of Subpart Dc of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60.

The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

Pursuant to 40 CFR Part 60.7, the permittee is hereby advised of the requirement to report the following at the appropriate times:

- a. construction date (no later than 30 days after such date);
- b. actual start-up date (within 15 days after such date); and,
- c. date of performance testing (if required, at least 30 days prior to testing).

Reports are to be sent to:

Ohio Environmental Protection Agency
DAPC - Permit Management Unit
P. O. Box 163669
Columbus, Ohio 43216-3669

and

Ohio Environmental Protection Agency
Northwest District Office
Division of Air Pollution Control
347 North Dunbridge Road
Bowling Green, Ohio 43402

3. The permittee shall submit annual reports to the appropriate Ohio EPA District Office or local air agency, documenting any changes made to a parameter or value used in the dispersion model, that was used to demonstrate compliance with the "Toxic Air

Issued: To be entered upon final issuance

Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration. If no changes to the emissions unit(s) or the exhaust stack have been made, then the report shall include a statement to this effect. This report shall be postmarked or delivered no later than January 31 following the end of each calendar year.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

E. Testing Requirements

1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. The emission testing shall be conducted on at least one of the following emissions units: B001, B002, B003, or B004.
 - b. The emission testing shall be conducted within 60 days after achieving the maximum production rate at which the emissions unit will be operated but not later than 180 days after initial startup of emissions units to be tested. The emissions unit to be tested shall be either B001, B002, B003 or B004, whichever unit achieves its maximum production rate first.
 - c. The emission testing shall be conducted to demonstrate compliance with the 0.020 lb/mmBtu emission limitation for NO_x and the 1.66 lbs/hr CO emission limitation.
 - d. The following test methods shall be employed to demonstrate compliance with the above emissions limitations:
 - i. for NO_x, Methods 1-4 and 7 of 40 CFR Part 60, Appendix A; and
 - ii. for CO, Methods 1-4 and 10 of 40 CFR Part 60, Appendix A.

Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA, NWDO.
 - e. The test(s) shall be conducted while the emissions unit is operating at its maximum capacity, unless otherwise specified or approved by the Ohio EPA, NWDO.

Issued: To be entered upon final issuance

- f. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, NWDO. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, NWDO's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA, NWDO shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report of the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA, NWDO within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, NWDO.

2. Compliance with the emission limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:

- a. Emissions Limitations: 0.020 lb NO_x/mmBtu; 8.09 TPY NO_x

Applicable Compliance Method:

Compliance with the lb NO_x/mmBtu emission limitation shall be demonstrated based on the results of emission testing conducted in accordance with Methods 1 - 4 and 7 of 40 CFR Part 60, Subpart A.

The annual emission limitation was developed by multiplying the lb NO_x/mmBtu limitation by the maximum heat input capacity of 92.4 mmBtu/hr, the maximum operating schedule of 8760 hours/year, and then applying the conversion factor of 2000 lb/ton. Therefore, if compliance is shown with the lb NO_x/mmBtu limitation, compliance with the annual limitation shall be assumed.

- b. Emissions Limitations: 1.66 lbs CO/hr; 7.27 TPY CO

Applicable Compliance Method:

Emissions Unit ID: **B002**

Compliance with the hourly allowable CO emission limitation shall be demonstrated based on the results of emission testing conducted in accordance with Methods 1 - 4 and 10 of 40 CFR Part 60, Subpart A.

The annual emission limitation was developed by multiplying the manufacturer's guaranteed emission factor of 0.018 lb CO/mmBtu limitation by the maximum heat input capacity of 92.4 mmBtu/hr, the maximum operating schedule of 8760 hours/year, and then applying the conversion factor of 2000 lb/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- c. Emissions Limitations: 0.50 lb VOC/hr; 2.19 TPY VOC

Applicable Compliance Method:

The hourly allowable VOC emission limitation was developed by multiplying the USEPA, AP42 emission factor of 5.5 lb/mmscf (Table 1.4-2, revised 7/98) by the maximum heat input capacity of 92.4 mmBtu/hr then dividing by the heating value of natural gas of 1020 mmscf/mmBtu.

If required, compliance with the hourly allowable emission limitation shall be determined in accordance with test Methods 1-4 and 18, 25 or 25A of 40 CFR Part 60, Appendix A.

The annual emission limitation was developed by multiplying the hourly allowable emission limitation by the maximum operating schedule of 8760 hours/year, and then applying the conversion factor of 2000 lb/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- d. Emissions Limitations: 0.69 lb PM10/hr; 3.02 TPY PM10

Applicable Compliance Method:

The hourly allowable PM10 emission limitation was developed by multiplying the USEPA, AP42 emission factor of 7.6 lb/mmscf (Table 1.4-2, revised 7/98) by the maximum heat input capacity of 92.4 mmBtu/hr then dividing by the heating value of natural gas of 1020 mmscf/mmBtu.

If required, compliance with the PM10 limitation shall be determined in

Issued: To be entered upon final issuance

accordance with the test methods and procedures specified in 40 CFR Part 51, Appendix M, Methods 201 and 202. Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA, Northwest District Office (NWDO).

The annual emission limitation was developed by multiplying the hourly allowable emission limitation by the maximum operating schedule of 8760 hours/year, and applying the conversion factor of 2000 lb/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- e. Emissions Limitation: Visible PE from the stack serving this emissions unit shall not exceed 20% opacity, as a six-minute average.

Applicable Compliance Method:

Compliance shall be demonstrated in accordance with OAC rule 3745-17-03(B)(1).

F. Miscellaneous Requirements

- 1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (B003) - 92.4 mmBtu/hr natural gas fired boiler

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(C)	<p>The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart Dc and OAC rule 3745-17-07(A)(1).</p> <p>Nitrogen oxides (NO_x) emissions shall not exceed 0.020 pound per million British thermal units (lbs/mmBtu) of actual heat input and 8.09 tons per year (TPY).</p> <p>Carbon monoxide (CO) emissions shall not exceed 1.66 lbs/hr and 7.27 TPY.</p> <p>Volatile organic compound (VOC) emissions shall not exceed 0.50 lb/hr and 2.19 TPY.</p> <p>Particulate matter equal to or less than 10 microns in size (PM₁₀) shall not exceed 0.69 pound per hour and 3.02 TPY.</p> <p>See sections A.2.a and A.2.e.</p>
OAC rule 3745-17-07(A)(1)	Visible PE shall not exceed 20% opacity, as a six-minute average, except as provided by rule.
OAC rule 3745-17-10(B)(1)	See section A.2.b.
40 CFR Part 60, Subpart Dc	See section B.1.
OAC rule 3745-114-01 ORC 3704.03(F)	See section C.3.
OAC rule 3745-21-08(B)	See section A.2.d.

Issued: To be entered upon final issuance

2. Additional Terms and Conditions

- 2.a** The permittee has requested voluntary allowable emission limitations for NO_x, CO, VOC and PM₁₀. The short-term (lb/hour) and long-term (tons/year) emission limitations for the specified pollutants are being established as practically and legally enforceable requirements representing the potential to emit based on the physical capacity of the emissions unit and the use of natural gas.
- 2.b** The emissions limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(C).
- 2.c** This emissions unit is exempt from the requirements of OAC rule 3745-18-06 in accordance with OAC rule 3745-18-06(A).
- 2.d** The permittee has satisfied the "best available control techniques and operating practices" required pursuant to OAC rule 3745-21-08(B) by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05(A)(3) in this Permit to Install.

On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the requirement to satisfy the "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

- 2.e** For the purposes of this permit, all PE is considered to be PM₁₀.

B. Operational Restrictions

- 1. The permittee shall burn only natural gas in this emissions unit.

C. Monitoring and/or Recordkeeping Requirements

- 1. Pursuant to 40 CFR Part 60, Subpart Dc, the permittee shall record and maintain records of the amount of each fuel combusted during each day. These records shall be maintained by the permittee for a period of two years following the date of such record.

Issued: To be entered upon final issuance

2. For each day during which the permittee burns a fuel other than natural gas, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.

3. The permit to install for these emissions unit(s) J001, B001-B004, P007, P008, P009 and P010 was evaluated based on the actual materials and the design parameters of the emissions unit's(s') exhaust system, as specified by the permittee in the permit application. The "Toxic Air Contaminant Statute", ORC 3704.03(F), was applied to this/these emissions unit(s) for each toxic air contaminant listed in OAC rule 3745-114-01, using data from the permit application; and modeling was performed for each toxic air contaminant(s) emitted at over one ton per year using an air dispersion model such as SCREEN 3.0, AERMOD, or ISCST3, or other Ohio EPA approved model. The predicted 1-hour maximum ground-level concentration result(s) from the approved air dispersion model, was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC), calculated as described in the Ohio EPA guidance document entitled "Review of New Sources of Air Toxic Emissions, Option A", as follows:
 - a. the exposure limit, expressed as a time-weighted average concentration for a conventional 8-hour workday and a 40-hour workweek, for each toxic compound(s) emitted from the emissions unit(s), (as determined from the raw materials processed and/or coatings or other materials applied) has been documented from one of the following sources and in the following order of preference (TLV was and shall be used, if the chemical is listed):
 - i. threshold limit value (TLV) from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices";
or
 - ii. STEL (short term exposure limit) or the ceiling value from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices"; the STEL or ceiling value is multiplied by 0.737 to convert the 15-minute exposure limit to an equivalent 8-hour TLV.

 - b. The TLV is divided by ten to adjust the standard from the working population to the general public (TLV/10).

 - c. This standard is/was then adjusted to account for the duration of the exposure or the operating hours of the emissions unit(s), i.e., "X" hours per day and "Y" days per week, from that of 8 hours per day and 5 days per week. The resulting

Emissions Unit ID: B003

calculation was (and shall be) used to determine the Maximum Acceptable Ground-Level Concentration (MAGLC):

$$TLV/10 \times 8/X \times 5/Y = 4 TLV/XY = MAGLC$$

- d. The following summarizes the results of dispersion modeling for the significant toxic contaminants (emitted at 1 or more tons/year) or "worst case" toxic contaminant(s):

Pollutant: Acetaldehyde

TLV (mg/m³): 45.0

Maximum Hourly Emission Rate (lbs/hr): 2.11

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 28.38

MAGLC (ug/m³): 1071.43

Pollutant: Hexane

TLV (mg/m³): 176.24

Maximum Hourly Emission Rate (lbs/hr): 1.09

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 0.81

MAGLC (ug/m³): 4,196

Pollutant: Methanol

TLV (mg/m³): 262

Maximum Hourly Emission Rate (lbs/hr): 0.34

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 0.69

MAGLC (ug/m³): 6238

The permittee, has demonstrated that emissions of acetaldehyde, hexane and methanol, from emissions unit(s) J001, B001, B002, B003, B004, P007, P008, P009 and P010, are calculated to be less than eighty per cent of the maximum acceptable ground level concentration (MAGLC); any new raw material or processing agent shall not be applied without evaluating each component toxic air contaminant in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F).

4. Prior to making any physical changes to or changes in the method of operation of the emissions unit(s), that could impact the parameters or values that were used in the predicted 1-hour maximum ground-level concentration", the permittee shall re-model the change(s) to demonstrate that the MAGLC has not been exceeded. Changes that can affect the parameters/values used in determining the 1-hour maximum ground-level concentration include, but are not limited to, the following:

Issued: To be entered upon final issuance

- a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a new toxic air contaminant with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any toxic air contaminant listed in OAC rule 3745-114-01, that was modeled from the initial (or last) application; and
- c. physical changes to the emissions unit(s) or its/their exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Toxic Air Contaminant Statute" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to a non-restrictive change to a parameter or process operation, where compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), has been documented. If the change(s) meet(s) the definition of a "modification" or if a new toxic is emitted, or the modeled toxic(s) is/are expected to exceed the previous modeled level(s), then the permittee shall apply for and obtain a final permit-to-install prior to the change. The Director may consider any significant departure from the operations of the emissions unit, described in the permit-to-install application, as a modification that results in greater emissions than the emissions rate modeled to determine the ground level concentration; and may require the permittee to submit a permit-to-install application for the increased emissions.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

5. The permittee shall collect, record, and retain the following information for each toxic evaluation conducted to determine compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F):
 - a. a description of the parameters/values used in each compliance demonstration and the parameters or values changed for any re-evaluation of the toxic(s) modeled (the composition of materials, new toxic contaminants emitted, change in stack/exhaust parameters, etc.);
 - b. the Maximum Acceptable Ground-Level Concentration (MAGLC) for each significant toxic contaminant or worst-case contaminant, calculated in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F);

Emissions Unit ID: **B003**

- c. a copy of the computer model run(s), that established the predicted 1-hour maximum ground-level concentration that demonstrated the emissions unit(s) to be in compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), initially and for each change that requires re-evaluation of the toxic air contaminant emissions; and
- d. the documentation of the initial evaluation of compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), and documentation of any determination that was conducted to re-evaluate compliance due to a change made to the emissions unit(s) or the materials applied.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

- 6. The permittee shall maintain a record of any change made to a parameter or value used in the dispersion model, used to demonstrate compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration. The record shall include the date and reason(s) for the change and if the change would increase the ground-level concentration.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

Issued: To be entered upon final issuance

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than natural gas was burned in the emissions unit. These reports shall be submitted to Ohio EPA, Northwest District Office (NWDO) within 30 days after the deviation occurs.
2. This emissions unit is subject to the applicable provisions of Subpart Dc of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60.

The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

Pursuant to 40 CFR Part 60.7, the permittee is hereby advised of the requirement to report the following at the appropriate times:

- a. construction date (no later than 30 days after such date);
- b. actual start-up date (within 15 days after such date); and,
- c. date of performance testing (if required, at least 30 days prior to testing).

Reports are to be sent to:

Ohio Environmental Protection Agency
DAPC - Permit Management Unit
P. O. Box 163669
Columbus, Ohio 43216-3669

and

Ohio Environmental Protection Agency
Northwest District Office
Division of Air Pollution Control
347 North Dunbridge Road
Bowling Green, Ohio 43402

3. The permittee shall submit annual reports to the appropriate Ohio EPA District Office or local air agency, documenting any changes made to a parameter or value used in the dispersion model, that was used to demonstrate compliance with the "Toxic Air

Issued: To be entered upon final issuance

Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration. If no changes to the emissions unit(s) or the exhaust stack have been made, then the report shall include a statement to this effect. This report shall be postmarked or delivered no later than January 31 following the end of each calendar year.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

E. Testing Requirements

1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. The emission testing shall be conducted on at least one of the following emissions units: B001, B002, B003, or B004.
 - b. The emission testing shall be conducted within 60 days after achieving the maximum production rate at which the emissions unit will be operated but not later than 180 days after initial startup of the emissions units to be tested. The emissions unit to be tested shall be either B001, B002, B003 or B004, whichever unit achieves its maximum production rate first.
 - c. The emission testing shall be conducted to demonstrate compliance with the 0.020 lb/mmBtu emission limitation for NO_x and the 1.66 lbs/hr CO emission limitation.
 - d. The following test methods shall be employed to demonstrate compliance with the above emissions limitations:
 - i. for NO_x, Methods 1-4 and 7 of 40 CFR Part 60, Appendix A; and
 - ii. for CO, Methods 1-4 and 10 of 40 CFR Part 60, Appendix A.

Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA, NWDO.
 - e. The test(s) shall be conducted while the emissions unit is operating at its maximum capacity, unless otherwise specified or approved by the Ohio EPA, NWDO.

Emissions Unit ID: **B003**

- f. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, NWDO. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, NWDO's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA, NWDO shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report of the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA, NWDO within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, NWDO.

2. Compliance with the emission limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:

- a. Emissions Limitations: 0.020 lb NOx/mmBtu; 8.09 TPY NOx

Applicable Compliance Method:

Compliance with the lb NOx/mmBtu emission limitation shall be demonstrated based on the results of emission testing conducted in accordance with Methods 1 - 4 and 7 of 40 CFR Part 60, Subpart A.

The annual emission limitation was developed by multiplying the lb NOx/mmBtu limitation by the maximum heat input capacity of 92.4 mmBtu/hr, the maximum operating schedule of 8760 hours/year, and then applying the conversion factor of 2000 lb/ton. Therefore, if compliance is shown with the lb NOx/mmBtu limitation, compliance with the annual limitation shall be assumed.

- b. Emissions Limitations: 1.66 lbs CO/hr; 7.27 TPY CO

Applicable Compliance Method:

Issued: To be entered upon final issuance

Compliance with the hourly allowable CO emission limitation shall be demonstrated based on the results of emission testing conducted in accordance with Methods 1 - 4 and 10 of 40 CFR Part 60, Subpart A.

The annual emission limitation was developed by multiplying the manufacturer's guaranteed emission factor of 0.018 lb CO/mmBtu limitation by the maximum heat input capacity of 92.4 mmBtu/hr, the maximum operating schedule of 8760 hours/year, and then applying the conversion factor of 2000 lb/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- c. Emissions Limitations: 0.50 lb VOC/hr; 2.19 TPY VOC

Applicable Compliance Method:

The hourly allowable VOC emission limitation was developed by multiplying the USEPA, AP42 emission factor of 5.5 lb/mmscf (Table 1.4-2, revised 7/98) by the maximum heat input capacity of 92.4 mmBtu/hr then dividing by the heating value of natural gas of 1020 mmscf/mmBtu.

If required, compliance with the hourly allowable emission limitation shall be determined in accordance with test Methods 1-4 and 18, 25 or 25A of 40 CFR Part 60, Appendix A.

The annual emission limitation was developed by multiplying the hourly allowable emission limitation by the maximum operating schedule of 8760 hours/year, and then applying the conversion factor of 2000 lb/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- d. Emissions Limitations: 0.69 lb PM10/hr; 3.02 TPY PM10

Applicable Compliance Method:

The hourly allowable PM10 emission limitation was developed by multiplying the USEPA, AP42 emission factor of 7.6 lb/mmscf (Table 1.4-2, revised 7/98) by the maximum heat input capacity of 92.4 mmBtu/hr then dividing by the heating value of natural gas of 1020 mmscf/mmBtu.

If required, compliance with the PM10 limitation shall be determined in

Emissions Unit ID: **B003**

accordance with the test methods and procedures specified in 40 CFR Part 51, Appendix M, Methods 201 and 202. Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA, Northwest District Office (NWDO).

The annual emission limitation was developed by multiplying the hourly allowable emission limitation by the maximum operating schedule of 8760 hours/year, and applying the conversion factor of 2000 lb/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- e. Emissions Limitation: Visible PE from the stack serving this emissions unit shall not exceed 20% opacity, as a six-minute average.

Applicable Compliance Method:

Compliance shall be demonstrated in accordance with OAC rule 3745-17-03(B)(1).

F. Miscellaneous Requirements

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (B004) - 92.4 mmBtu/hr natural gas fired boiler

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(C)	<p>The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart Dc and OAC rule 3745-17-07(A)(1).</p> <p>Nitrogen oxides (NO_x) emissions shall not exceed 0.020 pound per million British thermal units (lbs/mmBtu) of actual heat input and 8.09 tons per year (TPY).</p> <p>Carbon monoxide (CO) emissions shall not exceed 1.66 lbs/hr and 7.27 TPY.</p> <p>Volatile organic compound (VOC) emissions shall not exceed 0.50 lb/hr and 2.19 TPY.</p> <p>Particulate matter equal to or less than 10 microns in size (PM₁₀) shall not exceed 0.69 pound per hour and 3.02 TPY.</p> <p>See sections A.2.a and A.2.e.</p>
OAC rule 3745-17-07(A)(1)	Visible PE shall not exceed 20% opacity, as a six-minute average, except as provided by rule.
OAC rule 3745-17-10(B)(1)	See section A.2.b.
40 CFR Part 60, Subpart Dc	See section B.1.
OAC rule 3745-21-08(B)	See section A.2.d.
OAC rule 3745-114-01 ORC 3704.03(F)	See section C.3.

Issued: To be entered upon final issuance

2. Additional Terms and Conditions

- 2.a** The permittee has requested voluntary allowable emission limitations for NO_x, CO, VOC and PM₁₀. The short-term (lb/hour) and long-term (tons/year) emission limitations for the specified pollutants are being established as practically and legally enforceable requirements representing the potential to emit based on the physical capacity of the emissions unit and the use of natural gas.
- 2.b** The emissions limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(C).
- 2.c** This emissions unit is exempt from the requirements of OAC rule 3745-18-06 in accordance with OAC rule 3745-18-06(A).
- 2.d** The permittee has satisfied the "best available control techniques and operating practices" required pursuant to OAC rule 3745-21-08(B) by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05(A)(3) in this Permit to Install.

On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the requirement to satisfy the "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

- 2.e** For the purposes of this permit, all PE is considered to be PM₁₀.

B. Operational Restrictions

- 1. The permittee shall burn only natural gas in this emissions unit.

C. Monitoring and/or Recordkeeping Requirements

- 1. Pursuant to 40 CFR Part 60, Subpart Dc, the permittee shall record and maintain records of the amounts of each fuel combusted during each day. These records shall be maintained by the permittee for a period of two years following the date of such record.

Emissions Unit ID: **B004**

2. For each day during which the permittee burns a fuel other than natural gas, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.
3. The permit to install for these emissions unit(s) J001, B001-B004, P007, P008, P009 and P010 was evaluated based on the actual materials and the design parameters of the emissions unit's(s') exhaust system, as specified by the permittee in the permit application. The "Toxic Air Contaminant Statute", ORC 3704.03(F), was applied to this/these emissions unit(s) for each toxic air contaminant listed in OAC rule 3745-114-01, using data from the permit application; and modeling was performed for each toxic air contaminant(s) emitted at over one ton per year using an air dispersion model such as SCREEN 3.0, AERMOD, or ISCST3, or other Ohio EPA approved model. The predicted 1-hour maximum ground-level concentration result(s) from the approved air dispersion model, was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC), calculated as described in the Ohio EPA guidance document entitled "Review of New Sources of Air Toxic Emissions, Option A", as follows:
 - a. the exposure limit, expressed as a time-weighted average concentration for a conventional 8-hour workday and a 40-hour workweek, for each toxic compound(s) emitted from the emissions unit(s), (as determined from the raw materials processed and/or coatings or other materials applied) has been documented from one of the following sources and in the following order of preference (TLV was and shall be used, if the chemical is listed):
 - i. threshold limit value (TLV) from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices";
or
 - ii. STEL (short term exposure limit) or the ceiling value from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices"; the STEL or ceiling value is multiplied by 0.737 to convert the 15-minute exposure limit to an equivalent 8-hour TLV.
 - b. The TLV is divided by ten to adjust the standard from the working population to the general public (TLV/10).
 - c. This standard is/was then adjusted to account for the duration of the exposure or the operating hours of the emissions unit(s), i.e., "X" hours per day and "Y" days

Issued: To be entered upon final issuance

per week, from that of 8 hours per day and 5 days per week. The resulting calculation was (and shall be) used to determine the Maximum Acceptable Ground-Level Concentration (MAGLC):

$$TLV/10 \times 8/X \times 5/Y = 4 TLV/XY = MAGLC$$

- d. The following summarizes the results of dispersion modeling for the significant toxic contaminants (emitted at 1 or more tons/year) or "worst case" toxic contaminant(s):

Pollutant: AcetaldehydeTLV (mg/m³): 45.0

Maximum Hourly Emission Rate (lbs/hr): 2.11

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 28.38MAGLC (ug/m³): 1071.43**Pollutant:** HexaneTLV (mg/m³): 176.24

Maximum Hourly Emission Rate (lbs/hr): 1.09

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 0.81MAGLC (ug/m³): 4,196**Pollutant:** MethanolTLV (mg/m³): 262

Maximum Hourly Emission Rate (lbs/hr): 0.34

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 0.69MAGLC (ug/m³): 6238

The permittee, has demonstrated that emissions of acetaldehyde, hexane and methanol, from emissions unit(s) J001, B001, B002, B003, B004, P007, P008, P009 and P010, are calculated to be less than eighty per cent of the maximum acceptable ground level concentration (MAGLC); any new raw material or processing agent shall not be applied without evaluating each component toxic air contaminant in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F).

4. Prior to making any physical changes to or changes in the method of operation of the emissions unit(s), that could impact the parameters or values that were used in the predicted 1-hour maximum ground-level concentration", the permittee shall re-model the change(s) to demonstrate that the MAGLC has not been exceeded. Changes that can affect the parameters/values used in determining the 1-hour maximum ground-level

Emissions Unit ID: B004

concentration include, but are not limited to, the following:

- a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a new toxic air contaminant with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any toxic air contaminant listed in OAC rule 3745-114-01, that was modeled from the initial (or last) application; and
- c. physical changes to the emissions unit(s) or its/their exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Toxic Air Contaminant Statute" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to a non-restrictive change to a parameter or process operation, where compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), has been documented. If the change(s) meet(s) the definition of a "modification" or if a new toxic is emitted, or the modeled toxic(s) is/are expected to exceed the previous modeled level(s), then the permittee shall apply for and obtain a final permit-to-install prior to the change. The Director may consider any significant departure from the operations of the emissions unit, described in the permit-to-install application, as a modification that results in greater emissions than the emissions rate modeled to determine the ground level concentration; and may require the permittee to submit a permit-to-install application for the increased emissions.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

5. The permittee shall collect, record, and retain the following information for each toxic evaluation conducted to determine compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F):
 - a. a description of the parameters/values used in each compliance demonstration and the parameters or values changed for any re-evaluation of the toxic(s) modeled (the composition of materials, new toxic contaminants emitted, change in stack/exhaust parameters, etc.);
 - b. the Maximum Acceptable Ground-Level Concentration (MAGLC) for each significant toxic contaminant or worst-case contaminant, calculated in

Issued: To be entered upon final issuance

accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F);

- c. a copy of the computer model run(s), that established the predicted 1-hour maximum ground-level concentration that demonstrated the emissions unit(s) to be in compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), initially and for each change that requires re-evaluation of the toxic air contaminant emissions; and
- d. the documentation of the initial evaluation of compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), and documentation of any determination that was conducted to re-evaluate compliance due to a change made to the emissions unit(s) or the materials applied.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

- 6. The permittee shall maintain a record of any change made to a parameter or value used in the dispersion model, used to demonstrate compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration. The record shall include the date and reason(s) for the change and if the change would increase the ground-level concentration.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than natural gas was burned in the emissions unit. These reports shall be submitted to Ohio EPA, Northwest District Office (NWDO) within 30 days after the deviation occurs.
2. This emissions unit is subject to the applicable provisions of Subpart Dc of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60.

The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

Pursuant to 40 CFR Part 60.7, the permittee is hereby advised of the requirement to report the following at the appropriate times:

- a. construction date (no later than 30 days after such date);
- b. actual start-up date (within 15 days after such date); and,
- c. date of performance testing (if required, at least 30 days prior to testing).

Reports are to be sent to:

Ohio Environmental Protection Agency
DAPC - Permit Management Unit
P. O. Box 163669
Columbus, Ohio 43216-3669

and

Ohio Environmental Protection Agency
Northwest District Office
Division of Air Pollution Control
347 North Dunbridge Road
Bowling Green, Ohio 43402

3. The permittee shall submit annual reports to the appropriate Ohio EPA District Office or local air agency, documenting any changes made to a parameter or value used in the dispersion model, that was used to demonstrate compliance with the "Toxic Air

Issued: To be entered upon final issuance

Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration. If no changes to the emissions unit(s) or the exhaust stack have been made, then the report shall include a statement to this effect. This report shall be postmarked or delivered no later than January 31 following the end of each calendar year.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

E. Testing Requirements

1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. The emission testing shall be conducted on at least one of the following emissions units: B001, B002, B003, or B004.
 - b. The emission testing shall be conducted within 60 days after achieving the maximum production rate at which the emissions unit will be operated but not later than 180 days after initial startup of the emissions unit to be tested. The emissions unit to be tested shall be either B001, B002, B003 or B004, whichever unit achieves its maximum production rate first.
 - c. The emission testing shall be conducted to demonstrate compliance with the 0.020 lb/mmBtu emission limitation for NO_x and the 1.66 lbs/hr CO emission limitation.
 - d. The following test methods shall be employed to demonstrate compliance with the above emissions limitations:
 - i. for NO_x, Methods 1-4 and 7 of 40 CFR Part 60, Appendix A; and
 - ii. for CO, Methods 1-4 and 10 of 40 CFR Part 60, Appendix A.

Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA, NWDO.
 - e. The test(s) shall be conducted while the emissions unit is operating at its maximum capacity, unless otherwise specified or approved by the Ohio EPA, NWDO.

Emissions Unit ID: **B004**

- f. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, NWDO. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, NWDO's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA, NWDO shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report of the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA, NWDO within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, NWDO.

2. Compliance with the emission limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:

The emission testing shall be conducted within 60 days after achieving the maximum production rate at which emissions unit B001, B002, B003 or B004, whichever startup occurs first, will be operated, but not later than 180 days after initial startup of emissions units B001, B002, B003 or B004, whichever startup occurs first.

F. Miscellaneous Requirements

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (F001) - Paved Roadways and Parking Areas

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(A)(3)	<p>There shall be no visible particulate emissions (PE), except for one minute during any 60-minute period.</p> <p>Fugitive PE shall not exceed 32.98 tons per year (TPY).</p> <p>The permittee shall implement best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see Sections A.2.b through A.2.f).</p> <p>See Section A.2.i.</p>
OAC rule 3745-17-07(B)	See Section A.2.g.
OAC rule 3745-17-08(B)	See Section A.2.h.

2. Additional Terms and Conditions

- 2.a The paved roadways and parking areas that are covered by this permit and subject to the above-mentioned requirements are listed below:

Paved Roadways:

all paved road segments

Paved Parking Areas:

all paved parking areas

- 2.b The permittee shall employ best available control measures on all paved roadways and parking areas for the purpose of ensuring compliance with the

Issued: To be entered upon final issuance

above-mentioned applicable requirements. In accordance with the permit application, the permittee has committed to treat the paved roadways and parking areas by sweeping and/or watering at sufficient treatment frequencies to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other equally-effective control measures to ensure compliance.

- 2.c** The needed frequencies of implementation of the control measures shall be determined by the permittee's inspections pursuant to the monitoring section of this permit. Implementation of the control measures shall not be necessary for a paved roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Implementation of any control measure may be suspended if unsafe or hazardous driving conditions would be created by its use.
- 2.d** The permittee shall promptly remove, in such a manner as to minimize or prevent resuspension, earth and/or other material from paved streets onto which such material has been deposited by trucking or earth moving equipment or erosion by water or other means.
- 2.e** Open-bodied vehicles transporting materials likely to become airborne shall have such materials covered at all times if the control measure is necessary for the materials being transported.
- 2.f** Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the best available technology requirements of OAC rule 3745-31-05.
- 2.g** This emissions unit is exempt from the visible particulate emission limitations specified in OAC rule 3745-17-07(B) pursuant to OAC rule 3745-17-07(B)(11)(e).
- 2.h** This emissions unit is not located within an "Appendix A" area as identified in OAC rule 3745-17-08. Therefore, pursuant to OAC rule 3745-17-08(A), this emissions unit is exempt from the requirements of OAC rule 3745-17-08(B).
- 2.i** This emissions unit potential to emit for PM10 is less than 10 tons per year*. Therefore, pursuant to ORC 3704.03(T)(4), OAC rule 3745-31-05(A)(3) is not applicable.

Port Clinton Biofuels, Inc.
DTI Application: 03-17224

Facility ID: 0362010154

Emissions Unit ID: **F001**

* The potential to emit for this emissions unit is 6.34 TPY of PM10 based upon the calculations in USEPA, AP-42, Section 13.2.1.3 (revised 11/06).

B. Operational Restrictions

None.

Issued: To be entered upon final issuance**C. Monitoring and/or Recordkeeping Requirements**

1. Except as otherwise provided in this section, the permittee shall perform inspections of the paved roadways and parking areas in accordance with the following frequencies:

<u>Paved Roadways</u>	<u>Minimum Inspection Frequency</u>
-----------------------	-------------------------------------

All	Once Per Day
-----	--------------

<u>Paved Parking Areas</u>	<u>Minimum Inspection Frequency</u>
----------------------------	-------------------------------------

All	Once Per Day
-----	--------------

2. The purpose of the inspections is to determine the need for implementing the above-mentioned control measures. The inspections shall be performed during representative, normal traffic conditions. No inspection shall be necessary for a roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above-identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.
3. The permittee shall maintain records of the following information:
 - a. the date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;
 - b. the date and time of each inspection where it was determined by the permittee that it was necessary to implement the control measures;
 - c. the dates the control measures were implemented; and
 - d. on a calendar quarter basis, the total number of days the control measures were implemented and the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measures.

The information required in Section C.3.d shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

4. The permittee shall record the number of trucks hauling grain, ethanol, denaturant,

Issued: To be entered upon final issuance

and/or DDGS at the plant site and their respective weights on a daily basis.

D. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:
 - a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and
 - b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.
2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.
3. The permittee shall submit annual reports which specify the total for PE emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

E. Testing Requirements

1. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation: There shall be no visible PE, except for one minute during any 60-minute period.

Applicable Compliance Method:

Visible PE shall be determined in accordance with test Method 22 of 40 CFR Part 60, Subpart A.

- b. Emission Limitation: Fugitive PE shall not exceed 32.98 tons/year.

Applicable Compliance Method:

The annual emission limitation was developed using the calculations in USEPA, AP-42 Section 13.2.1.3 (revised 11/06) and inputs representing the potential to emit, as follows:

Emissions Unit ID: F001

$$E = k[(sL/2)^{0.65} (W/3)^{1.5} - C] (1 - P/4N)$$

Where

E = emission factor (lb/VMT)

k = particle size multiplier = 0.082

sL = silt content of road surface material, in g/m² = 0.4 (80% control applied)

W = mean vehicle weight, in tons = 29.0

C = emission factor for exhaust, brake wear and tire wear = 0.0005

P = number of wet days per averaging period with at least 0.01 inch of precipitation = 140

N = number of days per averaging period = 365

Using the equation and input values above:

$$E = 0.78 \text{ lb PE/vehicle mile traveled (VMT)}$$

Using the AP-42 emission factor and the maximum annual VMT*:

$$\begin{aligned} \text{PE} &= (0.78 \text{ lb/VMT})(84,552 \text{ VMT/yr})(\text{ton}/2000 \text{ lb}) \\ &= 32.98 \text{ tons/year} \end{aligned}$$

VMT = the number of trucks entering the plant site x 1.54 miles/truck
 (miles traveled per truck as specified in the permit application)

Compliance shall be demonstrated by the reporting requirement in Section D.3 above.

F. Miscellaneous Requirements

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (J001) - Ethanol loading operations

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(A)(3)	<p>Nitrogen oxides (NOx) emissions from emissions units J001, P007, P009 and P010, combined, shall not exceed 12.96 pounds per hour (lbs/hr) and 56.76 tons per year (TPY).</p> <p>Carbon monoxide (CO) emissions from J001, P007, P009 and P010 shall not exceed 15.40 lbs/hr and 67.46 TPY.</p> <p>Particulate emissions equal to or less than 10 microns in size (PM10), from emissions units J001, P007, P009 and P010, combined, shall not exceed 6.80 lbs/hr and 29.78 TPY.</p> <p>Volatile organic compound (VOC) emissions from emissions units J001, P007, P009 and P010, combined, shall not exceed 10.0 lbs/hr and 43.80 TPY.</p> <p>Fugitive VOC emissions from this emissions unit shall not exceed 4.49 TPY.</p> <p>Sulfur dioxide (SO2) emissions from emissions unit J001, P007, P009 and P010, combined shall not exceed 15 lbs/hr and 65.70 TPY.</p> <p>Visible particulate emissions (PE) from the stack(s) serving this emissions (Stacks S16 and/or S17) unit shall not exceed 5% opacity as a six-minute average.</p> <p>See Section A.2.a.</p>
OAC rule 3745-21-07(E)	See Sections A.2.b through A.2.f.
OAC rule 3745-21-08(B)	See Section A.2.g.

OAC rule 3745-114-01 ORC 3704.03(F)	See section C.4.
----------------------------------------	------------------

2. Additional Terms and Conditions

- 2.a** Best available technology (BAT) requirements for this emissions unit have been determined to be the use of the following:
- i. two (2) regenerative thermal oxidizers (RTO). The RTO shall meet a minimum control efficiency of 95% for both VOC and CO emissions; and
 - iii. firing only natural gas and the use of low NOx burners in the RTO.
- 2.c** During any transfer of material through the loading rack, the vapors displaced from the delivery vessel shall be collected and vented to either RTO#1 or RTO#2.
- 2.d** A means shall be provided to prevent liquid drainage from the loading device when it is not in use or to accomplish complete drainage before the loading device is disconnected.
- 2.e** The loading rack shall utilize top submerged filling or bottom filling for the transfer of materials.
- 2.f** All material loading lines, unloading lines and vapor lines shall be equipped with fittings which are vapor tight.
- 2.g** The permittee has satisfied the "best available control techniques and operating practices" required pursuant to OAC rule 3745-21-08(B) by complying with the requirements established pursuant to OAC rule 3745-21-07(E) in this Permit to Install.

On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and U.S. EPA approves the revision to OAC rule 3745-21-08, the requirements to satisfy "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

B. Operational Restrictions

Issued: To be entered upon final issuance

1. The maximum annual throughput rate of denatured ethanol for this emissions unit shall not exceed 115.5 million gallons.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain monthly records of the amount of denatured ethanol loaded in this emissions unit, in gallons per month and total gallons, to date for the calendar year.
2. The permittee shall record each time loading occurs and document when submerged or bottom loading is used.
3. The permittee shall properly install, operate, and maintain equipment to continuously monitor and record the combustion temperature within the thermal oxidizer(s) during operation of this emissions unit. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the combustion temperature within the thermal oxidizer(s) on a continuous basis.

Whenever the monitored value for the combustion temperature deviates from the value specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation: the date and time the deviation began and the magnitude of the deviation at that time, the date(s) the investigation was conducted, the names of the personnel who conducted the investigation, and the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable value specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken: a description of the corrective action, the date it was completed, the date and time the deviation ended, the total period of time (in minutes) during which there was a deviation, the combustion temperature within the thermal oxidizer(s) immediately after the corrective action, and the names of the personnel who performed the work. Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

The average combustion temperature within the thermal oxidizer(s), for any 3-hour

Emissions Unit ID: **J001**

block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.

This value is effective for the duration of this permit, unless revisions are requested by the permittee and approved in writing by the appropriate Ohio EPA District Office or local air agency.

4. The permit to install for these emissions unit(s) J001, B001-B004 and P007-P010, was evaluated based on the actual materials and the design parameters of the emissions unit's(s') exhaust system, as specified by the permittee in the permit application. The "Toxic Air Contaminant Statute", ORC 3704.03(F), was applied to this/these emissions unit(s) for each toxic air contaminant listed in OAC rule 3745-114-01, using data from the permit application; and modeling was performed for each toxic air contaminant(s) emitted at over one ton per year using an air dispersion model such as SCREEN 3.0, AERMOD, or ISCST3, or other Ohio EPA approved model. The predicted 1-hour maximum ground-level concentration result(s) from the approved air dispersion model, was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC), calculated as described in the Ohio EPA guidance document entitled "Review of New Sources of Air Toxic Emissions, Option A", as follows:
 - a. the exposure limit, expressed as a time-weighted average concentration for a conventional 8-hour workday and a 40-hour workweek, for each toxic compound(s) emitted from the emissions unit(s), (as determined from the raw materials processed and/or coatings or other materials applied) has been documented from one of the following sources and in the following order of preference (TLV was and shall be used, if the chemical is listed):
 - i. threshold limit value (TLV) from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices";
or
 - ii. STEL (short term exposure limit) or the ceiling value from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices"; the STEL or ceiling value is multiplied by 0.737 to convert the 15-minute exposure limit to an equivalent 8-hour TLV.
 - b. The TLV is divided by ten to adjust the standard from the working population to the general public (TLV/10).

Issued: To be entered upon final issuance

- c. This standard is/was then adjusted to account for the duration of the exposure or the operating hours of the emissions unit(s), i.e., "X" hours per day and "Y" days per week, from that of 8 hours per day and 5 days per week. The resulting calculation was (and shall be) used to determine the Maximum Acceptable Ground-Level Concentration (MAGLC):

$$TLV/10 \times 8/X \times 5/Y = 4 TLV/XY = MAGLC$$

- d. The following summarizes the results of dispersion modeling for the significant toxic contaminants (emitted at 1 or more tons/year) or "worst case" toxic contaminant(s):

Pollutant: AcetaldehydeTLV (mg/m³): 45.0

Maximum Hourly Emission Rate (lbs/hr): 2.11

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 28.38MAGLC (ug/m³): 1071.43**Pollutant:** HexaneTLV (mg/m³): 176.24

Maximum Hourly Emission Rate (lbs/hr): 1.09

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 0.81MAGLC (ug/m³): 4,196**Pollutant:** MethanolTLV (mg/m³): 262

Maximum Hourly Emission Rate (lbs/hr): 0.34

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 0.69MAGLC (ug/m³): 6238

The permittee, has demonstrated that emissions of acetaldehyde, hexane, methanol, from emissions unit(s) J001, B001-B004 and P007-P010, are calculated to be less than eighty per cent of the maximum acceptable ground level concentration (MAGLC); any new raw material or processing agent shall not be applied without evaluating each component toxic air contaminant in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F).

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

Emissions Unit ID: J001

5. Prior to making any physical changes to or changes in the method of operation of the emissions unit(s), that could impact the parameters or values that were used in the predicted 1-hour maximum ground-level concentration", the permittee shall re-model the change(s) to demonstrate that the MAGLC has not been exceeded. Changes that can affect the parameters/values used in determining the 1-hour maximum ground-level concentration include, but are not limited to, the following:
 - a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a new toxic air contaminant with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled;
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any toxic air contaminant listed in OAC rule 3745-114-01, that was modeled from the initial (or last) application; and
 - c. physical changes to the emissions unit(s) or its/their exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Toxic Air Contaminant Statute" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to a non-restrictive change to a parameter or process operation, where compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), has been documented. If the change(s) meet(s) the definition of a "modification" or if a new toxic is emitted, or the modeled toxic(s) is/are expected to exceed the previous modeled level(s), then the permittee shall apply for and obtain a final permit-to-install prior to the change. The Director may consider any significant departure from the operations of the emissions unit, described in the permit-to-install application, as a modification that results in greater emissions than the emissions rate modeled to determine the ground level concentration; and may require the permittee to submit a permit-to-install application for the increased emissions.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

6. The permittee shall collect, record, and retain the following information for each toxic evaluation conducted to determine compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F):
 - a. a description of the parameters/values used in each compliance demonstration and the parameters or values changed for any re-evaluation of the toxic(s)

Issued: To be entered upon final issuance

modeled (the composition of materials, new toxic contaminants emitted, change in stack/exhaust parameters, etc.);

- b. the Maximum Acceptable Ground-Level Concentration (MAGLC) for each significant toxic contaminant or worst-case contaminant, calculated in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F);
- c. a copy of the computer model run(s), that established the predicted 1-hour maximum ground-level concentration that demonstrated the emissions unit(s) to be in compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), initially and for each change that requires re-evaluation of the toxic air contaminant emissions; and
- d. the documentation of the initial evaluation of compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), and documentation of any determination that was conducted to re-evaluate compliance due to a change made to the emissions unit(s) or the materials applied.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

- 7. The permittee shall maintain a record of any change made to a parameter or value used in the dispersion model, used to demonstrate compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration. The record shall include the date and reason(s) for the change and if the change would increase the ground-level concentration.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

D. Reporting Requirements

1. The permittee shall submit annual reports that summarize the total annual denatured ethanol throughput, in gallons, for this emissions unit. These reports shall be submitted by January 31 of each year and shall cover the previous year.
2. The permittee shall submit quarterly reports that identify the following information concerning the operation of the control equipment (thermal oxidizer(s)) during the operation of this emissions unit:
 - a. all 3-hour blocks of time during which the average combustion temperature within the thermal oxidizer(s), when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent performance test that demonstrated the emissions unit was in compliance.
 - b. an identification of each incident of deviation described in (a) where a prompt investigation was not conducted;
 - c. an identification of each incident of deviation described in (a) where prompt corrective action, that would bring the combustion temperature into compliance with the acceptable range, was determined to be necessary and was not taken; and
 - d. an identification of each incident of deviation described in (a) where proper records were not maintained for the investigation and/or the corrective action.

These quarterly reports shall be submitted (i.e., postmarked) by January 31, April 30, July 31, and October 31 of each year; and each report shall cover the previous calendar quarter.

3. The permittee shall submit annual reports to the appropriate Ohio EPA District Office or local air agency, documenting any changes made to a parameter or value used in the dispersion model, that was used to demonstrate compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration. If no changes to the emissions unit(s) or the exhaust stack have been made, then the report shall include a statement to this effect. This report shall be postmarked or delivered no later than January 31 following the end of each calendar year.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering

Issued: To be entered upon final issuance
Guide #70

E. Testing Requirements

1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. The emission testing shall be conducted within 60 days after achieving the maximum production rate at which emissions units J001, P007, P009 and P010 will be operated, but not later than 180 days after initial startup of such emissions unit.
 - b. The emission testing shall be conducted to demonstrate compliance with the NO_x, CO, VOC, PM₁₀ and SO₂ mass emission limitations for this emissions unit. Emission testing shall also be conducted to verify the expected emissions for single and combined HAPs.
 - c. The following test methods shall be employed to demonstrate compliance with the above emission limitations:
 - i. for PM₁₀, Methods 201 and 202 of 40 CFR Part 51, Appendix M;
 - ii. for NO_x, Methods 1-4 and 7 of 40 CFR Part 60, Appendix A;
 - iii. for CO, Methods 1-4 and 10 of 40 CFR Part 60, Appendix A;
 - iv. for SO₂, Methods 1-4 and 6 of 40 CFR Part 60, Appendix A;
 - iv. for VOC, Methods 1-4 and 18, 25 or 25A of 40 CFR Part 60, Appendix A. Appropriate methods shall be used in conjunction with the test methods and procedures specified in Methods 18, 25, or 25A of 40 CFR Part 60, Appendix A for determining VOC mass emissions; and
 - v. for HAPs, Methods 18 or 320 from 40 CFR Part 60, Appendix A.

Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA, NWDO. The test method(s) which must be employed to demonstrate compliance with the control efficiencies are specified below.

- d. The control efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in Methods 18, 25, or 25A of 40 CFR Part 60, Appendix A for VOC emissions . The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases."

Emissions Unit ID: J001

- e. the test(s) shall be conducted while emissions units J001, P007, P009 and P010 are operating at their maximum capacities (as stated in the PTI application for this permit), unless otherwise specified or approved by the Ohio EPA, NWDO.
- f. During emission testing, the permittee shall also record the following information:
 - i. the average combustion temperature within the thermal oxidizer(s), in degrees Fahrenheit.
- g. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, NWDO. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, NWDO's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA, NWDO shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report of the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA, NWDO within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, NWDO.

- 2. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emission Limitations: 10.0 lbs VOC/hr, 43.80 tpy VOC (combined, for emissions unit J001, P007, P009 and P010)

Applicable Compliance Method:

Compliance with the hourly allowable emission limitation above shall be demonstrated based on the results of emission testing conducted in accordance

Emissions Unit ID: J001

with Methods 1-4 and 18, 25 or 25A of 40 CFR Part 60, Appendix A.

The annual emission limitation was developed by multiplying the hourly emission limitation by the maximum operating schedule of 8760 hours/year, and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- b. Emission Limitations: 12.96 lbs NO_x/hr, 56.76 tpy NO_x (combined, for emissions units J001, P007, P009, and P010)

Applicable Compliance Method:

Compliance with the hourly allowable emission limitation above shall be demonstrated based on the results of emission testing conducted in accordance with Methods 1-4 and 7 of 40 CFR Part 60, Appendix A.

The annual emission limitation was developed by multiplying the hourly emission limitation by the maximum operating schedule of 8760 hours/year, and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- c. Emission Limitations: 15.40 lbs CO/hr, 67.46 tpy CO (combined, for emissions units J001, P007, P009 and P010)

Applicable Compliance Method:

Compliance with the hourly allowable emission limitation above shall be demonstrated based on the results of emission testing conducted in accordance with Methods 1-4 and 10 of 40 CFR Part 60, Appendix A.

The annual emission limitation was developed by multiplying the hourly emission limitation by the maximum operating schedule of 8760 hours/year, and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- d. Emission Limitations: 6.90 lb PM₁₀, 30.22 tpy PM₁₀ (combined, for emissions units J001, P007, P009, and P010)

Applicable Compliance Method:

Issued: To be entered upon final issuance

Compliance with the hourly allowable emission limitation above shall be demonstrated based on the results of emission testing conducted in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M.

The annual emission limitation was developed by multiplying the hourly emission limitation by the maximum operating schedule of 8760 hours/year, and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- e. Emission Limitations: 15.0 lbs SO₂/hr, 65.70 tpy SO₂ (combined, for emissions units J001, P007, P009 and P010)

Applicable Compliance Method:

Compliance with the hourly allowable emission limitation above shall be demonstrated based on the results of emission testing conducted in accordance with Methods 1-4 and 6 of 40 CFR Part 60, Appendix A.

The annual emission limitation was developed by multiplying the hourly emission limitation by the maximum operating schedule of 8760 hours/year, and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- f. Emission Limitations:
The RTO shall meet a minimum control efficiency of 95% for both VOC and CO emissions.

Applicable Compliance Method:

Compliance with the control efficiency requirements above shall be demonstrated based on the results of emission testing conducted in accordance with the methods outlined in Section E.1 of this permit. Compliance with the CO destruction efficiency shall be assumed as long as compliance with the hourly CO mass emission limitation is maintained. [Due to creation of CO in the RTO, it is not possible to perform testing to demonstrate compliance directly associated with the destruction of CO entering the RTO.]

- g. Emission Limitation: Fugitive VOC emissions shall not exceed 4.49 TPY.

Applicable Compliance Method:

The annual emission limitation above was developed by the multiplying an

Emissions Unit ID: **J001**

emission factor of 7.78 lbs VOC/1000 gallons of ethanol [as determined through methodology in AP-42, section 5.2-2 (1/95) in conjunction with the information submitted by the permittee in PTI application #03-17224] by the maximum annual throughput of 115.5 million gallons, by 1% (assuming a 99% capture efficiency) and then dividing by 2000 lbs/ton.

Therefore, provided compliance is shown with the maximum annual amount of ethanol processed in this emissions unit, compliance with the annual emission limitation will be assumed.

- h. Emission Limitation: Visible PE from the stack(s) serving this emissions unit shall not exceed 5% opacity, as a six-minute average.

Appliance Compliance Method:

Compliance shall be determined according to test Method 9 of 40 CFR Part 60, Appendix A.

F. Miscellaneous Requirements

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P001) - grain handling (scalper and storage bins)

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(C)	<p>The baghouse(s) shall achieve an outlet emission rate of not greater than 0.010 grains of particulate matter equal to or less than 10 microns in size (PM10) per dry standard cubic foot of exhaust (gr/dscf).</p> <p>PM10 emissions shall not exceed 1.50 tons per year (TPY).</p> <p>Visible particulate emissions (PE) from the stack(s) serving this emissions unit shall not exceed 5% opacity, as a six-minute average.</p> <p>See A.2.a and A.2.d.</p>
OAC rule 3745-17-11(B)	See A.2.b.
OAC rule 3745-17-07(A)	See A.2.b.
40 CFR Part 60 Subpart DD	See A.2.c.

2. Additional Terms and Conditions

- 2.a The permit to install for this air contaminant source takes into account the use of a baghouse system (surge bin vents #1 and #2) and total enclosure (100% capture efficiency) to control PM10 emissions whenever this air contaminant source is in operation, as a voluntary restriction as proposed by the permittee for the purpose of avoiding Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3).
- 2.b The emission limitation specified by this rule is less stringent than the emissions

Emissions Unit ID: P001

limitation established pursuant to OAC rule 3745-31-05(C).

2.c 40 CFR Part 60, Subpart DD (Standards of Performance for Grain Elevators), is applicable to grain storage elevators at any wheat flour mill, wet corn mill, dry corn mill (human consumption), rice mill, or soybean oil extraction plant with a permanent grain storage capacity greater than 1.0 million U.S. bushels. The permanent grain storage capacity of this facility is 1.2 million bushels, but the facility is classified as a dry corn chemical manufacturing (not for human consumption). Therefore, 40 CFR Part 60, Subpart DD, is not applicable.

2.d For the purposes of this permit, all PE is considered to be PM10.

B. Operational Restrictions

1. The permittee shall operate the baghouse system at all times when this emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack(s) serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. the color of the emissions;
 - b. whether the emissions are representative of normal operations;
 - c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. the total duration of any visible emission incident; and
 - e. any corrective actions taken to eliminate the visible emissions.

D. Reporting Requirements

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the stack(s) serving this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.

Issued: To be entered upon final issuance

E. Testing Requirements

1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. The emission testing shall be conducted within 60 days after achieving the maximum production rate at which the emissions unit will be operated, but not later than 180 days after initial startup of such emissions unit.
 - b. The emission testing shall be conducted to:
 - i. demonstrate compliance with the baghouse(s) emission rate of 0.010 gr PM10/dscf.
 - c. The following test methods shall be employed to demonstrate compliance with the above emissions limitations:
 - i. for PM10, 40 CFR Part 51, Appendix M, Methods 201 and 202 and 40 CFR Part 60, Appendix A, Methods 1-4 (for volumetric air flow rate). Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA, NWDO.
 - d. The test(s) shall be conducted while the emissions unit is operating at its maximum capacity, unless otherwise specified or approved by the Ohio EPA, NWDO.
 - e. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, NWDO. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, NWDO's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA, NWDO shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report of the results of the emissions test(s) shall be

Emissions Unit ID: **P001**

signed by the person or persons responsible for the tests and submitted to the Ohio EPA, NWDO within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, NWDO.

2. Compliance with the emission limitations specified in Section A.1 of the terms and conditions of this permit shall be determined in accordance with the following method(s):
 - a. Emission Limitation: The baghouse(s) shall achieve a maximum outlet concentration of not greater than 0.010 gr PM10/dscf of exhaust gas.

Issued: To be entered upon final issuance

Applicable Compliance Method:

Compliance with the grain loading of 0.010 gr/dscf shall be demonstrated based on the results of emission testing conducted in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M.

- b. Emission Limitation: 1.50 ton PM10/yr

Applicable Compliance Method:

The annual allowable emission limitation was developed by the following calculation based on the baghouse design and a maximum operating schedule of 8760 hrs/yr:

$$= 0.010 \text{ gr/dscf} \times 1 \text{ lb/7000 gr} \times 4,000 \text{ dscfm (2,000 dscfm per baghouse)} \times 60 \text{ min/hour} \times 8760 \text{ hours/yr} \times 0.0005 \text{ ton/lb} = 1.50 \text{ tons/year}$$

Therefore, as long as compliance with the 0.010 gr/dscf is maintained, compliance with the annual PM10 limitation shall be ensured.

- c. Emission Limitation: Visible PE from the stack(s) serving this emissions unit shall not exceed 5% opacity, as a six-minute average.

Applicable Compliance Method:

Compliance with the visible emission limitation shall be demonstrated in accordance with test Method 9, as set forth in 40 CFR Part 60, Appendix A.

F. Miscellaneous Requirements

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P002) - Hammermill no. 1

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-0(C)	<p>The baghouse(s) shall achieve an outlet emission rate of not greater than 0.0050 grains of particulate matter equal to or less than 10 microns in size (PM10) per dry standard cubic foot of exhaust (gr/dscf).</p> <p>PM10 emissions shall not exceed 1.13 tons per year (TPY).</p> <p>Visible particulate emissions (PE) from the stack(s) serving this emissions unit shall not exceed 0% opacity, as a six-minute average.</p> <p>See Sections A.2.a and A.2.b.</p>
OAC rule 3745-17-07(A)	See Section A.2.d.
OAC rule 3745-17-11(B)	See Section A.2.c.

2. Additional Terms and Conditions

- 2.a The permit to install for this air contaminant source takes into account the use of a baghouse (hammermill baghouse #1) and total enclosure (100% capture) to control PM10 emissions whenever this air contaminant source is in operation, as a voluntary restriction as proposed by the permittee for the purpose of avoiding Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3).
- 2.b For the purposes of this permit, all PE is considered to be PM10.
- 2.c The uncontrolled mass rate of particulate emissions from this emissions unit cannot be ascertained. Therefore, pursuant to OAC pursuant to OAC rule

Emissions Unit ID: P002

3745-17-11(A)(2)(ii), Figure II of OAC rule 3745-17-11 does not apply. Also, Table 1 does not apply because the facility is located in Ottawa County.

- 2.d** This emissions unit is exempt from the visible emissions limitation specified in OAC rule 3745-17-07(A), pursuant to OAC rule 3745-17-07(A)(3)(h), because OAC rule 3745-17-11 is not applicable.

B. Operational Restrictions

1. The permittee shall operate the baghouse(s) at all times when this emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack(s) serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log, as well as the date and time the daily check was performed. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. the color of the emissions;
 - b. the total duration of any visible emission incident; and
 - c. any corrective actions taken to eliminate the visible emissions.

D. Reporting Requirements

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the stack(s) serving this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the appropriate Ohio EPA district or local field office by January 31 and July 31 of each year and shall cover the previous 6-month period.

E. Testing Requirements

1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. The emission testing shall be conducted within 60 days after achieving the maximum production rate at which the emissions unit(s) will be operated, but not

Issued: To be entered upon final issuance

later than 180 days after initial start-up of one of the five hammer mills.

- b. The emission testing shall be conducted to:
 - i. demonstrate compliance with the baghouse(s) grain loading of 0.0050 gr PM10/dscf.
- c. The following test methods shall be employed to demonstrate compliance with the above emissions limitations:
 - i. for PM10, 40 CFR Part 51, Appendix M, Methods 201 and 202 and 40 CFR Part 60, Appendix A, Methods 1-4 (for volumetric air flow rate). Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA, NWDO.
- d. The test(s) shall be conducted while the emissions unit is operating at its maximum capacity, unless otherwise specified or approved by the Ohio EPA, NWDO.
- e. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, NWDO. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, NWDO's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA, NWDO shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report of the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA, NWDO within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, NWDO.

- 2. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:

Emissions Unit ID: P002

- a. Emission Limitation: The baghouse(s) shall achieve a maximum outlet concentration of not greater than 0.0050 gr PM10/dscf of exhaust gas.

Applicable Compliance Method:

Compliance with the grain loading of 0.0050 gr/dscf shall be demonstrated based on the results of emission testing conducted in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M.

- b. Emission Limitations: 1.13 TPY PM10

Issued: To be entered upon final issuance

Applicable Compliance Method:

The annual allowable emission limitation was developed by the following calculation based on the baghouse design and a maximum operating schedule of 8760 hrs/yr:

$$= 0.0050 \text{ gr/dscf} \times 1 \text{ lb/7000 gr} \times 6,000 \text{ dscfm} \times 60 \text{ min/hour} \times 8760 \text{ hours/yr} \times 0.0005 \text{ ton/lb} = 1.13 \text{ TPY}$$

Therefore, as long as compliance with the 0.0050 gr/dscf is maintained, compliance with the annual PM10 limitation shall be ensured.

- c. Emission Limitation: Visible PE from the stack(s) serving this emissions unit shall not exceed 0% opacity, as a six-minute average.

Applicable Compliance Method:

Compliance shall be determined according to test Method 9, as set forth in 40 CFR Part 60, Appendix A.

F. Miscellaneous Requirements

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P003) - Hammermill no. 2

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(C)	<p>The baghouse(s) shall achieve an outlet emission rate of not greater than 0.0050 grains of particulate matter equal to or less than 10 microns in size (PM10) per dry standard cubic foot of exhaust (gr/dscf).</p> <p>PM10 emissions shall not exceed 1.13 tons per year (TPY).</p> <p>Visible particulate emissions (PE) from the stack(s) serving this emissions unit shall not exceed 0% opacity, as a six-minute average.</p> <p>See Sections A.2.a and A.2.b.</p>
OAC rule 3745-17-07(A)	See Sections A.2.d.
OAC rule 3745-17-11(B)	See Sections A.2.c.

2. Additional Terms and Conditions

- 2.a The permit to install for this air contaminant source takes into account the use of a baghouse (hammermill baghouse #2) and total enclosure (100% capture efficiency) to control PM10 emissions whenever this air contaminant source is in operation, as a voluntary restriction as proposed by the permittee for the purpose of avoiding Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3).
- 2.b For the purposes of this permit, all PE is considered to be PM10.
- 2.c The uncontrolled mass rate of particulate emissions from this emissions unit cannot be ascertained. Therefore, pursuant to OAC pursuant to OAC rule

Issued: To be entered upon final issuance

3745-17-11(A)(2)(ii), Figure II of OAC rule 3745-17-11 does not apply. Also, Table 1 does not apply because the facility is located in Ottawa County.

- 2.d** This emissions unit is exempt from the visible emissions limitation specified in OAC rule 3745-17-07(A), pursuant to OAC rule 3745-17-07(A)(3)(h), because OAC rule 3745-17-11 is not applicable.

B. Operational Restrictions

1. The permittee shall operate the baghouse(s) at all times when this emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack(s) serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log, as well as the date and time the daily check was performed. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. the color of the emissions;
 - b. the total duration of any visible emission incident; and
 - c. any corrective actions taken to eliminate the visible emissions.

D. Reporting Requirements

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the stack(s) serving this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the appropriate Ohio EPA district or local field office by January 31 and July 31 of each year and shall cover the previous 6-month period.

E. Testing Requirements

1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. The emission testing shall be conducted within 60 days after achieving the maximum production rate at which the emissions unit(s) will be operated, but not

Emissions Unit ID: P003

later than 180 days after initial start-up of one of the five hammer mills.

- b. The emission testing shall be conducted to:
 - i. demonstrate compliance with the baghouse(s) grain loading of 0.0050 gr PM10/dscf.
- c. The following test methods shall be employed to demonstrate compliance with the above emissions limitations:
 - i. for PM10, 40 CFR Part 51, Appendix M, Methods 201 and 202 and 40 CFR Part 60, Appendix A, Methods 1-4 (for volumetric air flow rate). Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA, NWDO.
- d. The test(s) shall be conducted while the emissions unit is operating at its maximum capacity, unless otherwise specified or approved by the Ohio EPA, NWDO.
- e. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, NWDO. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, NWDO's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA, NWDO shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report of the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA, NWDO within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, NWDO.

2. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:

Issued: To be entered upon final issuance

- a. Emission Limitation: The baghouse(s) shall achieve a maximum outlet concentration of not greater than 0.0050 gr PM10/dscf of exhaust gas.

Applicable Compliance Method:

Compliance with the grain loading of 0.0050 gr/dscf shall be demonstrated based on the results of emission testing conducted in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M.

- b. Emission Limitations: 1.13 TPY PM10

Issued: To be entered upon final issuance

Applicable Compliance Method:

The annual allowable emission limitation was developed by the following calculation based on the baghouse(s) design and a maximum operating schedule of 8760 hrs/yr:

$$= 0.0050 \text{ gr/dscf} \times 1 \text{ lb/7000 gr} \times 6,000 \text{ dscfm} \times 60 \text{ min/hour} \times 8760 \text{ hours/yr} \times 0.0005 \text{ ton/lb} = 1.13 \text{ TPY}$$

Therefore, as long as compliance with the 0.0050 gr/dscf is maintained, compliance with the annual PM10 limitation shall be ensured.

- c. Emission Limitation: Visible PE from the stack(s) serving this emissions unit shall not exceed 0% opacity, as a six-minute average.

Applicable Compliance Method:

Compliance shall be determined according to test Method 9, as set forth in 40 CFR Part 60, Appendix A.

F. Miscellaneous Requirements

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P004) - Hammermill no. 3

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(C)	The baghouse(s) shall achieve an outlet emission rate of not greater than 0.0050 grains of particulate matter equal to or less than 10 microns in size (PM10) per dry standard cubic foot of exhaust (gr/dscf). PM10 emissions shall not exceed 1.13 tons per year (TPY). Visible particulate emissions (PE) from the stack(s) serving this emissions unit shall not exceed 0% opacity, as a six-minute average. See Sections A.2.a and A.2.b.
OAC rule 3745-17-07(A)	See Section A.2.d.
OAC rule 3745-17-11(B)	See Section A.2.c.

2. Additional Terms and Conditions

- 2.a The permit to install for this air contaminant source takes into account the use of a baghouse (hammermill baghouse #3) and total enclosure (100% capture efficiency) to control PM10 emissions whenever this air contaminant source is in operation, as a voluntary restriction as proposed by the permittee for the purpose of avoiding Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3).
- 2.b For the purposes of this permit, all PE is considered to be PM10.
- 2.c The uncontrolled mass rate of particulate emissions from this emissions unit cannot be ascertained. Therefore, pursuant to OAC pursuant to OAC rule 3745-17-11(A)(2)(ii), Figure II of OAC rule 3745-17-11 does not apply. Also,

Issued: To be entered upon final issuance

Table 1 does not apply because the facility is located in Ottawa County.

- 2.d** This emissions unit is exempt from the visible emissions limitation specified in OAC rule 3745-17-07(A), pursuant to OAC rule 3745-17-07(A)(3)(h), because OAC rule 3745-17-11 is not applicable.

B. Operational Restrictions

1. The permittee shall operate the baghouse(s) at all times when this emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack(s) serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log, as well as the date and time the daily check was performed. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. the color of the emissions;
 - b. the total duration of any visible emission incident; and
 - c. any corrective actions taken to eliminate the visible emissions.

D. Reporting Requirements

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the stack(s) serving this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the appropriate Ohio EPA district or local field office by January 31 and July 31 of each year and shall cover the previous 6-month period.

E. Testing Requirements

1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. The emission testing shall be conducted within 60 days after achieving the maximum production rate at which the emissions unit(s) will be operated, but not later than 180 days after initial start-up of one of the five hammer mills.

- b. The emission testing shall be conducted to:
 - i. demonstrate compliance with the baghouse(s) grain loading of 0.0050 gr PM10/dscf.
- c. The following test methods shall be employed to demonstrate compliance with the above emissions limitations:
 - i. for PM10, 40 CFR Part 51, Appendix M, Methods 201 and 202 and 40 CFR Part 60, Appendix A, Methods 1-4 (for volumetric air flow rate). Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA, NWDO.
- d. The test(s) shall be conducted while the emissions unit is operating at its maximum capacity, unless otherwise specified or approved by the Ohio EPA, NWDO.
- e. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, NWDO. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, NWDO's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA, NWDO shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report of the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA, NWDO within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, NWDO.

- 2. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:

Issued: To be entered upon final issuance

- a. Emission Limitation: The baghouse(s) shall achieve a maximum outlet concentration of not greater than 0.0050 gr PM10/dscf of exhaust gas.

Applicable Compliance Method:

Compliance with the grain loading of 0.0050 gr/dscf shall be demonstrated based on the results of emission testing conducted in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M.

- b. Emission Limitations: 1.13 TPY PM10

Issued: To be entered upon final issuance

Applicable Compliance Method:

The annual allowable emission limitation was developed by the following calculation based on the baghouse(s) design and a maximum operating schedule of 8760 hrs/yr:

$$= 0.0050 \text{ gr/dscf} \times 1 \text{ lb/7000 gr} \times 6,000 \text{ dscfm} \times 60 \text{ min/hour} \times 8760 \text{ hours/yr} \times 0.0005 \text{ ton/lb} = 1.13 \text{ TPY}$$

Therefore, as long as compliance with the 0.0050 gr/dscf is maintained, compliance with the annual PM10 limitation shall be ensured.

- c. Emission Limitation: Visible PE from the stack(s) serving this emissions unit shall not exceed 0% opacity, as a six-minute average.

Applicable Compliance Method:

Compliance shall be determined according to test Method 9, as set forth in 40 CFR Part 60, Appendix A.

F. Miscellaneous Requirements

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P005) - Hammermill no. 4

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-0(C)	<p>The baghouse(s) shall achieve an outlet emission rate of not greater than 0.0050 grains of particulate matter equal to or less than 10 microns in size (PM10) per dry standard cubic foot of exhaust (gr/dscf).</p> <p>PM10 emissions shall not exceed 1.13 tons per year (TPY).</p> <p>Visible particulate emissions (PE) from the stack(s) serving this emissions unit shall not exceed 0% opacity, as a six-minute average.</p> <p>See Sections A.2.a and A.2.b.</p>
OAC rule 3745-17-07(A)	See Section A.2.d.
OAC rule 3745-17-11(B)	See Section A.2.c.

2. Additional Terms and Conditions

- 2.a The permit to install for this air contaminant source takes into account the use of a baghouse (hammermill baghouse #4) and total enclosure (100% capture efficiency) to control PM10 emissions whenever this air contaminant source is in operation, as a voluntary restriction as proposed by the permittee for the purpose of avoiding Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3).
- 2.b For the purposes of this permit, all PE is considered to be PM10.
- 2.c The uncontrolled mass rate of particulate emissions from this emissions unit cannot be ascertained. Therefore, pursuant to OAC pursuant to OAC rule

Emissions Unit ID: **P005**

3745-17-11(A)(2)(ii), Figure II of OAC rule 3745-17-11 does not apply. Also, Table 1 does not apply because the facility is located in Ottawa County.

- 2.d** This emissions unit is exempt from the visible emissions limitation specified in OAC rule 3745-17-07(A), pursuant to OAC rule 3745-17-07(A)(3)(h), because OAC rule 3745-17-11 is not applicable.

B. Operational Restrictions

1. The permittee shall operate the baghouse(s) at all times when this emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack(s) serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log, as well as the date and time the daily check was performed. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. the color of the emissions;
 - b. the total duration of any visible emission incident; and
 - c. any corrective actions taken to eliminate the visible emissions.

D. Reporting Requirements

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the stack serving this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the appropriate Ohio EPA district or local field office by January 31 and July 31 of each year and shall cover the previous 6-month period.

E. Testing Requirements

1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. The emission testing shall be conducted within 60 days after achieving the maximum production rate at which the emissions unit(s) will be operated, but not

Issued: To be entered upon final issuance

later than 180 days after initial start-up of one of the five hammer mills.

- b. The emission testing shall be conducted to:
 - i. demonstrate compliance with the baghouse(s) grain loading of 0.0050 gr PM10/dscf.
- c. The following test methods shall be employed to demonstrate compliance with the above emissions limitations:
 - i. for PM10, 40 CFR Part 51, Appendix M, Methods 201 and 202 and 40 CFR Part 60, Appendix A, Methods 1-4 (for volumetric air flow rate). Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA, NWDO.
- d. The test(s) shall be conducted while the emissions unit is operating at its maximum capacity, unless otherwise specified or approved by the Ohio EPA, NWDO.
- e. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, NWDO. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, NWDO's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA, NWDO shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report of the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA, NWDO within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, NWDO.

- 2. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:

Emissions Unit ID: P005

- a. Emission Limitation: The baghouse(s) shall achieve a maximum outlet concentration of not greater than 0.0050 gr PM10/dscf of exhaust gas.

Applicable Compliance Method:

Compliance with the grain loading of 0.0050 gr/dscf shall be demonstrated based on the results of emission testing conducted in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M.

- b. Emission Limitations: 1.13 TPY PM10

Issued: To be entered upon final issuance

Applicable Compliance Method:

The annual allowable emission limitation was developed by the following calculation based on the baghouse(s) design and a maximum operating schedule of 8760 hrs/yr:

$$= 0.0050 \text{ gr/dscf} \times 1 \text{ lb/7000 gr} \times 6,000 \text{ dscfm} \times 60 \text{ min/hour} \times 8760 \text{ hours/yr} \times 0.0005 \text{ ton/lb} = 1.13 \text{ TPY}$$

Therefore, as long as compliance with the 0.0050 gr/dscf is maintained, compliance with the annual PM10 limitation shall be ensured.

- c. Emission Limitation: Visible PE from the stack(s) serving this emissions unit shall not exceed 0% opacity, as a six-minute average.

Applicable Compliance Method:

Compliance shall be determined according to test Method 9, as set forth in 40 CFR Part 60, Appendix A.

F. Miscellaneous Requirements

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P006) - milled corn storage bin

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(C)	<p>The baghouse(s) shall achieve an outlet emission rate of not greater than 0.0050 grains of particulate matter equal to or less than 10 microns in size (PM10) per dry standard cubic foot of exhaust (gr/dscf).</p> <p>PM10 emissions shall not exceed 0.56 tons per year (TPY).</p> <p>Visible particulate emissions (PE) from the stack(s) serving this emissions unit shall not exceed 0% opacity, as a six-minute average.</p> <p>See Sections A.2.a and A.2.b.</p>
OAC rule 3745-17-07(A)	See Section A.2.d.
OAC rule 3745-17-11(B)	See Section A.2.c.

2. Additional Terms and Conditions

- 2.a The permit to install for this air contaminant source takes into account the use of a baghouse (ground corn storage bin fabric filter) and total enclosure (100% capture efficiency) to control PM10 emissions whenever this air contaminant source is in operation, as a voluntary restriction as proposed by the permittee for the purpose of avoiding Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3).
- 2.b For the purposes of this permit, all PE is considered to be PM10.
- 2.c The uncontrolled mass rate of particulate emissions from this emissions unit is less than ten pounds per hour. Therefore, pursuant to OAC pursuant to OAC

Emissions Unit ID: **P006**

rule 3745-17-11(A)(2)(ii), Figure II of OAC rule 3745-17-11 does not apply. Also, Table 1 does not apply because the facility is located in Ottawa County.

- 2.d** This emissions unit is exempt from the visible emissions limitation specified in OAC rule 3745-17-07(A), pursuant to OAC rule 3745-17-07(A)(3)(h), because OAC rule 3745-17-11 is not applicable.

B. Operational Restrictions

1. The permittee shall operate the baghouse(s) at all times when this emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack(s) serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log, as well as the date and time the daily check was performed. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. the color of the emissions;
 - b. the total duration of any visible emission incident; and
 - c. any corrective actions taken to eliminate the visible emissions.

D. Reporting Requirements

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the stack(s) serving this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the appropriate Ohio EPA district or local field office by January 31 and July 31 of each year and shall cover the previous 6-month period.

E. Testing Requirements

1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. The emission testing shall be conducted within 60 days after achieving the maximum production rate at which the emissions unit(s) will be operated, but not

Issued: To be entered upon final issuance

later than 180 days after initial start-up of one of the five hammer mills.

- b. The emission testing shall be conducted to:
 - i. demonstrate compliance with the baghouse(s) grain loading of 0.0050 gr PM10/dscf.
- c. The following test methods shall be employed to demonstrate compliance with the above emissions limitations:
 - i. for PM10, 40 CFR Part 51, Appendix M, Methods 201 and 202 and 40 CFR Part 60, Appendix A, Methods 1-4 (for volumetric air flow rate). Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA, NWDO.
- d. The test(s) shall be conducted while the emissions unit is operating at its maximum capacity, unless otherwise specified or approved by the Ohio EPA, NWDO.
- e. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, NWDO. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, NWDO's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA, NWDO shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report of the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA, NWDO within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, NWDO.

- 2. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:

Emissions Unit ID: P006

- a. Emission Limitation: The baghouse(s) shall achieve a maximum outlet concentration of not greater than 0.0050 gr PM10/dscf of exhaust gas.

Applicable Compliance Method:

Compliance with the grain loading of 0.0050 gr/dscf shall be demonstrated based on the results of emission testing conducted in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M.

- b. Emission Limitations: 0.56 TPY PM10

Issued: To be entered upon final issuance

Applicable Compliance Method:

The annual allowable emission limitation was developed by the following calculation based on the baghouse(s) design and a maximum operating schedule of 8760 hrs/yr:

$$= 0.0050 \text{ gr/dscf} \times 1 \text{ lb/7000 gr} \times 3,000 \text{ dscfm} \times 60 \text{ min/hour} \times 8760 \text{ hours/yr} \times 0.0005 \text{ ton/lb} = 0.56 \text{ TPY}$$

Therefore, as long as compliance with the 0.0050 gr/dscf is maintained, compliance with the annual PM10 limitation shall be ensured.

- c. Emission Limitation: Visible PE from the stack(s) serving this emissions unit shall not exceed 0% opacity, as a six-minute average.

Applicable Compliance Method:

Compliance shall be determined according to test Method 9, as set forth in 40 CFR Part 60, Appendix A.

F. Miscellaneous Requirements

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P007) - distillation operations and liquefaction tanks

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(A)(3)	<p>Nitrogen oxides (NOx) emissions from emissions units J001, P007, P009 and P010, combined, shall not exceed 12.96 pounds per hour (lbs/hr) and 56.76 tons per year (TPY).</p> <p>Carbon monoxide (CO) emissions from J001, P007, P009 and P010 shall not exceed 15.40 lbs/hr and 67.46 TPY.</p> <p>Particulate emissions equal to or less than 10 microns in size (PM10), from emissions units J001, P007, P009 and P010, combined, shall not exceed 6.80 lbs/hr and 29.78 TPY (See Section A.2.c).</p> <p>Volatile organic compound (VOC) emissions from emissions units J001, P007, P009 and P010, combined, shall not exceed 10.0 lbs/hr and 43.80 TPY.</p> <p>Sulfur dioxide (SO2) emissions from emissions unit J001, P007, P009 and P010, combined shall not exceed 15.0 lbs/hr and 65.70 TPY.</p> <p>Visible particulate emissions (PE) from the stack(s) serving this emissions unit shall not exceed 5% opacity as a six-minute average.</p> <p>See Sections A.2.a and A.2.f.</p>
OAC rule 3745-21-09(DD)	See the requirements for emissions unit P801.
40 CFR Part 60, Subpart VV	See the requirements for emissions unit P801.

Issued: To be entered upon final issuance

OAC rule 3745-17-07(A)	See Section A.2.d.
OAC rule 3745-17-11(B)	See Section A.2.d.
OAC rule 3745-18-06(E)(2)	See Section A.2.d.
OAC rule 3745-21-08(B)	See Section A.2.e.
OAC rule 3745-114-01 ORC 3704.03(F)	See section C.2.

2. Additional Terms and Conditions

- 2.a** Best available technology (BAT) requirements for this emissions unit has been determined to be the use of the following:
- i. two (2) regenerative thermal oxidizers (RTO). The RTO shall meet a minimum control efficiency of 95% for both VOC and CO emissions;
 - ii. firing of only natural gas and the use of low NOx burners in the RTOs; and
 - iii. the control systems (RTOs/multiclone) shall result in a PM10 mass emission rate not to exceed 6.80 lbs/hr.
- 2.b** The annual allowable emission rate is based on the annual production of 110 million gallons of 200-proof ethanol (115.5 million gallons denatured ethanol). Since the facility annual production rate is equivalent to the maximum facility capacity, no operational restrictions, monitoring, record keeping or reporting requirements are necessary to ensure that this emissions unit does not exceed its annual allowable emission rates. The requirement to record the amount of denatured ethanol produced is in the terms and conditions of emissions unit J001.
- 2.c** For the purposes of this permit, all PE is considered to be PM10.
- 2.d** The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
- 2.e** The permittee has satisfied the "best available control techniques and operating practices" required pursuant to OAC rule 3745-21-08(B) by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05(A)(3) in this Permit to Install.

Emissions Unit ID: P007

On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the requirement to satisfy the "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

- 2.f** This emissions unit includes the following air contaminant sources: slurry tank, liquefaction tank #1 & #2, beer column, stripper, rectifier, molecular sieves #1 & #2, 200-proof condenser, whole stillage tank, process condensate tank, evaporators syrup tank, thin stillage tank, and centrifuges #1 through #4.

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to continuously monitor and record the combustion temperature within the thermal oxidizer(s) during operation of this emissions unit. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the combustion temperature within the thermal oxidizer(s) on a continuous basis.

Whenever the monitored value for the combustion temperature deviates from the value specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation: the date and time the deviation began and the magnitude of the deviation at that time, the date(s) the investigation was conducted, the names of the personnel who conducted the investigation, and the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable value specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken: a description of the corrective action, the date it was completed, the date and time the deviation ended, the total period of time (in minutes) during which there was a deviation, the combustion

Issued: To be entered upon final issuance

temperature within the thermal oxidizer(s) immediately after the corrective action, and the names of the personnel who performed the work. Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

The average combustion temperature within the thermal oxidizer(s), for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.

This value is effective for the duration of this permit, unless revisions are requested by the permittee and approved in writing by the appropriate Ohio EPA District Office or local air agency.

2. The permit to install for these emissions unit(s) J001, B001-B004, P007, P008, P009 and P010 was evaluated based on the actual materials and the design parameters of the emissions unit's(s') exhaust system, as specified by the permittee in the permit application. The "Toxic Air Contaminant Statute", ORC 3704.03(F), was applied to this/these emissions unit(s) for each toxic air contaminant listed in OAC rule 3745-114-01, using data from the permit application; and modeling was performed for each toxic air contaminant(s) emitted at over one ton per year using an air dispersion model such as SCREEN 3.0, AERMOD, or ISCST3, or other Ohio EPA approved model. The predicted 1-hour maximum ground-level concentration result(s) from the approved air dispersion model, was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC), calculated as described in the Ohio EPA guidance document entitled "Review of New Sources of Air Toxic Emissions, Option A", as follows:
 - a. the exposure limit, expressed as a time-weighted average concentration for a conventional 8-hour workday and a 40-hour workweek, for each toxic compound(s) emitted from the emissions unit(s), (as determined from the raw materials processed and/or coatings or other materials applied) has been documented from one of the following sources and in the following order of preference (TLV was and shall be used, if the chemical is listed):
 - i. threshold limit value (TLV) from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices";
or
 - ii. STEL (short term exposure limit) or the ceiling value from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold

Emissions Unit ID: **P007**

Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices"; the STEL or ceiling value is multiplied by 0.737 to convert the 15-minute exposure limit to an equivalent 8-hour TLV.

- b. The TLV is divided by ten to adjust the standard from the working population to the general public (TLV/10).
- c. This standard is/was then adjusted to account for the duration of the exposure or the operating hours of the emissions unit(s), i.e., "X" hours per day and "Y" days per week, from that of 8 hours per day and 5 days per week. The resulting calculation was (and shall be) used to determine the Maximum Acceptable Ground-Level Concentration (MAGLC):

$$\text{TLV}/10 \times 8/X \times 5/Y = 4 \text{ TLV}/XY = \text{MAGLC}$$

- d. The following summarizes the results of dispersion modeling for the significant toxic contaminants (emitted at 1 or more tons/year) or "worst case" toxic contaminant(s):

Pollutant: Acetaldehyde

TLV (mg/m³): 45.0

Maximum Hourly Emission Rate (lbs/hr): 2.11

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 28.38

MAGLC (ug/m³): 1071.43

Pollutant: Hexane

TLV (mg/m³): 176.24

Maximum Hourly Emission Rate (lbs/hr): 1.09

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 0.81

MAGLC (ug/m³): 4,196

Pollutant: Methanol

TLV (mg/m³): 262

Maximum Hourly Emission Rate (lbs/hr): 0.34

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 0.69

MAGLC (ug/m³): 6238

The permittee, has demonstrated that emissions of acetaldehyde, hexane and methanol, from emissions unit(s) J001, B001, B002, B003, B004, P007, P008, P009 and P010, are calculated to be less than eighty per cent of the maximum acceptable ground level concentration (MAGLC); any new

Issued: To be entered upon final issuance

raw material or processing agent shall not be applied without evaluating each component toxic air contaminant in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F).

3. Prior to making any physical changes to or changes in the method of operation of the emissions unit(s), that could impact the parameters or values that were used in the predicted 1-hour maximum ground-level concentration", the permittee shall re-model the change(s) to demonstrate that the MAGLC has not been exceeded. Changes that can affect the parameters/values used in determining the 1-hour maximum ground-level concentration include, but are not limited to, the following:
 - a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a new toxic air contaminant with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled;
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any toxic air contaminant listed in OAC rule 3745-114-01, that was modeled from the initial (or last) application; and
 - c. physical changes to the emissions unit(s) or its/their exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Toxic Air Contaminant Statute" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to a non-restrictive change to a parameter or process operation, where compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), has been documented. If the change(s) meet(s) the definition of a "modification" or if a new toxic is emitted, or the modeled toxic(s) is/are expected to exceed the previous modeled level(s), then the permittee shall apply for and obtain a final permit-to-install prior to the change. The Director may consider any significant departure from the operations of the emissions unit, described in the permit-to-install application, as a modification that results in greater emissions than the emissions rate modeled to determine the ground level concentration; and may require the permittee to submit a permit-to-install application for the increased emissions.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

4. The permittee shall collect, record, and retain the following information for each toxic evaluation conducted to determine compliance with the "Toxic Air Contaminant

Emissions Unit ID: P007

Statute", ORC 3704.03(F):

- a. a description of the parameters/values used in each compliance demonstration and the parameters or values changed for any re-evaluation of the toxic(s) modeled (the composition of materials, new toxic contaminants emitted, change in stack/exhaust parameters, etc.);
- b. the Maximum Acceptable Ground-Level Concentration (MAGLC) for each significant toxic contaminant or worst-case contaminant, calculated in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F);
- c. a copy of the computer model run(s), that established the predicted 1-hour maximum ground-level concentration that demonstrated the emissions unit(s) to be in compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), initially and for each change that requires re-evaluation of the toxic air contaminant emissions; and
- d. the documentation of the initial evaluation of compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), and documentation of any determination that was conducted to re-evaluate compliance due to a change made to the emissions unit(s) or the materials applied.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

5. The permittee shall maintain a record of any change made to a parameter or value used in the dispersion model, used to demonstrate compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration. The record shall include the date and reason(s) for the change and if the change would increase the ground-level concentration.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

D. Reporting Requirements

1. The permittee shall submit quarterly reports that identify the following information concerning the operation of the control equipment (thermal oxidizer(s)) during the operation of this emissions unit:
 - a. all 3-hour blocks of time during which the average combustion temperature within the thermal oxidizer(s), when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the

Emissions Unit ID: **P007**

most recent performance test that demonstrated the emissions unit was in compliance.

- b. an identification of each incident of deviation described in (a) where a prompt investigation was not conducted;
- c. an identification of each incident of deviation described in (a) where prompt corrective action, that would bring the combustion temperature into compliance with the acceptable range, was determined to be necessary and was not taken; and
- d. an identification of each incident of deviation described in (a) where proper records were not maintained for the investigation and/or the corrective action.

These quarterly reports shall be submitted (i.e., postmarked) by January 31, April 30, July 31, and October 31 of each year; and each report shall cover the previous calendar quarter.

2. The permittee shall submit annual reports to the appropriate Ohio EPA District Office or local air agency, documenting any changes made to a parameter or value used in the dispersion model, that was used to demonstrate compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration. If no changes to the emissions unit(s) or the exhaust stack have been made, then the report shall include a statement to this effect. This report shall be postmarked or delivered no later than January 31 following the end of each calendar year.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

E. Testing Requirements

1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. The emission testing shall be conducted within 60 days after achieving the maximum production rate at which the emissions unit will be operated, but not later than 180 days after initial startup of such emissions unit.
 - b. The emission testing shall be conducted to demonstrate compliance with the NO_x, CO, VOC, PM₁₀ and SO₂ mass emission limitations for this emissions

Issued: To be entered upon final issuance

unit. Emission testing shall also be conducted to verify the expected emissions for single and combined HAPs.

- c. The following test methods shall be employed to demonstrate compliance with the above emission limitations:
 - i. for PM10, Methods 201 and 202 of 40 CFR Part 51, Appendix M;
 - ii. for NOx, Methods 1-4 and 7 of 40 CFR Part 60, Appendix A;
 - iii. for CO, Methods 1-4 and 10 of 40 CFR Part 60, Appendix A;
 - iv. for SO2, Methods 1-4 and 6 of 40 CFR Part 60, Appendix A;
 - iv. for VOC, Methods 1-4 and 18, 25 or 25A of 40 CFR Part 60, Appendix A. Appropriate methods shall be used in conjunction with the test methods and procedures specified in Methods 18, 25, or 25A of 40 CFR Part 60, Appendix A for determining VOC mass emissions; and
 - v. for HAPs, Methods 18 or 320 from 40 CFR Part 60, Appendix A.

Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA, NWDO.

- d. The control efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in Methods 18, 25, or 25A of 40 CFR Part 60, Appendix A for VOC emissions . The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases."
- e. the test(s) shall be conducted while emissions units J001, P007, P009 and P010 are operating at their maximum capacities (as stated in the PTI application for this permit), unless otherwise specified or approved by the Ohio EPA, NWDO.
- f. During emission testing, the permittee shall also record the following information:
 - i. the average combustion temperature within the thermal oxidizer(s), in degrees Fahrenheit.
- g. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, NWDO. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to

Emissions Unit ID: P007

submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, NWDO's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA, NWDO shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report of the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA, NWDO within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, NWDO.

2. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitations: 10.0 lbs VOC/hr, 43.80 tpy VOC (combined, for emissions unit J001, P007, P009 and P010)

Applicable Compliance Method:

Compliance with the hourly allowable emission limitation above shall be demonstrated based on the results of emission testing conducted in accordance with Methods 1-4 and 18, 25 or 25A of 40 CFR Part 60, Appendix A.

The annual emission limitation was developed by multiplying the hourly emission limitation by the maximum operating schedule of 8760 hours/year, and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- b. Emission Limitations: 12.96 lbs NO_x/hr, 56.76 tpy NO_x (combined, for emissions units J001, P007, P009, and P010)

Applicable Compliance Method:

Compliance with the hourly allowable emission limitation above shall be demonstrated based on the results of emission testing conducted in accordance with Methods 1-4 and 7 of 40 CFR Part 60, Appendix A.

Issued: To be entered upon final issuance

The annual emission limitation was developed by multiplying the hourly emission limitation by the maximum operating schedule of 8760 hours/year, and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- c. Emission Limitations: 15.40 lbs CO/hr, 67.46 tpy CO (combined, for emissions units J001, P007, P009 and P010)

Applicable Compliance Method:

Compliance with the hourly allowable emission limitation above shall be demonstrated based on the results of emission testing conducted in accordance with Methods 1-4 and 10 of 40 CFR Part 60, Appendix A.

The annual emission limitation was developed by multiplying the hourly emission limitation by the maximum operating schedule of 8760 hours/year, and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- d. Emission Limitations: 6.80 lb PM10, 29.78 tpy PM10 (combined, for emissions units J001, P007, P009, and P010)

Applicable Compliance Method:

Compliance with the hourly allowable emission limitation above shall be demonstrated based on the results of emission testing conducted in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M.

The annual emission limitation was developed by multiplying the hourly emission limitation by the maximum operating schedule of 8760 hours/year, and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- e. Emission Limitations: 15.0 lbs SO₂/hr, 65.70 tpy SO₂ (combined, for emissions units J001, P007, P009 and P010)

Applicable Compliance Method:

Compliance with the hourly allowable emission limitation above shall be demonstrated based on the results of emission testing conducted in accordance

Emissions Unit ID: P007

with Methods 1-4 and 6 of 40 CFR Part 60, Appendix A.

The annual emission limitation was developed by multiplying the hourly emission limitation by the maximum operating schedule of 8760 hours/year, and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

f. Emission Limitations:

The RTO shall meet a minimum control efficiency of 95% for both VOC and CO emissions.

Applicable Compliance Method:

Compliance with the control efficiency requirements above shall be demonstrated based on the results of emission testing conducted in accordance with the methods outlined in Section E.1 of this permit. Compliance with the CO destruction efficiency shall be assumed as long as compliance with the hourly CO mass emission limitation is maintained. [Due to creation of CO in the RTO, it is not possible to perform testing to demonstrate compliance directly associated with the destruction of CO entering the RTO.]

- g. Emission Limitation: Visible PE from the stack(s) serving this emissions unit shall not exceed 5% opacity, as a six-minute average.

Appliance Compliance Method:

Compliance shall be determined according to test Method 9 of 40 CFR Part 60, Appendix A.

F. Miscellaneous Requirements

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P008) - fermentation and beer well

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(A)(3)	Volatile organic compound (VOC) emissions from this emissions units shall not exceed 8.0 lbs/hr and 35.04 TPY. See Sections A.2.a.
OAC rule 3745-21-09(DD)	See the requirements for emissions unit P801.
40 CFR Part 60, Subpart VV	See the requirements for emissions unit P801.
OAC rule 3745-114-01 ORC 3704.03(F)	See section C.2

2. Additional Terms and Conditions

- 2.a Best available technology (BAT) requirements for this emissions unit has been determined to be the use of the following:
 - i. a wet scrubber for VOC control. The scrubber shall meet a minimum control efficiency of 98.5% for VOC emissions.
- 2.b The annual allowable emission rate is based on the annual production of 110 million gallons of 200-proof ethanol (115.5 million gallons denatured ethanol). Since the facility annual production rate is equivalent to the maximum facility capacity, no operational restrictions, monitoring, record keeping or reporting requirements are necessary to ensure that this emissions unit does not exceed its annual allowable emission rates. The requirement to record the amount of denatured ethanol produced is in the terms and conditions of emissions unit J001.

B. Operational Restrictions

Issued: To be entered upon final issuance
None

Emissions Unit ID: **P008**

Issued: To be entered upon final issuance

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to continuously monitor the pressure drop across the scrubber(s), in inches of water, and the scrubber(s) water flow rate, in gallons per minute during operation of this emissions unit. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop, in inches of water, across the scrubber(s) and the scrubber(s) water flow rate, in gallons per minute, on a once per shift basis.

Whenever the monitored value for the pressure drop and/or the monitor value for the water flow rate deviates from the value specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation: the date and time the deviation began and the magnitude of the deviation at that time, the date(s) the investigation was conducted, the names of the personnel who conducted the investigation, and the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable value specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken: a description of the corrective action, the date it was completed, the date and time the deviation ended, the total period of time (in minutes) during which there was a deviation, the pressure drop and/or water flow rate reading immediately after the corrective action, and the names of the personnel who performed the work. Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

The pressure drop across the scrubber(s) shall be maintained within the range established during the most recent emission testing that demonstrated the emissions unit was in compliance (until such time that such range is established, the pressure drop across the scrubber shall be maintained in accordance with the manufacturer's specifications). The scrubber water flow rate shall be no less the value established during the most recent emission testing that demonstrated the emissions unit was in compliance (until such time that such value is established, the scrubber(s) water flow rate shall be maintained in accordance with the manufacturer's specifications).

Emissions Unit ID: **P008**

The pressure drop range and water flow rate are effective for the duration of this permit, unless revisions are requested by the permittee and approved in writing by the appropriate Ohio EPA District Office or local air agency. The permittee may request revisions to the range and/or water flow rate based upon information obtained during future emission tests that demonstrate compliance with the allowable emission rates for this emissions unit. In addition, approved revisions to the pressure drop range and/or water flow rate value will not constitute a relaxation of the monitoring requirements of this permit and may be incorporated into the operating permit for the facility by means of a permit modification.

2. The permit to install for these emissions unit(s) J001, B001- B004, and P007 - P010, was evaluated based on the actual materials and the design parameters of the emissions unit's(s') exhaust system, as specified by the permittee in the permit application. The "Toxic Air Contaminant Statute", ORC 3704.03(F), was applied to this/these emissions unit(s) for each toxic air contaminant listed in OAC rule 3745-114-01, using data from the permit application; and modeling was performed for each toxic air contaminant(s) emitted at over one ton per year using an air dispersion model such as SCREEN 3.0, AERMOD, or ISCST3, or other Ohio EPA approved model. The predicted 1-hour maximum ground-level concentration result(s) from the approved air dispersion model, was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC), calculated as described in the Ohio EPA guidance document entitled "Review of New Sources of Air Toxic Emissions, Option A", as follows:
 - a. the exposure limit, expressed as a time-weighted average concentration for a conventional 8-hour workday and a 40-hour workweek, for each toxic compound(s) emitted from the emissions unit(s), (as determined from the raw materials processed and/or coatings or other materials applied) has been documented from one of the following sources and in the following order of preference (TLV was and shall be used, if the chemical is listed):
 - i. threshold limit value (TLV) from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices";
or
 - ii. STEL (short term exposure limit) or the ceiling value from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices"; the STEL or ceiling value is multiplied by 0.737 to convert the 15-minute exposure limit to an equivalent 8-hour TLV.

Emissions Unit ID: P008

- b. The TLV is divided by ten to adjust the standard from the working population to the general public (TLV/10).
- c. This standard is/was then adjusted to account for the duration of the exposure or the operating hours of the emissions unit(s), i.e., "X" hours per day and "Y" days per week, from that of 8 hours per day and 5 days per week. The resulting calculation was (and shall be) used to determine the Maximum Acceptable Ground-Level Concentration (MAGLC):

$$\text{TLV}/10 \times 8/X \times 5/Y = 4 \text{ TLV}/XY = \text{MAGLC}$$

- d. The following summarizes the results of dispersion modeling for the significant toxic contaminants (emitted at 1 or more tons/year) or "worst case" toxic contaminant(s):

Pollutant: AcetaldehydeTLV (mg/m³): 45.0

Maximum Hourly Emission Rate (lbs/hr): 2.11

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 28.38MAGLC (ug/m³): 1071.43**Pollutant:** HexaneTLV (mg/m³): 176.24

Maximum Hourly Emission Rate (lbs/hr): 1.09

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 0.81MAGLC (ug/m³): 4,196**Pollutant:** MethanolTLV (mg/m³): 262

Maximum Hourly Emission Rate (lbs/hr): 0.34

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 0.69MAGLC (ug/m³): 6238

The permittee, has demonstrated that emissions of acetaldehyde, hexane, methanol, from emissions unit(s) J001, B001-B004 and P007-P010, are calculated to be less than eighty per cent of the maximum acceptable ground level concentration (MAGLC); any new raw material or processing agent shall not be applied without evaluating each component toxic air contaminant in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F).

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering

Issued: To be entered upon final issuance

Guide #70

3. Prior to making any physical changes to or changes in the method of operation of the emissions unit(s), that could impact the parameters or values that were used in the predicted 1-hour maximum ground-level concentration", the permittee shall re-model the change(s) to demonstrate that the MAGLC has not been exceeded. Changes that can affect the parameters/values used in determining the 1-hour maximum ground-level concentration include, but are not limited to, the following:
 - a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a new toxic air contaminant with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled;
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any toxic air contaminant listed in OAC rule 3745-114-01, that was modeled from the initial (or last) application; and
 - c. physical changes to the emissions unit(s) or its/their exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Toxic Air Contaminant Statute" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to a non-restrictive change to a parameter or process operation, where compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), has been documented. If the change(s) meet(s) the definition of a "modification" or if a new toxic is emitted, or the modeled toxic(s) is/are expected to exceed the previous modeled level(s), then the permittee shall apply for and obtain a final permit-to-install prior to the change. The Director may consider any significant departure from the operations of the emissions unit, described in the permit-to-install application, as a modification that results in greater emissions than the emissions rate modeled to determine the ground level concentration; and may require the permittee to submit a permit-to-install application for the increased emissions.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

4. The permittee shall collect, record, and retain the following information for each toxic evaluation conducted to determine compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F):

Emissions Unit ID: P008

- a. a description of the parameters/values used in each compliance demonstration and the parameters or values changed for any re-evaluation of the toxic(s) modeled (the composition of materials, new toxic contaminants emitted, change in stack/exhaust parameters, etc.);
- b. the Maximum Acceptable Ground-Level Concentration (MAGLC) for each significant toxic contaminant or worst-case contaminant, calculated in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F);
- c. a copy of the computer model run(s), that established the predicted 1-hour maximum ground-level concentration that demonstrated the emissions unit(s) to be in compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), initially and for each change that requires re-evaluation of the toxic air contaminant emissions; and
- d. the documentation of the initial evaluation of compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), and documentation of any determination that was conducted to re-evaluate compliance due to a change made to the emissions unit(s) or the materials applied.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

5. The permittee shall maintain a record of any change made to a parameter or value used in the dispersion model, used to demonstrate compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration. The record shall include the date and reason(s) for the change and if the change would increase the ground-level concentration.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

D. Reporting Requirements

1. The permittee shall submit quarterly reports that identify the following information concerning the operation of the control equipment (scrubber) during the operation of this emissions unit:
 - a. each period of time when the pressure drop across the scrubber(s) was outside of the acceptable range;

Issued: To be entered upon final issuance

- b. each period of time when the scrubber(s) water flow rate deviated from the acceptable value;
- c. an identification of each incident of deviation described in (a) and/or (b) where prompt corrective action, that would bring the pressure drop and/or water flow rate into compliance with the acceptable range/value, was determined to be necessary and was not taken; and
- d. an identification of each incident of deviation described in (a) and/or (b) where proper records were not maintained for the investigation and/or the corrective action.

These quarterly reports shall be submitted (i.e., postmarked) by January 31, April 30, July 31, and October 31 of each year; and each report shall cover the previous calendar quarter.

- 2. The permittee shall submit annual reports to the appropriate Ohio EPA District Office or local air agency, documenting any changes made to a parameter or value used in the dispersion model, that was used to demonstrate compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration. If no changes to the emissions unit(s) or the exhaust stack have been made, then the report shall include a statement to this effect. This report shall be postmarked or delivered no later than January 31 following the end of each calendar year.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

E. Testing Requirements

- 1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. The emission testing shall be conducted within 60 days after achieving the maximum production rate at which the emissions unit will be operated, but not later than 180 days after initial startup of such emissions unit.
 - b. The emission testing shall be conducted to demonstrate compliance with the VOC mass emission limitations for this emissions unit. Emission testing shall also be conducted to demonstrate compliance with the control efficiency limitation for VOCs from the scrubber(s) controlling this emissions unit and to

Issued: To be entered upon final issuance

verify the expected emissions for single and combined HAPs.

- c. The following test methods shall be employed to demonstrate compliance with the above emission limitations:
 - i. for VOC Methods 1-4 and 18, 25 or 25A of 40 CFR Part 60, Appendix A. Appropriate methods shall be used in conjunction with the test methods and procedures specified in Methods 18, 25, or 25A of 40 CFR Part 60, Appendix A for determining VOC mass emissions; and
 - ii. for HAPs, Methods 18 or 320 from 40 CFR Part 60, Appendix A.

Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA, NWDO. The test method(s) which must be employed to demonstrate compliance with the control efficiencies are specified below.

- d. The control efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in Methods 18, 25, or 25A of 40 CFR Part 60, Appendix A for VOC emissions . The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases."
- e. the test(s) shall be conducted while the emissions unit is operating at its maximum capacity (as stated in the application for this permit), unless otherwise specified or approved by the Ohio EPA, NWDO.
- f. During emission testing, the permittee shall also record the following information:
 - i. the pressure drop across the scrubber(s), in inches of water; and
 - ii. the scrubber(s) water flow rate, in gallons/minute.
- g. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, NWDO. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, NWDO's refusal to accept the results of the emission test(s).

Emissions Unit ID: P008

Personnel from the Ohio EPA, NWDO shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report of the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA, NWDO within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, NWDO.

2. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitations: 8.0 lbs VOC/hr, 35.04 tpy VOC

Applicable Compliance Method:

Compliance with the hourly allowable emission limitation above shall be demonstrated based on the results of emission testing conducted in accordance with Methods 1-4 and 18, 25 or 25A of 40 CFR Part 60, Appendix A.

The annual emission limitation was developed by multiplying the hourly emission limitation by the maximum operating schedule of 8760 hours/year, and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- b. Emission Limitation: The scrubber(s) shall meet a minimum control efficiency of 98.5% for VOC emissions.

Applicable Compliance Method:

Compliance with the control efficiency requirements above shall be demonstrated based on the results of emission testing conducted in accordance with the methods outlined in Section E.1 of this permit.

F. Miscellaneous Requirements

Issued: To be entered upon final issuance

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P009) - DDGS drying and cooling no. 1 (90 mmBtu/hr natural gas fired dryer)

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(A)(3)	<p>Nitrogen oxides (NOx) emissions from emissions units J001, P007, P009 and P010, combined, shall not exceed 12.96 pounds per hour (lbs/hr) and 56.76 tons per year (TPY).</p> <p>Carbon monoxide (CO) emissions from J001, P007, P009 and P010 shall not exceed 15.40 lbs/hr and 67.46 TPY.</p> <p>Particulate emissions equal to or less than 10 microns in size (PM10), from emissions units J001, P007, P009 and P010, combined, shall not exceed 6.80 lbs/hr and 29.78 TPY (See Section A.2.c).</p> <p>Volatile organic compound (VOC) emissions from emissions units J001, P007, P009 and P010, combined, shall not exceed 10.0 lbs/hr and 43.80 TPY.</p> <p>Sulfur dioxide (SO2) emissions from emissions unit J001, P007, P009 and P010, combined shall not exceed 15.0 lbs/hr and 65.70 TPY.</p> <p>Visible particulate emissions (PE) from the stack(s) serving this emissions unit shall not exceed 5% opacity as a six-minute average.</p> <p>See Section A.2.a.</p>
OAC rule 3745-21-09(DD)	See the requirements for emissions unit P801.
40 CFR Part 60, Subpart VV	See the requirements for emissions unit P801.
OAC rule 3745-17-07(A)	See Section A.2.d.

Issued: To be entered upon final issuance

OAC rule 3745-17-11(B)	See Section A.2.d.
OAC rule 3745-18-06(E)(2)	See Section A.2.d.
OAC rule 3745-21-08(B)	See Section A.2.e.
OAC rule 3745-114-01 ORC 3704.03(F)	See section C.2.

2. Additional Terms and Conditions

- 2.a** Best available technology (BAT) requirements for this emissions unit has been determined to be the use of the following:
- i. two (2) regenerative thermal oxidizers (RTO). The RTO shall meet a minimum control efficiency of 95% for both VOC and CO emissions;
 - ii. firing of only natural gas and the use of low NO_x burners in the RTO's; and
 - iii. the control systems (RTOs/multiclone) shall result in a PM₁₀ mass emission rate not to exceed 6.80 lbs/hr.
- 2.b** The annual allowable emission rate is based on the annual production of 110 million gallons of 200-proof ethanol (115.5 million gallons denatured ethanol). Since the facility annual production rate is equivalent to the maximum facility capacity, no operational restrictions, monitoring, record keeping or reporting requirements are necessary to ensure that this emissions unit does not exceed its annual allowable emission rates. The requirement to record the amount of ethanol produced is in the terms and conditions of emissions unit J001.
- 2.c** For the purposes of this permit, all PE is considered to be PM₁₀.
- 2.d** The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
- 2.e** The permittee has satisfied the "best available control techniques and operating practices" required pursuant to OAC rule 3745-21-08(B) by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05(A)(3) in this Permit to Install.

On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the State regulations. However,

Issued: To be entered upon final issuance

that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the requirement to satisfy the "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

B. Operational Restrictions

1. Any wetcake generated by a malfunction or process upset shall be removed from the facility within 48 hours.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to continuously monitor and record the combustion temperature within the thermal oxidizer(s) during operation of this emissions unit. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the combustion temperature within the thermal oxidizer(s) on a continuous basis.

Whenever the monitored value for the combustion temperature deviates from the value specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation: the date and time the deviation began and the magnitude of the deviation at that time, the date(s) the investigation was conducted, the names of the personnel who conducted the investigation, and the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable value specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken: a description of the corrective action, the date it was completed, the date and time the deviation ended, the total period of time (in minutes) during which there was a deviation, the combustion temperature within the thermal oxidizer(s) immediately after the corrective action, and the names of the personnel who performed the work. Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

The average combustion temperature within the thermal oxidizer(s), for any 3-hour

Emissions Unit ID: **P009**

block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.

This value is effective for the duration of this permit, unless revisions are requested by the permittee and approved in writing by the appropriate Ohio EPA District Office or local air agency.

2. The permit to install for these emissions unit(s) J001, B001-B004 and P007-P010, was evaluated based on the actual materials and the design parameters of the emissions unit's(s') exhaust system, as specified by the permittee in the permit application. The "Toxic Air Contaminant Statute", ORC 3704.03(F), was applied to this/these emissions unit(s) for each toxic air contaminant listed in OAC rule 3745-114-01, using data from the permit application; and modeling was performed for each toxic air contaminant(s) emitted at over one ton per year using an air dispersion model such as SCREEN 3.0, AERMOD, or ISCST3, or other Ohio EPA approved model. The predicted 1-hour maximum ground-level concentration result(s) from the approved air dispersion model, was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC), calculated as described in the Ohio EPA guidance document entitled "Review of New Sources of Air Toxic Emissions, Option A", as follows:
 - a. the exposure limit, expressed as a time-weighted average concentration for a conventional 8-hour workday and a 40-hour workweek, for each toxic compound(s) emitted from the emissions unit(s), (as determined from the raw materials processed and/or coatings or other materials applied) has been documented from one of the following sources and in the following order of preference (TLV was and shall be used, if the chemical is listed):
 - i. threshold limit value (TLV) from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices";
or
 - ii. STEL (short term exposure limit) or the ceiling value from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices"; the STEL or ceiling value is multiplied by 0.737 to convert the 15-minute exposure limit to an equivalent 8-hour TLV.

Emissions Unit ID: P009

- b. The TLV is divided by ten to adjust the standard from the working population to the general public (TLV/10).
- c. This standard is/was then adjusted to account for the duration of the exposure or the operating hours of the emissions unit(s), i.e., "X" hours per day and "Y" days per week, from that of 8 hours per day and 5 days per week. The resulting calculation was (and shall be) used to determine the Maximum Acceptable Ground-Level Concentration (MAGLC):

$$\text{TLV}/10 \times 8/X \times 5/Y = 4 \text{ TLV}/XY = \text{MAGLC}$$

- d. The following summarizes the results of dispersion modeling for the significant toxic contaminants (emitted at 1 or more tons/year) or "worst case" toxic contaminant(s):

Pollutant: AcetaldehydeTLV (mg/m³): 45.0

Maximum Hourly Emission Rate (lbs/hr): 2.11

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 28.38MAGLC (ug/m³): 1071.43**Pollutant:** HexaneTLV (mg/m³): 176.24

Maximum Hourly Emission Rate (lbs/hr): 1.09

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 0.81MAGLC (ug/m³): 4,196**Pollutant:** MethanolTLV (mg/m³): 262

Maximum Hourly Emission Rate (lbs/hr): 0.34

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 0.69MAGLC (ug/m³): 6238

The permittee, has demonstrated that emissions of acetaldehyde, hexane, methanol, from emissions unit(s) J001, B001-B004 and P007-P010, are calculated to be less than eighty per cent of the maximum acceptable ground level concentration (MAGLC); any new raw material or processing agent shall not be applied without evaluating each component toxic air contaminant in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F).

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

Issued: To be entered upon final issuance

3. Prior to making any physical changes to or changes in the method of operation of the emissions unit(s), that could impact the parameters or values that were used in the predicted 1-hour maximum ground-level concentration", the permittee shall re-model the change(s) to demonstrate that the MAGLC has not been exceeded. Changes that can affect the parameters/values used in determining the 1-hour maximum ground-level concentration include, but are not limited to, the following:
 - a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a new toxic air contaminant with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled;
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any toxic air contaminant listed in OAC rule 3745-114-01, that was modeled from the initial (or last) application; and
 - c. physical changes to the emissions unit(s) or its/their exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Toxic Air Contaminant Statute" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to a non-restrictive change to a parameter or process operation, where compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), has been documented. If the change(s) meet(s) the definition of a "modification" or if a new toxic is emitted, or the modeled toxic(s) is/are expected to exceed the previous modeled level(s), then the permittee shall apply for and obtain a final permit-to-install prior to the change. The Director may consider any significant departure from the operations of the emissions unit, described in the permit-to-install application, as a modification that results in greater emissions than the emissions rate modeled to determine the ground level concentration; and may require the permittee to submit a permit-to-install application for the increased emissions.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

4. The permittee shall collect, record, and retain the following information for each toxic evaluation conducted to determine compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F):
 - a. a description of the parameters/values used in each compliance demonstration

Emissions Unit ID: **P009**

and the parameters or values changed for any re-evaluation of the toxic(s) modeled (the composition of materials, new toxic contaminants emitted, change in stack/exhaust parameters, etc.);

- b. the Maximum Acceptable Ground-Level Concentration (MAGLC) for each significant toxic contaminant or worst-case contaminant, calculated in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F);
- c. a copy of the computer model run(s), that established the predicted 1-hour maximum ground-level concentration that demonstrated the emissions unit(s) to be in compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), initially and for each change that requires re-evaluation of the toxic air contaminant emissions; and
- d. the documentation of the initial evaluation of compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), and documentation of any determination that was conducted to re-evaluate compliance due to a change made to the emissions unit(s) or the materials applied.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

5. The permittee shall maintain a record of any change made to a parameter or value used in the dispersion model, used to demonstrate compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration. The record shall include the date and reason(s) for the change and if the change would increase the ground-level concentration.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

D. Reporting Requirements

1. The permittee shall submit quarterly reports that identify the following information concerning the operation of the control equipment (thermal oxidizer) during the operation of this emissions unit:
 - a. all 3-hour blocks of time during which the average combustion temperature within the thermal oxidizer, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent performance test that demonstrated the emissions unit was in

Issued: To be entered upon final issuance
compliance.

- b. an identification of each incident of deviation described in (a) where a prompt investigation was not conducted;
- c. an identification of each incident of deviation described in (a) where prompt corrective action, that would bring the combustion temperature into compliance with the acceptable range, was determined to be necessary and was not taken; and
- d. an identification of each incident of deviation described in (a) where proper records were not maintained for the investigation and/or the corrective action.

These quarterly reports shall be submitted (i.e., postmarked) by January 31, April 30, July 31, and October 31 of each year; and each report shall cover the previous calendar quarter.

- 2. The permittee shall submit annual reports to the appropriate Ohio EPA District Office or local air agency, documenting any changes made to a parameter or value used in the dispersion model, that was used to demonstrate compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration. If no changes to the emissions unit(s) or the exhaust stack have been made, then the report shall include a statement to this effect. This report shall be postmarked or delivered no later than January 31 following the end of each calendar year.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

E. Testing Requirements

- 1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. The emission testing shall be conducted within 60 days after achieving the maximum production rate at which the emissions unit will be operated, but not later than 180 days after initial startup of such emissions unit.
 - b. The emission testing shall be conducted to demonstrate compliance with the NO_x, CO, VOC, PM₁₀ and SO₂ mass emission limitations for this emissions unit. Emission testing shall also be conducted to verify the expected emissions

Emissions Unit ID: P009

for single and combined HAPs.

- c. The following test methods shall be employed to demonstrate compliance with the above emission limitations:
- i. for PM₁₀, Methods 201 and 202 of 40 CFR Part 51, Appendix M;
 - ii. for NO_x, Methods 1-4 and 7 of 40 CFR Part 60, Appendix A;
 - iii. for CO, Methods 1-4 and 10 of 40 CFR Part 60, Appendix A;
 - iv. for SO₂, Methods 1-4 and 6 of 40 CFR Part 60, Appendix A;
 - iv. for VOC, Methods 1-4 and 18, 25 or 25A of 40 CFR Part 60, Appendix A. Appropriate methods shall be used in conjunction with the test methods and procedures specified in Methods 18, 25, or 25A of 40 CFR Part 60, Appendix A for determining VOC mass emissions; and
 - v. for HAPs, Methods 18 or 320 from 40 CFR Part 60, Appendix A.

Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA, NWDO.

- d. The control efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in Methods 18, 25, or 25A of 40 CFR Part 60, Appendix A for VOC emissions . The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases."
- e. the test(s) shall be conducted while emissions units J001, P007, P009 and P010 are operating at their maximum capacities (as stated in the PTI application for this permit), unless otherwise specified or approved by the Ohio EPA, NWDO.
- f. During emission testing, the permittee shall also record the following information:
- i. the average combustion temperature within the thermal oxidizer(s), in degrees Fahrenheit.
- g. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, NWDO. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in

Issued: To be entered upon final issuance

the Ohio EPA, NWDO's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA, NWDO shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report of the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA, NWDO within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, NWDO.

2. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitations: 10.0 lbs VOC/hr, 43.80 tpy VOC (combined, for emissions unit J001, P007, P009 and P010)

Applicable Compliance Method:

Compliance with the hourly allowable emission limitation above shall be demonstrated based on the results of emission testing conducted in accordance with Methods 1-4 and 18, 25 or 25A of 40 CFR Part 60, Appendix A.

The annual emission limitation was developed by multiplying the hourly emission limitation by the maximum operating schedule of 8760 hours/year, and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- b. Emission Limitations: 12.96 lbs NOx/hr, 56.76 tpy NOx (combined, for emissions units J001, P007, P009, and P010)

Applicable Compliance Method:

Compliance with the hourly allowable emission limitation above shall be demonstrated based on the results of emission testing conducted in accordance with Methods 1-4 and 7 of 40 CFR Part 60, Appendix A.

Emissions Unit ID: P009

The annual emission limitation was developed by multiplying the hourly emission limitation by the maximum operating schedule of 8760 hours/year, and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- c. Emission Limitations: 15.40 lbs CO/hr, 67.46 tpy CO (combined, for emissions units J001, P007, P009 and P010)

Applicable Compliance Method:

Compliance with the hourly allowable emission limitation above shall be demonstrated based on the results of emission testing conducted in accordance with Methods 1-4 and 10 of 40 CFR Part 60, Appendix A.

The annual emission limitation was developed by multiplying the hourly emission limitation by the maximum operating schedule of 8760 hours/year, and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- d. Emission Limitations: 6.90 lb PM10, 30.22 tpy PM10 (combined, for emissions units J001, P007, P009, and P010)

Applicable Compliance Method:

Compliance with the hourly allowable emission limitation above shall be demonstrated based on the results of emission testing conducted in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M.

The annual emission limitation was developed by multiplying the hourly emission limitation by the maximum operating schedule of 8760 hours/year, and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- e. Emission Limitations: 15.0 lbs SO₂/hr, 65.70 tpy SO₂ (combined, for emissions units J001, P007, P009 and P010)

Applicable Compliance Method:

Compliance with the hourly allowable emission limitation above shall be demonstrated based on the results of emission testing conducted in accordance with Methods 1-4 and 6 of 40 CFR Part 60, Appendix A.

Issued: To be entered upon final issuance

The annual emission limitation was developed by multiplying the hourly emission limitation by the maximum operating schedule of 8760 hours/year, and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- f. Emission Limitations:
The RTO shall meet a minimum control efficiency of 95% for both VOC and CO emissions.

Applicable Compliance Method:

Compliance with the control efficiency requirements above shall be demonstrated based on the results of emission testing conducted in accordance with the methods outlined in Section E.1 of this permit. Compliance with the CO destruction efficiency shall be assumed as long as compliance with the hourly CO mass emission limitation is maintained. [Due to creation of CO in the RTO, it is not possible to perform testing to demonstrate compliance directly associated with the destruction of CO entering the RTO.]

- g. Emission Limitation: Visible PE from the stack(s) serving this emissions unit shall not exceed 5% opacity, as a six-minute average.

Appliance Compliance Method:

Compliance shall be determined according to test Method 9 of 40 CFR Part 60, Appendix A.

F. Miscellaneous Requirements

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P010) - DDGS drying and cooling no. 2 (90 mmBtu/hr natural gas fired dryer)

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(A)(3)	<p>Nitrogen oxides (NOx) emissions from emissions units J001, P007, P009 and P010, combined, shall not exceed 12.24 pounds per hour (lbs/hr) and 53.61 tons per year (TPY).</p> <p>Carbon monoxide (CO) emissions from J001, P007, P009 and P010 shall not exceed 15.40 lbs/hr and 67.46 TPY.</p> <p>Particulate emissions equal to or less than 10 microns in size (PM10), from emissions units J001, P007, P009 and P010, combined, shall not exceed 6.80 lbs/hr and 29.78 TPY (See Section A.2.c).</p> <p>Volatile organic compound (VOC) emissions from emissions units J001, P007, P009 and P010, combined, shall not exceed 10.0 lbs/hr and 43.80 TPY.</p> <p>Sulfur dioxide (SO2) emissions from emissions unit J001, P007, P009 and P010, combined shall not exceed 15.0 lbs/hr and 65.70 TPY.</p> <p>Visible particulate emissions (PE) from the stack(s) serving this emissions unit shall not exceed 5% opacity as a six-minute average.</p> <p>See Section A.2.a.</p>
OAC rule 3745-21-09(DD)	See the requirements for emissions unit P801.
40 CFR Part 60, Subpart VV	See the requirements for emissions unit P801.

OAC rule 3745-17-07(A)	See Section A.2.d.
OAC rule 3745-17-11(B)	See Section A.2.d.
OAC rule 3745-18-06(E)(2)	See Section A.2.d.
OAC rule 3745-21-08(B)	See Section A.2.e.
OAC rule 3745-114-01 ORC 3704.03(F)	See section C.2

2. Additional Terms and Conditions

- 2.a** Best available technology (BAT) requirements for this emissions unit has been determined to be the use of the following:
- i. two (2) regenerative thermal oxidizers (RTO). The RTOs shall meet a minimum control efficiency of 95% for bot VOC and CO emissions; and
 - ii. firing of only natural gas and the use of low NOx burners in the RTO's; and
 - iii. the control systems (RTOs/multiclone) shall result in a PM10 mass emission rate not to exceed 6.80 lbs/hr.
- 2.b** The annual allowable emission rate is based on the annual production of 110 million gallons of 200-proof ethanol (115.5 million gallons denatured ethanol). Since the facility annual production rate is equivalent to the maximum facility capacity, no operational restrictions, monitoring, record keeping or reporting requirements are necessary to ensure that this emissions unit does not exceed its annual allowable emission rates. The requirement to record the amount of denatured ethanol produced is in the terms and conditions of emissions unit J001.
- 2.c** For the purposes of this permit, all PE is considered to be PM10.
- 2.d** The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
- 2.e** The permittee has satisfied the "best available control techniques and operating practices" required pursuant to OAC rule 3745-21-08(B) by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05(A)(3) in this Permit to Install.

On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph

Issued: To be entered upon final issuance

(B); therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the requirement to satisfy the "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

B. Operational Restrictions

1. Any wetcake generated by a malfunction or process upset shall be removed from the facility within 48 hours.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to continuously monitor and record the combustion temperature within the thermal oxidizer(s) during operation of this emissions unit. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the combustion temperature within the thermal oxidizer(s) on a continuous basis.

Whenever the monitored value for the combustion temperature deviates from the value specified below, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation: the date and time the deviation began and the magnitude of the deviation at that time, the date(s) the investigation was conducted, the names of the personnel who conducted the investigation, and the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable value specified below, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken: a description of the corrective action, the date it was completed, the date and time the deviation ended, the total period of time (in minutes) during which there was a deviation, the combustion temperature within the thermal oxidizer(s) immediately after the corrective action, and the names of the personnel who performed the work. Investigation and records required by this paragraph does not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.

Emissions Unit ID: P010

The average combustion temperature within the thermal oxidizer(s), for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.

This value is effective for the duration of this permit, unless revisions are requested by the permittee and approved in writing by the appropriate Ohio EPA District Office or local air agency.

2. The permit to install for these emissions unit(s) J001, B001-B004 and P007-P010, was evaluated based on the actual materials and the design parameters of the emissions unit's(s') exhaust system, as specified by the permittee in the permit application. The "Toxic Air Contaminant Statute", ORC 3704.03(F), was applied to this/these emissions unit(s) for each toxic air contaminant listed in OAC rule 3745-114-01, using data from the permit application; and modeling was performed for each toxic air contaminant(s) emitted at over one ton per year using an air dispersion model such as SCREEN 3.0, AERMOD, or ISCST3, or other Ohio EPA approved model. The predicted 1-hour maximum ground-level concentration result(s) from the approved air dispersion model, was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC), calculated as described in the Ohio EPA guidance document entitled "Review of New Sources of Air Toxic Emissions, Option A", as follows:
 - a. the exposure limit, expressed as a time-weighted average concentration for a conventional 8-hour workday and a 40-hour workweek, for each toxic compound(s) emitted from the emissions unit(s), (as determined from the raw materials processed and/or coatings or other materials applied) has been documented from one of the following sources and in the following order of preference (TLV was and shall be used, if the chemical is listed):
 - i. threshold limit value (TLV) from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices";
or
 - ii. STEL (short term exposure limit) or the ceiling value from the American Conference of Governmental Industrial Hygienists' (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices"; the STEL or ceiling value is multiplied by 0.737 to convert the 15-minute exposure limit to an equivalent 8-hour TLV.

Issued: To be entered upon final issuance

- b. The TLV is divided by ten to adjust the standard from the working population to the general public (TLV/10).
- c. This standard is/was then adjusted to account for the duration of the exposure or the operating hours of the emissions unit(s), i.e., "X" hours per day and "Y" days per week, from that of 8 hours per day and 5 days per week. The resulting calculation was (and shall be) used to determine the Maximum Acceptable Ground-Level Concentration (MAGLC):

$$\text{TLV}/10 \times 8/\text{X} \times 5/\text{Y} = 4 \text{ TLV}/\text{XY} = \text{MAGLC}$$

- d. The following summarizes the results of dispersion modeling for the significant toxic contaminants (emitted at 1 or more tons/year) or "worst case" toxic contaminant(s):

Pollutant: AcetaldehydeTLV (mg/m³): 45.0

Maximum Hourly Emission Rate (lbs/hr): 2.11

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 28.38MAGLC (ug/m³): 1071.43**Pollutant:** HexaneTLV (mg/m³): 176.24

Maximum Hourly Emission Rate (lbs/hr): 1.09

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 0.81MAGLC (ug/m³): 4,196**Pollutant:** MethanolTLV (mg/m³): 262

Maximum Hourly Emission Rate (lbs/hr): 0.34

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 0.69MAGLC (ug/m³): 6238

The permittee, has demonstrated that emissions of acetaldehyde, hexane, methanol, from emissions unit(s) J001, B001-B004 and P007-P010, are calculated to be less than eighty per cent of the maximum acceptable ground level concentration (MAGLC); any new raw material or processing agent shall not be applied without evaluating each component toxic air contaminant in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F).

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering

Emissions Unit ID: P010

Guide #70

3. Prior to making any physical changes to or changes in the method of operation of the emissions unit(s), that could impact the parameters or values that were used in the predicted 1-hour maximum ground-level concentration", the permittee shall re-model the change(s) to demonstrate that the MAGLC has not been exceeded. Changes that can affect the parameters/values used in determining the 1-hour maximum ground-level concentration include, but are not limited to, the following:
 - a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a new toxic air contaminant with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled;
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any toxic air contaminant listed in OAC rule 3745-114-01, that was modeled from the initial (or last) application; and
 - c. physical changes to the emissions unit(s) or its/their exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Toxic Air Contaminant Statute" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to a non-restrictive change to a parameter or process operation, where compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), has been documented. If the change(s) meet(s) the definition of a "modification" or if a new toxic is emitted, or the modeled toxic(s) is/are expected to exceed the previous modeled level(s), then the permittee shall apply for and obtain a final permit-to-install prior to the change. The Director may consider any significant departure from the operations of the emissions unit, described in the permit-to-install application, as a modification that results in greater emissions than the emissions rate modeled to determine the ground level concentration; and may require the permittee to submit a permit-to-install application for the increased emissions.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

4. The permittee shall collect, record, and retain the following information for each toxic evaluation conducted to determine compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F):

Issued: To be entered upon final issuance

- a. a description of the parameters/values used in each compliance demonstration and the parameters or values changed for any re-evaluation of the toxic(s) modeled (the composition of materials, new toxic contaminants emitted, change in stack/exhaust parameters, etc.);
- b. the Maximum Acceptable Ground-Level Concentration (MAGLC) for each significant toxic contaminant or worst-case contaminant, calculated in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F);
- c. a copy of the computer model run(s), that established the predicted 1-hour maximum ground-level concentration that demonstrated the emissions unit(s) to be in compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), initially and for each change that requires re-evaluation of the toxic air contaminant emissions; and
- d. the documentation of the initial evaluation of compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), and documentation of any determination that was conducted to re-evaluate compliance due to a change made to the emissions unit(s) or the materials applied.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

5. The permittee shall maintain a record of any change made to a parameter or value used in the dispersion model, used to demonstrate compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration. The record shall include the date and reason(s) for the change and if the change would increase the ground-level concentration.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

D. Reporting Requirements

1. The permittee shall submit quarterly reports that identify the following information concerning the operation of the control equipment (thermal oxidizer(s)) during the operation of this emissions unit:
 - a. all 3-hour blocks of time during which the average combustion temperature within the thermal oxidizer(s), when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the

Emissions Unit ID: **P010**

most recent performance test that demonstrated the emissions unit was in compliance.

- b. an identification of each incident of deviation described in (a) where a prompt investigation was not conducted;
- c. an identification of each incident of deviation described in (a) where prompt corrective action, that would bring the combustion temperature into compliance with the acceptable range, was determined to be necessary and was not taken; and
- d. an identification of each incident of deviation described in (a) where proper records were not maintained for the investigation and/or the corrective action.

These quarterly reports shall be submitted (i.e., postmarked) by January 31, April 30, July 31, and October 31 of each year; and each report shall cover the previous calendar quarter.

2. The permittee shall submit annual reports to the appropriate Ohio EPA District Office or local air agency, documenting any changes made to a parameter or value used in the dispersion model, that was used to demonstrate compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration. If no changes to the emissions unit(s) or the exhaust stack have been made, then the report shall include a statement to this effect. This report shall be postmarked or delivered no later than January 31 following the end of each calendar year.

[ORC 3704.03(F)(3)(c) and F(4)], [OAC rule 3745-114-01], Option A, Engineering Guide #70

Issued: To be entered upon final issuance**E. Testing Requirements**

1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. The emission testing shall be conducted within 60 days after achieving the maximum production rate at which the emissions unit will be operated, but not later than 180 days after initial startup of such emissions unit.
 - b. The emission testing shall be conducted to demonstrate compliance with the NO_x, CO, VOC, PM₁₀ and SO₂ mass emission limitations for this emissions unit. Emission testing shall also be conducted to verify the expected emissions for single and combined HAPs.
 - c. The following test methods shall be employed to demonstrate compliance with the above emission limitations:
 - i. for PM₁₀, Methods 201 and 202 of 40 CFR Part 51, Appendix M;
 - ii. for NO_x, Methods 1-4 and 7 of 40 CFR Part 60, Appendix A;
 - iii. for CO, Methods 1-4 and 10 of 40 CFR Part 60, Appendix A;
 - iv. for SO₂, Methods 1-4 and 6 of 40 CFR Part 60, Appendix A;
 - iv. for VOC, Methods 1-4 and 18, 25 or 25A of 40 CFR Part 60, Appendix A. Appropriate methods shall be used in conjunction with the test methods and procedures specified in Methods 18, 25, or 25A of 40 CFR Part 60, Appendix A for determining VOC mass emissions; and
 - v. for HAPs, Methods 18 or 320 from 40 CFR Part 60, Appendix A.

Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA, NWDO.

- d. The control efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in Methods 18, 25, or 25A of 40 CFR Part 60, Appendix A for VOC emissions . The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases."
- e. the test(s) shall be conducted while emissions units J001, P007, P009 and P010 are operating at their maximum capacities (as stated in the PTI application for this permit), unless otherwise specified or approved by the Ohio EPA, NWDO.

Emissions Unit ID: P010

- f. During emission testing, the permittee shall also record the following information:
- i. the average combustion temperature within the thermal oxidizer(s), in degrees Fahrenheit.
- g. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, NWDO. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, NWDO's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA, NWDO shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report of the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA, NWDO within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, NWDO.

2. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:
- a. Emission Limitations: 10.0 lbs VOC/hr, 43.80 tpy VOC (combined, for emissions unit J001, P007, P009 and P010)

Applicable Compliance Method:

Compliance with the hourly allowable emission limitation above shall be demonstrated based on the results of emission testing conducted in accordance with Methods 1-4 and 18, 25 or 25A of 40 CFR Part 60, Appendix A.

The annual emission limitation was developed by multiplying the hourly emission limitation by the maximum operating schedule of 8760 hours/year, and then

Issued: To be entered upon final issuance

dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- b. Emission Limitations: 12.96 lbs NO_x/hr, 56.76 tpy NO_x (combined, for emissions units J001, P007, P009, and P010)

Applicable Compliance Method:

Compliance with the hourly allowable emission limitation above shall be demonstrated based on the results of emission testing conducted in accordance with Methods 1-4 and 7 of 40 CFR Part 60, Appendix A.

The annual emission limitation was developed by multiplying the hourly emission limitation by the maximum operating schedule of 8760 hours/year, and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- c. Emission Limitations: 15.40 lbs CO/hr, 67.46 tpy CO (combined, for emissions units J001, P007, P009 and P010)

Applicable Compliance Method:

Compliance with the hourly allowable emission limitation above shall be demonstrated based on the results of emission testing conducted in accordance with Methods 1-4 and 10 of 40 CFR Part 60, Appendix A.

The annual emission limitation was developed by multiplying the hourly emission limitation by the maximum operating schedule of 8760 hours/year, and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- d. Emission Limitations: 6.90 lb PM₁₀, 30.22 tpy PM₁₀ (combined, for emissions units J001, P007, P009, and P010)

Applicable Compliance Method:

Compliance with the hourly allowable emission limitation above shall be demonstrated based on the results of emission testing conducted in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M.

Emissions Unit ID: **P010**

The annual emission limitation was developed by multiplying the hourly emission limitation by the maximum operating schedule of 8760 hours/year, and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- e. Emission Limitations: 15.0 lbs SO₂/hr, 65.70 tpy SO₂ (combined, for emissions units J001, P007, P009 and P010)

Applicable Compliance Method:

Compliance with the hourly allowable emission limitation above shall be demonstrated based on the results of emission testing conducted in accordance with Methods 1-4 and 6 of 40 CFR Part 60, Appendix A.

The annual emission limitation was developed by multiplying the hourly emission limitation by the maximum operating schedule of 8760 hours/year, and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

- f. Emission Limitations:
The RTO shall meet a minimum control efficiency of 95% for both VOC and CO emissions.

Applicable Compliance Method:

Compliance with the control efficiency requirements above shall be demonstrated based on the results of emission testing conducted in accordance with the methods outlined in Section E.1 of this permit. Compliance with the CO destruction efficiency shall be assumed as long as compliance with the hourly CO mass emission limitation is maintained. [Due to creation of CO in the RTO, it is not possible to perform testing to demonstrate compliance directly associated with the destruction of CO entering the RTO.]

- g. Emission Limitation: Visible PE from the stack(s) serving this emissions unit shall not exceed 5% opacity, as a six-minute average.

Appliance Compliance Method:

Compliance shall be determined according to test Method 9 of 40 CFR Part 60, Appendix A.

F. Miscellaneous Requirements

Issued: To be entered upon final issuance

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P011) - Cooling tower

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-02(A)	Particulate emissions equal to or less than 10 microns in size (PM10) shall not exceed 0.38 pounds/hour (lbs/hr) and 1.66 tons per year (TPY). Visible particulate emissions (PE) shall not exceed 10% opacity, as a six-minute average. See Section A.2.c.
OAC rule 3745-17-07(A)	See Section A.2.b.
OAC rule 3745-17-11(B)	See Section A.2.b.

2. Additional Terms and Conditions

- 2.a The permit to install for this air contaminant source takes into account a drift loss factor of 0.001% as a voluntary restriction as proposed by the permittee for the purpose of avoiding Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3).
- 2.b The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-02(A).
- 2.c For the purposes of this permit, all PE is considered to be PM10.

B. Operational Restrictions

1. The permittee shall maintain the total dissolved solids (TDS) content of the circulating cooling water at 2,500 mg/L or less.

Emissions Unit ID: P011

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to continuously monitor and continuously record the conductivity of the cooling tower water. The monitoring devices shall be installed, calibrated, operated, and maintained in accordance with the manufacturers' recommendations, instructions, and operating manuals.
2. The conductivity shall be used to determine the TDS content of the cooling tower water based on an established correlation between TDS and conductivity of the cooling water.

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify any exceedances of the TDS content requirement. These reports shall be submitted within 30 days after the deviation occurs.

E. Testing Requirements

1. Compliance with the emission limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emission Limitations: PM10 shall not exceed 0.38 lbs/hr and 1.66 TPY.

Applicable Compliance Methods:

The hourly allowable emission limitation was developed by multiplying the drift loss factor supplied by the permittee of 0.001 percent drift, by the maximum circulating water flow rate of 1.8 million gallons per hour, by the maximum average total dissolved solids content of the cooling water of 2500 mg/L and applying the conversion factors: 3.79 liter/gallon (L/gal), 60 minutes/hour (min/hr) and 2.2E-06 lb/milligram (lb/mg).

If required, the permittee shall submit a testing proposal to demonstrate that the maximum drift loss does not exceed 0.001 percent.

The annual emission limitation was developed by multiplying the hourly emission limitation by the maximum operating schedule of 8760 hours/year, and then dividing by 2000 lbs/ton. Therefore, if compliance is shown with the hourly limitation, compliance with the annual limitation shall be assumed.

Emissions Unit ID: **P011**

Issued: To be entered upon final issuance

- b. Emission Limitation: Visible particulate emissions shall not exceed 0% opacity as a six-minute average.

Issued: To be entered upon final issuance

Applicable Compliance Method:

Compliance with the visible emission limitation shall be demonstrated in accordance with Test Method 9 of 40 CFR Part 60, Appendix A.

F. Miscellaneous Requirements

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P012) - 3740 Hp emergency generator

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(C)	<p>Carbon monoxide (CO) emissions shall not exceed 70.02 pounds per hour (lbs/hr) and 1.75 tons per rolling, 12-month period.</p> <p>Nitrogen oxides (NOx) emissions shall not exceed 56.84 lbs/hr and 1.42 tons per rolling, 12-month period.</p> <p>Sulfur dioxide (SO₂) emissions shall not exceed 13.60 lbs/hr and 0.34 ton per rolling 12-month period.</p> <p>Particulate matter emissions (PE) shall not exceed 1.70 lbs/hr and 0.04 ton per rolling 12-month period.</p> <p>Volatile organic compound (VOC) emissions shall not exceed 2.64 lbs/hr and 0.07 ton per rolling, 12-month period.</p> <p>See Sections A.2.a, A.2.b and B.2.</p>
OAC rule 3745-17-07(A)	Visible PE shall not exceed 20% opacity, as a six-minute average, except as provided by rule.
OAC rule 3745-18-06(G)	0.50 lbs of SO ₂ per million british thermal units (mmBtu) of actual heat input.
OAC rule 3745-17-11(B)(5)(b)	0.062 lbs of PE per mmBtu of actual heat input.
OAC rule 3745-21-08(B)	See Section A.2.c.
40 CFR Part 60 Subpart IIII	See A.2.d.

2. Additional Terms and Conditions

- 2.a The Best Available Technology (BAT) requirements under OAC rule

Emissions Unit ID: P012

3745-31-05(A)(3) do not apply to the PM10 emissions from this air contaminant source since the calculated annual emission rates for PM10 is less than ten tons per year taking into account the federally enforceable restriction on the hours of operation under OAC rule 3745-31-05(C).

The annual emission rate for this emissions unit is 0.04 TPY of PM10; determined by multiplying the USEPA, AP-42 emission factor (Table 3.4-2) of 0.0573 lb/mmBtu of fuel input by the maximum fuel input of 27.20 mmBtu/hr, the maximum operating schedule of 50 hours per year and the dividing by 2000 lbs/ton.

2.b This permit establishes the following federally enforceable emission limitations based on an hours of operation restriction (See B.2) for purposes of avoiding Title V applicability:

- i. 1.75 ton CO per rolling, 12-month period;
- ii. 1.42 tons NOx per rolling, 12-month period;
- iii. 0.34 ton SO2 per rolling, 12-month period;
- iv. 0.04 ton PM per rolling, 12-month period; and
- v. 0.07 ton VOC per rolling, 12-month period.

2.c The permittee has satisfied the "best available control techniques and operating practices" required pursuant to OAC rule 3745-21-08(B) by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05(A)(3) in this Permit to Install.

On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the requirement to satisfy the "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

2.d This emissions unit is subject to 40 CFR Part 60, Subpart IIII, Standards of Performance for Stationary Compression Ignition Internal Combustion. The permittee shall comply with all applicable requirements of 40 CFR Part 60, Subpart IIII. The permittee shall also comply with all applicable requirements of 40 CFR Part 60, Subpart A. (General Provisions) as identified in Table 8 of 40 CFR Part 60, Subpart IIII.

Issued: To be entered upon final issuance**B. Operational Restrictions**

1. The permittee shall combust only diesel fuel that meets the per gallon standards of 40 CFR 80.510.
2. The maximum annual hours of operation for this emissions unit shall not exceed 50 hours per year, based upon a rolling 12-month summation of the operating hours. To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed the levels specified in the following table:

<u>Month(s)</u>	<u>Maximum Allowable Hours of Operation</u>
1	50
1-2	50
1-3	50
1-4	50
1-5	50
1-6	50
1-12	50

After the first 12 calendar months of operation following the issuance of this permit, compliance with the annual hours of operation limitation shall be based upon a rolling, 12-month summation of the operating hours.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain monthly records of the following information for this emissions unit:
 - a. the hours of operation;
 - b. the calculated monthly emission rate for CO using the following equation: CO emissions in tons = (hours of operation) x (potential hourly CO emissions) x (1 ton/2000 lbs) = (C.1.a) x (70.02 lbs CO) x (1/2000 lbs);
 - c. the calculated monthly emission rate for NOx using the following equation: NOx emissions (in tons) = (hours of operation) x (potential hourly NOx emissions) x (1

Emissions Unit ID: P012

ton/2000 lbs) = (C.1.a) x (56.84 lbs NOx) x (1/2000 lbs);

- d. the calculated monthly emission rate of SO₂ using the following equation: SO₂ emissions (in tons) = (hours of operation) x (potential hourly SO₂ emissions) x (1 ton/2000 lbs) = (C.1.a) x (13.60 lbs SO₂) x (1/2000 lbs);
 - e. the calculated monthly emission rate of PE using the following equation: PE emissions (in tons) = (hours of operation) x (potential hourly PE emissions) x (1 ton/2000 lbs) = (C.1.a) x (1.70 lbs PE) x (1/2000 lbs);
 - f. the calculated monthly emission rate of VOC using the following equation: VOC emissions (in tons) = (hours of operation) x (potential hourly VOC emissions) x (1 ton/2000 lbs) = (C.1.a) x (2.64 lbs VOC) x (1/2000 lbs);
 - g. for the first 12 months of operation following the issuance of this permit, the cumulative year-to-date total hours of operation.
 - h. beginning the first month, after the first 12 months of operation following the issuance of this permit, the following summations:
 - i. the rolling, 12-month CO emission rate, in tons;
 - ii. the rolling, 12-month NO_x emission rate, in tons;
 - iii. the rolling, 12-month SO₂ emission rate, in tons;
 - iv. the rolling, 12-month PE emission rate, in tons;
 - v. the rolling, 12-month VOC emission rate, in tons; and
 - vi. the rolling, 12-month hours of operation.
2. For each day during which the permittee burns a fuel other than diesel fuel the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit. The permittee shall also maintain documentation on the sulfur content of all fuels received.
 3. The permittee shall use records of fuel supplier certification to demonstrate compliance with the operational restriction in Section B.1. Records of fuel supplier certification shall include the following information:
 - a. the name of the oil supplier; and
 - b. a statement from the oil supplier that the oil complies with the specifications under the definition of distillate oil in B.1 above.

Issued: To be entered upon final issuance

D. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports which identify the following:
 - a. All exceedances of the rolling, 12-month restriction of 50 hours.
 - b. All exceedances of the rolling, 12-month CO emission limitation of 1.75 tons.
 - c. All exceedances of the rolling, 12-month NOx emission limitation of 1.42 tons.
 - d. All exceedances of the rolling, 12-month SO2 emission limitation of 0.76 tons.
 - e. All exceedances of the rolling, 12-month PE emission limitation of 0.04 tons.
 - f. All exceedances of the rolling, 12-month VOC emission limitation of 0.07 tons.
 - g. For the first 12 calendar months of operation following the issuance of this permit, all exceedances of the maximum allowable cumulative hours of operation specified in Section B.2.
 - h. All exceedances of the sulfur content fuel restriction specified in condition B.1.

These quarterly deviation (excursion) reports shall be submitted in accordance with the General Terms and Conditions of this permit.

2. The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than distillate fuel oil was burned in this emissions unit. Each report shall be submitted within 30 days after the deviation occurs.

E. Testing Requirements

1. Compliance with the emission limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emissions Limitation: 70.02 lbs CO/hr

Applicable Compliance Method:

The hourly allowable CO emission limitation was developed by multiplying the emission standard of 8.5 g/Hp-hr (40 CFR Part 60 Subpart IIII, Table 1) by the

Issued: To be entered upon final issuance

maximum power output of 3740 Hp and the conversion factor lb/454 gram.

If required, compliance with the hourly allowable CO emission limitation shall be determined according to test Methods 1-4, and 10, as set forth in the "Appendix on Test Methods" in 40 CFR Part 60 "Standards of Performance for New Stationary Sources."

- b. Emissions Limitation: 56.84 lbs NO_x/hr

Applicable Compliance Method:

The hourly allowable NO_x emission limitation was developed by multiplying the emission standard of 6.9 g/Hp-hr (40 CFR Part 60 Subpart IIII, Table 1) by the maximum power output of 3740 Hp and the conversion factor lb/454 gram.

If required, compliance with the hourly allowable NO_x emission limitation shall be determined according to test Methods 1-4, and 7, as set forth in the "Appendix on Test Methods" in 40 CFR Part 60 "Standards of Performance for New Stationary Sources."

- c. Emissions Limitation: 13.60 lbs SO₂/hr

Applicable Compliance Method:

The hourly allowable SO₂ emission limitation was developed by multiplying the emission standard of 0.50 lb/mmBtu of actual heat input by the maximum heat input rate of 27.20 mmBtu/hr.

If required, compliance with the hourly emission limitation shall be determined according to test Methods 1-4 and 6 as set forth in the "Appendix on Test Methods" in 40 CFR Part 60 "Standards of Performance for New Stationary Sources."

- d. Emissions Limitation: 1.70 lbs PE/hr

Applicable Compliance Method:

The hourly allowable PE limitation was developed by multiplying the emission standard of 0.062 lb/mmBtu of actual heat input by the maximum heat input rate of 27.20 mmBtu/hr.

Emissions Unit ID: P012

If required, compliance with the hourly allowable emission limitation shall be determined according to test Methods 1-5 as set forth in the "Appendix on Test Methods" in 40 CFR Part 60 "Standards of Performance for New Stationary Sources."

- e. Emissions Limitation: 2.64 lbs VOC/hr

Applicable Compliance Method:

The hourly allowable VOC emission limitation was developed by multiplying the USEPA, AP-42 emission factor, Table 3.4-1 (revised 10/96) of 0.000705 lbs/hp-hr by the maximum power output of 3740 hp.

If required, compliance with the hourly allowable emission limitation shall be determined according to test Methods 1-4, and 25 or 25A as set forth in the "Appendix on Test Methods" in 40 CFR Part 60 "Standards of Performance for New Stationary Sources."

- f. Emissions Limitation: 0.50 lbs SO₂ per mmBtu of actual heat input

Applicable Compliance Method:

Compliance with the allowable emission limitation shall be demonstrated in accordance with OAC rule 3745-18-06(A).

- g. Emissions Limitation: 0.062 lbs PE per mmBtu of actual heat input

Issued: To be entered upon final issuance

Applicable Compliance Method:

Compliance with the allowable emission limitation shall be demonstrated in accordance with OAC rule 3745-17-11(B)(10).

- h. Emissions Limitations:
 - 1.75 ton CO per rolling, 12-month period
 - 1.42 tons NOx per rolling, 12-month period
 - 0.34 ton SO2 per rolling, 12-month period
 - 0.04 ton PE per rolling, 12-month period
 - 0.07 ton VOC per rolling, 12-month period

Applicable Compliance Method:

Compliance with the ton per rolling 12-month period emission limitations above shall be demonstrated by the record keeping requirements established in Section C.1 of this permit.

- i. Emissions Limitation Visible PE from the stack(s) serving this emissions unit shall not exceed 20% opacity, as a 6-minute average.

Applicable Compliance Method:

Compliance shall be demonstrated in accordance with OAC rule 3745-17-03(B)(1).

F. Miscellaneous Requirements

1. The following terms and conditions are federally enforceable: A.1, B.2, C.1, D.1, E.1.a, E.1.b, E.1.c, E.1.d and E.1.f.
2. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P013) - emergency water pump (powered by a 290 Hp generator)

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(C)	<p>The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(C) and OAC rule 3745-17-11(B)(5)(b).</p> <p>Nitrogen oxides (NOx) emissions shall not exceed 4.99 lbs/hr and 0.50 ton per rolling, 12-month period.</p> <p>Carbon monoxide (CO) emissions shall not exceed 1.66 pounds per hour (lbs/hr) and 0.17 ton per rolling, 12-month period.</p> <p>Volatile organic compound (VOC) emissions shall not exceed 0.72 lb/hr and 0.07 ton per rolling, 12-month period.</p> <p>Sulfur dioxide (SO₂) emissions shall not exceed 0.59 lb/hr and 0.06 ton per rolling, 12-month period.</p> <p>Particulate matter emissions equal to or less than 10 microns in size (PM₁₀) shall not exceed 0.26 lb/hr and 0.03 tons per rolling, 12-month period.</p> <p>See Sections A.2.a, A.2.b and B.2.</p>
OAC rule 3745-17-07(A)	Visible particulate emissions (PE) shall not exceed 20% opacity, as a six-minute average, except as provided by rule.
OAC rule 3745-17-11(B)(5)(a)	0.310 pound of particulate emissions (PE) per million BTU of actual heat input.
OAC rule 3745-21-08(B)	See Section A.2.d.
OAC rule 3745-18-06	See Section A.2.e.

40 CFR Part 60 Subpart IIII	See Section A.2.f.
-----------------------------	--------------------

2. Additional Terms and Conditions

- 2.a** The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the sulfur dioxide (SO₂) and particulate matter of 10 microns or less (PM₁₀) emissions from this air contaminant source since the calculated annual emission rate for SO₂ and PM₁₀ emissions are less than ten tons per year taking into account the federally enforceable restriction on the hours of operation under OAC rule 3745-31-05(C).

The annual emission rate for this emissions unit is 0.06 TPY of SO₂; determined by multiplying the USEPA, AP-42 emission factor (Table 3.3-1, revised 10/06) of 0.002 pounds per horsepower-hour (lb/Hp-hr) by the maximum power input of 290 Hp, the maximum operating schedule of 100 hours per year and applying the conversion factor 2000 lbs/ton.

The annual emission rate for this emissions unit is 0.07 TPY of PM₁₀; determined by multiplying the allowable emission rate of 0.310 lbs/mmBtu [OAC rule 3745-17-11(B)(5)(a)] by the maximum fuel input rate of 2.11 mmBtu/hr, the maximum operating schedule of 200 hours per year and then dividing by 2000 lbs/ton.

- 2.b** This permit establishes the following federally enforceable emission limitations based on an hours of operation restriction (See Section B.2) for purposes of avoiding PSD applicability:
- i. 0.50 tons NO_x per rolling, 12-month period;
 - ii. 0.17 ton CO per rolling, 12-month period; and
 - iii. 0.07 ton VOC per rolling, 12-month period.
- 2.c** This emissions unit is exempt from the requirements of OAC rule 3745-18-06, pursuant to OAC rule 3745-18-06(B).
- 2.d** The permittee has satisfied the "best available control techniques and operating practices" required pursuant to OAC rule 3745-21-08(B) by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05(A)(3) in this Permit to Install.

On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the State regulations. However,

Issued: To be entered upon final issuance

that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the requirement to satisfy the "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

- 2.e** This emissions unit is exempt from the requirements of OAC rule 3745-18-06 in accordance with OAC rule 3745-18-06(B).
- 2.f** This emissions unit is subject to 40 CFR Part 60, Subpart IIII, Standards of Performance for Stationary Compression Ignition Internal Combustion. The permittee shall comply with all applicable requirements of 40 CFR Part 60, Subpart IIII. The permittee shall also comply with all applicable requirements of 40 CFR Part 60, Subpart A. (General Provisions) as identified in Table 8 of 40 CFR Part 60, Subpart IIII.

B. Operational Restrictions

1. The permittee shall combust only diesel fuel that meets the per gallon standards of 40 CFR 80.510.
2. The maximum annual hours of operation for this emissions unit shall not exceed 200 hours per year, based upon a rolling 12-month summation of the operating hours. To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed the levels specified in the following table:

<u>Month(s)</u>	<u>Maximum Allowable Hours of Operation</u>
1	20
1-2	40
1-3	60
1-4	80
1-5	100
1-6	120
1-12	200

After the first 12 calendar months of operation following the issuance of this permit,

Emissions Unit ID: P013

compliance with the annual hours of operation limitation shall be based upon a rolling, 12-month summation of the operating hours.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain monthly records of the following information for this emissions unit:
 - a. the hours of operation;
 - b. the calculated monthly emission rate for CO using the following equation: CO emissions in tons = (hours of operation) x (potential hourly CO emissions) x (1 ton/2000 lbs) = (C.1.a) x (1.66 lbs CO) x (1/2000 lbs);
 - c. the calculated monthly emission rate for NOx using the following equation: NOx emissions (in tons) = (hours of operation) x (potential hourly NOx emissions) x (1 ton/2000 lbs) = (C.1.a) x (4.99 lbs NOx) x (1/2000 lbs);
 - d. the calculated monthly emission rate of VOC using the following equation: VOC emissions (in tons) = (hours of operation) x (potential hourly VOC emissions) x (1 ton/2000 lbs) = (C.1.a) x (0.72 lbs VOC) x (1/2000 lbs);
 - e. for the first 12 months of operation following the issuance of this permit, the cumulative year-to-date total hours of operation.
 - f. beginning the first month, after the first 12 months of operation following the issuance of this permit, the following summations:
 - i. the rolling, 12-month CO emission rate, in tons;
 - ii. the rolling, 12-month NOx emission rate, in tons;
 - iii. the rolling, 12-month VOC emission rate, in tons; and
 - iv. the rolling, 12-month hours of operation.
2. For each day during which the permittee burns a fuel other than diesel fuel the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit. The permittee shall also maintain documentation on the sulfur content of all fuels received.
3. The permittee shall use records of fuel supplier certification to demonstrate compliance with the operational restriction in Section B.1. Records of fuel supplier certification shall include the following information:

Issued: To be entered upon final issuance

- a. the name of the oil supplier; and
- b. a statement from the oil supplier that the oil complies with the specifications under the definition of distillate oil in B.1 above.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports which identify the following:
 - a. All exceedances of the rolling, 12-month restriction of 200 hours.
 - b. All exceedances of the rolling, 12-month CO emission limitation of 0.17 tons.
 - c. All exceedances of the rolling, 12-month NOx emission limitation of 0.50 tons.
 - d. All exceedances of the rolling, 12-month VOC emission limitation of 0.07 tons.
 - e. For the first 12 calendar months of operation following the issuance of this permit, all exceedances of the maximum allowable cumulative hours of operation specified in Section B.2.
 - f. All exceedances of the sulfur content fuel restriction specified in condition B.1.

These quarterly deviation (excursion) reports shall be submitted in accordance with the General Terms and Conditions of this permit.

2. The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than distillate fuel oil was burned in this emissions unit. Each report shall be submitted within 30 days after the deviation occurs.

E. Testing Requirements

1. Compliance with the emission limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emissions Limitation: 1.66 lbs CO/hr
Applicable Compliance Method:

Emissions Unit ID: **P013**

The hourly allowable emission limitation was developed by multiplying an emission factor of 0.00573 lb/hp-hr (40 CFR Part 60, Subpart IIII, Table 3) by the maximum power input of 290 hp.

If required, compliance with the hourly allowable emission limitation shall be determined according to test Methods 1-4, and 10 of 40 CFR Part 60, Appendix A.

- b. Emissions Limitation: 4.99 lbs NOx/hr

Applicable Compliance Method:

The hourly allowable NOx emission limitation was developed by multiplying an emission factor of 0.0172 lb/hp-hr (40 CFR Part 60, Subpart IIII, Table 3) by the maximum power input of 290 hp.

If required, compliance with the hourly allowable emission limitation shall be determined according to test Methods 1-4, and 7 of 40 CFR Part 60, Appendix A.

- c. Emissions Limitation: 0.72 lbs VOC/hr

Applicable Compliance Method:

The hourly allowable emission limitation was developed by multiplying the USEPA, AP-42 emission factor, Table 3.3-1 (revised 10/96) of 0.0247 lbs/hp-hr by the maximum power input of 290 hp.

If required, compliance with the hourly allowable emission limitation shall be determined according to test Methods 1-4, and 25 or 25A of 40 CFR Part 60, Appendix A.

- d. Emissions Limitation 0.310 lbs PE/mmBtu of actual heat input

Applicable Compliance Method:

Compliance shall be demonstrated in accordance with OAC rule 3745-17-03(B)(10).

- e. Emissions Limitations: 0.17 ton CO per rolling, 12-month period.

Issued: To be entered upon final issuance

0.50 tons NOx per rolling, 12-month period.

0.07 ton VOC per rolling, 12-month period.

Applicable Compliance Method:

Compliance with the ton per rolling 12-month period emission limitations above shall be demonstrated by the record keeping requirements established in Section C.1 of this permit.

- f. Emissions Limitation Visible PE from the stack(s) serving this emissions unit shall not exceed 20% opacity, as a 6-minute average.

Applicable Compliance Method:

Compliance shall be demonstrated in accordance with OAC rule 3745-17-03(B)(1).

F. Miscellaneous Requirements

1. The following terms and conditions are federally enforceable: A.1, B.2, C.1, D.1, E.1.a, E.1.b, E.1.c and E.1.e.
2. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P801) - equipment leaks fugitive VOC emissions

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(A)(3)	<p>The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09(DD) and 40 CFR Part 60, Subpart VV.</p> <p>Volatile organic compound (VOC) emissions shall not exceed 3.48 tons/yr.</p>
OAC rule 3745-21-09(DD)	See Sections A.2.e and F.9.
40 CFR Part 60, Subpart VV	See sections below with references to 40 CFR Part 60.

2. Additional Terms and Conditions

2.a [60.482-1(a)]

Each owner or operator subject to the provisions of this subpart shall demonstrate compliance with the requirements of 60.482-1 through 60.482-10 or 60.480(e) for all equipment within 180 days of initial startup.

2.b [60.482-1(b)]

Compliance with 60.482-1 to 60.482-10 will be determined by review of records and reports, review of performance test results, and inspection using the methods and procedures specified in 60.485.

2.c [60.482-1(c)]

i. An owner or operator may request a determination of equivalence of a means of emission limitation to the requirements of 60.482-2, 60.482-3, 60.482-5, 60.482-6, 60.482-7, 60.482-8, and 60.482-10 as provided in 60.484.

ii. If the Administrator makes a determination that a means of emission

Emissions Unit ID: **P801**

limitation is at least equivalent to the requirements of 60.482-2, 60.482-3, 60.482-5, 60.482-6, 60.482-7, 60.482-8, or 60.482-10, an owner or operator shall comply with the requirements of that determination.

- 2.d** [60.482-1(d)]
Equipment that is in vacuum service is excluded from the requirements of 60.482-2 to 60.482-10 if it is identified as required in 60.486(e)(5).
- 2.e** The permittee shall employ best available control measures for the emissions unit for the purpose of ensuring compliance with the above-mentioned applicable requirements. The permittee has committed to implementing a Leak Detection and Repair (LDAR) program to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other equally-effective control measures to ensure compliance.

The permittee shall include the appropriate process equipment and regulated components in the LDAR program. The LDAR program shall comply with the appropriate provisions (including operational restrictions, monitoring and Record keeping, reporting, and testing) of OAC rule 3745-21-09(DD) (Leaks from Process Units that Produce Organic Chemicals) and 40 CFR Part 60, Subpart VV (Standards of Performance for Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry). In the case of overlapping provisions, the permittee shall comply with the more stringent requirement.

- 2.f** The annual allowable emission rate is based on the annual production of 69,000,000 gallons denatured ethanol. Since the facility annual production rate is equivalent to the maximum facility capacity, no operational restrictions, monitoring, record keeping or reporting requirements are necessary to ensure that this emissions unit does not exceed its annual allowable emission rates. The requirement to record the amount of ethanol produced is in the terms and conditions of emissions unit J001.

B. Operational Restrictions

1. [60.482-2(a)] Pumps in light liquid service.
 - a. Each pump in light liquid service shall be monitored monthly to detect leaks by the methods specified in 60.485(b), except as provided in 60.482-1(c) and paragraphs (d), (e), and (f) of this section.
 - b. Each pump in light liquid service shall be checked by visual inspection each calendar week for indications of liquids dripping from the pump seal.

Issued: To be entered upon final issuance

2. [60.482-2(b)]
 - a. If an instrument reading of 10,000 ppm or greater is measured, a leak is detected.
 - b. If there are indications of liquids dripping from the pump seal, a leak is detected.
3. [60.482-2(c)]
 - a. When a leak is detected, it shall be repaired as soon as practicable, but not later than 15 calendar days after it is detected, except as provided in 60.482-9.
 - b. A first attempt at repair shall be made no later than 5 calendar days after each leak is detected.
4. [60.482-2(d)]

Each pump equipped with a dual mechanical seal system that includes a barrier fluid system is exempt from the requirements of paragraph (a), *Provided* the following requirements are met:

 - a. Each dual mechanical seal system is --
 - i. Operated with the barrier fluid at a pressure that is at all times greater than the pump stuffing box pressure; or
 - ii. Equipment with a barrier fluid degassing reservoir that is routed to a process or fuel gas system or connected by a closed vent system to a control device that complies with the requirements of 60.482-10; or
 - iii. Equipped with a system that purges the barrier fluid into a process stream with zero VOC emissions to the atmosphere.
 - b. The barrier fluid system is in heavy liquid service or is not in VOC service.
 - c. Each barrier fluid system is equipped with a sensor that will detect failure of the seal system, the barrier fluid system, or both.
 - d. Each pump is checked by visual inspection, each calendar week, for indications of liquids dripping from the pump seals.
 - e.
 - i. Each sensor as described in paragraph (d)(3) is checked daily or is equipped with an audible alarm, and

Emissions Unit ID: P801

- ii. The owner or operator determines, based on design considerations and operating experience, a criterion that indicates failure of the seal system, the barrier fluid system, or both.
 - f.
 - i. If there are indications of liquids dripping from the pump seal or the sensor indicates failure of the seal system, the barrier fluid system, or both based on the criterion determined in paragraph (d)(5)(ii), a leak is detected.
 - ii. When a leak is detected, it shall be repaired as soon as practicable, but not later than 15 calendar days after it is detected, except as provided in 60.482-9.
 - iii. A first attempt at repair shall be made no later than 5 calendar days after each leak is detected.
- 5. [60.482-2(e)]
Any pump that is designated, as described in 60.486(e)(1) and (2), for no detectable emission, as indicated by an instrument reading of less than 500 ppm above background, is exempt from the requirements of paragraphs (a), (c), and (d) of this section if the pump:
 - a. Has no externally actuated shaft penetrating the pump housing,
 - b. Is demonstrated to be operating with no detectable emissions as indicated by an instrument reading of less than 500 ppm above background as measured by the methods specified in 60.485(c), and
 - c. Is tested for compliance with paragraph (e)(2) of this section initially upon designation, annually, and at other times requested by the Administrator.
- 6. [60.482-2(f)]
If any pump is equipped with a closed vent system capable of capturing and transporting any leakage from the seal or seals to a process or to a fuel gas system or to a control device that complies with the requirements of 60.482-10, it is exempt from paragraphs (a) through (e) of this section.
- 7. [60.482-2(g)]
Any pump that is designated, as described in 60.486(f)(1), as an unsafe-to-monitor pump is exempt from the monitoring and inspection requirements of paragraphs (a) and (d)(4) through (6) of this section if:

Issued: To be entered upon final issuance

- a. The owner or operator of the pump demonstrates that the pump is unsafe-to-monitor because monitoring personnel would be exposed to an immediate danger as a consequence of complying with paragraph (a) of this section; and
 - b. The owner or operator of the pump has a written plan that requires monitoring of the pump as frequently as practicable during safe-to-monitor times but not more frequently than the periodic monitoring schedule otherwise applicable, and repair of the equipment according to the procedures in paragraph (c) of this section if a leak is detected.
8. [60.482-2(h)]
Any pump that is located within the boundary of an unmanned plant site is exempt from the weekly visual inspection requirement of paragraphs (a)(2) and (d)(4) of this section, and the daily requirements of paragraph (d)(5) of this section, provided that each pump is visually inspected as often as practicable and at least monthly.
9. [60.482-3(a)] Compressors.
Each compressor shall be equipped with a seal system that includes a barrier fluid system and that prevents leakage of VOC to the atmosphere, except as provided in 60.482-1(c) and paragraph (h) and (i) of this section.
10. [60.482-3(b)]
Each compressor seal system as required in paragraph (a) shall be:
- a. Operated with the barrier fluid at a pressure that is greater than the compressor stuffing box pressure; or
 - b. Equipped with a barrier fluid system degassing reservoir that is routed to a process or fuel gas system or connected by a closed vent system to a control device that complies with the requirements of 60.482-10; or
 - c. Equipped with a system that purges the barrier fluid into a process stream with zero VOC emissions to the atmosphere.
11. [60.482-3(c)]
The barrier fluid system shall be in heavy liquid service or shall not be in VOC service.
12. [60.482-3(d)]
Each barrier fluid system as described in paragraph (a) shall be equipped with a sensor that will detect failure of the seal system, barrier fluid system, or both.

13. [60.482-3(e)]
 - a. Each sensor as required in paragraph (d) shall be checked daily or shall be equipped with an audible alarm.
 - b. The owner or operator shall determine, based on design considerations and operating experience, a criterion that indicates failure of the seal system, the barrier fluid system, or both.
14. [60.482-3(f)]

If the sensor indicates failure of the seal system, the barrier system, or both based on the criterion determined under paragraph (e)(2), a leak is detected.
15. [60.482-3(g)]
 - a. When a leak is detected, it shall be repaired as soon as practicable, but not later than 15 calendar days after it is detected, except as provided in 60.482-9.
 - b. A first attempt at repair shall be made no later than 5 calendar days after each leak is detected.
16. [60.482-3(h)]

A compressor is exempt from the requirements of paragraphs (a) and (b) of this section, if it is equipped with a closed vent system to capture and transport leakage from the compressor drive shaft back to a process or fuel gas system or to a control device that complies with the requirements of 60.482-10, except as provided in paragraph (i) of this section.
17. [60.482-3(i)]

Any compressor that is designated, as described in 60.486(e) (1) and (2), for no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, is exempt from the requirements of paragraphs (a)-(h) if the compressor:

 - a. Is demonstrated to be operating with no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, as measured by the methods specified in 60.485(c); and
 - b. Is tested for compliance with paragraph (i)(1) of this section initially upon designation, annually, and at other times requested by the Administrator.
18. [60.482-3(j)]

Issued: To be entered upon final issuance

Any existing reciprocating compressor in a process unit which becomes an affected facility under provisions of 60.14 or 60.15 is exempt from 60.482(a), (b), (c), (d), (e), and (h), provided the owner or operator demonstrates that recasting the distance piece or replacing the compressor are the only options available to bring the compressor into compliance with the provisions of paragraphs (a) through (e) and (h) of this section.

19. [60.482-4(a)] Pressure relief devices in gas/vapor service.
Except during pressure releases, each pressure relief device in gas/vapor service shall be operated with no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, as determined by the methods specified in 60.485(c).
20. [60.482-4(b)]
 - a. After each pressure release, the pressure relief device shall be returned to a condition of no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, as soon as practicable, but no later than 5 calendar days after the pressure release, except as provided in 60.482-9.
 - b. No later than 5 calendar days after the pressure release, the pressure relief device shall be monitored to confirm the conditions of no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, by the methods specified in 60.485(c).

Issued: To be entered upon final issuance

21. [60.482-4(c)]
Any pressure relief device that is routed to a process or fuel gas system or equipped with a closed vent system capable of capturing and transporting leakage through the pressure relief device to a control device as described in 60.482-10 is exempted from the requirements of paragraphs (a) and (b) of this section.

22. [60.482-4(d)]
 - a. Any pressure relief device that is equipped with a rupture disk upstream of the pressure relief device is exempt from the requirements of paragraphs (a) and (b) of this section, provided the owner or operator complies with the requirements in paragraph (d)(2) of this section.

 - b. After each pressure release, a new rupture disk shall be installed upstream of the pressure relief device as soon as practicable, but no later than 5 calendar days after each pressure release, except as provided in 60.482-9.

23. [60.482-5(a)] Sampling connection systems.
Each sampling connection system shall be equipped with a closed-purged, closed-loop, or closed-vent system, except as provided in 60.482-1(c). Gases displaced during filling of the sample container are not required to be collected or captured.

24. [60.482-5(b)]
Each closed-purge, closed-loop, or closed-vent system as required in paragraph (a) of this section shall comply with the requirements specified in paragraphs (b)(1) through (4) of this section:
 - a. Return the purged process fluid directly to the process line; or

 - b. Collect and recycle the purged process fluid to a process; or

 - c. Be designed and operated to capture and transport all the purged process fluid to a control device that complies with the requirements of 60.482-10; or

 - d. Collect, store, and transport the purged process fluid to any of the following systems or facilities:
 - i. A waste management unit as defined in 40 CFR 63.111, if the waste management unit is subject to, and operated in compliance with the provisions of 40 CFR part 63, subpart G, applicable to Group 1 wastewater streams;

- ii. A treatment, storage, or disposal facility subject to regulation under 40 CFR part 262, 264, 265, or 266; or
 - iii. A facility permitted, licensed, or registered by a State to manage municipal or industrial solid waste, if the process fluids are not hazardous waste as defined in 40 CFR part 261.
25. [60.482-5(c)]
In situ sampling systems and sampling systems without purges are exempt from the requirements of paragraphs (a) and (b) of this section.
26. [60.482-6(a)] Open-ended valves or lines.
- a. Each open-ended valve or line shall be equipped with a cap, blind flange, plug, or a second valve, except as provided in 60.482-1(c).
 - b. The cap, blind flange, plug, or second valve shall seal the open end at all times except during operations requiring process fluid flow through the open-ended valve or line.
27. [60.482-6(b)]
Each open-ended valve or line equipped with a second valve shall be operated in a manner such that the valve on the process fluid end is closed before the second valve is closed.
28. [60.482-6(c)]
When a double block-and-bleed system is being used, the bleed valve or line may remain open during operations that require venting the line between the block valves but shall comply with paragraph (a) at all other times.
29. [60.482-6(d)]
Open-ended valves or lines in an emergency shutdown system which are designed to open automatically in the event of a process upset are exempt from the requirements of paragraphs (a), (b) and (c) of this section.
30. [60.482-6(e)]
Open-ended valves or lines containing materials which would autocatalytically polymerize or would present an explosion, serious over pressure, or other safety hazard if capped or equipped with a double block and bleed system as specified in

Issued: To be entered upon final issuance

paragraphs (a) through (c) of this section are exempt from the requirements of paragraphs (a) through (c) of this section.

31. [60.482-7(a)] Valves in gas/vapor service and in light liquid service. Each valve shall be monitored monthly to detect leaks by the methods specified in 60.485(b) and shall comply with paragraphs (b) through (e), except as provided in paragraphs (f), (g), and (h), 60.483-1, 2, and 60.482-1(c).

Issued: To be entered upon final issuance

32. [60.482-7(b)]
If an instrument reading of 10,000 ppm or greater is measured, a leak is detected.
33. [60.482-7(c)]
 - a. Any valve for which a leak is not detected for 2 successive months may be monitored the first month of every quarter, beginning with the next quarter, until a leak is detected.
 - b. If a leak is detected, the valve shall be monitored monthly until a leak is not detected for 2 successive months.
34. [60.482-7(d)]
 - a. When a leak is detected, it shall be repaired as soon as practicable, but no later than 15 calendar days after the leak is detected, except as provided in 60.482-9.
 - b. A first attempt at repair shall be made no later than 5 calendar days after each leak is detected.
35. [60.482-7(e)]

First attempts at repair include, but are not limited to, the following best practices where practicable:

 - a. Tightening of bonnet bolts;
 - b. Replacement of bonnet bolts;
 - c. Tightening of packing gland nuts;
 - d. Injection of lubricant into lubricated packing.
36. [60.482-7(f)]

Any valve that is designated, as described in 60.486(e)(2), for no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, is exempt from the requirements of paragraph (a) if the valve:

 - a. Has no external actuating mechanism in contact with the process fluid,
 - b. Is operated with emissions less than 500 ppm above background as determined by the method specified in 60.485(c), and
 - c. Is tested for compliance with paragraph (f)(2) of this section initially upon

Emissions Unit ID: P801

designation, annually, and at other times requested by the Administrator.

37. [60.482-7(g)]
Any valve that is designated, as described in 60.486(f)(1), as an unsafe-to-monitor valve is exempt from the requirements of paragraph (a) if:
- a. The owner or operator of the valve demonstrates that the valve is unsafe to monitor because monitoring personnel would be exposed to an immediate danger as a consequence of complying with paragraph (a), and
 - b. The owner or operator of the valve adheres to a written plan that requires monitoring of the valve as frequently as practicable during safe-to-monitor times.
38. [60.482-7(h)]
Any valve that is designated, as described in 60.486(f)(2), as a difficult-to-monitor valve is exempt from the requirements of paragraph (a) if:
- a. The owner or operator of the valve demonstrates that the valve cannot be monitored without elevating the monitoring personnel more than 2 meters above a support surface.
 - b. The process unit within which the valve is located either becomes an affected facility through 60.14 or 60.15 or the owner or operator designates less than 3.0 percent of the total number of valves as difficult-to-monitor, and
 - c. The owner or operator of the valve follows a written plan that requires monitoring of the valve at least once per calendar year.
39. [60.482-8(a)] Pumps and valves in heavy liquid service, pressure relief devices in light liquid or heavy liquid service, and connectors.

If evidence of a potential leak is found by visual, audible, olfactory, or any other detection method at pumps and valves in heavy liquid service, pressure relief devices in light liquid or heavy liquid service, and connectors, the owner or operator shall follow either one of the following procedures:

- a. The owner or operator shall monitor the equipment within 5 days by the method specified in 60.485(b) and shall comply with the requirements of paragraphs (b) through (d) of this section.
- b. The owner or operator shall eliminate the visual, audible, olfactory, or other indication of a potential leak.

Issued: To be entered upon final issuance

40. [60.482-8(b)]
If an instrument reading of 10,000 ppm or greater is measured, a leak is detected.
41. [60.482-8(c)]
 - a. When a leak is detected, it shall be repaired as soon as practicable, but not later than 15 calendar days after it is detected, except as provided in 60.482-9.
 - b. The first attempt at repair shall be made no later than 5 calendar days after each leak is detected.
42. [60.482-8(d)]
First attempts at repair include, but are not limited to, the best practices described under 60.482-7(e).
43. [60.482-9(a)] Delay of repair.
Delay of repair of equipment for which leaks have been detected will be allowed if repair within 15 days is technically infeasible without a process unit shutdown. Repair of this equipment shall occur before the end of the next process unit shutdown.
44. [60.482-9(b)]
Delay of repair of equipment will be allowed for equipment which is isolated from the process and which does not remain in VOC service.
45. [60.482-9(c)]
Delay of repair for valves will be allowed if:
 - a. The owner or operator demonstrates that emissions of purged material resulting from immediate repair are greater than the fugitive emissions likely to result from delay of repair, and
 - b. When repair procedures are effected, the purged material is collected and destroyed or recovered in a control device complying with 60.482-10.
46. [60.482-9(d)]
Delay of repair for pumps will be allowed if:
 - a. Repair requires the use of a dual mechanical seal system that includes a barrier fluid system, and
 - b. Repair is completed as soon as practicable, but not later than 6 months after the

Emissions Unit ID: P801

leak was detected.

47. [60.482-9(e)]
Delay of repair beyond a process unit shutdown will be allowed for a valve, if valve assembly replacement is necessary during the process unit shutdown, valve assembly supplies have been depleted, and valve assembly supplies had been sufficiently stocked before the supplies were depleted. Delay of repair beyond the next process unit shutdown will not be allowed unless the next process unit shutdown occurs sooner than 6 months after the first process unit shutdown.
48. [60.482-10(a)] Closed vent systems and control devices.
Owners or operators of closed vent systems and control devices used to comply with provisions of this subpart shall comply with the provisions of this section.
49. [60.482-10(b)]
Vapor recovery systems (for example, condensers and absorbers) shall be designed and operated to recover the VOC emissions vented to them with an efficiency of 95 percent or greater, or to an exit concentration of 20 parts per million by volume, whichever is less stringent.
50. [60.482-10(c)]
Enclosed combustion devices shall be designed and operated to reduce the VOC emissions vented to them with an efficiency of 95 percent or greater, or to an exit concentration of 20 parts per million by volume, on a dry basis, corrected to 3 percent oxygen, whichever is less stringent or to provide a minimum residence time of 0.75 seconds at a minimum temperature of 816 °C.
51. [60.482-10(d)]
Flares used to comply with this subpart shall comply with the requirements of 60.18.
52. [60.482-10(e)]
Owners or operators of control devices used to comply with the provisions of this subpart shall monitor these control devices to ensure that they are operated and maintained in conformance with their designs.
53. [60.482-10(f)]
Except as provided in paragraphs (i) through (k) of this section, each closed vent system shall be inspected according to the procedures and schedule specified in paragraphs (f)(1) and (f)(2) of this section.

Issued: To be entered upon final issuance

- a. If the vapor collection system or closed vent system is constructed of hard-piping, the owner or operator shall comply with the requirements specified in paragraphs (f)(1)(i) and (f)(1)(ii) of this section:
 - i. Conduct an initial inspection according to the procedures in 60.485(b);
and
 - ii. Conduct annual visual inspections for visible, audible, or olfactory indications of leaks.

- b. If the vapor collection system or closed vent system is constructed of ductwork, the owner or operator shall:
 - i. Conduct an initial inspection according to the procedures in 60.485(b);
and
 - ii. Conduct annual inspections according to the procedures in 60.485(b).

Issued: To be entered upon final issuance

54. [60.482-10(g)]
Leaks, as indicated by an instrument reading greater than 500 parts per million by volume above background or by visual inspections, shall be repaired as soon as practicable except as provided in paragraph (h) of this section.
- a. A first attempt at repair shall be made no later than 5 calendar days after the leak is detected.
 - b. Repair shall be completed no later than 15 calendar days after the leak is detected.
55. [60.482-10(h)]
Delay of repair of a closed vent system for which leaks have been detected is allowed if the repair is technically infeasible without a process unit shutdown or if the owner or operator determines that emissions resulting from immediate repair would be greater than the fugitive emissions likely to result from delay of repair. Repair of such equipment shall be complete by the end of the next process unit shutdown.
56. [60.482-10(i)]
If a vapor collection system or closed vent system is operated under a vacuum, it is exempt from the inspection requirements of paragraphs (f)(1)(i) and (f)(2) of this section.
57. [60.482-10(j)]
Any parts of the closed vent system that are designated, as described in paragraph (l)(1) of this section, as unsafe to inspect are exempt from the inspection requirements of paragraphs (f)(1)(i) and (f)(2) of this section if they comply with the requirements specified in paragraphs (j)(1) and (j)(2) of this section:
- a. The owner or operator determines that the equipment is unsafe to inspect because inspecting personnel would be exposed to an imminent or potential danger as a consequence of complying with paragraphs (f)(1)(i) or (f)(2) of this section; and
 - b. The owner or operator has a written plan that requires inspection of the equipment as frequently as practicable during safe-to-inspect times.
58. [60.482-10(k)]
Any parts of the closed vent system that are designated, as described in paragraph (l)(2) of this section, as difficult to inspect are exempt from the inspection requirements

Emissions Unit ID: P801

of paragraphs (f)(1)(i) and (f)(2) of this section if they comply with the requirements specified in paragraphs (k)(1) through (k)(3) of this section:

- a. The owner or operator determines that the equipment cannot be inspected without elevating the inspecting personnel more than 2 meters above a support surface; and
- b. The process unit within which the closed vent system is located becomes an affected facility through 60.14 or 60.15, or the owner or operator designates less than 3.0 percent of the total number of closed vent system equipment as difficult to inspect; and
- c. The owner or operator has a written plan that requires inspection of the equipment at least once every 5 years. A closed vent system is exempt from inspection if it is operated under a vacuum.

59. [60.482-10(l)]

The owner or operator shall record the information specified in paragraphs (l)(1) through (l)(5) of this section.

- a. Identification of all parts of the closed vent system that are designated as unsafe to inspect, an explanation of why the equipment is unsafe to inspect, and the plan for inspecting the equipment.
- b. Identification of all parts of the closed vent system that are designated as difficult to inspect, an explanation of why the equipment is difficult to inspect, and the plan for inspecting the equipment.
- c. For each inspection during which a leak is detected, a record of the information specified in 60.486(c).
- d. For each inspection conducted in accordance with 60.485(b) during which no leaks are detected, a record that the inspection was performed, the date of the inspection, and a statement that no leaks were detected.
- e. For each visual inspection conducted in accordance with paragraph (f)(1)(ii) of this section during which no leaks are detected, a record that the inspection was performed, the date of the inspection, and a statement that no leaks were detected.

60. [60.482-10(m)]

Issued: To be entered upon final issuance

Closed vent systems and control devices used to comply with provisions of this subpart shall be operated at all times when emissions may be vented to them.

61. [60.483-1(a)] Alternative standards for valves -- allowable percentage of valves leaking.
An owner or operator may elect to comply with an allowable percentage of valves leaking of equal to or less than 2.0 percent.
62. [60.483-1(b)]
The following requirements shall be met if an owner or operator wishes to comply with an allowable percentage of valves leaking:
 - a. An owner or operator must notify the Administrator that the owner or operator has elected to comply with the allowable percentage of valves leaking before implementing this alternative standard, as specified in 60.487(d).
 - b. A performance test as specified in paragraph (c) of this section shall be conducted initially upon designation, annually, and at other times requested by the Administrator.
 - c. If a valve leak is detected, it shall be repaired in accordance with 60.482-7(d) and (e).
63. [60.483-1(c)]
Performance tests shall be conducted in the following manner:
 - a. All valves in gas/vapor and light liquid service within the affected facility shall be monitored within 1 week by the methods specified in 60.485(b).
 - b. If an instrument reading of 10,000 ppm or greater is measured, a leak is detected.
 - c. The leak percentage shall be determined by dividing the number of valves for which leaks are detected by the number of valves in gas/vapor and light liquid service within the affected facility.
64. [60.483-1(d)]
Owners and operators who elect to comply with this alternative standard shall not have an affected facility with a leak percentage greater than 2.0 percent.
65. [60.483-2(a)] Alternative standards for valves -- skip period leak detection and repair.

Emissions Unit ID: P801

- a. An owner or operator may elect to comply with one of the alternative work practices specified in paragraphs (b)(2) and (3) of this section.
 - b. An owner or operator must notify the Administrator before implementing one of the alternative work practices, as specified in 60.487(d).
66. [60.483-2(b)]
- a. An owner or operator shall comply initially with the requirements for valves in gas/vapor service and valves in light liquid service, as described in 60.482-7.
 - b. After 2 consecutive quarterly leak detection periods with the percent of valves leaking equal to or less than 2.0, an owner or operator may begin to skip 1 of the quarterly leak detection periods for the valves in gas/vapor and light liquid service.
 - c. After 5 consecutive quarterly leak detection periods with the percent of valves leaking equal to or less than 2.0, an owner or operator may begin to skip 3 of the quarterly leak detection periods for the valves in gas/vapor and light liquid service.
 - d. If the percent of valves leaking is greater than 2.0, the owner or operator shall comply with the requirements as described in 60.482-7 but can again elect to use this section.
 - e. The percent of valves leaking shall be determined by dividing the sum of valves found leaking during current monitoring and valves for which repair has been delayed by the total number of valves subject to the requirements of this section.
 - f. An owner or operator must keep a record of the percent of valves found leaking during each leak detection period.

C. Monitoring and/or Record keeping Requirements

1. [60.486] Record keeping requirements.
 - a. Each owner or operator subject to the provisions of this subpart shall comply with the Record keeping requirements of this section.
 - b. An owner or operator of more than one affected facility subject to the provisions of this subpart may comply with the Record keeping requirements for these facilities in one Record keeping system if the system identifies each record by each facility.
2. [60.486(b)]

Issued: To be entered upon final issuance

When each leak is detected as specified in 60.482-2, 60.482-3, 60.482-7, 60.482-8, and 60.483-2, the following requirements apply:

- a. A weatherproof and readily visible identification, marked with the equipment identification number, shall be attached to the leaking equipment.
- b. The identification on a valve may be removed after it has been monitored for 2 successive months as specified in 60.482-7(c) and no leak has been detected during those 2 months.
- c. The identification on equipment except on a valve, may be removed after it has been repaired.

3. [60.486(c)]

When each leak is detected as specified in 60.482-2, 60.482-3, 60.482-7, 60.482-8, and 60.483-2, the following information shall be recorded in a log and shall be kept for 2 years in a readily accessible location:

- a. The instrument and operator identification numbers and the equipment identification number.
- b. The date the leak was detected and the dates of each attempt to repair the leak.
- c. Repair methods applied in each attempt to repair the leak.
- d. "Above 10,000" if the maximum instrument reading measured by the methods specified in 60.485(a) after each repair attempt is equal to or greater than 10,000 ppm.
- e. "Repair delayed" and the reason for the delay if a leak is not repaired within 15 calendar days after discovery of the leak.
- f. The signature of the owner or operator (or designate) whose decision it was that repair could not be effected without a process shutdown.
- g. The expected date of successful repair of the leak if a leak is not repaired within 15 days.
- h. Dates of process unit shutdowns that occur while the equipment is unrepaired.
- i. The date of successful repair of the leak.

Emissions Unit ID: P801

4. [60.486(d)]
The following information pertaining to the design requirements for closed vent systems and control devices described in 60.482-10 shall be recorded and kept in a readily accessible location:
- a. Detailed schematics, design specifications, and piping and instrumentation diagrams.
 - b. The dates and descriptions of any changes in the design specifications.
 - c. A description of the parameter or parameters monitored, as required in 60.482-10(e), to ensure that control devices are operated and maintained in conformance with their design and an explanation of why that parameter (or parameters) was selected for the monitoring.
 - d. Periods when the closed vent systems and control devices required in 60.482-2, 60.482-3, 60.482-4, and 60.482-5 are not operated as designed, including periods when a flare pilot light does not have a flame.
 - e. Dates of startups and shutdowns of the closed vent systems and control devices required in 60.482-2, 60.482-3, 60.482-4, and 60.482-5.
5. [60.486(e)]
The following information pertaining to all equipment subject to the requirements in 60.482-1 to 60.482-10 shall be recorded in a log that is kept in a readily accessible location:
- a. A list of identification numbers for equipment subject to the requirements of this subpart.
 - b.
 - i. A list of identification numbers for equipment that are designated for no detectable emissions under the provisions of 60.482-2(e), 60.482-3(i) and 60.482-7(f).
 - ii. The designation of equipment as subject to the requirements of 60.482-2(e), 60.482-3(i), or 60.482-7(f) shall be signed by the owner or operator.
 - c. A list of equipment identification numbers for pressure relief devices required to comply with 60.482-4.

Issued: To be entered upon final issuance

- d.
 - i. The dates of each compliance test as required in 60.482-2(e), 60.482-3(i), 60.482-4, and 60.482-7(f).
 - ii. The background level measured during each compliance test.
 - iii. The maximum instrument reading measured at the equipment during each compliance test.
 - e. A list of identification numbers for equipment in vacuum service.
6. [60.486(f)]
The following information pertaining to all valves subject to the requirements of 60.482-7(g) and (h) and to all pumps subject to the requirements of 60.482-2(g) shall be recorded in a log that is kept in a readily accessible location:
- a. A list of identification numbers for valves and pumps that are designated as unsafe-to-monitor, an explanation for each valve or pump stating why the valve or pump is unsafe-to-monitor, and the plan for monitoring each valve or pump.
 - b. A list of identification numbers for valves that are designated as difficult-to-monitor, an explanation for each valve stating why the valve is difficult-to-monitor, and the schedule for monitoring each valve.
7. [60.486(g)]
The following information shall be recorded for valves complying with 60.483-2:
- a. A schedule of monitoring.
 - b. The percent of valves found leaking during each monitoring period.
8. [60.486(h)]
The following information shall be recorded in a log that is kept in a readily accessible location:
- a. Design criterion required in 60.482-2(d)(5) and 60.482-3(e)(2) and explanation of the design criterion; and
 - b. Any changes to this criterion and the reasons for the changes.
9. [60.486(i)]
The following information shall be recorded in a log that is kept in a readily accessible

Issued: To be entered upon final issuance

location for use in determining exemptions as provided in 60.480(d):

- a. An analysis demonstrating the design capacity of the affected facility,
 - b. A statement listing the feed or raw materials and products from the affected facilities and an analysis demonstrating whether these chemicals are heavy liquids or beverage alcohol, and
 - c. An analysis demonstrating that equipment is not in VOC service.
10. [60.486(j)]
Information and data used to demonstrate that a piece of equipment is not in VOC service shall be recorded in a log that is kept in a readily accessible location.
11. [60.486(k)]
The provisions of 60.7(b) and (d) do not apply to affected facilities subject to this subpart.

D. Reporting Requirements

1. [60.487(a)] Reporting requirements.
Each owner or operator subject to the provisions of this subpart shall submit semiannual reports to the Administrator beginning six months after the initial startup date.
2. [60.487(b)]
The initial semiannual report to the Administrator shall include the following information:
 - a. Process unit identification.
 - b. Number of valves subject to the requirements of 60.482-7, excluding those valves designated for no detectable emissions under the provisions of 60.482-7(f).
 - c. Number of pumps subject to the requirements of 60.482-2, excluding those pumps designated for no detectable emissions under the provisions of 60.482-2(e) and those pumps complying with 60.482-2(f).
 - d. Number of compressors subject to the requirements of 60.482-3, excluding those compressors designated for no detectable emissions under the provisions of

Emissions Unit ID: P801

60.482-3(i) and those compressors complying with 60.482-3(h).

3. [60.487(c)]

All semiannual reports to the Administrator shall include the following information, summarized from the information in 60.486:

- a. Process unit identification.
- b. For each month during the semiannual reporting period,
 - i. Number of valves for which leaks were detected as described in 60.482(7)(b) or 60.483-2,
 - ii. Number of valves for which leaks were not repaired as required in 60.482-7(d)a.,
 - iii. Number of pumps for which leaks were detected as described in 60.482-2(b) and (d)(6)(i),
 - iv. Number of pumps for which leaks were not repaired as required in 60.482-2(c)a. and (d)(6)(ii),
 - v. Number of compressors for which leaks were detected as described in 60.482-3(f),
 - vi. Number of compressors for which leaks were not repaired as required in 60.482-3(g)a., and
 - (vii) The facts that explain each delay of repair and, where appropriate, why a process unit shutdown was technically infeasible.
- c. Dates of process unit shutdowns which occurred within the semiannual reporting period.
- d. Revisions to items reported according to paragraph (b) if changes have occurred since the initial report or subsequent revisions to the initial report.

4. [60.487(d)]

An owner or operator electing to comply with the provisions of 60.483-1 or 60.483-2 shall notify the Administrator of the alternative standard selected 90 days before implementing either of the provisions.

Issued: To be entered upon final issuance

5. [60.487(e)]
An owner or operator shall report the results of all performance tests in accordance with 60.8 of the General Provisions. The provisions of 60.8(d) do not apply to affected facilities subject to the provisions of this subpart except that an owner or operator must notify the Administrator of the schedule for the initial performance tests at least 30 days before the initial performance tests.

6. [60.487(f)]
The requirements of paragraphs (a) through (c) of this section remain in force until and unless EPA, in delegating enforcement authority to a State under section 111(c) of the Act, approves reporting requirements or an alternative means of compliance surveillance adopted by such State. In that event, affected sources within the State will be relieved of the obligation to comply with the requirements of paragraphs (a) through (c) of this section, provided that they comply with the requirements established by the State.

E. Testing Requirements

1. [60.485(a)] Test methods and procedures.
In conducting the performance tests required in 60.8, the owner or operator shall use as reference methods and procedures the test methods in appendix A of this part or other methods and procedures as specified in this section, except as provided in 60.8(b).

2. [60.485(b)]
The owner or operator shall determine compliance with the standards in 60.482, 60.483, and 60.484 as follows:
 - a. Method 21 shall be used to determine the presence of leaking sources. The instrument shall be calibrated before use each day of its use by the procedures specified in Method 21. The following calibration gases shall be used:
 - i. Zero air (less than 10 ppm of hydrocarbon in air); and
 - ii. A mixture of methane or n-hexane and air at a concentration of about, but less than, 10,000 ppm methane or n-hexane.

3. [60.485(c)]
The owner or operator shall determine compliance with the no detectable emission standards in 60.482-2(e), 60.482-3(i), 60.482-4, 60.482-7(f), and 60.482-10(e) as follows:

Emissions Unit ID: P801

- a. The requirements of paragraph (b) shall apply.
 - b. Method 21 shall be used to determine the background level. All potential leak interfaces shall be traversed as close to the interface as possible. The arithmetic difference between the maximum concentration indicated by the instrument and the background level is compared with 500 ppm for determining compliance.
4. [60.485(d)]
The owner or operator shall test each piece of equipment unless he demonstrates that a process unit is not in VOC service, i.e., that the VOC content would never be reasonably expected to exceed 10 percent by weight. For purposes of this demonstration, the following methods and procedures shall be used:
- a. Procedures that conform to the general methods in ASTM E260-73, 91, or 96, E168-67, 77, or 92, E169-63, 77, or 93 (incorporated by reference -- see 60.17) shall be used to determine the percent VOC content in the process fluid that is contained in or contacts a piece of equipment.
 - b. Organic compounds that are considered by the Administrator to have negligible photochemical reactivity may be excluded from the total quantity of organic compounds in determining the VOC content of the process fluid.
 - c. Engineering judgment may be used to estimate the VOC content, if a piece of equipment had not been shown previously to be in service. If the Administrator disagrees with the judgment, paragraphs (d)a. and (2) of this section shall be used to resolve the disagreement.
- 5 [60.485(e)]
The owner or operator shall demonstrate that an equipment is in light liquid service by showing that all the following conditions apply:
- a. The vapor pressure of one or more of the components is greater than 0.3 kPa at 20 °C (1.2 in. H₂O at 68 °F). Standard reference texts or ASTM D2879-83, 96, or 97 (incorporated by reference -- see 60.17) shall be used to determine the vapor pressures.
 - b. The total concentration of the pure components having a vapor pressure greater than 0.3 kPa at 20 °C (1.2 in. H₂O at 68 °F) is equal to or greater than 20 percent by weight.

Issued: To be entered upon final issuance

- c. The fluid is a liquid at operating conditions.
6. [60.485(f)]
Samples used in conjunction with paragraphs (d), (e), and (g) of this section shall be representative of the process fluid that is contained in or contacts the equipment or the gas being combusted in the flare.
7. [60.485(g)]
The owner or operator shall determine compliance with the standards of flares as follows:
- a. Method 22 shall be used to determine visible emissions.
- b. A thermocouple or any other equivalent device shall be used to monitor the presence of a pilot flame in the flare.
- c. The maximum permitted velocity for air assisted flares shall be computed using the following equation:

$$V_{\max} = K_1 + K_2 H_T$$

Where:

V_{\max} = Maximum permitted velocity, m/sec (ft/sec)

H_T = Net heating value of the gas being combusted, MJ/scm (Btu/scf).

K_1 = 8.706 m/sec (metric units) = 28.56 ft/sec (English units)

K_2 = 0.7084 m^{1/2}/(MJ-sec) (metric units) = 0.087 ft^{1/2}/(Btu-sec) (English units)

- d. The net heating value (H_T) of the gas being combusted in a flare shall be computed using the following equation:

n

$$H_T = K \sum_{i=1}^n C_i H_i$$

Where:

K = Conversion constant, 1.740×10^{-7} (g-mole)(MJ)/ (ppm-scm-kcal) (metric units) = 4.674×10^{-8} [(g-mole)(Btu)/(ppm-scf-kcal)] (English units)

C_i = Concentration of sample component "i," ppm

H_i = net heat of combustion of sample component "i" at 25 °C and 760 mm Hg (77 °F and 14.7 psi), kcal/g-mole

Issued: To be entered upon final issuance

- e. Method 18 and ASTM D2504-67, 77, or 88 (Re-approved 1993) (incorporated by reference -- see 60.17) shall be used to determine the concentration of sample component "i."
 - f. ASTM D2382-76 or 88 or D4809-95 (incorporated by reference -- see 60.17) shall be used to determine the net heat of combustion of component "i" if published values are not available or cannot be calculated.
 - g. Method 2, 2A, 2C, or 2D, as appropriate, shall be used to determine the actual exit velocity of a flare. If needed, the unobstructed (free) cross-sectional area of the flare tip shall be used.
8. Compliance with the emission limitation in Section A.1. of these terms and conditions shall be determined in accordance with the following method:

Emission Limitation: VOC emissions shall not exceed 3.48 tons/yr.

Applicable Compliance Method:

Compliance with the annual emission limitation has been determined by the permittee using the estimated component count based on similar ethanol plants and emission factors from 'Protocol for Equipment Leak Emission Estimates', EPA-453/R-95-017, Table 5-2. No testing is specifically required by this permit but, if appropriate, may be requested pursuant to OAC rule 3745-15-04(A). Such testing would be required to comply with methods described in OAC rule 3745-21-10 for organic compounds.

F. Miscellaneous Requirements

- 1. [60.484(a)] Equivalence of means of emission limitation.
Each owner or operator subject to the provisions of this subpart may apply to the Administrator for determination of equivalence for any means of emission limitation that achieves a reduction in emissions of VOC at least equivalent to the reduction in emissions of VOC achieved by the controls required in this subpart.
- 2. [60.484(b)]
Determination of equivalence to the equipment, design, and operational requirements of this subpart will be evaluated by the following guidelines:
 - a. Each owner or operator applying for an equivalence determination shall be responsible for collecting and verifying test data to demonstrate equivalence of

Emissions Unit ID: P801

means of emission limitation.

- b. The Administrator will compare test data for the means of emission limitation to test data for the equipment, design, and operational requirements.
 - c. The Administrator may condition the approval of equivalence on requirements that may be necessary to assure operation and maintenance to achieve the same emission reduction as the equipment, design, and operational requirements.
3. [60.484(c)]
Determination of equivalence to the required work practices in this subpart will be evaluated by the following guidelines:
- a. Each owner or operator applying for a determination of equivalence shall be responsible for collecting and verifying test data to demonstrate equivalence of an equivalent means of emission limitation.
 - b. For each affected facility for which a determination of equivalence is requested, the emission reduction achieved by the required work practice shall be demonstrated.
 - c. For each affected facility, for which a determination of equivalence is requested, the emission reduction achieved by the equivalent means of emission limitation shall be demonstrated.
 - d. Each owner or operator applying for a determination of equivalence shall commit in writing to work practice(s) that provide for emission reductions equal to or greater than the emission reductions achieved by the required work practice.
 - e. The Administrator will compare the demonstrated emission reduction for the equivalent means of emission limitation to the demonstrated emission reduction for the required work practices and will consider the commitment in paragraph (c)(4).
 - f. The Administrator may condition the approval of equivalence on requirements that may be necessary to assure operation and maintenance to achieve the same emission reduction as the required work practice.
4. [60.484(d)]
An owner or operator may offer a unique approach to demonstrate the equivalence of

Issued: To be entered upon final issuance

any equivalent means of emission limitation.

5. [60.484(e)]
 - a. After a request for determination of equivalence is received, the Administrator will publish a notice in the Federal Register and provide the opportunity for public hearing if the Administrator judges that the request may be approved.
 - b. After notice and opportunity for public hearing, the Administrator will determine the equivalence of a means of emission limitation and will publish the determination in the Federal Register.
 - c. Any equivalent means of emission limitations approved under this section shall constitute a required work practice, equipment, design, or operational standard within the meaning of section 111(h)a. of the Clean Air Act.
6. [60.484(f)]
 - a. Manufacturers of equipment used to control equipment leaks of VOC may apply to the Administrator for determination of equivalence for any equivalent means of emission limitation that achieves a reduction in emissions of VOC achieved by the equipment, design, and operational requirements of this subpart.
 - b. The Administrator will make an equivalence determination according to the provisions of paragraphs (b), (c), (d), and (e) of this section.
7. [60.488(a)] Reconstruction.
For the purposes of this subpart:

The cost of the following frequently replaced components of the facility shall not be considered in calculating either the "fixed capital cost of the new components" or the "fixed capital costs that would be required to construct a comparable new facility" under 60.15: pump seals, nuts and bolts, rupture disks, and packings.
8. [60.488(b)]
Under 60.15, the "fixed capital cost of new components" includes the fixed capital cost of all depreciable components (except components specified in 60.488 (a)) which are or will be replaced pursuant to all continuous programs of component replacement which are commenced within any 2-year period following the applicability date for the appropriate subpart. (See the "Applicability and designation of affected facility" section of the appropriate subpart.) For purposes of this paragraph, "commenced" means that an owner or operator has undertaken a continuous program of component replacement or that an owner or operator has entered into a contractual obligation to undertake and

Emissions Unit ID: **P801**

complete, within a reasonable time, a continuous program of component replacement.

9. Within 180 days of the start up of this emissions unit, the permittee shall develop a facility LDAR program. At a minimum, the program shall include all the appropriate process equipment and regulated components that are subject to this program and clearly identify how the permittee will comply with the appropriate provisions (including operational restrictions, monitoring and Record keeping, reporting, and testing) of OAC rule 3745-21-09(DD) and 40 CFR Part 60, Subpart VV.
10. The permittee shall submit annual reports which specify the total VOC emissions from this emissions unit for the previous calendar year. This report shall be submitted by January 31 of each year. This requirement may be satisfied, if required, by including and identifying the specific emissions data from these emissions units in the annual Fee Emission Report.
11. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P802) - wetcake fugitive VOC emissions

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(C)	Volatile organic compound (VOC) emissions shall not exceed 3.85 tons/yr.

2. **Additional Terms and Conditions**

- 2.a None

B. Operational Restrictions

1. The maximum annual wetcake throughput for this emissions unit shall not exceed 928,560 tons.
2. All wetcake must be removed from the wetcake storage area within 48 hours of production/placement to storage. If material is removed from the storage area it may be either recycled back into the system or removed off of the property.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain monthly records of the wetcake throughput for this emissions unit (in tons per month and total tons, to date for the calendar year).
2. The permittee shall maintain records of the following information:
 - a. a daily record of the time and quantity of wetcake that is added to the wetcake storage enclosure each day as a result of production;
 - b. a daily record of the time and quantity of wetcake that is added to the wetcake storage enclosure each day as a result of a malfunction or process upset;

Emissions Unit ID: P802

- c. a weekly record of the total amount of wetcake produced in pounds, along with the total throughput of corn used for the facility;
- d. a daily record showing the time and quantity for each loadout of wetcake which is removed from the wetcake storage area and the reason for removal (shipment, recycle or waste).

This data is to be kept in a log book within 50 yards of the storage facility for easy review.

D. Reporting Requirements

1. The permittee shall submit reports that summarize the total annual wetcake throughput for this emissions unit. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.
2. The permittee shall submit semiannual reports that (a) identify all days during which wetcake was added to the storage enclosure as a result of production (b) identify all days during which wetcake was added to the storage enclosure as a result of a malfunction or process upset and (c) describe any actions that resulted in wetcake being removed as waste. These reports shall be submitted to the Ohio EPA, NWDO by January 31 and July 31 of each year and shall cover the previous 6-month period.

E. Testing Requirements

1. Compliance with the emission limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emission Limitation: VOC emissions shall not exceed 3.85 tons/yr

Applicable Compliance Method:

The emission limitation was developed by multiplying an emission factor of 0.0083 lbs VOC/ton of wetcake (Diversified Energy Facility in Morris, MN, stack test date: November 2, 2004) by the maximum annual wetcake throughput of 928,560 tons and dividing by 2000 lbs per ton. Therefore, provided compliance is shown with the maximum annual wetcake throughput, compliance with the annual limitation will be assumed.

F. Miscellaneous Requirements

Issued: To be entered upon final issuance

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P901) - grain receiving, transferring, conveying and storage

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
--------------------------------------	----------------------------------------------------------

Issued: To be entered upon final issuance

OAC rule 3745-31-05(A)(3)	<p><u>Stack Emissions:</u> The baghouse(s) shall achieve the following outlet emission rates for particulate matter equal to or less than 10 microns in size (PM10):</p> <p><i>grain receiving baghouse:</i> 0.005 grains per dry standard cubic foot of exhaust gases (gr/dscf).</p> <p><i>corn storage bin vent #1:</i> 0.010 gr/dscf</p> <p><i>corn storage bin vent #2:</i> 0.010 gr/dscf</p> <p>PM10 emissions from this emissions unit shall not exceed 8.63 tons per year (TPY).</p> <p>Visible particulate emissions (PE) from the stack(s) serving this emissions unit shall not exceed 0% opacity, as a 6-minute average.</p> <p><u>Fugitive Emissions:</u> Fugitive PE shall not exceed 4.04 TPY.</p> <p>Fugitive PM10 emissions shall not exceed 0.90 TPY.</p> <p>Visible fugitive PE shall not exceed 5% opacity, as a 3-minute average, from any truck or rail unloading.</p> <p>Visible fugitive PE shall not exceed 0% opacity, as a 3-minute average, from any grain handling operations.</p> <p>See Sections A.2.a and A.2.f.</p>
OAC rule 3745-17-07 (B)	See Section A.2.b.
OAC rule 3745-17-08(A)	See section A.2.c.
OAC rule 3745-17-07(A)	See section A.2.c.
OAC rule 3745-17-11(B)	See section A.2.d.
40 CFR Part 60, Subpart DD	See section A.2.e.

2. Additional Terms and Conditions

2.a Best available technology (BAT) control requirements for this emissions unit has

Emissions Unit ID: P901

been determined to be:

- i. for dry grain receiving, partial enclosure with aspiration to baghouse (S01); and
- ii. for transferring, conveying and storage, the use total enclosure and a baghouse system (corn storage bin vents #1 and #2).

BAT also includes compliance with the terms and conditions of this permit.

- 2.b** This emissions unit is exempt from the visible particulate emission limitations specified in OAC rule 3745-17-07(B), pursuant to OAC rule 3745-17-07(B)(11)(e).
- 2.c** This emissions unit is not located within an "Appendix A" area as identified in OAC rule 3745-17-08. Therefore, pursuant to OAC rule 3745-17-08(A), this emissions unit is exempt from the requirements of OAC rule 3745-17-08(B).
- 2.d** The emission limitation specified by these rules is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
- 2.e** 40 CFR Part 60, Subpart DD (Standards of Performance for Grain Elevators), is applicable to grain storage elevators at any wheat flour mill, wet corn mill, dry corn mill (human consumption), rice mill, or soybean oil extraction plant with a permanent grain storage capacity greater than 1.0 million U.S. bushels. The permanent grain storage capacity of this facility is 1.20 million bushels, but the facility is classified as a dry corn chemical manufacturing (not for human consumption). Therefore, 40 CFR Part 60, Subpart DD, is not applicable.
- 2.f** For the purposes of this permit, all stack PE is considered to be PM10.

Issued: To be entered upon final issuance

B. Operational Restrictions

1. The maximum annual corn throughput for this emissions unit shall not exceed 1,153,558 tons.
2. The permittee shall operate the baghouse(s) at all times when this emissions unit is in operation.

C. Monitoring and/or Record keeping Requirements

1. The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack(s) serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log, as well as the date and time the daily check was performed. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. the color of the emissions;
 - b. the total duration of any visible emission incident; and
 - c. any corrective actions taken to eliminate the visible emissions.
2. The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible fugitive particulate emissions from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit. The presence or absence of any visible fugitive emissions shall be noted in an operations log, as well as the date and time the daily check was performed. If visible fugitive emissions are observed, the permittee shall also note the following in the operations log:
 - a. the color of the emissions;
 - b. whether the emissions are representative of normal operations;
 - c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. the total duration of any visible emission incident; and
 - e. any corrective actions taken to eliminate the visible emissions.
3. The permittee shall maintain monthly records of the amount (tons of corn per month and total tons of corn, to date for the calendar year) material throughput for this emissions unit.

D. Reporting Requirements

Issued: To be entered upon final issuance

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the stack(s) serving this emissions unit (b) identify all days during which any visible fugitive particulate emissions were observed from the egress points serving this emissions unit (c) describe any corrective actions taken to eliminate the visible particulate emissions from the baghouse stack and (d) describe any corrective actions taken to eliminate the visible fugitive particulate emissions from the egress points serving this emissions unit. These reports shall be submitted to the Ohio EPA, NWDO by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall submit annual records that summarize the total annual corn throughput for this emissions unit, in tons. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

E. Testing Requirements

1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. The emission testing shall be conducted within 60 days after achieving the maximum production rate at which the emissions unit will be operated, but not later than 180 days after initial startup of such emissions unit.
 - b. The emission testing shall be conducted to demonstrate compliance with the grain receiving baghouse outlet emission rate of 0.0050 gr/dscf.
 - c. The following test methods shall be employed to demonstrate compliance with the above emissions limitations: for PM10, 40 CFR Part 51, Appendix M, Methods 201 and 202. Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA, NWDO.
 - d. The test(s) shall be conducted while the emissions unit is operating at its maximum capacity, unless otherwise specified or approved by the Ohio EPA, NWDO.
 - e. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, NWDO. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to

Emissions Unit ID: **P901**

submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, NWDO's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA, NWDO shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report of the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA, NWDO within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, NWDO.

2. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation: 0.005 gr PM10/dscf of exhaust gas for the grain receiving baghouse

Applicable Compliance Method:

Compliance with the grain loading of 0.0050 gr/dscf shall be demonstrated based on the results of emission testing conducted in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M and 40 CFR Part 60, Appendix A, Methods 1-4 (volumetric air flow rate). Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA, NWDO.

- b. Emission Limitation: 8.63 TPY PM10

Compliance with the annual allowable PM10 emission limitation shall be demonstrated using the following calculation based on the baghouse design and a maximum operating schedule of 8760 hrs/yr:

$$= [(0.005 \text{ gr/dscf} \times 30,000 \text{ dscfm}) + (0.010 \text{ gr/dscf} \times 4000 \text{ dscfm}) + (0.010 \text{ gr/dscf} \times 4000 \text{ dscfm})] \times 1 \text{ lb/7000 gr} \times 60 \text{ min/hour} \times 8760 \text{ hours/yr} \times 0.0005 \text{ ton/lb} = 8.63 \text{ tons/year}$$

Therefore, as long as compliance with the 0.0050 gr/dscf is maintained, compliance with the annual PM10 limitation shall be ensured.

Issued: To be entered upon final issuance

- c. Emission Limitation: Fugitive PE shall not exceed 4.04 tons/yr, fugitive PM10 shall not exceed 0.90 tons/yr.

Applicable Compliance Method:

The annual emission limitations above were developed by the following calculations using the AP-42 emission factors (Section 9.9.1-1, revised March 2003) and the maximum corn throughput.

= 1,153,558 ton/yr x 0.035 lb PE/ton x 0.0005 ton/lb x 0.2 (80% capture efficiency) = 4.04 tons PE/year

= 1,153,558 ton/yr x 0.0078 lb PM10/ton x 0.0005 ton/lb x 0.2 (80% capture efficiency) = 0.90 tons PM10/year

Therefore, provided compliance is shown with the maximum annual corn throughput, compliance with the annual emission limitation will be assumed.

- d. Emission Limitation: Visible PE from the baghouse stack(s) shall not exceed 0% opacity, as a 6-minute average.

Applicable Compliance Method:

Compliance shall be determined according to test Method 9 of 40 CFR Part 60, Appendix A.

- e. Emission Limitation: Visible fugitive PE shall not exceed 5% opacity, as a 3-minute average, from any truck or rail unloading.

Applicable Compliance Method:

Compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

- f. Emission Limitation: Visible fugitive PE shall not exceed 0% opacity, as a 3-minute average, from any grain receiving operations.

Applicable Compliance Method:

Compliance with the visible emission limitation shall be determined in

Emissions Unit ID: **P901**

accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P902) - DDGS reclaim and storage

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(C)	<p><u>Stack Emissions</u></p> <p>The baghouse(s) shall achieve an outlet emission rate of not greater than 0.0050 grains of particulate matter equal to or less than 10 microns in size (PM10) per dry standard cubic foot of exhaust gases (gr/dscf).</p> <p>PM10 emissions shall not exceed 0.38 tons per year (TPY).</p> <p>Visible particulate emissions (PE) from the stack(s) serving this emissions unit shall not exceed 0% opacity as a six minute average.</p> <p><u>Fugitive Emissions</u></p> <p>Fugitive PE shall not exceed 0.12 TPY.</p> <p>Fugitive PM10 emissions shall not exceed 0.030 TPY.</p> <p>Visible fugitive PE shall not exceed 5% opacity as a three minute average.</p> <p>See Sections A.2.a and A.2.d.</p>
OAC rule 3745-17-07(B)	See Section A.2.b.
OAC rule 3745-17-08(A)	See Section A.2.c.
OAC rule 3745-17-07(A)	See Section A.2.e.
OAC rule 3745-17-11(B)	See Section A.2.e.

Issued: To be entered upon final issuance

Emissions Unit ID: **P902**

Issued: To be entered upon final issuance

2. Additional Terms and Conditions

- 2.a** The permit to install for this air contaminant source takes into account the use of a baghouse (DDGS reclaim baghouse) and partial enclosure to control PM10 emissions, whenever this air contaminant source is in operation, as a voluntary restriction as proposed by the permittee for the purpose of avoiding Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3).
- 2.b** This emissions unit is exempt from the visible PE limitation specified in OAC rule 3745-17-07(B), pursuant to OAC rule 3745-17-07(B)(11)(e).
- 2.c** This emissions unit is not located in an "Appendix A" area as identified in OAC rule 3745-17-08. Therefore, pursuant to OAC rule 3745-17-8(A), this emissions unit is exempt from the requirements of OAC rule 3745-17-08(B).
- 2.d** For the purposes of this permit, all stack PE is considered to be PM10.
- 2.e** The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

- 1. The maximum annual amount of dried distillers goods with solubles (DDGS) processed in this emissions unit shall not exceed 360,036 tons.
- 2. The permittee shall operate the baghouse(s) at all times when this emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the baghouse stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log, as well as the date and time the daily check was performed. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. the color of the emissions;
 - b. the total duration of any visible emission incident; and
 - c. any corrective actions taken to eliminate the visible emissions.

Emissions Unit ID: P902

2. The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible fugitive particulate emissions from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit. The presence or absence of any visible fugitive emissions shall be noted in an operations log, as well as the date and time the daily check was performed. If visible fugitive emissions are observed, the permittee shall also note the following in the operations log:
 - a. the color of the emissions;
 - b. whether the emissions are representative of normal operations;
 - c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. the total duration of any visible emission incident; and
 - e. any corrective actions taken to eliminate the visible emissions.
3. The permittee shall maintain monthly records of the amount of DDGS processed in this emissions unit (in tons per month and total tons, to date for the calendar year).

D. Reporting Requirements

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the baghouse stack serving this emissions unit (b) identify all days during which any visible fugitive particulate emissions were observed from the egress points serving this emissions unit (c) describe any corrective actions taken to eliminate the visible particulate emissions from the baghouse stack and (d) describe any corrective actions taken to eliminate the visible fugitive particulate emissions from the egress points serving this emissions unit. These reports shall be submitted to the Ohio EPA, NWDO by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall submit reports that summarize the total annual amount of DDGS processed in this emissions unit. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

E. Testing Requirements

1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. The emission testing shall be conducted within 60 days after achieving the

Issued: To be entered upon final issuance

maximum production rate at which the emissions unit will be operated, but not later than 180 days after initial startup of such emissions unit.

- b. The emission testing shall be conducted to demonstrate compliance with the baghouse grain loading of 0.005 gr/dscf.
- c. The following test methods shall be employed to demonstrate compliance with the above emissions limitations: for PM10, 40 CFR Part 51, Appendix M, Methods 201 and 202 and 40 CFR Part 60, Appendix A, Methods 1-4 (volumetric air flow rate). Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA, NWDO.
- d. The test(s) shall be conducted while the emissions unit is operating at its maximum capacity, unless otherwise specified or approved by the Ohio EPA, NWDO.
- e. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, NWDO. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, NWDO's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA, NWDO shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report of the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA, NWDO within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, NWDO.

- 2. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emission Limitation: The baghouse shall achieve an outlet emission rate of not greater than 0.005 grain of particulate emissions per dry standard

Emissions Unit ID: P902

cubic foot of exhaust gases.

Applicable Compliance Method:

Compliance with the grain loading of 0.005 gr/dscf shall be demonstrated based on the results of emission testing conducted in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M. Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA, NWDO.

- b. Emission Limitations: PM10 from the baghouse stack shall not exceed 0.38 TPY.

Applicable Compliance Method:

Compliance with the annual allowable PM10 emission limitation shall be demonstrated using the following calculation based on the bag house design and a maximum operating schedule of 8760 hrs/yr:

$$= 0.005 \text{ gr/dscf} \times 1 \text{ lb/7000 gr} \times 2,000 \text{ dscfm} \times 60 \text{ min/hour} \times 8760 \text{ hours/yr} \times 0.0005 \text{ ton/lb} = 0.38 \text{ tons/year}$$

Therefore, as long as compliance with the 0.0050 gr/dscf is maintained, compliance with the annual PM10 limitation shall be ensured.

- c. Emission Limitation: Visible particulate emissions from the baghouse stack shall not exceed 0% opacity, as a 6-minute average.

Applicable Compliance Method:

Compliance shall be determined according to test Method 9 as set forth in the "Appendix on Test Methods" in 40 CFR Part 60 "Standards of Performance for New Stationary Sources."

- d. Emission Limitation: Visible fugitive particulate emissions shall not exceed 5% opacity, as a 3-minute average.

Applicable Compliance Method:

Compliance with the visible emission limitation shall be determined in

Issued: To be entered upon final issuance

accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

- e. Emission Limitations: Fugitive PE shall not exceed 0.12TPY;
Fugitive PM10 shall not exceed 0.03 TPY.

Applicable Compliance Method:

The annual emission limitations above were developed by the following calculations using the AP-42 emission factors (Section 9.9.1-2, revised March 2003) and the maximum annual amount of DDGS processed.

= 360,036 ton/yr x 0.0033 lb PM/ton x 0.0005 ton/lb x 0.2 (80% capture efficiency) = 0.12 tons PE/year

= 360,036 ton/yr x 0.0008 lb PM/ton x 0.0005 ton/lb x 0.2 (80% capture efficiency) = 0.03 tons PE/year

Therefore, provided compliance is shown with the maximum annual amount of DDGS processed, compliance with the annual emission limitation will be assumed.

F. Miscellaneous Requirements

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

Emissions Unit ID: P903

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P903) - DDGS loadout (rail and truck)

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(C)	<p><u>Stack Emissions:</u> The baghouse(s) shall achieve an outlet emission rate of not greater than 0.0050 grain of particulate emissions equal to or less than 10 microns in size (PM10) per dry standard cubic foot of exhaust gases (gr/dscf).</p> <p>PE shall not exceed 1.13 tpy.</p> <p>Visible particulate emissions (PE) from the stack(s) serving this emissions unit shall not exceed 0% opacity as a 6-minute average.</p> <p><u>Fugitive Emissions:</u> Fugitive PE shall not exceed 0.12 TPY.</p> <p>Fugitive PM10 emissions shall not exceed 0.03 TPY.</p> <p>Visible fugitive PE shall not exceed 5% opacity, as a 3-minute average, from DDGS loadout.</p> <p>See sections A.2.a and A.2.d.</p>
OAC rule 3745-17-07(B)	See sections A.2.b.
OAC rule 3745-17-08(A)	See sections A.2.c.
OAC rule 3745-17-07(A)	See sections A.2.e.
OAC rule 3745-17-11(B)	See sections A.2.e.

2. Additional Terms and Conditions

- 2.a The permit to install for this air contaminant source takes into account the use of three baghouses and a partial enclosure* (with a maximum outlet grain loading

Issued: To be entered upon final issuance

of 0.0050 gr PM10/dscf for the baghouse) to control PM10 emissions, whenever this air contaminant source is in operation, as a voluntary restriction as proposed by the permittee for the purpose of avoiding Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3).

*for DDGS rail and truck load out, the use of partial enclosures and a baghouse

- 2.b** This emissions unit is exempt from the visible particulate emission limitation specified in OAC rule 3745-17-07(B), pursuant to OAC rule 3745-17-07(B)(11)(e).
- 2.c** This emissions unit is not located within an "Appendix A" area as identified in OAC rule 3745-17-08. Therefore, pursuant to OAC rule 3745-17-08(A), this emissions unit is exempt from the requirements of OAC rule 3745-17-08(B).
- 2.d** For the purposes of this permit, all stack PE is considered to be PM10.
- 2.e** The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

- 1. The permittee shall operate the baghouse(s) at all times when this emissions unit is in operation.

C. Monitoring and/or Record keeping Requirements

- 1. The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the baghouse stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log, as well as the date and time the daily check was performed. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. the color of the emissions;
 - b. the total duration of any visible emission incident; and
 - c. any corrective actions taken to eliminate the visible emissions.
- 2. The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible fugitive particulate emissions from

Emissions Unit ID: **P903**

Issued: To be entered upon final issuance

the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit. The presence or absence of any visible fugitive emissions shall be noted in an operations log, as well as the date and time the daily check was performed. If visible fugitive emissions are observed, the permittee shall also note the following in the operations log:

Emissions Unit ID: **P903**

- a. the color of the emissions;
- b. whether the emissions are representative of normal operations;
- c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;
- d. the total duration of any visible emission incident; and
- e. any corrective actions taken to eliminate the visible emissions.

D. Reporting Requirements

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the baghouse stack serving this emissions unit (b) identify all days during which any visible fugitive particulate emissions were observed from the egress points serving this emissions unit (c) describe any corrective actions taken to eliminate the visible particulate emissions from the baghouse stack and (d) describe any corrective actions taken to eliminate the visible fugitive particulate emissions from the egress points serving this emissions unit. These reports shall be submitted to the Ohio EPA, NWDO by January 31 and July 31 of each year and shall cover the previous 6-month period.

E. Testing Requirements

1. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. The emission testing shall be conducted within 60 days after achieving the maximum production rate at which the emissions unit will be operated, but not later than 180 days after initial startup of such emissions unit.
 - b. The emission testing shall be conducted to demonstrate compliance with the baghouse(s) grain loading of 0.0050 gr/dscf.
 - c. The following test methods shall be employed to demonstrate compliance with the above emissions limitations: for PM₁₀, 40 CFR Part 51, Appendix M, Methods 201 and 202 and 40 CFR Part 60, Appendix A, Methods 1-4 (volumetric air flow rate). Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA, NWDO.
 - d. The test(s) shall be conducted while the emissions unit is operating at its maximum capacity, unless otherwise specified or approved by the Ohio EPA, NWDO.

Issued: To be entered upon final issuance

- e. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, NWDO. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, NWDO's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA, NWDO shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report of the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA, NWDO within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, NWDO.

2. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation: The baghouse shall achieve an outlet emission rate of not greater than 0.0050 grain of particulate emissions per dry standard cubic foot of exhaust gases.

Applicable Compliance Method:

Compliance with the grain loading of 0.0050 gr/dscf shall be demonstrated based on the results of emission testing conducted in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M. Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA, NWDO.

- b. Emission Limitations: PM10 from the baghouse stack shall not exceed 1.13 TPY.

Applicable Compliance Method:

Compliance with the annual allowable PM10 emission limitation shall be demonstrated using the following calculation based on the bag house design

Emissions Unit ID: P903

and a maximum operating schedule of 8760 hrs/yr:

$$= 0.0050 \text{ gr/dscf} \times 1 \text{ lb/7000 gr} \times 6000 \text{ dscfm (3 stacks at 2000 dscfm)} \times 60 \text{ min/hour} \times 8760 \text{ hours/yr} \times 0.0005 \text{ ton/lb} = 0.38 \text{ tons/year}$$

Therefore, as long as compliance with the 0.0050 gr/dscf is maintained, compliance with the annual PM10 limitation shall be ensured.

- c. Emission Limitation: Visible particulate emissions from the baghouse stack(s) shall not exceed 0% opacity, as a 6-minute average.

Applicable Compliance Method:

Compliance shall be determined according to test Method 9 as set forth in the "Appendix on Test Methods" in 40 CFR Part 60 "Standards of Performance for New Stationary Sources."

- d. Emission Limitation: Visible fugitive particulate emissions shall not exceed 5% opacity, as a 3-minute average, from DDGS loadout.

Applicable Compliance Method:

Compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

- e. Emission Limitation: Fugitive PE shall not exceed 0.12 TPY; fugitive PM10 shall not exceed 0.03 TPY.

Applicable Compliance Method:

The annual emission limitations above were developed by the following calculation using the AP-42 emission factor (Section 9.9.1-2, revised March 2003) and the maximum amount of DDGS processed in emissions unit P902:

$$= 360,036 \text{ ton/yr} \times 0.0033 \text{ lb PM/ton} \times 0.0005 \text{ ton/lb} \times 0.20 \text{ (80\% capture efficiency)} = 0.12 \text{ tons PE/year}$$

$$= 360,036 \text{ ton/yr} \times 0.0008 \text{ lbPM10/ton} \times 0.0005 \text{ ton/lb} \times 0.20 \text{ (80\% capture efficiency)} = 0.03 \text{ ton PM10/year}$$

Issued: To be entered upon final issuance

Therefore, provided compliance is shown with the maximum annual amount of DDGS processed in emissions unit P902, compliance with the annual emission limitation will be assumed.

F. Miscellaneous Requirements

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (T001) - 100,000 gallon storage tank (200-proof ethanol)

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(C)	<p>Volatile organic compounds (VOC) shall not exceed 0.25 ton per year (TPY)</p> <p>See A.2.a.</p>
40 CFR, Part 60, Subpart Kb	See A.2.o.
OAC rule 3745-21-09(L)	See A.2.n.

2. Additional Terms and Conditions

- 2.a** The permit to install for this air contaminant source takes into account the use of an internal floating roof and a maximum material throughput of 55,000,000 gallons to control VOC emissions, whenever this air contaminant source is in operation, as a voluntary restriction as proposed by the permittee for the purpose of avoiding Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3).

Issued: To be entered upon final issuance

- 2.b** The fixed roof storage tank shall be equipped with an internal floating roof.
- 2.c** The automatic bleeder vents shall be closed at all times except when the roof is floated off or landed on the roof leg supports, and the rim vents, if provided, shall be set to open when the roof is being floated off the roof leg supports or is at the manufacturer's recommended setting.
- 2.d** All openings, except stub drains, shall be equipped with a cover, seal or lid which is to be in a closed position at all times except when in actual use for tank gauging or sampling.
- 2.e** The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal floating roof shall be floating on the liquid surface at all times, except during initial fill and during those intervals when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible.
- 2.f** Each internal floating roof shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof:
- i. A foam- or liquid-filled seal mounted in contact with the liquid (liquid-mounted seal). A liquid-mounted seal means a foam- or liquid-filled seal mounted in contact with the liquid between the wall of the storage vessel and the floating roof continuously around the circumference of the tank.
 - ii. Two seals mounted one above the other so that each forms a continuous closure that completely covers the space between the wall of the storage vessel and the edge of the internal floating roof. The lower seal may be vapor-mounted, but both must be continuous.
 - iii. A mechanical shoe seal. A mechanical shoe seal is a metal sheet held vertically against the wall of the storage vessel by springs or weighted levers and is connected by braces to the floating roof. A flexible coated fabric (envelope) spans the annular space between the metal sheet and the floating roof.
- 2.g** Each opening in a non-contact internal floating roof except for automatic bleeder vents (vacuum breaker vents) and the rim space vents is to provide a projection

Emissions Unit ID: T001

below the liquid surface.

- 2.h** Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use.
- 2.i** Automatic bleeder vents shall be equipped with a gasket and are to be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports.
- 2.j** Rim space vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting.
- 2.k** Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The sample well shall have a slit fabric cover that covers at least 90 percent of the opening.
- 2.l** Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover.
- 2.m** Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover.
- 2.n** OAC rule 3745-21-09(L) is not applicable because this tank does not store petroleum liquids as defined in OAC rule 3745-21-01 (E)(13).
- 2.o** The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-02(A).

B. Operational Restrictions

1. The permittee shall not exceed an annual material throughput rate of 55,000,000 gallons.
2. The maximum true vapor pressure of organic liquid stored in this storage tank shall not

Issued: To be entered upon final issuance

exceed 0.754 pound per square inch absolute.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain records of the following information:
 - a. The types of petroleum liquids stored in the tank.
 - b. The maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 0.754 pound per square inch absolute. Available data on the storage temperature may be used to determine the maximum true vapor pressure as in the following:
 - i. For vessels operated above or below ambient temperatures, the maximum true vapor pressure is calculated based upon the highest expected calendar-month average of the storage temperature. For vessels operated at ambient temperatures, the maximum true vapor pressure is calculated based upon the maximum local monthly average ambient temperature as reported by the National Weather Service.
 - ii. For refined petroleum products the vapor pressure may be obtained by the following:
 - (a) Available data on the Reid vapor pressure and the maximum expected storage temperature based on the highest expected calendar-month average temperature of the stored product may be used to determine the maximum true vapor pressure from nomographs contained in API Bulletin 2517 (incorporated by reference--see Sec. 60.17), unless the Ohio EPA, NWDO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s).
 - (b) The true vapor pressure of each type of crude oil with a Reid vapor pressure less than 13.8 kPa or with physical properties that preclude determination by the recommended method is to be determined from available data and recorded if the estimated maximum true vapor pressure is greater than 3.5 kPa.
 - iii. For other liquids, the vapor pressure:

- (a) May be obtained from standard reference texts, or
 - (b) Determined by ASTM Method D2879-83 (incorporated by reference--see Sec. 60.17); or
 - (c) Measured by an appropriate method approved by the Ohio EPA, NWDO; or
 - (d) Calculated by an appropriate method approved by the Ohio EPA, NWDO.
2. Visually inspect the internal floating roof, the primary seal, and the secondary seal (if one is in service), prior to filling the storage vessel with VOL. If there are holes, tears, or other openings in the primary seal, the secondary seal, or the seal fabric or defects in the internal floating roof, or both, the owner or operator shall repair the items before filling the storage vessel.
3. For vessels equipped with a liquid-mounted or mechanical shoe primary seal, the permittee shall visually inspect the internal floating roof and the primary seal or the secondary seal (if one is in service) through manholes and roof hatches on the fixed roof at least once every 12 months after initial fill. If the internal floating roof is not resting on the surface of the VOL inside the storage vessel, or there is liquid accumulated on the roof, or the seal is detached, or there are holes or tears in the seal fabric, the owner or operator shall repair the items or empty and remove the storage vessel from service within 45 days. If a failure that is detected during inspections required in this paragraph cannot be repaired within 45 days and if the vessel cannot be emptied within 45 days, a 30-day extension may be requested from Ohio EPA, NWDO in the inspection report required in D.3. Such a request for an extension must document that alternate storage capacity is unavailable and specify a schedule of actions the company will take that will assure that the control equipment will be repaired or the vessel will be emptied as soon as possible.
4. For vessels equipped with a double-seal system as specified in A.2.f.ii:
 - a. The permittee shall visually inspect the vessel as specified in C.5 at least every 5 years; or
 - b. The permittee shall visually inspect the vessel as specified in C.3.
5. The permittee shall visually inspect the internal floating roof, the primary seal, the secondary seal (if one is in service), gaskets, slotted membranes and sleeve seals (if any) each time the storage vessel is emptied and degassed. If the internal floating roof has defects, the primary seal has holes, tears, or other openings in the seal or the seal

Issued: To be entered upon final issuance

fabric, or the secondary seal has holes, tears, or other openings in the seal or the seal fabric, or the gaskets no longer close off the liquid surfaces from the atmosphere, or the slotted membrane has more than 10 percent open area, the owner or operator shall repair the items as necessary so that none of the conditions specified in this paragraph exist before refilling the storage vessel with VOL. In no event shall inspections conducted in accordance with this provision occur at intervals greater than 10 years in the case of vessels conducting the annual visual inspection as specified in C.3 and C.4.b and at intervals no greater than 5 years in the case of vessels specified in C.4.a.

6. The owner or operator shall keep copies of all reports and records required in D.2, D.3, and D.4, for at least 2 years.
7. The permittee shall keep a record of each inspection performed as required by C.2, C.3, C.4, and C.5. Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment (seals, internal floating roof, and fittings).
8. The owner or operator shall keep copies of all records required by C.2 through C.8, for at least 2 years.
9. The owner or operator shall keep readily accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel (shall be kept for the life of the source).
10. The permittee shall maintain monthly records of the amount of (gallons per month and total gallons, to date for the calendar year) of material throughput for this emissions unit.

D. Reporting Requirements

1. The permittee shall notify the Ohio EPA, NWDO in writing at least 30 days prior to the filling or refilling of each storage vessel for which an inspection is required by C.2 and C.5 to afford the Ohio EPA, NWDO the opportunity to have an observer present. If the inspection required by C.5 is not planned and the owner or operator could not have known about the inspection 30 days in advance or refilling the tank, the owner or operator shall notify the Ohio EPA, NWDO at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so that it is received by the Ohio EPA, NWDO at least 7 days prior to the refilling.
2. The permittee shall furnish the Ohio EPA, NWDO with a report that describes the control equipment and certifies that the control equipment meets the specifications of A.2.e through A.2.m and C.2. This report shall be an attachment to the notification of the actual date of initial startup of an affected facility postmarked within 15 days after such date.
3. If any of the conditions described in C.3 are detected during the annual visual inspection required by C.3, a report shall be furnished to the Ohio EPA, NWDO within 30 days of the inspection. Each report shall identify the storage vessel, the nature of the defects, and the date the storage vessel was emptied or the nature of and date the repair was made.
4. After each inspection required by C.4 that finds holes or tears in the seal or seal fabric, or defects in the internal floating roof, or other control equipment defects listed in C.4.b, a report shall be furnished to the Ohio EPA, NWDO within 30 days of the inspection. The report shall identify the storage vessel and the reason it did not meet the specifications of A.2.e through A.2.m or C.4 and list each repair made.
5. If the permittee placed, stored, or held in this emissions unit any petroleum liquid with a true vapor pressure which was greater than 0.754 pounds per square inch absolute, the permittee shall notify the Ohio EPA, NWDO within 30 days of becoming aware of the occurrence.
6. The permittee shall submit records that summarize the total annual material throughput for this emissions unit. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

Issued: To be entered upon final issuance

E. Testing Requirements

1. Compliance with the emission limitations in section A.1 of the terms and conditions of this permit shall be determined in accordance with the following methods:

Emission Limitation: 0.25 TPY of VOC

Applicable Compliance Method:

The permittee shall demonstrate compliance with the annual allowable VOC emission limitation by rim seal loss, withdraw loss and deck fitting loss calculations as determined by U.S. EPA Tanks 4.0 program with a maximum annual material throughput of 55,000,000 gallons.

F. Miscellaneous Requirements

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (T002) - 100,000 gallon storage tank (200-proof ethanol)

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(C)	<p>Volatile organic compounds (VOC) shall not exceed 0.25 ton per year (TPY)</p> <p>See A.2.a.</p>
40 CFR, Part 60, Subpart Kb	See A.2.o.
OAC rule 3745-21-09(L)	See A.2.n.

2. Additional Terms and Conditions

- 2.a The permit to install for this air contaminant source takes into account the use of an internal floating roof and a maximum material throughput of 55,000,000 gallons to control VOC emissions, whenever this air contaminant source is in operation, as a voluntary restriction as proposed by the permittee for the purpose of avoiding Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3).
- 2.b The fixed roof storage tank shall be equipped with an internal floating roof.
- 2.c The automatic bleeder vents shall be closed at all times except when the roof is floated off or landed on the roof leg supports, and the rim vents, if provided, shall be set to open when the roof is being floated off the roof leg supports or is at the manufacturer's recommended setting.
- 2.d All openings, except stub drains, shall be equipped with a cover, seal or lid which is to be in a closed position at all times except when in actual use for tank gauging or sampling.
- 2.e The internal floating roof shall rest or float on the liquid surface (but not

Issued: To be entered upon final issuance

necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal floating roof shall be floating on the liquid surface at all times, except during initial fill and during those intervals when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible.

- 2.f** Each internal floating roof shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof:
- i. A foam- or liquid-filled seal mounted in contact with the liquid (liquid-mounted seal). A liquid-mounted seal means a foam- or liquid-filled seal mounted in contact with the liquid between the wall of the storage vessel and the floating roof continuously around the circumference of the tank.
 - ii. Two seals mounted one above the other so that each forms a continuous closure that completely covers the space between the wall of the storage vessel and the edge of the internal floating roof. The lower seal may be vapor-mounted, but both must be continuous.
 - iii. A mechanical shoe seal. A mechanical shoe seal is a metal sheet held vertically against the wall of the storage vessel by springs or weighted levers and is connected by braces to the floating roof. A flexible coated fabric (envelope) spans the annular space between the metal sheet and the floating roof.
- 2.g** Each opening in a non-contact internal floating roof except for automatic bleeder vents (vacuum breaker vents) and the rim space vents is to provide a projection below the liquid surface.
- 2.h** Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use.
- 2.i** Automatic bleeder vents shall be equipped with a gasket and are to be closed at all times when the roof is floating except when the roof is being floated off or is

Emissions Unit ID: T002

being landed on the roof leg supports.

- 2.j Rim space vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting.
- 2.k Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The sample well shall have a slit fabric cover that covers at least 90 percent of the opening.
- 2.l Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover.
- 2.m Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover.
- 2.n OAC rule 3745-21-09(L) is not applicable because this tank does not store petroleum liquids as defined in OAC rule 3745-21-01 (E)(13).
- 2.o The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-02(A).

B. Operational Restrictions

1. The permittee shall not exceed an annual material throughput rate of 55,000,000 gallons.
2. The maximum true vapor pressure of organic liquid stored in this storage tank shall not exceed 0.754 pound per square inch absolute.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain records of the following information:
 - a. The types of petroleum liquids stored in the tank.
 - b. The maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 0.754 pound per square inch absolute. Available data on the storage temperature may be used to determine the maximum true vapor pressure as in

Issued: To be entered upon final issuance

the following:

- i. For vessels operated above or below ambient temperatures, the maximum true vapor pressure is calculated based upon the highest expected calendar-month average of the storage temperature. For vessels operated at ambient temperatures, the maximum true vapor pressure is calculated based upon the maximum local monthly average ambient temperature as reported by the National Weather Service.
 - ii. For refined petroleum products the vapor pressure may be obtained by the following:
 - (a) Available data on the Reid vapor pressure and the maximum expected storage temperature based on the highest expected calendar-month average temperature of the stored product may be used to determine the maximum true vapor pressure from nomographs contained in API Bulletin 2517 (incorporated by reference--see Sec. 60.17), unless the Ohio EPA, NWDO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s).
 - (b) The true vapor pressure of each type of crude oil with a Reid vapor pressure less than 13.8 kPa or with physical properties that preclude determination by the recommended method is to be determined from available data and recorded if the estimated maximum true vapor pressure is greater than 3.5 kPa.
 - iii. For other liquids, the vapor pressure:
 - (a) May be obtained from standard reference texts, or
 - (b) Determined by ASTM Method D2879-83 (incorporated by reference--see Sec. 60.17); or
 - (c) Measured by an appropriate method approved by the Ohio EPA, NWDO; or
 - (d) Calculated by an appropriate method approved by the Ohio EPA, NWDO.
2. Visually inspect the internal floating roof, the primary seal, and the secondary seal (if one is in service), prior to filling the storage vessel with VOL. If there are holes, tears,

Issued: To be entered upon final issuance

- or other openings in the primary seal, the secondary seal, or the seal fabric or defects in the internal floating roof, or both, the owner or operator shall repair the items before filling the storage vessel.
3. For vessels equipped with a liquid-mounted or mechanical shoe primary seal, the permittee shall visually inspect the internal floating roof and the primary seal or the secondary seal (if one is in service) through manholes and roof hatches on the fixed roof at least once every 12 months after initial fill. If the internal floating roof is not resting on the surface of the VOL inside the storage vessel, or there is liquid accumulated on the roof, or the seal is detached, or there are holes or tears in the seal fabric, the owner or operator shall repair the items or empty and remove the storage vessel from service within 45 days. If a failure that is detected during inspections required in this paragraph cannot be repaired within 45 days and if the vessel cannot be emptied within 45 days, a 30-day extension may be requested from Ohio EPA, NWDO in the inspection report required in D.3. Such a request for an extension must document that alternate storage capacity is unavailable and specify a schedule of actions the company will take that will assure that the control equipment will be repaired or the vessel will be emptied as soon as possible.
 4. For vessels equipped with a double-seal system as specified in A.2.f.ii:
 - a. The permittee shall visually inspect the vessel as specified in C.5 at least every 5 years; or
 - b. The permittee shall visually inspect the vessel as specified in C.3.
 5. The permittee shall visually inspect the internal floating roof, the primary seal, the secondary seal (if one is in service), gaskets, slotted membranes and sleeve seals (if any) each time the storage vessel is emptied and degassed. If the internal floating roof has defects, the primary seal has holes, tears, or other openings in the seal or the seal fabric, or the secondary seal has holes, tears, or other openings in the seal or the seal fabric, or the gaskets no longer close off the liquid surfaces from the atmosphere, or the slotted membrane has more than 10 percent open area, the owner or operator shall repair the items as necessary so that none of the conditions specified in this paragraph exist before refilling the storage vessel with VOL. In no event shall inspections conducted in accordance with this provision occur at intervals greater than 10 years in the case of vessels conducting the annual visual inspection as specified in C.3 and C.4.b and at intervals no greater than 5 years in the case of vessels specified in C.4.a.
 6. The owner or operator shall keep copies of all reports and records required in D.2, D.3, and D.4, for at least 2 years.

Emissions Unit ID: **T002**

7. The permittee shall keep a record of each inspection performed as required by C.2, C.3, C.4, and C.5. Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment (seals, internal floating roof, and fittings).
8. The owner or operator shall keep copies of all records required by C.2 through C.8, for at least 2 years.
9. The owner or operator shall keep readily accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel (shall be kept for the life of the source).
10. The permittee shall maintain monthly records of the amount of (gallons per month and total gallons, to date for the calendar year) of material throughput for this emissions unit.

Issued: To be entered upon final issuance**D. Reporting Requirements**

1. The permittee shall notify the Ohio EPA, NWDO in writing at least 30 days prior to the filling or refilling of each storage vessel for which an inspection is required by C.2 and C.5 to afford the Ohio EPA, NWDO the opportunity to have an observer present. If the inspection required by C.5 is not planned and the owner or operator could not have known about the inspection 30 days in advance or refilling the tank, the owner or operator shall notify the Ohio EPA, NWDO at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so that it is received by the Ohio EPA, NWDO at least 7 days prior to the refilling.
2. The permittee shall furnish the Ohio EPA, NWDO with a report that describes the control equipment and certifies that the control equipment meets the specifications of A.2.e through A.2.m and C.2. This report shall be an attachment to the notification of the actual date of initial startup of an affected facility postmarked within 15 days after such date.
3. If any of the conditions described in C.3 are detected during the annual visual inspection required by C.3, a report shall be furnished to the Ohio EPA, NWDO within 30 days of the inspection. Each report shall identify the storage vessel, the nature of the defects, and the date the storage vessel was emptied or the nature of and date the repair was made.
4. After each inspection required by C.4 that finds holes or tears in the seal or seal fabric, or defects in the internal floating roof, or other control equipment defects listed in C.4.b, a report shall be furnished to the Ohio EPA, NWDO within 30 days of the inspection. The report shall identify the storage vessel and the reason it did not meet the specifications of A.2.e through A.2.m or C.4 and list each repair made.
5. If the permittee placed, stored, or held in this emissions unit any petroleum liquid with a true vapor pressure which was greater than 0.754 pounds per square inch absolute, the permittee shall notify the Ohio EPA, NWDO within 30 days of becoming aware of the occurrence.
6. The permittee shall submit records that summarize the total annual material throughput for this emissions unit. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

E. Testing Requirements

1. Compliance with the emission limitations in section A.1 of the terms and conditions of this permit shall be determined in accordance with the following methods:

Emission Limitation: 0.25 TPY of VOC

Applicable Compliance Method:

The permittee shall demonstrate compliance with the annual allowable VOC emission limitation by rim seal loss, withdraw loss and deck fitting loss calculations as determined by U.S. EPA Tanks 4.0 program with a maximum annual material throughput of 55,000,000 gallons.

F. Miscellaneous Requirements

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (T003) - 75,000 gallon storage tank (denaturant)

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(C)	Volatile organic compounds (VOC) shall not exceed 0.75 ton per year (TPY) .
40 CFR, Part 60, Subpart Kb	See A.2.b through A.2.m.
OAC rule 3745-21-09(L)	See A.2.n.

2. Additional Terms and Conditions

- 2.a The permit to install for this air contaminant source takes into account the use of a ventless delivery system for the unloading of gasoline to this storage tank , an internal floating roof and a maximum material throughput of 5,500,000 gallons to control VOC emissions, whenever this air contaminant source is in operation, as a voluntary restriction as proposed by the permittee for the purpose of avoiding Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3).
- 2.b The fixed roof storage tank shall be equipped with an internal floating roof.
- 2.c The automatic bleeder vents shall be closed at all times except when the roof is floated off or landed on the roof leg supports, and the rim vents, if provided, shall be set to open when the roof is being floated off the roof leg supports or is at the manufacturer's recommended setting.
- 2.d All openings, except stub drains, shall be equipped with a cover, seal or lid which is to be in a closed position at all times except when in actual use for tank gauging or sampling.
- 2.e The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed

Issued: To be entered upon final issuance

roof. The internal floating roof shall be floating on the liquid surface at all times, except during initial fill and during those intervals when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible.

- 2.f** Each internal floating roof shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof:
- i. A foam- or liquid-filled seal mounted in contact with the liquid (liquid-mounted seal). A liquid-mounted seal means a foam- or liquid-filled seal mounted in contact with the liquid between the wall of the storage vessel and the floating roof continuously around the circumference of the tank.
 - ii. Two seals mounted one above the other so that each forms a continuous closure that completely covers the space between the wall of the storage vessel and the edge of the internal floating roof. The lower seal may be vapor-mounted, but both must be continuous.
 - iii. A mechanical shoe seal. A mechanical shoe seal is a metal sheet held vertically against the wall of the storage vessel by springs or weighted levers and is connected by braces to the floating roof. A flexible coated fabric (envelope) spans the annular space between the metal sheet and the floating roof.
- 2.g** Each opening in a non-contact internal floating roof except for automatic bleeder vents (vacuum breaker vents) and the rim space vents is to provide a projection below the liquid surface.
- 2.h** Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use.
- 2.i** Automatic bleeder vents shall be equipped with a gasket and are to be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports.

Emissions Unit ID: **T003**

- 2.j** Rim space vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting.
- 2.k** Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The sample well shall have a slit fabric cover that covers at least 90 percent of the opening.
- 2.l** Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover.
- 2.m** Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover.
- 2.n** OAC rule 3745-21-09(L) is not applicable because this tank does not store petroleum liquids as defined in OAC rule 3745-21-01 (E)(13).
- 2.o** The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-02(A).

B. Operational Restrictions

- 1. The permittee shall not exceed an annual material throughput rate of 5,500,000 gallons.
- 2. The maximum true vapor pressure of organic liquid stored in this storage tank shall not exceed 11.11 pound per square inch absolute.

C. Monitoring and/or Record keeping Requirements

- 1. The permittee shall maintain records of the following information:
 - a. The types of petroleum liquids stored in the tank.
 - b. The maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 11.11 pound per square inch absolute. Available data on the storage temperature may be used to determine the maximum true vapor pressure as in the following:

Issued: To be entered upon final issuance

- i. For vessels operated above or below ambient temperatures, the maximum true vapor pressure is calculated based upon the highest expected calendar-month average of the storage temperature. For vessels operated at ambient temperatures, the maximum true vapor pressure is calculated based upon the maximum local monthly average ambient temperature as reported by the National Weather Service.
 - ii. For refined petroleum products the vapor pressure may be obtained by the following:
 - (a) Available data on the Reid vapor pressure and the maximum expected storage temperature based on the highest expected calendar-month average temperature of the stored product may be used to determine the maximum true vapor pressure from nomographs contained in API Bulletin 2517 (incorporated by reference--see Sec. 60.17), unless the Ohio EPA, NWDO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s).
 - (b) The true vapor pressure of each type of crude oil with a Reid vapor pressure less than 13.8 kPa or with physical properties that preclude determination by the recommended method is to be determined from available data and recorded if the estimated maximum true vapor pressure is greater than 3.5 kPa.
 - iii. For other liquids, the vapor pressure:
 - (a) May be obtained from standard reference texts, or
 - (b) Determined by ASTM Method D2879-83 (incorporated by reference--see Sec. 60.17); or
 - (c) Measured by an appropriate method approved by the Ohio EPA, NWDO; or
 - (d) Calculated by an appropriate method approved by the Ohio EPA, NWDO.
2. Visually inspect the internal floating roof, the primary seal, and the secondary seal (if one is in service), prior to filling the storage vessel with VOL. If there are holes, tears, or other openings in the primary seal, the secondary seal, or the seal fabric or defects

Emissions Unit ID: T003

in the internal floating roof, or both, the owner or operator shall repair the items before filling the storage vessel.

3. For vessels equipped with a liquid-mounted or mechanical shoe primary seal, the permittee shall visually inspect the internal floating roof and the primary seal or the secondary seal (if one is in service) through manholes and roof hatches on the fixed roof at least once every 12 months after initial fill. If the internal floating roof is not resting on the surface of the VOL inside the storage vessel, or there is liquid accumulated on the roof, or the seal is detached, or there are holes or tears in the seal fabric, the owner or operator shall repair the items or empty and remove the storage vessel from service within 45 days. If a failure that is detected during inspections required in this paragraph cannot be repaired within 45 days and if the vessel cannot be emptied within 45 days, a 30-day extension may be requested from the Ohio EPA, NWDO in the inspection report required in D.3. Such a request for an extension must document that alternate storage capacity is unavailable and specify a schedule of actions the company will take that will assure that the control equipment will be repaired or the vessel will be emptied as soon as possible.
4. For vessels equipped with a double-seal system as specified in A.2.f.ii:
 - a. The permittee shall visually inspect the vessel as specified in C.5 at least every 5 years; or
 - b. The permittee shall visually inspect the vessel as specified in C.3.
5. The permittee shall visually inspect the internal floating roof, the primary seal, the secondary seal (if one is in service), gaskets, slotted membranes and sleeve seals (if any) each time the storage vessel is emptied and degassed. If the internal floating roof has defects, the primary seal has holes, tears, or other openings in the seal or the seal fabric, or the secondary seal has holes, tears, or other openings in the seal or the seal fabric, or the gaskets no longer close off the liquid surfaces from the atmosphere, or the slotted membrane has more than 10 percent open area, the owner or operator shall repair the items as necessary so that none of the conditions specified in this paragraph exist before refilling the storage vessel with VOL. In no event shall inspections conducted in accordance with this provision occur at intervals greater than 10 years in the case of vessels conducting the annual visual inspection as specified in C.3 and C.4.b and at intervals no greater than 5 years in the case of vessels specified in C.4.a.
6. The owner or operator shall keep copies of all reports and records required in D.2, D.3, and D.4, for at least 2 years.
7. The permittee shall keep a record of each inspection performed as required by C.2,

Issued: To be entered upon final issuance

C.3, C.4, and C.5. Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment (seals, internal floating roof, and fittings).

8. The owner or operator shall keep copies of all records required by C.2 through C.8, for at least 2 years.
9. The owner or operator shall keep readily accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel (shall be kept for the life of the source).
10. The permittee shall maintain monthly records of the amount of (gallons per month and total gallons, to date for the calendar year) of material throughput for this emissions unit.

D. Reporting Requirements

1. The permittee shall notify the Ohio EPA, NWDO in writing at least 30 days prior to the filling or refilling of each storage vessel for which an inspection is required by C.2 and C.5 to afford the Ohio EPA, NWDO the opportunity to have an observer present. If the inspection required by C.5 is not planned and the owner or operator could not have known about the inspection 30 days in advance or refilling the tank, the owner or operator shall notify the Ohio EPA, NWDO at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so that it is received by the Ohio EPA, NWDO at least 7 days prior to the refilling.
2. The permittee shall furnish the Ohio EPA, NWDO with a report that describes the control equipment and certifies that the control equipment meets the specifications of A.2.e through A.2.m and C.2. This report shall be an attachment to the notification of the actual date of initial startup of an affected facility postmarked within 15 days after such date.
3. If any of the conditions described in C.3 are detected during the annual visual inspection required by C.3, a report shall be furnished to the Ohio EPA, NWDO within 30 days of the inspection. Each report shall identify the storage vessel, the nature of

Emissions Unit ID: **T003**

the defects, and the date the storage vessel was emptied or the nature of and date the repair was made.

4. After each inspection required by C.4 that finds holes or tears in the seal or seal fabric, or defects in the internal floating roof, or other control equipment defects listed in C.4.b, a report shall be furnished to the Ohio EPA, NWDO within 30 days of the inspection. The report shall identify the storage vessel and the reason it did not meet the specifications of A.2.e through A.2.m or C.4 and list each repair made.
5. If the permittee placed, stored, or held in this emissions unit any petroleum liquid with a true vapor pressure which was greater than 11.11 pounds per square inch absolute, the permittee shall notify the Ohio EPA, NWDO within 30 days of becoming aware of the occurrence.
6. The permittee shall submit records that summarize the total annual material throughput for this emissions unit. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

E. Testing Requirements

1. Compliance with the emission limitations in section A.1 of the terms and conditions of this permit shall be determined in accordance with the following methods:

Emission Limitation: 0.75 TPY of VOC

Applicable Compliance Method:

The permittee shall demonstrate compliance with the annual allowable VOC emission limitation by rim seal loss, withdraw loss and deck fitting loss calculations as determined by U.S. EPA Tanks 4.0 program with a maximum annual material throughput of 5,500,000 gallons.

F. Miscellaneous Requirements

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (T004) - one million gallon storage tank (denatured ethanol)

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(C)	Volatile organic compounds (VOC) shall not exceed 0.21 ton per year (TPY) .
40 CFR, Part 60, Subpart Kb	See A.2.o.
OAC rule 3745-21-09(L)	See A.2.n.

2. Additional Terms and Conditions

- 2.a The permit to install for this air contaminant source takes into account the use of an internal floating roof and a maximum material throughput of 115,500,000 gallons to control VOC emissions, whenever this air contaminant source is in operation, as a voluntary restriction as proposed by the permittee for the purpose of avoiding Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3).
- 2.b The fixed roof storage tank shall be equipped with an internal floating roof.
- 2.c The automatic bleeder vents shall be closed at all times except when the roof is floated off or landed on the roof leg supports, and the rim vents, if provided, shall be set to open when the roof is being floated off the roof leg supports or is at the manufacturer's recommended setting.
- 2.d All openings, except stub drains, shall be equipped with a cover, seal or lid which is to be in a closed position at all times except when in actual use for tank gauging or sampling.
- 2.e The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed

Emissions Unit ID: T004

roof. The internal floating roof shall be floating on the liquid surface at all times, except during initial fill and during those intervals when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible.

- 2.f** Each internal floating roof shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof:
- i. A foam- or liquid-filled seal mounted in contact with the liquid (liquid-mounted seal). A liquid-mounted seal means a foam- or liquid-filled seal mounted in contact with the liquid between the wall of the storage vessel and the floating roof continuously around the circumference of the tank.
 - ii. Two seals mounted one above the other so that each forms a continuous closure that completely covers the space between the wall of the storage vessel and the edge of the internal floating roof. The lower seal may be vapor-mounted, but both must be continuous.
 - iii. A mechanical shoe seal. A mechanical shoe seal is a metal sheet held vertically against the wall of the storage vessel by springs or weighted levers and is connected by braces to the floating roof. A flexible coated fabric (envelope) spans the annular space between the metal sheet and the floating roof.
- 2.g** Each opening in a non-contact internal floating roof except for automatic bleeder vents (vacuum breaker vents) and the rim space vents is to provide a projection below the liquid surface.
- 2.h** Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use.
- 2.i** Automatic bleeder vents shall be equipped with a gasket and are to be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports.

Issued: To be entered upon final issuance

- 2.j** Rim space vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting.
- 2.k** Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The sample well shall have a slit fabric cover that covers at least 90 percent of the opening.
- 2.l** Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover.
- 2.m** Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover.
- 2.n** OAC rule 3745-21-09(L) is not applicable because this tank does not store petroleum liquids as defined in OAC rule 3745-21-01 (E)(13).
- 2.o** The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-02(A).

B. Operational Restrictions

- 1. The permittee shall not exceed an annual material throughput rate of 115,500,000 gallons.
- 2. The maximum true vapor pressure of organic liquid stored in this storage tank shall not exceed 0.754 pound per square inch absolute.

C. Monitoring and/or Record keeping Requirements

- 1. The permittee shall maintain records of the following information:
 - a. The types of petroleum liquids stored in the tank.
 - b. The maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 0.754 pound per square inch absolute. Available data on the storage temperature may be used to determine the maximum true vapor pressure as in

the following:

- i. For vessels operated above or below ambient temperatures, the maximum true vapor pressure is calculated based upon the highest expected calendar-month average of the storage temperature. For vessels operated at ambient temperatures, the maximum true vapor pressure is calculated based upon the maximum local monthly average ambient temperature as reported by the National Weather Service.
 - ii. For refined petroleum products the vapor pressure may be obtained by the following:
 - (a) Available data on the Reid vapor pressure and the maximum expected storage temperature based on the highest expected calendar-month average temperature of the stored product may be used to determine the maximum true vapor pressure from nomographs contained in API Bulletin 2517 (incorporated by reference--see Sec. 60.17), unless the Ohio EPA, NWDO specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s).
 - (b) The true vapor pressure of each type of crude oil with a Reid vapor pressure less than 13.8 kPa or with physical properties that preclude determination by the recommended method is to be determined from available data and recorded if the estimated maximum true vapor pressure is greater than 3.5 kPa.
 - iii. For other liquids, the vapor pressure:
 - (a) May be obtained from standard reference texts, or
 - (b) Determined by ASTM Method D2879-83 (incorporated by reference--see Sec. 60.17); or
 - (c) Measured by an appropriate method approved by the Ohio EPA, NWDO; or
 - (d) Calculated by an appropriate method approved by the Ohio EPA, NWDO.
2. Visually inspect the internal floating roof, the primary seal, and the secondary seal (if one is in service), prior to filling the storage vessel with VOL. If there are holes, tears, or other openings in the primary seal, the secondary seal, or the seal fabric or defects

Issued: To be entered upon final issuance

in the internal floating roof, or both, the owner or operator shall repair the items before filling the storage vessel.

3. For vessels equipped with a liquid-mounted or mechanical shoe primary seal, the permittee shall visually inspect the internal floating roof and the primary seal or the secondary seal (if one is in service) through manholes and roof hatches on the fixed roof at least once every 12 months after initial fill. If the internal floating roof is not resting on the surface of the VOL inside the storage vessel, or there is liquid accumulated on the roof, or the seal is detached, or there are holes or tears in the seal fabric, the owner or operator shall repair the items or empty and remove the storage vessel from service within 45 days. If a failure that is detected during inspections required in this paragraph cannot be repaired within 45 days and if the vessel cannot be emptied within 45 days, a 30-day extension may be requested from Ohio EPA, NWDO in the inspection report required in D.3. Such a request for an extension must document that alternate storage capacity is unavailable and specify a schedule of actions the company will take that will assure that the control equipment will be repaired or the vessel will be emptied as soon as possible.
4. For vessels equipped with a double-seal system as specified in A.2.f.ii:
 - a. The permittee shall visually inspect the vessel as specified in C.5 at least every 5 years; or
 - b. The permittee shall visually inspect the vessel as specified in C.3.
5. The permittee shall visually inspect the internal floating roof, the primary seal, the secondary seal (if one is in service), gaskets, slotted membranes and sleeve seals (if any) each time the storage vessel is emptied and degassed. If the internal floating roof has defects, the primary seal has holes, tears, or other openings in the seal or the seal fabric, or the secondary seal has holes, tears, or other openings in the seal or the seal fabric, or the gaskets no longer close off the liquid surfaces from the atmosphere, or the slotted membrane has more than 10 percent open area, the owner or operator shall repair the items as necessary so that none of the conditions specified in this paragraph exist before refilling the storage vessel with VOL. In no event shall inspections conducted in accordance with this provision occur at intervals greater than 10 years in the case of vessels conducting the annual visual inspection as specified in C.3 and C.4.b and at intervals no greater than 5 years in the case of vessels specified in C.4.a.
6. The owner or operator shall keep copies of all reports and records required in D.2, D.3, and D.4, for at least 2 years.

Emissions Unit ID: T004

7. The permittee shall keep a record of each inspection performed as required by C.2, C.3, C.4, and C.5. Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment (seals, internal floating roof, and fittings).
8. The owner or operator shall keep copies of all records required by C.2 through C.8, for at least 2 years.
9. The owner or operator shall keep readily accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel (shall be kept for the life of the source).
10. The permittee shall maintain monthly records of the amount of (gallons per month and total gallons, to date for the calendar year) of material throughput for this emissions unit.

Issued: To be entered upon final issuance**D. Reporting Requirements**

1. The permittee shall notify the Ohio EPA, NWDO in writing at least 30 days prior to the filling or refilling of each storage vessel for which an inspection is required by C.2 and C.5 to afford the Ohio EPA, NWDO the opportunity to have an observer present. If the inspection required by C.5 is not planned and the owner or operator could not have known about the inspection 30 days in advance or refilling the tank, the owner or operator shall notify the Ohio EPA, NWDO at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so that it is received by the Ohio EPA, NWDO at least 7 days prior to the refilling.
2. The permittee shall furnish the Ohio EPA, NWDO with a report that describes the control equipment and certifies that the control equipment meets the specifications of A.2.e through A.2.m and C.2. This report shall be an attachment to the notification of the actual date of initial startup of an affected facility postmarked within 15 days after such date.
3. If any of the conditions described in C.3 are detected during the annual visual inspection required by C.3, a report shall be furnished to the Ohio EPA, NWDO within 30 days of the inspection. Each report shall identify the storage vessel, the nature of the defects, and the date the storage vessel was emptied or the nature of and date the repair was made.
4. After each inspection required by C.4 that finds holes or tears in the seal or seal fabric, or defects in the internal floating roof, or other control equipment defects listed in C.4.b, a report shall be furnished to the Ohio EPA, NWDO within 30 days of the inspection. The report shall identify the storage vessel and the reason it did not meet the specifications of A.2.e through A.2.m or C.4 and list each repair made.
5. If the permittee placed, stored, or held in this emissions unit any petroleum liquid with a true vapor pressure which was greater than 0.754 pounds per square inch absolute, the permittee shall notify the Ohio EPA, NWDO within 30 days of becoming aware of the occurrence.
6. The permittee shall submit records that summarize the total annual material throughput for this emissions unit. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

E. Testing Requirements

1. Compliance with the emission limitations in section A.1 of the terms and conditions of this permit shall be determined in accordance with the following methods:

Emission Limitation: 0.21 TPY of VOC

Applicable Compliance Method:

The permittee shall demonstrate compliance with the annual allowable VOC emission limitation by rim seal loss, withdraw loss and deck fitting loss calculations as determined by U.S. EPA Tanks 4.0 program with a maximum annual material throughput of 115,500,000 gallons.

F. Miscellaneous Requirements

1. Construction and/or operation of this facility shall not commence until all required permits/written authorizations are received from Ohio EPA. Authorizations must be received at a minimum from the Division of Solid and Infectious Waste Management, Division of Surface Water, and Division of Hazardous Waste Management.

Emissions Unit ID: T004

SIC CODE 2869 SCC CODE 1-02-006-01 EMISSIONS UNIT ID B001
 EMISSIONS UNIT DESCRIPTION 92.4 mmBtu/hr natural gas fired boiler
 DATE INSTALLED 7/1/2007

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			0.69	3.02
PM ₁₀	attainment			0.69	3.02
Sulfur Dioxide	attainment	0.05	0.24		
Organic Compounds	attainment			0.50	2.19
Nitrogen Oxides	attainment			0.020 lb/mmBtu of actual heat input	8.10
Carbon Monoxide	attainment			1.66	7.27
Lead	attainment		0.000198		
Other: Air Toxics hexane formaldehyde		0.16 0.01	0.70 0.04		

APPLICABLE FEDERAL RULES:

NSPS? _____ NESHAP? Db,VV, kb PSD? _____ OFFSET POLICY? _____

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? yes
 OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ _____

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? x YES _____ NO _____

IDENTIFY THE AIR CONTAMINANTS: hexane and formaldehyde

Emissions Unit ID: T004

SIC CODE 2869 SCC CODE 1-02-006-01 EMISSIONS UNIT ID B002
 EMISSIONS UNIT DESCRIPTION 92.4 mmBtu/hr natural gas fired boiler
 DATE INSTALLED 7/1/2007

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			0.69	3.02
PM ₁₀	attainment			0.69	3.02
Sulfur Dioxide	attainment	0.05	0.24		
Organic Compounds	attainment			0.50	2.19
Nitrogen Oxides	attainment			0.020 lb/mmBtu of actual heat input	8.10
Carbon Monoxide	attainment			1.66	7.27
Lead	attainment		0.000198		
Other: Air Toxics		0.16 0.01	0.70 0.04		

APPLICABLE FEDERAL RULES:

NSPS? _____ NESHAP? Db, VV, kb PSD? _____ OFFSET POLICY? _____

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? yes
 OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ _____

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? x YES _____ NO _____

IDENTIFY THE AIR CONTAMINANTS: hexane and formaldehyde

Emissions Unit ID: T004

SIC CODE 2869 SCC CODE 1-02-006-01 EMISSIONS UNIT ID B003
 EMISSIONS UNIT DESCRIPTION 92.4 mmBtu/hr natural gas fired boiler
 DATE INSTALLED 7/1/2007

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			0.69	3.02
PM ₁₀	attainment			0.69	3.02
Sulfur Dioxide	attainment	0.05	0.24		
Organic Compounds	attainment			0.50	2.19
Nitrogen Oxides	attainment			0.020 lb/mmBtu of actual heat input	8.10
Carbon Monoxide	attainment			1.66	7.27
Lead	attainment		0.000198		
Other: Air Toxics		0.16 0.01	0.70 0.04		

APPLICABLE FEDERAL RULES:

NSPS? _____ NESHAP? Db, VV, kb PSD? _____ OFFSET POLICY? _____

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? yes
 OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ _____

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? x YES _____ NO _____

IDENTIFY THE AIR CONTAMINANTS: hexane and formaldehyde

Port Clinton Biofuels, Inc.
 PTI Application: 03-17224
 Issued: To be entered upon final issuance

Facility ID: 0362010154

Emissions Unit ID: T004

SIC CODE 2869 SCC CODE 1-02-006-01 EMISSIONS UNIT ID B004
 EMISSIONS UNIT DESCRIPTION 92.4 mmBtu/hr natural gas fired boiler
 DATE INSTALLED 7/1/2007

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			0.69	3.02
PM ₁₀	attainment			0.69	3.02
Sulfur Dioxide	attainment	0.05	0.24		
Organic Compounds	attainment			0.50	2.19
Nitrogen Oxides	attainment			0.020 lb/mmBtu of actual heat input	8.10
Carbon Monoxide	attainment			1.66	7.27
Lead	attainment		0.000198		
Other: Air Toxics		0.16 0.01	0.70 0.04		

APPLICABLE FEDERAL RULES:

NSPS? _____ NESHAP? Db, VV, kb PSD? _____ OFFSET POLICY? _____

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? yes
 OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ _____

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? x YES _____ NO _____

IDENTIFY THE AIR CONTAMINANTS: hexane and formaldehyde

Emissions Unit ID: **T004**

Issued: To be entered upon final issuance

SIC CODE 2869 SCC CODE 2-29-400-00 EMISSIONS UNIT ID F001
 EMISSIONS UNIT DESCRIPTION Paved Roadways and Parking Areas
 DATE INSTALLED 7/1/2007

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment				32.98
PM ₁₀	attainment				6.34
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? _____ NESHAP? **Db, VV, kb** PSD? _____ OFFSET POLICY? _____

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? no
 OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES _____ NO

IDENTIFY THE AIR CONTAMINANTS: _____

Port Clinton Biofuels, Inc.
 PTI Application: 03-17224
 Issued: To be entered upon final issuance

Facility ID: 0362010154

Emissions Unit ID: T004

SIC CODE 2869 SCC CODE 4-04-002-50 EMISSIONS UNIT ID J001
 EMISSIONS UNIT DESCRIPTION Ethanol and gasoline loading operations
 DATE INSTALLED 7/1/2007

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			6.8*	29.78*
PM ₁₀	attainment			6.8*	29.78*
Sulfur Dioxide	attainment			15.0*	65.70*
Organic Compounds	attainment			10.0*	43.80*
Nitrogen Oxides	attainment			12.96*	56.76*
Carbon Monoxide	attainment				
Lead					
Other: Air Toxics					

*TOTAL COMBINED FOR EMISSIONS UNIT J001, P007, P009, AND P010

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? **Db, VV, kb** PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? yes
 OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? x YES NO

IDENTIFY THE AIR CONTAMINANTS: _____

Emissions Unit ID: **T004**

Issued: To be entered upon final issuance

SIC CODE SCC CODE EMISSIONS UNIT ID
 EMISSIONS UNIT DESCRIPTION
 DATE INSTALLED

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			0.010 gr/dscf	1.50
PM ₁₀	attainment			0.010 gr/dscf	1.50
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? Db,VV, kb PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?
 OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT?

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

Port Clinton Biofuels, Inc.
 PTI Application: 03-17224
 Issued: To be entered upon final issuance

Facility ID: 0362010154

Emissions Unit ID: T004

SIC CODE SCC CODE EMISSIONS UNIT ID
 EMISSIONS UNIT DESCRIPTION
 DATE INSTALLED

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			0.0050 gr/dscf	1.13
PM ₁₀	attainment			0.0050 gr/dscf	1.13
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?
 OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT?

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

Port Clinton Biofuels, Inc.
 PTI Application: 03-17224
 Issued: To be entered upon final issuance

Facility ID: 0362010154

Emissions Unit ID: T004

SIC CODE SCC CODE EMISSIONS UNIT ID
 EMISSIONS UNIT DESCRIPTION
 DATE INSTALLED

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			0.0050 gr/dscf	1.13
PM ₁₀	attainment			0.0050 gr/dscf	1.13
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? Db,VV, kb PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT?

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

Emissions Unit ID: **T004**

Issued: To be entered upon final issuance

SIC CODE SCC CODE EMISSIONS UNIT ID
 EMISSIONS UNIT DESCRIPTION
 DATE INSTALLED

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			0.0050 gr/dscf	1.13
PM ₁₀	attainment			0.0050 gr/dscf	1.13
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? Db,VV, kb PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT?

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

Port Clinton Biofuels, Inc.
 PTI Application: 03-17224
 Issued: To be entered upon final issuance

Facility ID: 0362010154

Emissions Unit ID: T004

SIC CODE SCC CODE EMISSIONS UNIT ID
 EMISSIONS UNIT DESCRIPTION
 DATE INSTALLED

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			0.0050 gr/dscf	1.13
PM ₁₀	attainment			0.0050 gr/dscf	1.13
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? Db,VV, kb PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT?

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

Emissions Unit ID: **T004**

Issued: To be entered upon final issuance

SIC CODE SCC CODE EMISSIONS UNIT ID
 EMISSIONS UNIT DESCRIPTION
 DATE INSTALLED

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			0.0050 gr/dscf	0.56
PM ₁₀	attainment			0.0050 gr/dscf	0.56
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? Db,VV, kb PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?
 OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT?

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

Port Clinton Biofuels, Inc.
 PTI Application: 03-17224
 Issued: To be entered upon final issuance

Facility ID: 0362010154

Emissions Unit ID: T004

SIC CODE 2869 SCC CODE 3-01-250-99 EMISSIONS UNIT ID P007
 EMISSIONS UNIT DESCRIPTION distillation operations and liquefaction tanks
 DATE INSTALLED 7/1/2007

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			6.8*	29.78*
PM ₁₀	attainment			6.8*	29.78*
Sulfur Dioxide	attainment			15.0*	65.70*
Organic Compounds	attainment			10.0*	43.80*
Nitrogen Oxides	attainment			12.96*	56.76*
Carbon Monoxide	attainment				
Lead					
Other: Air Toxics					

*COMBINED FOR J001, P007, P009 AND P010

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? **Db, VV, kb** PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES _____ NO

IDENTIFY THE AIR CONTAMINANTS: _____

Port Clinton Biofuels, Inc.
 PTI Application: 03-17224
 Issued: To be entered upon final issuance

Facility ID: 0362010154

Emissions Unit ID: T004

SIC CODE SCC CODE EMISSIONS UNIT ID
 EMISSIONS UNIT DESCRIPTION
 DATE INSTALLED

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter					
PM ₁₀					
Sulfur Dioxide					
Organic Compounds	attainment			8.0	35.04
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? Db, VV, kb PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT?

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

Emissions Unit ID: **T004**

Issued: To be entered upon final issuance

SIC CODE 2869 SCC CODE 3-01-250-99 EMISSIONS UNIT ID P009
 EMISSIONS UNIT DESCRIPTION DDGS drying and cooling no. 1 (90 mmBtu/hr natural gas fired dryer)
 DATE INSTALLED 7/1/2007

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			6.8*	29.78*
PM ₁₀	attainment			6.8*	29.78*
Sulfur Dioxide	attainment			15.0*	65.70*
Organic Compounds	attainment			10.0*	43.80*
Nitrogen Oxides	attainment			12.96*	56.76*
Carbon Monoxide	attainment				
Lead					
Other: Air Toxics					

*COMBINED FOR J001, P007, P009 AND P010

APPLICABLE FEDERAL RULES:

NSPS? _____ NESHAP? **Db, VV, kb** PSD? _____ OFFSET POLICY? _____

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? _____

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ _____

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES _____ NO

IDENTIFY THE AIR CONTAMINANTS: _____

Port Clinton Biofuels, Inc.
 PTI Application: 03-17224
 Issued: To be entered upon final issuance

Facility ID: 0362010154

Emissions Unit ID: T004

SIC CODE 2869 SCC CODE 3-01-250-99 EMISSIONS UNIT ID P010
 EMISSIONS UNIT DESCRIPTION DDGS drying and cooling no. 2 (90 mmBtu/hr natural gas fired dryer)
 DATE INSTALLED 7/1/2007

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			6.8*	29.78*
PM ₁₀	attainment			6.8*	29.78*
Sulfur Dioxide	attainment			15.0*	65.70*
Organic Compounds	attainment			10.0*	43.80*
Nitrogen Oxides	attainment			12.96*	56.76*
Carbon Monoxide	attainment				
Lead					
Other: Air Toxics					

*COMBINED FOR J001, P007, P009 AND P010

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? **Db, VV, kb** PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES _____ NO

IDENTIFY THE AIR CONTAMINANTS: _____

Port Clinton Biofuels, Inc.
 PTI Application: 03-17224
 Issued: To be entered upon final issuance

Facility ID: 0362010154

Emissions Unit ID: T004

SIC CODE SCC CODE EMISSIONS UNIT ID
 EMISSIONS UNIT DESCRIPTION
 DATE INSTALLED

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			0.38	1.66
PM ₁₀	attainment			0.38	1.66
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT?

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

Emissions Unit ID: T004

SIC CODE 2869 SCC CODE 2-02-004-01 EMISSIONS UNIT ID P012
 EMISSIONS UNIT DESCRIPTION emergency generator
 DATE INSTALLED 7/1/2007

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			1.70	0.04 tons per rolling 12-month period
PM ₁₀	attainment	1.56	0.04		
Sulfur Dioxide	attainment			13.60	0.34 tons per rolling 12-month period
Organic Compounds	attainment			2.64	0.07 tons per rolling 12-month period
Nitrogen Oxides	attainment			56.84	1.42 tons per rolling 12-month period
Carbon Monoxide	attainment			70.02	1.75 tons per rolling 12-month period
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? IIII NESHAP? PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? _____

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ _____

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES _____ NO

IDENTIFY THE AIR CONTAMINANTS: _____

Port Clinton Biofuels, Inc.
PTI Application: 03-17224
Issued: To be entered upon final issuance

Facility ID: 0362010154

Emissions Unit ID: T004

Emissions Unit ID: **T004**

Issued: To be entered upon final issuance

SIC CODE 2869 SCC CODE 2-02-004-01 EMISSIONS UNIT ID P013
 EMISSIONS UNIT DESCRIPTION emergency water pump
 DATE INSTALLED 7/1/2007

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment			0.26	0.03 tons per rolling 12-month period
PM ₁₀	attainment			0.26	0.03 tons per rolling 12-month period
Sulfur Dioxide	attainment			0.59	0.06 tons per rolling 12-month period
Organic Compounds	attainment			0.64	0.06 tons per rolling 12-month period
Nitrogen Oxides	attainment			4.99	0.50 tons per rolling 12-month period
Carbon Monoxide	attainment			1.66	0.17 tons per rolling 12-month period
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? **Db,VV, kb** PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

TOXIC AIR CONTAMINANTS

Emissions Unit ID: **T004**

Issued: To be entered upon final issuance

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*?

YES

NO

IDENTIFY THE AIR CONTAMINANTS:

Emissions Unit ID: **T004**

Issued: To be entered upon final issuance

SIC CODE SCC CODE EMISSIONS UNIT ID
 EMISSIONS UNIT DESCRIPTION
 DATE INSTALLED

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter					
PM ₁₀					
Sulfur Dioxide					
Organic Compounds	attainment				3.48
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? Db,VV, kb PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT?

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

Port Clinton Biofuels, Inc.
 PTI Application: 03-17224
 Issued: To be entered upon final issuance

Facility ID: 0362010154

Emissions Unit ID: T004

SIC CODE SCC CODE EMISSIONS UNIT ID
 EMISSIONS UNIT DESCRIPTION
 DATE INSTALLED

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter					
PM ₁₀					
Sulfur Dioxide					
Organic Compounds	attainment				3.85
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? Db, VV, kb PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT?

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

Port Clinton Biofuels, Inc.
 PTI Application: 03-17224
 Issued: To be entered upon final issuance

Facility ID: 0362010154

Emissions Unit ID: T004

SIC CODE 2869 SCC CODE 3-02-005-51 EMISSIONS UNIT ID P901
 EMISSIONS UNIT DESCRIPTION grain receiving, transferring, conveying and storage
 DATE INSTALLED 7/1/2007

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment				12.67
PM ₁₀	attainment				9.53
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? **Db, VV, kb** PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES _____ NO

IDENTIFY THE AIR CONTAMINANTS: _____

Emissions Unit ID: **T004**

Issued: To be entered upon final issuance

SIC CODE 2869 SCC CODE 3-02-250-999 EMISSIONS UNIT ID P902
 EMISSIONS UNIT DESCRIPTION DDGS reclaim and storage
 DATE INSTALLED 7/1/2007

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment				0.50
PM ₁₀	attainment				0.41
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? _____ NESHAP? **Db, VV, kb** PSD? _____ OFFSET POLICY? _____

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? _____

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ _____

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES _____ NO

IDENTIFY THE AIR CONTAMINANTS: _____

Port Clinton Biofuels, Inc.
 PTI Application: 03-17224
 Issued: To be entered upon final issuance

Facility ID: 0362010154

Emissions Unit ID: T004

SIC CODE SCC CODE EMISSIONS UNIT ID
 EMISSIONS UNIT DESCRIPTION
 DATE INSTALLED

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	attainment				1.25
PM ₁₀	attainment				1.16
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? Db, VV, kb PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT?

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

Emissions Unit ID: **T004**

Issued: To be entered upon final issuance

SIC CODE SCC CODE EMISSIONS UNIT ID
 EMISSIONS UNIT DESCRIPTION
 DATE INSTALLED

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter					
PM ₁₀					
Sulfur Dioxide					
Organic Compounds	attainment				0.25
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? Db,VV, kb PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT?

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

Port Clinton Biofuels, Inc.
 PTI Application: 03-17224
 Issued: To be entered upon final issuance

Facility ID: 0362010154

Emissions Unit ID: T004

SIC CODE 2869 SCC CODE 3-01-250-99 EMISSIONS UNIT ID T002
 EMISSIONS UNIT DESCRIPTION 100,000 gallon storage tank (200-proof ethanol)
 DATE INSTALLED 7/1/2007

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter					
PM ₁₀					
Sulfur Dioxide					
Organic Compounds	attainment				0.25
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? _____ NESHAP? **Db, VV, kb** PSD? _____ OFFSET POLICY? _____

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ _____

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES _____ NO

IDENTIFY THE AIR CONTAMINANTS: _____

Port Clinton Biofuels, Inc.
 PTI Application: 03-17224
 Issued: To be entered upon final issuance

Facility ID: 0362010154

Emissions Unit ID: T004

SIC CODE SCC CODE EMISSIONS UNIT ID
 EMISSIONS UNIT DESCRIPTION
 DATE INSTALLED

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter					
PM ₁₀					
Sulfur Dioxide					
Organic Compounds	attainment				0.75
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? Db,VV, kb PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT?

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

Emissions Unit ID: **T004****Issued: To be entered upon final issuance**

SIC CODE SCC CODE EMISSIONS UNIT ID
 EMISSIONS UNIT DESCRIPTION
 DATE INSTALLED

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter					
PM ₁₀					
Sulfur Dioxide					
Organic Compounds	attainment				0.21
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS?

NESHAP? **Db, VV, kb**

PSD?

OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT?

\$ **TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*?

 YES NOIDENTIFY THE AIR CONTAMINANTS: