



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL
PAULDING COUNTY**

CERTIFIED MAIL

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049

Application No: 03-14069

DATE: 11/10/2003

Deseret Grain Storage
James Williams
61 South 600 West
Kaysville, UT 84037

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, Ohio 43215

Sincerely,

Michael W. Ahern, Supervisor
Field Operations and Permit Section
Division of Air Pollution Control

cc: USEPA

NWDO



**Permit To Install
Terms and Conditions**

**Issue Date: 11/10/2003
Effective Date: 11/10/2003**

FINAL PERMIT TO INSTALL 03-14069

Application Number: 03-14069
APS Premise Number: 0363000041
Permit Fee: **\$3750**
Name of Facility: Deseret Grain Storage
Person to Contact: James Williams
Address: 61 South 600 West
Kaysville, UT 84037

Location of proposed air contaminant source(s) [emissions unit(s)]:
**14260 State Route 613 PO Box 89
Latty, Ohio**

Description of proposed emissions unit(s):
Grain receiving pits and loading station.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Deseret Grain Storage
PTI Application: 03-14069
Issued: 11/10/2003

Facility ID: 0363000041

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized

Deseret Grain Storage
PTI Application: 03-14069
Issued: 11/10/2003

Facility ID: 0363000041

representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions

Deseret Grain Storage
PTI Application: 03-14069
Issued: 11/10/2003

Facility ID: 0363000041

and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

Deseret Grain Storage
PTI Application: 03-14069
Issued: 11/10/2003

Facility ID: 0363000041

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
PE	4.61
PM ₁₀	0.86

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
F001 - Grain loading operations (truck/railcar)	OAC rule 3745-31-05(A)(3)	see A.2.a
		0.77 ton fugitive particulate emissions (PE)/year
		Visible fugitive PE shall not exceed 20% opacity, as a 3-minute average from truck/railcar loading operations
		0.26 ton fugitive particulate matter with diameter 10 microns or less (PM ₁₀)/year
	OAC rule 3745-17-07 (B)	See A.2.b
	OAC rule 3745-17-08(B)	See A.2.c

2. Additional Terms and Conditions

- 2.a The "Best Available Technology" (BAT) control requirements for emissions unit F001 has been determined to be the use of an adjustable chute for all truck/railcar loading operations. BAT requirements also include compliance with the terms and conditions of this permit.
- 2.b This emissions unit is exempt from the visible particulate emission limitations specified in OAC rule 3745-17-07(B) pursuant to OAC rule 3745-17-07(B)(11)(e).

- 2.c Deseret Grain Storage is not located within an "Appendix A" area as identified in OAC rule 3745-17-08. Therefore, pursuant to OAC rule 3745-17-08(A), this emissions unit is exempt from the requirements of OAC rule 3745-17-08.

B. Operational Restrictions

1. The maximum annual grain throughput for emissions unit F001 shall not exceed 72,000 tons.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the truck/railcar loading operations. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. the color and location of the emissions;
 - b. whether the emissions are representative of normal operations;
 - c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. the total duration of any visible emission incident; and,
 - e. any corrective actions taken to eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item (iv.) above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

D. Reporting Requirements

1. The permittee shall submit annual reports which identify any exceedance of the annual grain throughput limitation, as well as the corrective actions that were taken to achieve compliance. If no deviations occurred during the calendar year, the permittee shall submit an annual report, which states that no deviations occurred during that calendar year. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.
2. The permittee shall submit semiannual written reports that (a) identify all days during which any abnormal visible particulate emissions were observed from the truck/railcar loading operation and (b) describe any corrective actions taken to eliminate the abnormal visible particulate emissions.

Deseret Grain Storage
PTI Application: 03 14060
Issued

Facility ID: 0363000041

Emissions Unit ID: F001

These reports shall be submitted to the Director (the Northwest District Office) by January 31 and July 31 of each year and shall cover the previous 6-month period.

E. Testing Requirements

1. Compliance Methods Requirements: Compliance with the emission limitation(s) established in the Applicable Emissions Limitation section of this permit shall be determined in accordance with the following method(s):

- a. Emission Limitation
0.77 ton fugitive PE/year

Applicable Compliance Method

The emission limitation was established by multiplying an AP-42 emission factor of 0.086 lbs PE/ton grain (Section 9.9.1 (3/2003)) by a maximum annual grain throughput of 72,000 tons of grain, applying a control efficiency of 75% for adjustable chutes, and multiplying by a conversion factor of ton/2000 lbs. Therefore provided compliance is shown with the maximum annual grain throughput restriction, compliance with the annual emission limitation will be assumed.

- b. Emission Limitation
Visible fugitive PE shall not exceed 20% opacity, as a 3-minute average, from truck/railcar loading operations

Applicable Compliance Method

If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

- c. Emission Limitation
0.26 tons fugitive PM₁₀/year

Applicable Compliance Method

The emission limitation was established by multiplying an AP-42 emission factor of 0.029 lbs PM₁₀/ton grain (Section 9.9.1 (3/2003)) by a maximum annual grain throughput of 72,000 tons of grain, applying a control efficiency of 75% for adjustable chutes, and multiplying by a conversion factor of ton/2000 lbs. Therefore provided compliance is shown with the maximum annual grain throughput restriction, compliance with the annual emission limitation will be assumed.

F. Miscellaneous Requirements

12

Deser

PTI A

Issued: 11/10/2003

Emissions Unit ID: **F001**

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
P901 - grain receiving operations, includes (2) truck grain receiving pits and transferring/conveying	OAC rule 3745-31-05(A)(3)	OAC rule 3745-17-07 (B) OAC rule 3745-17-08(B)

Applicable Emissions
Limitations/Control Measures

Control requirements (see A.2.a)

Truck grain receiving:

2.74 lbs particulate emissions (PE)
per hr; 1.05 tons PE per year from
baghouse stack (see A.2.d)

Visible PE shall not exceed 0%
opacity as a six-minute average
from baghouse stack

0.81 ton fugitive PE per year

Visible fugitive PE shall not exceed
20% opacity, as a three-minute
average from truck grain receiving
operations

0.27 ton fugitive particulate matter
less than 10 microns in size (PM₁₀)
per year

Transferring/Conveying:

0.06 ton fugitive PE per year

Visible fugitive PE shall not exceed
5% opacity, as a three-minute
average from transferring/conveying

0.03 ton fugitive PM₁₀ per year

see A.2.b

see A.2.c

2. Additional Terms and Conditions

- 2.a** The "Best Available Technology" (BAT) control requirements for this emissions unit has been determined to be:
- i. use of a baghouse control system with a maximum outlet concentration of 0.02gr/dscf for truck grain receiving;
 - ii. use of a total enclosure for transferring/conveying
- BAT also includes compliance with the terms and conditions of this permit.
- 2.b** This emissions unit is exempt from the visible particulate emission limitations specified in OAC rule 3745-17-07(B) pursuant to OAC rule 3745-17-07(B)(11)(e).
- 2.c** Deseret Grain Storage is not located within an "Appendix A" area as identified in OAC rule 3745-17-08. Therefore, pursuant to OAC rule 3745-17-08(A), this emissions unit is exempt from the requirements of OAC rule 3745-17-08.
- 2.d** PE from the baghouse stack is inclusive of and assumed to be PM₁₀.

B. Operational Restrictions

1. The maximum annual grain throughput for emissions unit P901 shall not exceed 36,000 tons.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain monthly records of the amount of grain throughput for this emissions unit (in tons per month and total tons, to date for the calendar year).
2. The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for (a) any visible particulate emissions from the baghouse stack serving the truck grain receiving pits, (b) visible fugitive emissions from the truck grain receiving pits, and (c) any visible particulate emissions from transferring and conveying operations. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. for visible particulate emissions from the baghouse stack serving the truck grain receiving pits:
 - i. the color of the emissions;

- ii. the total duration of any visible emission incident; and
 - iii. any corrective actions taken to eliminate the visible emissions.
- b. for visible fugitive emissions from the truck grain receiving pits
- i. the location and color of the emissions;
 - ii. whether the emissions are representative of normal operations;
 - iii. if the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - iv. the total duration of any visible emission incident; and,
 - v. any corrective actions taken to eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item (iv) above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

- c. for visible particulate emissions from transfer/conveying operations:
- i. the color of the emissions;
 - ii. the total duration of any visible emission incident; and
 - iii. any corrective actions taken to eliminate the visible emissions.

D. Reporting Requirements

1. The permittee shall submit annual reports which identify any exceedance of the annual grain throughput limitation, as well as the corrective actions that were taken to achieve compliance. If no deviations occurred during the calendar year, the permittee shall submit an annual report, which states that no deviations occurred during that calendar year. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.
2. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the baghouse stack serving the truck grain receiving pits, (b) identify all days during which any abnormal visible fugitive particulate emissions

were observed from the truck grain receiving pits, and (c) identify all days during which any visible particulate emissions were observed from transferring and conveying operations and (c) describe any corrective actions taken to eliminate the visible particulate emissions and abnormal visible fugitive particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.

E. Testing Requirements

1. Compliance Methods Requirements: Compliance with the emission limitation(s) established in the Applicable Emissions Limitation section of this permit shall be determined in accordance with the following method(s):

- a. Emission Limitation:
0.02 gr/dscf from baghouse stack serving truck grain receiving pits

Applicable Compliance Method:

The emission limitation was established in accordance with the manufacturers guaranteed outlet grain loading. If required, compliance with this emission limitation shall be determined in accordance with the test methods and procedures in 40 CFR Part 60, Appendix A, Methods 1-5.

- b. Emission Limitation:
2.74 lbs PE/hour from baghouse stack serving truck grain receiving pits

Applicable Compliance Method

The permittee shall demonstrate compliance with the hourly emission limitation by multiplying the outlet grain concentration of 0.02 gr/dscf by a maximum volumetric flow rate of 16,000 dscfm, 60 minutes/hour, and 1 lb/7000 grains. If required, the permittee shall demonstrate compliance in accordance with the test methods and procedures in 40 CFR Part 60, Appendix A, Methods 1-5.

- c. Emission Limitation:
1.05 tons PE/year from baghouse stack serving truck grain receiving pits

Applicable Compliance Method

The emission limitation was developed by multiplying an AP-42 emission factor of 0.18 lbs PE/ton grain (Section 9.9.1 (3/2003)), a maximum annual grain throughput of 36,000 tons, applying an overall control efficiency of 67.5 % for the baghouse control system (75% capture efficiency - 90% removal efficiency), and multiplying by a conversion factor

Emissions Unit ID: P901

of ton/2000 lbs. Therefore provided compliance is shown with the annual grain throughput restriction, compliance with the annual limitation will be assumed.

- c. Emission Limitation:
Visible PE shall not exceed 0% opacity as a six-minute average from the baghouse stack serving the truck grain receiving pits

Applicable Compliance Method

If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources")

- d. Emission Limitation:
0.81 ton fugitive PE/year from truck grain receiving pits

Applicable Compliance Method

The emission limitation was developed by multiplying an AP-42 emission factor of 0.18 lbs PE/ton grain (Section 9.9.1 (3/2003)), a maximum annual grain throughput of 36,000 tons, applying a capture efficiency of 75% for the baghouse control system, and multiplying by a conversion factor of ton/2000 lbs. Therefore provided compliance is shown with the annual grain throughput restriction, compliance with the annual limitation will be assumed.

- e. Emission Limitation:
0.27 ton fugitive PM₁₀/year from truck grain receiving pits

Applicable Compliance Method

The emission limitation was developed by multiplying an AP-42 emission factor of 0.059 lbs PM₁₀/ton grain (Section 9.9.1 (3/2003)), a maximum annual grain throughput of 36,000 tons of grain, applying a capture efficiency of 75% for the baghouse control system, and multiplying by a conversion factor of ton/2000 lbs. Therefore provided compliance is shown with the annual grain throughput restriction, compliance with the annual limitation will be assumed.

- f. Emission Limitation:
0.06 tons fugitive PE/year from transferring/conveying

Applicable Compliance Method

The emission limitation was established by multiplying an AP-42 emission factor of 0.061 lbs PE/ton grain (Section 9.9.1 (3/2003)), a maximum annual grain throughput of 36,000 tons of grain, applying a control efficiency of 95% for total enclosure, and multiplying by a

conversion factor of ton/2000 lbs. Therefore provided compliance is shown with the annual grain throughput restriction, compliance with the annual limitation will be assumed.

- g. Emission Limitation:
0.03 ton fugitive PM₁₀/year from transferring/conveying

Applicable Compliance Method

The emission limitation was developed by multiplying an AP-42 emission factor of 0.034 lbs PM₁₀/ton grain (Section 9.9.1 (3/2003)), a maximum annual grain throughput of 36,000 tons of grain, applying a control efficiency of 95% for total enclosure, and multiplying by a conversion factor of ton/2000 lbs. Therefore provided compliance is shown with the annual grain throughput restriction, compliance with the annual limitation will be assumed.

- h. Emission Limitation:
Visible fugitive PE shall not exceed 20% opacity, as a three-minute average, from truck grain receiving pits

Applicable Compliance Method

If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

- i. Emission Limitation
Visible fugitive PE shall not exceed 5% opacity, as a three-minute average from transferring/conveying operations

Applicable Compliance Method

If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

None

20

Deseret Grain Storage
PTI Application: 03 14060
Issued

Facility ID: 0363000041

Emissions Unit ID: P901

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
P902 - (1) Railcar grain receiving station and transferring/conveying	OAC rule 3745-31-05(A)(3)	OAC rule 3745-17-07 (B) OAC rule 3745-17-08(B)

Applicable Emissions
Limitations/Control Measures

Control requirements (see A.2.a)

Railcar grain receiving:

2.74 lbs particulate emissions (PE)/hr; 1.05 tons PE per year from baghouse stack (see A.2.d)

Visible PE shall not exceed 0% opacity as a six-minute average from baghouse stack

0.81 ton fugitive PE per year

Visible fugitive PE shall not exceed 20% opacity, as a three-minute average, from railcar grain receiving operations

0.27 ton fugitive particulate matter less than 10 microns in size (PM₁₀) per year

Transferring/Conveying:

0.06 tons fugitive PE per year

Visible fugitive PE shall not exceed 5% opacity, as a three-minute average from transferring/conveying

0.03 tons fugitive PM₁₀ per year

see A.2.b

see A.2.c

2. Additional Terms and Conditions

- 2.a** The "Best Available Technology" (BAT) control requirements for this emissions unit has been determined to be:
- i. use of a baghouse control system with a maximum outlet concentration of 0.02gr/dscf for railcar grain receiving;
 - ii. use of a total enclosure for transferring/conveying
- BAT also includes compliance with the terms and conditions of this permit.
- 2.b** This emissions unit is exempt from the visible particulate emission limitations specified in OAC rule 3745-17-07(B) pursuant to OAC rule 3745-17-07(B)(11)(e).
- 2.c** Deseret Grain Storage is not located within an "Appendix A" area as identified in OAC rule 3745-17-08. Therefore, pursuant to OAC rule 3745-17-08(A), this emissions unit is exempt from the requirements of OAC rule 3745-17-08.
- 2.d** PE from the baghouse stack is inclusive of and assumed to be PM₁₀.

B. Operational Restrictions

1. The maximum annual grain throughput for emissions unit P902 shall not exceed 36,000 tons.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain monthly records of the amount of grain throughput for this emissions unit (in tons per month and total tons, to date for the calendar year).
2. The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for (a) any visible particulate emissions from the baghouse stack serving the railcar grain receiving operation, (b) visible fugitive emissions from the railcar grain receiving operation, and (c) any visible particulate emissions from transferring/conveying operations. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. for visible particulate emissions from the baghouse stack serving the railcar grain receiving operation:
 - i. the color of the emissions;

Emissions Unit ID: **P902**

- ii. the total duration of any visible emission incident; and
 - iii. any corrective actions taken to eliminate the visible emissions.
- b. for visible fugitive emissions from the railcar grain receiving operation:
- i. the location and color of the emissions;
 - ii. whether the emissions are representative of normal operations;
 - iii. if the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - iv. the total duration of any visible emission incident; and,
 - v. any corrective actions taken to eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item (iv) above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

- c. for visible particulate emissions from transfer/conveying operations:
- i. the color of the emissions;
 - ii. the total duration of any visible emission incident; and
 - iii. any corrective actions taken to eliminate the visible emissions.

D. Reporting Requirements

1. The permittee shall submit annual reports which identify any exceedance of the annual grain throughput limitation, as well as the corrective actions that were taken to achieve compliance. If no deviations occurred during the calendar year, the permittee shall submit an annual report, which states that no deviations occurred during that calendar year. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.
2. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the baghouse stack serving the railcar grain receiving operation, (b) identify all days during which any abnormal visible fugitive particulate

emissions were observed from the railcar grain receiving operation, and (c) identify all days during which any visible particulate emissions were observed from transferring/conveying operations and (c) describe any corrective actions taken to eliminate the visible particulate emissions and abnormal visible fugitive particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.

E. Testing Requirements

1. Compliance Methods Requirements: Compliance with the emission limitation(s) established in the Applicable Emissions Limitation section of this permit shall be determined in accordance with the following method(s):

- a. Emission Limitation:
0.02 gr/dscf from baghouse stack serving railcar grain receiving operation

Applicable Compliance Method:

The emission limitation was established in accordance with the manufacturers guaranteed outlet grain loading. If required, compliance with this emission limitation shall be determined in accordance with the test methods and procedures in 40 CFR Part 60, Appendix A, Methods 1-5.

- b. Emission Limitation:
2.74 lbs PE/hour from baghouse stack serving railcar grain receiving operation

Applicable Compliance Method

The permittee shall demonstrate compliance with the hourly emission limitation by multiplying the outlet grain concentration of 0.02 gr/dscf by a maximum volumetric flow rate of 16,000 dscfm, 60 minutes/hour, and 1 lb/7000 grains. If required, the permittee shall demonstrate compliance in accordance with the test methods and procedures in 40 CFR Part 60, Appendix A, Methods 1-5.

- c. Emission Limitation:
1.05 tons PE/year from baghouse stack serving railcar grain receiving operation

Applicable Compliance Method

The emission limitation was developed by multiplying an AP-42 emission factor of 0.18 lbs PE/ton grain (Section 9.9.1 (3/2003)), a maximum annual grain throughput of 36,000 tons, applying an overall control efficiency of 67.5 % for the baghouse control system (75% capture efficiency - 90% removal efficiency), and multiplying by a conversion factor

Emissions Unit ID: P902

of ton/2000 lbs. Therefore provided compliance is shown with the annual grain throughput restriction, compliance with the annual limitation will be assumed.

- c. Emission Limitation:
Visible PE shall not exceed 0% opacity as a six-minute average from the baghouse stack serving the railcar grain receiving operation

Applicable Compliance Method

If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources")

- d. Emission Limitation:
0.81 ton fugitive PE/year from railcar grain receiving operation

Applicable Compliance Method

The emission limitation was developed by multiplying an AP-42 emission factor of 0.18 lbs PE/ton grain (Section 9.9.1 (3/2003)), a maximum annual grain throughput of 36,000 tons, applying a capture efficiency of 75% for the baghouse control system, and multiplying by a conversion factor of ton/2000 lbs. Therefore provided compliance is shown with the annual grain throughput restriction, compliance with the annual limitation will be assumed.

- e. Emission Limitation:
0.27 ton fugitive PM₁₀/year from railcar grain receiving operation

Applicable Compliance Method

The emission limitation was developed by multiplying an AP-42 emission factor of 0.059 lbs PM₁₀/ton grain (Section 9.9.1 (3/2003)), a maximum annual grain throughput of 36,000 tons of grain, applying a capture efficiency of 75% for the baghouse control system, and multiplying by a conversion factor of ton/2000 lbs. Therefore provided compliance is shown with the annual grain throughput restriction, compliance with the annual limitation will be assumed.

- f. Emission Limitation:
0.06 tons fugitive PE/year from transferring/conveying

Applicable Compliance Method

The emission limitation was established by multiplying an AP-42 emission factor of 0.061 lbs PE/ton grain (Section 9.9.1 (3/2003)), a maximum annual grain throughput of 36,000 tons of grain, applying a control efficiency of 95% for total enclosure, and multiplying by a

conversion factor of ton/2000 lbs. Therefore provided compliance is shown with the annual grain throughput restriction, compliance with the annual limitation will be assumed.

- g. Emission Limitation:
0.03 tons fugitive PM₁₀/year from transferring/conveying

Applicable Compliance Method

The emission limitation was developed by multiplying an AP-42 emission factor of 0.034 lbs PM₁₀/ton grain (Section 9.9.1 (3/2003)), a maximum annual grain throughput of 36,000 tons of grain, applying a control efficiency of 95% for total enclosure, and multiplying by a conversion factor of ton/2000 lbs. Therefore provided compliance is shown with the annual grain throughput restriction, compliance with the annual limitation will be assumed.

- h. Emission Limitation:
Visible fugitive PE shall not exceed 20% opacity, as a three-minute average, from railcar grain receiving operation

Applicable Compliance Method

If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

- i. Emission Limitation
Visible fugitive PE shall not exceed 5% opacity, as a three-minute average from transferring and conveying operations

Applicable Compliance Method

If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

None