



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL
SANDUSKY COUNTY**

CERTIFIED MAIL

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049

Application No: 03-16291

Fac ID: 0372030245

DATE: 5/17/2005

Precision Aggregates
Bernie Schneider
12205 E. Gypsy Lane
Bowling Green, OH 43402

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, Ohio 43215

Sincerely,

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: USEPA

NWDO



**Permit To Install
Terms and Conditions**

**Issue Date: 5/17/2005
Effective Date: 5/17/2005**

FINAL PERMIT TO INSTALL 03-16291

Application Number: 03-16291
Facility ID: 0372030245
Permit Fee: **\$3000**
Name of Facility: Precision Aggregates
Person to Contact: Bernie Schneider
Address: 12205 E. Gypsy Lane
Bowling Green, OH 43402

Location of proposed air contaminant source(s) [emissions unit(s)]:

**100 N. Brush Street
Fremont, Ohio**

Description of proposed emissions unit(s):

Aggregate processing plant with storage piles, roadways and parking areas.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized

representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio

Precision Aggregates
PTI Application: 03-16291
Issued: 5/17/2005

Facility ID: 0372030245

Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

Precision Aggregates
 PTI Application: 03-16291
 Issued: 5/17/2005

Facility ID: 0372030245

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
 TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
Fugitive PE	22.58

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
F001 - 300 tons/hr aggregate processing plant with primary crushing, primary and secondary screening and transferring and conveying	OAC rule 3745-31-05(A)(3)	15.06 tons fugitive particulate emissions (PE)/yr Visible particulate emissions shall not exceed 20% opacity as a 3-minute average from front end loaders into feed hoppers. Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see A.2.a through A.2.c) See A.2.d
	OAC rule 3745-17-07(B)	See A.2.e
	OAC rule 3745-17-08(B)	See A.2.f
	40 CFR, Part 60, Subpart OOO	Visible Emission Restrictions (see A.2.g)

2. Additional Terms and Conditions

- 2.a The permittee shall employ best available control measures for the material processing/handling operations identified below, for the purpose of ensuring compliance with the above mentioned applicable requirements. In accordance with the permit

application, the permittee maintains that the inherent moisture content of the materials processed/handled is at a level which is more than sufficient to comply with all applicable requirements. If at anytime the moisture content is not sufficient to meet the above applicable requirements, the permittee shall employ best available control measures to ensure compliance.

Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

- 2.b** For each material handling operation that is not adequately enclosed, the above-identified control measures shall be implemented if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measures are necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measures shall continue during the operation of the material handling operations until further observation confirms that use of the control measures is unnecessary.
- 2.c** Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the requirements of OAC rule 3745-31-05.
- 2.d** The requirements of this rule also include compliance with 40 CFR Part 60, Subpart OOO.
- 2.e** This emissions unit is exempt from the visible particulate emission limitations specified in OAC rule 3745-17-07(B) pursuant to OAC rule 3745-17-07(B)(11)(e).
- 2.f** This facility is not located within an "Appendix A" area as identified in OAC rule 3745-17-08. Therefore, pursuant to OAC rule 3745-17-08(A), this emissions unit is exempt from the requirements of OAC rule 3745-17-08(B).
- 2.g** Visible particulate emissions from the aggregate processing equipment included under this permit shall not exceed the following opacity restrictions:
 - i. The permittee shall not cause to be discharged into the atmosphere from any crusher, at which a capture system is not used, fugitive emissions which exhibit greater than 15% opacity.
 - ii. The permittee shall not cause to be discharged into the atmosphere from any

Precision Aggregates

PTI Application: 03-16201

Issued

Facility ID: 0372030245

Emissions Unit ID: **F001**

transfer point on belt conveyors or from any other affected facility any fugitive emissions which exhibit greater than 10% opacity.

- 2.h** The application and enforcement of the provisions of NSPS, as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60, are delegated to the Ohio Environmental Protection Agency. The requirements for 40 CFR Part 60 are also federally enforceable.

B. Operational Restrictions

1. The permittee shall not exceed 300,000 tons per year of aggregate processed in emissions unit F001. This restriction is based on the aggregate throughput of the primary crusher.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain monthly records of the amount (tons per month and total tons, to date, for the calendar year) of aggregate processed through the primary crusher of emissions unit F001.
2. Except as otherwise provided in this section, for material handling operations that are not adequately enclosed, the permittee shall perform inspections of such operations in accordance with the following minimum frequencies:

<u>Material Handling Operations</u>	<u>Minimum Inspection Frequency</u>
All	Once During Each Day of Operation

3. The above-mentioned inspections shall be performed during representative, normal operating conditions.
4. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.
5. The permittee shall maintain records of the following information:
 - a. the date and reason any required inspection was not performed;
 - b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measure(s);
 - c. the dates the control measure(s) was (were) implemented; and
 - d. on a calendar quarter basis, the total number of days the control measure(s) was (were) implemented.

The information in 5.d. shall be kept separately for each material handling operation identified above, and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit an annual report which identifies the annual amount of aggregate processed in emissions unit F001. This report shall be submitted by January 31 of each year.
2. The permittee shall submit deviation reports that identify any of the following occurrences:
 - a. each day during which an inspection was not performed by the required frequency; and
 - b. each instance when a control measure, that was to be performed as a result of an inspection, was not implemented.
3. The permittee shall submit written reports of the results of all performance tests conducted to demonstrate compliance with the standards set forth in 40 CFR, Part 60, Subpart OOO, including the reports of opacity observations using Method 9 to demonstrate compliance with this subpart.
4. The permittee shall submit the following information for each piece of equipment that is replaced by a piece of equipment having the same function as the existing facility:
 - a. for a crusher:
 - i. the rated capacity, in tons per hour, of the existing facility being replaced, and
 - ii. the rated capacity, in tons per hour, of the replacement equipment; and
 - b. for a screen:
 - i. the rated capacity, in tons per hour, of the existing facility being replaced, and
 - ii. the rated capacity, in tons per hour, of the replacement equipment; and
 - c. for a conveyor belt:
 - i. the width of the existing belt being replaced, and
 - ii. the width of the replacement conveyor belt.

The notification shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days of after the equipment replacement.

13

Precis

PTI A

Issued: 5/17/2005

Emissions Unit ID: **F001**

5. Pursuant to the general provisions of NSPS, the source owner/operator is hereby advised of the requirement to report the following at the appropriate times for this emissions unit:

Precision Aggregates
PTI Application: 03-16201
Issued

Facility ID: 0372030245

Emissions Unit ID: F001

- a. construction date (no later than 30 days after such date);
- b. actual start-up date (within 15 days after such date); and
- c. date of performance testing (if required, at least 30 days prior to testing).

Reports are to be sent to:

Ohio Environmental Protection Agency
DAPC - Permit Management Unit
Lazarus Government Center
P.O. Box 1049
Columbus, OH 43216-1049

and Ohio EPA, Northwest District Office
347 North Dunbridge Road
Bowling Green, OH 43402

E. Testing Requirements

1. The permittee shall conduct, or have conducted, emission testing for all transfer points, screens and crushers of emissions unit F001.
2. Testing shall be conducted in accordance with the provisions of 40 CFR Part 60, Subpart A, Section 60.8 and 40 CFR Part 60, Subpart OOO, Section 60.675.
3. The emission testing shall be conducted within 60 days after achieving the maximum production rate at which the affected facility will be operated, by not later than 180 days after initial startup of such facility and at such other times as may be required by the Ohio Environmental Protection Agency, Division of Air Pollution Control. The emission testing shall be conducted to demonstrate compliance with the allowable visible emission rates for particulate emissions.
4. The following test methods shall be employed to demonstrate compliance with the allowable visible emissions rates:
 - a. Method 9 of 40 CFR Part 60, Appendix A shall be used to determine opacity.
5. The tests shall be conducted while the emissions unit is operating at its maximum capacity, unless otherwise specified or approved by the Ohio EPA, Division of Air Pollution Control. Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, Division of Air Pollution Control. The "Intent to Test" notification

shall describe in detail the proposed test methods and procedures, the emissions unit operation parameters, the times and dates of the tests, and the person(s) who will be conducting the tests. Failure to submit such notification for review and approval prior to the tests may result in the Ohio EPA District Office's air agency's refusal to accept the results of the emission tests.

6. Personnel from the Ohio EPA District Office's air agency shall be permitted to witness the test, examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions unit and /or the performance of the control equipment. A comprehensive written report on the emissions tests shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA Division of Air Pollution Control within 30 days following completion of the tests.
7. Compliance with the emission limitations in section A.1 of the terms and conditions of this permit shall be determined in accordance with the following methods:

- a. Emission Limitation: 12.55 tons fugitive PE/yr

Applicable Compliance Method: The emission limitation was developed in accordance with the following equation: Total Emissions = crushing* + screening** + transfer points***

*Crushing: For each crusher, multiply the AP-42 emission factor of 0.0054 lb PE/ton (Section 11.19.2 - 8/04) by the maximum annual throughput of 300,000 tons and divide by 2000.

**Screening: For each screen, multiply the AP-42 emission factor of 0.025 lb PE/ton (Section 11.19.2 - 8/04) by the maximum annual throughput of 300,000 tons and divide by 2000.

***Transfer Points: For each transfer point, multiply the AP-42 emission factor of 0.0030 lb PE/ton (Section 11.19.2 - 8/04) by the maximum annual throughput of 300,000 tons and divide by 2000.

Therefore, provided compliance is shown with the requirement to apply best available control measures, compliance with the ton per year PE limitation will be assumed.

- b. Emission Limitation: Visible particulate emissions shall not exceed 20% opacity as a 3-minute average from front end loaders into feed hoppers.

Applicable Compliance Method: If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

- c. Emission Limitation: The permittee shall not cause to be discharged into the atmosphere from any crusher, at which a capture system is not used, fugitive emissions which exhibit greater than 15% opacity.

Applicable Compliance Method: Compliance shall be demonstrated using Method 9 of 40 CFR, Part 60, Appendix A, and the procedures in 40 CFR, Part 60, Subpart OOO as specified in sections E.1 through E.6 above.

- d. Emission Limitation: The permittee shall not cause to be discharged into the atmosphere from any transfer point on belt conveyors or from any other affected facility any fugitive emissions which exhibit greater than 10% opacity.

Applicable Compliance Method: Compliance shall be demonstrated using Method 9 of 40 CFR, Part 60, Appendix A, and the procedures in 40 CFR, Part 60, Subpart OOO as specified in sections E.1 through E.6 above.

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
F002 - Mineral extraction operations including drilling, blasting and loading of limestone	OAC rule 3745-31-05(A)(3)	1.59 tons fugitive particulate emissions (PE)/yr Opacity Restrictions (see A.2.b) Use of best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see A.2.c and A.2.d)
	OAC rule 3745-17-07(B)	See A.2.e
	OAC rule 3745-17-08(B)	See A.2.f

2. Additional Terms and Conditions

- 2.a The mineral extraction operations that are covered by this permit and subject to the above mentioned requirements are listed below:

Drilling, blasting and loading of limestone

- 2.b Visible particulate emissions shall not exceed 20% opacity as a 3-minute average from the following mineral extraction operations: drilling and loading of limestone.

- 2.c The permittee shall employ best available control measures for the above-identified mineral extraction operations for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit

18

Precis

PTI A

Issued: 5/17/2005

Emissions Unit ID: **F002**

application, the permittee has committed to perform the following control measures to ensure compliance:

<u>mineral extraction operation</u>	<u>control measure(s)</u>
drilling	either water control system or vent to a cyclone and/or baghouse
blasting	minimize area to be blasted and prevention of overshooting
loading of limestone	maintenance of an inherent moisture content

Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

- 2.d** Implementation of the above-mentioned control measure(s) in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the requirements of OAC rule 3745-31-05(A)(3).
- 2.e** This emissions unit is exempt from the visible particulate emission limitations specified in OAC rule 3745-17-07(B) pursuant to OAC rule 3745-17-07(B)(11)(e).
- 2.f** This facility is not located within an "Appendix A" area as identified in OAC rule 3745-17-08. Therefore, pursuant to OAC rule 3745-17-08(A), this emissions unit is exempt from the requirements of OAC rule 3745-17-08(B).

B. Operational Restrictions

- 1. The permittee shall be limited to 18 blasts per year.
- 2. The permitte shall not process more than 300,000 tons of mineral per year.

C. Monitoring and/or Recordkeeping Requirements

- 1. Except as otherwise provided in this section, for mineral extraction operations that are not adequately enclosed, the permittee shall perform inspections of such operations in accordance with the following minimum frequencies:

<u>mineral extraction operation</u>	<u>minimum inspection frequency</u>
All	Once During Each Day of Operation

Emissions Unit ID: **F002**

2. The above-mentioned inspections shall be performed during representative, normal operating conditions.
3. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.
4. The permittee shall maintain records of the following information:
 - a. the date and reason any required inspection was not performed;
 - b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measure(s);
 - c. the dates the control measure(s) was (were) implemented; and
 - d. on a calendar quarter basis, the total number of days the control measure(s) was (were) implemented.

The information in 4.d. shall be kept separately for each mineral extraction operation identified above, and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

5. The permittee shall maintain the following monthly records for each blast:
 - a. the date the blast occurred;
 - b. the total number of blasts each month; and
 - c. the annual year to date, number of blasts (sum of b for each calendar month to date from January to December).
6. The permittee shall maintain monthly records of the quantity of mineral processed, in tons per month. For each month, the permittee shall also calculate the annual, year-to-date, amount of stone processed (cumulative total of each month to date from January to December).

D. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:

- a. each day during which an inspection was not performed by the required frequency; and
- b. each instance when a control measure, that was to be performed as a result of an inspection, was not implemented.

The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

2. The permittee shall submit annual deviation reports that identify exceedances of the following:
 - a. the annual number of blasts per year; and
 - b. the annual limit of the amount of mineral processed.

If no deviations occurred during a calendar year, the permittee shall submit an annual report, which states that no deviations occurred during that calendar year. The reports shall be submitted annually, by January 31 of each year and shall cover the previous calendar year.

E. Testing Requirements

1. Compliance with the emissions limitations in section A.1 of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emission Limitation: 1.59 tons fugitive PE/yr

Applicable Compliance Method: The annual particulate emission limitations were developed by applying the following emission factors/equations and control efficiencies to the associated process weight rates:

Mineral Extraction Operation	Maximum Process Weight Rate	Control Efficiency	Emission Factor	Emission Factor Citation
Drilling	300,000 tons/yr	90%	0.008 lb/ton	RACM, Table 2.4.4-4 (9/88)
Blasting	18 blasts/yr	None	58.5 lbs/blast	RACM, Table 2.4.4-4 (9/88)
Loading of Limestone	300,000 tons/yr	90%	0.063 lb/ton	AP-42, Section 13.2.4 (1/95)

Therefore, provided compliance is shown with the requirements of this permit to apply

best available control measures, compliance with the ton per year PE limitation will be assumed.

- b. Emission Limitation: Visible particulate emissions shall not exceed 20% opacity as a 3-minute average from the following mineral extraction operations: drilling and loading of limestone.

Applicable Compliance Method: If required, compliance with the visible emission limitation for the material handling operation(s) identified above shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
F003 - Storage Piles	OAC rule 3745-31-05(A)(3)	OAC rule 3745-17-07(B) OAC rule 3745-17-08(B)
load-in and load-out of storage piles (see Section A.2.a for identification of storage piles)	OAC rule 3745-31-05(A)(3)	
	OAC rule 3745-17-07(B)	
	OAC rule 3745-17-08(B)	
wind erosion from storage piles (see Section A.2.a for identification of storage piles)	OAC rule 3745-31-05(A)(3)	

Applicable Emissions
Limitations/Control Measures

1.99 tons fugitive particulate emissions (PE)/yr

No visible particulate emissions except for a period of time not to exceed one minute during any 60-minute observation period.

Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see A.2.b, A.2.c and A.2.f)

See A.2.g

See A.2.h

No visible particulate emissions except for a period of time not to exceed one minute during any 60-minute observation period.

Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see A.2.d through A.2.f)

See A.2.g

See A.2.h

2. Additional Terms and Conditions

2.a The storage piles that are covered by this permit and subject to the above-mentioned

requirements are listed below:

All storage piles

- 2.b** The permittee shall employ best available control measures on all load-in and load-out operations associated with the storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to watering, low drop heights from front end loaders and conveyors and maintenance of inherent moisture content to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.
- 2.c** The above-mentioned control measures shall be employed for each load-in and load-out operation of each storage pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measures are necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measures shall continue during any such operation until further observation confirms that use of the measures is unnecessary.
- 2.d** The permittee shall employ best available control measures for wind erosion from the surfaces of all storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to watering, maintenance of as low a pile height as possible and maintenance of inherent moisture content to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.
- 2.e** The above-mentioned control measures shall be employed for wind erosion from each pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measures are necessary to ensure compliance with the above-mentioned applicable requirements. Implementation of the control measures shall not be necessary for a storage pile that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements.
- 2.f** Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the requirements of OAC rule 3745-31-05.
- 2.g** This emissions unit is exempt from the visible particulate emission limitations specified in

OAC rule 3745-17-07(B) pursuant to OAC rule 3745-17-07(B)(11)(e).

- 2.h** This facility is not located within an "Appendix A" area as identified in OAC rule 3745-17-08. Therefore, pursuant to OAC rule 3745-17-08(A), this emissions unit is exempt from the requirements of OAC rule 3745-17-08(B).

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform inspections of each load-in operation at each storage pile in accordance with the following frequencies:

Storage Pile Identification
all storage piles

Minimum Load-In Inspection Frequency
once during each day of operation

2. Except as otherwise provided in this section, the permittee shall perform inspections of each load-out operation at each storage pile in accordance with the following frequencies:

Storage Pile identification
all storage piles

Minimum Load-Out Inspection Frequency
once during each day of operation

3. Except as otherwise provided in this section, the permittee shall perform inspections of the wind erosion from pile surfaces associated with each storage pile in accordance with the following frequencies:

Storage Pile Identification
all storage piles

Minimum Wind Erosion Inspection Frequency
once during each day of operation

4. No inspection shall be necessary for wind erosion from the surface of a storage pile when the pile is covered with snow and/or ice and for any storage pile activity if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is

within one week.

5. The purpose of the inspections is to determine the need for implementing the control measures specified in this permit for load-in and load-out of a storage pile, and wind erosion from the surface of a storage pile. The inspections shall be performed during representative, normal storage pile operating conditions.
6. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.
7. The permittee shall maintain records of the following information:
 - a. the date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;
 - b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;
 - c. the dates the control measures were implemented; and
 - d. on a calendar quarter basis, the total number of days the control measures were implemented and, for wind erosion from pile surfaces, the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measure(s).

The information required in 7.d. shall be kept separately for (i) the load-in operations, (ii) the load-out operations, and (iii) the pile surfaces (wind erosion), and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:
 - a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and
 - b. each instance when a control measure, that was to be implemented as a result of an

inspection, was not implemented.

The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the emission limitations in Section A.1. of the terms and conditions of this permit shall be determined in accordance with the following methods:

- a. Emission Limitation: 1.99 tons fugitive PE/yr

Applicable Compliance Method: The emission limitation was established by combining the emissions from load-in and load-out operations and from wind erosion from each storage pile as listed in the permittee's application and applying a 95% control efficiency for use of best available control measures. Load-in and load-out operation emissions are based on a maximum load-in and load-out rate of 300,000 tons per year of limestone and 300,000 tons per year of concrete sand. Wind erosion emissions are based on a maximum storage pile surface area of 0.5 acres for limestone and 0.5 acres for concrete sand as listed in the permit application:

The emission rate was determined as follows:

- i. Load-in - emissions associated with load-in operations were established by multiplying the maximum load-in rate of 300,000 tons per year of limestone and concrete sand by the appropriate emission factor from AP-42 section 13.2.4.(1/95) [0.063 lb PE/ton product], applying a 95% control efficiency and dividing by 2000 lbs/ton. (0.95 tons fugitive PE/yr for limestone and 0.95 tons fugitive PE/yr for concrete sand)
- ii. Load-out - emissions associated with load-out operations were established by multiplying the maximum load-out rate of 300,000 tons per year of limestone and concrete sand by the appropriate emission factor from AP-42 section 13.2.4.(1/95) [0.063 lb PE/ton product], applying a 95% control efficiency and dividing by 2000 lbs/ton. (0.95 tons fugitive PE/yr for limestone and 0.95 tons fugitive PE/yr for concrete sand)
- iii. Wind erosion - emissions were established by multiplying a maximum combined storage pile surface area of 0.5 acres for limestone and 0.5 acres for concrete sand, the appropriate emission factor from USEPA's Control of Open Fugitive Dust

Emissions Unit ID: F003

Sources (9/88) [10.41 lbs PE/acre/day of limestone and 10.41 lbs PE/acre/day of concrete sand], a maximum operating schedule of 365 days per year and dividing by 2000 and applying a 95% control efficiency. (0.047 tons fugitive PE/yr for limestone and 0.047 tons fugitive PE/yr for concrete sand)

Therefore, provided compliance is shown with the requirements of this permit to apply best available control measures, compliance with the ton per year PE limitation will be assumed.

- b. Emission Limitation: No visible particulate emissions except for a period of time not to exceed one minute during any 60-minute observation period from load-in and load-out of the storage piles

Applicable Compliance Method: Compliance with the visible emission limitations for the storage piles identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

- c. Emission Limitation: No visible particulate emissions except for a period of time not to exceed one minute during any 60-minute observation period from wind erosion

Applicable Compliance Method: Compliance with the visible emission limitations for the storage piles identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
		OAC rule 3745-17-07(B)
		OAC rule 3745-17-08(B)
F004 - Paved and unpaved roadways and parking areas	OAC rule 3745-31-05(A)(3)	
paved roadways and parking areas (see Section A.2.a)	OAC rule 3745-31-05(A)(3)	
	OAC rule 3745-17-07(B)	
	OAC rule 3745-17-08(B)	
unpaved roadways and parking areas (see Section A.2.b)	OAC rule 3745-31-05(A)(3)	

Applicable Emissions
Limitations/Control Measures

3.94 tons fugitive particulate emissions (PE)/yr

no visible particulate emissions except for one minute during any 60-minute period

best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see Sections A.2.c, and A.2.e through A.2.i)

See A.2.j

See A.2.k

no visible particulate emissions except for 3 minutes during any 60-minute period

best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see Sections A.2.d through A.2.i)

See A.2.j

See A.2.k

2. Additional Terms and Conditions

- 2.a The paved roadways and parking areas that are covered by this permit and subject to the above-mentioned requirements are listed below:

paved roadways:

all paved roadways

paved parking areas:

all paved parking area

- 2.b The unpaved roadways and parking areas that are covered by this permit and subject to the above-mentioned requirements are listed below:

unpaved roadways:

all unpaved roadways

unpaved parking areas:

none

- 2.c The permittee shall employ best available control measures on all paved roadways and parking areas for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to treat the paved roadways and parking areas by watering and sweeping at sufficient treatment frequencies to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

- 2.d The permittee shall employ best available control measures on all unpaved roadways and parking areas for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to treat the unpaved roadways and parking areas with water, speed reduction and good housekeeping at sufficient treatment frequencies to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

- 2.e The needed frequencies of implementation of the control measures shall be determined by the permittee's inspections pursuant to the monitoring section of this permit. Implementation of the control measures shall not be necessary for a paved or unpaved roadway or parking area that is covered with snow and/or ice or if precipitation has

occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Implementation of any control measure may be suspended if unsafe or hazardous driving conditions would be created by its use.

- 2.f** Any unpaved roadway or parking area, which during the term of this permit is paved or takes the characteristics of a paved surface due to the application of certain types of dust suppressants, may be controlled with the control measure(s) specified above for paved surfaces. Any unpaved roadway or parking area that takes the characteristics of a paved roadway or parking area due to the application of certain types of dust suppressants shall remain subject to the visible emission limitation for unpaved roadways and parking areas. Any unpaved roadway or parking area that is paved shall be subject to the visible emission limitation for paved roadways and parking areas.
- 2.g** The permittee shall promptly remove, in such a manner as to minimize or prevent resuspension, earth and/or other material from paved streets onto which such material has been deposited by trucking or earth moving equipment or erosion by water or other means.
- 2.h** Open-bodied vehicles transporting materials likely to become airborne shall have such materials covered at all times if the control measure is necessary for the materials being transported.
- 2.i** Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the best available technology requirements of OAC rule 3745-31-05.
- 2.j** This emissions unit is exempt from the visible emissions limitations specified in OAC rule 3745-17-07(B), pursuant to OAC rule 3745-17-07(B)(11)(e).
- 2.k** This facility is not located within an "Appendix A" areas as identified in OAC rule 3745-17-08. Therefore, pursuant to OAC rule 3745-17-08(A), this emissions unit is exempt from the requirements of OAC rule 3745-17-08(B).

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform inspections of the

roadways and parking areas in accordance with the following frequencies:

paved roadways and parking areas
all

minimum inspection frequency
once during each day of operation

unpaved roadways and parking areas
all

minimum inspection frequency
once during each day of operation

2. The purpose of the inspections is to determine the need for implementing the above-mentioned control measures. The inspections shall be performed during representative, normal traffic conditions. No inspection shall be necessary for a roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above-identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.
3. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.
4. The permittee shall maintain records of the following information:
 - a. the date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;
 - b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;
 - c. the dates the control measures were implemented; and
 - d. on a calendar quarter basis, the total number of days the control measures were implemented and the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measures.

The information required in 4.d. shall be kept separately for (i) the paved roadways and parking areas and (ii) the unpaved roadways and parking areas, and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:
 - a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and
 - b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.

The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the emission limitations in Section A.1. of the terms and conditions of this permit shall be determined in accordance with the following methods:

- a. Emission Limitation: 3.94 tons fugitive PE/yr from paved and unpaved roadways and parking areas

Applicable Compliance Method: This emission limitation was developed by multiplying emission factors from AP-42, Chapter 13.2.1 [paved] and Chapter 13.2.2 (12/03) [unpaved], the maximum vehicle miles traveled, a 95% control efficiency and dividing by 2000 lbs/ton:

- i. scale road (paved): $(32.94 \text{ lb PE/VMT}) (416 \text{ VMT}) (\text{ton}/2000 \text{ lbs}) (1-0.95) = 0.34 \text{ tons/yr}$
- ii. haul roads (unpaved): $(14.40 \text{ lb PE/VMT}) (5000 \text{ VMT}) (\text{ton}/2000 \text{ lbs}) (1-0.95) = 1.80 \text{ tons/yr}$
- iii. road from storage piles (unpaved): $(14.40 \text{ lb PE/VMT}) (5000 \text{ VMT}) (\text{ton}/2000 \text{ lbs}) (1-0.95) = 1.80 \text{ tons/yr}$

Therefore provided compliance is shown with the requirements of this permit to apply best available control measures, compliance with the annual limitation will be assumed.

Precision Aggregates

PTI Application: 03-16201

Issued

Facility ID: 0372030245

Emissions Unit ID: F004

- b. Emission Limitation: no visible particulate emissions except for 1 minutes during any 60-minute period from paved roadways and parking areas

Applicable Compliance Method: Compliance with the visible emission limitation specified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(d) of OAC rule 3745-17-03.

- c. Emission Limitation: no visible particulate emissions except for 3 minutes during any 60-minute period from unpaved roadways and parking areas

Applicable Compliance Method: Compliance with the visible emission limitation specified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(d) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

None