



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL MODIFICATION
WILLIAMS COUNTY**

CERTIFIED MAIL

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049

Application No: 03-16162

Fac ID: 0386010104

DATE: 8/24/2004

Allied Moulded Products Inc
Ron Clark
P O Box 587 222 North Union Street
Bryan, OH 43506

Enclosed Please find a modification to the Ohio EPA Permit To Install referenced above which will modify the terms and conditions.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, Ohio 43215

Sincerely,

Michael W. Ahern

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

cc: USEPA

NWDO



**Permit To Install
Terms and Conditions**

**Issue Date: 8/24/2004
Effective Date: 8/24/2004**

FINAL ADMINISTRATIVE MODIFICATION OF PERMIT TO INSTALL 03-16162


Application Number: 03-16162
Facility ID: 0386010104
Permit Fee: **\$3075**
Name of Facility: Allied Moulded Products Inc
Person to Contact: Ron Clark
Address: P O Box 587 222 North Union Street
Bryan, OH 43506

Location of proposed air contaminant source(s) [emissions unit(s)]:
**222 North Union Street
Bryan, Ohio**

Description of proposed emissions unit(s):
ADMINISTRATIVE MODIFICATION: PTIs 03-9409, 03-9601, 03-11228, 03-13420, 03-13631 - correct unit maximum capacities, BAT emissions limits.

The above named entity is hereby granted a modification to the permit to install described above pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this modification does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described source(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans included in the application, the above described source(s) of pollutants will be granted the necessary operating permits.

This permit is granted subject to the conditions attached hereto.


Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. State and Federally Enforceable Permit To Install General Terms and Conditions

1. Monitoring and Related Recordkeeping and Reporting Requirements

- a. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:
 - i. The date, place (as defined in the permit), and time of sampling or measurements.
 - ii. The date(s) analyses were performed.
 - iii. The company or entity that performed the analyses.
 - iv. The analytical techniques or methods used.
 - v. The results of such analyses.
 - vi. The operating conditions existing at the time of sampling or measurement.
- b. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.
- c. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall submit required reports in the following manner:
 - i. Reports of any required monitoring and/or recordkeeping of federally enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
 - ii. Quarterly written reports of (i) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, excluding deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06, that have been detected by the testing, monitoring and recordkeeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures taken, shall be made to the appropriate Ohio EPA District Office or local air agency. The written reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous

calendar quarters. See B.9 below if no deviations occurred during the quarter.

- iii. Written reports, which identify any deviations from the federally enforceable monitoring, recordkeeping, and reporting requirements contained in this permit shall be submitted to the appropriate Ohio EPA District Office or local air agency every six months, i.e., by January 31 and July 31 of each year for the previous six calendar months. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report, which states that no deviations occurred during that period.
- iv. Each written report shall be signed by a responsible official certifying that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.

2. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction, i.e., upset, of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. (The definition of an upset condition shall be the same as that used in OAC rule 3745-15-06(B)(1) for a malfunction.) The verbal and written reports shall be submitted pursuant to OAC rule 3745-15-06.

Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emission unit(s) that is (are) served by such control system(s).

3. Risk Management Plans

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. 7401 et seq. ("Act"), the permittee shall comply with the requirement to register such a plan.

4. Title IV Provisions

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

5. Severability Clause

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition

declared invalid.

6. General Requirements

- a. The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and reissuance, or modification, or for denial of a permit renewal application.
- b. It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.
- c. This permit may be modified, reopened, revoked, or revoked and reissued, for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.
- d. This permit does not convey any property rights of any sort, or any exclusive privilege.
- e. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

7. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit To Install fees within 30 days after the issuance of this Permit To Install.

8. Federal and State Enforceability

Only those terms and conditions designated in this permit as federally enforceable, that are

required under the Act, or any of its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA, the State, and citizens under the Act. All other terms and conditions of this permit shall not be federally enforceable and shall be enforceable under State law only.

9. Compliance Requirements

- a. Any document (including reports) required to be submitted and required by a federally applicable requirement in this permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.
- b. Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:
 - i. At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.
 - ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with ORC section 3704.08.
 - iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.
 - iv. As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.
- c. The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually, or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:
 - i. Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
 - ii. An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

10. Permit To Operate Application

- a. If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).
- b. If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35, the source(s) identified in this Permit To Install is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the source(s) covered by this permit.

11. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

12. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

Allied Moulded Products Inc
PTI Application: 03-16162
Modification Issued: 8/24/2004

Facility ID: 0386010104

B. State Only Enforceable Permit To Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping of state-only enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from state-only required emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

4. Termination of Permit To Install

This permit to install shall terminate within eighteen months of the effective date of the permit to install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete

Allied Moulded Products Inc
PTI Application: 03-16162
Modification Issued: 8/24/2004

Facility ID: 0386010104

within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

5. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

6. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

7. Applicability

Allied Moulded Products Inc
PTI Application: 03-16162
Modification Issued: 8/24/2004

Facility ID: 0386010104

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

8. Construction Compliance Certification

If applicable, the applicant shall provide Ohio EPA with a written certification (see enclosed form if applicable) that the facility has been constructed in accordance with the Permit To Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

9. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations (See Section A of This Permit)

If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.

C. Permit To Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
OC	229.0 *

* This number represents the additive total of all the individual emission units' allowable limitations. The potential emissions from all the individual emissions units combined is lower than 229 tons OC based on an inherent physical limitation.

Allied Moulded Products Inc
PTI Application: 03-16162
Modification Issued: 8/24/2004

Facility ID: 0386010104

Allied Moulded Products Inc
PTI Application: 03 16162
Modif

Facility ID: 0386010104

Emissions Unit ID: P009

Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

A. State and Federally Enforceable Permit To Install Facility Specific Terms and Conditions

1. This emissions unit is subject to 40 CFR Part 63, Subpart WWWW, National Emission Standards for Hazardous Air Pollutants: Reinforced Plastic Composite Production. The permittee shall comply with all applicable requirements of 40 CFR Part 63, Subpart WWWW. The permittee shall also comply with all applicable requirements of 40 CFR Part 63, Subpart A (General Provisions) as identified in Table 2 of 40 CFR Part 63, Subpart WWWW. Compliance with all applicable requirements shall be achieved by the dates set forth in 40 CFR Part 63, Subpart WWWW and Subpart A.

B. State Only Enforceable Permit To Install Facility Specific Terms and Conditions

None

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P009 - Injection Press #432 - Bulk Molding Compound (BMC)	OAC rule 3745-31-05(A)(3)	0.29 lb organic compounds (OC)/hr, 1.28 tons OC/yr
(Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. **Additional Terms and Conditions**

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

14

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P009

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

0.29 lb OC /hr

1.28 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 262 lbs BMC per hour, multiplied by a maximum resin content of 0.20 lb resin per lb BMC (20%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P009

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P009 - Injection Press - Bulk Molding Compound (No. 432)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

17

Allied Moulded Products Inc
PTI Application: 03 16162
Modif

Facility ID: 0386010104

Emissions Unit ID: P009

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P010

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P010 - Compression Press #7 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	0.13 lb organic compounds (OC)/hr, 0.56 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. **Additional Terms and Conditions**

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

19

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P010

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

0.13 lb OC /hr

0.56 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 96 lbs BMC per hour, multiplied by a maximum resin content of 0.24 lb resin per lb BMC (24%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P010

B. State Only Enforceable Section**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P010 - Compression Press - Bulk Molding Compound (No. 7)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

22

Allied Moulded Products Inc
PTI Application: 03 16162
Modif

Facility ID: 0386010104

Emissions Unit ID: P010

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P011

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P011 - Compression Press #13 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	0.12 lb organic compounds (OC)/hr, 0.52 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

24

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P011

IV. Reporting Requirements

None

Allied**PTI A****Modification Issued: 8/24/2004**

Emissions Unit ID: P011

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

0.12 lb OC /hr

0.52 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 89 lbs BMC per hour, multiplied by a maximum resin content of 0.24 lb resin per lb BMC (24%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P011

B. State Only Enforceable Section**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P011 - Compression Press - Bulk Molding Compound (No. 13)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

27

Allied Moulded Products Inc
PTI Application: 03 16162
Modif

Facility ID: 0386010104

Emissions Unit ID: P011

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P012

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P012 - Compression Press #9 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	0.12 lb organic compounds (OC)/hr, 0.52 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

29

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P012

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

0.12 lb OC /hr

0.52 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 89 lbs BMC per hour, multiplied by a maximum resin content of 0.24 lb resin per lb BMC (24%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P012

B. State Only Enforceable Section**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P012 - Compression Press - Bulk Molding Compound (No. 9)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

32

Allied Moulded Products Inc
PTI Application: 03 16162
Modif

Facility ID: 0386010104

Emissions Unit ID: P012

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P013

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P013 - Compression Press #31 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	0.13 lb organic compounds (OC)/hr, 0.56 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

34

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P013

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

0.13 lb OC /hr

0.56 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 96 lbs BMC per hour, multiplied by a maximum resin content of 0.24 lb resin per lb BMC (24%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P013 - Compression Press - Bulk Molding Compound (No. 31)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

37

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P013

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P014

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P014 - Injection Press #35 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	0.24 lb organic compounds (OC)/hr, 1.09 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

Allied Moulded Products Inc
PTI Application: 03 16162
Modif

Facility ID: 0386010104

Emissions Unit ID: P014

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

0.24 lb OC /hr

1.09 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 224 lbs BMC per hour, multiplied by a maximum resin content of 0.20 lb resin per lb BMC (20%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P014 - Injection Press - Bulk Molding Compound (No. 35)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

42

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P014

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P015 - Injection Press#3401 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	0.24 lb organic compounds (OC)/hr, 1.09 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. **Additional Terms and Conditions**

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

Allied Moulded Products Inc
PTI Application: 03 16162
Modif

Facility ID: 0386010104

Emissions Unit ID: P015

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

0.24 lb OC /hr

1.09 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 224 lbs BMC per hour, multiplied by a maximum resin content of 0.20 lb resin per lb BMC (20%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P015 - Injection Press - Bulk Molding Compound (No. 3401)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

47

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P015

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P016

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P016 - Injection Press#3301 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	0.24 lb organic compounds (OC)/hr, 1.09 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

Allied Moulded Products Inc
PTI Application: 03 16162
Modif

Facility ID: 0386010104

Emissions Unit ID: P016

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

0.24 lb OC /hr

1.09 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 224 lbs BMC per hour, multiplied by a maximum resin content of 0.20 lb resin per lb BMC (20%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P016 - Injection Press - Bulk Molding Compound (No. 3301)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

52

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P016

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P018

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P018 - Injection Press #591-Bulk Molding Compound (BMC) (Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	0.32 lb organic compounds (OC)/hr, 1.39 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

Allied Moulded Products Inc
PTI Application: 03 16162
Modif

Facility ID: 0386010104

Emissions Unit ID: P018

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

0.32 lb OC /hr

1.39 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 284 lbs BMC per hour, multiplied by a maximum resin content of 0.20 lb resin per lb BMC (20%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P018

B. State Only Enforceable Section**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P018 - Injection Press - Bulk Molding Compound (No. 591)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

57

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P018

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P019

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P019 - Injection Press #590 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	0.32 lb organic compounds (OC)/hr, 1.39 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

Allied Moulded Products Inc
PTI Application: 03 16162
Modif

Facility ID: 0386010104

Emissions Unit ID: P019

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

0.32 lb OC /hr

1.39 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 284 lbs BMC per hour, multiplied by a maximum resin content of 0.20 lb resin per lb BMC (20%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P019

B. State Only Enforceable Section**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P019 - Injection Press - Bulk Molding Compound (No. 590)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

62

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P019

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P020

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P020 - Injection Press #601 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	0.29 lb organic compounds (OC)/hr, 1.28 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

Allied Moulded Products Inc
PTI Application: 03 16162
Modif

Facility ID: 0386010104

Emissions Unit ID: P020

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

0.29 lb OC /hr

1.28 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 262 lbs BMC per hour, multiplied by a maximum resin content of 0.20 lb resin per lb BMC (20%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P020

B. State Only Enforceable Section**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P020 - Injection Press - Bulk Molding Compound (No. 601)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

67

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P020

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P021

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P021 - Injection Press #602 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	0.29 lb organic compounds (OC)/hr, 1.28 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

69

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P021

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

0.29 lb OC /hr

1.28 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 262 lbs BMC per hour, multiplied by a maximum resin content of 0.20 lb resin per lb BMC (20%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P021

B. State Only Enforceable Section**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P021 - Injection Press - Bulk Molding Compound (No. 602)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

72

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P021

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P022

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P022 - Injection Press #465 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	5.87 lb organic compounds (OC)/hr, 25.7 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

74

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P022

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

5.87 lb OC /hr

25.7 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 5261 lbs BMC per hour, multiplied by a maximum resin content of 0.20 lb resin per lb BMC (20%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P022 - Injection Press - Bulk Molding Compound (No. 465)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P023

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P023 - Injection Press #462 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	5.87 lb organic compounds (OC)/hr, 25.7 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

78

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P023

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

5.87 lb OC /hr

25.7 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 5261 lbs BMC per hour, multiplied by a maximum resin content of 0.20 lb resin per lb BMC (20%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P023 - Injection Press - Bulk Molding Compound (No. 462)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P024

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P024 - Injection Press #481 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	5.87 lb organic compounds (OC)/hr, 25.7 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

82

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P024

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

5.87 lb OC /hr

25.7 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 5261 lbs BMC per hour, multiplied by a maximum resin content of 0.20 lb resin per lb BMC (20%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P024 - Injection Press - Bulk Molding Compound (No. 481)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P025

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P025 - Injection Press #482 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	5.87 lb organic compounds (OC)/hr, 25.7 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

86

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P025

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

5.87 lb OC /hr

25.7 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 5261 lbs BMC per hour, multiplied by a maximum resin content of 0.20 lb resin per lb BMC (20%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P025 - Injection Press - Bulk Molding Compound (No. 482)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P026

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P026 - Injection Press #811 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	5.87 lb organic compounds (OC)/hr, 25.7 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

90

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P026

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

5.87 lb OC /hr

25.7 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 5261 lbs BMC per hour, multiplied by a maximum resin content of 0.20 lb resin per lb BMC (20%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P026 - Injection Press - Bulk Molding Compound (No. 811)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P027

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P027 - Injection Press #480 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	5.87 lb organic compounds (OC)/hr, 25.7 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

94

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P027

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

5.87 lb OC /hr

25.7 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 5261 lbs BMC per hour, multiplied by a maximum resin content of 0.20 lb resin per lb BMC (20%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P027 - Injection Press - Bulk Molding Compound (No. 480)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P029 - Injection Press#1073 - Bulk Molding Compound (BMC)	OAC rule 3745-31-05(A)(3)	5.87 lb organic compounds (OC)/hr, 25.7 tons OC/yr
(Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

5.87 lb OC /hr

25.7 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 5261 lbs BMC per hour, multiplied by a maximum resin content of 0.20 lb resin per lb BMC (20%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P029

B. State Only Enforceable Section**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P029 - Injection Press - Bulk Molding Compound (No. 1073)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

100

Allied Moulded Products Inc

PTI Application: 03 16162

Modif

Facility ID: 0386010104

Emissions Unit ID: P029

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P030

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P030 - Injection Press#1074 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	5.87 lb organic compounds (OC)/hr, 25.7 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

102

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P030

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

5.87 lb OC /hr

25.7 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 5261 lbs BMC per hour, multiplied by a maximum resin content of 0.20 lb resin per lb BMC (20%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P030 - Injection Press - Bulk Molding Compound (No. 1074)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

105

Allied Moulded Products Inc

PTI Application: 03 16162

Modif

Facility ID: 0386010104

Emissions Unit ID: P030

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P032

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P032 - Compression Press #665 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	0.19 lb organic compounds (OC)/hr, 0.81 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. **Additional Terms and Conditions**

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

107

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P032

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

0.19 lb OC /hr

0.81 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 138 lbs BMC per hour, multiplied by a maximum resin content of 0.24 lb resin per lb BMC (24%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P032 - Compression Press - Bulk Molding Compound (No. 665)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

110

Allied Moulded Products Inc

PTI Application: 03 16162

Modif

Facility ID: 0386010104

Emissions Unit ID: P032

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P033

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P033 - Compression Press #696 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3) OAC 3745-21-07(G) 40 CFR Part 63, Subpart WWWW	0.15 lb organic compounds (OC)/hr, 0.64 tons OC/yr None (see Section A.I.2.a) See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. **Additional Terms and Conditions**

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

112

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P033

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

0.15 lb OC /hr

0.64 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 109 lbs BMC per hour, multiplied by a maximum resin content of 0.24 lb resin per lb BMC (24%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P033 - Compression Press - Bulk Molding Compound (No. 696)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

115

Allied Moulded Products Inc

PTI Application: 03 16162

Modif

Facility ID: 0386010104

Emissions Unit ID: P033

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P034

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P034 - Compression Press #734 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	0.30 lb organic compounds (OC)/hr, 1.32 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

117

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P034

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

0.30 lb OC /hr

1.32 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 225 lbs BMC per hour, multiplied by a maximum resin content of 0.24 lb resin per lb BMC (24%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P034

B. State Only Enforceable Section**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P034 - Compression Press - Bulk Molding Compound (No. 734)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

120

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P034

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P035

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P035 - Compression Press #733 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-9409 issued January 10, 1996 and modified April 3, 1996 to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	0.30 lb organic compounds (OC)/hr, 1.32 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

122

Allied Moulded Products Inc
PTI Application: 03 16162
Modif

Facility ID: 0386010104

Emissions Unit ID: P035

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

0.30 lb OC /hr

1.32 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 225 lbs BMC per hour, multiplied by a maximum resin content of 0.24 lb resin per lb BMC (24%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P035 - Compression Press - Bulk Molding Compound (No. 733)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

125

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P035

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P042

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P042 - Injection Press#1439 - Bulk Molding Compound (BMC)	OAC rule 3745-31-05(A)(3)	0.32 lb organic compounds (OC)/hr and 1.39 tons OC/yr
(Administrative modification to PTI 03-11228 issued June 30, 1999, to adjust maximum capacity and emission limits)	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

0.32 lb OC /hr

1.39 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 284 lbs BMC per hour, multiplied by a maximum resin content of 0.20 lb resin per lb BMC (20%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P042 - Injection Press - Bulk Molding Compound (No. 1439)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

129

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P042

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P043

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P043 - Compression Press #1685 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-13420 issued June 14, 2000, to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	0.30 lb organic compounds (OC)/hr, 1.32 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

0.30 lb OC /hr

1.32 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 225 lbs BMC per hour, multiplied by a maximum resin content of 0.24 lb resin per lb BMC (24%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P043 - Compression Press - Bulk Molding Compound (No. 1685)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

133

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P043

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P044

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P044 - Compression Press #1686 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-13420 issued June 14, 2000, to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	0.30 lb organic compounds (OC)/hr, 1.32 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

Allied Moulded Products Inc
PTI Application: 03-16162
Modif

Facility ID: 0386010104

Emissions Unit ID: P044

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

0.30 lb OC /hr

1.32 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 225 lbs BMC per hour, multiplied by a maximum resin content of 0.24 lb resin per lb BMC (24%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P044

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P044 - Compression Press - Bulk Molding Compound (No. 1686)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

137

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P044

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P047

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P047 - Injection Press#1726 - Bulk Molding Compound (BMC) (Administrative modification to PTI 03-13631 issued September 18, 2001, to adjust maximum capacity and emission limits)	OAC rule 3745-31-05(A)(3)	0.73 lb organic compounds (OC)/hr, 3.18 tons OC/yr
	OAC 3745-21-07(G)	None (see Section A.I.2.a)
	40 CFR Part 63, Subpart WWWW	See Section A. of Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

2. Additional Terms and Conditions

- 2.a This emissions unit is not subject to the requirements in OAC rule 3745-21-07(G) because no liquid organic material is employed in this emissions unit. "Liquid organic material" is defined in OAC rule 3745-21-01(C)(3).

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

139

Allied Moulded Products Inc
PTI Application: 03 16162
Modif

Facility ID: 0386010104

Emissions Unit ID: P047

None

V. Testing Requirements

1. Compliance with the emissions limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitations:

0.73 lb OC /hr

3.18 ton OC /yr

Applicable Compliance Method:

The emission limitations are based on the emission unit's Potential to Emit*. Therefore, no recordkeeping, deviation reporting or compliance method calculations are required to demonstrate compliance with this limitation.

* The Potential to Emit for this emissions unit is based on a maximum throughput of 650 lbs BMC per hour, multiplied by a maximum resin content of 0.20 lb resin per lb BMC (20%), then multiplied by a maximum resin styrene (OC monomer) content of 0.30 (30%), then multiplied by an emission factor of 0.0186 (1.86%) (emissions factor is based on a consolidation of information from the Society of the Plastics Industry (SPI) and other sources).

The annual allowable OC limitation was developed by multiplying the hourly limitation by 8760, and then dividing by 2000.

2. Formulation data or USEPA Method 311 shall be used to determine the monomer (OC) content of each BMC resin.

VI. Miscellaneous Requirements

1. The permittee shall maintain a current list of BMC raw materials in use which provides all of the OC data necessary to evaluate compliance as described in Section A.V.1 above. Such information shall be retained for at least 5 years after the issuance date of this permit.

Allied

PTI A

Modification Issued: 8/24/2004

Emissions Unit ID: P047

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P047 - Injection Press - Bulk Molding Compound (No. 1726)	None	None

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None