

Synthetic Minor Determination and/or **Netting Determination**
Permit To Install **03-13984**

A. Source Description

On March 27, 2001, the permittee received PTI No. 03-13066 for their rubber curing and extrusion operations, which included emissions units: P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054. The permittee has submitted PTI application No. 03-13984 to modify the units by increasing the pound/hour emission rates.

B. Facility Emissions and Attainment Status

The permittee is a PSD minor facility. The company has requested a federally enforceable VOC emission limitation for the purpose of maintaining their current PSD status. The facility is located in Wood County which is in attainment for all criteria pollutants.

C. Source Emissions

For purposes of maintaining the company's PSD minor facility status and reducing potential VOC emissions, the permittee has requested a federally enforceable, combined limitation for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054 of 20.8 tons VOC per year based on an annual production rate limitation.

D. Conclusion

Federally enforceable permit conditions will reduce potential VOC emission to 20.8 tons per year. This is not an increase over the limit established in PTI No. 03-13066.



State of Ohio Environmental Protection Agency

RE: DRAFT PERMIT TO INSTALL CERTIFIED MAIL
WOOD COUNTY

Street Address:

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov.
Center

Application No: 03-13984

DATE: 5/1/2003

Cooper Engineered Products
Stacey Rader
1175 N Main St
Bowling Green, OH 43402

You are hereby notified that the Ohio Environmental Protection Agency has made a draft action recommending that the Director issue a Permit to Install for the air contaminant source(s) [emissions unit(s)] shown on the enclosed draft permit. This draft action is not an authorization to begin construction or modification of your emissions unit(s). The purpose of this draft is to solicit public comments on the proposed installation. A public notice concerning the draft permit will appear in the Ohio EPA Weekly Review and the newspaper in the county where the facility will be located. Public comments will be accepted by the field office within 30 days of the date of publication in the newspaper. Any comments you have on the draft permit should be directed to the appropriate field office within the comment period. A copy of your comments should also be mailed to Robert Hodanbosi, Division of Air Pollution Control, Ohio EPA, P.O. Box 1049, Columbus, OH, 43266-0149.

A Permit to Install may be issued in proposed or final form based on the draft action, any written public comments received within 30 days of the public notice, or record of a public meeting if one is held. You will be notified in writing of a scheduled public meeting. Upon issuance of a final Permit to Install a fee of **\$3200** will be due. Please do not submit any payment now.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469. If you have any questions about this draft permit, please contact the field office where you submitted your application, or Mike Ahern, Field Operations & Permit Section at (614) 644-3631.

Very truly yours,

Michael W. Ahern

Michael W. Ahern, Supervisor
Field Operations and Permit Section
Division of Air Pollution Control

CC: USEPA

NWDO

Toledo Metro Area Council of Gov.

IN

MI

WOOD COUNTY

PUBLIC NOTICE

ISSUANCE OF DRAFT ADMINISTRATIVE MODIFICATION OF PERMIT TO INSTALL 03-13984

On 5/1/2003 the Director of the Ohio Environmental Protection Agency issued a draft action of an administrative modification of a prior Permit To Install document for an air contaminant source for **Cooper Engineered Products**, located at **1175 N. Main St., Bowling Green, Ohio**.

The administrative modification shall become effective upon final issuance.

Modification to rubber extrusion lines.

Comments concerning this draft action, or a request for a public hearing, must be sent in writing to the address identified below no later than thirty (30) days from the date this notice is published. All inquiries concerning this draft action may be directed to the contact identified below.

Don Waltermeyer, Ohio EPA, Northwest District Office, 347 North Dunbridge Road, Bowling Green, OH 43402
[(419)352-8461]



**Permit To Install
Terms and Conditions**

**Issue Date: To be entered upon final issuance
Effective Date: To be entered upon final issuance**

DRAFT PERMIT TO INSTALL 03-13984

Application Number: 03-13984
APS Premise Number: 0387020045
Permit Fee: **To be entered upon final issuance**
Name of Facility: Cooper Engineered Products
Person to Contact: Stacey Rader
Address: 1175 N Main St
Bowling Green, OH 43402

Location of proposed air contaminant source(s) [emissions unit(s)]:
**1175 N. Main St.
Bowling Green, Ohio**

Description of proposed emissions unit(s):
Modification to rubber extrusion lines.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

A. State and Federally Enforceable Permit To Install General Terms and Conditions**1. Monitoring and Related Recordkeeping and Reporting Requirements**

- a. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:
 - i. The date, place (as defined in the permit), and time of sampling or measurements.
 - ii. The date(s) analyses were performed.
 - iii. The company or entity that performed the analyses.
 - iv. The analytical techniques or methods used.
 - v. The results of such analyses.
 - vi. The operating conditions existing at the time of sampling or measurement.
- b. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.
- c. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall submit required reports in the following manner:
 - i. Reports of any required monitoring and/or recordkeeping of federally enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
 - ii. Quarterly written reports of (i) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, excluding deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06, that have been detected by the testing, monitoring and recordkeeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures taken, shall be made to the appropriate Ohio EPA District Office or local air agency. The written reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. See B.9 below if no deviations occurred during the quarter.

- iii. Written reports, which identify any deviations from the federally enforceable monitoring, recordkeeping, and reporting requirements contained in this permit shall be submitted to the appropriate Ohio EPA District Office or local air agency every six months, i.e., by January 31 and July 31 of each year for the previous six calendar months. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report, which states that no deviations occurred during that period.
- iv. Each written report shall be signed by a responsible official certifying that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.

2. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction, i.e., upset, of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. (The definition of an upset condition shall be the same as that used in OAC rule 3745-15-06(B)(1) for a malfunction.) The verbal and written reports shall be submitted pursuant to OAC rule 3745-15-06.

Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emission unit(s) that is (are) served by such control system(s).

3. Risk Management Plans

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. 7401 et seq. ("Act"), the permittee shall comply with the requirement to register such a plan.

4. Title IV Provisions

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

5. Severability Clause

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition declared invalid.

Cooper Engineered Products

Facility ID: 0387020045

PTI Application: 03-13984

Issued: To be entered upon final issuance

6. General Requirements

- a. The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and reissuance, or modification, or for denial of a permit renewal application.
- b. It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.
- c. This permit may be modified, reopened, revoked, or revoked and reissued, for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.
- d. This permit does not convey any property rights of any sort, or any exclusive privilege.
- e. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

7. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit To Install fees within 30 days after the issuance of this Permit To Install.

8. Federal and State Enforceability

Only those terms and conditions designated in this permit as federally enforceable, that are required under the Act, or any of its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA, the State, and citizens under the Act. All other terms and conditions of this permit

shall not be federally enforceable and shall be enforceable under State law only.

9. Compliance Requirements

- a. Any document (including reports) required to be submitted and required by a federally applicable requirement in this permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.
- b. Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:
 - i. At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.
 - ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with ORC section 3704.08.
 - iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.
 - iv. As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.
- c. The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually, or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:
 - i. Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
 - ii. An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

10. Permit To Operate Application

- a. If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete

Cooper Engineered Products

Facility ID: 0387020045

PTI Application: 03-13984

Issued: To be entered upon final issuance

Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).

- b. If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35, the source(s) identified in this Permit To Install is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the source(s) covered by this permit.

11. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

12. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

Cooper Engineered Products

Facility ID: 0387020045

PTI Application: 03-13984

Issued: To be entered upon final issuance

B. State Only Enforceable Permit To Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping of state-only enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from state-only required emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

4. Termination of Permit To Install

This permit to install shall terminate within eighteen months of the effective date of the permit to install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

Cooper Engineered Products

Facility ID: 0387020045

PTI Application: 03-13984

Issued: To be entered upon final issuance

5. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

6. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

7. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

8. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the

Cooper Engineered Products

Facility ID: 0387020045

PTI Application: 03-13984

Issued: To be entered upon final issuance

facility has been constructed in accordance with the Permit To Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

9. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations (See Section A of This Permit)

If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.

C. Permit To Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
VOC	20.8

13

Cooper Engineered Products

PTI Application: 03-13984

Issued: To be entered upon final issuance

Facility ID: 0387020045

Cooper Engineered Products

Facility ID: 0387020045

PTI Application: 03-13984

Issued: To be entered upon final issuance

Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

A. State and Federally Enforceable Permit To Install Facility Specific Terms and Conditions

None

B. State Only Enforceable Permit To Install Facility Specific Terms and Conditions

None

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P003 - Cascade Line #2 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P003)	OAC rule 3745-31-05(A)(3)	1.74 pounds volatile organic compounds (VOC)/hour and 7.6 tons VOC/year See A.I.2.a.
	OAC rule 3745-31-05(D)	20.8 tons VOC/rolling, 12-month period (See A.I.2.b.) from units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

2. Additional Terms and Conditions

- 2.a The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(D).
- 2.b The permittee has requested a federally enforceable, combined emission limitation for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054 of 20.8 tons VOC per rolling 12-month period based on production restrictions for purposes of maintaining PSD minor facility status (see A.II.1.).
- 2.c The emissions unit is not subject to the requirements of OAC rule 3745-21-07(G) because liquid organic materials are not employed.

II. Operational Restrictions

1. The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined, shall not exceed 25,000 tons of rubber per year, based on a rolling, 12-month summation of the monthly production rates.

Emissions Unit ID: P003

2. The operational restriction in A.II.1 is an "existing" restriction which was established in PTI No. 03-13066 issued on March 27, 2001. The permittee has current records demonstrating compliance with this restriction, therefore no additional restrictions are needed during the first 12 months of operation to ensure federal enforceability.

III. Monitoring and/or Recordkeeping Requirements

1. In order to demonstrate compliance with the combined emission limitation of 20.8 tons per rolling, 12-month period and the maximum allowable production limit of 25,000 tons of rubber per rolling, 12-month period, the permittee shall collect and record the following information each month for the following grouped emission units combined: P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054:
 - a. the quantity of rubber cured and extruded, in tons;
 - b. the monthly VOC emission rate*, in tons;
 - c. the rolling, 12- month summation of the quantity of rubber cured and extruded, in tons; and,
 - d. the rolling, 12- month summation of the emission rate for VOC, in tons.

*The permittee shall use the most current Rubber Manufacturers Association (RMA) emission factors, available for these operations. At the time of issuance of this permit, these emission factors are 8.25E-4 pound VOC per pound of rubber cured and 3.52E-6 pound VOC per pound of rubber extruded.

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify any exceedance of the following:
 - a. the annual rubber production limitation of 25,000 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined; and,
 - b. the VOC emission limitation of 20.8 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

These deviation reports shall be submitted in accordance with the General Terms and Conditions of this permit.

V. Testing Requirements

1. Compliance with the allowable emission limitations in this permit shall be determined according to

Issued: To be entered upon final issuance

the following methods:

- a. Emission Limitation:
1.74 pounds VOC/hour, 7.6 tons VOC/year

Applicable Compliance Method:

The hourly and annual VOC limits for rubber curing & extruding are based on the emission unit's potential to emit (maximum rubber throughput of 2100 pounds/hour multiplied by the RMA emission factors for rubber curing & extruding, see A.III.1.), at a maximum operating schedule of 8760 hrs/yr. Therefore, no record keeping, deviation reporting, or compliance method calculations are required to demonstrate compliance with these limits. If required, compliance with the hourly emissions rate shall be based on stack testing using the methods and procedures specified in Methods 1-4 and 25/25A of 40 CFR Part 60, Appendix A.

- b. Emission Limitation:
20.8 tons/rolling, 12-month period from emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

- c. Emission Limitation:
The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined shall not exceed 25,000 tons of rubber per rolling, 12-month period.

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

VI. Miscellaneous Requirements

None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P003 - Cascade Line #2 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P003)		See B.III. below

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

- 1. The permit to install for this emissions unit was evaluated based on the actual materials used and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant:

Pollutant: acetophenone
 TLV (mg/m3): 49
 Maximum Hourly Emission Rate (lbs/hr): 0.48
 Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 136.8
 MAGLC (ug/m3): 1,167

19

Coope

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: P003

Issued: To be entered upon final issuance

Pollutant: carbon disulfide

TLV (mg/m3): 31

Maximum Hourly Emission Rate (lbs/hr): 1.36

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 181.6

MAGLC (ug/m3): 738

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and,
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

2. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still

satisfies the "Air Toxic Policy"; and,

- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

22

Coope
PTI A

Emissions Unit ID: P003

Issued: To be entered upon final issuance

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Coope
PTI A

Emissions Unit ID: P005

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P005 - Cascade Line #3 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P005)	OAC rule 3745-31-05(A)(3)	1.74 pounds volatile organic compounds (VOC)/hour and 7.6 tons VOC/year See A.I.2.a.
	OAC rule 3745-31-05(D)	20.8 tons VOC/rolling, 12-month period (See A.I.2.b.) from units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

2. Additional Terms and Conditions

- 2.a The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(D).
- 2.b The permittee has requested a federally enforceable, combined emission limitation for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054 of 20.8 tons VOC per rolling 12-month period based on production restrictions for purposes of maintaining PSD minor facility status (see A.II.1.).
- 2.c The emissions unit is not subject to the requirements of OAC rule 3745-21-07(G) because liquid organic materials are not employed.

II. Operational Restrictions

Issued: To be entered upon final issuance

1. The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined, shall not exceed 25,000 tons of rubber per year, based on a rolling, 12-month summation of the monthly production rates.
2. The operational restriction in A.II.1 is an "existing" restriction which was established in PTI No. 03-13066 issued on March 27, 2001. The permittee has current records demonstrating compliance with this restriction, therefore no additional restrictions are needed during the first 12 months of operation to ensure federal enforceability.

III. Monitoring and/or Recordkeeping Requirements

1. In order to demonstrate compliance with the combined emission limitation of 20.8 tons per rolling, 12-month period and the maximum allowable production limit of 25,000 tons of rubber per rolling, 12-month period, the permittee shall collect and record the following information each month for the following grouped emission units combined: P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054:
 - a. the quantity of rubber cured and extruded, in tons;
 - b. the monthly VOC emission rate*, in tons;
 - c. the rolling, 12- month summation of the quantity of rubber cured and extruded, in tons; and,
 - d. the rolling, 12- month summation of the emission rate for VOC, in tons.

*The permittee shall use the most current Rubber Manufacturers Association (RMA) emission factors, available for these operations. At the time of issuance of this permit, these emission factors are 8.25E-4 pound VOC per pound of rubber cured and 3.52E-6 pound VOC per pound of rubber extruded.

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify any exceedance of the following:
 - a. the annual rubber production limitation of 25,000 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined; and,

Emissions Unit ID: P005

- b. the VOC emission limitation of 20.8 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

These deviation reports shall be submitted in accordance with the General Terms and Conditions of this permit.

V. Testing Requirements

1. Compliance with the allowable emission limitations in this permit shall be determined according to the following methods:

- a. Emission Limitation:
1.74 pounds VOC/hour, 7.6 tons VOC/year

Applicable Compliance Method:

The hourly and annual VOC limits for rubber curing & extruding are based on the emission unit's potential to emit (maximum rubber throughput of 2100 pounds/hour multiplied by the RMA emission factors for rubber curing & extruding, see A.III.1.), at a maximum operating schedule of 8760 hrs/yr. Therefore, no record keeping, deviation reporting, or compliance method calculations are required to demonstrate compliance with these limits. If required, compliance with the hourly emissions rate shall be based on stack testing using the methods and procedures specified in Methods 1-4 and 25/25A of 40 CFR Part 60, Appendix A.

- b. Emission Limitation:
20.8 tons/rolling, 12-month period from emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

- c. Emission Limitation:
The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined shall not exceed 25,000 tons of rubber per rolling, 12-month period.

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

VI. Miscellaneous Requirements

None

Coope
PTI A

Emissions Unit ID: P005

Issued: To be entered upon final issuance

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P005 - Cascade Line #3 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P005)		See B.III. below

2. Additional Terms and Conditions

- 2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit was evaluated based on the actual materials used and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant:

Pollutant: acetophenone

Cooper Engineered Products
PTI Application: 02 12084
Issued

Facility ID: 0387020045

Emissions Unit ID: P005

TLV (mg/m3): 49

Maximum Hourly Emission Rate (lbs/hr): 0.48

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 136.8

MAGLC (ug/m3): 1,167

Issued: To be entered upon final issuance

Pollutant: carbon disulfide

TLV (mg/m3): 31

Maximum Hourly Emission Rate (lbs/hr): 1.36

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 181.6

MAGLC (ug/m3): 738

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and,
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

2. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still

Issued: To be entered upon final issuance

satisfies the "Air Toxic Policy"; and,

- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

30

**Coope
PTI A**

Emissions Unit ID: P005

Issued: To be entered upon final issuance

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P012 - Flock Line #1 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P012)	OAC rule 3745-31-05(A)(3)	0.99 pound volatile organic compounds (VOC)/hour and 4.3 tons VOC/year See A.I.2.a.
	OAC rule 3745-31-05(D)	20.8 tons VOC/rolling, 12-month period (See A.I.2.b.) from units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

2. Additional Terms and Conditions

- 2.a The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(D).
- 2.b The permittee has requested a federally enforceable, combined emission limitation for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054 of 20.8 tons VOC per rolling 12-month period based on production restrictions for purposes of maintaining PSD minor facility status (see A.II.1.).
- 2.c The emissions unit is not subject to the requirements of OAC rule 3745-21-07(G) because liquid organic materials are not employed.

II. Operational Restrictions

Emissions Unit ID: P012

1. The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined, shall not exceed 25,000 tons of rubber per year, based on a rolling, 12-month summation of the monthly production rates.
2. The operational restriction in A.II.1 is an "existing" restriction which was established in PTI No. 03-13066 issued on March 27, 2001. The permittee has current records demonstrating compliance with this restriction, therefore no additional restrictions are needed during the first 12 months of operation to ensure federal enforceability.

III. Monitoring and/or Recordkeeping Requirements

1. In order to demonstrate compliance with the combined emission limitation of 20.8 tons per rolling, 12-month period and the maximum allowable production limit of 25,000 tons of rubber per rolling, 12-month period, the permittee shall collect and record the following information each month for the following grouped emission units combined: P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054:
 - a. the quantity of rubber cured and extruded, in tons;
 - b. the monthly VOC emission rate*, in tons;
 - c. the rolling, 12- month summation of the quantity of rubber cured and extruded, in tons; and,
 - d. the rolling, 12- month summation of the emission rate for VOC, in tons.

*The permittee shall use the most current Rubber Manufacturers Association (RMA) emission factors, available for these operations. At the time of issuance of this permit, these emission factors are 8.25E-4 pound VOC per pound of rubber cured and 3.52E-6 pound VOC per pound of rubber extruded.

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify any exceedance of the following:
 - a. the annual rubber production limitation of 25,000 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined; and,
 - b. the VOC emission limitation of 20.8 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

These deviation reports shall be submitted in accordance with the General Terms and Conditions

Issued: To be entered upon final issuance
of this permit.

V. Testing Requirements

1. Compliance with the allowable emission limitations in this permit shall be determined according to the following methods:

- a. Emission Limitation:
0.99 pound VOC/hour, 4.3 tons VOC/year

Applicable Compliance Method:

The hourly and annual VOC limits for rubber curing & extruding are based on the emission unit's potential to emit (maximum rubber throughput of 1200 pounds/hour multiplied by the RMA emission factors for rubber curing & extruding, see A.III.1.), at a maximum operating schedule of 8760 hrs/yr. Therefore, no record keeping, deviation reporting, or compliance method calculations are required to demonstrate compliance with these limits. If required, compliance with the hourly emissions rate shall be based on stack testing using the methods and procedures specified in Methods 1-4 and 25/25A of 40 CFR Part 60, Appendix A.

- b. Emission Limitation:
20.8 tons/rolling, 12-month period from emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

- c. Emission Limitation:
The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined shall not exceed 25,000 tons of rubber per rolling, 12-month period.

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

VI. Miscellaneous Requirements

None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P012 - Flock Line #1 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P012)		See B.III. below

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

- 1. The permit to install for this emissions unit was evaluated based on the actual materials used and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant:

Pollutant: acetophenone
 TLV (mg/m3): 49
 Maximum Hourly Emission Rate (lbs/hr): 0.48
 Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 136.8
 MAGLC (ug/m3): 1,167

Issued: To be entered upon final issuance

Pollutant: carbon disulfide

TLV (mg/m3): 31

Maximum Hourly Emission Rate (lbs/hr): 1.36

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 181.6

MAGLC (ug/m3): 738

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and,
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

2. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:":
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still

satisfies the "Air Toxic Policy"; and,

- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Coope
PTI A

Emissions Unit ID: P016

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P016 - Flock Line #2 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P016)	OAC rule 3745-31-05(A)(3)	0.99 pound volatile organic compounds (VOC)/hour and 4.3 tons VOC/year See A.I.2.a.
	OAC rule 3745-31-05(D)	20.8 tons VOC/rolling, 12-month period (See A.I.2.b.) from units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

2. Additional Terms and Conditions

- 2.a** The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(D).
- 2.b** The permittee has requested a federally enforceable, combined emission limitation for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054 of 20.8 tons VOC per rolling 12-month period based on production restrictions for purposes of maintaining PSD minor facility status (see A.II.1.).
- 2.c** The emissions unit is not subject to the requirements of OAC rule 3745-21-07(G) because liquid organic materials are not employed.

II. Operational Restrictions

Issued: To be entered upon final issuance

1. The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined, shall not exceed 25,000 tons of rubber per year, based on a rolling, 12-month summation of the monthly production rates.
2. The operational restriction in A.II.1 is an "existing" restriction which was established in PTI No. 03-13066 issued on March 27, 2001. The permittee has current records demonstrating compliance with this restriction, therefore no additional restrictions are needed during the first 12 months of operation to ensure federal enforceability.

III. Monitoring and/or Recordkeeping Requirements

1. In order to demonstrate compliance with the combined emission limitation of 20.8 tons per rolling, 12-month period and the maximum allowable production limit of 25,000 tons of rubber per rolling, 12-month period, the permittee shall collect and record the following information each month for the following grouped emission units combined: P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054:
 - a. the quantity of rubber cured and extruded, in tons;
 - b. the monthly VOC emission rate*, in tons;
 - c. the rolling, 12- month summation of the quantity of rubber cured and extruded, in tons; and,
 - d. the rolling, 12- month summation of the emission rate for VOC, in tons.

*The permittee shall use the most current Rubber Manufacturers Association (RMA) emission factors, available for these operations. At the time of issuance of this permit, these emission factors are 8.25E-4 pound VOC per pound of rubber cured and 3.52E-6 pound VOC per pound of rubber extruded.

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify any exceedance of the following:
 - a. the annual rubber production limitation of 25,000 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined; and,

Emissions Unit ID: P016

- b. the VOC emission limitation of 20.8 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

These deviation reports shall be submitted in accordance with the General Terms and Conditions of this permit.

V. Testing Requirements

1. Compliance with the allowable emission limitations in this permit shall be determined according to the following methods:

- a. Emission Limitation:
0.99 pound VOC/hour, 4.3 tons VOC/year

Applicable Compliance Method:

The hourly and annual VOC limits for rubber curing & extruding are based on the emission unit's potential to emit (maximum rubber throughput of 1200 pounds/hour multiplied by the RMA emission factors for rubber curing & extruding, see A.III.1.), at a maximum operating schedule of 8760 hrs/yr. Therefore, no record keeping, deviation reporting, or compliance method calculations are required to demonstrate compliance with these limits. If required, compliance with the hourly emissions rate shall be based on stack testing using the methods and procedures specified in Methods 1-4 and 25/25A of 40 CFR Part 60, Appendix A.

- b. Emission Limitation:
20.8 tons/rolling, 12-month period from emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

- c. Emission Limitation:
The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined shall not exceed 25,000 tons of rubber per rolling, 12-month period.

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

VI. Miscellaneous Requirements

None

Coope
PTI A

Emissions Unit ID: P016

Issued: To be entered upon final issuance

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P016 - Flock Line #2 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P016)		See B.III. below

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit was evaluated based on the actual materials used and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant:

Pollutant: acetophenone

Issued: To be entered upon final issuanceTLV (mg/m³): 49

Maximum Hourly Emission Rate (lbs/hr): 0.48

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 136.8MAGLC (ug/m³): 1,167

Pollutant: carbon disulfide

TLV (mg/m³): 31

Maximum Hourly Emission Rate (lbs/hr): 1.36

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 181.6MAGLC (ug/m³): 738

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and,
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

2. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and,
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Coope
PTI A

Emissions Unit ID: P019

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P019 - Flock Line #3 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P019)	OAC rule 3745-31-05(A)(3)	0.99 pound volatile organic compounds (VOC)/hour and 4.3 tons VOC/year See A.I.2.a.
	OAC rule 3745-31-05(D)	20.8 tons VOC/rolling, 12-month period (See A.I.2.b.) from units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

2. Additional Terms and Conditions

- 2.a The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(D).
- 2.b The permittee has requested a federally enforceable, combined emission limitation for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054 of 20.8 tons VOC per rolling 12-month period based on production restrictions for purposes of maintaining PSD minor facility status (see A.II.1.).
- 2.c The emissions unit is not subject to the requirements of OAC rule 3745-21-07(G) because liquid organic materials are not employed.

II. Operational Restrictions

Emissions Unit ID: P019

1. The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined, shall not exceed 25,000 tons of rubber per year, based on a rolling, 12-month summation of the monthly production rates.
2. The operational restriction in A.II.1 is an "existing" restriction which was established in PTI No. 03-13066 issued on March 27, 2001. The permittee has current records demonstrating compliance with this restriction, therefore no additional restrictions are needed during the first 12 months of operation to ensure federal enforceability.

III. Monitoring and/or Recordkeeping Requirements

1. In order to demonstrate compliance with the combined emission limitation of 20.8 tons per rolling, 12-month period and the maximum allowable production limit of 25,000 tons of rubber per rolling, 12-month period, the permittee shall collect and record the following information each month for the following grouped emission units combined: P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054:
 - a. the quantity of rubber cured and extruded, in tons;
 - b. the monthly VOC emission rate*, in tons;
 - c. the rolling, 12- month summation of the quantity of rubber cured and extruded, in tons; and,
 - d. the rolling, 12- month summation of the emission rate for VOC, in tons.

*The permittee shall use the most current Rubber Manufacturers Association (RMA) emission factors, available for these operations. At the time of issuance of this permit, these emission factors are 8.25E-4 pound VOC per pound of rubber cured and 3.52E-6 pound VOC per pound of rubber extruded.

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify any exceedance of the following:
 - a. the annual rubber production limitation of 25,000 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined; and,
 - b. the VOC emission limitation of 20.8 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

These deviation reports shall be submitted in accordance with the General Terms and Conditions

Issued: To be entered upon final issuance
of this permit.

V. Testing Requirements

1. Compliance with the allowable emission limitations in this permit shall be determined according to the following methods:

- a. Emission Limitation:
0.99 pound VOC/hour, 4.3 tons VOC/year

Applicable Compliance Method:

The hourly and annual VOC limits for rubber curing & extruding are based on the emission unit's potential to emit (maximum rubber throughput of 1200 pounds/hour multiplied by the RMA emission factors for rubber curing & extruding, see A.III.1.), at a maximum operating schedule of 8760 hrs/yr. Therefore, no record keeping, deviation reporting, or compliance method calculations are required to demonstrate compliance with these limits. If required, compliance with the hourly emissions rate shall be based on stack testing using the methods and procedures specified in Methods 1-4 and 25/25A of 40 CFR Part 60, Appendix A.

- b. Emission Limitation:
20.8 tons/rolling, 12-month period from emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

- c. Emission Limitation:
The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined shall not exceed 25,000 tons of rubber per rolling, 12-month period.

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

VI. Miscellaneous Requirements

None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P019 - Flock Line #3 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P019)		See B.III. below

2. Additional Terms and Conditions

- None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

- The permit to install for this emissions unit was evaluated based on the actual materials used and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant:

Pollutant: acetophenone

TLV (mg/m³): 49

Maximum Hourly Emission Rate (lbs/hr): 0.48

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 136.8

MAGLC (ug/m³): 1,167

Issued: To be entered upon final issuance

Pollutant: carbon disulfide

TLV (mg/m3): 31

Maximum Hourly Emission Rate (lbs/hr): 1.36

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 181.6

MAGLC (ug/m3): 738

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and,
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

2. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still

satisfies the "Air Toxic Policy"; and,

- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P023 - Dual Durometer #6 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P023)	OAC rule 3745-31-05(A)(3)	0.99 pound volatile organic compounds (VOC)/hour and 4.3 tons VOC/year See A.I.2.a.
	OAC rule 3745-31-05(D)	20.8 tons VOC/rolling, 12-month period (See A.I.2.b.) from units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

2. Additional Terms and Conditions

- 2.a The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(D).
- 2.b The permittee has requested a federally enforceable, combined emission limitation for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054 of 20.8 tons VOC per rolling 12-month period based on production restrictions for purposes of maintaining PSD minor facility status (see A.II.1.).
- 2.c The emissions unit is not subject to the requirements of OAC rule 3745-21-07(G) because liquid organic materials are not employed.

II. Operational Restrictions

Issued: To be entered upon final issuance

1. The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined, shall not exceed 25,000 tons of rubber per year, based on a rolling, 12-month summation of the monthly production rates.
2. The operational restriction in A.II.1 is an "existing" restriction which was established in PTI No. 03-13066 issued on March 27, 2001. The permittee has current records demonstrating compliance with this restriction, therefore no additional restrictions are needed during the first 12 months of operation to ensure federal enforceability.

III. Monitoring and/or Recordkeeping Requirements

1. In order to demonstrate compliance with the combined emission limitation of 20.8 tons per rolling, 12-month period and the maximum allowable production limit of 25,000 tons of rubber per rolling, 12-month period, the permittee shall collect and record the following information each month for the following grouped emission units combined: P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054:
 - a. the quantity of rubber cured and extruded, in tons;
 - b. the monthly VOC emission rate*, in tons;
 - c. the rolling, 12- month summation of the quantity of rubber cured and extruded, in tons; and,
 - d. the rolling, 12- month summation of the emission rate for VOC, in tons.

*The permittee shall use the most current Rubber Manufacturers Association (RMA) emission factors, available for these operations. At the time of issuance of this permit, these emission factors are 8.25E-4 pound VOC per pound of rubber cured and 3.52E-6 pound VOC per pound of rubber extruded.

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify any exceedance of the following:
 - a. the annual rubber production limitation of 25,000 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined; and,

Emissions Unit ID: P023

- b. the VOC emission limitation of 20.8 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

These deviation reports shall be submitted in accordance with the General Terms and Conditions of this permit.

V. Testing Requirements

1. Compliance with the allowable emission limitations in this permit shall be determined according to the following methods:

- a. Emission Limitation:
0.99 pound VOC/hour, 3.3 tons VOC/year

Applicable Compliance Method:

The hourly and annual VOC limits for rubber curing & extruding are based on the emission unit's potential to emit (maximum rubber throughput of 1200 pounds/hour multiplied by the RMA emission factors for rubber curing & extruding, see A.III.1.), at a maximum operating schedule of 8760 hrs/yr. Therefore, no record keeping, deviation reporting, or compliance method calculations are required to demonstrate compliance with these limits. If required, compliance with the hourly emissions rate shall be based on stack testing using the methods and procedures specified in Methods 1-4 and 25/25A of 40 CFR Part 60, Appendix A.

- b. Emission Limitation:
20.8 tons/rolling, 12-month period from emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

- c. Emission Limitation:
The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined shall not exceed 25,000 tons of rubber per rolling, 12-month period.

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

VI. Miscellaneous Requirements

None

Coope
PTI A

Emissions Unit ID: P023

Issued: To be entered upon final issuance

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P023 - Dual Durometer #6 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P023)		See B.III. below

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit was evaluated based on the actual materials used and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant:

Pollutant: acetophenone

53

Coope

PTI A

Emissions Unit ID: P023

Issued: To be entered upon final issuance

TLV (mg/m3): 49

Maximum Hourly Emission Rate (lbs/hr): 0.48

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 136.8

MAGLC (ug/m3): 1,167

Pollutant: carbon disulfide

TLV (mg/m³): 31

Maximum Hourly Emission Rate (lbs/hr): 1.36

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 181.6

MAGLC (ug/m³): 738

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and,
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

2. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and,
 - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

55

Coope

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: P023

56

**Coope
PTI A**

Emissions Unit ID: P023

Issued: To be entered upon final issuance

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P026 - Dual Durometer #7 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P026)	OAC rule 3745-31-05(A)(3)	0.99 pound volatile organic compounds (VOC)/hour and 4.3 tons VOC/year See A.I.2.a.
	OAC rule 3745-31-05(D)	20.8 tons VOC/rolling, 12-month period (See A.I.2.b.) from units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

2. Additional Terms and Conditions

- 2.a The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(D).
- 2.b The permittee has requested a federally enforceable, combined emission limitation for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054 of 20.8 tons VOC per rolling 12-month period based on production restrictions for purposes of maintaining PSD minor facility status (see A.II.1.).
- 2.c The emissions unit is not subject to the requirements of OAC rule 3745-21-07(G) because liquid organic materials are not employed.

II. Operational Restrictions

Emissions Unit ID: P026

1. The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined, shall not exceed 25,000 tons of rubber per year, based on a rolling, 12-month summation of the monthly production rates.
2. The operational restriction in A.II.1 is an "existing" restriction which was established in PTI No. 03-13066 issued on March 27, 2001. The permittee has current records demonstrating compliance with this restriction, therefore no additional restrictions are needed during the first 12 months of operation to ensure federal enforceability.

III. Monitoring and/or Recordkeeping Requirements

1. In order to demonstrate compliance with the combined emission limitation of 20.8 tons per rolling, 12-month period and the maximum allowable production limit of 25,000 tons of rubber per rolling, 12-month period, the permittee shall collect and record the following information each month for the following grouped emission units combined: P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054:
 - a. the quantity of rubber cured and extruded, in tons;
 - b. the monthly VOC emission rate*, in tons;
 - c. the rolling, 12- month summation of the quantity of rubber cured and extruded, in tons; and,
 - d. the rolling, 12- month summation of the emission rate for VOC, in tons.

*The permittee shall use the most current Rubber Manufacturers Association (RMA) emission factors, available for these operations. At the time of issuance of this permit, these emission factors are 8.25E-4 pound VOC per pound of rubber cured and 3.52E-6 pound VOC per pound of rubber extruded.

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify any exceedance of the following:
 - a. the annual rubber production limitation of 25,000 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined; and,
 - b. the VOC emission limitation of 20.8 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

These deviation reports shall be submitted in accordance with the General Terms and Conditions

Issued: To be entered upon final issuance
of this permit.

V. Testing Requirements

1. Compliance with the allowable emission limitations in this permit shall be determined according to the following methods:

- a. Emission Limitation:
0.99 pound VOC/hour, 4.3 tons VOC/year

Applicable Compliance Method:

The hourly and annual VOC limits for rubber curing & extruding are based on the emission unit's potential to emit (maximum rubber throughput of 1200 pounds/hour multiplied by the RMA emission factors for rubber curing & extruding, see A.III.1.), at a maximum operating schedule of 8760 hrs/yr. Therefore, no record keeping, deviation reporting, or compliance method calculations are required to demonstrate compliance with these limits. If required, compliance with the hourly emissions rate shall be based on stack testing using the methods and procedures specified in Methods 1-4 and 25/25A of 40 CFR Part 60, Appendix A.

- b. Emission Limitation:
20.8 tons/rolling, 12-month period from emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

- c. Emission Limitation:
The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined shall not exceed 25,000 tons of rubber per rolling, 12-month period.

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

VI. Miscellaneous Requirements

None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P026 - Dual Durometer #7 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P026)		See B.III. below

2. Additional Terms and Conditions

- None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

- The permit to install for this emissions unit was evaluated based on the actual materials used and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant:

Pollutant: acetophenone

TLV (mg/m³): 49

Maximum Hourly Emission Rate (lbs/hr): 0.48

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 136.8

MAGLC (ug/m³): 1,167

61

Coope

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: P026

Issued: To be entered upon final issuance

Pollutant: carbon disulfide

TLV (mg/m³): 31

Maximum Hourly Emission Rate (lbs/hr): 1.36

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 181.6

MAGLC (ug/m³): 738

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and,
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

2. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still

satisfies the "Air Toxic Policy"; and,

- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

64

**Coope
PTI A**

Emissions Unit ID: P026

Issued: To be entered upon final issuance

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P028 - Dual Durometer #8 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P028)	OAC rule 3745-31-05(A)(3)	0.99 pound volatile organic compounds (VOC)/hour and 4.3 tons VOC/year See A.I.2.a.
	OAC rule 3745-31-05(D)	20.8 tons VOC/rolling, 12-month period (See A.I.2.b.) from units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

2. Additional Terms and Conditions

- 2.a The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(D).
- 2.b The permittee has requested a federally enforceable, combined emission limitation for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054 of 20.8 tons VOC per rolling 12-month period based on production restrictions for purposes of maintaining PSD minor facility status (see A.II.1.).
- 2.c The emissions unit is not subject to the requirements of OAC rule 3745-21-07(G) because liquid organic materials are not employed.

II. Operational Restrictions

Issued: To be entered upon final issuance

1. The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined, shall not exceed 25,000 tons of rubber per year, based on a rolling, 12-month summation of the monthly production rates.
2. The operational restriction in A.II.1 is an "existing" restriction which was established in PTI No. 03-13066 issued on March 27, 2001. The permittee has current records demonstrating compliance with this restriction, therefore no additional restrictions are needed during the first 12 months of operation to ensure federal enforceability.

III. Monitoring and/or Recordkeeping Requirements

1. In order to demonstrate compliance with the combined emission limitation of 20.8 tons per rolling, 12-month period and the maximum allowable production limit of 25,000 tons of rubber per rolling, 12-month period, the permittee shall collect and record the following information each month for the following grouped emission units combined: P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054:
 - a. the quantity of rubber cured and extruded, in tons;
 - b. the monthly VOC emission rate*, in tons;
 - c. the rolling, 12- month summation of the quantity of rubber cured and extruded, in tons; and,
 - d. the rolling, 12- month summation of the emission rate for VOC, in tons.

*The permittee shall use the most current Rubber Manufacturers Association (RMA) emission factors, available for these operations. At the time of issuance of this permit, these emission factors are 8.25E-4 pound VOC per pound of rubber cured and 3.52E-6 pound VOC per pound of rubber extruded.

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify any exceedance of the following:
 - a. the annual rubber production limitation of 25,000 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined; and,

Emissions Unit ID: P028

- b. the VOC emission limitation of 20.8 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

These deviation reports shall be submitted in accordance with the General Terms and Conditions of this permit.

V. Testing Requirements

1. Compliance with the allowable emission limitations in this permit shall be determined according to the following methods:

- a. Emission Limitation:
0.99 pound VOC/hour, 4.3 tons VOC/year

Applicable Compliance Method:

The hourly and annual VOC limits for rubber curing & extruding are based on the emission unit's potential to emit (maximum rubber throughput of 1200 pounds/hour multiplied by the RMA emission factors for rubber curing & extruding, see A.III.1.), at a maximum operating schedule of 8760 hrs/yr. Therefore, no record keeping, deviation reporting, or compliance method calculations are required to demonstrate compliance with these limits. If required, compliance with the hourly emissions rate shall be based on stack testing using the methods and procedures specified in Methods 1-4 and 25/25A of 40 CFR Part 60, Appendix A.

- b. Emission Limitation:
20.8 tons/rolling, 12-month period from emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

- c. Emission Limitation:
The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined shall not exceed 25,000 tons of rubber per rolling, 12-month period.

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

VI. Miscellaneous Requirements

None

Coope
PTI A

Emissions Unit ID: P028

Issued: To be entered upon final issuance

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P028 - Dual Durometer #8 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P028)		See B.III. below

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit was evaluated based on the actual materials used and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant:

Pollutant: acetophenone

Cooper Engineered Products
PTI Application: 02 12084
Issued

Facility ID: 0387020045

Emissions Unit ID: P028

TLV (mg/m3): 49

Maximum Hourly Emission Rate (lbs/hr): 0.48

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 136.8

MAGLC (ug/m3): 1,167

Issued: To be entered upon final issuance

Pollutant: carbon disulfide

TLV (mg/m³): 31

Maximum Hourly Emission Rate (lbs/hr): 1.36

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 181.6

MAGLC (ug/m³): 738

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and,
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

2. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still

Issued: To be entered upon final issuance

satisfies the "Air Toxic Policy"; and,

- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

72

**Coope
PTI A**

Emissions Unit ID: P028

Issued: To be entered upon final issuance

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Coope
PTI A

Emissions Unit ID: P038

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P038 - Cascade Line #1 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P038)	OAC rule 3745-31-05(A)(3)	1.74 lbs volatile organic compounds (VOC)/hour and 7.6 tons VOC/year See A.I.2.a.
	OAC rule 3745-31-05(D)	20.8 tons VOC/rolling, 12-month period (See A.I.2.b.) from units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

2. Additional Terms and Conditions

- 2.a The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(D).
- 2.b The permittee has requested a federally enforceable, combined emission limitation for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054 of 20.8 tons VOC per rolling 12-month period based on production restrictions for purposes of maintaining PSD minor facility status (see A.II.1.).
- 2.c The emissions unit is not subject to the requirements of OAC rule 3745-21-07(G) because liquid organic materials are not employed.

II. Operational Restrictions

Emissions Unit ID: P038

1. The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined, shall not exceed 25,000 tons of rubber per year, based on a rolling, 12-month summation of the monthly production rates.
2. The operational restriction in A.II.1 is an "existing" restriction which was established in PTI No. 03-13066 issued on March 27, 2001. The permittee has current records demonstrating compliance with this restriction, therefore no additional restrictions are needed during the first 12 months of operation to ensure federal enforceability.

III. Monitoring and/or Recordkeeping Requirements

1. In order to demonstrate compliance with the combined emission limitation of 20.8 tons per rolling, 12-month period and the maximum allowable production limit of 25,000 tons of rubber per rolling, 12-month period, the permittee shall collect and record the following information each month for the following grouped emission units combined: P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054:
 - a. the quantity of rubber cured and extruded, in tons;
 - b. the monthly VOC emission rate*, in tons;
 - c. the rolling, 12- month summation of the quantity of rubber cured and extruded, in tons; and,
 - d. the rolling, 12- month summation of the emission rate for VOC, in tons.

*The permittee shall use the most current Rubber Manufacturers Association (RMA) emission factors, available for these operations. At the time of issuance of this permit, these emission factors are 8.25E-4 pound VOC per pound of rubber cured and 3.52E-6 pound VOC per pound of rubber extruded.

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify any exceedance of the following:
 - a. the annual rubber production limitation of 25,000 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined; and,
 - b. the VOC emission limitation of 20.8 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

These deviation reports shall be submitted in accordance with the General Terms and Conditions

Issued: To be entered upon final issuance
of this permit.

V. Testing Requirements

1. Compliance with the allowable emission limitations in this permit shall be determined according to the following methods:

- a. Emission Limitation:
1.74 pounds VOC/hour, 7.6 tons VOC/year

Applicable Compliance Method:

The hourly and annual VOC limits for rubber curing & extruding are based on the emission unit's potential to emit (maximum rubber throughput of 2100 pounds/hour multiplied by the RMA emission factors for rubber curing & extruding, see A.III.1.), at a maximum operating schedule of 8760 hrs/yr. Therefore, no record keeping, deviation reporting, or compliance method calculations are required to demonstrate compliance with these limits. If required, compliance with the hourly emissions rate shall be based on stack testing using the methods and procedures specified in Methods 1-4 and 25/25A of 40 CFR Part 60, Appendix A.

- b. Emission Limitation:
20.8 tons/rolling, 12-month period from emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

- c. Emission Limitation:
The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined shall not exceed 25,000 tons of rubber per rolling, 12-month period.

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

VI. Miscellaneous Requirements

None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P038 - Cascade Line #1 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P038)		See B.III. below

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

- 1. The permit to install for this emissions unit was evaluated based on the actual materials used and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant:

Pollutant: acetophenone
 TLV (mg/m3): 49
 Maximum Hourly Emission Rate (lbs/hr): 0.48
 Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 136.8
 MAGLC (ug/m3): 1,167

77

Coope

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: P038

Issued: To be entered upon final issuance

Pollutant: carbon disulfide

TLV (mg/m³): 31

Maximum Hourly Emission Rate (lbs/hr): 1.36

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 181.6

MAGLC (ug/m³): 738

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and,
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

2. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still

satisfies the "Air Toxic Policy"; and,

- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

80

Coope

PTI A

Emissions Unit ID: P038

Issued: To be entered upon final issuance

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Coope
PTI A

Emissions Unit ID: P046

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P046 - Dual Durometer #9 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P046)	OAC rule 3745-31-05(A)(3)	0.99 pound volatile organic compounds (VOC)/hour and 4.3 tons VOC/year See A.I.2.a.
	OAC rule 3745-31-05(D)	20.8 tons VOC/rolling, 12-month period (See A.I.2.b.) from units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

2. Additional Terms and Conditions

- 2.a The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(D).
- 2.b The permittee has requested a federally enforceable, combined emission limitation for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054 of 20.8 tons VOC per rolling 12-month period based on production restrictions for purposes of maintaining PSD minor facility status (see A.II.1.).
- 2.c The emissions unit is not subject to the requirements of OAC rule 3745-21-07(G) because liquid organic materials are not employed.

II. Operational Restrictions

Issued: To be entered upon final issuance

1. The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined, shall not exceed 25,000 tons of rubber per year, based on a rolling, 12-month summation of the monthly production rates.
2. The operational restriction in A.II.1 is an "existing" restriction which was established in PTI No. 03-13066 issued on March 27, 2001. The permittee has current records demonstrating compliance with this restriction, therefore no additional restrictions are needed during the first 12 months of operation to ensure federal enforceability.

III. Monitoring and/or Recordkeeping Requirements

1. In order to demonstrate compliance with the combined emission limitation of 20.8 tons per rolling, 12-month period and the maximum allowable production limit of 25,000 tons of rubber per rolling, 12-month period, the permittee shall collect and record the following information each month for the following grouped emission units combined: P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054:
 - a. the quantity of rubber cured and extruded, in tons;
 - b. the monthly VOC emission rate*, in tons;
 - c. the rolling, 12- month summation of the quantity of rubber cured and extruded, in tons; and,
 - d. the rolling, 12- month summation of the emission rate for VOC, in tons.

*The permittee shall use the most current Rubber Manufacturers Association (RMA) emission factors, available for these operations. At the time of issuance of this permit, these emission factors are 8.25E-4 pound VOC per pound of rubber cured and 3.52E-6 pound VOC per pound of rubber extruded.

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify any exceedance of the following:
 - a. the annual rubber production limitation of 25,000 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined; and,

Emissions Unit ID: P046

- b. the VOC emission limitation of 20.8 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

These deviation reports shall be submitted in accordance with the General Terms and Conditions of this permit.

V. Testing Requirements

1. Compliance with the allowable emission limitations in this permit shall be determined according to the following methods:

- a. Emission Limitation:
0.99 pound VOC/hour, 4.3 tons VOC/year

Applicable Compliance Method:

The hourly and annual VOC limits for rubber curing & extruding are based on the emission unit's potential to emit (maximum rubber throughput of 1200 pounds/hour multiplied by the RMA emission factors for rubber curing & extruding, see A.III.1.), at a maximum operating schedule of 8760 hrs/yr. Therefore, no record keeping, deviation reporting, or compliance method calculations are required to demonstrate compliance with these limits. If required, compliance with the hourly emissions rate shall be based on stack testing using the methods and procedures specified in Methods 1-4 and 25/25A of 40 CFR Part 60, Appendix A.

- b. Emission Limitation:
20.8 tons/rolling, 12-month period from emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

- c. Emission Limitation:
The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined shall not exceed 25,000 tons of rubber per rolling, 12-month period.

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

VI. Miscellaneous Requirements

None

Coope
PTI A

Emissions Unit ID: P046

Issued: To be entered upon final issuance

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P046 - Dual Durometer #9 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P046)		See B.III. below

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit was evaluated based on the actual materials used and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant:

Pollutant: acetophenone

85

Coope

PTI A

Emissions Unit ID: P046

Issued: To be entered upon final issuance

TLV (mg/m³): 49

Maximum Hourly Emission Rate (lbs/hr): 0.48

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 136.8

MAGLC (ug/m³): 1,167

Pollutant: carbon disulfide

TLV (mg/m³): 31

Maximum Hourly Emission Rate (lbs/hr): 1.36

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 181.6

MAGLC (ug/m³): 738

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and,
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

2. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and,
 - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

87

Coope

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: P046

88

**Coope
PTI A**

Emissions Unit ID: P046

Issued: To be entered upon final issuance

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Coope
PTI A

Emissions Unit ID: P049

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P049 - Flock Line #4 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P049)	OAC rule 3745-31-05(A)(3)	0.99 pound volatile organic compounds (VOC)/hour and 4.3 tons VOC/year See A.I.2.a.
	OAC rule 3745-31-05(D)	20.8 tons VOC/rolling, 12-month period (See A.I.2.b.) from units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

2. Additional Terms and Conditions

- 2.a The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(D).
- 2.b The permittee has requested a federally enforceable, combined emission limitation for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054 of 20.8 tons VOC per rolling 12-month period based on production restrictions for purposes of maintaining PSD minor facility status (see A.II.1.).
- 2.c The emissions unit is not subject to the requirements of OAC rule 3745-21-07(G) because liquid organic materials are not employed.

II. Operational Restrictions

Emissions Unit ID: P049

1. The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined, shall not exceed 25,000 tons of rubber per year, based on a rolling, 12-month summation of the monthly production rates.
2. The operational restriction in A.II.1 is an "existing" restriction which was established in PTI No. 03-13066 issued on March 27, 2001. The permittee has current records demonstrating compliance with this restriction, therefore no additional restrictions are needed during the first 12 months of operation to ensure federal enforceability.

III. Monitoring and/or Recordkeeping Requirements

1. In order to demonstrate compliance with the combined emission limitation of 20.8 tons per rolling, 12-month period and the maximum allowable production limit of 25,000 tons of rubber per rolling, 12-month period, the permittee shall collect and record the following information each month for the following grouped emission units combined: P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054:
 - a. the quantity of rubber cured and extruded, in tons;
 - b. the monthly VOC emission rate*, in tons;
 - c. the rolling, 12- month summation of the quantity of rubber cured and extruded, in tons; and,
 - d. the rolling, 12- month summation of the emission rate for VOC, in tons.

*The permittee shall use the most current Rubber Manufacturers Association (RMA) emission factors, available for these operations. At the time of issuance of this permit, these emission factors are 8.25E-4 pound VOC per pound of rubber cured and 3.52E-6 pound VOC per pound of rubber extruded.

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify any exceedance of the following:
 - a. the annual rubber production limitation of 25,000 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined; and,
 - b. the VOC emission limitation of 20.8 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

These deviation reports shall be submitted in accordance with the General Terms and Conditions

Issued: To be entered upon final issuance
of this permit.

V. Testing Requirements

1. Compliance with the allowable emission limitations in this permit shall be determined according to the following methods:

- a. Emission Limitation:
0.99 pound VOC/hour, 4.3 tons VOC/year

Applicable Compliance Method:

The hourly and annual VOC limits for rubber curing & extruding are based on the emission unit's potential to emit (maximum rubber throughput of 1200 pounds/hour multiplied by the RMA emission factors for rubber curing & extruding, see A.III.1.), at a maximum operating schedule of 8760 hrs/yr. Therefore, no record keeping, deviation reporting, or compliance method calculations are required to demonstrate compliance with these limits. If required, compliance with the hourly emissions rate shall be based on stack testing using the methods and procedures specified in Methods 1-4 and 25/25A of 40 CFR Part 60, Appendix A.

- b. Emission Limitation:
20.8 tons/rolling, 12-month period from emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

- c. Emission Limitation:
The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined shall not exceed 25,000 tons of rubber per rolling, 12-month period.

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

VI. Miscellaneous Requirements

None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P049 - Flock Line #4 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P049)		See B.III. below

2. Additional Terms and Conditions

- 2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit was evaluated based on the actual materials used and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant:

Pollutant: acetophenone
 TLV (mg/m3): 49
 Maximum Hourly Emission Rate (lbs/hr): 0.48
 Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 136.8
 MAGLC (ug/m3): 1,167

Issued: To be entered upon final issuance

Pollutant: carbon disulfide

TLV (mg/m³): 31

Maximum Hourly Emission Rate (lbs/hr): 1.36

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 181.6

MAGLC (ug/m³): 738

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and,
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

2. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still

satisfies the "Air Toxic Policy"; and,

- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P050 - Dual Durometer #1 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P050)	OAC rule 3745-31-05(A)(3)	0.99 pound volatile organic compounds (VOC)/hour and 4.3 tons VOC/year See A.I.2.a.
	OAC rule 3745-31-05(D)	20.8 tons VOC/rolling, 12-month period (See A.I.2.b.) from units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

2. Additional Terms and Conditions

- 2.a The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(D).
- 2.b The permittee has requested a federally enforceable, combined emission limitation for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054 of 20.8 tons VOC per rolling 12-month period based on production restrictions for purposes of maintaining PSD minor facility status (see A.II.1.).
- 2.c The emissions unit is not subject to the requirements of OAC rule 3745-21-07(G) because liquid organic materials are not employed.

II. Operational Restrictions

Issued: To be entered upon final issuance

1. The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined, shall not exceed 25,000 tons of rubber per year, based on a rolling, 12-month summation of the monthly production rates.
2. The operational restriction in A.II.1 is an "existing" restriction which was established in PTI No. 03-13066 issued on March 27, 2001. The permittee has current records demonstrating compliance with this restriction, therefore no additional restrictions are needed during the first 12 months of operation to ensure federal enforceability.

III. Monitoring and/or Recordkeeping Requirements

1. In order to demonstrate compliance with the combined emission limitation of 20.8 tons per rolling, 12-month period and the maximum allowable production limit of 25,000 tons of rubber per rolling, 12-month period, the permittee shall collect and record the following information each month for the following grouped emission units combined: P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054:
 - a. the quantity of rubber cured and extruded, in tons;
 - b. the monthly VOC emission rate*, in tons;
 - c. the rolling, 12- month summation of the quantity of rubber cured and extruded, in tons; and,
 - d. the rolling, 12- month summation of the emission rate for VOC, in tons.

*The permittee shall use the most current Rubber Manufacturers Association (RMA) emission factors, available for these operations. At the time of issuance of this permit, these emission factors are 8.25E-4 pound VOC per pound of rubber cured and 3.52E-6 pound VOC per pound of rubber extruded.

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify any exceedance of the following:
 - a. the annual rubber production limitation of 25,000 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined; and,

Emissions Unit ID: P050

- b. the VOC emission limitation of 20.8 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

These deviation reports shall be submitted in accordance with the General Terms and Conditions of this permit.

V. Testing Requirements

1. Compliance with the allowable emission limitations in this permit shall be determined according to the following methods:

- a. Emission Limitation:
0.99 pound VOC/hour, 4.3 tons VOC/year

Applicable Compliance Method:

The hourly and annual VOC limits for rubber curing & extruding are based on the emission unit's potential to emit (maximum rubber throughput of 1200 pounds/hour multiplied by the RMA emission factors for rubber curing & extruding, see A.III.1.), at a maximum operating schedule of 8760 hrs/yr. Therefore, no record keeping, deviation reporting, or compliance method calculations are required to demonstrate compliance with these limits. If required, compliance with the hourly emissions rate shall be based on stack testing using the methods and procedures specified in Methods 1-4 and 25/25A of 40 CFR Part 60, Appendix A.

- b. Emission Limitation:
20.8 tons/rolling, 12-month period from emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

- c. Emission Limitation:
The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined shall not exceed 25,000 tons of rubber per rolling, 12-month period.

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

VI. Miscellaneous Requirements

None

Coope
PTI A

Emissions Unit ID: P050

Issued: To be entered upon final issuance

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P050 - Dual Durometer #1 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P050)		See B.III. below

2. Additional Terms and Conditions

- 2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit was evaluated based on the actual materials used and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant:

Pollutant: acetophenone

99

**Coope
PTI A**

Emissions Unit ID: P050

Issued: To be entered upon final issuance

TLV (mg/m3): 49

Maximum Hourly Emission Rate (lbs/hr): 0.48

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 136.8

MAGLC (ug/m3): 1,167

Pollutant: carbon disulfide

TLV (mg/m3): 31

Maximum Hourly Emission Rate (lbs/hr): 1.36

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 181.6

MAGLC (ug/m3): 738

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and,
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

2. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and,
 - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

101

Coope

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: P050

102

Coope

PTI A

Emissions Unit ID: P050

Issued: To be entered upon final issuance

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P051 - Dual Durometer #2 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P051)	OAC rule 3745-31-05(A)(3) OAC rule 3745-31-05(D)	0.99 pound volatile organic compounds (VOC)/hour and 4.3 tons VOC/year See A.I.2.a. 20.8 tons VOC/rolling, 12-month period (See A.I.2.b.) from units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

2. Additional Terms and Conditions

- 2.a The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(D).
- 2.b The permittee has requested a federally enforceable, combined emission limitation for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054 of 20.8 tons VOC per rolling 12-month period based on production restrictions for purposes of maintaining PSD minor facility status (see A.II.1.).
- 2.c The emissions unit is not subject to the requirements of OAC rule 3745-21-07(G) because liquid organic materials are not employed.

II. Operational Restrictions

Issued

Emissions Unit ID: P051

1. The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined, shall not exceed 25,000 tons of rubber per year, based on a rolling, 12-month summation of the monthly production rates.
2. The operational restriction in A.II.1 is an "existing" restriction which was established in PTI No. 03-13066 issued on March 27, 2001. The permittee has current records demonstrating compliance with this restriction, therefore no additional restrictions are needed during the first 12 months of operation to ensure federal enforceability.

III. Monitoring and/or Recordkeeping Requirements

1. In order to demonstrate compliance with the combined emission limitation of 20.8 tons per rolling, 12-month period and the maximum allowable production limit of 25,000 tons of rubber per rolling, 12-month period, the permittee shall collect and record the following information each month for the following grouped emission units combined: P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054:
 - a. the quantity of rubber cured and extruded, in tons;
 - b. the monthly VOC emission rate*, in tons;
 - c. the rolling, 12- month summation of the quantity of rubber cured and extruded, in tons; and,
 - d. the rolling, 12- month summation of the emission rate for VOC, in tons.

*The permittee shall use the most current Rubber Manufacturers Association (RMA) emission factors, available for these operations. At the time of issuance of this permit, these emission factors are 8.25E-4 pound VOC per pound of rubber cured and 3.52E-6 pound VOC per pound of rubber extruded.

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify any exceedance of the following:
 - a. the annual rubber production limitation of 25,000 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined; and,
 - b. the VOC emission limitation of 20.8 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

These deviation reports shall be submitted in accordance with the General Terms and Conditions

Issued: To be entered upon final issuance
of this permit.

V. Testing Requirements

1. Compliance with the allowable emission limitations in this permit shall be determined according to the following methods:

- a. Emission Limitation:
0.99 pound VOC/hour, 4.3 tons VOC/year

Applicable Compliance Method:

The hourly and annual VOC limits for rubber curing & extruding are based on the emission unit's potential to emit (maximum rubber throughput of 1200 pounds/hour multiplied by the RMA emission factors for rubber curing & extruding, see A.III.1.), at a maximum operating schedule of 8760 hrs/yr. Therefore, no record keeping, deviation reporting, or compliance method calculations are required to demonstrate compliance with these limits. If required, compliance with the hourly emissions rate shall be based on stack testing using the methods and procedures specified in Methods 1-4 and 25/25A of 40 CFR Part 60, Appendix A.

- b. Emission Limitation:
20.8 tons/rolling, 12-month period from emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

- c. Emission Limitation:
The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined shall not exceed 25,000 tons of rubber per rolling, 12-month period.

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

VI. Miscellaneous Requirements

None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P051 - Dual Durometer #2 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P051)		See B.III. below

2. Additional Terms and Conditions

- 2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit was evaluated based on the actual materials used and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant:

Pollutant: acetophenone
 TLV (mg/m3): 49
 Maximum Hourly Emission Rate (lbs/hr): 0.48
 Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 136.8
 MAGLC (ug/m3): 1,167

107

Coope

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: P051

Issued: To be entered upon final issuance

Pollutant: carbon disulfide

TLV (mg/m³): 31

Maximum Hourly Emission Rate (lbs/hr): 1.36

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 181.6

MAGLC (ug/m³): 738

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and,
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

2. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still

satisfies the "Air Toxic Policy"; and,

- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

110

Coope

PTI A

Emissions Unit ID: P051

Issued: To be entered upon final issuance

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P052 - Dual Durometer #3 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P052)	OAC rule 3745-31-05(A)(3)	0.99 pound volatile organic compounds (VOC)/hour and 4.3 tons VOC/year See A.I.2.a.
	OAC rule 3745-31-05(D)	20.8 tons VOC/rolling, 12-month period (See A.I.2.b.) from units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

2. Additional Terms and Conditions

- 2.a The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(D).
- 2.b The permittee has requested a federally enforceable, combined emission limitation for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054 of 20.8 tons VOC per rolling 12-month period based on production restrictions for purposes of maintaining PSD minor facility status (see A.II.1.).
- 2.c The emissions unit is not subject to the requirements of OAC rule 3745-21-07(G) because liquid organic materials are not employed.

II. Operational Restrictions

Issued: To be entered upon final issuance

1. The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined, shall not exceed 25,000 tons of rubber per year, based on a rolling, 12-month summation of the monthly production rates.
2. The operational restriction in A.II.1 is an "existing" restriction which was established in PTI No. 03-13066 issued on March 27, 2001. The permittee has current records demonstrating compliance with this restriction, therefore no additional restrictions are needed during the first 12 months of operation to ensure federal enforceability.

III. Monitoring and/or Recordkeeping Requirements

1. In order to demonstrate compliance with the combined emission limitation of 20.8 tons per rolling, 12-month period and the maximum allowable production limit of 25,000 tons of rubber per rolling, 12-month period, the permittee shall collect and record the following information each month for the following grouped emission units combined: P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054:
 - a. the quantity of rubber cured and extruded, in tons;
 - b. the monthly VOC emission rate*, in tons;
 - c. the rolling, 12- month summation of the quantity of rubber cured and extruded, in tons; and,
 - d. the rolling, 12- month summation of the emission rate for VOC, in tons.

*The permittee shall use the most current Rubber Manufacturers Association (RMA) emission factors, available for these operations. At the time of issuance of this permit, these emission factors are 8.25E-4 pound VOC per pound of rubber cured and 3.52E-6 pound VOC per pound of rubber extruded.

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify any exceedance of the following:
 - a. the annual rubber production limitation of 25,000 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined; and,

Emissions Unit ID: P052

- b. the VOC emission limitation of 20.8 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

These deviation reports shall be submitted in accordance with the General Terms and Conditions of this permit.

V. Testing Requirements

1. Compliance with the allowable emission limitations in this permit shall be determined according to the following methods:

- a. Emission Limitation:
0.99 pound VOC/hour, 4.3 tons VOC/year

Applicable Compliance Method:

The hourly and annual VOC limits for rubber curing & extruding are based on the emission unit's potential to emit (maximum rubber throughput of 1200 pounds/hour multiplied by the RMA emission factors for rubber curing & extruding, see A.III.1.), at a maximum operating schedule of 8760 hrs/yr. Therefore, no record keeping, deviation reporting, or compliance method calculations are required to demonstrate compliance with these limits. If required, compliance with the hourly emissions rate shall be based on stack testing using the methods and procedures specified in Methods 1-4 and 25/25A of 40 CFR Part 60, Appendix A.

- b. Emission Limitation:
20.8 tons/rolling, 12-month period from emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

- c. Emission Limitation:
The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined shall not exceed 25,000 tons of rubber per rolling, 12-month period.

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

VI. Miscellaneous Requirements

None

Coope
PTI A

Emissions Unit ID: P052

Issued: To be entered upon final issuance

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P052 - Dual Durometer #3 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P052)		See B.III. below

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit was evaluated based on the actual materials used and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant:

Pollutant: acetophenone

115

Cooper Engineered Products

PTI Application: 02 12084

Issued

Facility ID: 0387020045

Emissions Unit ID: P052

TLV (mg/m3): 49

Maximum Hourly Emission Rate (lbs/hr): 0.48

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 136.8

MAGLC (ug/m3): 1,167

Issued: To be entered upon final issuance

Pollutant: carbon disulfide

TLV (mg/m3): 31

Maximum Hourly Emission Rate (lbs/hr): 1.36

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 181.6

MAGLC (ug/m3): 738

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and,
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

2. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still

Issued: To be entered upon final issuance

satisfies the "Air Toxic Policy"; and,

- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

118

Coope

PTI A

Emissions Unit ID: P052

Issued: To be entered upon final issuance

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P053 - Dual Durometer #4 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P053)	OAC rule 3745-31-05(A)(3) OAC rule 3745-31-05(D)	0.99 pound volatile organic compounds (VOC)/hour and 4.3 tons VOC/year See A.I.2.a. 20.8 tons VOC/rolling, 12-month period (See A.I.2.b.) from units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

2. Additional Terms and Conditions

- 2.a The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(D).
- 2.b The permittee has requested a federally enforceable, combined emission limitation for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054 of 20.8 tons VOC per rolling 12-month period based on production restrictions for purposes of maintaining PSD minor facility status (see A.II.1.).
- 2.c The emissions unit is not subject to the requirements of OAC rule 3745-21-07(G) because liquid organic materials are not employed.

II. Operational Restrictions

Emissions Unit ID: P053

1. The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined, shall not exceed 25,000 tons of rubber per year, based on a rolling, 12-month summation of the monthly production rates.
2. The operational restriction in A.II.1 is an "existing" restriction which was established in PTI No. 03-13066 issued on March 27, 2001. The permittee has current records demonstrating compliance with this restriction, therefore no additional restrictions are needed during the first 12 months of operation to ensure federal enforceability.

III. Monitoring and/or Recordkeeping Requirements

1. In order to demonstrate compliance with the combined emission limitation of 20.8 tons per rolling, 12-month period and the maximum allowable production limit of 25,000 tons of rubber per rolling, 12-month period, the permittee shall collect and record the following information each month for the following grouped emission units combined: P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054:
 - a. the quantity of rubber cured and extruded, in tons;
 - b. the monthly VOC emission rate*, in tons;
 - c. the rolling, 12- month summation of the quantity of rubber cured and extruded, in tons; and,
 - d. the rolling, 12- month summation of the emission rate for VOC, in tons.

*The permittee shall use the most current Rubber Manufacturers Association (RMA) emission factors, available for these operations. At the time of issuance of this permit, these emission factors are 8.25E-4 pound VOC per pound of rubber cured and 3.52E-6 pound VOC per pound of rubber extruded.

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify any exceedance of the following:
 - a. the annual rubber production limitation of 25,000 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined; and,
 - b. the VOC emission limitation of 20.8 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

These deviation reports shall be submitted in accordance with the General Terms and Conditions

Issued: To be entered upon final issuance
of this permit.

V. Testing Requirements

1. Compliance with the allowable emission limitations in this permit shall be determined according to the following methods:

- a. Emission Limitation:
0.99 pound VOC/hour, 4.3 tons VOC/year

Applicable Compliance Method:

The hourly and annual VOC limits for rubber curing & extruding are based on the emission unit's potential to emit (maximum rubber throughput of 1200 pounds/hour multiplied by the RMA emission factors for rubber curing & extruding, see A.III.1.), at a maximum operating schedule of 8760 hrs/yr. Therefore, no record keeping, deviation reporting, or compliance method calculations are required to demonstrate compliance with these limits. If required, compliance with the hourly emissions rate shall be based on stack testing using the methods and procedures specified in Methods 1-4 and 25/25A of 40 CFR Part 60, Appendix A.

- b. Emission Limitation:
20.8 tons/rolling, 12-month period from emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

- c. Emission Limitation:
The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined shall not exceed 25,000 tons of rubber per rolling, 12-month period.

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

VI. Miscellaneous Requirements

None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P053 - Dual Durometer #4 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P053)		See B.III. below

2. Additional Terms and Conditions

- 2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit was evaluated based on the actual materials used and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant:

Pollutant: acetophenone
 TLV (mg/m3): 49
 Maximum Hourly Emission Rate (lbs/hr): 0.48
 Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 136.8
 MAGLC (ug/m3): 1,167

123

Coope

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: P053

Issued: To be entered upon final issuance

Pollutant: carbon disulfide

TLV (mg/m3): 31

Maximum Hourly Emission Rate (lbs/hr): 1.36

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 181.6

MAGLC (ug/m3): 738

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and,
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

2. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still

satisfies the "Air Toxic Policy"; and,

- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

126

Coope

PTI A

Emissions Unit ID: P053

Issued: To be entered upon final issuance

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P054 - Dual Durometer #5 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P054)	OAC rule 3745-31-05(A)(3)	0.99 pound volatile organic compounds (VOC)/hour and 4.3 tons VOC/year See A.I.2.a.
	OAC rule 3745-31-05(D)	20.8 tons VOC/rolling, 12-month period (See A.I.2.b.) from units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

2. Additional Terms and Conditions

- 2.a The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(D).
- 2.b The permittee has requested a federally enforceable, combined emission limitation for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054 of 20.8 tons VOC per rolling 12-month period based on production restrictions for purposes of maintaining PSD minor facility status (see A.II.1.).
- 2.c The emissions unit is not subject to the requirements of OAC rule 3745-21-07(G) because liquid organic materials are not employed.

II. Operational Restrictions

Issued: To be entered upon final issuance

1. The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined, shall not exceed 25,000 tons of rubber per year, based on a rolling, 12-month summation of the monthly production rates.
2. The operational restriction in A.II.1 is an "existing" restriction which was established in PTI No. 03-13066 issued on March 27, 2001. The permittee has current records demonstrating compliance with this restriction, therefore no additional restrictions are needed during the first 12 months of operation to ensure federal enforceability.

III. Monitoring and/or Recordkeeping Requirements

1. In order to demonstrate compliance with the combined emission limitation of 20.8 tons per rolling, 12-month period and the maximum allowable production limit of 25,000 tons of rubber per rolling, 12-month period, the permittee shall collect and record the following information each month for the following grouped emission units combined: P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054:
 - a. the quantity of rubber cured and extruded, in tons;
 - b. the monthly VOC emission rate*, in tons;
 - c. the rolling, 12- month summation of the quantity of rubber cured and extruded, in tons; and,
 - d. the rolling, 12- month summation of the emission rate for VOC, in tons.

*The permittee shall use the most current Rubber Manufacturers Association (RMA) emission factors, available for these operations. At the time of issuance of this permit, these emission factors are 8.25E-4 pound VOC per pound of rubber cured and 3.52E-6 pound VOC per pound of rubber extruded.

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify any exceedance of the following:
 - a. the annual rubber production limitation of 25,000 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined; and,

Emissions Unit ID: P054

- b. the VOC emission limitation of 20.8 tons/rolling, 12-month period for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined.

These deviation reports shall be submitted in accordance with the General Terms and Conditions of this permit.

V. Testing Requirements

1. Compliance with the allowable emission limitations in this permit shall be determined according to the following methods:

- a. Emission Limitation:
0.99 pound VOC/hour, 4.3 tons VOC/year

Applicable Compliance Method:

The hourly and annual VOC limits for rubber curing & extruding are based on the emission unit's potential to emit (maximum rubber throughput of 1200 pounds/hour multiplied by the RMA emission factors for rubber curing & extruding, see A.III.1.), at a maximum operating schedule of 8760 hrs/yr. Therefore, no record keeping, deviation reporting, or compliance method calculations are required to demonstrate compliance with these limits. If required, compliance with the hourly emissions rate shall be based on stack testing using the methods and procedures specified in Methods 1-4 and 25/25A of 40 CFR Part 60, Appendix A.

- b. Emission Limitation:
20.8 tons/rolling, 12-month period from emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

- c. Emission Limitation:
The maximum annual production rate for emissions units P003, P005, P012, P016, P019, P023, P026, P028, P038, P046, P049, P050, P051, P052, P053, and P054, combined shall not exceed 25,000 tons of rubber per rolling, 12-month period.

Applicable Compliance Method:

Compliance with the annual emission limitation shall be determined by the record keeping required in condition A.III.1.

VI. Miscellaneous Requirements

None

Coope
PTI A

Emissions Unit ID: P054

Issued: To be entered upon final issuance

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P054 - Dual Durometer #5 Rubber Curing and Extrusion: (modification of PTI No. 03-13066 issued on March 27, 2001 to increase pound/hour and ton/year limits for P054)		See B.III. below

2. Additional Terms and Conditions

- 2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for this emissions unit was evaluated based on the actual materials used and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant:

Pollutant: acetophenone

131

Cooper Engineered Products

PTI Application: 02 12084

Issued

Facility ID: 0387020045

Emissions Unit ID: P054

TLV (mg/m3): 49

Maximum Hourly Emission Rate (lbs/hr): 0.48

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 136.8

MAGLC (ug/m3): 1,167

Issued: To be entered upon final issuance

Pollutant: carbon disulfide

TLV (mg/m3): 31

Maximum Hourly Emission Rate (lbs/hr): 1.36

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 181.6

MAGLC (ug/m3): 738

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and,
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

2. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still

Issued: To be entered upon final issuance

satisfies the "Air Toxic Policy"; and,

- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

134

Coope

PTI A

Emissions Unit ID: P054

Issued: To be entered upon final issuance

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None