



State of Ohio Environmental Protection Agency

Street Address:

Mailing Address:

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Lazarus Gov.
Center

**RE: DRAFT PERMIT TO INSTALL MODIFICATION
LUCAS COUNTY
Application No: 04-01429
Fac ID: 0448002007**

CERTIFIED MAIL

DATE: 8/31/2006

Rexam Beverage Can Company
Geoffrey Wortley
8770 West Bryn Mawr Ave Suite 175
Chicago, IL 606313655

You are hereby notified that the Ohio Environmental Protection Agency has made a draft action recommending that the Director issue a Permit to Install modification for the air contaminant source(s) [emissions unit(s)] shown on the enclosed draft permit modification. This draft action is not an authorization to begin construction or modification of your emissions unit(s). The purpose of this draft is to solicit public comments on the proposed installation. A public notice concerning the draft permit will appear in the Ohio EPA Weekly Review and the newspaper in the county where the facility will be located. Public comments will be accepted by the field office within 30 days of the date of publication in the newspaper. Any comments you have on the draft permit modification should be directed to the appropriate field office within the comment period. A copy of your comments should also be mailed to Robert Hodanbosi, Division of Air Pollution Control, Ohio EPA, P.O. Box 1049, Columbus, OH, 43266-0149.

A Permit to Install modification may be issued in proposed or final form based on the draft action, any written public comments received within 30 days of the public notice, or record of a public meeting if one is held. You will be notified in writing of a scheduled public meeting. Upon issuance of a final Permit to Install modification a fee of **\$ 100** will be due. Please do not submit any payment now.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469. If you have any questions about this draft permit, please contact the field office where you submitted your application, or Mike Ahern, Field Operations & Permit Section at (614) 644-3631.

Sincerely,

Michael W. Ahern

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: USEPA

TDES

Toledo Met Area Council of Govs

IN

MI

LUCAS COUNTY

PUBLIC NOTICE

**ISSUANCE OF DRAFT PERMIT TO INSTALL 04-01429 FOR AN AIR CONTAMINANT SOURCE FOR
Rexam Beverage Can Company**

On 8/31/2006 the Director of the Ohio Environmental Protection Agency issued a draft action of a Permit To Install an air contaminant source for **Rexam Beverage Can Company**, located at **10444 Waterville Swanton Road, Whitehouse**, Ohio.

Installation of the air contaminant source identified below may proceed upon final issuance of Permit To Install 04-01429:

An administrative modification to re-proportion the restriction on gallons of coating for K011. This modification will not change the total VOC but only the ratio of coating restrictions.

Comments concerning this draft action, or a request for a public meeting, must be sent in writing to the address identified below no later than thirty (30) days from the date this notice is published. All inquiries concerning this draft action may be directed to the contact identified below.

Karen Granata, Toledo Department of Environmental Services, 348 South Erie Street, Toledo, OH 43602
[(419)936-3015]



**Permit To Install
Terms and Conditions**

**Issue Date: To be entered upon final issuance
Effective Date: To be entered upon final issuance**

DRAFT MODIFICATION OF PERMIT TO INSTALL 04-01429

Application Number: 04-01429
Facility ID: 0448002007
Permit Fee: **To be entered upon final issuance**
Name of Facility: Rexam Beverage Can Company
Person to Contact: Geoffrey Wortley
Address: 8770 West Bryn Mawr Ave Suite 175
Chicago, IL 606313655

Location of proposed air contaminant source(s) [emissions unit(s)]:
**10444 Waterville Swanton Road
Whitehouse, Ohio**

Description of proposed emissions unit(s):
**An administrative modification to re-proportion the restriction on gallons of coating for K011.
This modification will not change the total VOC but only the ratio of coating restrictions.**

The above named entity is hereby granted a modification to the permit to install described above pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this modification does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described source(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans included in the application, the above described source(s) of pollutants will be granted the necessary operating permits.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. State and Federally Enforceable Permit-To-Install General Terms and Conditions

1. Monitoring and Related Recordkeeping and Reporting Requirements

- a. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:
 - i. The date, place (as defined in the permit), and time of sampling or measurements.
 - ii. The date(s) analyses were performed.
 - iii. The company or entity that performed the analyses.
 - iv. The analytical techniques or methods used.
 - v. The results of such analyses.
 - vi. The operating conditions existing at the time of sampling or measurement.
- b. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.
- c. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall submit required reports in the following manner:
 - i. Reports of any required monitoring and/or recordkeeping of federally enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
 - ii. Quarterly written reports of (i) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, excluding deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06, that have been detected by the testing, monitoring and recordkeeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures taken, shall be made to the appropriate Ohio EPA District Office or local air agency. The written

reports shall be submitted (i.e., postmarked) quarterly, by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. See B.9 below if no deviations occurred during the quarter.

- iii. Written reports, which identify any deviations from the federally enforceable monitoring, recordkeeping, and reporting requirements contained in this permit shall be submitted (i.e., postmarked) to the appropriate Ohio EPA District Office or local air agency every six months, by January 31 and July 31 of each year for the previous six calendar months. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report, which states that no deviations occurred during that period.
 - iv. If this permit is for an emissions unit located at a Title V facility, then each written report shall be signed by a responsible official certifying that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.
- d. The permittee shall report actual emissions pursuant to OAC Chapter 3745-78 for the purpose of collecting Air Pollution Control Fees.

2. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction, i.e., upset, of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. (The definition of an upset condition shall be the same as that used in OAC rule 3745-15-06(B)(1) for a malfunction.) The verbal and written reports shall be submitted pursuant to OAC rule 3745-15-06.

Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emission unit(s) that is (are) served by such control system(s).

3. Risk Management Plans

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. 7401 et seq. ("Act"), the

Rexam Beverage Can Company

Facility ID: 0448002007

PTI Application: 04-01429

Issued: To be entered upon final issuance

permittee shall comply with the requirement to register such a plan.

4. Title IV Provisions

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

5. Severability Clause

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition declared invalid.

6. General Requirements

- a. The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and re-issuance, or modification
- b. It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.
- c. This permit may be modified, revoked, or revoked and reissued, for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.
- d. This permit does not convey any property rights of any sort, or any exclusive privilege.
- e. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the

Rexam Beverage Can Company

Facility ID: 0448002007

PTI Application: 04-01429

Issued: To be entered upon final issuance

permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

7. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable permit-to-install fees within 30 days after the issuance of any permit-to-install. The permittee shall pay all applicable permit-to-operate fees within thirty days of the issuance of the invoice.

8. Federal and State Enforceability

Only those terms and conditions designated in this permit as federally enforceable, that are required under the Act, or any its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA and the State and by citizens (to the extent allowed by section 304 of the Act) under the Act. All other terms and conditions of this permit shall not be federally enforceable and shall be enforceable under State law only.

9. Compliance Requirements

- a. Any document (including reports) required to be submitted and required by a federally applicable requirement in this permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.
- b. Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:
 - i. At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.
 - ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with ORC section 3704.08.
 - iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.

- iv. As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.
- c. The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually, or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:
 - i. Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
 - ii. An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

10. Permit-To-Operate Application

- a. If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).
- b. If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35, the source(s) identified in this permit is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the source(s) covered by this permit.

11. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

12. Air Pollution Nuisance

Rexam Beverage Can Company

Facility ID: 0448002007

PTI Application: 04-01429

Issued: To be entered upon final issuance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

13. Permit-To-Install

A permit-to-install must be obtained pursuant to OAC Chapter 3745-31 prior to "installation" of "any air contaminant source" as defined in OAC rule 3745-31-01, or "modification", as defined in OAC rule 3745-31-01, of any emissions unit included in this permit.

B. State Only Enforceable Permit-To-Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping of state-only enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from state-only required emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted (i.e., postmarked) quarterly, by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

4. Authorization To Install or Modify

If applicable, authorization to install or modify any new or existing emissions unit included in this permit shall terminate within eighteen months of the effective date of the permit if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

5. Construction of New Sources(s)

This permit does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. This permit does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the application and terms and conditions of this permit. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of this permit does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Issuance of this permit is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

6. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

7. Applicability

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

Rexam Beverage Can Company

Facility ID: 0448002007

PTI Application: 04-01429

Issued: To be entered upon final issuance

8. Construction Compliance Certification

If applicable, the applicant shall provide Ohio EPA with a written certification (see enclosed form if applicable) that the facility has been constructed in accordance with

Rexam Beverage Can Company
PTI Application: 04-01429
Issued: To be entered upon final issuance

Facility ID: 0448002007

Rexar

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: K009

the permit-to-install application and the terms and conditions of the permit-to-install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

9. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations (See Section A of This Permit)

If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly (i.e., postmarked), by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.

C. Permit-To-Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
<u>HAPs</u>	
any one HAP	9.9 <i>(no change)</i>
total, combined facility HAP	24.9 <i>(no change)</i>
CO (Line 2 base coater w/pin oven and Line 3)	4.68 <i>(no change)</i>
NOx (Line 2 base coater w/pin oven and Line 3)	5.57 <i>(no change)</i>
PE (Line 2 base coater w/pin oven and Line 3)	2.33 <i>(no change)</i>
PM10 (Line 2 base coater w/pin oven and Line 3)	2.62 <i>(no change)</i>
SO2 (Line 2 base coater w/pin oven and Line 3)	0.20 <i>(no change)</i>
VOC (from PTI 04-01379, Title V Permit)	417.85 <i>(no change)</i>

Rexam Beverage Can Company
PTI Application: 04-01429
Issued: To be entered upon final issuance

Facility ID: 0448002007

Rexar

PTI A

Emissions Unit ID: K009

Issued: To be entered upon final issuance

Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

A. State and Federally Enforceable Permit To Install Facility Specific Terms and Conditions

None

B. State Only Enforceable Permit To Install Facility Specific Terms and Conditions

None

Rexar

PTI A

Emissions Unit ID: K009

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K009 - Can manufacturing line 1 - a minor source of HAPs. Line 1 includes the interior body coating line, continuous motion printer, and continuous motion coater lines with ovens. (Modification 11/29/2005)	OAC rule 3745-31-02(A)(2)	See Section A.I.2.a.
	OAC 3745-21-09(D)	4.2 pounds VOC per gallon of coating (excluding water and exempt solvents) for the Interior Body Coating Line, Line 1 Can Body Sprayers.
		2.8 pounds of VOC per gallon of coating (excluding water and exempt solvents) for the continuous motion printer, line 1 deco & over varnish with oven(s).
		2.8 pounds of VOC per gallon of coating (excluding water and exempt solvents) for the continuous motion coater, line 1 base coating line with oven(s).

2. Additional Terms and Conditions

- 2.a The emissions of hazardous air pollutants (HAPs) from this facility, as identified in Section 112(b) of Title III of the Clean Air Act, shall not exceed 9.9 tons per year for any single HAP and 24.9 tons per year for any combination of HAPs.

II. Operational Restrictions

1. The individual HAP and total HAP, combined, emission rates for all emissions units at the facility shall not exceed 9.9 and 24.9 tons per year, respectively, based upon a rolling, 12-month summation of emission rates. To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed the usage levels for all emissions units at the facility specified in the following table:

<u>Month(s)</u>	<u>Total HAP Emissions (Tons)</u>	<u>Individual HAP Emissions (Tons)</u>
1	2.1	0.9
1-2	4.2	1.7
1-3	6.3	2.6
1-4	8.4	3.4
1-5	10.5	4.3
1-6	12.6	5.1
1-7	14.7	6.0
1-8	16.8	6.8
1-9	18.9	7.7
1-10	20.9	8.5
1-11	22.9	9.4
1-12	24.9	9.9

After the first 12 calendar months of operation following the issuance of this permit, compliance with the individual HAP and total HAP, combined, emission limitations for all emissions units at the facility shall be based upon a rolling, 12-month summation of the monthly usage emission figures.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each month for the line:
 - a. the name and identification number of each coating and cleanup material (i.e. over varnish, bottom varnish, or inside spray coating), as applied;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the total HAP content of each coating, and cleanup material, in pounds per gallon;

- d. the individual HAP content of each coating, and cleanup material, in pounds per gallon;
 - e. the number of gallons of each coating, and cleanup material employed;
 - f. the total VOC emissions (VOC applied) from all coatings, and cleanup materials employed [the sum of (1.b. times 1.e. divided by 2000 lbs/ton) for all coatings and cleanup materials], in tons;
 - g. the total HAP emissions (HAP applied) from all coatings and cleanup materials employed, in tons;
 - h. the individual HAP emissions (HAP applied) from all coatings and cleanup materials employed, in tons;
 - i. the rolling, 12-month summation of the VOC emissions in tons;
 - j. the rolling, 12-month summation of total HAP emissions, in tons;
 - k. the rolling, 12-month summation of individual HAP emissions, in tons, and
 - l. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation of the gallons of each coating and clean-up material employed. Also, during the first 12 calendar months of operation following issuance of this permit, the permittee shall record the cumulative coating usage for all emissions units at the facility for each calendar month.
2. The permittee shall maintain records of the facility's potential to emit for each individual hazardous air pollutant and the total of all hazardous air pollutants combined by maintaining a formal up-to-date HAP emissions inventory from all HAP emissions units at the facility. The permittee shall maintain a record including methods, procedures, and assumptions supporting the calculations.

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.
2. The permittee shall submit deviation (excursion) reports that identify all exceedances

Rexar

PTI A

Emissions Unit ID: K009

Issued: To be entered upon final issuance

of the rolling, 12-month total HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative total HAP emission limitation set forth in Part III, section A.II.1 of this permit.

3. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month individual HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative individual HAP emission limitation set forth in Part III, section A.II.1 of this permit.
4. The permittee shall notify in writing the Toledo Division of Environmental Services within 2 weeks of becoming aware of an exceedance of either of the limits specified under A.I.2.a.

V. Testing Requirements

1. Compliance with the coating restriction in Section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

a. Emission Limitation:

Emissions for all emissions units at the facility shall not exceed 9.9 tons per rolling, 12-month period for any single HAP and 24.9 tons per rolling, 12-month period for any combination of HAPs.

Applicable Compliance Method:

The monitoring and recordkeeping requirement A.III.2 will be used to demonstrate compliance.

b. Emission Limitation:

4.2 pounds of VOC per gallon of coating (excluding water and exempt solvents) for the Interior Body Coating, line 1 can body sprayers with oven(s).

Applicable Compliance Method:

Daily records shall be maintained of the VOC content of all coatings employed. In accordance with OAC rule 3745-21-10(B) and OAC rule 3745-21-04(B)(5), only coatings supplied by companies or entities that use USEPA Method 24 to determine the VOC content of coatings and properly report that content on USEPA-approved VOC Data Sheets shall be

Emissions Unit ID: K009

employed. If the permittee determines that Method 24 has not been used for a particular coating, the permittee shall request that the coating supplier perform Method 24 on the coating in question. If the supplier determines that Method 24 cannot be used, the permittee shall so notify the Administrator of the USEPA and pursuant to section 4.3 of Method 24, 40 CFR Part 60, Appendix A, will request that the supplier use formulation data to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

c. Emission Limitation:

2.8 pounds of VOC per gallon of coating (excluding water and exempt solvents) for the Continuous Motion Printer, line 1 deco & over varnish with oven(s).

Applicable Compliance Method:

Daily records shall be maintained of the VOC content of all coatings employed. In accordance with OAC rule 3745-21-10(B) and OAC rule 3745-21-04(B)(5), only coatings supplied by companies or entities that use USEPA Method 24 to determine the VOC content of coatings and properly report that content on USEPA-approved VOC Data Sheets shall be employed. If the permittee determines that Method 24 has not been used for a particular coating, the permittee shall request that the coating supplier perform Method 24 on the coating in question. If the supplier determines that Method 24 cannot be used, the permittee shall so notify the Administrator of the USEPA and pursuant to section 4.3 of Method 24, 40 CFR Part 60, Appendix A, will request that the supplier use formulation data to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

d. Emission Limitation:

2.8 pounds of VOC per gallon of coating (excluding water and exempt solvents) for the continuous motion coater, line 1 base coating line with oven(s).

Applicable Compliance Method:

Daily records shall be maintained of the VOC content of all coatings employed. In accordance with OAC rule 3745-21-10(B) and OAC rule 3745-21-04(B)(5), only coatings supplied by companies or entities that use USEPA Method 24 to determine the VOC content of coatings and properly report that content on USEPA-approved VOC Data Sheets

Rexar

PTI A

Emissions Unit ID: K009

Issued: To be entered upon final issuance

shall be employed. If the permittee determines that Method 24 has not been used for a particular coating, the permittee shall request that the coating supplier perform Method 24 on the coating in question. If the supplier determines that Method 24 cannot be used, the permittee shall so notify the Administrator of the USEPA and pursuant to section 4.3 of Method 24, 40 CFR Part 60, Appendix A, will request that the supplier use formulation data to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

Rexar Beverage Can Company
PTI A
Issue

Facility ID: 044000007

Emissions Unit ID: K009

VI. Miscellaneous Requirements

1. The terms and conditions contained in this permit to install for emissions unit K009 shall supercede all requirements for emissions units K001, K002, and K003 contained in the facility's Title V Permit (issued 8/13/1998).

Rexar

PTI A

Emissions Unit ID: K009

Issued: To be entered upon final issuance

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K009 - Can manufacturing line 1 - a minor source of HAPs. Line 1 includes the interior body coating line, continuous motion printer, and continuous motion coater lines with ovens. (Modification 11/29/2005)		

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

Rexar

PTI A

Issued: To be entered upon final issuance

None

Emissions Unit ID: K009

Rexar

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: K009

VI. Miscellaneous Requirements

None

Rexar

PTI A

Emissions Unit ID: K010

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>		<u>Applicable Rules/Requirements</u>
K010 - Can manufacturing line 2 - a minor source of HAPs. Line 2 includes the interior body coating line, continuous motion printer, and continuous motion base coater lines with ovens. (Modification 11/29/2005)	direct fired natural gas pin oven with no controls.	OAC rule 3745-31-02(A)(2)
Interior body coating line, line 2 can body sprayers with oven(s).		OAC rule 3745-21-09(D)
Continuous motion printer, line 2 deco & over varnish with oven(s).		OAC rule 3745-21-09(D)
2-piece beverage can continuous motion base coater and 3.0 mmBtu		OAC rule 3745-31-05(C)
		OAC 3745-31-05(A)(3) (PTI 04-01269 issued 9/25/2001)

Rexar

PTI A

Emissions Unit ID: K010

Issued: To be entered upon final issuance

	<u>Applicable Emissions Limitations/Control Measures</u>	
OAC rule 3745-31-05(C)	See Section A.I.2.a.	0.30 pound per hour and 1.32 tons per year nitrogen oxides (NOx) emissions; 0.01 pound per hour and 0.05 ton per year of (PE); 0.03 pound per hour and 0.13 ton per year of PM ₁₀ ; and 0.01 pound per hour and 0.05 ton per year sulfur dioxide (SO ₂) emissions; and 0.02 pound per hour and 0.09 ton VOC per rolling, 12-month period from the combustion of natural gas (see Section A.I.2.c)
	4.2 pounds of VOC per gallon of coating (excluding water and exempt solvents) for the Interior body coating, line 2 can body sprayers with oven(s).	See Section A.I.2.d
	2.8 pounds of VOC per gallon of coating (excluding water and exempt solvents) for the	2.42 pounds of VOC per gallon of coating solids (0.29 kilogram of VOC per liter of coating solids); and see section A.I.2.e
OAC rule 3745-21-09(D)(1)	Continuous motion printer, line 2 deco & over varnish with oven(s).	See Section A.I.2.d
40 CFR Part 60, Subpart WW	5.13 tons VOC per rolling, 12-month period	See Section A.I.2.f
	2.0 pounds of volatile organic compounds (VOC) per gallon of coating minus water and exempt solvents; and see Section A.I.2.b	See Section A.I.2.g
OAC rule 3745-18-06(C)		
OAC rule 3745-21-08(B)	6.16 pounds per hour and 5.04 tons VOC per rolling, 12-month period from all coatings and clean-up materials;	
OAC rule 3745-23-06(B)	0.25 pound per hour and 1.10 tons per year carbon monoxide (CO) emissions;	

2. Additional Terms and Conditions

- 2.a** The emissions of hazardous air pollutants (HAPs) from this facility, as identified in Section 112(b) of Title III of the Clean Air Act, shall not exceed 9.9 tons per year for any single HAP and 24.9 tons per year for any combination of HAPs.
- 2.b** The requirements of this rule also include compliance with the requirements of 40 CFR Part 60, Subpart WW.

Issued: To be entered upon final issuance

- 2.c** The hourly and annual emission limitations were established for PTI purposes to reflect the potential to emit for the combustion of natural gas in this emissions unit at the maximum burner capacity of 3.0 mmBtu per hour. Therefore, it is not necessary to develop monitoring, record keeping and/or reporting requirements to ensure compliance with these limitations.
- 2.d** The emission limitation specified by this rule is less stringent than the emission limitation established by OAC rule 3745-31-05(A)(3).
- 2.e** This emissions unit is subject to the applicable provisions of Subpart WW of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60. The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.
- 2.f** The permittee has satisfied the "best available control techniques and operating practices" required pursuant to OAC rule 3745-21-08(B) by complying with all applicable rules.

On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the requirement to satisfy the "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

- 2.g** The permittee has satisfied the "latest available control techniques and operating practices" required pursuant to OAC rule 3745-23-06(B) by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05(A)(3) in this Permit to Install.

On February 14, 2005, OAC rule 3745-23-06 was rescinded; therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the U.S. EPA approves the revision to OAC rule 3745-23-06, the requirement to satisfy the "latest available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

Issued: To be entered upon final issuance

II. Operational Restrictions

1. The permittee shall burn only natural gas as fuel in the 3.0 mmBtu direct fired natural gas pin oven (with no controls) emissions unit.
2. Coating usage for the 2-piece beverage can Continuous Motion Coater, line 2 base coating line with oven(s) shall not exceed 10,181 gallons per year based upon a rolling, 12-month summation of the usage rates. To ensure enforceability during the first twelve calendar months of operation, following the issuance of this permit, actual emissions calculated from material usage records from the previous 11 calendar months of operation shall be used to calculate the rolling, 12-month emissions from this emissions unit and the facility.
3. The individual HAP and total HAP, combined, emission rates for all emissions units at the facility shall not exceed 9.9 and 24.9 tons per year, respectively, based upon a rolling, 12-month summation of emission rates. To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed the usage levels for all emissions units at this facility specified in the following table:

<u>Month(s)</u>	<u>Total HAP Emissions (Tons)</u>	<u>Individual HAP Emissions (Tons)</u>
1	2.1	0.9
1-2	4.2	1.7
1-3	6.3	2.6
1-4	8.4	3.4
1-5	10.5	4.3
1-6	12.6	5.1
1-7	14.7	6.0
1-8	16.8	6.8
1-9	18.9	7.7
1-10	20.9	8.5
1-11	22.9	9.4
1-12	24.9	9.9

After the first 12 calendar months of operation following the issuance of this permit, compliance with the individual HAP and total HAP, combined, emission limitations for all emissions units at the facility shall be based upon a rolling, 12-month summation of the monthly usage emission figures.

III. Monitoring and/or Recordkeeping Requirements

1. For each day during which the permittee burns a fuel other than natural gas in the 3.0 mmBtu direct fired natural gas pin oven (with no controls), the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.
2. The permittee shall collect and record the following information each month for the 2-piece beverage can continuous motion base coater line:
 - a.
 - i. the name and identification number of each coating (i.e., base coat), as applied,
 - ii. the volume of each coating, in gallons,
 - iii. the VOC content of each coating, in pounds of VOC per gallon of coating,
 - iv. the VOC content of each coating, in pounds of VOC per gallon of coating excluding water and exempt solvents,
 - v. the VOC content of each coating, in pounds of VOC per gallon of solids, as applied,
 - vi. the monthly total VOC emissions from all coatings employed (ii) x (iii), in tons;
 - b.
 - i. the name and identification number of each clean-up material employed,
 - ii. the volume of each clean-up material employed, in gallons,
 - iii. the VOC content of each clean-up material employed, in pounds of VOC per gallon,
 - iv. the monthly total VOC emissions from all clean-up materials employed (ii) x (iii), in tons;
 - c. the rolling, 12-month summation of all coatings employed, in gallons; and
 - d. the rolling, 12-month summation of VOC emissions from all coatings and clean-up materials employed, in tons.
3. The permittee shall collect and record the following information each month for the line:
 - a. the name and identification number (i.e. over varnish, bottom varnish, or inside spray coating) of each coating, and each cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the total HAP content of each coating, and cleanup material, in pounds per

Rexar

PTI A

Emissions Unit ID: K010

Issued: To be entered upon final issuance

gallon;

- d. the individual HAP content of each coating, and cleanup material, in pounds per gallon;
- e. the number of gallons of each coating, and cleanup material employed;
- f. the total VOC emissions (VOC applied) from all coatings, and cleanup materials employed [the sum of (1.b. times 1.e. divided by 2000 lbs/ton) for all coatings and cleanup materials], in tons;

Issued: To be entered upon final issuance

- g. the total HAP emissions (HAP applied) from all coatings and cleanup materials employed, in tons;
 - h. the individual HAP emissions (HAP applied) from all coatings and cleanup materials employed, in tons;
 - i. the rolling, 12-month summation of the VOC emissions in tons;
 - j. the rolling, 12-month summation of total HAP emissions, in tons;
 - k. the rolling, 12-month summation of individual HAP emissions, in tons, and
 - l. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation of the gallons of each coating and clean-up material employed. Also, during the first 12 calendar months of operation following issuance of this permit, the permittee shall record the cumulative coating usage for all emissions units at the facility for each calendar month.
4. The permittee shall maintain records of the facility's potential to emit for each individual hazardous air pollutant and the total of all hazardous air pollutants combined by maintaining a formal up-to-date HAP emissions inventory from all HAP emissions units at the facility. The permittee shall maintain a record including methods, procedures, and assumptions supporting the calculations.

IV. Reporting Requirements

- 1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.
- 2. The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than natural gas was burned in this emissions unit as fuel. Each report shall be submitted within 30 days after the deviation occurs.
- 3. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month usage rate limitations for coatings specified under A.II.2. These reports are due by the date described in Part I - General Terms and

Rexar Beverage Co. Company
PTI A
Issue

Facility ID: 044000007

Emissions Unit ID: K010

Conditions of this permit under section A.1.

Rexar

PTI A

Emissions Unit ID: K010

Issued: To be entered upon final issuance

4. Pursuant to the 40 CFR Part 60.7, the permittee shall submit quarterly written reports listing each coating used during the previous calendar quarter and the VOC content of each coating determined using Method 24 or supplied by the manufacturers of the coatings. These reports are due by the date described in Part I - General Terms and Conditions of this permit under section A.1.
5. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month total HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative total HAP emission limitation set forth in Part III, section A.II.1 of this permit.
6. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month individual HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative individual HAP emission limitation set forth in Part III, section A.II.1 of this permit.
7. The permittee shall notify in writing the Toledo Division of Environmental Services within 30 days of becoming aware of an exceedance of either of the limits specified under A.I.2.a.

V. Testing Requirements

1. Compliance with the Section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emission Limitation:

Emissions for all emissions units at the facility shall not exceed 9.9 tons per year for any single HAP and 24.9 tons per year for any combination of HAPs.

Applicable Compliance Method:

The monitoring and recordkeeping requirement A.III.4 will be used to demonstrate compliance.
 - b. Emission Limitation:

4.2 pounds of VOC per gallon of coating (excluding water and exempt solvents) for the Interior body coating, line 2 can body sprayers with oven(s).

Rexar

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: K010

Rexar

PTI A

Emissions Unit ID: K010

Issued: To be entered upon final issuance

Applicable Compliance Method:

Daily records shall be maintained of the VOC content of all coatings employed. In accordance with OAC rule 3745-21-10(B) and OAC rule 3745-21-04(B)(5), only coatings supplied by companies or entities that use USEPA Method 24 to determine the VOC content of coatings and properly report content on USEPA-approved VOC Data Sheets shall be employed. If the permittee determines that Method 24 has not been used for a particular coating, the permittee shall request that the coating supplier perform Method 24 on the coating in question. If the supplier determines that Method 24 cannot be used, the permittee shall so notify the Administrator of the USEPA and pursuant to section 4.3 of Method 24, 40 CFR Part 60, Appendix A, will request that the supplier use formulation data to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

c. Emission Limitation:

2.8 pounds of VOC per gallon of coating (excluding water and exempt solvents) for the Continuous Motion Printer, line 2 deco & over varnish with oven(s).

Applicable Compliance Method:

Daily records shall be maintained of the VOC content of all coatings employed. In accordance with OAC rule 3745-21-10(B) and OAC rule 3745-21-04(B)(5), only coatings supplied by companies or entities that use USEPA Method 24 to determine the VOC content of coatings and properly report content on USEPA-approved VOC Data Sheets shall be employed. If the permittee determines that Method 24 has not been used for a particular coating, the permittee shall request that the coating supplier perform Method 24 on the coating in question. If the supplier determines that Method 24 cannot be used, the permittee shall so notify the Administrator of the USEPA and pursuant to section 4.3 of Method 24, 40 CFR Part 60, Appendix A, will request that the supplier use formulation data to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

d. Emission Limitation:

0.25 pound per hour CO emissions

Applicable Compliance Method

Compliance shall be demonstrated by multiplying the maximum burner capacity (3.0 mmBtu/hr) by an emission factor of 84 pounds of CO per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Methods 1 thru 4 and 10 of 40 CFR Part 60 Appendix A. Alternative U.S. EPA approved test methods may be used with prior approval from Ohio EPA.

e. Emission Limitation:

1.10 tons per year CO emissions

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate (0.25 pound CO per hour) multiplied by 8760 hours per year and divided by 2000 pounds/ton. Therefore, compliance with the hourly CO limit constitutes compliance with the annual CO limit.

f. Emission Limitation:

0.30 pound per hour NO_x emissions

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner capacity (3.0 mmBtu/hr) by an emission factor of 100 pounds of NO_x per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

If required, the permittee shall demonstrate compliance using Methods 1 through 4 and 7E of 40 CFR Part 60, Appendix A. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

g. Emission Limitation:

Rexar

PTI A

Issued: To be entered upon final issuance

1.32 tons per year NO_x emissions

Emissions Unit ID: K010

Rexar

PTI A

Emissions Unit ID: K010

Issued: To be entered upon final issuance

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate (0.30 pound NO_x/hr) multiplied by 8760 hours per year and divided by 2000 pounds/ton. Therefore, compliance with the hourly NO_x limit constitutes compliance with the annual NO_x limit.

h. Emission Limitation:

0.01 pound per hour PE

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner capacity (3.0 mmBtu/hr) by an emission factor of 1.9 pounds of PE per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

If required, the permittee shall demonstrate compliance using Methods 1 thru 5 of 40 CFR part 60, Appendix A. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

i. Emission Limitation:

0.05 ton per year PE

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate (0.01 pound per hour) multiplied by 8760 hours per year and divided by 2000 pounds/ton. Therefore, compliance with the hourly particulate emission limit constitutes compliance with the annual particulate emission limit.

j. Emission Limitation:

0.03 pound per hour PM₁₀

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner

Rexar

PTI A

Emissions Unit ID: K010

Issued: To be entered upon final issuance

capacity (3.0 mmBtu/hr) by an emission factor of 7.6 pounds of PM₁₀ per million standard

Rexar

PTI A

Emissions Unit ID: K010

Issued: To be entered upon final issuance

cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

k. Emission Limitation:

0.13 ton per year PM₁₀

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate(0.03 pound per hour PM₁₀) multiplied by 8760 hours per year and divided by 2000 pounds/ton. Therefore, compliance with the hourly particulate emission limit constitutes compliance with the annual particulate emission limit.

l. Emission Limitation:

0.01 pound per hour SO₂

Applicable Compliance Method

Compliance shall be demonstrated by multiplying the maximum burner capacity (3.0 mmBtu/hr) by an emission factor of 0.6 pound of SO₂ per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

If required, the permittee shall demonstrate compliance using Methods 1 through 4 and 6 of 40 CFR part 60, Appendix A. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

m. Emission Limitation:

0.05 ton per year SO₂ emissions from the pin oven

Applicable Compliance Method

Annual allowable emissions are based on the hourly allowable emission rate (0.01 pound per hour SO₂) multiplied by 8760 hours per year and divided by 2000 pounds/ton. Therefore, compliance with the hourly emission limitation constitutes compliance with the annual SO₂ emission limitation.

n. Emission Limitation:

0.02 pound per hour VOC emissions from the combustion of natural gas

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner capacity (3.0 mmBtu/hr) by an emission factor of 5.5 pounds of VOC per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-2, dated 7/98.

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with Method 25 of 40 CFR Part 60, Appendix A. This demonstration shall be based on a summation of the emissions from the combustion of natural gas (0.02 pound per hour) and the emissions from all coatings and clean-up materials utilized (6.11 pounds per hour). Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

o. Emission Limitation:

0.09 ton of VOC per year from the combustion of natural gas

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate (0.01 pound per hour VOC) multiplied by 8760 hours per year and divided by 2000 pounds/ton. Therefore, compliance with the hourly emission limitation constitutes compliance with the annual VOC emission limitation.

p. Emission limitation:

2.0 pounds of VOC per gallon of coating minus water and exempt solvents

Applicable Compliance Method:

Rexar

PTI A

Emissions Unit ID: K010

Issued: To be entered upon final issuance

Compliance shall be determined through the monitoring and record keeping requirements of section A.III. If required, compliance shall be demonstrated by an evaluation performed in accordance with OAC rule(s) 3745-21-09(B)(3)(f) and 3745-21-10(B) using the methods and procedures specified in USEPA Reference Method 24 of 40 CFR Part 60, Appendix A.

Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

q. Emission limitation:

2.42 pound of VOC per gallon of coating solids (0.29 kilogram of VOC per liter of coating solids)

Applicable Compliance Method:

Compliance shall be determined through the monitoring and record keeping requirements of section A.III. If required, compliance shall be demonstrated by an evaluation performed in accordance with OAC rule 3745-21-10(B) and 40 CFR 60.496 using the methods and procedures specified in USEPA Reference Method 24 of 40 CFR Part 60, Appendix A.

Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

r. Emission Limitation:

6.16 pounds per hour VOC emissions from the coatings and clean-up materials

Applicable Compliance Method:

Rexar Beverage Can Company
PTI A
Issue

Facility ID: 044000007

Emissions Unit ID: K010

Compliance shall be demonstrated by multiplying the maximum coating application rate (6.22 gallon per hour) by the maximum VOC content recorded in Section A.III. above (in pounds VOC per gallon).

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with Method 25 of 40 CFR Part 60, Appendix A. This demonstration shall be based on a summation of the emissions from the

Rexar

PTI A

Emissions Unit ID: K010

Issued: To be entered upon final issuance

combustion of natural gas (0.02 pound per hour) and the emissions from all coatings and clean-up materials utilized (6.11 pounds per hour). Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

s. Emission Limitation:

5.04 tons of VOC per year from all coatings and clean-up materials

Applicable Compliance Method:

Compliance with this emission limitation will be demonstrated by the monitoring and recordkeeping requirements of Section III.

t. Emission Limitation:

5.13 tons of VOC per rolling, 12-month period

Applicable Compliance Method:

Compliance with this emissions limitation shall be demonstrated as the summation of the VOC emissions for the combustion of natural gas and the VOC emissions from all coatings and clean-up materials. Compliance with this emission limitation will be demonstrated by the monitoring and recordkeeping requirements of Section III.

VI. Miscellaneous Requirements

1. The terms and conditions contained in this permit to install for emissions unit K010 shall supercede all requirements for emissions units K004, K005, contained in the facility's Title V permit (issued 8/13/1998) and K006 contained in Permit to Install 04-01269 (issued 9/25/2001) and Permit to Install 04-01379 (issued 1/20/2005).

Rexar

PTI A

Emissions Unit ID: K010

Issued: To be entered upon final issuance

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K010 - Can manufacturing line 2 - a minor source of HAPs. Line 2 includes the interior body coating line, continuous motion printer, and continuous motion base coater lines with ovens. (Modification 11/29/2005)		

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

1. Should any coating formulations cause an odor, or process changes cause an increase in the quantity or intensity of odors emitted from this facility, as determined by the Toledo Division of Environmental Services, the company shall take corrective action to reduce the impact of the odors. The time schedule for the corrective action shall be approved by the Toledo Division of Environmental Services.

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for emissions units K010 (former emissions units K006 (Continuous Motion Coater, Line 2 Base Coating Line)) and K011 was evaluated

Rexar

PTI A

Emissions Unit ID: K010

Issued: To be entered upon final issuance

based on the actual materials and the design parameters of the each emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: glycol ethers

TLV (mg/m³): 19 (5ppm*90.12/24.05)

Maximum Hourly Emission Rate (lbs/hr): 11.41

(for former emissions units K006 (Continuous Motion Coater, Line 2 Base Coating Line) and K011 (Line 3 Interior Body Coating (can body sprayers) and Line 3 Continuous Motion Printer (deco & over varnish))

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 79.81 µg/m³

2. Physical changes to or changes in the method of operation of the emissions unit(s) after its (their) installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
 - a. changes in the composition of the materials used (typically for coatings or clean-up materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

Emissions Unit ID: K010

- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

- 3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
 - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Rexar

PTI A

Emissions Unit ID: K011

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, <u>and/or Equipment</u>	1.925 mmBtu/hr direct-fired natural gas washer drying oven with no controls	direct-fired natural gas curing oven, with no controls
K011 - Modification for can manufacturing line 3 to re-proportion yearly gallon limits on coatings. Line 3 is a two-piece beverage can manufacturing and coating line with 4 exhaust stacks and is a minor source of HAPS.		
12-ounce and 24-ounce beverage can body making process consisting of: (1) cupper, and (2) trimmers, all uncontrolled, and (2) body makers controlled by an oil mist collector		
	continuous motion printer and pin oven - ink, over varnish, and exterior bottom end varnish application, clean-up solvent emissions and 2.75 mmBtu/hr	inside body spray coating with 5.2 mmBtu/hr direct fired natural gas inside body bake oven, with no controls

Rexar
PTI A
Issue

Facility ID: 044000007

Emissions Unit ID: K011

Applicable
Rules/Requirements

OAC rule 3745-31-10 thru
27

OAC rule
3745-31-02(A)(2)

OAC rule
3745-31-05(A)(3)

OAC rule 3745-17-
07(A)(1)

OAC rule 3745-17-
11(B)(1)

OAC rule 3745-21-
07(G)(1)

OAC rule
3745-31-05(A)(3)

Rexar

PTI A

Emissions Unit ID: K011

Issued: To be entered upon final issuance

		<u>Applicable Emissions Limitations/Control Measures</u>
	OAC rule 3745-23-06(B)	
	40 CFR Part 60, Subpart WW	101.15 tons per rolling, 12-month period of volatile organic compound (VOC) emissions
	OAC rule 3745-31-05(A)(3)	See Section A.I.2.a.
OAC rule 3745-18-06(C)		
OAC rule 3745-21-08(B)		0.30 pound per hour and 1.32 tons per year of particulate emissions (PE);
OAC rule 3745-23-06(B)		0.30 pound per hour and 1.32 tons per year of PM ₁₀ ;
OAC rule 3745-31-05(A)(3)	rule	0.04 pound per hour and 0.18 ton per year VOC; and see sections A.I.2.b. and A.I.2.c
		See section A.I.2.d
		See section A.I.2.d
		See section A.I.2.d
	OAC rule 3745-17-07(A)(1)	0.16 pound per hour and 0.69 ton per year carbon monoxide (CO) emissions;
	OAC rule 3745-17-11(B)(1)	0.19 pound per hour and 0.83 ton per year nitrogen oxides (NOx) emissions;
	OAC rule 3745-18-06(C)	0.01 pound per hour and 0.05 ton per year of (PE);
OAC rule 3745-18-06(C)	OAC rule 3745-21-09(D)	0.02 pound per hour and 0.09 ton per year of PM ₁₀ ; and
OAC rule 3745-21-08(B)	OAC rule 3745-23-06(B)	0.01 pound per hour and 0.05 ton per year sulfur dioxide (SO ₂) emissions;
OAC rule 3745-21-09(D)	40 CFR Part 60, Subpart WW	and

Rexar

PTI A

Emissions Unit ID: K011

Issued: To be entered upon final issuance

0.01 pound per hour and 0.05 ton VOC per year from the combustion of natural gas; and see sections A.I.2.e and A.I.2.f	See section A.I.2.d	See section A.I.2.g
See section A.I.2.d	See section A.I.2.g	See section A.I.2.d
See section A.I.2.g	See section A.I.2.d	See section A.I.2.h
See section A.I.2.h	See section A.I.2.h	See section A.I.2.k
See section A.I.2.h	See section A.I.2.k	
0.23 pound per hour and 1.01 tons per year carbon monoxide (CO) emissions;	0.43 pound per hour and 1.88 tons per year CO emissions;	
0.27 pound per hour and 1.18 tons per year nitrogen oxides (NOx) emissions;	0.51 pound per hour and 2.24 tons per year NOx emissions;	
0.01 pound per hour and 0.05 ton per year of PE;	0.01 pound per hour and 0.05 ton per year of PE;	
0.02 pound per hour and 0.09 ton per year of PM ₁₀ ;	0.04 pound per hour and 0.18 ton per year of PM ₁₀ ;	
0.01 pound per hour and 0.05 ton per year sulfur dioxide (SO ₂) emissions;	0.01 pound per hour and 0.05 ton per year SO ₂ emissions;	
0.02 pound per hour and 0.09 ton VOC per year from the combustion of natural gas (see section A.I.2.e);	0.03 pound per hour and 0.13 ton VOC per year from the combustion of natural gas (see section A.I.2.e);	
9.86 pounds per hour and 34.36 tons per year VOC emissions from all coatings and clean-up materials; and see sections A.I.2.f, A.I.2.i, and A.I.2.j	0.26 pound per hour and 0.81 ton per year of PE from all coating operations;	
	0.26 pound per hour and 0.81 ton per year of PM ₁₀ from all coating operations;	
	21.68 pounds per hour and 66.34 tons per year VOC emissions from all coatings; and see sections A.I.2.f, A.I.2.j, and A.I.2.l	
	See section A.I.2.m	
	See section A.I.2.d	
	See section A.I.2.d	

Rexar

PTI A

Emissions Unit ID: K011

Issued: To be entered upon final issuance

2. Additional Terms and Conditions

- 2.a** The emissions of hazardous air pollutants (HAPs) from this facility, as identified in Section 112(b) of Title III of the Clean Air Act, shall not exceed 9.9 tons per year for any single HAP and 24.9 tons per year for any combination of HAPs.

Issued: To be entered upon final issuance

- 2.b** The permittee shall not operate the body making equipment when the oil mist collection system is not in operation.
- 2.c** Visible particulate emissions from the oil mist collector exhaust shall not exceed 5% opacity as a 6-minute average.
- 2.d** The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
- 2.e** The hourly and annual emission limitations were established for PTI purposes to reflect the potential to emit for the combustion of natural gas in this emissions unit at the maximum burner capacity. Therefore, it is not necessary to develop monitoring, record keeping and/or reporting requirements to ensure compliance with these limitations.
- 2.f** Visible particulate emissions from the oven exhaust shall not exceed 10% opacity as a 6-minute average.
- 2.g** The permittee has satisfied the "best available control techniques and operating practices" required pursuant to OAC rule 3745-21-08(B) by complying with all applicable rules.

On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the requirement to satisfy the "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

- 2.h** The permittee has satisfied the "latest available control techniques and operating practices" required pursuant to OAC rule 3745-23-06(B) by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05(A)(3) in this Permit to Install.

On February 14, 2005, OAC rule 3745-23-06 was rescinded; therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision

Emissions Unit ID: K011

to Ohio's State Implementation Plan (SIP). Therefore, until the U.S. EPA approves the revision to OAC rule 3745-23-06, the requirement to satisfy the "latest available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

- 2.i** Volatile organic compound (VOC) emissions from individual coatings shall not exceed the following:

inks:	1.81 pounds per gallon of coating excluding water and exempt solvents;
over varnish:	2.1 pounds per gallon of coating excluding water and exempt solvents;
over varnish:	2.9 pounds per gallon of coating solids;
exterior bottom end varnish:	2.1 pounds per gallon of coating excluding water and exempt solvents;
exterior bottom end varnish:	2.9 pounds per gallon of coating solids; and
clean-up solvent:	6.0 pounds of VOC per gallon.

- 2.j** The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09(D) and 40 CFR Part 60, Subpart WW.

- 2.k** This emissions unit is subject to the applicable provisions of Subpart WW of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60. The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

- 2.l** Volatile organic compound (VOC) emissions from individual coatings shall not exceed the following:

inside spray: 2.9 pounds per gallon of coating excluding water and exempt solvents; and
inside spray: 4.9 pounds per gallon of coating solids.

- 2.m** Visible particulate emissions from the inside body spray coating exhaust shall not exceed 5% opacity as a 6-minute average.

II. Operational Restrictions

1. The permittee shall burn only natural gas as fuel in this emissions unit.
2. Coating and clean-up material usage shall not exceed the following levels based upon a rolling, 12-month summation of the usage rates:

Rexar

PTI A

Emissions Unit ID: K011

Issued: To be entered upon final issuance

Inside spray: 144,040 gallons per rolling 12-month period;
Over varnish: 56,667 gallons per rolling 12-month period;
Bottom varnish: 2,447 gallons per rolling 12-month period;
Inks: 5,017 gallons per rolling 12-month period; and
Clean-up solvent: 360 gallons per rolling 12-month period.

To ensure enforceability during the first 12 calendar months of operation following issuance of this permit, the permittee shall not exceed the production levels specified in the following table:

Maximum Allowable Cumulative Usage

<u>Month</u> Over	Bottom Varnish <u>gallons</u>	Inside Varnish <u>gallons</u>	Spray <u>gallons</u>	Inks <u>gallons</u>	Cleanup Solvent <u>gallons</u>
1	4,850	220	12,640	430	30
1-2	9,700	440	25,280	860	60
1-3	14,550	660	37,920	1,290	90
1-4	19,400	880	50,560	1,720	120
1-5	24,250	1,100	63,200	2,150	150
1-6	29,100	1,320	75,840	2,580	180
1-7	33,950	1,540	88,480	3,010	210
1-8	38,800	1,760	101,120	3,440	240
1-9	43,650	1,980	113,760	3,870	270
1-10	48,500	2,200	126,400	4,300	300
1-11	53,350	2,440	139,040	4,730	330
1-12	56,667	2,447	144,040	5,017	360

After the first 12 calendar months of operation following issuance of this permit, compliance with the annual usage limitations shall be based upon a rolling, 12-month summation of the usage rates.

3. The individual HAP and total HAP, combined, emission rates for all emissions units at the facility shall not exceed 9.9 and 24.9 tons per year, respectively, based upon a rolling, 12-month summation of emission rates. To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed the usage levels for all emissions units at this facility specified in the following table:

Total HAP Individual HAP

<u>Month(s)</u>	<u>Emissions (Tons)</u>	<u>Emissions (Tons)</u>
1	2.1	0.9
1-2	4.2	1.7
1-3	6.3	2.6
1-4	8.4	3.4
1-5	10.5	4.3
1-6	12.6	5.1
1-7	14.7	6.0
1-8	16.8	6.8
1-9	18.9	7.7
1-10	20.9	8.5
1-11	22.9	9.4
1-12	24.9	9.9

After the first 12 calendar months of operation following the issuance of this permit, compliance with the individual HAP and total HAP, combined, emission limitations for all emissions units at the facility shall be based upon a rolling, 12-month summation of the monthly usage emission figures.

III. Monitoring and/or Recordkeeping Requirements

1. For each day during which the permittee burns a fuel other than natural gas, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.
2. The permittee shall maintain daily records that document any time periods when the oil mist collection system was not in service when the body making equipment was in operation.
3. The permittee shall perform daily checks, when the body making process is in operation and when the weather conditions allow, for any visible particulate emissions from the oil mist collector stack. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. the color of the emissions;
 - b. whether the emissions are representative of normal operations;
 - c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. the total duration of any visible emission incident; and
 - e. any corrective actions taken to eliminate the visible emissions.

If the daily checks show no visible emissions for 30 consecutive days, the required

Issued: To be entered upon final issuance

frequency of visible emissions checks may be reduced to weekly (once per week), when the emissions unit is in operation. If a subsequent check by the permittee or an Ohio EPA inspector indicates visible emissions, the frequency of emissions checks shall revert to daily until such time as there are 30 consecutive days of no visible emissions during operation.

4. The permittee shall collect and record the following information each month for the line:
 - a.
 - i. the name and identification number of each coating (i.e., over varnish, bottom varnish or inside spray coating), as applied,
 - ii. the volume of each coating, in gallons,
 - iii. the VOC content of each coating, in pounds of VOC per gallon of coating,
 - iv. the VOC content of each coating, in pounds of VOC per gallon of coating excluding water and exempt solvents,
 - v. the VOC content of each coating, in pounds of VOC per gallon of solids, as applied,
 - vi. the monthly total VOC emissions from all coatings employed, $(ii) \times (iii) \div 2000$, in tons;
 - b.
 - i. the name and identification number of each ink, as applied,
 - ii. the volume (and mass) of each ink, in gallons (and pounds),
 - iii. the VOC content of each ink, in pounds of VOC per gallon (or pound) of ink,
 - iv. the VOC content of each ink, in pounds of VOC per gallon of coating excluding water and exempt solvents,
 - v. the monthly total VOC emissions from all inks employed, calculated on a volume (or mass) basis, $(ii) \times (iii) \div 2000$, in tons;
 - c.
 - i. the name and identification number of each clean-up material employed,
 - ii. the volume of each clean-up material employed, in gallons,
 - iii. the VOC content of each clean-up material employed, in pounds of VOC per gallon,
 - iv. the monthly total VOC emissions from all clean-up materials employed, $(ii) \times (iii) \div 2000$, in tons;
 - d. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation of VOC emissions from all coatings, inks and clean-up materials employed, in tons. Also, during the first

Emissions Unit ID: K011

12 calendar months of operation following issuance of this permit, the permittee shall record the cumulative VOC emission rate for each calendar month.

- e. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation, of each type of coating employed in gallons. Also, during the first 12 calendar months of operation following issuance of this permit, the permittee shall record the cumulative coating usage rates for each calendar month.
- f. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation, of each type of ink employed in gallons. Also, during the first 12 calendar months of operation following issuance of this permit, the permittee shall record the cumulative ink usage rates for each calendar month.

Rexar

PTI A

Emissions Unit ID: K011

Issued: To be entered upon final issuance

emissions units at the facility. The permittee shall maintain a record including methods, procedures, and assumptions supporting the calculations.

Issued: To be entered upon final issuance

IV. Reporting Requirements

1. The permittee shall notify in writing the Toledo Division of Environmental Services within 30 days of becoming aware of an exceedance of either of the limits specified under A.I.2.a.
2. The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than natural gas was burned in this emissions unit as fuel. Each report shall be submitted within 30 days after the deviation occurs.
3. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any daily record showing that the oil mist collector was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.
4. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any monthly record showing the use of noncomplying coatings, inks, or clean-up solvent. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.
5. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month usage rate limitations for coatings, inks and clean-up solvents specified under A.II.2. and, for the first 12 calendar months of operation following issuance of this permit, all exceedances of the maximum allowable cumulative usage levels of coatings, inks and clean-up solvents. These reports are due by the date described in Part I - General Terms and Conditions of this permit under section A.1.
6. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from any stack serving this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
7. Pursuant to the 40 CFR Part 60.8, the permittee shall submit quarterly written reports listing each coating used during the previous calendar quarter and the VOC content of each coating determined using Method 24 or supplied by the

Rexar Beverage Can Company
PTI A
Issue

Facility ID: 014000007

Emissions Unit ID: K011

manufacturers of the coatings. These reports are due by the date described in Part I
- General Terms and Conditions of this permit under section A.1.

Rexar

PTI A

Emissions Unit ID: K011

Issued: To be entered upon final issuance

8. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month total HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative total HAP emission limitation set forth in Part III, section A.II.2 of this permit.
9. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month individual HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative individual HAP emission limitation set forth in Part III, section A.II.2 of this permit.

V. Testing Requirements

1. Compliance with the emission limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation:

Emissions for all emissions units at the facility shall not exceed 9.9 tons per year for any single HAP and 24.9 tons per year for any combination of HAPs.

Applicable Compliance Method:

The monitoring and recordkeeping requirement A.III.5 will be used to demonstrate compliance.

- b. Emission Limitation:

101.15 tons of VOC per rolling, 12-month period

Applicable Compliance Method:

Compliance with this emissions limitation shall be demonstrated as the summation of the VOC emissions for the combustion of natural gas and the VOC emissions from all coatings, inks and clean-up materials. Compliance with this emission limitation will be demonstrated by the monitoring and recordkeeping requirements of Section III.

- c. Emission Limitation:

10% opacity as a 6-minute average from the oven exhaust

Rexar

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: K011

Rexar

PTI A

Emissions Unit ID: K011

Issued: To be entered upon final issuance

Applicable Compliance Method:

If required, compliance shall be demonstrated through visible emissions readings taken in accordance with Method 9 of 40 CFR Part 60, Appendix A.

d. Emission Limitation:

5% opacity as a 6-minute average from the oil mist collector and inside body spray

Applicable Compliance Method:

If required, compliance shall be demonstrated through visible emissions readings taken in accordance with Method 9 of 40 CFR Part 60, Appendix A.

e. Emission Limitation:

0.30 pound per hour PE from the body making process

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum coolant usage (1.25 gal/hr) by the coolant density (8.55 lb coating/gal coating), the solid concentration (0.55 lb PE/lb coating) and the estimated oil mist collector efficiency (1-0.95).

If required, the permittee shall demonstrate compliance using Methods 1 thru 5 of 40 CFR part 60, Appendix A. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

f. Emission Limitation:

1.32 tons per year PE from the body making process

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate (0.30 pound per hour) multiplied by the maximum annual operating hours (8760 hours per year), divided by 2000 pounds/ton. Therefore, compliance with the hourly particulate emission limitation constitutes compliance with the annual particulate emission limitation.

Rexar Beverage Co. Company
PTI A
Issue

Facility ID: 014000007

Emissions Unit ID: K011

Rexar

PTI A

Emissions Unit ID: K011

Issued: To be entered upon final issuance

g. Emission Limitation:

0.30 pound per hour PM₁₀ from the body making process

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum coolant usage (1.25 gal/hr) by the coolant density (8.55 lb coating/gal coating), the solid concentration (0.55 lb PM₁₀/lb coating) and the estimated oil mist collector efficiency (1-0.95).

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

h. Emission Limitation:

1.32 tons per year PM₁₀ from the body making process

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate (0.30 pound per hour PM₁₀) multiplied by 8760 hours per year and divided by 2000 pounds/ton. Therefore, compliance with the hourly emission limitation constitutes compliance with the annual PM₁₀ emission limitation.

i. Emission Limitation:

0.04 pound per hour VOC from the body making process

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum coolant usage (1.25 gal/hr) by the coolant density (8.55 lb coating/gal coating), the VOC concentration (0.065 lb PE/lb coating) and the estimated oil mist collector efficiency (1-0.95).

If required, the permittee shall demonstrate compliance using Methods 1 thru 5 of 40 CFR part 60, Appendix A. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

Rexar

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: K011

Rexar

PTI A

Emissions Unit ID: K011

Issued: To be entered upon final issuance

j. Emission Limitation:

0.18 ton per year VOC from the body making process

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate (0.04 pound per hour) multiplied by the maximum annual operating hours (8760 hours per year), divided by 2000 pounds/ton. Therefore, compliance with the hourly VOC emission limitation constitutes compliance with the annual particulate emission limitation.

k. Emission Limitation:

0.16 pound per hour CO emissions from the washer oven

Applicable Compliance Method

Compliance shall be demonstrated by multiplying the maximum burner capacity (1.925 mmBtu/hr) by an emission factor of 84 pounds of CO per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Methods 1 thru 4 and 10 of 40 CFR Part 60 Appendix A. Alternative U.S. EPA approved test methods may be used with prior approval from Ohio EPA.

l. Emission Limitation:

0.69 ton per year CO emissions from the washer oven

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate (0.16 pound per hour) multiplied by 8760 hours per year and divided by 2000 pounds/ton. Therefore, compliance with the hourly CO limit constitutes compliance with the annual CO limit.

m. Emission Limitation:

0.19 pound per hour NO_x emissions from the washer oven

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner capacity (1.925 mmBtu/hr) by an emission factor of 100 pounds of NO_x per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

If required, the permittee shall demonstrate compliance using Methods 1 through 4 and 7E of 40 CFR Part 60, Appendix A. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

n. Emission Limitation:

0.83 ton per year NO_x emissions from the washer oven

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate (0.19 pound per hour) multiplied by 8760 hours per year and divided by 2000 pounds/ton. Therefore, compliance with the hourly NO_x limit constitutes compliance with the annual NO_x limit.

o. Emission Limitation:

0.01 pound per hour PE from the washer oven

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner capacity (1.925 mmBtu/hr) by an emission factor of 1.9 pounds of PE per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

If required, the permittee shall demonstrate compliance using Method 5 of 40 CFR part 60, Appendix A. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

p. Emission Limitation:

Rexar

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: K011

0.05 ton per year PE from the washer oven

Issued: To be entered upon final issuance

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate (0.01 pound per hour) multiplied by 8760 hours per year and divided by 2000 pounds/ton. Therefore, compliance with the hourly particulate emission limit constitutes compliance with the annual particulate emission limit.

q. Emission Limitation:

0.02 pound per hour PM₁₀ from the washer oven

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner capacity (1.925 mmBtu/hr) by an emission factor of 7.6 pounds of PM₁₀ per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

r. Emission Limitation:

0.09 ton per year PM₁₀ from the washer oven

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate (0.02 pound per hour) multiplied by 8760 hours per year and divided by 2000 pounds/ton. Therefore, compliance with the hourly particulate emission limit constitutes compliance with the annual particulate emission limit.

s. Emission Limitation:

0.01 pound per hour SO₂ emissions from the washer oven

Applicable Compliance Method

Rexar

PTI A

Emissions Unit ID: K011

Issued: To be entered upon final issuance

Compliance shall be demonstrated by multiplying the maximum burner capacity (1.925 mmBtu/hr) by an emission factor of 0.6 pound of SO₂ per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

If required, the permittee shall demonstrate compliance using Methods 1 through 4 and 6 of 40 CFR part 60, Appendix A. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

t. Emission Limitation:

0.05 ton per year SO₂ emissions from the washer oven

Applicable Compliance Method

Annual allowable emissions are based on the hourly allowable emission rate (0.01 pound per hour) multiplied by 8760 hours per year and divided by 2000 pounds/ton. Therefore, compliance with the hourly emission limitation constitutes compliance with the annual SO₂ emission limitation.

u. Emission Limitation:

0.01pound per hour VOC emissions from the combustion of natural gas in the washer oven

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner capacity (1.925 mmBtu/hr) by an emission factor of 5.5 pounds of VOC per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with Method 25 of 40 CFR Part 60, Appendix A. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

v. Emission Limitation:

Rexar Beverage Can Company
PTI A
Issue

Facility ID: 044000007

Emissions Unit ID: K011

0.05 ton per year VOC emissions from the combustion of natural gas in the washer oven

Issued: To be entered upon final issuance

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate (0.01 pound per hour) multiplied by 8760 hours per year and divided by 2000 pounds/ton. Compliance with the hourly VOC emissions limit constitutes compliance with the annual limit.

w. Emission Limitation:

0.23 pound per hour CO emissions from the combustion of natural gas in the pin oven

Applicable Compliance Method

Compliance shall be demonstrated by multiplying the maximum burner capacity (2.75 mmBtu/hr) by an emission factor of 84 pounds of CO per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Methods 1 thru 4 and 10 of 40 CFR Part 60 Appendix A. Alternative U.S. EPA approved test methods may be used with prior approval from Ohio EPA.

x. Emission Limitation:

1.01 tons per year CO emissions from the combustion of natural gas in the pin oven

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate (0.23 pound per hour) multiplied by 8760 hours per year and divided by 2000 pounds/ton. Therefore, compliance with the hourly CO limit constitutes compliance with the annual CO limit.

y. Emission Limitation:

0.27 pound per hour NO_x emissions from the combustion of natural gas in the pin oven

Rexar

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: K011

Rexar

PTI A

Emissions Unit ID: K011

Issued: To be entered upon final issuance

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner capacity (2.75 mmBtu/hr) by an emission factor of 100 pounds of NO_x per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

If required, the permittee shall demonstrate compliance using Methods 1 through 4 and 7E of 40 CFR Part 60, Appendix A. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

z. Emission Limitation:

1.18 tons per year NO_x emissions from the combustion of natural gas in the pin oven

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate (0.27 pound per hour) multiplied by 8760 hours per year and divided by 2000 pounds/ton. Therefore, compliance with the hourly NO_x limit constitutes compliance with the annual NO_x limit.

aa. Emission Limitation:

0.01 pound per hour PE emissions from the combustion of natural gas in the pin oven

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner capacity (2.75 mmBtu/hr) by an emission factor of 1.9 pounds of PE per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

If required, the permittee shall demonstrate compliance using Methods 1 thru 5 of 40 CFR part 60, Appendix A. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

bb. Emission Limitation:

0.05 ton per year PE emissions from the combustion of natural gas in the pin oven

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate (0.01 pound per hour) multiplied by 8760 hours per year and divided by 2000 pounds/ton. Therefore, compliance with the hourly particulate emission limit constitutes compliance with the annual particulate emission limit.

cc. Emission Limitation:

0.02 pound per hour PM₁₀ emissions from the combustion of natural gas in the pin oven

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner capacity (2.75 mmBtu/hr) by an emission factor of 7.6 pounds of PM₁₀ per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

dd. Emission Limitation:

0.09 ton per year PM₁₀ emissions from the combustion of natural gas in the pin oven

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate (0.02 pound per hour) multiplied by 8760 hours per year and divided by 2000 pounds/ton. Therefore, compliance with the hourly particulate emission limit constitutes compliance with the annual particulate emission limit.

ee. Emission Limitation:

0.01 pound per hour SO₂ emissions from the combustion of natural gas in the pin oven

Applicable Compliance Method

Compliance shall be demonstrated by multiplying the maximum burner capacity (2.75 mmBtu/hr) by an emission factor of 0.6 pound of SO₂ per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

If required, the permittee shall demonstrate compliance using Methods 1 through 4 and 6 of 40 CFR part 60, Appendix A. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

ff. Emission Limitation:

0.05 ton per year SO₂ emissions from the combustion of natural gas in the pin oven

Applicable Compliance Method

Annual allowable emissions are based on the hourly allowable emission rate (0.01 pound per hour) multiplied by 8760 hours per year and divided by 2000 pounds/ton. Therefore, compliance with the hourly emission limitation constitutes compliance with the annual SO₂ emission limitation.

gg. Emission Limitation:

0.02 pound per hour VOC emissions from the combustion of natural gas in the pin oven

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner capacity (2.75 mmBtu/hr) by an emission factor of 5.5 pound of VOC per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air

Rexar

PTI A

Emissions Unit ID: K011

Issued: To be entered upon final issuance

Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

Issued: To be entered upon final issuance

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with Method 25 of 40 CFR Part 60, Appendix A. This demonstration shall be based on a summation of the emissions from the combustion of natural gas in the pin oven (0.02 pound per hour) and the emissions from all coatings and clean-up materials utilized in the continuous motion printer (9.86 pounds per hour). Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

hh. Emission Limitation:

0.09 ton per year VOC emissions from the combustion of natural gas in the pin oven

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate (0.02 pound per hour) multiplied by 8760 hours per year and divided by 2000 pounds/ton. Compliance with the hourly VOC emissions limit constitutes compliance with the annual limit.

ii. Emission Limitation:

9.86 pounds per hour VOC emissions from all coatings, inks and clean-up materials utilized in the continuous motion printer.

Applicable Compliance Method:

Compliance shall be demonstrated by a summation of the VOC emissions from each coating and ink, calculated as the maximum application rate (in gallons per hour) for each coating and ink, multiplied by the maximum VOC content recorded in Section A.III. above (in pounds VOC per gallon).

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with Method 25 of 40 CFR Part 60, Appendix A. This demonstration shall be based on a summation of the emissions from the combustion of natural gas in the pin oven (0.02 pound per hour) and the emissions from all coatings, inks and clean-up materials utilized in the continuous motion printer (9.86 pounds per hour). Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

Rexar Beverage Co. Company
PTI A
Issue

Facility ID: 014000007

Emissions Unit ID: K011

Rexar

PTI A

Emissions Unit ID: K011

Issued: To be entered upon final issuance

jj. Emission Limitation:

34.36 tons of VOC per year emissions from all coatings, inks and clean-up materials utilized in the continuous motion printer

Applicable Compliance Method:

Compliance with this emission limitation will be demonstrated by the monitoring and recordkeeping requirements of Section III.

kk. Emission Limitation:

0.43 pound per hour CO emissions from the combustion of natural gas in the inside body bake oven

Applicable Compliance Method

Compliance shall be demonstrated by multiplying the maximum burner capacity (5.2 mmBtu/hr) by an emission factor of 84 pounds of CO per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Methods 1 thru 4 and 10 of 40 CFR Part 60 Appendix A. Alternative U.S. EPA approved test methods may be used with prior approval from Ohio EPA.

ll. Emission Limitation:

1.88 tons per year CO emissions from the combustion of natural gas in the inside body bake oven.

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate (0.43 pound per hour) multiplied by the maximum annual hours of operation (8,760 hrs/yr), and divided by 2000 pounds/ton. Therefore, compliance with the hourly CO limit constitutes compliance with the annual CO limit.

mm. Emission Limitation:

Rexar

PTI A

Emissions Unit ID: K011

Issued: To be entered upon final issuance

0.51 pound per hour NO_x emissions from the combustion of natural gas in the inside body bake oven

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner capacity (5.2 mmBtu/hr) by an emission factor of 100 pounds of NO_x per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

If required, the permittee shall demonstrate compliance using Methods 1 through 4 and 7E of 40 CFR Part 60, Appendix A. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

nn. Emission Limitation:

2.24 tons per year NO_x emissions from the combustion of natural gas in the inside body bake oven

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate (0.51 pound per hour) multiplied by the maximum annual hours of operation (8760 hrs/yr), and divided by 2000 pounds/ton. Therefore, compliance with the hourly NO_x limit constitutes compliance with the annual NO_x limit.

oo. Emission Limitation:

0.01 pound per hour PE emissions from the combustion of natural gas in the inside body bake oven

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner capacity (5.2 mmBtu/hr) by an emission factor of 1.7 pounds of PE per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

Emissions Unit ID: K011

If required, the permittee shall demonstrate compliance using Methods 1 thru 5 of 40 CFR part 60, Appendix A. This demonstration shall be based on a summation of the emissions from the combustion of natural gas in the inside body bake oven (0.01 pound per hour) and the emissions from all coatings utilized in the inside body spray operation (0.19 pound per hour). Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

pp. Emission Limitation:

0.05 ton per year PE emissions from the combustion of natural gas in the inside body bake oven

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate (0.01 pound per hour) multiplied by the maximum annual hours of operation (8760 hrs/yr), and divided by 2000 pounds/ton. Therefore, compliance with the hourly particulate emission limit constitutes compliance with the annual particulate emission limit.

qq. Emission Limitation:

0.04 pound per hour PM₁₀ emissions from the combustion of natural gas in the inside body bake oven

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner capacity (5.2 mmBtu/hr) by an emission factor of 7.6 pound of PM₁₀ per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M. This demonstration shall be based on a summation of the emissions from the combustion of natural gas in the inside body bake oven (0.04 pound per hour) and the emissions from all coatings utilized in the inside body spray operation (0.19 pound per hour). Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

rr. Emission Limitation:

Rexar

PTI A

Emissions Unit ID: K011

Issued: To be entered upon final issuance

0.18 ton per year PM₁₀ emissions from the combustion of natural gas in the inside body bake oven.

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate (0.04 pound per hour) multiplied by the maximum annual hours of operation (8760 hrs/yr), and divided by 2000 pounds/ton. Therefore, compliance with the hourly particulate emission limit constitutes compliance with the annual particulate emission limit.

ss. Emission Limitation:

0.01 pound per hour SO₂ emissions from the combustion of natural gas in the inside body bake oven

Applicable Compliance Method

Compliance shall be demonstrated by multiplying the maximum burner capacity (5.2 mmBtu/hr) by an emission factor of 0.6 pound of SO₂ per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

If required, the permittee shall demonstrate compliance using Methods 1 through 4 and 6 of 40 CFR part 60, Appendix A. Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

tt. Emission Limitation:

0.05 ton per year SO₂ emissions from the combustion of natural gas in the inside body bake oven

Applicable Compliance Method

Annual allowable emissions are based on the hourly allowable emission rate (0.01 pound per hour) multiplied by 8760 hours per year and divided by 2000 pounds/ton. Therefore, compliance with the hourly emission limitation constitutes compliance with the annual SO₂ emission limitation.

uu. Emission Limitation:

Issued: To be entered upon final issuance

0.03 pound per hour VOC emissions from the combustion of natural gas in the inside body bake oven

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum burner capacity (5.2 mmBtu/hr) by an emission factor of 5.5 pounds of VOC per million standard cubic feet of natural gas (mmscft) divided by a heating value of 1020 million Btu per mmscft from AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 1.4, Table 1.4-1, dated 7/98.

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with Method 25 of 40 CFR Part 60, Appendix A. This demonstration shall be based on a summation of the emissions from the combustion of natural gas in the inside body bake oven (0.03 pound per hour) and the emissions from all coatings utilized in the inside body spray operation (21.68 pounds per hour). Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

vv. Emission Limitation:

0.13 ton per year of VOC emissions from the inside body bake oven

Applicable Compliance Method:

Annual allowable emissions are based on the hourly allowable emission rate (0.03 pound per hour) multiplied by 8760 hours per year and divided by 2000 pounds/ton. Compliance with the hourly VOC emissions limit constitutes compliance with the annual limit.

ww. Emission Limitation:

0.26 pound per hour PE emissions from the inside body spray

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum coating usage rate (23.52 gal/hr) by the coating density (8.43 lb coating/gal coating), the solid concentration (0.216 lb PE/lb coating), the estimated transfer efficiency (1-0.94) and the estimated collector efficiency (1-0.90).

If required, the permittee shall demonstrate compliance using Methods 1 thru 5 of 40 CFR part 60, Appendix A. This demonstration shall be based on a summation of the emissions from the combustion of natural gas in the inside body bake oven (0.01 pound per hour) and the emissions from all coatings utilized in the inside body spray operation (0.26 pound per hour). Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

xx. Emission Limitation:

0.81 ton per year PE emissions from the inside body spray

Rexar

PTI A

Emissions Unit ID: K011

Issued: To be entered upon final issuance

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum coating usage rate (148,214 gal/yr) by the coating density (8.43 lb coating/gal coating), the solid concentration (0.216 lb PE/lb coating), the estimated transfer efficiency (1-0.94) and the estimated collector efficiency (1-0.90), and then dividing by 2000 lb/ton.

yy. Emission Limitation:

0.26 pound per hour PM₁₀ emissions from the inside body spray

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum coating usage rate (23.52 gal/hr) by the coating density (8.43 lb coating/gal coating), the solid concentration (0.216 lb PM₁₀/lb coating), the estimated transfer efficiency (1-0.94) and the estimated collector efficiency (1-0.90).

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M. This demonstration shall be based on a summation of the emissions from the combustion of natural gas in the inside body bake oven (0.04 pound per hour) and the emissions from all coatings utilized in the inside body spray operation (0.19 pound per hour). Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

zz. Emission Limitation:

0.81 ton per year PM₁₀ emissions from the inside body spray

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the maximum coating usage rate (148,214 gal/yr) by the coating density (8.43 lb coating/gal coating), the solid concentration (0.55 lb PM₁₀/lb coating), the estimated transfer efficiency (1-0.94) and the estimated collector efficiency (1-0.90), and then dividing by 2000 lb/ton.

aaa. Emission Limitation:

Rexar

PTI A

Emissions Unit ID: K011

Issued: To be entered upon final issuance

21.68 pounds per hour VOC emissions from all coatings utilized in the inside body spray operation

Applicable Compliance Method:

Compliance shall be demonstrated by a summation of the VOC emissions from each coating utilized, calculated as the maximum application rate for the inside spray coating (23.52 gallons per hour), multiplied by the maximum VOC content recorded in Section A.III. above (in pounds VOC per gallon).

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with Method 25 of 40 CFR Part 60, Appendix A. This demonstration shall be based on a summation of the emissions from the combustion of natural gas in the inside body bake oven (0.03 pound per hour) and the emissions from all coatings utilized in the inside body spray operation (21.68 pounds per hour). Alternative U.S. EPA-approved test methods can be used with prior approval from Ohio EPA.

bbb. Emission Limitation:

66.34 tons of VOC per year emissions from all coatings utilized in the inside body spray operation

Applicable Compliance Method:

Compliance with this emission limitation will be demonstrated by the monitoring and recordkeeping requirements of Section III.

ccc. Emission limitation:

inks: 1.81 pounds per gallon of coating excluding water and exempt solvents

Applicable Compliance Method:

Compliance shall be determined through the monitoring and record keeping requirements of section A.III. If required, compliance shall be demonstrated by an evaluation performed in accordance with OAC rule(s) 3745-21-09(B)(3)(f) and 3745-21-10(B) using the methods and procedures specified in USEPA Reference Method 24 of 40 CFR Part 60, Appendix A.

Alternate, equivalent methods may be used upon approval by the Toledo

Emissions Unit ID: K011

Division of Environmental Services. If, pursuant to Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

ddd. Emission limitation:

over varnish: 2.1 pounds per gallon of coating, excluding water and exempt solvents

Applicable Compliance Method:

Compliance shall be determined through the monitoring and record keeping requirements of section A.III. If required, compliance shall be demonstrated by an evaluation performed in accordance with OAC rule(s) 3745-21-09(B)(3)(f) and 3745-21-10(B) using the methods and procedures specified in USEPA Reference Method 24 of 40 CFR Part 60, Appendix A.

Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

eee. Emission limitation:

over varnish: 2.9 pounds per gallon of coating solids

Applicable Compliance Method:

Compliance shall be determined through the monitoring and record keeping requirements of section A.III. If required, compliance shall be demonstrated by an evaluation performed in accordance with OAC rule 3745-21-10(B) and 40 CFR 60.496 using the methods and procedures specified in USEPA Reference Method 24 of 40 CFR Part 60, Appendix A.

Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to

Rexar

PTI A

Emissions Unit ID: K011

Issued: To be entered upon final issuance

demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

fff. Emission limitation:

bottom varnish (exterior bottom end coating): 2.1 pounds per gallon of coating excluding water and exempt solvents

Applicable Compliance Method:

Compliance shall be determined through the monitoring and record keeping requirements of section A.III. If required, compliance shall be demonstrated by an evaluation performed in accordance with OAC rule(s) 3745-21-09(B)(3)(f) and 3745-21-10(B) using the methods and procedures specified in USEPA Reference Method 24 of 40 CFR Part 60, Appendix A.

Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

ggg. Emission limitation:

bottom varnish (exterior bottom end coating): 2.9 pounds per gallon of coating solids.

Applicable Compliance Method:

Compliance shall be determined through the monitoring and record keeping requirements of section A.III. If required, compliance shall be demonstrated by an evaluation performed in accordance with OAC rule 3745-21-10(B) and 40 CFR 60.496 using the methods and procedures specified in USEPA Reference Method 24 of 40 CFR Part 60, Appendix A.

Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to

demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

hhh. Emission limitation:

clean-up solvent: 6.0 pounds of VOC per gallon.

Applicable Compliance Method:

The permittee shall determine the VOC-content of the clean-up solvent from manufacturer's formulation data.

iii. Emission limitation:

inside spray: 2.9 pounds per gallon of coating excluding water and exempt solvents

Applicable Compliance Method:

Compliance shall be determined through the monitoring and record keeping requirements of section A.III. If required, compliance shall be demonstrated by an evaluation performed in accordance with OAC rule(s) 3745-21-09(B)(3)(f) and 3745-21-10(B) using the methods and procedures specified in USEPA Reference Method 24 of 40 CFR Part 60, Appendix A.

Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

jjj. Emission limitation:

inside spray: 4.9 pounds per gallon of coating solids

Applicable Compliance Method:

Compliance shall be determined through the monitoring and record keeping requirements of section A.III. If required, compliance shall be demonstrated by an evaluation performed in accordance with 3745-21-10(B) and 40 CFR 60.496 using the methods and procedures specified in USEPA Reference Method 24 of 40 CFR Part 60, Appendix A.

Alternate, equivalent methods may be used upon approval by the Toledo

Rexar

PTI A

Emissions Unit ID: K011

Issued: To be entered upon final issuance

Division of Environmental Services. If, pursuant to Method 24, 40 CFR Part 60, Appendix A, the permittee determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

Rexar

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: K011

VI. Miscellaneous Requirements

1. The terms and conditions contained in this permit to install for emissions unit K011 shall supercede all requirements for emissions unit K011 contained in Permit to Install 04-01269 (issued 9/25/2001) and Permit to Install 04-01379 (issued 1/20/2005).

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K011 - Modification for can manufacturing line 3 to re-proportion yearly gallon limits on coatings. Line 3 is a two-piece beverage can manufacturing and coating line with 4 exhaust stacks and is a minor source of HAPS.		

2. Additional Terms and Conditions

- 2.a** None

II. Operational Restrictions

1. Should any coating formulations cause an odor, or process changes cause an increase in the quantity or intensity of odors emitted from this facility, as determined by the Toledo Division of Environmental Services, the company shall take corrective action to reduce the impact of the odors. The time schedule for the corrective action shall be approved by the Toledo Division of Environmental Services.

III. Monitoring and/or Recordkeeping Requirements

1. The permit to install for emissions units K010 (former emissions units K006 (Continuous Motion Coater, Line 2 Base Coating Line)) and K011 was evaluated based on the actual materials and the design parameters of the each emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit

Rexar

PTI A

Emissions Unit ID: K011

Issued: To be entered upon final issuance

using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: glycol ethers

TLV (mg/m³): 19 (5ppm*90.12/24.05)

Maximum Hourly Emission Rate (lbs/hr): 11.41

(for former emissions units K006 and K011 - under PTI 04-01429, the emission units are the continuous motion coater, line 2 base coating line under K013 and all of K014)

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 79.81 µg/m³

2. Physical changes to or changes in the method of operation of the emissions unit(s) after its (their) installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
 - a. changes in the composition of the materials used (typically for coatings or clean-up materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

Emissions Unit ID: K011

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
 - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Rexar

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: K011

NEW SOURCE REVIEW FORM B

PTI Number: 04-01429 Facility ID: 0448002007

FACILITY NAME Rexam Beverage Can CompanyFACILITY DESCRIPTION Aluminum Can Coating Facility CITY/TWP WhitehouseSIC CODE 3411 SCC CODE 2401040000 EMISSIONS UNIT ID K009EMISSIONS UNIT DESCRIPTION Can manufacturing line 1- a minor source of HAPs.DATE INSTALLED June, 1974

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	N/A				
PM ₁₀	Unclassified				
Sulfur Dioxide	Attainment				
Organic Compounds	Non-attainment				174.96
Nitrogen Oxides	Unclassified/Attainment				
Carbon Monoxide	Unclassified/Attainment				
Lead					
Other: Air Toxics	HAPs				9.9 tpy & 24.9 tpy

APPLICABLE FEDERAL RULES:

NSPS? No

NESHAP? **WW**

PSD? No

OFFSET POLICY? No

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Use of waterborne, low solvent coating

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? No

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES X NO

IDENTIFY THE AIR CONTAMINANTS: _____

NEW SOURCE REVIEW FORM B

PTI Number: 04-01429 Facility ID: 0448002007

FACILITY NAME Rexam Beverage Can Company

FACILITY DESCRIPTION Aluminum Can Coating Facility CITY/TWP Whitehouse

Emissions Unit ID: K011

SIC CODE 3411 SCC CODE 2401040000 EMISSIONS UNIT ID K010

EMISSIONS UNIT DESCRIPTION Can manufacturing line 2 - a minor source of HAPs

DATE INSTALLED June, 1974

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	N/A			0.01 lb/hr	0.05
PM ₁₀	Unclassified			0.03 lb/hr	0.13
Sulfur Dioxide	Attainment			0.01 lb/hr	0.05
Organic Compounds	Non-Attainment				141.74
Nitrogen Oxides	Unclassified/Attainment			0.30 lb/hr	1.32
Carbon Monoxide	Unclassified/Attainment			0.25 lb/hr	1.10
Lead					
Other: Air Toxics	HAPs				9.9 tpy & 24.9 tpy

APPLICABLE FEDERAL RULES:

NSPS? No

NESHAP? **WW**

PSD? No

OFFSET POLICY? No

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

2.0 lbs VOC/gal - water and exempt solvents for base coater

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? Yes

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ _____

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES X NO

IDENTIFY THE AIR CONTAMINANTS: _____

NEW SOURCE REVIEW FORM B

PTI Number: 04-01429

Facility ID: 0448002007

FACILITY NAME Rexam Beverage Can CompanyFACILITY DESCRIPTION Aluminum Can Coating FacilityCITY/TWP Whitehouse

Emissions Unit ID: K011

ADMINISTRATIVE MODIFICATION
inter-office communication**To:** DAPC, Air Quality Modeling and Planning**From:** Brad Faggionato**Subject:** Administrative Modification to Permit To Install**Date:** July 28, 2006

Choose one:

Initiated by: Permittee DO/LAA This modification is the result of an appeal to the Environmental Review Appeals Commission*Please fill out the following:*

SUMMARY (for informational purposes only)

TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**Pollutant Tons Per Year**

<u>HAPs</u>	
any one HAP	9.9
total, combined facility	24.9
HAP	
CO (Line 2 base coater w/pin oven and Line 3)	4.68
NOx (Line 2 base coater w/pin oven and Line 3)	5.57
PE (Line 2 base coater w/pin oven and Line 3)	2.33
PM10 (Line 2 base coater w/pin oven and Line 3)	2.62
SO2 (Line 2 base coater w/pin oven and Line 3)	0.20
VOC (from PTI 04-01379, Title V Permit)	417.85

Please provide a fairly detailed description of the basis for the modification and how the permit is being modified:

10
NEW SC
PTI Nur
FACILIT

FACILITY DESCRIPTION Aluminum Can Coating Facility

Emissions Unit ID: K011 ___
CITY/TWP Whitehouse

Additional Comments:

This administrative PTI modification (originally issued 11/29/2005) is on the request of permittee to re-proportion the gallon restrictions on coatings per rolling 12-month period for K011 - Can manufacturing Line 3. The coatings included in these restrictions are the Inside Spray, Over Varnish, Bottom Varnish, Inks, and Cleaning Solvents. These gallon restrictions on coatings were enacted to limit the tons of VOC per year for K011. This modification will only effect the ratio between the coatings restriction on total gallons per year but will not change the total amount of VOCs allowed for these coatings. The overall amount of VOC allowed on K011 will remain unchanged at 101.15 tons/year. Since there was no change in emissions, no modeling was needed.

The permittee also requested that the percent by weight of solvent, excluding water and exempt solvents, in the ink be reduced from 20% to 14%. This change is based on permittee's data received from supplier on the ink batches permittee had received. This results in a reduction for the ink from 2.59 pounds VOC per gallon of coating excluding water and exempt solvents to 1.81 pounds VOC per gallon.

Gallon Restrictions:

**Inside OverBottomCleaning
SprayVarnishVarnishInksSolvent**

Current Yearly Usage

Restriction in gallons 148,21450,5962,4474,270360

**Resulting VOC emissions
in tons/year 68.2724.211.615.53*1.08**

Proposed Yearly Usage

Restriction in gallons 144,04056,6672,4475,017360

**Resulting VOC emissions
in tons/year 66.3427.121.614.55*1.08**

*** Current VOC emissions for ink based on 20% by weight of solvent while the Proposed VOC emissions are based on 14% by weight of solvent.**

VOC emissions = (gallons of coating)*(density in lbs/gal)*(% by weight of solvent)/(2000 lbs/ton)

**Current Coating VOC emissions = 68.27+24.21+1.61+5.53+1.08 = 100.7 tons/year
Proposed Coating VOC emissions = 66.34+27.12+1.61+4.55+1.08 = 100.7 tons/year
Therefore, total VOC emissions from coatings remains unchanged.**

1 NEW SOURCE REVIEW FORM B

PTI Number: 04-01429

Facility ID: 0448002007

FACILITY NAME Rexam Beverage Can Company

FACILITY DESCRIPTION Aluminum Can Coating Facility

CITY/TWP Whitehouse

Emissions Unit ID: K011

Percent by weight of ink:

VOC emission limitation (excluding water and exempt solvents) on Ink:

VOC Limitation (lbs/gal) = (density in lbs/gal)*(% by weight of solvent)

Current VOC Limitation = (12.96 lbs/gal)*(0.20) = 2.59 lbs/gal

Proposed VOC Limitation = (12.96 lbs/gal)*(0.14) = 1.81 lbs/gal

1 NEW SC

PTI Nun

FACILIT

Emissions Unit ID: K011 _____

FACILITY DESCRIPTION Aluminum Can Coating Facility

CITY/TWP Whitehouse

Ohio EPA Permit to Install Information Form

Please describe below any documentation which is being submitted with this recommendation (must be sent the same day). Electronic items should be submitted with the e-mail transmitting the PTI terms, and in software that CO can utilize. If mailing any hard copy, this section must be printed as a cover page. All items must be clearly labeled indicating the PTI name and number. Submit **hard copy items to Pam McGraner, AQM&P, DAPC, Central Office, and electronic files to airpti@epa.state.oh.us**

Please fill out the following. If the checkbox does not work, replace it with an 'X'

<u>Please fill out the following. If the checkbox does not work, replace it with an 'X'</u>	<u>Electroni c</u>	<u>Additional information File Name Convention (your PTI # plus this letter)</u>	<u>Hard Cop y</u>	<u>Non e</u>
<u>Calculations (required)</u>	<input type="checkbox"/>	000000c.wpd	<input type="checkbox"/>	
<u>Modeling form/results</u>	<input type="checkbox"/>	000000s.wpd	<input type="checkbox"/>	<input type="checkbox"/>
<u>PTI Application (complete or partial)*</u>	<input type="checkbox"/>	000000a.wpd	<input type="checkbox"/>	<input type="checkbox"/>
<u>BAT Study</u>	<input type="checkbox"/>	000000b.wpd	<input type="checkbox"/>	<input type="checkbox"/>
<u>Other/misc.</u>	<input type="checkbox"/>	000000t.wpd	<input type="checkbox"/>	<input type="checkbox"/>

* Mandatory for netting, PSD, nonattainment NSR, 112(g), 21-07(G)(9)(g) and 21-09(U)(2)(f) - 2 complete copies.

Please complete (see comment bubble to the left for additional instructions):

NSR Discussion

This facility is an aluminum can coating facility. The facility currently operates 3 different coating lines identified as Line 1, Line 2, and Line 3. Line 1 consists of an interior body coater (line 1 can body sprayers), a continuous motion printer (line 1 deco & over varnish), and a continuous motion coater (line 1 base coating line). Line 2 consists of an interior body coater (line 2 can body sprayers), a continuous motion printer (line 2 deco & over varnish), and a continuous motion coater and coater pin oven (line 2 base coating line). Line 3 consists of a continuous motion printer (line 3 deco & over varnish) and an interior body coater (line 3 can body sprayer).

This administrative PTI modification (originally issued 11/29/2005) is on the request of permittee to re-proportion the gallon restrictions on coatings per rolling 12-month period for K011 - Can manufacturing Line 3. The coatings included in these restrictions are the Inside Spray, Over Varnish, Bottom Varnish, Inks, and Cleaning Solvents. These gallon restrictions on coatings were enacted to limit the tons of VOC per year for K011. This modification will only effect the ratio between the coatings restriction on total gallons per year but will not change the total amount of VOCs allowed for these coatings. The overall amount of VOC allowed on K011 will remain unchanged at 101.15 tons/year. Since there was no change in emissions, no modeling was needed.

NEW SOURCE REVIEW FORM B

PTI Number: 04-01429

Facility ID: 0448002007

FACILITY NAME Rexam Beverage Can CompanyFACILITY DESCRIPTION Aluminum Can Coating FacilityCITY/TWP Whitehouse

Emissions Unit ID: K011

The permittee also requested that the percent by weight of solvent, excluding water and exempt solvents, in the ink be reduced from 20% to 14%. This change is based on permittee's data received from supplier on the ink batches permittee had received. This results in a reduction for the ink from 2.59 pounds VOC per gallon of coating excluding water and exempt solvents to 1.81 pounds VOC per gallon.

Gallon Restrictions:

	<u>Inside Spray</u>	<u>Over Varnish</u>	<u>Bottom Inks</u>	<u>Cleaning Solvent</u>
Current Yearly Usage Restriction in gallons	148,214	50,596	2,447 4,270	360
Resulting VOC emissions in tons/year	68.27	24.21	1.61 5.53*	1.08
Proposed Yearly Usage Restriction in gallons	144,040	56,667	2,447 5,017	360
Resulting VOC emissions in tons/year	66.34	27.12	1.61 4.55*	1.08

* Current VOC emissions for ink based on 20% by weight of solvent while the Proposed VOC emissions are based on 14% by weight of solvent.

VOC emissions = (gallons of coating)*(density in lbs/gal)*(% by weight of solvent)/(2000 lbs/ton)

Current Coating VOC emissions = 68.27+24.21+1.61+5.53+1.08 = 100.7 tons/year

Proposed Coating VOC emissions = 66.34+27.12+1.61+4.55+1.08 = 100.7 tons/year

Therefore, total VOC emissions from coatings remains unchanged.

Percent by weight of ink:

VOC emission limitation (excluding water and exempt solvents) on Ink:

VOC Limitation (lbs/gal) = (density in lbs/gal)*(% by weight of solvent)

Current VOC Limitation = (12.96 lbs/gal)*(0.20) = 2.59 lbs/gal

Proposed VOC Limitation = (12.96 lbs/gal)*(0.14) = 1.81 lbs/gal

Please complete for these type permits ([For PSD/NSR Permit, place mouse over this text](#)):

Synthetic Minor Determination and/or Netting Determination

Permit To Install 04-01429

NEW SOURCE REVIEW FORM B

PTI Number: 04-01429

Facility ID: 0448002007

FACILITY NAME **Rexam Beverage Can Company**

FACILITY DESCRIPTION **Aluminum Can Coating Facility**

CITY/TWP **Whitehouse**

Emissions Unit ID: K011

PLEASE PROVIDE ADDITIONAL NOTES OR COMMENTS AS NECESSARY:

Description:

Applicable Regulations:

- OAC rule 3745-18-06(C) 0.5 pounds SO2/mmBtu actual heat input
- OAC rule 3745-21-08(B) Rescinded 11/5/02
- OAC rule 3745-21-09(D)(1) 2.8 pounds of VOC per gallon of coating, excluding water and exempt solvents for basecoat coating line and over varnish coating line
- OAC rule 3745-23-06(B) Rescinded 2/15/05
- OAC rule 3745-31-02(A)(2) HAPs emissions shall not exceed 9.9 TPY for any single HAP or 24.9 TPY total HAPs emissions
- OAC rule 3745-31-05(A)(3) Best available technology - use of waterborne, low solvent coatings
- 40 CFR 60 Subpart WW 0.29 kilogram of VOC per liter of coating solids or 2.42 pounds of VOC per gallon of coating solids.
- 40 CFR Part 63, Subpart KKKK Not applicable

Fees

- Permit modification of coating operation with a process weight rate 0 - 1,000 lbs/hr:
- K009 no modification \$0
- K010 no modification \$0
- K011 \$200/2 = \$100
- total \$100

Please complete:

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
------------------	----------------------

1 NEW SC
PTI Nun
FACILIT

Emissions Unit ID: K011

FACILITY DESCRIPTION Aluminum Can Coating Facility CITY/TWP Whitehouse

<u>HAPs</u>	
any one HAP	9.9 (no change)
total, combined facility HAP	24.9 (no change)
CO (Line 2 base coater w/pin oven and Line 3)	4.68 (no change)
NOx (Line 2 base coater w/pin oven and Line 3)	5.57 (no change)
PE (Line 2 base coater w/pin oven and Line 3)	2.33 (no change)
PM10 (Line 2 base coater w/pin oven and Line 3)	2.62 (no change)
SO2 (Line 2 base coater w/pin oven and Line 3)	0.20 (no change)
VOC (from PTI 04-01379, Title V Permit)	417.85 (no change)