



State of Ohio Environmental Protection Agency

Street Address:

Mailing Address:

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Lazarus Gov.
Center

RE: **FINAL PERMIT TO INSTALL MODIFICATION** CERTIFIED MAIL
LUCAS COUNTY
Application No: 04-01102

DATE: 9/8/2005

DaimlerChrysler Corp
Roger Brown
CIMS 516-04-31 4400 Chrysler Drive
Toledo, OH 43608

Enclosed Please find a modification to the Ohio EPA Permit To Install referenced above which will modify the terms and conditions.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, Ohio 43215

Sincerely,

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

cc: USEPA

TDES



**Permit To Install
Terms and Conditions**

**Issue Date: 9/8/2005
Effective Date: 9/8/2005**

FINAL ADMINISTRATIVE MODIFICATION OF PERMIT TO INSTALL 04-01102

Application Number: **04-01102**
APS Premise Number: **0448010414**
Permit Fee: **\$3550**
Name of Facility: **DaimlerChrysler Corp Brown**
Person to Contact: **Roger**
Address: **CIMS 516-04-31 4400 Chrysler Drive
Toledo, OH 43608**

Location of proposed air contaminant source(s) [emissions unit(s)]:
**4400 Chrysler Dr
Toledo, OHIO**

Description of modification:
Modification in support of 2007 and 2008 model year vehicles and revision of emission factors for natural gas fired space heaters.

The above named entity is hereby granted a modification to the permit to install described above pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this modification does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described source(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans included in the application, the above described source(s) of pollutants will be granted the necessary operating permits.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

GENERAL PERMIT CONDITIONS

TERMINATION OF PERMIT TO INSTALL

Substantial construction for installation must take place within 18 months of the effective date of this permit. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

NOTICE OF INSPECTION

The Director of the Ohio Environmental Protection Agency, or his authorized representatives, may enter upon the premises of the above-named applicant during construction and operation at any reasonable time for the purpose of making inspections, conducting tests, or to examine records or reports pertaining to the construction, modification or installation of the source(s) of environmental pollutants identified within this permit.

CONSTRUCTION OF NEW SOURCES

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

PERMIT TO INSTALL FEE

In accordance with Ohio Revised Code 3745.11, the specified Permit to Install fee must be remitted within 30 days of the effective date of this permit to install.

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

PUBLIC DISCLOSURE

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC Rule 3745-49-03.

APPLICABILITY

This Permit to Install is applicable only to the contaminant sources identified. Separate application must be made to the Director for the installation or modification of any other contaminant sources.

BEST AVAILABLE TECHNOLOGY

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

SOURCE OPERATION AND OPERATING PERMIT REQUIREMENTS AFTER COMPLETION OF CONSTRUCTION

If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).

If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35, the source(s) identified in this Permit To Install is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the source(s) covered by this permit.

5

DaimlerChrysler Corp

PTI Application: 04-01102

Modification Issued: 9/8/2005

Facility ID: **0448010414**

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

Ohio EPA Source <u>Number</u>	Source Identification <u>Number</u>	BAT <u>Determination</u>	Applicable Federal & OAC Rules	Permit Allowable Mass Emissions and/or Control/Usage <u>Requirements</u>
--	---	-----------------------------	-----------------------------------	---

AIR EMISSION SUMMARY

The air contaminant emissions units listed below comprise the Permit to Install for **DaimlerChrysler Corp.** located in **Lucas** County. The emissions units listed below shall not exceed the emission limits/control requirements contained in the table. This condition in no way limits the applicability of any other state or federal regulations. Additionally, this condition does not limit the applicability of additional special terms and conditions of this permit.

Ohio EPA
Source
Number

B008

B011

B008
Cont'd

B009

B009
Cont'd

B012

B010

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
---	---	------------------------------	---	--

B013	B015	B017	B019	B021
------	------	------	------	------

B014	B016	B018	B020	B022
------	------	------	------	------

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
---	---	------------------------------	---	--

G003

B023

B025

B027

K021

K022

B024

B026

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
---	---	------------------------------	---	--

K027

P007

K024

P008

K029

K023

P009

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
	P012			<u>Source Identification Description</u> 32.66 MMBtu/hour natural gas boiler
		B029		
	F001		B031	
	P011			
	B028			
		B030		

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
12.02 MMBtu/hour air makeup unit, BC ASH 6	12.02 MMBtu/hour air makeup unit, CC ASH 7	13.53 MMBtu/hour air makeup unit, CC ASH 9	15.03 MMBtu/hour air makeup unit, CC ASH 15	15.03 MMBtu/hour air makeup unit, Misc No. 1 (F1)
13.53 MMBtu/hour air makeup unit, BC ASH 13	10.52 MMBtu/hour air makeup unit, CC ASH 8	10.52 MMBtu/hour air makeup unit, CC ASH 14	15.03 MMBtu/hour air makeup unit, CC ASH 16	13.53 MMBtu/hour air makeup unit, Misc No. 2 (E1)

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u> Fill Stations	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u> MMBtu/hr each
-------------------------------	--	--------------------------	---	---

13.53 E-Coat with 26.0
 MMBtu/hr indirect
 ur fired, natural gas
 air makeup drying oven
 unit, Misc
 No. 8 (D)

Powder anti-chip with 35.8
 MMBtu/hr natural gas-fired
 curing oven

Topcoat with (2) natural
 gas infrared flash tunnels
 and (2) indirect fired,
 drying ovens at 22.2

Gasoline

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
		Non-production maintenance materials, spray booth and purge	Miscellaneous solvents, plantwide use of photo-chemically reactive solvents	
Low bake repair with Spovens (combination spray booth and electric oven)		Sealers and adhesives	BIW Inspection and Grinding	Roadways and parking areas
	Interior touchup			12.02 MMBtu/hour natural gas, direct fired air makeup unit, ASH E
Blackout		Miscellaneous solvents, solvent body wipes and use of other non-photo-	Finish welding	

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
	air space heater, ASH G	<u>BAT Determination</u>		
16.53 MMBtu/hour natural gas, direct fired air space heater, ASH F		Exclusive combustion of natural gas and low NO _x burners.	Exclusive combustion of natural gas and low NO _x burners.	
	12.02 MMBtu/hour natural gas, direct fired air space heater, ASH G			Exclusive combustion of natural gas and low NO _x burners.
11.03 MMBtu/hour natural gas, direct-fired				

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
Exclusive combustion of natural gas and emissions levels equivalent to FIRE emission factors.	Exclusive combustion of natural gas and emissions levels equivalent to FIRE emission factors.	Exclusive combustion of natural gas and emissions levels equivalent to FIRE emission factors.	Exclusive combustion of natural gas and emissions levels equivalent to FIRE emission factors.	
Exclusive combustion of natural gas and emissions levels equivalent to FIRE emission factors.	Exclusive combustion of natural gas and emissions levels equivalent to FIRE emission factors.	Exclusive combustion of natural gas and emissions levels equivalent to FIRE emission factors.	Exclusive combustion of natural gas and emissions levels equivalent to FIRE emission factors.	Exclusive combustion of natural gas and emissions levels equivalent to FIRE emission factors.

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
Exclusive combustion of natural gas and emissions levels equivalent to FIRE emission factors.	Exclusive combustion of natural gas and emissions levels equivalent to FIRE emission factors.	combustion of natural gas and emissions levels equivalent to FIRE emission factors.	Exclusive combustion of natural gas and emissions levels equivalent to FIRE emission factors.	Exclusive combustion of natural gas and emissions levels equivalent to FIRE emission factors.
Exclusive combustion of natural gas and emissions levels equivalent to FIRE emission factors.	Exclusive	Exclusive combustion of natural gas and emissions levels equivalent to FIRE emission factors.	Exclusive combustion of natural gas and emissions levels equivalent to FIRE emission factors.	Stage I and II submerged fill for the storage tanks. Compliance with the Ohio EPA Air Toxics Policy

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
5 percent opacity, particulate filtration Use of low VOC coatings. Compliance with the Ohio EPA Air Toxics Policy	Compliance coatings, adequate enclosure and control, 5 percent opacity. Compliance with the Ohio EPA Air Toxics Policy.	Non-photochemically reactive low VOC materials, proper dispenser and disposal container design. Compliance with the Ohio EPA Air Toxics Policy.	Adequate enclosure and control, 20 percent opacity.	Paving, sweeping and adequate moisture; no visible emissions except: paved - 1 minute per hour, covered vehicles, clean up of spilled material.
Low VOC materials, proper dispenser and disposal container design. Compliance with the Ohio EPA Air Toxics Policy	Low VOC materials, proper dispenser and disposal container design. Compliance with the Ohio EPA Air Toxics Policy.	Non-photochemically reactive low VOC materials, proper dispenser and disposal container design. Compliance with the Ohio EPA Air Toxics Policy.	Adequate enclosure and control, 20 percent opacity	Exclusive combustion of natural gas and emission levels equivalent to FIRE emission factors
	Compliance with the Ohio EPA Air Toxics Policy	8 pounds of VOC per hour and 40 pounds of VOC per day, proper dispenser and disposal container design. Compliance with the Ohio EPA Air Toxics Policy.		

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

Ohio EPA Source Number	Source Identification Number	BAT Determination	Applicable Federal & OAC Rules	Permit Allowable Mass Emissions and/or Control/Usage Requirements
Exclusive combustion of natural gas and emission levels equivalent to FIRE emission factors	Exclusive combustion of natural gas and emission levels equivalent to FIRE emission factors	Applicable Federal & OAC Rules	345-31-10 thru 20, and 40 CFR Part 52.21	345-31-10 thru 20, and 40 CFR Part 52.21
		40 CFR Part 60, Subpart Dc	40 CFR Part 63, Subparts A and DDDDD	40 CFR Part 63, Subparts A and DDDDD
		3745-17-07(A)	40 CFR Part 60, Subpart Dc	40 CFR Part 60, Subpart Dc
		3745-17-10 (B)(1)* 3745-18-06(A) and (D) 3745-21-08 (B) 3745-23-06 (B)	3745-17-07(A)	3745-17-07(A)*
		3745-31-05	3745-17-10 (B)(1)* 3745-18-06(A) and (D) 3745-21-08 (B) 3745-23-06 (B)	3745-17-10 (B)(1)* 3745-18-06(A) and (D) 3745-21-08 (B) 3745-23-06 (B)
			3745-31-05	3745-31-05
Exclusive combustion of natural gas and emission levels equivalent to FIRE emission factors				

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
	(A) and (B)	3745-21-08(B)	3745-21-08(B)	3745-21-08(B)
345-31-10 thru 20, and 40 CFR Part 52.21	3745-21-08(B) 3745-23-06(B) 3745-31-05	3745-23-06(B) 3745-31-05	3745-23-06(B) 3745-31-05	3745-23-06(B) 3745-31-05
40 CFR Part 63, Subparts A and DDDDD				
		3745-31-10 thru 20 and 40 CFR Part 52.21	3745-31-10 thru 20 and 40 CFR Part 52.21	3745-31-10 thru 20 and 40 CFR Part 52.21
3745-18-06 (A) and (B) thru 20 and 40 CFR Part 52.21	3745-31-10	3745-18-06 (A) and (B)	3745-18-06 (A) and (B)	3745-18-06 (A) and (B)
3745-21-08 (B)		3745-21-08 (B)	3745-21-08(B)	3745-21-08(B)
3745-23-06 (B)	3745-18-06 (A) and (B)	3745-23-06 (B)	3745-23-06(B)	3745-23-06(B)
3745-31-05	3745-21-08(B) 3745-23-06(B) 3745-31-05	3745-31-05	3745-31-05	3745-31-05
		3745-31-10 thru 20 and 40 CFR Part 52.21	3745-31-10 thru 20 and 40 CFR Part 52.21	3745-31-10 thru 20 and 40 CFR Part 52.21
3745-31-10 thru 20 and 40 CFR Part 52.21	3745-31-10	3745-18-06 (A) and (B)	3745-18-06 (A) and (B)	3745-18-06 (A) and (B)

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: 0448010414

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
3745-21-08 (B)	40 CFR Part 52.21	3745-31-10 thru 20, and 40 CFR Part 52.21	3745-31-10 thru 20, and 40 CFR Part 52.21	3745-31-10 thru 20 and 40 CFR Part 52.21
3745-23-06 (B)	3745-18-06 (A) and (B)	3745-18-06 (A) and (B)	3745-18-06 (A) and (B)	3745-21-09(R)
3745-31-05	3745-21-08(B) 3745-23-06(B) 3745-31-05	3745-21-08(B) 3745-23-06(B) 3745-31-05	3745-21-08(B) 3745-23-06(B) 3745-31-05	3745-21-09(DDD)(4)(c) 3745-31-05
3745-31-10 thru 20, and 40 CFR Part 52.21	3745-31-10 thru 20, and 40 CFR Part 52.21	3745-31-10 thru 20, and 40 CFR Part 52.21	3745-31-10 thru 20, and 40 CFR Part 52.21	3745-31-10 thru 20 and 40 CFR Part 52.21
3745-18-06 (A) and (B)	3745-18-06 (A) and (B)	3745-18-06 (A) and (B)	3745-18-06 (A) and (B)*	COATING: 40 CFR Part 60 Subpart MM*
3745-21-08 (B)	3745-21-08(B) 3745-23-06(B) 3745-31-05	3745-21-08(B) 3745-23-06(B) 3745-31-05	3745-21-08(B) 3745-23-06(B) 3745-31-05	3745-21-09 (B)(1) and (3)(j)* 3745-21-09 (C)(1)(a)(ii)-(iv)* 3745-31-05
3745-31-10 thru 20, and				

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
3745-31-10	40 CFR Part 63, thru 20, and Subparts A, III, and 40 CFR Part 52.21	3745-31-10 thru 20, and 40 CFR Part 52.21	3745-21-08(B) 3745-23-06(B) 3745-31-05	40 CFR Part 63, Subpart A and III
3745-17-07 (A)(1)*	COATING: 40 CFR Part 60 Subpart MM* 3745-21-09	40 CFR Part 63, Subparts A, III, and DDDDD		3745-17-07(A)(1)* 3745-17-11(A)(2) 3745-21-09 (B)(1) and (3)(f) and (g)
3745-17-10 (B)(1) and (3)(j)*	3745-21-09(C)(1)(a)			3745-21-09(U)(1)(i)*
3745-18-06 (v)*	COATING: 40 CFR Part 60 Subpart MM* 3745-31-05			3745-31-05
3745-21-08 (B)	3745-31-10			
3745-23-06 thru 20, and (A) and B)	40 CFR Part 52.21			
3745-17-07 (A)(1)*	OVEN: 3745-17-07(A)(1)* 3745-17-10(B)(1)* 3745-18-06(A) 3745-21-08(B)* 3745-23-06(A) and (B)* 3745-31-05	3745-17-07(A)(1)* 3745-17-11(A)(2)* 3745-21-09 (B)(1) and (3)(j)* 3745-21-09(C)(1)(c)* 3745-31-05	3745-31-10 thru 20 and 40 CFR Part 52.21	3745-31-10 thru 20, and 40 CFR Part 52.21
3745-17-07 (A)(1)			3745-17-07(A)(1) 3745-17-11(A)(2) 3745-21-09 (B)(1) and (3)(f) and (g) 3745-21-09(C)(1)(d)*	40 CFR Part 63, Subparts A and III
3745-31-10 thru 20, and 40 CFR Part 52.21		3745-31-10 thru 20, and 40 CFR Part 52.21	3745-31-05	3745-17-08(B)(3) 3745-21-09* (B)(1) and (B) (3) (a), (f) & (g) or (h) & (i) 3745-21-09(C)(1)(d)
3745-17-07 (A)(1)*		3745-17-07 (A)(1)*	3745-31-10 thru 20, and 40 CFR Part 52.21	
3745-17-10 (B)(1)*		3745-17-10 (B)(1)*		
3745-18-06(A)		3745-18-06(A)		

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
3745-31-05	40 CFR Part 52.21	3745-31-05	(B)(8), (B)(9)*	
3745-31-10 thru 20, and 40 CFR Part 52.21	40 CFR Part 63, Subparts A and III	3745-31-10 thru 20, and 40 CFR Part 52.21	OAC rule 3745-18-06 (A) and (B) OAC rule 3745-21-08 (B)	3745-31-10 thru 20, and 40 CFR Part 52.21
40 CFR Part 63, Subparts A and III	3745-21-07(G)(9)(f) 3745-31-05	40 CFR Part 63, Subparts A and III 3745-17-07(B)(1)	OAC rule 3745-23-06 (B) OAC rule 3745-31-05(A)(3)	OAC rule 3745-18-06 (A) and (B) OAC rule 3745-21-08 (B) OAC rule 3745-23-06 (B)
3745-31-05	3745-31-10 thru 20, and 40 CFR Part 52.21	3745-17-08(B)(3) 3745-31-05		OAC rule 3745-31-05(A)(3)
3745-31-10	40 CFR Part 63, Subparts A and III			
40 CFR Part 52.21	3745-21-07(G)(2)	3745-31-10 thru 20, and 40 CFR Part 52.21	3745-31-10 thru 20, and 40 CFR Part 52.21	
40 CFR Part 63, Subparts A and III	3745-31-05	40 CFR Part 63, Subparts A and III	OAC rule 3745-18-06 (A) and (B) OAC rule 3745-21-08 (B)	3745-31-10 thru 20, and 40 CFR Part 52.21
3745-21-07(G)(9)(f)	3745-31-10 thru 20, and 40 CFR Part 52.21	3745-31-05	OAC rule 3745-23-06 (B) OAC rule 3745-31-05(A)(3)	OAC rule 3745-18-06 (A) and (B) OAC rule 3745-21-08 (B)
3745-31-05	40 CFR Part 63, Subpart A and III	3745-17-07(B)(1)		OAC rule 3745-23-06 (B)
3745-31-10		3745-17-08 (B), (B)(7),		OAC rule 3745-31-05(A)(3)

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
	Permit Allowable Mass Emissions and/or Control/Usage Requirements	See II.	7.0 tons NO _x /year, 0.81 tons PM ₁₀ /year, 0.09 ton SO ₂ /year, and 0.78 ton VOC/year. See II.	0.81 tons PM ₁₀ /year, 0.09 ton SO ₂ /year, and 0.78 ton VOC/year. See II.
	See II.B.2.			
3745-31-10 thru 20, and 40 CFR Part 52.21		See I.A.3.	See I.A.3.	See I.A.3.
		See II.B.2.	See II.B.2.	See XVII.A
	see II.A.1.		see II.A.1.	0.02 pound CO/MMBTU actual heat input.
	See II.A.2.** Gas: 0.083 pound CO/MMBTU, 0.049 pound NO _x /MMBTu,** 0.0056 pound PM ₁₀ /MMBTU,** 0.0006 pound SO ₂ /MMBTU, 0.0054 pound VOC/MMBTu** and 5 percent opacity. 11.9 tons CO/year, 7.0 tons NO _x /year, 0.81 tons PM ₁₀ /year, 0.09 ton SO ₂ /year, and 0.78 ton VOC/year.	see II.A.1. See II.A.2.** Gas: 0.083 pound CO/MMBTU, 0.049 pound NO _x /MMBTu,** 0.0056 pound PM ₁₀ /MMBTU,** 0.0006 pound SO ₂ /MMBTU, 0.0054 pound VOC/MMBTu** and 5 percent opacity. 11.9 tons CO/year, 7.0 tons NO _x /year, 0.81 tons PM ₁₀ /year, 0.09 ton SO ₂ /year, and 0.78 ton VOC/year.	See II.A.2.** 0.083 pound CO/MMBTU, 0.049 pound NO _x /MMBTu,** 0.0056 pound PM ₁₀ /MMBTU,** 0.0006 pound SO ₂ /MMBTU, 0.0054 pound VOC/MMBTu** and 5 percent opacity. 11.9 tons CO/year, 7.0 tons NO _x /year,	0.1 pound NO _x /MMBTU actual heat input**. 0.0052 pound VOC/MMBTu actual heat input**. 1.1 tons CO/year 5.3 tons NO _x /year 0.28 ton VOC/year See XVII. See XVII.A. 0.02 pound CO/MMBTU actual heat input.

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
0.1 pound NO _x /MMBTU actual heat input**. 0.0052 pound VOC/MMBTU actual heat input**. 1.4 tons CO/year	heat input**. 1.4 tons CO/year 6.6 tons NO _x /year 0.35 ton VOC/year See XVII.	heat input**. 0.0052 pound VOC/MMBTU actual heat input**. 1.4 tons CO/year 6.6 tons NO _x /year 0.35 ton VOC/year See XVII.	heat input**. 0.0052 pound VOC/MMBTU actual heat input**. 1.1 tons CO/year 5.3 tons NO _x /year 0.28 ton VOC/year See XVII.	input. 0.1 pound NO _x /MMBTU actual heat input**. 0.0052 pound VOC/MMBTU actual heat input**. 1.1 tons CO/year 5.3 tons NO _x /year 0.28 ton VOC/year See XVII.
0.02 pound CO/MMBTU actual heat input. 0.1 pound NO _x /MMBTU actual heat input. 0.0052 pound VOC/MMBTU actual heat input. 1.1 tons CO/year 5.3 tons NO _x /year 0.28 ton VOC/year See XVII.	See XVII.A. 0.02 pound CO/MMBTU actual heat input. 0.1 pound NO _x /MMBTU actual heat input**. 0.0052 pound VOC/MMBTU actual heat input**. 1.1 tons CO/year 5.3 tons NO _x /year 0.28 ton VOC/year See XVII.	See XVII.A. 0.02 pound CO/MMBTU actual heat input. 0.1 pound NO _x /MMBTU actual heat input**. 0.0052 pound VOC/MMBTU actual heat input**. 1.1 tons CO/year 5.3 tons NO _x /year 0.28 ton VOC/year See XVII.	See XVII.A. 0.02 pound CO/MMBTU actual heat input. 0.1 pound NO _x /MMBTU actual heat input**. 0.0052 pound VOC/MMBTU actual heat input**. 1.2 tons CO/year 6.0 tons NO _x /year 0.51 ton VOC/year See XVII.	See XVII.A. 0.02 pound CO/MMBTU actual heat input. 0.1 pound NO _x /MMBTU actual heat input**. 0.0052 pound VOC/MMBTU actual heat input**. 0.93 tons CO/year 4.6 tons NO _x /year 0.24 ton VOC/year See XVII.
0.02 pound CO/MMBTU actual heat input. 0.1 pound NO _x /MMBTU actual heat input. 0.0052 pound VOC/MMBTU actual heat input. 0.1 pound NO _x /MMBTU actual heat input.	See XVII.A. 0.02 pound CO/MMBTU actual heat input. 0.1 pound NO _x /MMBTU actual heat input. 0.0052 pound VOC/MMBTU actual heat input.	See XVII.A. 0.02 pound CO/MMBTU actual heat input. 0.1 pound NO _x /MMBTU actual heat input. 0.0052 pound VOC/MMBTU actual heat input.	See XVII.A. 0.02 pound CO/MMBTU actual heat input. 0.1 pound NO _x /MMBTU actual heat input. 0.0052 pound VOC/MMBTU actual heat input.	See XVII.A. 0.02 pound CO/MMBTU actual heat input. 0.1 pound NO _x /MMBTU actual heat input. 0.0052 pound VOC/MMBTU actual heat input.

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: 0448010414

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
0.1 pound NO _x /MMBTU actual heat input**.	VOC/MMBTu actual heat input**.	0.002 pound CO/MMBTU actual heat input.	actual heat input.	See III.A.1.**
TU actual heat input**.	0.93 ton CO/year	0.1 pound NO _x /MMBTU actual heat input**.	NO _x /MMBTU actual heat input**.	See III.D.2.g.
0.0052 pound VOC/MMBTU actual heat input**.	4.6 tons NO _x /year	0.0052 pound VOC/MMBTu actual heat input**.	0.0052 pound VOC/MMBTu actual heat input**.	See III.A.4.**
1.2 tons CO/year	0.24 ton VOC/year	1.4 tons CO/year	1.2 tons CO/year	34 tons VOC/year,
6.0 tons NO _x /year	See XVII.	6.6 tons NO _x /year	6.0 tons NO _x /year	See III.
0.31 ton VOC/year	See XVII.A.	0.35 ton VOC/year	0.31 ton VOC/year	
See XVII.	0.002 pound CO/MMBTU actual heat input.	See XVII.A.	See XVII.A.	
See XVII.A.	0.1 pound NO _x /MMBTU actual heat input**.	0.02 pound CO/MMBTU actual heat input.	0.002 pound CO/MMBTU actual heat input.	0.23 pound of VOC per gallon of applied coating solids**.
	0.0052 pound VOC/MMBTu actual heat input**.	0.0052 pound VOC/MMBTu actual heat input**.	0.0052 pound VOC/MMBTu actual heat input**.	See IV.A.1. and 2.**
	1.4 tons CO/year	1.4 tons CO/year	1.4 tons CO/year	52.01 tons VOC/year,
	6.6 tons NO _x /year	6.6 tons NO _x /year	6.6 tons NO _x /year	5 percent opacity,
	0.35 ton VOC/year	0.35 ton VOC/year	0.35 ton VOC/year	See IV.
0.02 pound CO/MMBTU actual heat input.	See XVII.	See XVII.	See XVII.	
0.1 pound NO _x /MMBTU actual heat input**.	See XVII.A.	See XVII.A.	See XVII.A.	
0.0052 pound		0.02 pound CO/MMBTU		See IV.A.3.

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
CO - 0.083 pound/MM BTU and 9.5 tons/year, NO _x - 0.100 pound/MM BTU** and 11.4 tons/year, PM ₁₀ - 0.0056 pound/MM Btu** and 0.64 ton/year, SO ₂ - 0.0006 pound/MM Btu and 0.068 ton/year, VOC - 0.0054 pound/MM Btu** and 0.62 ton/year, 5 percent opacity, See IV.	1.40 kg VOC/l (11.7 pounds VOC/gal) of applied coating solids**. see V.A. 2. 3.25 tons VOC per rolling 12-month period** See V.A. 1. CO - 0.083 pound/MMBtu and 12.9 tons/year, NO _x - 0.100 pound/MMBtu** and 15.5 tons/year, PM ₁₀ - 0.0056 pound/MMBtu** and 0.87 ton/year, SO ₂ - 0.0006 pound/MMBTU and 0.093 ton/year, VOC - 0.0054 pound/MMBTU** and 0.84 ton/year, 5 percent opacity, See V.	See I.A.3. 8.63 pounds VOC per gallon of applied coating solids**, See VI.A.1. and 2. 768.68 tons VOC/year, 15.3 pounds PM ₁₀ /hour**, and 66.9 tons PM ₁₀ /year, 5 percent opacity. See VI. See I.A.3. See VI.A.3.	CO - 0.083 pound/MMBtu and 16.2 tons/year, NO _x - 0.100 pound/MMBtu** and 19.5 tons/year, PM ₁₀ - 0.0056 pound/MMBtu** and 1.1 tons/year, SO ₂ - 0.0006 pound/MMBtu and 0.12 ton/year, VOC - 0.0054 pound/MMBtu** and 1.1 tons/year, 5 percent opacity, See VI. 0.551 pound PM ₁₀ /hour**, 4.8 pounds of VOC per gallon of coating, excluding water and exempt solvents**, 28 tons VOC/year, 2.4 tons PM ₁₀ /year, 5 percent opacity See VII.	See I.A.3. 0.63 pound PM ₁₀ /hour** 2.0 pounds of VOC per gallon of coating excluding water and exempt solvents**, 54 tons VOC/year, 2.8 tons PM ₁₀ /year, 5 percent opacity. See X. See I.A.3. See XII.A. 4.8 pounds of VOC per gallon of coating excluding water and exempt solvents**

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
5.6 tons VOC/year, See XII.	VOC/year, See XIV.	See I.A.3.	1.4 tons PM ₁₀ /year.	CO/MMBTU actual heat input. 0.1 pound NO _x /MMBTU actual heat input**.
		See XVIII.A.1.		0.0052 pound VOC/MMBtu actual heat input**.
		See XVIII.A.2.		1.45 tons CO/year 7.24 tons NO _x /year 0.38 ton VOC/year
See I.A.3.	See I.A.3.	0.48 pound PM ₁₀ /hour**, 2.1 tons PM ₁₀ /year.	See XVII.A.	See XVII.
See XIII.A.2.**	See XV.A.1.			
514.18 tons VOC per rolling 12-month period**, See XIII.	See XV.A.3.** 52.28 tons VOC per rolling 12-month period**, See XV.	See I.A.3.		See XVII.A.
		See XIX.A.1.	0.02 pound CO/MMBTU actual heat input. 0.1 pound NO _x /MMBTU actual heat input**.	
		See XIX.A.2.	0.0052 pound VOC/MMBtu actual heat input**.	0.02 pound CO/MMBTU actual heat input.
See I.A.3.	See I.A.3.	0.56 pound PM ₁₀ /hour**, 2.4 tons PM ₁₀ /year.	1.06 tons CO/year 5.27 tons NO _x /year 0.28 ton VOC/year See XVII	0.1 pound NO _x /MMBTU actual heat input**. 0.0052 pound VOC/MMBtu actual heat input**.
See XIV.A.1.	8 pounds of VOC per hour and 40 pounds of VOC per day**, 5.1 tons VOC/year. See XVI.	See XIX.		0.97 ton CO/year 4.84 tons NO _x /year 0.26 ton VOC/year See XVII.
0.5 pound VOC/gallon excluding water and exempt solvents as a monthly average**, 55.06 tons		See I.A.3.	See XVII.A.	
		See XX.B.1 .		See XVII.A
		0.32 pound PM ₁₀ /hour.	0.02 pound	

DaimlerChrysler Corp
 PTI Application: 04-01102
 Modification Issued: 9/8/2005

Facility ID: 0448010414

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
-------------------------------	-------------------------------------	--------------------------	---	--

0.02 pound
 CO/MMBT
 U actual
 heat input.
 0.1 pound
 NO_x/MMB
 TU actual
 heat
 input**.
 0.0052
 pound
 VOC/MMB
 tu actual
 heat
 input**.
 1.06 tons
 CO/year
 5.27 tons
 NO_x/year
 0.28 ton
 VOC/year
 See XVII.

* This applicable rule is less stringent than the rule that resulted in the emission limitation.

** This is a federally enforceable BACT limitation. The State BAT limitation is equivalent to this value.

SUMMARY TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons/Year</u>
VOC	1583.68
Particulate/PM ₁₀	83.04
NO _x	189.32
CO	99.4
SO ₂	0.55

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

NSPS REQUIREMENTS

The following sources are subject to the applicable provisions of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60.

<u>Source Number</u>	<u>Source Description</u>	<u>NSPS Regulation (Subpart)</u>
K021	EDP prime coat operation	MM
K022	Powder anti-chip (guidecoat) operation	MM
K023	Topcoat operation	MM
B008	Energy center boiler	Dc
B009	Energy center boiler	Dc
B010	Energy center boiler	Dc

The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

Pursuant to the NSPS, the source owner/operator is hereby advised of the requirement to report the following at the appropriate times:

- a. construction date (no later than 30 days after such date);
- b. anticipated start-up date (not more than 60 days or less than 30 days prior to such date);
- c. actual start-up date (within 15 days after such date); and
- d. date of performance testing (If required, at least 30 days prior to testing).

Reports are to be sent to:

Ohio Environmental Protection Agency
DAPC - Permit Management Unit
P.O. Box 163669
Columbus, OH 43216-3669

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

and **Toledo Division of Environmental Services**
348 South Erie Street
Toledo, OH 43602

PSD REQUIREMENTS

The source described in this Permit to Install is subject to the applicable provisions of the Prevention of Significant Deterioration (PSD) regulations as promulgated by the United States Environmental Protection Agency 40 CFR 52.21. The authority to apply and enforce the PSD regulations has been delegated to the Ohio Environmental Protection Agency. The terms and conditions of this permit and the requirements of the PSD regulations are also enforceable by the United States Environmental Protection Agency.

In accordance with 40 CFR 124.15, 124.19 and 124.20, the following shall apply: (1) the effective date of this permit shall be 30 days after the service of notice to any public commentors of the final decision to issue, modify, or revoke and re-issue the permit, unless the service of notice is by mail, in which case the effective date of the permit shall be 33 days after the service of notice; and (2) if an appeal is made to the Administrator of the United States Environmental Protection Agency, the effective date of the permit is suspended until such time as the appeal is resolved or denied.

RECORD(S) RETENTION AND AVAILABILITY

All records required by this Permit to Install shall be retained on file for a period of not less than three years unless otherwise indicated by Ohio Environmental Protection Agency. All records shall be made available to the Director, or any representative of the Director, for review during normal business hours.

REPORTING REQUIREMENTS

Unless otherwise specified, reports required by the Permit to Install need only be submitted to **Toledo Division of Environmental Services, 348 South Erie Street, Toledo, OH 43602.**

WASTE DISPOSAL

The owner/operator shall comply with any applicable state and federal requirements governing the storage, treatment, transport and disposal of any waste material generated by the operation of the sources.

MAINTENANCE OF EQUIPMENT

This source and its associated air pollution control system(s) shall be maintained regularly in accordance with good engineering practices and the recommendations of the respective manufacturers in order to minimize air contaminant emissions.

MALFUNCTION/ABATEMENT

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

In accordance with OAC RULE 3745-15-06, any malfunction of the source(s) or associated air pollution control system(s) shall be reported immediately to the **Toledo Division of Environmental Services, 348 South Erie Street, Toledo, OH 43602**.

Except as provided by OAC Rule 3745-15-06(A)(3), scheduled maintenance of air pollution control equipment that requires the shutdown or bypassing of air pollution control system(s) must be accompanied by the shutdown of the associated air pollution sources.

AIR POLLUTION NUISANCES PROHIBITED

The air contaminant source(s) identified in this permit may not cause a public nuisance in violation of OAC Rule 3745-15-07.

NINETY DAY OPERATING PERIOD

The facility will be permitted to operate during a 90-day period in accordance with OAC Rule 3745-35-02(C)(4)(b). The purpose of this period of operation is to fulfill the performance tests conditions used in the determination of compliance with the provisions of this Permit to Install or other applicable Ohio EPA rules.

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

GASOLINE DISPENSING FACILITIES

BAT for any gasoline dispensing operation identified within this permit consists of the use of Stage I vapor balance system. The vapor balance system shall be designed and operated to route at least 90% by weight of the organic compounds in the displaced vapors from the storage tanks to the delivery vessel and shall be equipped with a means to prevent the discharge into the atmosphere of displaced vapors from an unconnected vapor line. This shall be used at all times when filling the tanks.

The transfer of gasoline from a delivery vessel to a stationary storage tank shall be conducted by use of submerged fill into the storage tank. The submerged fill pipe(s) are to be installed so they are within six (6) inches of the bottom of the storage tank.

This facility shall be serviced by a bulk gasoline plant or terminal that is in compliance with OAC Rule 3745-21-09(P) or (Q), respectively.

There shall be no leaks in the vapor and liquid lines during the transfer of gasoline.

All fill caps shall be "in place" and clamped during normal storage conditions.

The gasoline dispensing facility shall repair within 15 days any leaks from the vapor balance system which is employed to meet the requirements of Paragraph (A)(3) of OAC Rule 3745-31-05 or Paragraph (R)(1) of OAC Rule 3745-21-09 when such leaks are equal to or greater than 100% of the lower explosive limit of propane, as determined under Paragraph (K) of OAC Rule 3745-21-10.

CONSTRUCTION COMPLIANCE CERTIFICATION

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

ADDITIONAL SPECIAL TERMS AND CONDITIONS

I. Facility

A. Operational Restrictions

1. These Additional Special Terms and Conditions do not release the owner or operator from meeting other applicable requirements of the appropriate MACT federal standards.
2. The emissions of CO, NO_x, PM₁₀, SO₂ and VOC from this facility shall not exceed 99.4, 189.32, 83.04, 0.55 and 1583.68 tons per year, respectively, as a rolling, 12-month total.

Compliance with the annual emission limitations shall be based upon a rolling, 12-month summation of the monthly emissions.

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

3. The permittee shall comply with all applicable requirements of 40 CFR Part 63, Subparts A, IIII, and DDDDD.
4. Emissions units K025 (underbody deadener), K026(chassis spray), and K028(export coating) were never installed and have been deleted from this PTI.

B. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain monthly records of the:
 - a. usage of each VOC containing material such as paints, solvents, sealers and adhesives;
 - b. VOC content and solids content (as appropriate) of these materials;
 - c. natural gas usage;
 - d. most recent complete and approved testing results of pollution control systems and related factors used in determining emissions; and,
 - e. documentation for determination of emissions of monthly VOC emissions and conformance with VOC BAT limits to demonstrate compliance with these emissions limitations. The rolling 12-month summation of the monthly emissions will be used to demonstrate compliance with the annual emission limitations.

C. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify all exceedances of the rolling, 12-month emission limitations for CO, NO_x, PM₁₀, SO₂ and/or VOC and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative emission levels.
2. The permittee shall also submit annual reports which specify the facility wide emissions of CO, NO_x, PM₁₀, SO₂ and VOC for the previous calendar year. These reports shall be submitted by April 30 of each year.
3. The permittee shall submit quarterly reports summarizing the ongoing construction progress on the emissions units comprising this permit to install. These reports shall, at a minimum, identify those emissions units for which installation is not complete, and the scheduled completed installation date for each such unit.

These reports shall begin with the first full quarter in which a saleable vehicle is produced and shall be submitted by April thirtieth, July thirty-first, October thirty-first, and January thirty-first of each year, unless otherwise specified by the Toledo Division of Environmental Services, and shall cover the data obtained during the previous calendar quarters.

D. Testing Requirements

1. Compliance with the rolling, 12-month emission limitations for CO, NO_x, PM₁₀, SO₂ and/or VOC shall be demonstrated by calculations from the record_keeping requirements of Additional Special Terms and Conditions I.B.

E. Miscellaneous Requirements

1. The permittee is approved to make the changes listed below to the extent allowed under Ohio Administrative Code Chapter 3745-31 (Note: It is highly recommended that the permittee discuss any future changes with the Toledo Division of Environmental Services **prior** to making those changes in order to avoid potential compliance problems):
 - a. components of the emissions units may be replaced in kind or replaced with a component with equivalent or inherently lower emissions if such a replacement would not qualify as a "reconstruction" under 40 CFR 60.15, and if, where applicable, the appropriate emission activity category form is revised to reflect the change;
 - b. operational changes which will not increase the short term emission limit established or exceed long term emission limitations;
 - c. any of the exemptions listed under OAC rule 3745-31-03;
 - d. introduction of new types of VOC containing materials used for new models which meet the requirements of Additional Special Terms and Conditions I.E.2. and which will not increase the short term emission limit established or exceed long term emission limitations;
 - e. changes in the number and type of applicator equipment if such components have equivalent or inherently lower emissions and will not increase the short term emission limit established or exceed long term emission limitations;
 - f. changes in the physical dimensions of each booth, dip tank or oven to accommodate production needs, provided that these changes do not reduce the overall collection efficiency, will not increase the short term emissions limits established or exceed the long term emissions limitations and, where applicable, the appropriate emission activity category form is revised to reflect the change;
 - g. addition or modification of auxiliary cleaning steps or coating operations where the process is covered by an existing permit and such changes will have equivalent or inherently lower emissions and will not increase the short term emission limit established or exceed long term emission limitations, and if, where applicable, the appropriate emission activity category form is revised to reflect the change;
 - h. changes in the number and type of emergency generators and fire pumps of 50 horsepower or less capacity and meeting the permanent exemption requirements in OAC 3745-31-03(A)(1)(nn);
 - i. changes in the number and type of space heaters and water heaters used to meet space or process heating needs of less than 10 million Btu capacity and meeting the permanent exemption requirements in OAC 3745-31-03(A)(1)(a);

- j. new or replacement air pollution devices (such as scrubbers, baghouses and thermal oxidizers) where such changes will result in equivalent or inherently lower emissions and written notification of the change is forwarded to the Toledo Division of Environmental Services to schedule possible stack testing, and if, where applicable, the appropriate emission activity category form is revised to reflect the change;
- k. changes to assembly operations (such as the use of sealers, wipes or adhesives and welding operations) where the operation is covered by an existing permit and such changes will not increase the short term emission limit established or exceed long term emission limitations, or where the operation meets the exemption requirements in OAC 3745-15-05(B) or OAC 3745-15-05(D), and if, where applicable, the appropriate emission activity category form is revised to reflect the change; and,
- l. any other change for which the emissions impact of any involved emissions unit is below the significance level for all criteria pollutants and which is specifically exempted by regulation from State and Federal permitting requirements, including PSD and if, where applicable, the appropriate emission activity category form is revised to reflect the change.
2. This permit allows the use of the coatings and cleanup materials specified by the permittee in the application for PTI number 04-1102. In conjunction with the best available technology requirements of OAC rule 3745-31-05, the Toluene 2,4 diisocyanate, Formaldehyde, Phosphoric acid, Triethanolamine, Nitric acid, Ethanolamine, Glycerine, Vinyl chloride, Benzene, Vinyl acetate, n-Butyl alcohol, Ethylene glycol monobutyl ether (2-butoxy ethanol), 1,2,4-Trimethylbenzene, Diisobutyl ketone, Isobutyl alcohol, Toluene, Methyl isobutyl ketone, Methyl amyl ketone, Cumene, Methanol, Propylene glycol methyl ether, Ethylbenzene, Xylene, 3-Methyl butyl acetate (i.e., isoamyl acetate), n-Amyl acetate, Methyl ethyl ketone, Tetrahydrofuran, Dipropylene glycol monomethyl ether, Methyl n-propyl ketone, Isobutyl acetate, Butyl Acetate, Natural gasoline, Isopropyl alcohol, Isopropyl acetate, Aromatic Controlled Naphtha, Mineral Spirits, VM&P Naphtha (Mineral Spirits), Petroleum naphtha, Petroleum distillates, Naphthol Spirits, Solvent naphtha light aliphatic, Aromatic solvent 150, Light aromatic solvent naphtha, Odorless mineral spirits, Mineral Spirits (Hydrocarbons), Petroleum Distillates, Ethyl acetate, Heptane, Acetone and Ethanol emission concentrations specified in this permit were established in accordance with the Ohio EPA's "Air Toxics Policy" and are based on both the coating and cleanup material formulation data and the design parameters of the emissions unit's exhaust system, as specified in the application. Compliance with the Ohio EPA's "Air Toxics Policy" was demonstrated for each pollutant based on the "ISCST3" model and a comparison of the predicted 1 hour maximum ground-level concentration to the MAGLC. The following table summarizes the results of the modeling for each pollutant:

CAS#:	Chemical Name:	Modeling	Max imum	Screening	TLV
		Input File	Concentratio	[ug/m3]:	(mg/m3)
		Name	(ug/m3)	(1/42 of	
584849	Toluene 2,4 diisocyanate	emissions	<1.0 TPY	0.86	0.036
50000	Formaldehyde	TACF2_9	6.5	6.5	0.37*
7664382	Phosphoric acid	TACD__8	6.4	24	1
102716	Triethanolamine	TACE__8	0.9	119	5
7697372	Nitric acid	TACD__8	6.4	124	5.2

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: 0448010414

141435	Ethanolamine	TACA__8	163.4	179	7.5
56815	Glycerine	TACA__8	3.4	238	10
75014	Vinyl chloride	emissions	<1.0 TPY	310	13
71432	Benzene	TACC__8	16.7	762	32
108054	Vinyl acetate	TACB__8	459	833	35
71363	n-Butyl alcohol	TACVOC	1,691	2,667	152*
111762	Ethylene glycol monobutyl ether; (2-butoxy ethanol)	TACVOC 91	1,691	2,881	121
95636	1,2,4-Trimethylbenzene	TACVOC	1,691	2,929	123
108838	Diisobutyl ketone	TACVOC	1,691	3,452	145
78831	Isobutyl alcohol	TACVOC	1,691	3,619	152
108883	Toluene	TACVOC	1,691	4,476	188
108101	Methyl isobutyl ketone	TACVOC	1,691	4,881	205
110430	Methyl amyl ketone	TACVOC	1,691	5,548	233
98828	Cumene	TACVOC	1,691	5,857	246
67561	Methanol	TACVOC	1,691	6,238	262
107982	Propylene glycol methyl ether	TACVOC	1,691	8,786	369
100414	Ethylbenzene	TACVOC	1,691	10,333	434
1330207	Xylene	TACVOC	1,691	10,333	434
123922	3-Methyl butyl acetate (i.e., isoamyl acetate)	TACVOC 91	1,691	12,667	532
628637	n-Amyl acetate	TACVOC	1,691	12,667	532
78933	Methyl ethyl ketone	TACVOC	1,691	14,048	590
109999	Tetrahydrofuran	TACVOC	1,691	14,048	590
34590948	Dipropylene glycol monomethyl ether	TACVOC 91	1,691	14,429	606
107879	Methyl n-propyl ketone	TACVOC	1,691	16,786	705
110190	Isobutyl acetate	TACVOC	1,691	16,976	713
123864	Butyl Acetate	TACVOC	1,691	16,976	713
8006619	Natural gasoline	TACVOC	1,691	21,190	890
67630	Isopropyl alcohol	TACVOC	1,691	23,405	983
108214	Isopropyl acetate	TACVOC	1,691	24,762	1040

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

64602	Aromatic Controlled Naphtha	TACVOC	1,691	32,619	1370
64704	Mineral Spirits (1)	TACVOC	1,691	32,619	1370
8032324	VM&P Naphtha (Mineral	TACVOC	1,691	32,619	1370
64741419	Petroleum naphtha (1)	TACVOC	1,691	32,619	1370
64741657	Mineral spirits (1)	TACVOC	1,691	32,619	1370
64741895	Petroleum distillates (1)	TACVOC	1,691	32,619	1370
64742489	Naphthol Spirits (1)	TACVOC	1,691	32,619	1370
64742887	Mineral spirits (1)	TACVOC	1,691	32,619	1370
64742898	Solvent naphtha, light	TACVOC	1,691	32,619	1370
64742945	Aromatic solvent 150 (1)	TACVOC	1,691	32,619	1370
64742956	Light aromatic solvent	TACVOC	1,691	32,619	1370
68551177	Odorless mineral spirits (1)	TACVOC	1,691	32,619	1370
68647609	Mineral Spirits	TACVOC	1,691	32,619	1370
64742536A	Petroleum Distillates (1)	TACVOC	1,691	32,619	1370
141786	Ethyl acetate	TACVOC	1,691	34,286	1440
142825	Heptane	TACVOC	1,691	39,048	1640
67641	Acetone	TACVOC	1,691	42,381	1780
64175	Ethanol	TACVOC	1,691	44,762	1880

* 8 hour STEL which may be converted to a one-hour concentration using a factor of 0.737,

Note: "worse case scenario" assumes that any given toxic comprises the entire stream.

3. Any of the following changes may be deemed a "modification" to the emissions unit and, as such, prior notification to and approval from the Toledo Division of Environmental Services is required, including the possible issuance of modifications to PTI number 04-1102 and the operating permit:
 - a. any changes in the composition of the coatings or cleanup materials, or the use of new coatings or cleanup materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value specified in the above table;
 - b. any change to the emissions unit or its exhaust parameters (e.g., increased emission rate, reduction of exhaust gas flow rate, and decreased stack height) that would result in an exceedance of any MAGLC specified in the above table; and,
 - c. any change to the emissions unit or its method of operation that would either require an increase in the emission limitation(s) established by this permit or would otherwise be considered a "modification" as defined in OAC rule 3745-31-01.

II. Energy Center Boiler (B008, B009 & B010)

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

A. Operational Restrictions

1. This emissions unit shall be exempt from the stated sulfur dioxide limitations during any calendar day in which natural gas having a heat content greater than 950 Btu per standard cubic foot and a sulfur content less than 0.6 pound per million standard cubic feet is the only fuel burned.
2. The permittee shall burn only natural gas in these emissions units.

B. Monitoring and/or Record Keeping Requirements

1. The permittee shall comply with the applicable monitoring and record_keeping requirements in 40 CFR Part 60 Subpart Dc.
2. The permittee shall maintain monthly records of the total quantity of natural gas burned in this emissions unit.
3. For each day during which the permittee burns a fuel other than natural gas , the permittee shall maintain a record of the type and quantity of fuel burned in these emissions units.

C. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than natural gas was burned in these emissions units. Each report shall be submitted within 30 days after the deviation occurs.

D. Testing Requirements

1. Compliance with the emission limitation(s) of these terms and conditions shall be determined in accordance with the following methods(s):
 - a. Emission Limitation

5 percent opacity for gas , as a 6 minute average except as provided by rule.

Applicable Compliance Method

If required, compliance shall be determined through visible emissions observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services.
 - b. Emission Limitation

0.083 pound of carbon monoxide emissions per MMBtu actual heat input

Applicable Compliance Method

Compliance with the pound/MMBtu limitation may be based upon an emission factor of 0.083 lb CO/MMBtu ((84 lb/mmscf)/(1020 Btu/scf)) specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 1.4-1, dated 7/98. If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in Method 10 of 40 CFR Part 60, Appendix A. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services.

c. Emission Limitation

0.049 pound of nitrogen oxides emissions per MMBtu actual heat input for gas

Applicable Compliance Method

Compliance with the pound/MMBtu limitation may be based upon an emission factor of 0.049 lb NO_x/MMBtu ((50 lb/mmscf)/(1020 Btu/scf)) specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 1.4-1, dated 7/98. If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in Method 7 of 40 CFR Part 60, Appendix A. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services.

d. Emission Limitation

0.0056 pound of particulate matter (as PM₁₀) per million Btu of actual heat input for gas

Applicable Compliance Method

Compliance with the pound/MMBtu limitation may be based upon an emission factor of 0.0056 lb PM₁₀/MMBtu ((5.7 lb/mmscf)/(1020 Btu/scf)) specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 1.4-2, dated 7/98. If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in Methods 201 and 202 of 40 CFR Part 51, Appendix M. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services.

e. Emission Limitation

0.0006 pound of sulfur dioxide emissions per million Btu actual heat input

Applicable Compliance Method

Compliance with the pound/MMBtu emission limitation may be based upon an emission factor of 0.0006 lb SO₂/MMBtu ((0.6 lb/mmscf)/(1020 Btu/scf)) specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 1.4-2, dated 7/98, or OAC rule 3745-18-04(G)(3). If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in Method 6 of 40

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

CFR Part 60, Appendix A. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services.

f. Emission Limitation

0.0054 pound of volatile organic compound per million Btu of actual heat input for gas

Applicable Compliance Method

Compliance with the pound/MMBtu emission limitation may be based upon an emission factor of 0.0054 lb VOC/MMBtu ((5.5 lb/mmscf)/(1020 Btu/scf) specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 1.4-2, dated 7/98. If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in Method 25 or 25A of 40 CFR Part 60, Appendix A. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services.

g. Emission Limitation

11.9 tons CO, 7.0 tons NO_x, 0.81 ton PM, 0.09 ton SO₂, and 0.78 ton VOC per calendar year.

Applicable Compliance Method

Compliance with this emission limitation shall be determined by multiplying the pound/MMBtu emission limitation for each pollutant by the maximum annual firing rate (32.66 MMBtu/hr x 8,760 hrs/yr) , in MMBtu/yr, and dividing by 2000 lbs/ton.

h. Emission Limitation

Natural gas having a heat content greater than 950 Btu per standard cubic foot and a sulfur content less than 0.6 pound per million standard cubic feet.

Applicable Compliance Method

The exclusive use of commercially available natural gas will be considered adequate demonstration of compliance.

E. Miscellaneous Requirements

1. If in the future the permittee applies for a permit modification to burn fuels other than the natural gas allowed by this permit, the BAT determination for this emissions unit will be re-evaluated on a case by case basis.

III. Gasoline Fill Stations, G003

A. Operational Restrictions

1. The permittee shall not cause, allow or permit the transfer of gasoline at a gasoline dispensing facility used to fuel newly constructed vehicles unless the following requirements are met:
 - a. any stationary storage tank which stores gasoline at the gasoline dispensing facility is equipped with a submerged fill pipe;
 - b. for any transfer of gasoline from a delivery vessel to a stationary storage tank located at the gasoline dispensing facility, the vapors displaced from the stationary storage tank are processed by one of the following systems:
 - i. a vapor balance system which is designed and operated to route at least 90 percent by weight of the VOC in the displaced vapors to the delivery vessel and which is equipped with a means to prevent the discharge of displaced vapors from an unconnected vapor line;
 - ii. a vapor control system which is designed and operated to recover at least 90 percent by weight of the VOC in the displaced vapors.
2. The permittee shall comply with the following operational restrictions for the Stage I vapor control system:
 - a. the vapor balance system shall be kept in good working order and shall be used at all times during the transfer of gasoline;
 - b. there shall be no leaks in the delivery vessel pressure/vacuum relief valves and hatch covers;
 - c. there shall be no leaks in the vapor liquid lines during the transfer of gasoline; and,
 - d. all fill caps shall be "in place" and clamped during normal storage conditions.
3. The permittee shall repair within 15 days any leak from the vapor balance system or vapor control system which is employed to meet the requirements of paragraph (R)(1) of OAC rule 3745-21-09 when such leak is equal to or greater than 100 percent of the lower explosive limit as propane, as determined under paragraph (K) of OAC rule 3745-21-10.
4. The permittee shall not cause, allow, or permit the transfer of gasoline from a stationary storage tank into a motor vehicle unless all vapors displaced from the motor vehicle are vented to a vapor control system which is designed and operated to maintain an overall control efficiency of not less than 90 percent, by weight, for the VOC in the displaced vapors. The vapor control system shall employ only coaxial hoses, and the use of remote check valves shall be prohibited.
5. All the vehicles filled by this gasoline dispensing facility shall be equipped with an ORVR system that achieves a 95% overall control efficiency for VOCs and meets the requirements of 40 CFR 86.099-8. Because an ORVR control system is employed, the other requirements of OAC rule 3745-21-09(DDD) relating to Stage II control systems are not relevant.

B. Monitoring and/or Record Keeping Requirements

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

1. When the Stage I vapor control system is being used for control, The permittee shall maintain records of the following information:
 - a. the results of any leak checks, including, at a minimum, the following information:
 - i. date of inspection;
 - ii. findings (may indicate no leaks discovered or location, nature, and severity of each leak);
 - iii. leak determination method;
 - iv. corrective action, when such actions are necessary (date each leak repaired and reasons for any repair interval in excess of 15 calendar days); and,
 - v. inspector's name and signature.
 - b. the quantity of gasoline delivered to the facility during each calendar month;
 - c. the results of any tests performed pursuant to the testing requirements specified in this permit;
 - d. a log of the date and description of all repair and maintenance work performed (including, but not limited to, work performed to meet manufacturer's specifications), or any other modifications made to the vapor control system;
 - e. proof of attendance and completion of the training required by the Ohio EPA for the operator or local supervisor of the gasoline dispensing facility; and,
 - f. copies of all completed post test inspection forms.

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

C. Reporting Requirements

1. When the Stage I vapor recovery system is being used for control, any leak from the vapor balance system or vapor control system that is not repaired within 15 days after identification shall be reported to the Director within 30 days after the repair is completed.
2. A comprehensive written report on the results of any tests performed in accordance with the requirements of this permit shall be submitted within 30 days following the completion of the tests.

D. Testing Requirements

1. Compliance with the emission limitation(s) of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation

34 tons of VOC emissions per year.

Applicable Compliance Method

Multiply the 1/95 AP-42 emission factor of 3.1 pounds VOC per 1000 gallons of gasoline by the annual summation of gasoline throughput.
 - b. Emission Limitation

Detection of leaks.

Applicable Compliance Method

OAC 3745-21-10(K) and OAC 3745-21-10(Q). Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services.
 - c. Compliance with the emission limitation(s) in section A.I.1. of these terms and conditions shall be determined in accordance with the following method(s):

Emission Limitation:

95% overall control efficiency for VOCs

Applicable Compliance Method:

Compliance with this emission limitation shall be based upon USEPA's measurements of the ORVR system for each vehicle model produced at this facility and as documented in the USEPA's certificate of conformity. The permittee shall maintain records of all such certificates of conformity for the vehicles produced at this facility.

E. Miscellaneous Requirements

1. None.

IV. E-COAT (K021)

A. Operational Restrictions

1. The permittee shall operate and maintain a thermal incinerator, with a 100 percent capture efficiency and a minimum of 95 percent control efficiency, to control VOC emissions from the drying oven. The thermal incinerator shall be installed, operated and maintained in accordance with the manufacturer's recommendations.
2. The average combustion temperature within the thermal incinerator, for any 3-hour block of time when the incinerator is in operation as a VOC control device for compliance purposes, shall not be below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
3. This emissions unit shall be exempt from the stated sulfur dioxide limitations during any calendar day in which natural gas having a heat content greater than 950 Btu per standard cubic foot and a sulfur content less than 0.6 pound per million standard cubic feet is the only fuel burned.

B. Monitoring and/or Record Keeping Requirements

1. The permittee shall comply with the applicable monitoring and record keeping requirements in 40 CFR Part 60.394 and 60.395.
2. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the thermal incinerator when the incinerator is in operation. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee and approved by the Toledo Division of Environmental Services.
3. The permittee shall collect and record the following information for each month for the coating line and control equipment:
 - a. the name and identification number of each coating, as applied;
 - b. the mass of VOC per volume of coating solids, as applied, the volume solids content, as applied, and the volume, as applied, of each coating;
 - c. the maximum VOC content (in mass of VOC per volume of applied coating solids) or the daily volume-weighted average VOC content (in mass of VOC per volume of applied coating solids) of all the coatings;
 - d. the calculated, controlled VOC emission rate, in mass of VOC per volume of applied coating

solids. The controlled VOC emission rate shall be calculated using (i) either the maximum VOC content or the daily volume-weighted VOC content recorded in accordance with paragraph "c." above and (ii) the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the emissions unit was in compliance;

- e. the calculated, controlled VOC emissions, in tons of VOC/month and tons of VOC per rolling, 12-month period. The controlled VOC emissions shall be calculated using the controlled VOC emissions rate in Section IV.B.3.d. above and the volume solids content per month from Section IV.B.3.b. above and a factor of 2000 lbs/ton.
- f. a log or record of operating time for the capture (collection) system, control device, monitoring equipment, and the associated emissions unit; and,
- g. all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator, when the emissions unit was in operation, was below the average temperature during the most recent emission test that demonstrated that the emissions unit was in compliance.

Alternate, equivalent record_keeping methods may be used upon written approval by the Toledo Division of Environmental Services.

C. Reporting Requirements

1. The permittee shall comply with the applicable reporting and record_keeping requirements in 40 CFR Part 60.395.
2. The permittee shall submit quarterly deviation (excursion) reports that identify all monthly records showing that the calculated, controlled VOC emission rate exceeds the applicable mass of VOC per volume of applied coating solids limitation. The notification shall include a copy of such record.
3. The permittee shall submit quarterly temperature deviation (excursion) reports that identify all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated that the emissions unit was in compliance.

D. Testing Requirements

1. Compliance with the emission limitation(s) of these terms and conditions shall be determined in accordance with the following methods(s):
 - a. Emission Limitation

0.23 pound of VOC per gallon of applied coating solids.

Applicable Compliance Method

The permittee shall use the procedures in 40 CFR Part 60.393 for determining the monthly volume weighted average mass of VOC emitted per volume of applied solids.
 - b. Emission Limitation

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

5 percent opacity from the incinerator.

Applicable Compliance Method

OAC rule 3745-17-03(B)(1). Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services.

c. Emission Limitation

52.01 tons VOC/yr.

Applicable Compliance Method

Compliance with the emissions limitation will be demonstrated by the record keeping requirements of Additional Special Terms and Conditions IV.B.3., and by monthly records of coating usage and VOC content.

d. Emission Limitation

CO: 0.083 pound/MMBtu & 9.5 tons/year, NO_x: 0.100 lb/MMBtu & 11.4 tons/year, PM₁₀: 0.0056 pound/MMBtu and 0.064 ton/year, SO₂: 0.0006 pound/MMBtu and 0.068 ton/year, VOC: 0.0054 pound/MMBtu and 0.62 ton/year and 5 percent opacity from the oven combustion gases.

Applicable Compliance Method

CO: Compliance with the pound/MMBtu limitation may be based upon an emission factor of 0.083 lb CO/MMBtu ((84 lb/mmscf)/(1020 Btu/scf)) specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 1.4-1, dated 7/98. If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in Methods 1 through 4 and 10 of 40 CFR Part 60, Appendix A. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. Compliance with the ton/year emission limitation shall be determined by multiplying the lb/MMBtu emission limitation of 0.083 lb/MMBtu by the maximum annual firing rate for this emissions unit (26.0 MMBtu/hr x 8,760 hrs/yr), in MMBtu/yr, and dividing by 2000 lbs/ton.

NO_x: Compliance with the pound/MMBtu emission limitation may be based upon an emission factor of 0.099 lb NO_x/MMBtu ((100 lb/mmscf)/1020 Btu/scf) in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 1.4-1, dated 7/98. If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in Methods 1 through 4 and 7 of 40 CFR Part 60,

Appendix A. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. Compliance with the ton/year emission limitation shall be determined by multiplying the lb/MMBtu emission limitation of 0.099 lb/MMBtu by the maximum annual firing rate for this emissions unit (26.0 MMBtu/hr x 8,760 hrs/yr), in MMBtu/yr, and dividing by 2000 lbs/ton.

PM₁₀: Compliance with the lb/MMBtu emission limitation may be based upon an emission factor of 0.0056 lb PM₁₀/MMBtu ((5.7 lb PM/mmscf)/(1020 Btu/scf)) specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 1.4-2, dated 7/98. AP-42 states that all particulate from this process is presumed to be less than 1.0 micron in diameter. If required, the permittee shall demonstrate compliance with this emission limitation in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. Compliance with the ton/year emission limitation shall be determined by multiplying the lb/MMBtu emission limitation of 0.0056 lb/MMBtu by the maximum annual firing rate for this emissions unit (26.0 MMBtu/hr x 8,760 hrs/yr), in MMBtu/yr, and dividing by 2000 lbs/ton.

SO₂: Compliance with the pound/MMBtu emission limitation may be based upon an emission factor of 0.0006 lb SO₂/MMBtu ((0.6 lb/mmscf)/(1020 Btu/scf)) specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 1.4-2, dated 7/98, or OAC rule 3745-18-04(G)(3). If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in Methods 1 through 4 and 6 of 40 CFR Part 60 Appendix A, using the methods and procedures specified in OAC rule 3745-18-04. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. Compliance with the ton/year emission limitation shall be determined by multiplying the lb/MMBtu emission limitation of 0.0006 lb/MMBtu by the maximum annual firing rate for this emissions unit (26.0 MMBtu/hr x 8,760 hrs/yr), in MMBtu/yr, and dividing by 2000 lbs/ton.

VOC: Compliance with the pound/MMBtu emission limitation may be based upon an emission factor of 0.0054 lb VOC/MMBtu ((5.5 lb/mmscf)/(1020 Btu/scf)) specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 1.4-2, dated 7/98. If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in Methods 1 through 4 and 25 or 25A of 40 CFR Part 60, Appendix A, using the methods and procedures specified in OAC rule 3745-21-10. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. Compliance with the ton/year emission limitation shall be determined by multiplying the lb/MMBtu emission limitation of 0.0054 lb/MMBtu by the maximum annual firing rate for this emissions unit (26.0 MMBtu/hr x 8,760 hrs/yr), in MMBtu/yr, and dividing by 2000 lbs/ton.

e. Emission Limitation

Natural gas having a heat content greater than 950 Btu per standard cubic foot and a sulfur content less than 0.6 pound per million standard cubic feet.

Applicable Compliance Method

The exclusive use of commercially available natural gas will be considered adequate demonstration

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

of compliance.

2. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. the emission testing shall be conducted within 30 days after achieving the maximum production rate at which the facility will be operated but not later than 180 days after the initial startup of the facility;
 - b. the emission testing shall be conducted to demonstrate compliance with the emission limitations for VOC;
 - c. the following test method(s) shall be employed to demonstrate compliance with the allowable mass emission rate(s): Method 25 of 40 CFR Part 60, Appendix A in accordance with the procedures specified in 40 CFR Part 60.393. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services;
 - d. the test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity;
 - e. the capture efficiency (i.e., the percent of total VOC which enters the control device) shall be determined in accordance with the test methods and procedures specified in 40 CFR Part 60.393; and,
 - f. the control efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in 40 CFR Part 60.393. The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Toledo Division of Environmental Services. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the local air agency' refusal to accept the results of the emission test(s).

Personnel from the Toledo Division of Environmental Services shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or

persons responsible for the tests and submitted to the Toledo Division of Environmental Services within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Toledo Division of Environmental Services.

E. Miscellaneous Requirements

1. Should any coating formulations cause a nuisance odor, or process changes cause an increase in the quantity or intensity of odors emitted from this facility, as determined by the Toledo Division of Environmental Services, the company shall take corrective action to reduce the impact of the odors. The time schedule for the corrective action shall be approved by the Toledo Division of Environmental Services.

V. Powder Anti-chip (K022)

A. Operational Restrictions

1. This emissions unit shall be exempt from the stated sulfur dioxide limitations during any calendar day in which natural gas having a heat content greater than 950 Btu per standard cubic foot and a sulfur content less than 0.6 pound per million standard cubic feet is the only fuel burned.
2. The emissions of VOC from this emissions unit shall not exceed 3.25 tons per year, as a rolling, 12-month total.

To ensure enforceability during the first 12 calendar months of operation, the permittee shall not exceed the emission levels specified in the following table:

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

<u>Month(s)</u>	<u>Maximum Allowable Cumulative Emissions (Tons)VOC</u>
1	0.27
1-2	0.54
1-3	0.81
1-4	1.08
1-5	1.35
1-6	1.62
1-7	1.89
1-8	2.16
1-9	2.43
1-10	2.70
1-11	2.97
1-12	3.25

After the first 12 calendar months of operation following the issuance of this permit, compliance with the annual emission limitations shall be based upon a rolling, 12-month summation of the monthly emissions.

B. Monitoring and/or Record Keeping Requirements

1. The permittee shall comply with the applicable monitoring and record_keeping requirements in 40 CFR Part 60.394 and 60.395.
2. The permittee shall collect and record the following information for each month for the coating line and control equipment:
 - a. the name and identification number of each coating, as applied;
 - b. the mass of VOC per volume of coating solids, as applied, the volume solids content, as applied, and the volume, as applied, of each coating;
 - c. the maximum VOC content (in mass of VOC per volume of applied coating solids, as applied) or the daily volume-weighted average VOC content (in mass of VOC per volume of applied coating solids) of all the coatings;
 - d. the calculated, VOC emission rate, in mass of VOC per volume of applied coating solids. The VOC emission rate shall be calculated using the maximum VOC content or the daily volume-weighted VOC content recorded in accordance with paragraph (c) above.
 - e. the monthly emissions of VOC and the rolling, 12-month summation of the monthly emissions;
 - f. a log or record of operating time for the capture (collection) system, control device(s), monitoring

DaimlerChrysler Corp

PTI Application: 04-01102

Modification Issued: 9/8/2005

Facility ID: **0448010414**

equipment, and the associated emissions unit.

Alternate, equivalent record-keeping methods may be used upon written approval by the Toledo Division of Environmental Services.

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

C. Reporting Requirements

1. The permittee shall comply with the applicable reporting and record_keeping requirements in 40 CFR Part 60.395.
2. The permittee shall submit quarterly deviation (excursion) reports that identify all daily records showing that the calculated, controlled VOC emission rate exceeds the applicable tons of VOC per rolling, 12-month period limitation. The notification shall include a copy of such record.

D. Testing Requirements

1. Compliance with the emission limitation(s) of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation

1.40 kilogram of VOC/liter (11.7 pounds VOC/gal)of applied coating solids.

Applicable Compliance Method

The permittee shall use the procedures in 40 CFR Part 60.393 for determining the monthly volume weighted average mass of VOC emitted per volume of applied solids.
 - b. Emission Limitation

3.25 tons VOC per rolling 12-month period.

Applicable Compliance Method

The permittee shall calculate the rolling 12-month summation of emissions based on the record_keeping requirements of Additional Special Term and Condition V.B.2. Where applicable, the permittee shall use OAC 3745-21-10(B) and the procedures in 40 CFR Part 60.393 for determining the monthly volume weighted average mass of VOC emitted per volume of applied solids.
 - c. Emission Limitation

5 percent opacity from the oven.

Applicable Compliance Method

OAC rule 3745-17-03(B)(1). Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services.

d. Emission Limitation

CO: 0.083 pound/MMBtu and 12.9 tons/year, NO_x: 0.100 pound/MMBtu and 15.5 tons/year, PM₁₀: 0.0056 pound/MMBtu and 0.87 ton/year, SO₂: 0.0006 pound/MMBtu and 0.093 ton/year, VOC: 0.0054 pound/MMBtu and 0.84 ton/year and 5 percent opacity from the oven combustion gases.

Applicable Compliance Method

CO: Compliance with the pound/MMBtu limitation may be based upon an emission factor of 0.083 lb CO/MMBtu ((84 lb/mmscf)/(1020 Btu/scf)) specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 1.4-1, dated 7/98. If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in Methods 1 through 4 and 10 of 40 CFR Part 60, Appendix A. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. Compliance with the ton/year emission limitation shall be determined by multiplying the lb/MMBtu emission limitation of 0.083 lb/MMBtu by the maximum annual firing rate for this emissions unit (35.8 MMBtu/hr x 8,760 hrs/yr), in MMBtu/yr, and dividing by 2000 lbs/ton.

NO_x: Compliance with the pound/MMBtu emission limitation may be based upon an emission factor of 0.099 lb NO_x/MMBtu ((100 lb/mmscf)/1020 Btu/scf) in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 1.4-1, dated 7/98. If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in Methods 1 through 4 and 7 of 40 CFR Part 60, Appendix A. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. Compliance with the ton/year emission limitation shall be determined by multiplying the lb/MMBtu emission limitation of 0.099 lb/MMBtu by the maximum annual firing rate for this emissions unit (35.8 MMBtu/hr x 8,760 hrs/yr), in MMBtu/yr, and dividing by 2000 lbs/ton.

PM₁₀: Compliance with the lb/MMBtu emission limitation may be based upon an emission factor of 0.0056 lb PM₁₀/MMBtu ((5.7 lb PM/mmscf)/(1020 Btu/scf)) specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 1.4-2, dated 7/98. AP-42 states that all particulate from this process is presumed to be less than 1.0 micron in diameter. If required, the permittee shall demonstrate compliance with this emission limitation in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. Compliance with the ton/year emission limitation shall be determined by multiplying the lb/MMBtu emission limitation of 0.0056 lb/MMBtu by the maximum annual firing rate for this emissions unit (35.8 MMBtu/hr x 8,760 hrs/yr), in MMBtu/yr, and dividing by 2000 lbs/ton.

SO₂: Compliance with the pound/MMBtu emission limitation may be based upon an emission factor of 0.0006 lb SO₂/MMBtu ((0.6 lb/mmscf)/(1020 Btu/scf)) specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 1.4-2, dated 7/98, or OAC rule 3745-18-04(G)(3). If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in Methods 1 through 4 and 6 of 40 CFR Part 60 Appendix A, using the methods and procedures specified in OAC rule 3745-18-04. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. Compliance with the ton/year emission limitation shall be determined by multiplying the lb/MMBtu emission limitation of 0.0006 lb/MMBtu by the maximum annual firing rate for this emissions unit (35.8 MMBtu/hr x 8,760 hrs/yr), in MMBtu/yr, and dividing by 2000 lbs/ton.

VOC: Compliance with the pound/MMBtu emission limitation may be based upon an emission factor of 0.0054 lb VOC/MMBtu ((5.5 lb/mmscf)/(1020 Btu/scf)) specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 1.4-2, dated 7/98. If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in Methods 1 through 4 and 25 or 25A of 40 CFR Part 60, Appendix A, using the methods and procedures specified in OAC rule 3745-21-10. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. Compliance with the ton/year emission limitation shall be determined by multiplying the lb/MMBtu emission limitation of 0.0054 lb/MMBtu by the maximum annual firing rate for this emissions unit (35.8 MMBtu/hr x 8,760 hrs/yr), in MMBtu/yr, and dividing by 2000 lbs/ton.

e. Emission Limitation

Natural gas having a heat content greater than 950 Btu per standard cubic foot and a sulfur content less than 0.6 pound per million standard cubic feet.

Applicable Compliance Method

The exclusive use of commercially available natural gas will be considered adequate demonstration of compliance.

E. Miscellaneous Requirements

- Should any coating formulations cause a nuisance odor, or process changes cause an increase in the quantity or intensity of odors emitted from this facility, as determined by the Toledo Division of Environmental Services, the company shall take corrective action to reduce the impact of the odors. The time schedule for the corrective action shall be approved by the Toledo Division of Environmental Services.

VI. Topcoat (K023)

A. Operational Restrictions

- The permittee shall operate and maintain a thermal incinerator, with a 100 percent capture efficiency and a minimum of 95 percent control efficiency, to control VOC emissions from the clearcoat drying oven. The thermal incinerator shall be installed, operated and maintained in accordance with the manufacturer's recommendations.

2. The average combustion temperature within the thermal incinerator, for any 3-hour block of time when the incinerator is in operation as a VOC control device for emissions fee or compliance purposes, shall not be below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
3. This emissions unit shall be exempt from the stated sulfur dioxide limitations during any calendar day in which natural gas having a heat content greater than 950 Btu per standard cubic foot and a sulfur content less than 0.6 pound per million standard cubic feet is the only fuel burned.

B. Monitoring and/or Record Keeping Requirements

1. The permittee shall comply with the applicable monitoring and record_keeping requirements in 40 CFR Part 60.394.
2. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the thermal incinerator when the incinerator is in operation. Units shall be in degrees Fahrenheit and/or Centigrade. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee and approved by the Toledo Division of Environmental Services.
3. The permittee shall collect and record for each day a log or record of operating time for the capture (collection) system, control device(s), monitoring equipment, and the associated emissions unit.
4. The permittee shall collect and record the following information for each month for the coating line and control equipment:
 - a. the name and identification number of each coating, as applied;
 - b. the mass of VOC per volume of coating solids, as applied, the volume solids content, as applied, and the volume, as applied, of each coating;
 - c. the maximum VOC content (in mass of VOC per volume of applied coating solids) or the daily volume-weighted average VOC content (in mass of VOC per volume of applied coating solids) of all the coatings;
 - d. the calculated, controlled VOC emission rate, in mass of VOC per volume of applied coating solids. The controlled VOC emission rate shall be calculated using (i) either the maximum VOC content or the daily volume-weighted VOC content recorded in accordance with paragraph (c) above and (ii) the overall control efficiency for the control equipment as determined during the most recent emission test that demonstrated that the emissions unit was in compliance; and,
 - e. all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator, when the emissions unit was in operation, was below the average temperature during the most recent emission test that demonstrated that the emissions unit was in compliance.

Alternate, equivalent record_keeping methods may be used upon written approval by the Toledo Division of

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

Environmental Services.

C. Reporting Requirements

1. The permittee shall comply with the applicable reporting and record_keeping requirements in 40 CFR Part 60.395.
2. The permittee shall submit quarterly deviation (excursion) reports that identify all daily records which show that the calculated, controlled VOC emission rate exceeds the applicable mass of VOC per volume of solids limitation. The notification shall include a copy of such record.
3. The permittee shall submit quarterly temperature deviation (excursion) reports that identify all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator, when the emissions unit was in operation, was below the average temperature during the most recent emission test that demonstrated that the emissions unit was in compliance.

D. Testing Requirements

1. Compliance with the emission limitation(s) of these terms and conditions shall be determined in accordance with the following methods(s):

a. Emission Limitation

8.63 pounds VOC per gallon of applied coating solids.

Applicable Compliance Method

The permittee shall use the procedures in 40 CFR Part 60.393 for determining the monthly volume weighted average mass of VOC emitted per volume of applied solids. Where applicable, compliance shall also be demonstrated pursuant to the methods and procedures set forth in the "Protocol for Determining the Daily Volatile Organic Compound Emission Rate of Automobile and Light-Duty

Truck Topcoat Operations", EPA-450-3-88-018, dated December 1988, and any subsequent revision approved by the EPA and the State of Ohio Environmental Protection Agency. For compliance purposes, a VOC content of 12.26 pounds per gallon will be considered to be equivalent to 1.47 kilograms per liter.

b. Emission Limitation

15.3 pounds of PM₁₀ per hour and 66.9 tons of PM₁₀ per year.

Applicable Compliance Method

The use of adequate control equipment, as demonstrated by the log or record of congruent operating times for the emissions unit, capture (collection) system and control device(s) required by special terms and conditions IV.B.3., shall be considered adequate demonstration of compliance.

c. Emission Limitation

5 percent opacity from the incinerator.

Applicable Compliance Method

OAC rule 3745-17-03(B)(1). Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services.

d. Emission Limitation

768.68 tons VOC/year.

Applicable Compliance Method

Compliance with the emissions limitation will be demonstrated by calculation from the record keeping requirements of special terms and conditions VI.B.4.

e. Emission Limitation

CO: 0.083 pound/MMBtu and 16.2 tons/year, NO_x: 0.100 pound/MMBtu and 19.5 tons/year, PM₁₀: 0.0056 pound/MMBtu and 1.1 tons/year, SO₂: 0.0006 pound/MMBtu and 0.12 ton/year, VOC: 0.0054 pound/MMBtu and 1.1 tons/year and 5 percent opacity from the oven combustion gases.

Applicable Compliance Method

CO: Compliance with the pound/MMBtu limitation may be based upon an emission factor of 0.083 lb CO/MMBtu ((84 lb/mm scf)/(1020 Btu/scf)) specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 1.4-1, dated 7/98. If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in Methods 1 through 4 and 10 of 40 CFR Part 60, Appendix A. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. Compliance with the ton/year emission limitation shall be determined by multiplying the lb/MMBtu emission limitation of 0.083 lb/MMBtu by the maximum annual firing rate for this emissions unit (44.4 MMBtu/hr x 8,760 hrs/yr), in MMBtu/yr, and dividing by 2000 lbs/ton.

NO_x: Compliance with the pound/MMBtu emission limitation may be based upon an emission factor of 0.099 lb NO_x/MMBtu ((100 lb/mm scf)/1020 Btu/scf) in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 1.4-1, dated 7/98. If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in Methods 1 through 4 and 7 of 40 CFR Part 60, Appendix A. Alternate, equivalent methods may be used upon approval by the Toledo Division of

Environmental Services. Compliance with the ton/year emission limitation shall be determined by multiplying the lb/MMBtu emission limitation of 0.099 lb/MMBtu by the maximum annual firing rate for this emissions unit (44.4 MMBtu/hr x 8,760 hrs/yr), in MMBtu/yr, and dividing by 2000 lbs/ton.

PM₁₀: Compliance with the lb/MMBtu emission limitation may be based upon an emission factor of 0.0056 lb PM₁₀/MMBtu ((5.7 lb PM/mmscf)/(1020 Btu/scf)) specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 1.4-2, dated 7/98. AP-42 states that all particulate from this process is presumed to be less than 1.0 micron in diameter. If required, the permittee shall demonstrate compliance with this emission limitation in accordance with Methods 201 and 202 of 40 CFR Part 51, Appendix M. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. Compliance with the ton/year emission limitation shall be determined by multiplying the lb/MMBtu emission limitation of 0.0056 lb/MMBtu by the maximum annual firing rate for this emissions unit (44.4 MMBtu/hr x 8,760 hrs/yr), in MMBtu/yr, and dividing by 2000 lbs/ton.

SO₂: Compliance with the pound/MMBtu emission limitation may be based upon an emission factor of 0.0006 lb SO₂/MMBtu ((0.6 lb/mmscf)/(1020 Btu/scf)) specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 1.4-2, dated 7/98, or OAC rule 3745-18-04(G)(3). If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in Methods 1 through 4 and 6 of 40 CFR Part 60 Appendix A, using the methods and procedures specified in OAC rule 3745-18-04. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. Compliance with the ton/year emission limitation shall be determined by multiplying the lb/MMBtu emission limitation of 0.0006 lb/MMBtu by the maximum annual firing rate for this emissions unit (44.4 MMBtu/hr x 8,760 hrs/yr), in MMBtu/yr, and dividing by 2000 lbs/ton.

VOC: Compliance with the pound/MMBtu emission limitation may be based upon an emission factor of 0.0054 lb VOC/MMBtu ((5.5 lb/mmscf)/(1020 Btu/scf)) specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 1.4-2, dated 7/98. If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in Methods 1 through 4 and 25 or 25A of 40 CFR Part 60, Appendix A, using the methods and procedures specified in OAC rule 3745-21-10. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. Compliance with the ton/year emission limitation shall be determined by multiplying the lb/MMBtu emission limitation of 0.0054 lb/MMBtu by the maximum annual firing rate for this emissions unit (44.4 MMBtu/hr x 8,760 hrs/yr), in MMBtu/yr, and dividing by 2000 lbs/ton.

f. Emission Limitation

Natural gas having a heat content greater than 950 Btu per standard cubic foot and a sulfur content

less than 0.6 pound per million standard cubic feet.

Applicable Compliance Method

The exclusive use of commercially available natural gas will be considered adequate demonstration of compliance.

2. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. the emission testing shall be conducted within 30 days after achieving the maximum production rate at which the facility will be operated but not later than 180 days after the initial startup of the facility;
 - b. the emission testing shall be conducted to demonstrate compliance with the emission limitations for VOC for the booth/oven and particulate from the booth;
 - c. the following test method(s) shall be employed to demonstrate compliance with the allowable mass emission rate(s): Method 25 of 40 CFR Part 60, Appendix A in accordance with the procedures specified in 40 CFR Part 60.393 for the VOC emissions and OAC rule 3745-17-03(B)(10) for the particulate emissions. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services;
 - d. the test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity, unless otherwise specified or approved by the Toledo Division of Environmental Services;
 - e. the capture efficiency (i.e., the percent of total VOC which enters the control device) shall be determined in accordance with the test methods and procedures specified in 40 CFR Part 60.393; and,

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

- f. the control efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in 40 CFR Part 60.393. The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Toledo Division of Environmental Services. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the local air agency' refusal to accept the results of the emission test(s).

Personnel from the Toledo Division of Environmental Services shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Toledo Division of Environmental Services within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Toledo Division of Environmental Services.

E. Miscellaneous Requirements

1. Should any coating formulations cause a nuisance odor, or process changes cause an increase in the quantity or intensity of odors emitted from this facility, as determined by the Toledo Division of Environmental Services, the company shall take corrective action to reduce the impact of the odors. The time schedule for the corrective action shall be approved by the Toledo Division of Environmental Services.

VII. Low Bake Repair (K024)

A. Operational Restrictions

1. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

B. Monitoring and/or Record Keeping Requirements

1. When using complying coatings (i.e., each coating contains a maximum of 4.8 pounds VOC per gallon, excluding water and exempt solvents), the permittee shall collect and record the following information each month for this emissions unit;
 - i. the name and identification number of each coating, as applied,

- ii. VOC content (excluding water and exempt solvents) and the number of gallons (excluding water and exempt solvents) of each coating, as applied, and
 - iii. the volume-weighted average VOC content of all coatings, as applied, calculated in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for CVOC,2.
2. When calculating a daily volume-weighted average VOC content, the permittee shall collect and record the following information each day for this emissions unit;
- i. the name and identification number of each coating, as applied,
 - ii. VOC content (excluding water and exempt solvents) and the number of gallons (excluding water and exempt solvents) of each coating, as applied, and
 - iii. the volume-weighted average VOC content of all coatings, as applied, calculated in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for CVOC,2.

The permittee shall notify the Toledo Division of Environmental Services, in advance, when daily averaging will be used instead of monthly record keeping. Alternate, equivalent record keeping methods may be used upon written approval by the Toledo Division of Environmental Services.

Alternate, equivalent record keeping methods may be used upon written approval by the Toledo Division of Environmental Services.

3. The permittee shall maintain daily records that document any periods when the dry filtration system was not in service when the emissions unit was in operation.
4. The permittee shall collect and record the following information each month for the purpose of determining the average daily, monthly and annual VOC emissions:
- a. the name and identification number of each coating, as applied;
 - b. the VOC content of each coating (excluding water and exempt solvents), as applied;
 - c. the number of gallons (excluding water and exempt solvents) of each coating employed;
 - d. the total number of gallons (excluding water and exempt solvents) of all coatings employed, calculated as a summation of the quantities recorded in (c) above;
 - e. the total VOC emissions from all coatings employed, in tons per month;
 - f. the rolling 12-month summation of emissions from all coatings employed, in tons per year;
 - g. the number of days the emissions units was in operation; and
 - h. the daily average VOC emissions rate, (e)/(g), in pounds per day.

C. Reporting Requirements

1. The permittee shall notify the Toledo Division of Environmental Services in writing of any record showing the use of noncomplying coatings. The notification shall include a copy of such record and shall be sent to the Toledo Division of Environmental Services within 45 days after the exceedance occurs.
2. The permittee shall notify the Toledo Division of Environmental Services in writing of any daily record that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Toledo Division of Environmental Services within 30 days after the event occurs.

D. Testing Requirements

1. Compliance with the emission limitation(s) of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation

4.8 pounds per gallon of coating, excluding water and exempt solvents.

Applicable Compliance Method

OAC rule(s) 3745-21-09(C)(2) and 3745-21-10(B). USEPA Methods 24 and 24A shall be used to determine the VOC content. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to section 4.3 of Method 24, 40 CFR Part 60, Appendix A, an owner or operator determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A. Alternative formulation data may be used upon written approval of the Toledo Division of Environmental Services.

- b. Emission Limitation

0.551 pound of PM₁₀ per hour and 2.4 tons of PM₁₀ per year.

Applicable Compliance Method

The Monitoring and Record keeping requirements of Section VII.B.3., shall be considered adequate demonstration of compliance.

- c. Emission Limitation

5 percent opacity from the spoven.

Applicable Compliance Method

OAC rule 3745-17-03(B)(1). Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services.

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

d. Emission Limitation

28 tons VOC/year.

Applicable Compliance Method

Use of monthly records of each coating used and the VOC content of each coating used.

E. Miscellaneous Requirements

1. Should any coating formulations cause a nuisance odor, or process changes cause an increase in the quantity or intensity of odors emitted from this facility, as determined by the Toledo Division of Environmental Services, the company shall take corrective action to reduce the impact of the odors. The time schedule for the corrective action shall be approved by the Toledo Division of Environmental Services.

X. Blackout (K027)

A. Operational Restrictions

1. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

B. Monitoring and/or Record Keeping Requirements

1. When using a compliance coating (i.e., the coating contains a maximum of 2.0 pounds VOC per gallon, excluding water and exempt solvents), the permittee shall collect and record the following information for this emissions unit;
 - i. the name and identification number of the coating, as applied,
 - ii. VOC content (excluding water and exempt solvents) and the number of gallons (excluding water and exempt solvents) of the coating, as applied, and
 - iii. the volume-weighted average VOC content of the coating, as applied, calculated in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for CVOC,2.
2. When calculating a daily volume-weighted average VOC content, the permittee shall collect and record the following information each day for this emissions unit;
 - i. the name and identification number of each coating, as applied,
 - ii. VOC content (excluding water and exempt solvents) and the number of gallons (excluding water and exempt solvents) of each coating, as applied, and

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

- iii. the volume-weighted average VOC content of all coatings, as applied, calculated in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for CVOC,².

The permittee shall notify the Toledo Division of Environmental Services, in advance, when daily averaging will be used instead of monthly record keeping. Alternate, equivalent record keeping methods may be used upon written approval by the Toledo Division of Environmental Services.

Alternate, equivalent record_keeping methods may be used upon written approval by the Toledo Division of Environmental Services.

3. The permittee shall maintain daily records that document any periods when the control system was not in service when the emissions unit was in operation.

4. The permittee shall collect and record the following information each month for the purpose of determining the average daily, monthly and annual VOC emissions:
 - a. the name and identification number of each coating, as applied;
 - b. the VOC content of each coating (excluding water and exempt solvents), as applied;
 - c. the number of gallons (excluding water and exempt solvents) of each coating employed;
 - d. the total number of gallons (excluding water and exempt solvents) of all coatings employed, calculated as a summation of the quantities recorded in (c) above;
 - e. the total VOC emissions from all coatings employed, in tons per month;
 - f. the rolling 12-month summation of emissions from all coatings employed, in tons per year;
 - g. the number of days the emissions units was in operation; and
 - h. the daily average VOC emissions rate, (e)/(g), in pounds per day.

C. Reporting Requirements

1. The permittee shall notify the Toledo Division of Environmental Services in writing of any record showing the use of noncomplying coatings. The notification shall include a copy of such record and shall be sent to the Toledo Division of Environmental Services within 30 days following the end of the calendar month.
2. The permittee shall notify the Toledo Division of Environmental Services in writing of any daily record that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Toledo Division of Environmental Services within 30 days after the event occurs.

D. Testing Requirements

1. Compliance with the emission limitation(s) of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation

2.0 pounds VOC per gallon of coating excluding water and exempt solvents.

Applicable Compliance Method

OAC rule 3745-21-10(B). USEPA Methods 24 and 24A shall be used to determine the VOC content. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to section 4.3 of Method 24, 40 CFR Part 60, Appendix A, an owner or operator determines that Method 24 or 24A cannot be used for a particular coating or ink,

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A. Alternative formulation data may be used upon written approval of the Toledo Division of Environmental Services.

b. Emission Limitation

54 tons VOC/year.

Applicable Compliance Method

Use of monthly records of each coating used and the VOC content of each coating used.

c. Emission Limitation

0.63 pound of PM₁₀ per hour and 2.8 tons of PM₁₀ per year.

Applicable Compliance Method

The Monitoring and Record keeping requirements of Section X.B.,3 shall be considered adequate demonstration of compliance.

d. Emission Limitation

5 percent opacity.

Applicable Compliance Method

OAC rule 3745-17-03(B)(1). Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services.

E. Miscellaneous Requirements

1. Should any coating formulations cause a nuisance odor, or process changes cause an increase in the quantity or intensity of odors emitted from this facility, as determined by the Toledo Division of Environmental Services, the company shall take corrective action to reduce the impact of the odors. The time schedule for the corrective action shall be approved by the Toledo Division of Environmental Services.

XII. Interior Touch-up (K029)

A. Operational Restrictions

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

1. The permittee shall install and use hoods, fans, and/or other equipment to adequately enclose, contain, capture, vent and control the fugitive dust.
2. The permittee shall operate the control system whenever this emissions unit is in operation.

B. Monitoring and/or Record Keeping Requirements

1. When using complying coatings (i.e., each coating contains a maximum of 4.8 pounds VOC per gallon, excluding water and exempt solvents), the permittee shall collect and record the following information each month for this emissions unit;
 - i. the name and identification number of each coating, as applied,
 - ii. VOC content (excluding water and exempt solvents) and the number of gallons (excluding water and exempt solvents) of each coating, as applied, and
 - iii. the volume-weighted average VOC content of all coatings, as applied, calculated in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for CVOC,2.
2. When calculating a daily volume-weighted average VOC content, the permittee shall collect and record the following information each day for this emissions unit;
 - i. the name and identification number of each coating, as applied,
 - ii. VOC content (excluding water and exempt solvents) and the number of gallons (excluding water and exempt solvents) of each coating, as applied, and
 - iii. the volume-weighted average VOC content of all coatings, as applied, calculated in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for CVOC,2.

The permittee shall notify the Toledo Division of Environmental Services, in advance, when daily averaging will be used instead of monthly record keeping. Alternate, equivalent record keeping methods may be used upon written approval by the Toledo Division of Environmental Services.

Alternate, equivalent record keeping methods may be used upon written approval by the Toledo Division of Environmental Services.

3. The permittee shall maintain daily records that document any periods when the control system was not in service when the emissions unit was in operation.
4. The permittee shall collect and record the following information each month for the purpose of determining the average daily, monthly and annual VOC emissions:
 - a. the name and identification number of each coating, as applied;
 - b. the VOC content of each coating (excluding water and exempt solvents), as applied;
 - c. the number of gallons (excluding water and exempt solvents) of each coating employed;

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

- d. the total number of gallons (excluding water and exempt solvents) of all coatings employed, calculated as a summation of the quantities recorded in (c) above;
- e. the total VOC emissions from all coatings employed, in tons per month;
- f. the rolling 12-month summation of emissions from all coatings employed, in tons per year;
- g. the number of days the emissions units was in operation; and
- h. the daily average VOC emissions rate, (e)/(g), in pounds per day.

C. Reporting Requirements

- 1. The permittee shall notify the Toledo Division of Environmental Services in writing of any record showing the use of noncomplying coatings. The notification shall include a copy of such record and shall be sent to the Toledo Division of Environmental Services within 45 days after the exceedance occurs.
- 2. The permittee shall notify the Toledo Division of Environmental Services in writing of any daily record that the control system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Toledo Division of Environmental Services within 30 days after the event occurs.

D. Testing Requirements

- 1. Compliance with the emission limitation(s) of these terms and conditions shall be determined in accordance with the following methods(s):
 - a. Emission Limitation

4.8 pounds of VOC per gallon of coating excluding water and exempt solvents.
Applicable Compliance Method

Compliance will be demonstrated through the record keeping requirements of XII.B.
 - b. Emission Limitation

5.6 tons VOC/year.

Applicable Compliance Method

Compliance shall be determined by utilizing the daily records contained in Section XII.B.

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

E. Miscellaneous Requirements

1. None.

XIII. P007, Non-Production Maintenance Materials

A. Operational Restrictions

1. The permittee shall employ only appropriate solvent dispensers, disposal containers and booth cleaning techniques appropriate to minimize evaporation in this emissions unit.

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

2. The emissions of VOC from this emissions unit shall not exceed 514.18 tons per year, as a rolling, 12-month total.

To ensure enforceability during the first 12 calendar months of operation, the permittee shall not exceed the emission levels specified in the following table:

<u>Month(s)</u>	<u>Maximum Allowable Cumulative Emissions (Tons) VOC</u>
1	42
1-2	85
1-3	128
1-4	171
1-5	214
1-6	257
1-7	299
1-8	342
1-9	385
1-10	420
1-11	471
1-12	514.18

After the first 12 calendar months of operation following the issuance of this permit, compliance with the annual emission limitations shall be based upon a rolling, 12-month summation of the monthly emissions.

B. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for the non-production maintenance material operations:
 - a. the company identification for each non-production maintenance material employed;
 - b. the number of gallons of each non-production maintenance material employed;
 - c. the organic compound content of each non-production maintenance material, in pounds per gallon excluding water and exempt solvents; and,
 - d. the monthly emissions of VOC and the rolling, 12-month summation of the monthly emissions.

Alternate, equivalent record_keeping methods may be used upon written approval by the Toledo Division of Environmental Services.

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

C. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports identifying any photochemically reactive non-production maintenance material that was used.

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

2. The permittee shall submit quarterly deviation (excursion) reports that identify records showing that the material used in this emissions unit exceeds the applicable limitation. The notification shall include a copy of such record.

D. Testing Requirements

1. Compliance with the emission limitation(s) of these terms and conditions shall be determined in accordance with the following methods(s):

- a. Emission Limitation

514.18 tons VOC per year, as a rolling, 12-month total.

Applicable Compliance Method

Compliance shall be demonstrated through the record keeping requirements of Additional Special Terms and Conditions XIII.B., and OAC rule 3745-21-10(B). USEPA Methods 24 and 24A shall be used to determine the VOC content. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to section 4.3 of Method 24, 40 CFR Part 60, Appendix A, an owner or operator determines that Method 24 or 24A cannot be used for a particular non-production maintenance material, the permittee shall notify the Administrator of the USEPA and shall use formulation data for that non-production maintenance material to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

E. Miscellaneous Requirements

1. None.

XIV. P008, Sealers and Adhesives

A. Operational Restrictions

1. The permittee shall employ only non-photochemically reactive materials in this emissions unit.
2. The permittee shall employ only dispensers and disposal containers appropriate to minimize exposure times in this emissions unit.

B. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for the sealer and adhesive operations:

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

- a. the company identification for each sealer and adhesive material employed;
- b. a determination of whether each sealer and adhesive material is photochemically reactive or non-photochemically reactive as defined in OAC rule 3745-21-09(C)(5).
- c. the unit quantity of each sealer and adhesive material employed;
- d. the organic compound content of each sealer and adhesive material, in pounds per gallon excluding water and exempt solvents;
- e. the monthly average organic compound content for all sealer and adhesive material, in pounds VOC per gallon excluding water and exempt solvents; and,
- f. the monthly emissions of VOC and the rolling, 12-month summation of the monthly emissions.

Alternate, equivalent recordkeeping methods may be used upon written approval by the Toledo Division of Environmental Services.

C. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports identifying any photochemically reactive sealer or adhesive material that was used.
2. The permittee shall submit quarterly deviation (excursion) reports that identify records showing that the material used in this emissions unit exceeds the applicable limitation. The notification shall include a copy of such record.

D. Testing Requirements

1. Compliance with the emission limitation(s) of these terms and conditions shall be determined in accordance with the following methods(s):
 - a. Emission Limitation

0.5 pound VOC per gallon of sealer and adhesive material excluding water and exempt solvents as a monthly average.

Applicable Compliance Method

OAC rule 3745-21-10(B). USEPA Methods 24 and 24A shall be used to determine the VOC content. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to section 4.3 of Method 24, 40 CFR Part 60, Appendix A, an owner or operator determines that Method 24 or 24A cannot be used for a particular

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

non-production maintenance material, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that non-production maintenance material to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A. Alternative, formulation data may be used upon approval by the Toledo Division of Environmental Services.

b. Emission Limitation

55.06 tons VOC/year.

Applicable Compliance Method

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

Use of monthly records of each sealer and adhesive used and the VOC content of each sealer and adhesive used.

c. Emission Limitation

Employ only non-photochemically reactive materials.

Applicable Compliance Method

Exclusion of materials meeting the definition in OAC 3745-21-01(C)(5).

E. Miscellaneous Requirements

1. None.

XV. P009, Miscellaneous Solvents, solvent body wipes and plantwide use of other non-photochemically reactive solvents

A. Operational Restrictions

1. The permittee shall employ only non-photochemically reactive materials in this emissions unit.
2. The permittee shall employ only dispensers and disposal containers appropriate to minimize exposure times.
3. The emissions of VOC from this emissions unit shall not exceed 52.28 tons per year, as a rolling, 12-month total.

Compliance with the annual emission limitations shall be based upon a rolling, 12-month summation of the monthly emissions.

B. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for the solvent body wipes operations:
 - a. the company identification for each solvent employed;
 - b. a determination of whether each solvent is photochemically reactive or non-photochemically reactive as defined in OAC rule 3745-21-09(C)(5).
 - c. the number of gallons of each solvent employed;

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

- d. the organic compound content of each solvent, in pounds per gallon excluding water and exempt solvents; and,
- e. the monthly emissions of VOC and the rolling, 12-month summation of the monthly emissions.

Alternate, equivalent record_keeping methods may be used upon written approval by the Toledo Division of Environmental Services.

C. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports identifying any photochemically reactive sealer or adhesive material that was used.
2. The permittee shall submit quarterly deviation (excursion) reports that identify records showing that the material used in this emissions unit exceeds the applicable limitation. The notification shall include a copy of such record.

D. Testing Requirements

1. Compliance with the emission limitation(s) of these terms and conditions shall be determined in accordance with the following methods(s):

- a. Emission Limitation

52.28 tons VOC per year, as a rolling, 12-month total.

Applicable Compliance Method

Compliance shall be demonstrated through the record_keeping requirements of Additional Special Terms and Conditions XV.B., and OAC rule 3745-21-10(B). USEPA Methods 24 and 24A shall be used to determine the VOC content. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to section 4.3 of Method 24, 40 CFR Part 60, Appendix A, an owner or operator determines that Method 24 or 24A cannot be used for a particular non-production maintenance material, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that non-production maintenance material to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A. Alternative, formulation data may be used upon approval by the Toledo Division of Environmental Services.

- b. Emission Limitation

Employ only non-photochemically reactive materials.

Applicable Compliance Method

Exclusion of materials meeting the definition in OAC 3745-21-01(C)(5).

E. Miscellaneous Requirements

1. None.

XVI. P010, Miscellaneous Solvents, plantwide use of photochemically reactive solvents

A. Operational Restrictions

1. The permittee shall employ only dispensers and disposal containers appropriate to minimize exposure times.

B. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information for each day for the coating operation:
 - a. the company identification for each photochemically reactive cleanup material employed;
 - b. the number of gallons of each photochemically reactive cleanup material employed;
 - c. the organic compound content of each photochemically reactive cleanup material, in pounds per gallon;
 - d. the total organic compound emission rate for all photochemically reactive cleanup materials, in pounds per day;
 - e. the total number of hours the emissions unit was in operation;
 - f. the average hourly organic compound emission rate for all photochemically reactive cleanup materials, i.e., (d)/(e), in pounds per hour (average); and,
 - g. the monthly emissions of OC and the rolling, 12-month summation of the monthly emissions.

Alternate, equivalent record_keeping methods may be used upon written approval by the Toledo Division of Environmental Services.

C. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports which include the following information:
 - a. an identification of each day during which the average hourly organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day; and,
 - b. an identification of each day during which the organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 40 pounds per day, and the actual organic

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

compound emissions for each such day.

D. Testing Requirements

1. Compliance with the emission limitation(s) in Section XVI.A.1. of these Additional Special Terms and Conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation

8 pounds of VOC per hour and 40 pounds of VOC per day.

Applicable Compliance Method

OAC rules 3745-21-09(B) and 3745-21-10(C). USEPA Methods 24 and 24A shall be used to determine the VOC content. Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services. If, pursuant to section 4.3 of Method 24, 40 CFR Part 60, Appendix A, an owner or operator determines that Method 24 or 24A cannot be used for a particular non-production maintenance material, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that non-production maintenance material to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A. Compliance shall be demonstrated through the recordkeeping requirements of Additional Special Terms and Conditions XVI.B.

- b. Emission Limitation

5.1 tons VOC/year.

Applicable Compliance Method

Compliance shall be demonstrated through the record_keeping requirements of Additional Special Terms and Conditions XVI.B.

E. Miscellaneous Requirements

1. None.

XVII. Additional terms for make up air units which are >10 MMBtu/hr & natural gas direct fired, B011 to B031

A. Operational Restrictions

1. The permittee shall restrict the fuel burned in this emissions unit to natural gas having a heat content greater than 950 Btu per standard cubic foot and a sulfur content less than 0.6 pound per million standard cubic feet.

B. Monitoring and/or Record Keeping Requirements

1. None.

C. Reporting Requirements

1. None.

D. Testing Requirements

1. Compliance with the emission limitation(s) in Section XVII.A.1. of these Additional Special Terms and

Conditions shall be determined in accordance with the following methods(s):

- a. Emission Limitation

Natural gas having a heat content greater than 950 Btu per standard cubic foot and a sulfur content less than 0.6 pound per million standard cubic feet.

Applicable Compliance Method

The exclusive use of commercially available natural gas will be considered adequate demonstration of compliance.

- b. Emission Limitation

0.02 pound of carbon monoxide emissions per MMBtu actual heat input.

Applicable Compliance Method

Compliance shall be based upon an emission factor of 0.02 pound/MMBtu (20 lb/mmscf / 1020 Btu/scf). This emission factor is specified in USEPA FIRE software v6.24 .

- c. Emission Limitation

0.1 0.1 pound of nitrogen oxides emissions per MMBtu actual heat input.

Applicable Compliance Method

Compliance shall be based upon an emission factor of 0.1 pound/MMBtu (100 lb/mmscf / 1020 Btu/scf). This emission factor is specified in USEPA FIRE software v6.24 .

- d. Emission Limitation

0.0052 pound of VOC emissions per MMBtu actual heat input.

Applicable Compliance Method

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

Compliance shall be based upon an emission factor of 0.0052 pound/MMBtu (5.3 lb/mmcf / 1020 Btu/scf). This emission factor is specified in USEPA FIRE software v6.24.

E. Miscellaneous Requirements

1. None.

XVIII. P011, BIW Inspection and Grinding

A. Operational Restrictions

1. Visible particulate emissions shall not exceed 20 percent opacity, except for a period of time not to exceed three minutes during any 60-minute observation period.
2. The permittee shall install and use hoods, fans, and/or other equipment to adequately enclose, contain, capture, vent and control the fugitive dust.

B. Monitoring and/or Record Keeping Requirements

1. None.

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

C. Reporting Requirements

1. None.

D. Testing Requirements

1. Compliance with the emission limitation(s) in Section XVIII.A.1. of these Additional Special Terms and Conditions shall be determined in accordance with the following methods(s):

- a. Emission Limitation

Adequate enclosure and control.

Applicable Compliance Method

Collection efficiency sufficient to minimize or eliminate visible particulate: OAC rule 3745-17-08(C)(1), and 0.030 grain of particulate emissions per dry standard cubic foot of exhaust gases or there are no visible particulate emissions: OAC rule 3745-17-03(B). Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services.

- b. Emission Limitation

20 percent opacity, except for a period of time not to exceed three minutes.

Applicable Compliance Method

OAC rule 3745-17-03(B)(3). Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services.

- c. Emission Limitation

0.48 pound PM₁₀/hour and 2.1 tons PM₁₀/year.

Applicable Compliance Method

Compliance with the adequate enclosure and control, and opacity limitations will be considered adequate demonstration of compliance.

E. Miscellaneous Requirements

1. None.

XIX. P012, Finish Welding

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

A. Operational Restrictions

1. Visible particulate emissions shall not exceed 20 percent opacity, except for a period of time not to exceed three minutes during any 60-minute observation period.
2. The permittee shall install and use hoods, fans, and/or other equipment to adequately enclose, contain, capture, vent and control the fugitive dust.

B. Monitoring and/or Record Keeping Requirements

1. None.

C. Reporting Requirements

1. None.

D. Testing Requirements

1. Compliance with the emission limitation(s) in Section XIX.A.1. of these Additional Special Terms and Conditions shall be determined in accordance with the following methods(s):

a. Emission Limitation

Adequate enclosure and control.
Applicable Compliance Method

Collection efficiency sufficient to minimize or eliminate visible particulate: OAC rule 3745-17-08(C)(1), and 0.030 grain of particulate emissions per dry standard cubic foot of exhaust gases or there are no visible particulate emissions: OAC rule 3745-17-03(B). Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services.

b. Emission Limitation

20 percent opacity, except for a period of time not to exceed three minutes.

Applicable Compliance Method

OAC rule 3745-17-03(B)(3). Alternate, equivalent methods may be used upon approval by the Toledo Division of Environmental Services.

c. Emission Limitation

0.56 pound PM₁₀/hour and 2.4 tons PM₁₀/year.

Applicable Compliance Method

Compliance with the adequate enclosure and control, and opacity limitations will be considered adequate demonstration of compliance.

E. Miscellaneous Requirements

1. None.

XX. F001, Plant Roadways and Parking Areas

A. Additional Terms and Conditions

1. All roadways and parking areas shall be paved.
2. The paved roadways and parking areas that are covered by this permit and subject to the requirements of OAC rules 3745-17-07 and 3745-17-08 are listed below:

Paved roadways:

Loop Road,
T/C/F Avenue 3,
Paint Avenue 4,
Body Avenue 5,
Office Road - Existing Plant.

Paved parking areas:

Truck marshalling Lot A,
Truck marshalling Lot B,
North Parking Lot,
South Parking Lot,
West Parking Lot,
Visitor Parking Lot
Shipping Lot A
Shipping Lot B

3. Upon start-up, the permittee shall employ best available control measures on all paved roadways and parking areas for the purpose of ensuring compliance with the above-mentioned applicable requirements. The permittee shall treat the paved roadways and parking areas by flushing with water, sweeping, and/or watering at sufficient treatment frequencies to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.
4. The permittee shall promptly remove, in such a manner as to minimize or prevent resuspension, earth and/or other material from paved streets onto which such material has been deposited by trucking or earth moving equipment or erosion by water or other means.

DaimlerChrysler Corp
PTI Application: 04-01102
Modification Issued: 9/8/2005

Facility ID: **0448010414**

5. The needed frequencies of implementation of the control measures shall be determined by the permittee's inspections pursuant to the monitoring section of this permit. Implementation of the control measures shall not be necessary for a paved or unpaved roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Implementation of any control measure may be suspended if unsafe or hazardous driving conditions would be created by its use.
6. Open-bodied vehicles transporting materials likely to become airborne shall have such materials covered at all times if the control measure is necessary for the materials being transported.

B. Operational Restrictions

1. No visible particulate emissions except for 1 minute during any 60-minute period for paved roadways and parking areas.

C. Monitoring and/or Record Keeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform inspections of the roadways and parking areas in accordance with the following frequencies:

<u>paved roadways and parking areas</u>	<u>minimum inspection frequency</u>
all	weekly

The purpose of the inspections is to determine the need for implementing the control measures specified in Section A.2. The inspections shall be performed during representative, normal traffic conditions. No inspection shall be necessary for a roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above-identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.

The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.

2. The permittee shall maintain records of the following information for a minimum of five years:
 - a. the date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;
 - b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;
 - c. the dates the control measures were implemented; and,
 - d. on a calendar quarter basis, the total number of days the control measures were implemented and the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measures.

The information required in Section XX.C.2.d shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify any of the following occurrences:
 - a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and,
 - b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section XX.B.1 of the Additional Special Terms and Conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation

No visible particulate emissions except for 1 minute during any 60-minute period for paved roadways and parking areas.

Applicable Compliance Method

Compliance with these emissions limitations shall be demonstrated through the monitoring and record keeping requirements of Sections XX.C. If required, compliance shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 "Standards of Performance for New Stationary Sources," as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(d) of OAC rule 3745-17-03.

- b. Emission Limitation

0.32 pounds PM₁₀/hour and 1.4 tons PM₁₀/year.

Applicable Compliance Method

Compliance with the paving, sweeping, adequate moisture and opacity limitations will be considered adequate demonstration of compliance.

F. Miscellaneous Requirements

None.