



State of Ohio Environmental Protection Agency

Street Address:

Mailing Address:

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Lazarus Gov. Center

RE: DRAFT PERMIT TO INSTALL CERTIFIED MAIL
LUCAS COUNTY
Application No: 04-01294

DATE: 5/9/2002

C n C Concrete n Supply Co.
Kenneth Mikolas
2724 Avondale Ave.
Toledo, OH 43607

You are hereby notified that the Ohio Environmental Protection Agency has made a draft action recommending that the Director issue a Permit to Install for the air contaminant source(s) [emissions unit(s)] shown on the enclosed draft permit. This draft action is not an authorization to begin construction or modification of your emissions unit(s). The purpose of this draft is to solicit public comments on the proposed installation. A public notice concerning the draft permit will appear in the Ohio EPA Weekly Review and the newspaper in the county where the facility will be located. Public comments will be accepted by the field office within 30 days of the date of publication in the newspaper. Any comments you have on the draft permit should be directed to the appropriate field office within the comment period. A copy of your comments should also be mailed to Robert Hodanbosi, Division of Air Pollution Control, Ohio EPA, P.O. Box 1049, Columbus, OH, 43266-0149.

A Permit to Install may be issued in proposed of final form based on the draft action, any written public comments received within 30 days of the public notice, or record of a public meeting if one is held. You will be notified in writing of a scheduled public meeting. Upon issuance of a final Permit to Install a fee of \$4800 will be due. Please do not submit any payment now.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469. If you have any questions about this draft permit, please contact the field office where you submitted your application, or Mike Ahern, Field Operations & Permit Section at (614) 644-3631.

Very truly yours,
Thomas G. Rigo

Thomas G. Rigo, Manager
Field Operations and Permit Section
Division of Air Pollution Control

CC: USEPA TDES Toledo Metro Area Council of Gov. IN MI



STATE OF OHIO ENVIRONMENTAL PROTECTION AGENCY

**Permit To Install  
Terms and Conditions**

**Issue Date: To be entered upon final issuance  
Effective Date: To be entered upon final issuance**

**DRAFT PERMIT TO INSTALL 04-01294**

Application Number: 04-01294  
APS Premise Number: 0448011713  
Permit Fee: **To be entered upon final issuance**  
Name of Facility: C n C Concrete n Supply Co.  
Person to Contact: Kenneth Mikolas  
Address: 2724 Avondale Ave.  
Toledo, OH 43607

Location of proposed air contaminant source(s) [emissions unit(s)]:  
**2724 Avandale Ave.  
Toledo, Ohio**

Description of proposed emissions unit(s):  
**Concrete batch plant.**

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

---

Director

**Part I - GENERAL TERMS AND CONDITIONS**

**A. Permit to Install General Terms and Conditions**

**1. Compliance Requirements**

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

**2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements**

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

**3. Records Retention Requirements**

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

**4. Inspections and Information Requests**

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any

**C n C Concrete n Supply Co.**

**Facility ID: 0448011713**

**PTI Application: 04-01294**

**Issued: To be entered upon final issuance**

information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

**5. Scheduled Maintenance/Malfunction Reporting**

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

**6. Permit Transfers**

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

**7. Air Pollution Nuisance**

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

**8. Termination of Permit to Install**

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

**9. Construction of New Sources(s)**

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may

lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

**10. Public Disclosure**

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

**11. Applicability**

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit to Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

**12. Best Available Technology**

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

**13. Source Operation and Operating Permit Requirements After Completion of Construction**

- a. If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule

C n C Concrete n Supply Co.

Facility ID: 0448011713

PTI Application: 04-01294

Issued: To be entered upon final issuance

3745-77-08(C)(3)(d).

- b. If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35, the source(s) identified in this Permit To Install is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within thirty (30) days after commencing operation of the source(s) covered by this permit.

**14. Construction Compliance Certification**

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

**15. Fees**

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

**B. Permit to Install Summary of Allowable Emissions**

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)  
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
PE	6.0

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	OAC rule 3745-17-08 (B), (B)(6)
F001 - load-in and load-out of storage piles (see Section A.2.a for identification of storage piles)	OAC rule 3745-31-05 (A)(3)	
wind erosion from storage piles (see Section A.2.a for identification of storage piles)	OAC rule 3745-31-05 (A)(3)	
load-in and load-out of storage piles, and wind erosion from storage piles	OAC rule 3745-31-05 (A)(3) OAC rule 3745-31-05 (D) OAC rule 3745-17-07 (B)(6)	

C n C

PTI /

Emissions Unit ID: **F001**

**Issued: To be entered upon final issuance**

Applicable Emissions  
Limitations/Control Measures

pursuant to OAC rule  
3745-31-05(A)(3).

no visible emissions except for one  
minute in any hour

1.58 pounds of fugitive particulate  
emissions (PE) per hour

best available control measures that  
are sufficient to minimize or  
eliminate visible emissions of  
fugitive dust (see Sections A.2.b,  
A.2.c and A.2.f)

no visible emissions except for one  
minute in any hour

0.07 pound of fugitive PE per hour

best available control measures that  
are sufficient to minimize or  
eliminate visible emissions of  
fugitive dust (see Sections A.2.d  
through A.2.f)

1.08 tons of PE per calendar year

See Section A.2.h

The emission limitation specified by  
this rule is less stringent than the  
emission limitation established  
pursuant to OAC rule  
3745-31-05(A)(3).

The emission limitation specified by  
this rule is less stringent than the  
emission limitation established

**Issued: To be entered upon final issuance****2. Additional Terms and Conditions**

- 2.a** The storage piles that are covered by this permit and subject to the above-mentioned requirements are listed below:

Limestone storage pile

Sand storage pile

- 2.b** The permittee shall employ best available control measures on all load-in and load-out operations associated with the storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to treat the load-in and load-out material(s) with water and to maintain a wind guard enclosure to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.
- 2.c** The above-mentioned control measure(s) shall be employed for each load-in and load-out operation of each storage pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) are necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measure(s) shall continue during any such operation until further observation confirms that use of the measure(s) is unnecessary.
- 2.d** The permittee shall employ best available control measures for wind erosion from the surfaces of all storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to treat the storage pile with water and to maintain a wind guard enclosure to ensure compliance to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.
- 2.e** The above-mentioned control measure(s) shall be employed for wind erosion from each pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) are necessary to ensure compliance with the above-mentioned applicable requirements. Implementation of the control measure(s) shall not be necessary for a storage pile that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements.

Issue

Emissions Unit ID: F001

- 2.f Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the requirements of OAC rules 3745-17-08 and 3745-31-05.
- 2.g The maximum annual production rate for this emissions unit shall not exceed 100,000 cubic yards of concrete.
- 2.h The hourly emissions limitations outlined above are based upon the emission unit's potential to emit (PTE). Therefore, no hourly records are required to demonstrate compliance with these limits.

**B. Operational Restrictions**

None

**C. Monitoring and/or Recordkeeping Requirements**

- 1. Except as otherwise provided in this section, the permittee shall perform inspections of each load-in operation at each storage pile in accordance with the following frequencies:

<u>storage pile identification</u>	<u>minimum load-in inspection frequency</u>
limestone	daily
sand	daily

- 2. Except as otherwise provided in this section, the permittee shall perform inspections of each load-out operation at each storage pile in accordance with the following frequencies:

<u>storage pile identification</u>	<u>minimum load-out inspection frequency</u>
limestone	daily
sand	daily

- 3. Except as otherwise provided in this section, the permittee shall perform inspections of the wind erosion from pile surfaces associated with each storage pile in accordance with the following frequencies:

<u>storage pile identification</u>	<u>minimum wind erosion inspection frequency</u>
limestone	daily

C n C

PTI /

Emissions Unit ID: **F001**

**Issued: To be entered upon final issuance**

sand

daily

4. No inspection shall be necessary for wind erosion from the surface of a storage pile when the pile is covered with snow and/or ice and for any storage pile activity if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.
5. The purpose of the inspections is to determine the need for implementing the control measures specified in this permit for load-in and load-out of a storage pile, and wind erosion from the surface of a storage pile. The inspections shall be performed during representative, normal storage pile operating conditions.
6. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.
7. The permittee shall maintain records of the following information:
  - a. the date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;
  - b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures; and
  - c. the dates the control measures were implemented..
  - d. The permittee shall maintain annual records of the quantity, in cubic yards, of concrete produced in this emissions unit.

#### **D. Reporting Requirements**

1. The permittee shall submit deviation reports that identify any of the following occurrences:
  - a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and
  - b. each instance when a control measure, that was to be implemented as a result of an

inspection, was not implemented.

c. any exceedances of the annual production rate limitation.

2. These reports shall be submitted within 30 days of discovery.

#### E. Testing Requirements

1. Compliance with the allowable emission limitations in this permit shall be determined according to the following methods:

a. Emission Limitation;

no visible emissions except for one minute in any hour

Applicable Compliance Method;

Compliance with the visible emission limitations for the storage piles identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

b. Emission Limitation;

1.58 pounds of particulate emissions (PE) per hour.

Applicable Compliance Method;

Compliance may be determined through calculations based on emission factors specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 11.12-3 dated 10/01, as follows: sum the emission factors of; 0.0064 pound of PE per cubic yard of concrete for aggregate delivery to ground storage, 0.0015 pound of PE per cubic yard of concrete for sand delivery to ground storage, 0.0064 pound of PE per cubic yard of concrete for aggregate transfer to elevated storage and 0.0015 pound of PE per cubic yard of concrete for sand transfer to elevated storage, and multiply this summation by the design maximum throughput capacity of 100 cubic yards per hour.

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Method 5 of 40 CFR Part 60 Appendix A using the methods and procedures specified in OAC rule 3745-17-03(B)(7).

c. Emission Limitation;

C n C

PTI /

Emissions Unit ID: **F001**

**Issued: To be entered upon final issuance**

0.07 pound of particulate emissions (PE) per hour.

Applicable Compliance Method;

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Method 5 of 40 CFR Part 60 Appendix A using the methods and procedures specified in OAC rule 3745-17-03(B)(7).

C n C

PTI /

Emissions Unit ID: **F001**

**Issued: To be entered upon final issuance**

d. Emission Limitation;

1.08 tons of PE per calendar year

Applicable Compliance Method;

This limitation represents the full potential to emit for this emissions unit operating at the maximum annual allowable throughput rate. Therefore, provided compliance is shown with the annual allowable throughput limitation, and compliance is also shown with the short term emissions limitations above, compliance shall also be shown with the annual emission limitation.

**F. Miscellaneous Requirements**

None

C n C

PTI /

Emissions Unit ID: **F002**

**Issued: To be entered upon final issuance**

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
F002 - Concrete batch plant: transfer of sand and aggregate to elevated bins with no control	OAC rule 3745-31-05(A)(3)	OAC rule 3745-17-08(B)
cement unloading to elevated storage bins controlled by fabric filters	OAC rule 3745-31-05(A)(3)	
	OAC rule 3745-17-07(B)(1)	

Applicable Emissions  
Limitations/Control Measures

no visible emissions except for one  
minute in any hour

0.79 pound of fugitive particulate  
emissions (PE) per hour

0.40 ton of PE per calendar year

best available control measures that  
are sufficient to minimize or  
eliminate visible emissions of  
fugitive dust (see A.2.b through  
A.2.d)

no visible emissions from the  
baghouse exhaust stack

0.05 pound of PE per hour

0.02 ton of PE per calendar year

best available control measures that  
are sufficient to minimize or  
eliminate visible emissions of  
fugitive dust (see A.2.b through  
A.2.d)

The emission limitation specified by  
this rule is less stringent than the  
emission limitation established  
pursuant to OAC rule  
3745-31-05(A)(3).

The emission limitation specified by  
this rule is less stringent than the  
emission limitation established  
pursuant to OAC rule  
3745-31-05(A)(3).

Issued: To be entered upon final issuance

**2. Additional Terms and Conditions**

**2.a** The material handling operation(s) that are covered by this permit and subject to the above-mentioned requirements are listed below:

transfer of sand and aggregate to elevated bins, and  
cement unloading to elevated storage bins controlled by fabric filters

**2.b** The permittee shall employ best available control measures for the above-identified material handling operation(s) for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to perform the following control measure(s) to ensure compliance:

<u>material handling operation(s)</u>	<u>control measure(s)</u>
transfer of sand and aggregate to elevated bins	partial enclosure adequate moisture
cement unloading to elevated storage bins	fabric filters

Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

**2.c** For each material handling operation that is not adequately enclosed, the above-identified control measure(s) shall be implemented if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) is (are) necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measure(s) shall continue during the operation of the material handling operation(s) until further observation confirms that use of the control measure(s) is unnecessary.

**2.d** Implementation of the above-mentioned control measure(s) in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the requirements of OAC rules 3745-17-08 and 3745-31-05.

**2.e** The maximum annual production rate for this emissions unit shall not exceed 100,000 cubic yards of concrete.

C n C

PTI /

Emissions Unit ID: **F002**

**Issued: To be entered upon final issuance**

- 2.f** The hourly emissions limitations outlined above are based upon the emission unit's potential to emit (PTE). Therefore, no hourly records are required to demonstrate compliance with these limits.

**B. Operational Restrictions**

None

**C. Monitoring and/or Recordkeeping Requirements**

1. Except as otherwise provided in this section, for material handling operations that are not adequately enclosed, the permittee shall perform inspections of such operations in accordance with the following minimum frequencies:

<u>material handling operation(s)</u>	<u>minimum inspection frequency</u>
transfer of sand to elevated bins	daily
transfer of aggregate to elevated bins	daily
cement unloading to elevated storage bins	daily

2. The above-mentioned inspections shall be performed during representative, normal operating conditions.
3. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.
4. The permittee shall maintain records of the following information:
- a. the date and reason any required inspection was not performed;
  - b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measure(s); and
  - c. the dates the control measure(s) was (were) implemented.
5. The permittee shall maintain annual records of the quantity, in cubic yards, of concrete produced in this emissions unit.

**D. Reporting Requirements**

**C n C Concrete n Supply Co.**

**PTI A-04-01004**

**Issue**

**Facility ID: 0448011713**

**Emissions Unit ID: F002**

1. The permittee shall submit deviation reports that identify any of the following occurrences:

C n C

PTI /

Emissions Unit ID: **F002**

**Issued: To be entered upon final issuance**

- a. each day during which an inspection was not performed by the required frequency; and
  - b. each instance when a control measure, that was to be performed as a result of an inspection, was not implemented.
  - c. any exceedances of the annual production rate limitation.
2. These reports shall be submitted within 30 days of discovery.

**E. Testing Requirements**

1. Compliance with the allowable emission limitations in this permit shall be determined according to the following methods:

- a. Emission Limitation;

no visible emissions except for one minute in any hour

Applicable Compliance Method;

Compliance with the visible emission limitations for the storage piles identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

- b. Emission Limitation;

0.79 pound of particulate emissions (PE) per hour.

Applicable Compliance Method;

Compliance may be determined through calculations based on emission factors specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 11.12-3 dated 10/01, as follows: sum the emission factors of; 0.0064 pound of PE per cubic yard of concrete for aggregate transfer to elevated storage and 0.0015 pound of PE per cubic yard of concrete for sand transfer to elevated storage, and multiply this summation by the design maximum throughput capacity of 100 cubic yards of concrete per hour.

If required, the permittee shall demonstrate compliance with this emission limitation through

C n C

PTI /

Emissions Unit ID: **F002**

**Issued: To be entered upon final issuance**

emission testing performed in accordance with Method 5 of 40 CFR Part 60 Appendix A using the methods and procedures specified in OAC rule 3745-17-03(B)(7).

C n C

PTI /

Emissions Unit ID: **F002**

**Issued: To be entered upon final issuance**

- c. Emission Limitation;

0.40 ton of PE per calendar year

Applicable Compliance Method;

This limitation represents the full potential to emit for this emissions unit operating at the maximum annual allowable throughput rate. Therefore, provided compliance is shown with the annual allowable throughput limitation, and compliance is also shown with the short term emissions limitations above, compliance shall also be shown with the annual emission limitation.

- d. Emission Limitation;

no visible emissions from the stack

Applicable Compliance Method;

Compliance with the visible emission limitations for the storage piles identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

- e. Emission Limitation;

0.05 pound of particulate emissions (PE) per hour.

Applicable Compliance Method;

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Method 5 of 40 CFR Part 60 Appendix A using the methods and procedures specified in OAC rule 3745-17-03(B)(10).

- f. Emission Limitation;

0.02 ton of PE per calendar year

Applicable Compliance Method;

This limitation represents the full potential to emit for this emissions unit operating at the

C n C

PTI /

Emissions Unit ID: **F002**

**Issued: To be entered upon final issuance**

maximum annual allowable throughput rate. Therefore, provided compliance is shown with the annual allowable throughput limitation, and compliance is also shown with the short term emissions limitations above, compliance shall also be shown with the annual emission limitation.

**F. Miscellaneous Requirements**

None

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
F003 - Concrete batch plant: weigh hopper and mixer loading of cement, sand and aggregate	OAC rule 3745-31-05 (A)(3)	no visible particulate emissions except for one minute in any hour  6.6 pounds of particulate emissions (PE) per hour  3.3 tons of PE per calendar year  best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see A.2.b through A.2.d)
	OAC rule 3745-17-07 (B)(1)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-08 (B)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

**2. Additional Terms and Conditions**

- 2.a The material handling operation(s) that are covered by this permit and subject to the above-mentioned requirements are listed below:

weigh hopper and mixer loading of cement, sand and aggregate

**Issued: To be entered upon final issuance**

- 2.b** The permittee shall employ best available control measures for the above-identified material handling operation(s) for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to perform the following control measure(s) to ensure compliance:

<u>material handling operation(s)</u>	<u>control measure(s)</u>
weigh hopper loading of cement, sand and aggregate	fabric filter
mixer loading of cement, sand and aggregate	telescopic boot and curtains

Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

- 2.c** For each material handling operation that is not adequately enclosed, the above-identified control measure(s) shall be implemented if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) is (are) necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measure(s) shall continue during the operation of the material handling operation(s) until further observation confirms that use of the control measure(s) is unnecessary.
- 2.d** Implementation of the above-mentioned control measure(s) in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the requirements of OAC rules 3745-17-08 and 3745-31-05.
- 2.e** The maximum annual production rate for this emissions unit shall not exceed 100,000 cubic yards of concrete.
- 2.f** The hourly emissions limitations outlined above are based upon the emission unit's potential to emit (PTE). Therefore, no hourly records are required to demonstrate compliance with these limits.

## **B. Operational Restrictions**

None

## **C. Monitoring and/or Recordkeeping Requirements**

1. Except as otherwise provided in this section, for material handling operations that are not adequately enclosed, the permittee shall perform inspections of such operations in accordance with

**C n C**  
**PTI /**

**Issued: To be entered upon final issuance**  
the following minimum frequencies:

Emissions Unit ID: **F003**

C n C

PTI /

Emissions Unit ID: **F003**

**Issued: To be entered upon final issuance**

<u>material handling operation(s)</u>	<u>minimum inspection frequency</u>
---------------------------------------	-------------------------------------

weigh hopper loading of cement, sand and aggregate	daily
mixer loading of cement, sand and aggregate	daily

2. The above-mentioned inspections shall be performed during representative, normal operating conditions.
3. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.
4. The permittee shall maintain records of the following information:
  - a. the date and reason any required inspection was not performed;
  - b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measure(s): and
  - c. the dates the control measure(s) was (were) implemented.
5. The permittee shall maintain annual records of the quantity, in cubic yards, of concrete produced in this emissions unit.

**D. Reporting Requirements**

1. The permittee shall submit deviation reports that identify any of the following occurrences:
  - a. each day during which an inspection was not performed by the required frequency; and
  - b. each instance when a control measure, that was to be performed as a result of an inspection, was not implemented.
  - c. any exceedances of the annual production rate limitation.
2. These reports shall be submitted within 30 days of discovery.

**E. Testing Requirements**

1. Compliance with the allowable emission limitations in this permit shall be determined according to

the following methods:

- a. Emission Limitation;

no visible emissions except for one minute in any hour

Applicable Compliance Method;

Compliance with the visible emission limitations for the storage piles identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

- b. Emission Limitation;

6.6 pounds of particulate emissions (PE) per hour.

Applicable Compliance Method;

Compliance may be determined through calculations based on emission factors specified in USEPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Table 11.12-3 dated 10/01, as follows: sum the emission factors of; 0.0079 pound of PE per cubic yard of concrete for weigh hopper loading and 0.058 pound of PE per cubic yard of concrete for controlled mix truck loading, and multiply this summation by the design maximum throughput capacity of 100 cubic yards per hour.

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Method 5 of 40 CFR Part 60 Appendix A using the methods and procedures specified in OAC rule 3745-17-03(B)(7).

- c. Emission Limitation;

3.3 tons of PE per calendar year

Applicable Compliance Method;

This limitation represents the full potential to emit for this emissions unit operating at the maximum annual allowable throughput rate. Therefore, provided compliance is shown with the annual allowable throughput limitation, and compliance is also shown with the short term emissions limitations above, compliance shall also be shown with the annual emission limitation.

## F. Miscellaneous Requirements

**C n C**

**PTI /**

**Issued: To be entered upon final issuance**

Emissions Unit ID: **F003**

None

Issued: To be entered upon final issuance

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
F004 - Concrete batch plant: roadways and parking lots (see A.2.a)	OAC rule 3745-31-05(A)(3)	no visible particulate emissions except for one minute during any 60-minute period  1.19 tons of particulate emissions (PE) per year  best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see A.2.c, and A.2.e through A.2.i)
	OAC rule 3745-17-07(B)(4)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-08(B), (B)(8), (B)(9)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

**2. Additional Terms and Conditions**

- 2.a** The paved roadways and parking areas that are covered by this permit and subject to the above-mentioned requirements are listed below:
- paved roadways:
- Main roadway
- paved parking areas:
- Main parking area
- 2.b** The permittee shall employ best available control measures on all paved roadways and parking areas for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to treat the paved roadways and parking areas by flushing with water, sweeping, and/or watering at sufficient treatment frequencies to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance. (Note that "water flushing" refers to using large quantities of water to carry off surface material, while "watering" refers to simply wetting the surface material.)
- 2.c** The needed frequencies of implementation of the control measures shall be determined by the permittee's inspections pursuant to the monitoring section of this permit. Implementation of the control measures shall not be necessary for a paved roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Implementation of any control measure may be suspended if unsafe or hazardous driving conditions would be created by its use.
- 2.d** The permittee shall promptly remove, in such a manner as to minimize or prevent resuspension, earth and/or other material from paved streets onto which such material has been deposited by trucking or earth moving equipment or erosion by water or other means.
- 2.e** Open-bodied vehicles transporting materials likely to become airborne shall have such materials covered at all times if the control measure is necessary for the materials being transported.
- 2.f** Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the best available technology requirements of OAC rule 3745-31-05.
- 2.g** The maximum annual production rate for this emissions unit shall not exceed 100,000 cubic yards of concrete.

**B. Operational Restrictions**

**C n C**

**PTI /**

**Issued: To be entered upon final issuance**

Emissions Unit ID: **F004**

None

Issued: To be entered upon final issuance

### C. Monitoring and/or Recordkeeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform inspections of the paved roadways and parking areas in accordance with the following frequencies:

<u>paved roadways</u>	<u>minimum inspection frequency</u>
-----------------------	-------------------------------------

Main roadway	daily
--------------	-------

<u>paved parking areas</u>	<u>minimum inspection frequency</u>
----------------------------	-------------------------------------

Main parking lot	daily
------------------	-------

2. The purpose of the inspections is to determine the need for implementing the above-mentioned control measures. The inspections shall be performed during representative, normal traffic conditions. No inspection shall be necessary for a roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above-identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.
3. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.
4. The permittee shall maintain records of the following information:
  - a. the date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;
  - b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures; and
  - c. the dates the control measures were implemented.
5. The permittee shall maintain annual records of the quantity, in cubic yards, of concrete produced in this emissions unit.

### D. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:
  - a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and
  - b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.
  - c. any exceedances of the annual production rate limitation.
2. These reports shall be submitted within 30 days of discovery.

**E. Testing Requirements**

1. Compliance with the emission limitation for the paved roadways and parking areas identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources," as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(d) of OAC rule 3745-17-03.
2. The 1.19 tons of PE per year emission limitation was established by multiplying the 1.98 pounds per vehicle mile traveled emission rate predicted by Equation #1 in AP-42 Section 13.2.1.3 dated 10/97 by the number of miles traveled to load-out a maximum annual through-put of 100,000 cubic yards of concrete (1200 miles), and dividing by 2000 pounds per ton. Therefore, provided compliance is shown with the annual through-put limitation, compliance shall also be shown with the annual emission limitation.

**F. Miscellaneous Requirements**

None