



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL
LUCAS COUNTY**

CERTIFIED MAIL

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049

Application No: 04-01324

DATE: 6/10/2003

Keystone Restyling Products
Alan Golding
2959 Nebraska Ave.
Toledo, OH 43607

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
236 East Town Street, Room 300
Columbus, Ohio 43215

Very truly yours,

Michael W. Ahern, Supervisor
Field Operations and Permit Section
Division of Air Pollution Control

cc: USEPA

TDES



**Permit To Install
Terms and Conditions**

**Issue Date: 6/10/2003
Effective Date: 6/10/2003**

FINAL PERMIT TO INSTALL 04-01324

Application Number: 04-01324
APS Premise Number: 0448011720
Permit Fee: **\$800**
Name of Facility: Keystone Restyling Products
Person to Contact: Alan Golding
Address: 2959 Nebraska Ave.
Toledo, OH 43607

Location of proposed air contaminant source(s) [emissions unit(s)]:
**2959 Nebraska Ave.
Toledo, Ohio**

Description of proposed emissions unit(s):
five workstations used for the manufacture of fiberglass parts.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized

representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio

Keystone Restyling Products
PTI Application: 04-01324
Issued: 6/10/2003

Facility ID: 0448011720

Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)
 TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
OC	16.1
PE	10.4
individual HAPs	<10
combined HAPs	<25

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P001 - fiberglass parts grinding booth controlled by fabric filtration	OAC rule 3745-31-05(A)(3)	5% opacity as a six minute average, 3.2 tons of particulate emissions (PE) per year, and see section 2.a.
	OAC rule 3745-17-07(A)(1)	See section 2.b.
	OAC rule 3745-17-11(B)(1)	0.72 pound of PE per hour.

2. Additional Terms and Conditions

- 2.a The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-11(B)(1).
- 2.b The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

The permittee shall operate the particulate filtration system whenever this emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

The permittee shall maintain daily records that document any time periods when the particulate filtration system was not in service when the emissions unit was in operation.

D. Reporting Requirements

The permittee shall notify the Toledo Division of Environmental Services (TDOES) in writing of any daily record showing that the particulate filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the TDOES within 30 days after the event occurs.

E. Testing Requirements

Compliance with the allowable emission limitations in this permit shall be determined according to the following methods:

1. Emission Limitation;

5% opacity, as a six-minute average.

Applicable Compliance Method;

Compliance shall be determined through visible emission observations performed in accordance with Method 9 of 40 CFR Part 60, Appendix A using the methods and procedures specified in OAC rule 3745-17-03(B)(1).

2. Emission Limitation:

0.72 pound of PE per hour.

Applicable Compliance Method:

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Method 5 of 40 CFR Part 60 Appendix A using the methods and procedures specified in OAC rule 3745-17-03(B)(9).

3. Emission Limitation:

3.2 tons of PE per year.

Applicable Compliance Method:

This emission limitation was established to reflect the potential to emit for this emissions unit. Compliance may be demonstrated through calculations performed as follows: multiply the short

Keysto
PTI A
Issued: 6/10/2003

Emissions Unit ID: **P001**

term emission rate of 0.72 pound of PE per hour by 8,760 hours per year and divide by 2,000 pounds per ton.

F. Miscellaneous Requirements

none

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
R001 - fiberglass stray chop booth with particulate filtration	OAC rule 3745-31-05(A)(3)	5% opacity as a six minute average, 2.4 tons of particulate emissions (PE) per year, 3.7 pounds of organic compounds (OC) per hour, 16 tons of OC per year, and see sections 2.a and 2.b.
	OAC rule 3745-17-07(A)(1)	See section 2.c.
	OAC rule 3745-17-11(B)(1)	0.551 pound of PE per hour.
	OAC rule 3745-21-07(G)(2)	8 pounds of OC per hour, 40 pounds of OC per day, and see section 2.d.

2. Additional Terms and Conditions

- 2.a The emissions of hazardous air pollutants (HAPs) from all emissions units at this facility, as identified in Section 112(b) of Title III of the Clean Air Act, shall be restricted to less than 10 tons per year for any individual HAP, and less than 25 tons per year for any combination of HAPs, as rolling 12-month summations.
- 2.b The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-11(B)(1).

- 2.c** The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
- 2.d** Compliance with this applicable rule will be established by incorporating control equivalent to the RACT requirements of OAC rule 3745-21-07(G)(2). OAC rule 3745-21-07(G)(6)(c) allows for a determination of equivalency of the control. The MACT annual average emission limits in Table 3 and the work practice standards in Table 4 of 40 CFR Part 63, Subpart WWWW are deemed adequate to satisfy the requirements for this equivalency of the control, and are included in this permit as follows:
- i. emissions from the mechanical application of resin shall not exceed 110 pounds of styrene per ton of resin applied as an annual average,
 - ii. emissions from the manual application of resin shall not exceed 83 pounds of styrene per ton of resin applied as an annual average,
 - iii. emissions from the application of white/off white pigmented gel coat shall not exceed 265 pounds of styrene per ton of gel coat applied as an annual average,
 - iv. emissions from the application of all other pigmented gel coat shall not exceed 377 pounds of styrene per ton of gel coat applied as an annual average,
 - v. emissions from the application of clear production gel coat shall not exceed 504 pounds of styrene per ton of gel coat applied as an annual average,
 - vi. the use of cleaning solvents containing HAPs, as identified in Section 112(b) of Title III of the Clean Air Act, in this emissions unit is prohibited, and
 - vii. containers that store HAP containing materials shall be kept closed or covered except during the addition or removal of materials.

B. Operational Restrictions

1. The permittee shall operate the particulate filtration system whenever this emissions unit is in operation.
2. The use of photochemically reactive materials, as defined in OAC rule 3745-21-01 (C)(5), as clean-up materials in this emissions unit is prohibited. Prior to employing any photochemically reactive materials, the permittee shall provide written notification to, and obtain approval from, the TDOES. Such notification shall include information sufficient to determine that the emissions associated with the proposed change in materials will comply with the emissions limits and/or

control requirements as defined in OAC 3745-21-07(G)(2). This notification, at a minimum, shall include the company identification of the new material to be employed, the solvent composition of the material, and the maximum amount to be used, in pounds per hour.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain daily records that document any time periods when the particulate filtration system was not in service when the emissions unit was in operation.
2. The permittee shall collect and record the following information monthly for this emissions unit:
 - a. The company identification for each resin employed for manual application.
 - b. The number of tons of each resin employed for manual application.
 - c. The styrene content of each resin employed for manual application, as the % styrene in the resin by weight.
 - d. The annual average styrene emission rate from the manual application of resin, calculated as a volume weighted average, (i.e., calculated using a summation of the usage data in paragraph (b) above, for each concentration of resin employed as recorded in paragraphs (c) above, the data from the previous 11 calendar months of operation, and the styrene emission factors presented by the Composites Fabrication Association in their Table entitled "United Emission Factors for Open Molding of Composites"), in pounds of styrene per ton of resin applied.
 - e. The company identification for each resin employed for mechanical application.
 - f. The number of tons of each resin employed for mechanical application.
 - g. The styrene content of each resin employed for mechanical application, as the % styrene content in the resin by weight.
 - h. The annual average styrene emission rate from the mechanical application of resin, calculated as a volume weighted average, (i.e., calculated using a summation of the usage data in paragraph (f) above, for each concentration of resin employed as recorded in paragraph (g) above, the data from the previous 11 calendar months of operation, and the styrene emission factors presented by the Composites Fabrication Association in their Table entitled "United Emission Factors for Open Molding of Composites"), in pounds of styrene per ton of resin applied.
 - i. The company identification for each white/off white pigmented gel coat employed.

- j. The number of tons of each white/off white pigmented gel coat employed.
- k. The styrene content of each white/off white pigmented gel coat employed, as the % styrene in the gel coat by weight.
- l. The annual average styrene emission rate from white/off white pigmented gel coat, calculated as a volume weighted average, (i.e., calculated using a summation of the usage data in paragraph (j) above, for each concentration of gel coat employed as recorded in paragraphs

(k) above, the data from the previous 11 calendar months of operation, and the styrene emission factors presented by the Composites Fabrication Association in their Table entitled "United Emission Factors for Open Molding of Composites"), in pounds of styrene per ton of gel coat applied.
- m. The company identification for all other pigmented gel coat employed.
- n. The number of tons of all other pigmented gel coat employed.
- o. The styrene content of all other pigmented gel coat employed, as the % styrene in the gel coat by weight.
- p. The annual average styrene emission rate from all other pigmented gel coat, calculated as a volume weighted average, (i.e., calculated using a summation of the usage data in paragraph (n) above, for each concentration of gel coat employed as recorded in paragraphs (o) above, the data from the previous 11 calendar months of operation, and the styrene emission factors presented by the Composites Fabrication Association in their Table entitled "United Emission Factors for Open Molding of Composites"), in pounds of styrene per ton of gel coat applied.
- q. The company identification for each clear production gel coat employed.
- r. The number of tons of each clear production gel coat employed.
- s. The styrene content of each clear production gel coat employed, as the % styrene in the gel coat by weight.
- t. The annual average styrene emission rate from clear production gel coat, calculated as a volume weighted average, (i.e., calculated using a summation of the usage data in paragraph (r) above, for each concentration of gel coat employed as recorded in paragraphs (s) above, the data from the previous 11 calendar months of operation, and

the styrene emission factors presented by the Composites Fabrication Association in their Table entitled "United Emission Factors for Open Molding of Composites"), in pounds of styrene per ton of gel coat applied.

- u. The rolling, 12-month total styrene emission rate from this emissions unit, calculated as a summation of the data above, in tons per year.
 - v. The combined annual styrene emission rate from all emissions units at this facility, calculated as a summation of the rolling, 12-month total styrene emission rates from emissions units R001, R002 and R003.
3. The permit to install for this emissions unit, PTI 04-1324, was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant:	styrene
TLV (mg/m3):	85,200 ug/m3
Maximum Hourly Emission Rate (lbs/hr):	6.2 combined for R001, R002 and R003 modeled as if emitted from the stack serving R001
Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3):	382.1
MAGLC (ug/m3):	2,028 ug/m3

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
4. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall notify the Toledo Division of Environmental Services (TDOES) in writing of any daily record showing that the particulate filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the TDOES within 30 days after the event occurs.
2. The permittee shall submit deviation (excursion) reports which include the following information:

- a. An identification of each month during which the annual average styrene emission rate from the manual application of resin exceeded 83 pounds styrene per ton of resin, and the actual average styrene emissions rate from the manual application of resin for each such month.
- b. An identification of each month during which the annual average styrene emission rate from the mechanical application of resin exceeded 110 pounds styrene per ton of resin, and the actual average styrene emissions rate from the mechanical application of resin for each such month.
- c. An identification of each month during which the annual average styrene emission rate from the white/off white pigmented gel coat exceeded 265 pounds styrene per ton of gel coat, and the actual average styrene emissions rate from the white/off white pigmented gel coat for each such month.
- d. An identification of each month during which the annual average styrene emission rate from all other pigmented gel coat exceeded 377 pounds styrene per ton of gel coat, and the actual average styrene emissions rate from all other pigmented gel coat for each such month.
- e. An identification of each month during which the annual average styrene emission rate from the clear production gel coat exceeded 504 pounds styrene per ton of gel coat, and the actual average styrene emissions rate from the clear production gel coat for each such month.
- f. An identification of each month during which the combined annual styrene emission rate from all emissions units at this facility equaled or exceeded 10 tons, and the actual rolling, 12-month summation styrene emissions each such month.

Each report shall be submitted to the Toledo Division of Environmental Services at 348 S. Erie St., Toledo, OH 43602, within 30 days of the discovery of an exceedance.

E. Testing Requirements

Compliance with the allowable emission limitations in this permit shall be determined according to the following methods:

1. Emission Limitation;

5% opacity, as a six-minute average.

Applicable Compliance Method;

Compliance shall be determined through visible emission observations performed in accordance with Method 9 of 40 CFR Part 60, Appendix A using the methods and procedures specified in OAC rule 3745-17-03(B)(1).

2. Emission Limitation:

0.551 pound of PE per hour.

Applicable Compliance Method:

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Method 5 of 40 CFR Part 60 Appendix A using the methods and procedures specified in OAC rule 3745-17-03(B)(9).

3. Emission Limitation:

2.4 tons of PE per year.

Applicable Compliance Method:

This emission limitation was established to reflect the potential to emit for this emissions unit. Compliance may be demonstrated through calculations performed as follows: multiply the short term emission rate of 0.551 pound of PE per hour by 8,760 hours per year and divide by 2,000 pounds per ton.

4. Emission Limitation:

3.7 pounds of OC per hour.

Applicable Compliance Method:

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Method 25 of 40 CFR Part 60 Appendix A using the methods and procedures specified in OAC rule 3745-21-10.

5. Emission Limitation:

16 tons of OC per year.

Applicable Compliance Method:

This emission limitation was established to reflect the potential to emit for this emissions unit.

Compliance may be demonstrated through calculations performed as follows: multiply the short term emission rate of 3.7 pounds of OC per hour by 8,760 hours per year and divide by 2,000 pounds per ton.

F. Miscellaneous Requirements

1. The following terms and conditions of this permit are federally enforceable: A.2.a, C.2.v. and D.2.f.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
R002 - fiberglass gel coat booth with particulate filtration	OAC rule 3745-31-05(A)(3)	5% opacity as a six minute average, 2.4 tons of particulate emissions (PE) per year, 1.6 pounds of organic compounds (OC) per hour, 7.0 tons of OC per year, and see sections 2.a and 2.b.
	OAC rule 3745-17-07(A)(1)	See section 2.c.
	OAC rule 3745-17-11(B)(1)	0.551 pound of PE per hour.
	OAC rule 3745-21-07(G)(2)	8 pounds of OC per hour, 40 pounds of OC per day, and see section 2.d.

2. Additional Terms and Conditions

- 2.a The emissions of hazardous air pollutants (HAPs) from all emissions units at this facility, as identified in Section 112(b) of Title III of the Clean Air Act, shall be restricted to less than 10 tons per year for any individual HAP, and less than 25 tons per year for any combination of HAPs, as rolling 12-month summations.
- 2.b The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-11(B)(1).

Emissions Unit ID: **R002**

- 2.c** The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
- 2.d** Compliance with this applicable rule will be established by incorporating control equivalent to the RACT requirements of OAC rule 3745-21-07(G)(2). OAC rule 3745-21-07(G)(6)(c) allows for a determination of equivalency of the control. The MACT annual average emission limits in Table 3 and the work practice standards in Table 4 of 40 CFR Part 63, Subpart WWWW are deemed adequate to satisfy the requirements for this equivalency of the control, and are included in this permit as follows:
- i. emissions from the mechanical application of resin shall not exceed 110 pounds of styrene per ton of resin applied as an annual average,
 - ii. emissions from the manual application of resin shall not exceed 83 pounds of styrene per ton of resin applied as an annual average,
 - iii. emissions from the application of white/off white pigmented gel coat shall not exceed 265 pounds of styrene per ton of gel coat applied as an annual average,
 - iv. emissions from the application of all other pigmented gel coat shall not exceed 377 pounds of styrene per ton of gel coat applied as an annual average,
 - v. emissions from the application of clear production gel coat shall not exceed 504 pounds of styrene per ton of gel coat applied as an annual average,
 - vi. the use of cleaning solvents containing HAPs, as identified in Section 112(b) of Title III of the Clean Air Act, in this emissions unit is prohibited, and
 - vii. containers that store HAP containing materials shall be kept closed or covered except during the addition or removal of materials.

B. Operational Restrictions

1. The permittee shall operate the particulate filtration system whenever this emissions unit is in operation.
2. The use of photochemically reactive materials, as defined in OAC rule 3745-21-01 (C)(5), as clean-up materials in this emissions unit is prohibited. Prior to employing any photochemically reactive materials, the permittee shall provide written notification to, and obtain approval from, the TDOES. Such notification shall include information sufficient to determine that the emissions associated with the proposed change in materials will comply with the emissions limits and/or

control requirements as defined in OAC 3745-21-07(G)(2). This notification, at a minimum, shall include the company identification of the new material to be employed, the solvent composition of the material, and the maximum amount to be used, in pounds per hour.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain daily records that document any time periods when the particulate filtration system was not in service when the emissions unit was in operation.
2. The permittee shall collect and record the following information monthly for this emissions unit:
 - a. The company identification for each resin employed for manual application.
 - b. The number of tons of each resin employed for manual application.
 - c. The styrene content of each resin employed for manual application, as the % styrene in the resin by weight.
 - d. The annual average styrene emission rate from the manual application of resin, calculated as a volume weighted average, (i.e., calculated using a summation of the usage data in paragraph (b) above, for each concentration of resin employed as recorded in paragraphs (c) above, the data from the previous 11 calendar months of operation, and the styrene emission factors presented by the Composites Fabrication Association in their Table entitled "United Emission Factors for Open Molding of Composites"), in pounds of styrene per ton of resin applied.
 - e. The company identification for each resin employed for mechanical application.
 - f. The number of tons of each resin employed for mechanical application.
 - g. The styrene content of each resin employed for mechanical application, as the % styrene content in the resin by weight.
 - h. The annual average styrene emission rate from the mechanical application of resin, calculated as a volume weighted average, (i.e., calculated using a summation of the usage data in paragraph (f) above, for each concentration of resin employed as recorded in paragraph (g) above, the data from the previous 11 calendar months of operation, and the styrene emission factors presented by the Composites Fabrication Association in their Table entitled "United Emission Factors for Open Molding of Composites"), in pounds of styrene per ton of resin applied.
 - i. The company identification for each white/off white pigmented gel coat employed.

- j. The number of tons of each white/off white pigmented gel coat employed.
- k. The styrene content of each white/off white pigmented gel coat employed, as the % styrene in the gel coat by weight.
- l. The annual average styrene emission rate from white/off white pigmented gel coat, calculated as a volume weighted average, (i.e., calculated using a summation of the usage data in paragraph (j) above, for each concentration of gel coat employed as recorded in paragraphs (k) above, the data from the previous 11 calendar months of operation, and the styrene emission factors presented by the Composites Fabrication Association in their Table entitled "United Emission Factors for Open Molding of Composites"), in pounds of styrene per ton of gel coat applied.
- m. The company identification for all other pigmented gel coat employed.
- n. The number of tons of all other pigmented gel coat employed.
- o. The styrene content of all other pigmented gel coat employed, as the % styrene in the gel coat by weight.
- p. The annual average styrene emission rate from all other pigmented gel coat, calculated as a volume weighted average, (i.e., calculated using a summation of the usage data in paragraph (n) above, for each concentration of gel coat employed as recorded in paragraphs (o) above, the data from the previous 11 calendar months of operation, and the styrene emission factors presented by the Composites Fabrication Association in their Table entitled "United Emission Factors for Open Molding of Composites"), in pounds of styrene per ton of gel coat applied.
- q. The company identification for each clear production gel coat employed.
- r. The number of tons of each clear production gel coat employed.
- s. The styrene content of each clear production gel coat employed, as the % styrene in the gel coat by weight.
- t. The annual average styrene emission rate from clear production gel coat, calculated as a volume weighted average, (i.e., calculated using a summation of the usage data in paragraph (r) above, for each concentration of gel coat employed as recorded in paragraphs (s) above, the data from the previous 11 calendar months of operation, and the styrene emission factors presented by the Composites Fabrication Association in their Table entitled "United Emission Factors for Open Molding of Composites"), in pounds of

styrene per ton of gel coat applied.

- u. The rolling, 12-month total styrene emission rate from this emissions unit, calculated as a summation of the data above, in tons per year.
 - v. The combined annual styrene emission rate from all emissions units at this facility, calculated as a summation of the rolling, 12-month total styrene emission rates from emissions units R001, R002 and R003.
3. The permit to install for this emissions unit, PTI 04-1324, was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant:	styrene
TLV (mg/m3):	85,200 ug/m3
Maximum Hourly Emission Rate (lbs/hr):	6.2 combined for R001, R002 and R003 modeled as if emitted from the stack serving R001
Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3):	382.1
MAGLC (ug/m3):	2,028 ug/m3

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup

Keystone Restyling Products

PTI Application: 04-01324

Issued**Facility ID: 0448011720**Emissions Unit ID: **R002**

materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

4. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall notify the Toledo Division of Environmental Services (TDOES) in writing of any daily record showing that the particulate filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the TDOES within 30 days after the event occurs.
2. The permittee shall submit deviation (excursion) reports which include the following information:
 - a. An identification of each month during which the annual average styrene emission rate from the manual application of resin exceeded 83 pounds styrene per ton of resin, and the actual average styrene emissions rate from the manual application of resin for each such month.
 - b. An identification of each month during which the annual average styrene emission rate from the mechanical application of resin exceeded 110 pounds styrene per ton of resin, and the actual average styrene emissions rate from the mechanical application of resin for each such month.
 - c. An identification of each month during which the annual average styrene emission rate

Emissions Unit ID: **R002**

from the white/off white pigmented gel coat exceeded 265 pounds styrene per ton of gel coat, and the actual average styrene emissions rate from the white/off white pigmented gel coat for each such month.

- d. An identification of each month during which the annual average styrene emission rate from all other pigmented gel coat exceeded 377 pounds styrene per ton of gel coat, and the actual average styrene emissions rate from all other pigmented gel coat for each such month.
- e. An identification of each month during which the annual average styrene emission rate from the clear production gel coat exceeded 504 pounds styrene per ton of gel coat, and the actual average styrene emissions rate from the clear production gel coat for each such month.
- f. An identification of each month during which the combined annual styrene emission rate from all emissions units at this facility equaled or exceeded 10 tons, and the actual rolling, 12-month summation styrene emissions each such month.

Each report shall be submitted to the Toledo Division of Environmental Services at 348 S. Erie St., Toledo, OH 43602, within 30 days of the discovery of an exceedance.

E. Testing Requirements

Compliance with the allowable emission limitations in this permit shall be determined according to the following methods:

1. Emission Limitation;

5% opacity, as a six-minute average.

Applicable Compliance Method;

Compliance shall be determined through visible emission observations performed in accordance with Method 9 of 40 CFR Part 60, Appendix A using the methods and procedures specified in OAC rule 3745-17-03(B)(1).

2. Emission Limitation:

0.551 pound of PE per hour.

Applicable Compliance Method:

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Method 5 of 40 CFR Part 60 Appendix A using the methods and procedures specified in OAC rule 3745-17-03(B)(9).

3. Emission Limitation:

2.4 tons of PE per year.

Applicable Compliance Method:

This emission limitation was established to reflect the potential to emit for this emissions unit. Compliance may be demonstrated through calculations performed as follows: multiply the short term emission rate of 0.551 pound of PE per hour by 8,760 hours per year and divide by 2,000 pounds per ton.

4. Emission Limitation:

1.6 pounds of OC per hour.

Applicable Compliance Method:

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Method 25 of 40 CFR Part 60 Appendix A using the methods and procedures specified in OAC rule 3745-21-10.

5. Emission Limitation:

7.0 tons of OC per year.

Applicable Compliance Method:

This emission limitation was established to reflect the potential to emit for this emissions unit. Compliance may be demonstrated through calculations performed as follows: multiply the short term emission rate of 1.6 pounds of OC per hour by 8,760 hours per year and divide by 2,000 pounds per ton.

F. Miscellaneous Requirements

1. The following terms and conditions of this permit are federally enforceable: A.2.a, C.2.v. and

30

Keyst

PTI A

Issued: 6/10/2003

Emissions Unit ID: **R002**

D.2.f.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
R003 - fiberglass mold booth with particulate filtration	OAC rule 3745-31-05(A)(3)	5% opacity as a six minute average, 2.4 tons of particulate emissions (PE) per year, 0.78 pounds of organic compounds (OC) per hour, 3.4 tons of OC per year, and see sections 2.a and 2.b.
	OAC rule 3745-17-07(A)(1)	See section 2.c.
	OAC rule 3745-17-11(B)(1)	0.551 pound of PE per hour.
	OAC rule 3745-21-07(G)(2)	8 pounds of OC per hour, 40 pounds of OC per day, and see section 2.d.

2. Additional Terms and Conditions

- 2.a The emissions of hazardous air pollutants (HAPs) from all emissions units at this facility, as identified in Section 112(b) of Title III of the Clean Air Act, shall be restricted to less than 10 tons per year for any individual HAP, and less than 25 tons per year for any combination of HAPs, as rolling 12-month summations.
- 2.b The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-11(B)(1).

Emissions Unit ID: **R003**

- 2.c** The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
- 2.d** Compliance with this applicable rule will be established by incorporating control equivalent to the RACT requirements of OAC rule 3745-21-07(G)(2). OAC rule 3745-21-07(G)(6)(c) allows for a determination of equivalency of the control. The MACT annual average emission limits in Table 3 and the work practice standards in Table 4 of 40 CFR Part 63, Subpart WWWW are deemed adequate to satisfy the requirements for this equivalency of the control, and are included in this permit as follows:
- i. emissions from the mechanical application of resin shall not exceed 110 pounds of styrene per ton of resin applied as an annual average,
 - ii. emissions from the manual application of resin shall not exceed 83 pounds of styrene per ton of resin applied as an annual average,
 - iii. emissions from the application of white/off white pigmented gel coat shall not exceed 265 pounds of styrene per ton of gel coat applied as an annual average,
 - iv. emissions from the application of all other pigmented gel coat shall not exceed 377 pounds of styrene per ton of gel coat applied as an annual average,
 - v. emissions from the application of clear production gel coat shall not exceed 504 pounds of styrene per ton of gel coat applied as an annual average,
 - vi. the use of cleaning solvents containing HAPs, as identified in Section 112(b) of Title III of the Clean Air Act, in this emissions unit is prohibited, and
 - vii. containers that store HAP containing materials shall be kept closed or covered except during the addition or removal of materials.

B. Operational Restrictions

1. The permittee shall operate the particulate filtration system whenever this emissions unit is in operation.
2. The use of photochemically reactive materials, as defined in OAC rule 3745-21-01 (C)(5), as clean-up materials in this emissions unit is prohibited. Prior to employing any photochemically reactive materials, the permittee shall provide written notification to, and obtain approval from, the TDOES. Such notification shall include information sufficient to determine that the emissions associated with the proposed change in materials will comply with the emissions limits and/or

control requirements as defined in OAC 3745-21-07(G)(2). This notification, at a minimum, shall include the company identification of the new material to be employed, the solvent composition of the material, and the maximum amount to be used, in pounds per hour.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain daily records that document any time periods when the particulate filtration system was not in service when the emissions unit was in operation.
2. The permittee shall collect and record the following information monthly for this emissions unit:
 - a. The company identification for each resin employed for manual application.
 - b. The number of tons of each resin employed for manual application.
 - c. The styrene content of each resin employed for manual application, as the % styrene in the resin by weight.
 - d. The annual average styrene emission rate from the manual application of resin, calculated as a volume weighted average, (i.e., calculated using a summation of the usage data in paragraph (b) above, for each concentration of resin employed as recorded in paragraphs (c) above, the data from the previous 11 calendar months of operation, and the styrene emission factors presented by the Composites Fabrication Association in their Table entitled "United Emission Factors for Open Molding of Composites"), in pounds of styrene per ton of resin applied.
 - e. The company identification for each resin employed for mechanical application.
 - f. The number of tons of each resin employed for mechanical application.
 - g. The styrene content of each resin employed for mechanical application, as the % styrene content in the resin by weight.
 - h. The annual average styrene emission rate from the mechanical application of resin, calculated as a volume weighted average, (i.e., calculated using a summation of the usage data in paragraph (f) above, for each concentration of resin employed as recorded in paragraph (g) above, the data from the previous 11 calendar months of operation, and the styrene emission factors presented by the Composites Fabrication Association in their Table entitled "United Emission Factors for Open Molding of Composites"), in pounds of styrene per ton of resin applied.
 - i. The company identification for each white/off white pigmented gel coat employed.

- j. The number of tons of each white/off white pigmented gel coat employed.
- k. The styrene content of each white/off white pigmented gel coat employed, as the % styrene in the gel coat by weight.
- l. The annual average styrene emission rate from white/off white pigmented gel coat, calculated as a volume weighted average, (i.e., calculated using a summation of the usage data in paragraph (j) above, for each concentration of gel coat employed as recorded in paragraphs (k) above, the data from the previous 11 calendar months of operation, and the styrene emission factors presented by the Composites Fabrication Association in their Table entitled "United Emission Factors for Open Molding of Composites"), in pounds of styrene per ton of gel coat applied.
- m. The company identification for all other pigmented gel coat employed.
- n. The number of tons of all other pigmented gel coat employed.
- o. The styrene content of all other pigmented gel coat employed, as the % styrene in the gel coat by weight.
- p. The annual average styrene emission rate from all other pigmented gel coat, calculated as a volume weighted average, (i.e., calculated using a summation of the usage data in paragraph (n) above, for each concentration of gel coat employed as recorded in paragraphs (o) above, the data from the previous 11 calendar months of operation, and the styrene emission factors presented by the Composites Fabrication Association in their Table entitled "United Emission Factors for Open Molding of Composites"), in pounds of styrene per ton of gel coat applied.
- q. The company identification for each clear production gel coat employed.
- r. The number of tons of each clear production gel coat employed.
- s. The styrene content of each clear production gel coat employed, as the % styrene in the gel coat by weight.
- t. The annual average styrene emission rate from clear production gel coat, calculated as a volume weighted average, (i.e., calculated using a summation of the usage data in paragraph (r) above, for each concentration of gel coat employed as recorded in paragraphs (s) above, the data from the previous 11 calendar months of operation, and the styrene emission factors presented by the Composites Fabrication Association in their Table entitled "United Emission Factors for Open Molding of Composites"), in pounds of

styrene per ton of gel coat applied.

- u. The rolling, 12-month total styrene emission rate from this emissions unit, calculated as a summation of the data above, in tons per year.
 - v. The combined annual styrene emission rate from all emissions units at this facility, calculated as a summation of the rolling, 12-month total styrene emission rates from emissions units R001, R002 and R003.
3. The permit to install for this emissions unit, PTI 04-1324, was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant:	styrene
TLV (mg/m3):	85,200 ug/m3
Maximum Hourly Emission Rate (lbs/hr):	6.2 combined for R001, R002 and R003 modeled as if emitted from the stack serving R001
Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3):	382.1
MAGLC (ug/m3):	2,028 ug/m3

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup

Keystone Restyling Products

PTI Application: 04-01324

Issued

Facility ID: 0448011720

Emissions Unit ID: **R003**

materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

4. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall notify the Toledo Division of Environmental Services (TDOES) in writing of any daily record showing that the particulate filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the TDOES within 30 days after the event occurs.
2. The permittee shall submit deviation (excursion) reports which include the following information:
 - a. An identification of each month during which the annual average styrene emission rate from the manual application of resin exceeded 83 pounds styrene per ton of resin, and the actual average styrene emissions rate from the manual application of resin for each such month.
 - b. An identification of each month during which the annual average styrene emission rate from the mechanical application of resin exceeded 110 pounds styrene per ton of resin, and the actual average styrene emissions rate from the mechanical application of resin for each such month.
 - c. An identification of each month during which the annual average styrene emission rate

Emissions Unit ID: **R003**

from the white/off white pigmented gel coat exceeded 265 pounds styrene per ton of gel coat, and the actual average styrene emissions rate from the white/off white pigmented gel coat for each such month.

- d. An identification of each month during which the annual average styrene emission rate from all other pigmented gel coat exceeded 377 pounds styrene per ton of gel coat, and the actual average styrene emissions rate from all other pigmented gel coat for each such month.
- e. An identification of each month during which the annual average styrene emission rate from the clear production gel coat exceeded 504 pounds styrene per ton of gel coat, and the actual average styrene emissions rate from the clear production gel coat for each such month.
- f. An identification of each month during which the combined annual styrene emission rate from all emissions units at this facility equaled or exceeded 10 tons, and the actual rolling, 12-month summation styrene emissions each such month.

Each report shall be submitted to the Toledo Division of Environmental Services at 348 S. Erie St., Toledo, OH 43602, within 30 days of the discovery of an exceedance.

E. Testing Requirements

Compliance with the allowable emission limitations in this permit shall be determined according to the following methods:

1. Emission Limitation;

5% opacity, as a six-minute average.

Applicable Compliance Method;

Compliance shall be determined through visible emission observations performed in accordance with Method 9 of 40 CFR Part 60, Appendix A using the methods and procedures specified in OAC rule 3745-17-03(B)(1).

2. Emission Limitation:

0.551 pound of PE per hour.

Applicable Compliance Method:

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Method 5 of 40 CFR Part 60 Appendix A using the methods and procedures specified in OAC rule 3745-17-03(B)(9).

3. Emission Limitation:

2.4 tons of PE per year.

Applicable Compliance Method:

This emission limitation was established to reflect the potential to emit for this emissions unit. Compliance may be demonstrated through calculations performed as follows: multiply the short term emission rate of 0.551 pound of PE per hour by 8,760 hours per year and divide by 2,000 pounds per ton.

4. Emission Limitation:

0.78 pound of OC per hour.

Applicable Compliance Method:

If required, the permittee shall demonstrate compliance with this emission limitation through emission testing performed in accordance with Method 25 of 40 CFR Part 60 Appendix A using the methods and procedures specified in OAC rule 3745-21-10.

5. Emission Limitation:

3.4 tons of OC per year.

Applicable Compliance Method:

This emission limitation was established to reflect the potential to emit for this emissions unit. Compliance may be demonstrated through calculations performed as follows: multiply the short term emission rate of 0.78 pound of OC per hour by 8,760 hours per year and divide by 2,000 pounds per ton.

F. Miscellaneous Requirements

1. The following terms and conditions of this permit are federally enforceable: A.2.a, C.2.v. and

41

Keyst

PTI A

Issued: 6/10/2003

Emissions Unit ID: **R003**

D.2.f.