



State of Ohio Environmental Protection Agency

Street Address:

Mailing Address:

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Lazarus Gov. Center

**RE: DRAFT PERMIT TO INSTALL MODIFICATION
LUCAS COUNTY
Application No: 04-01405
Fac ID: 0448970001**

CERTIFIED MAIL

DATE: 6/2/2005

Kuhlman Corporation
James D. Gilmore
1845 Indianwood Circle
Maumee, OH 43537

You are hereby notified that the Ohio Environmental Protection Agency has made a draft action recommending that the Director issue a Permit to Install modification for the air contaminant source(s) [emissions unit(s)] shown on the enclosed draft permit modification. This draft action is not an authorization to begin construction or modification of your emissions unit(s). The purpose of this draft is to solicit public comments on the proposed installation. A public notice concerning the draft permit will appear in the Ohio EPA Weekly Review and the newspaper in the county where the facility will be located. Public comments will be accepted by the field office within 30 days of the date of publication in the newspaper. Any comments you have on the draft permit modification should be directed to the appropriate field office within the comment period. A copy of your comments should also be mailed to Robert Hodanbosi, Division of Air Pollution Control, Ohio EPA, P.O. Box 1049, Columbus, OH, 43266-0149.

A Permit to Install modification may be issued in proposed or final form based on the draft action, any written public comments received within 30 days of the public notice, or record of a public meeting if one is held. You will be notified in writing of a scheduled public meeting. Upon issuance of a final Permit to Install modification a fee of **\$ 1450** will be due. Please do not submit any payment now.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469. If you have any questions about this draft permit, please contact the field office where you submitted your application, or Mike Ahern, Field Operations & Permit Section at (614) 644-3631.

Sincerely,

Michael W. Ahern

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: USEPA

TDES

Toledo Metro. Area Council of Gov.

IN

MI

LUCAS COUNTY

PUBLIC NOTICE

**ISSUANCE OF DRAFT PERMIT TO INSTALL 04-01405 FOR AN AIR CONTAMINANT SOURCE FOR
Kuhlman Corporation**

On 6/2/2005 the Director of the Ohio Environmental Protection Agency issued a draft action of a Permit To Install an air contaminant source for **Kuhlman Corporation**, located at **444 Kuhlman Drive, Toledo, Ohio**.

Installation of the air contaminant source identified below may proceed upon final issuance of Permit To Install 04-01405:

portable plant seven, 160 cuyd/hr portable trans-mix concrete plant.

Comments concerning this draft action, or a request for a public meeting, must be sent in writing to the address identified below no later than thirty (30) days from the date this notice is published. All inquiries concerning this draft action may be directed to the contact identified below.

Karen Granata, Toledo Department of Environmental Services, 348 South Erie Street, Toledo, OH 43602
[(419)936-3015]



**Permit To Install
Terms and Conditions**

**Issue Date: To be entered upon final issuance
Effective Date: To be entered upon final issuance**

DRAFT MODIFICATION OF PERMIT TO INSTALL 04-01405

Application Number: 04-01405
Facility ID: 0448970001
Permit Fee: **To be entered upon final issuance**
Name of Facility: Kuhlman Corporation
Person to Contact: James D. Gilmore
Address: 1845 Indianwood Circle
Maumee, OH 43537

Location of proposed air contaminant source(s) [emissions unit(s)]:

**444 Kuhlman Drive
Toledo, Ohio**

Description of proposed emissions unit(s):

Portable plant seven, 160 cuyd/hr portable trans-mix concrete plant.

The above named entity is hereby granted a modification to the permit to install described above pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this modification does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described source(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans included in the application, the above described source(s) of pollutants will be granted the necessary operating permits.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any

Issued: To be entered upon final issuance

information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions

Issued: To be entered upon final issuance

and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

Kuhlman Corporation
PTI Application: 04-01405
Issued: To be entered upon final issuance

Facility ID: 0448970001

Kuhlman Corporation

Facility ID: 0448970001

PTI Application: 04-01405

Issued: To be entered upon final issuance

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
PE	6.19
PM10	2.01

Kuhln

PTI A

Emissions Unit ID: **F001**

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property,
and/or Equipment

Applicable Rules/Requirements

F001 - portable plant seven, 160
cuyd/hr portable trans-mix concrete
plant:

OAC rule 3745-31-05(A)(3)

loading of the trans-mix trucks

loading of the weigh hopper

OAC rule 3745-31-05(C)

OAC rule 3745-17-07(B)(1)

Kuhln

PTI A

Emissions Unit ID: **F001**

Issued: To be entered upon final issuance

OAC rule 3745-17-08(B), (B)(3)

OAC rule 3745-31-05(A)(3)

OAC rule 3745-31-05(C)

OAC rule 3745-17-07(B)(1)

OAC rule 3745-17-08(B), (B)(3)

Applicable Emissions
Limitations/Control Measures

The emissions of fugitive dust shall not exceed 9.28 pounds of particulate emissions (PE) per hour.

The emissions of fugitive dust equal to or less than 10 microns in diameter (PM10) shall not exceed 2.24 pounds per hour.

Visible emissions of fugitive dust shall not exceed 10% opacity as a three-minute average.

See sections A.2.a through c.

The emissions of fugitive dust shall not exceed 2.18 tons of PE per rolling, 12-month period.

The emissions of fugitive PM10 shall not exceed 0.53 ton per rolling, 12-month period.

See section A.2.d.

See section A.2. e.

See section A.2. e.

The emissions of fugitive dust shall not exceed 1.26 pounds of particulate emissions (PE) per hour .

The emissions of fugitive dust equal

to or less than 10 microns in diameter (PM10) shall not exceed 0.61 pound per hour.

Visible emissions of fugitive dust shall not exceed 10% opacity as a three-minute average.

See sections A.2.b, c and f.

The emissions of fugitive dust shall not exceed 0.30 ton of PE per rolling, 12-month period.

The emissions of fugitive PM10 shall not exceed 0.14 ton per rolling, 12-month period.

See section A.2.d.

See section A.2. e.

See section A.2. e.

2. Additional Terms and Conditions

- 2.a** The permittee shall employ the following best available control measures for the transit-mix truck loading process for the purpose of ensuring compliance with the above-mentioned applicable requirements:

The permittee shall install and employ a water spray system to maintain adequate moisture in the feed stock. A choke feed fill system shall be utilized for the purpose of controlling fugitive dust emissions from the truck loading process. These control systems shall be operated at all times that trucks are being loaded and these controls shall be sufficient to minimize or eliminate visible emissions of fugitive dust from this emissions unit. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

- 2.b** The hourly particulate emission limitations specified above are based upon the emissions unit's potential to emit. Therefore, no hourly records are required to be maintained to demonstrate compliance with these limitations.

- 2.c** The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(C).

- 2.d** The rolling, 12-month particulate emission limitations specified above are based upon the emissions unit's potential to emit at a rolling, 12-month production restriction of 75,000 cubic yards of concrete. Therefore, no annual emission records are required to be maintained for this emissions unit to demonstrate compliance with these limitations.

- 2.e** The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

- 2. f** The permittee shall employ the following best available control measures for the weigh hopper for the purpose of ensuring compliance with the above-mentioned applicable requirements:

The permittee shall install and employ a water spray system to maintain adequate moisture in the feed stock. The weigh hoppers shall be sufficiently enclosed so as to minimize or eliminate at all times visible emissions of fugitive dust. These control systems shall be operated at all times that the weigh hopper is being loaded and these controls shall be sufficient to minimize or eliminate visible emissions of fugitive dust from this emissions unit. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

B. Operational Restrictions

1. The maximum throughput for this emissions unit shall not exceed 75,000 cubic yards of concrete,

Kuhln

PTI A

Emissions Unit ID: **F001**

Issued: To be entered upon final issuance

based upon a rolling, 12-month summation of the concrete production.

To ensure enforceability during the first 12 calendar months of operation, the permittee shall not exceed the production levels specified in the following table:

<u>Month(s)</u>	<u>Maximum Allowable Cumulative Cubic Yards of Concrete Produced</u>
1	40,000
1-2	75,000
1-3	75,000
1-4	75,000
1-5	75,000
1-6	75,000
1-7	75,000
1-8	75,000
1-9	75,000
1-10	75,000
1-11	75,000
1-12	75,000

After the first 12 calendar months of operation, compliance with the annual production limitation shall be based upon a rolling, 12-month summation of the concrete production.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain monthly records of the following information:
 - a. the volume of concrete produced in this emissions unit for each month, in cubic yards;
 - b. beginning after the first 12 calendar months of operation, the rolling, 12-month summation of the concrete production; and
 - c. during the first 12 calendar months of operation, the permittee shall record the cumulative concrete production for each calendar month.

2. The permittee shall perform daily checks, when the emissions unit is in operation, for any visible fugitive particulate emissions from the weigh hopper. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. the color of the emissions;
 - b. the total duration of any visible emission incident; and

- c. any corrective actions taken to eliminate the visible emissions.
3. The permittee shall perform daily checks, when the emissions unit is in operation, for any visible fugitive particulate emissions from the area immediately above the loading truck. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. the color of the emissions;
 - b. the total duration of any visible emission incident; and
 - c. any corrective actions taken to eliminate the visible emissions.

D. Reporting Requirements

1. The permittee shall submit semi-annual reports that identify any exceedances of the rolling 12-month concrete production limitation. These reports shall be submitted to the City of Toledo, Division of Environmental Services and the appropriate field office (having jurisdiction over the new site) by January 31 and July 31 of each year and shall cover the previous 6-month period.

Kuhln

PTI A

Emissions Unit ID: **F001**

Issued: To be entered upon final issuance

2. The permittee shall submit semiannual written reports that (a) identify all days during which any visible fugitive particulate emissions were observed from this emissions unit and (b) describe any corrective actions taken to eliminate the visible fugitive particulate emissions. These reports shall be submitted to the City of Toledo, Division of Environmental Services and the appropriate field office (having jurisdiction over the new site by January 31 and July 31 of each year and shall cover the previous 6-month period.
3. Pursuant to OAC rule 3745-31-03(A)(1)(p), the permittee of a portable emissions unit may relocate within the State of Ohio without first obtaining a permit to install (PTI) providing certain criteria are met. The portable emissions unit shall meet one of the two following scenarios in order to qualify for this PTI exemption for the new location:
 - a. The following determinations have been documented, pursuant to OAC rule 3745-31-03(A)(1)(p)(i):
 - i. the portable emissions unit is equipped with the best available technology for such portable emissions unit;
 - ii. the portable emissions unit is operating pursuant to a currently effective permit to operate (PTO) or registration status;
 - iii. the applicant has provided proper notice of intent to relocate the portable emissions unit to the City of Toledo, Division of Environmental Services and the appropriate field office having jurisdiction over the new site within a minimum of 30 days prior to the scheduled relocation; and
 - iv. in the City of Toledo, Division of Environmental Services and the appropriate field office's (having jurisdiction over the new site) judgement, the proposed site is acceptable under OAC rule 3745-15-07.
 - b. In the alternative, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), the permittee of a portable emissions unit may relocate within the State of Ohio without first obtaining a PTI, providing the following criteria of OAC rule 3745-31-05(E) are met:
 - i. the portable emissions unit permittee possesses an Ohio EPA PTI, PTO or registration status;
 - ii. the portable emissions unit is equipped with best available technology;
 - iii. the portable emissions unit owner has identified the proposed site to Ohio EPA;

Kuhln

PTI A

Emissions Unit ID: **F001**

Issued: To be entered upon final issuance

- iv. Ohio EPA has determined that the portable emissions unit, at the proposed site, will have an acceptable environmental impact;

Kuhln

PTI A

Emissions Unit ID: **F001**

Issued: To be entered upon final issuance

- v. a public notice, consistent with OAC Chapter 3745-47, is published in the county where the proposed site is located;
- vi. the owner of the proposed site has provided the portable emissions unit owner with approval or equivalent declaration that it is acceptable to the site owner to move the portable emissions unit to this proposed site; and
- vii. the portable emissions unit owner has provided Ohio EPA with 15 days written notice of the relocation.

Any site approvals issued by the Ohio EPA, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), shall be valid for no longer than 3 years and are subject to renewal.

In order for the City of Toledo, Division of Environmental Services and the appropriate field office having jurisdiction over the new site to determine compliance with all of the above criteria, the permittee of the portable emissions unit must file a " Notice of Intent to Relocate", within the specified time frame (30 or 15 days) prior to the relocation of the emissions unit with the City of Toledo, Division of Environmental Services and the appropriate field office having jurisdiction over the new site. Upon receipt of the notice, the City of Toledo, Division of Environmental Services, and/or appropriate field office having jurisdiction over the new site, will evaluate the request in accordance with the above criteria.

Failure to submit said notification and to receive Ohio EPA approval prior to relocation of the emissions unit may result in fines and civil penalties.

Pursuant to OAC rule 3745-31-05(F), the Director may modify the site approval to add or delete certain portable sources or add or delete certain terms and conditions as appropriate.

E. Testing Requirements

1. Compliance with the emission limitations in section A.1. of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation:

Visible emissions of fugitive dust shall not exceed 10% opacity as a three-minute average.

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with Method 9 of 40 CFR Part 60, Appendix A using the methods and

Kuhlman Corporation
PTI A
Issued

Facility ID: 0448970001

Emissions Unit ID: F001

procedures specified in OAC rule 3745-17-03(B)(3).

Kuhln

PTI A

Emissions Unit ID: **F001**

Issued: To be entered upon final issuance

b. Emission Limitation:

The emissions of fugitive dust shall not exceed 9.28 pounds of PE per hour.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum hourly throughput rate (160 cuyd) and the controlled emissions factor listed in AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 11.12, Table 11.12-3, dated 10/01/98, (0.058 lb PE/cuyd) as follows:

$$(160 \text{ cuyd/hr})(0.058 \text{ lb PE/cuyd}) = 9.28 \text{ lb PE/hr}$$

c. Emission Limitation:

The emissions of fugitive dust shall not exceed 2.18 tons of PE per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum annual throughput rate (75,000 cuyd) and the controlled emissions factor listed in AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 11.12, Table 11.12-3, dated 10/01/98, (0.058 lb PE/cuyd) as follows:

$$(75,000 \text{ cuyd/yr})(0.058 \text{ lb PE/cuyd})(1 \text{ t}/2000 \text{ lb}) = 2.18 \text{ tPE/yr}$$

d. Emission Limitation:

The emissions of fugitive dust shall not exceed 2.24 pounds of PM10 per hour.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum hourly throughput rate (160 cuyd) and the controlled emissions factor listed in AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 11.12, Table 11.12-3, dated 10/01/98, (0.014 lb PM10/cuyd) as follows:

$$(160 \text{ cuyd/hr})(0.014 \text{ lb PM10/cuyd}) = 2.24 \text{ lb PM10/hr}$$

e. Emission Limitation:

Kuhln

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: **F001**

The emissions of fugitive dust shall not exceed 0.53 ton of PM10 per rolling, 12-month period.

Kuhln

PTI A

Emissions Unit ID: **F001**

Issued: To be entered upon final issuance

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum annual throughput rate (75,000 cuyd) and the controlled emissions factor listed in AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 11.12, Table 11.12-3, dated 10/01/98, (0.014 lb PM10/cuyd) as follows:

$$(75,000 \text{ cuyd/yr})(0.014 \text{ lb PM10/cuyd})(1 \text{ t}/2000 \text{ lb}) = 0.53 \text{ tPM10/yr}$$

f. Emission Limitation:

The emissions of fugitive dust shall not exceed 1.26 pounds of PE per hour.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum hourly throughput rate (160 cuyd) and the controlled emissions factor listed in AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 11.12, Table 11.12-3, dated 10/01/98, (0.0079 lb PE/cuyd) as follows:

$$(160 \text{ cuyd/hr})(0.0079 \text{ lb PE/cuyd}) = 1.26 \text{ lb PE/hr}$$

g. Emission Limitation:

The emissions of fugitive dust shall not exceed 0.30 ton of PE per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum annual throughput rate (75,000 cuyd) and the controlled emissions factor listed in AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 11.12, Table 11.12-3, dated 10/01/98, (0.0079 lb PE/cuyd) as follows:

$$(75,000 \text{ cuyd/yr})(0.0079 \text{ lb PE/cuyd})(1 \text{ t}/2000 \text{ lb}) = 0.30 \text{ tPE/yr}$$

h. Emission Limitation:

The emissions of fugitive dust shall not exceed 0.61 pound of PM10 per hour.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum hourly throughput rate (160 cuyd) and the controlled emissions factor listed in AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 11.12, Table 11.12-3, dated 10/01/98, (0.0038 lb PM10/cuyd) as follows:

$$(160 \text{ cuyd/hr})(0.0038 \text{ lb PM10/cuyd}) = 0.61 \text{ lb PM10/hr}$$

i. Emission Limitation:

The emissions of fugitive dust shall not exceed 0.14 ton of PM10 per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum annual throughput rate (75,000 cuyd) and the controlled emissions factor listed in AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 11.12, Table 11.12-3, dated 10/01/98, (0.0038 lb PM10/cuyd) as follows:

$$(75,000 \text{ cuyd/yr})(0.0038 \text{ lb PM10/cuyd})(1 \text{ t}/2000 \text{ lb}) = 0.14 \text{ t PM10/yr}$$

F. Miscellaneous Requirements

1. All requirements of Sections A. through E. of this permit to install are federally enforceable.

Kuhln

PTI A

Emissions Unit ID: **F002**

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, <u>and/or Equipment</u>		
F002 - portable plant seven, 160 cuyd/hr portable trans-mix concrete plant: sand and aggregate storage piles	load-out	front end loader
load-in		

Kuhln

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: **F002**

	<u>Applicable Rules/Requirements</u>	
	OAC rule 3745-31-05(A)(3)	OAC rule 3745-31-05(A)(3)
wind erosion	OAC rule 3745-31-05(C)	OAC rule 3745-31-05(C)
	OAC rule 3745-17-07(B)(1)	OAC rule 3745-17-07(B)(1)
	OAC rules 3745-17-08(B), (B)(3), (B)(6), (B)(7)	OAC rules 3745-17-08(B), (B)(3), (B)(6), (B)(7)
		OAC rule 3745-31-05(A)(3)

Kuhln

PTI A

Emissions Unit ID: F002

Issued: To be entered upon final issuance

	<u>Applicable Emissions Limitations/Control Measures</u>	
	The emissions of fugitive dust shall not exceed 1.26 pounds of particulate emissions (PE) per hour.	diameter (PM10) shall not exceed 0.61 pound per hour.
	The emissions of fugitive dust equal to or less than 10 microns in diameter (PM10) shall not exceed 0.61 pound per hour.	There shall be no visible emissions of fugitive dust except for a period of time not to exceed 1 minute in any 60-minute observation period.
OAC rule 3745-31-05(C)	There shall be no visible emissions of fugitive dust except for a period of time not to exceed 1 minute in any 60-minute observation period.	See sections A.2.a, c, d and e.
	See sections A.2.a, c, d and e.	The emissions of fugitive dust shall not exceed 0.30 ton of PE per rolling, 12-month period.
OAC rules 3745-17-07(B)(1), (B)(5)	The emissions of fugitive dust shall not exceed 0.30 ton of PE per rolling, 12-month period.	The emissions of fugitive dust equal to or less than 10 microns in diameter (PM10) shall not exceed 0.15 ton per rolling, 12-month period.
OAC rules 3745-17-08(B), (B)(2)	The emissions of fugitive dust equal to or less than 10 microns in diameter (PM10) shall not exceed 0.15 ton per rolling, 12-month period.	See section A.2.f.
OAC rule 3745-31-05(A)(3)	See section A.2.f. See section A.2.g.	See section A.2.g.
OAC rule 3745-31-05(C)	See section A.2.g.	The emissions of fugitive dust shall not exceed 1.38 pounds of particulate emissions (PE) per hour.
OAC rule 3745-17-07(B)(6)	The emissions of fugitive dust shall not exceed 1.26 pounds of particulate emissions (PE) per hour.	The emissions of fugitive dust equal to or less than 10 microns in diameter (PM10) shall not exceed 0.38 pound per hour.
OAC rules 3745-17-08(B), (B)(6)	The emissions of fugitive dust equal to or less than 10 microns in	There shall be no visible emissions of fugitive dust except for a period of time not to exceed 3 minutes in any 60-minute observation period.

See sections A.2.a, c, d and e.

The emissions of fugitive dust shall not exceed 0.32 ton of PE per rolling, 12-month period.

The emissions of fugitive PM10 shall not exceed 0.09 ton per rolling, 12-month period.

See section A.2.f.

See section A.2.g.

See sections A.2. g.

There shall be no visible emissions of fugitive dust except for a period of time not to exceed 1 minute in any 60-minute observation period.

See sections A.2.a through e.

The emissions of fugitive dust shall not exceed 1.07 tons of PE per rolling, 12-month period.

The emissions of fugitive dust equal to or less than 10 microns in diameter (PM10) shall not exceed 0.43 ton per rolling, 12-month period.

See section A.2.f.

See section A.2. g.

See section A.2. g.

Issued: To be entered upon final issuance

2. Additional Terms and Conditions

- 2.a** The permittee shall employ the following best available control measures for the processes comprising this emissions unit for the purpose of ensuring compliance with the above-mentioned applicable requirements:

The permittee shall install and employ a water spray system to maintain adequate moisture in the materials being handled and stored. These control systems shall be operated at all times that the associated process is in operation and these controls shall be sufficient to minimize or eliminate visible emissions of fugitive dust from this emissions unit. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

- 2.b** The above-mentioned control measure(s) shall be employed for wind erosion from each pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) are necessary to ensure compliance with the above-mentioned applicable requirements. Implementation of the control measure(s) shall not be necessary for a storage pile that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements.
- 2.c** Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the requirements of OAC rules 3745-17-08 and 3745-31-05.
- 2.d** The hourly particulate emission limitations specified above are based upon the emissions unit's potential to emit. Therefore, no hourly records are required to be maintained to demonstrate compliance with these limitations.
- 2.e** The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(C).
- 2.f** The rolling, 12-month particulate emission limitations specified above are based upon the emissions unit's potential to emit at a rolling, 12-month production restriction of 75,000 cubic yards of concrete made enforceable in the associated emissions unit, F001. Therefore, no emission records are required to be maintained for this emissions unit to demonstrate compliance with these limitations.
- 2. g** The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform daily inspections of each of the above-identified processes at each storage pile.
2. No inspection shall be necessary for wind erosion from the surface of a storage pile when the pile is covered with snow and/or ice and for any storage pile activity if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements.
3. The purpose of the inspections is to determine the need for implementing the control measures specified in this permit. The inspections shall be performed during representative, normal storage pile operating conditions.
4. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.
5. The permittee shall maintain records of the following information:
 - a. the date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;
 - b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;
 - c. the dates the control measures were implemented; and
 - d. on a calendar quarter basis, the total number of days the control measures were implemented and, for wind erosion from pile surfaces, the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measure(s).

The information required in 5.d. shall be kept separately for (i) the load-in operations, (ii) the load-out operations, (iii) front end loader operation and (iv) the pile surfaces (wind erosion), and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit semi-annual deviation reports that identify any of the following occurrences:
 - a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and
 - b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.

These reports shall be submitted to the City of Toledo, Division of Environmental Services and the appropriate field office (having jurisdiction over the new site) by January 31 and July 31 of each year and shall cover the previous 6-month period.

2. Pursuant to OAC rule 3745-31-03(A)(1)(p), the permittee of a portable emissions unit may relocate within the State of Ohio without first obtaining a permit to install (PTI) providing certain criteria are met. The portable emissions unit shall meet one of the two following scenarios in order to qualify for this PTI exemption for the new location:
 - a. The following determinations have been documented, pursuant to OAC rule 3745-31-03(A)(1)(p)(i):
 - i. the portable emissions unit is equipped with the best available technology for such portable emissions unit;
 - ii. the portable emissions unit is operating pursuant to a currently effective permit to operate (PTO) or registration status;
 - iii. the applicant has provided proper notice of intent to relocate the portable emissions unit to the City of Toledo, Division of Environmental Services and the appropriate field office having jurisdiction over the new site within a minimum of 30 days prior to the scheduled relocation; and
 - iv. in the City of Toledo, Division of Environmental Services and the appropriate field office's (having jurisdiction over the new site) judgement, the proposed site is acceptable under OAC rule 3745-15-07.

Kuhln

PTI A

Emissions Unit ID: **F002**

Issued: To be entered upon final issuance

- b. In the alternative, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), the permittee of a portable emissions unit may relocate within the State of Ohio without first obtaining a PTI, providing the following criteria of OAC rule 3745-31-05(E) are met:
 - i. the portable emissions unit permittee possesses an Ohio EPA PTI, PTO or registration status;
 - ii. the portable emissions unit is equipped with best available technology;
 - iii. the portable emissions unit owner has identified the proposed site to Ohio EPA;
 - iv. Ohio EPA has determined that the portable emissions unit, at the proposed site, will have an acceptable environmental impact;
 - v. a public notice, consistent with OAC Chapter 3745-47, is published in the county where the proposed site is located;

Emissions Unit ID: **F002**

- vi. the owner of the proposed site has provided the portable emissions unit owner with approval or equivalent declaration that it is acceptable to the site owner to move the portable emissions unit to this proposed site; and
- vii. the portable emissions unit owner has provided Ohio EPA with 15 days written notice of the relocation.

Any site approvals issued by the Ohio EPA, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), shall be valid for no longer than 3 years and are subject to renewal.

In order for the City of Toledo, Division of Environmental Services and the appropriate field office having jurisdiction over the new site to determine compliance with all of the above criteria, the permittee of the portable emissions unit must file a " Notice of Intent to Relocate", within the specified time frame (30 or 15 days) prior to the relocation of the emissions unit with the City of Toledo, Division of Environmental Services and the appropriate field office having jurisdiction over the new site. Upon receipt of the notice, the City of Toledo, Division of Environmental Services, and/or appropriate field office having jurisdiction over the new site, will evaluate the request in accordance with the above criteria.

Failure to submit said notification and to receive Ohio EPA approval prior to relocation of the emissions unit may result in fines and civil penalties.

Pursuant to OAC rule 3745-31-05(F), the Director may modify the site approval to add or delete certain portable sources or add or delete certain terms and conditions as appropriate.

E. Testing Requirements

1. Compliance with the emission limitations in section A.1. of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation:

There shall be no visible emissions of fugitive dust except for a period of time not to exceed 1 minute in any 60-minute observation period.

Applicable Compliance Method:

Compliance with the visible emission limitations for the storage piles identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs

Kuhln

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: **F002**

(B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

Kuhln

PTI A

Emissions Unit ID: **F002**

Issued: To be entered upon final issuance

b. Emission Limitation:

The emissions of fugitive dust shall not exceed 1.26 pounds of particulate emissions (PE) per hour.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum hourly throughput rate (160 cuyd) and the controlled emissions factor listed in AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 11.12, Table 11.12-3, dated 10/01/98, (0.0064 lb PE/cuyd for aggregate and 0.0015 lb PE/cuyd for sand) as follows:

$$(160 \text{ cuyd/hr})(0.0064 + 0.0015 \text{ lb PE/cuyd}) = 1.26 \text{ lb PE/hr}$$

c. Emission Limitation:

The emissions of fugitive dust shall not exceed 0.30 ton of PE per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum annual throughput rate (75,000 cuyd) and the controlled emissions factor listed in AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 11.12, Table 11.12-3, dated 10/01/98, (0.0064 lb PE/cuyd for aggregate and 0.0015 lb PE/cuyd for sand) as follows:

$$(75,000 \text{ cuyd/yr})(0.0064 + 0.0015 \text{ lb PE/cuyd}) \div (2000 \text{ lb /t}) = 0.30 \text{ tPE/yr}$$

d. Emission Limitation:

The emissions of fugitive dust shall not exceed 0.61 pound of PM10 per hour.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum hourly throughput rate (160 cuyd) and the controlled emissions factor listed in AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 11.12, Table 11.12-3, dated 10/01/98, (0.0031 lb PM10/cuyd for aggregate and 0.0007 lb PM10/cuyd

Kuhlman Corporation
PTI A
Issued

Facility ID: 0448970001

Emissions Unit ID: F002

for sand) as follows:

$$(160 \text{ cuyd/hr})(0.0031 + 0.0007 \text{ lb PM}_{10}/\text{cuyd}) = 0.61 \text{ lb PM}_{10}/\text{hr}$$

Kuhln

PTI A

Emissions Unit ID: **F002**

Issued: To be entered upon final issuance

e. Emission Limitation:

The emissions of fugitive dust shall not exceed 0.15 ton of PM10 per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum annual throughput rate (75,000 cuyd) and the controlled emissions factor listed in AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 11.12, Table 11.12-3, dated 10/01/98, (0.0031 lb PM10/cuyd for aggregate and 0.0007 lb PM10/cuyd for sand) as follows:

$$(75,000 \text{ cuyd/yr})(0.0031 + 0.0007 \text{ lb PM10/cuyd}) \div (2000 \text{ lb /t}) = 0.15 \text{ tPM10/yr}$$

f. Emission Limitation:

The emissions of fugitive dust shall not exceed 1.38 pounds of particulate emissions (PE) per hour.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum annual throughput rate (75,000 cuyd), 75% control efficiency for adequate moisture and the emissions factor calculated by AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 13.2.2, Equation 1a, dated 12/03 as follows:

$$E = [k(s/12)^a (W/3)^b] = 8.11 \text{ lb PE/VMT}$$

Where:

E = emission factor, pounds per vehicle mile traveled (lb/VMT)

k = 4.9 for PE

a = 0.7 for PE

b = 0.45

s = surface material silt content = 7.1 (Table 13.2.2-2)

W = average vehicle weight (20.8 tons per Kuhlman)

Given 160 yard per hour of concrete production, sand and aggregate to comprise 90% of the concrete by volume, a four yard bucket and 100 feet round trip:

Kuhln

PTI A

Emissions Unit ID: **F002**

Issued: To be entered upon final issuance

$$\begin{aligned} \text{VMT/hr} &= 100 \text{ ft/load} (1 \text{ mi}/5280 \text{ ft})(160 \text{ yd concrete/hr})(0.9 \text{ yd/yd concrete})(1 \text{ load}/4 \text{ yd}) \\ \text{VMT/hr} &= 0.68 \text{ mi/hr} \end{aligned}$$

Then with 75% effective control by watering:

$$\text{Emissions} = (8.11 \text{ lb PE/VMT})(0.68 \text{ mi/hr})(1 - 0.75) = 1.38 \text{ lb PE/hr}$$

g. Emission Limitation:

The emissions of fugitive dust shall not exceed 0.32 ton of PE per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum annual throughput rate (75,000 cuyd) and the hourly emission factor calculated above:

$$\text{Emissions} = 1.38 \text{ lb/hr} (75000 \text{ yd/yr})(1 \text{ hr}/160 \text{ yd})(1 \text{ t}/2000 \text{ lb}) = 0.32 \text{ t PE/yr}$$

h. Emission Limitation:

The emissions of fugitive dust shall not exceed 0.38 pound of PM10 per hour.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum annual throughput rate (75,000 cuyd), 75% control efficiency for adequate moisture and the emissions factor calculated by AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 13.2.2, Equation 1a, dated 12/03 as follows:

$$E = k(s/12)^a (W/3)^b = 2.24 \text{ lb PM10/VMT}$$

Where:

E = emission factor, pounds per vehicle mile traveled (lb/VMT)

k = 1.5 for PM10

a = 0.9 for PM10

b = 0.45

Kuhln

PTI A

Emissions Unit ID: **F002**

Issued: To be entered upon final issuance

s = surface material silt content = 7.1 (Table 13.2.2-2)

W = average vehicle weight (20.8 tons per Kuhlman)

Given 160 yard per hour of concrete production, sand and aggregate to comprise 90% of the concrete by volume, a four yard bucket and 100 feet round trip:

$VMT/hr = 100 \text{ ft/load} (1 \text{ mi}/5280 \text{ ft})(160 \text{ yd concrete/hr})(0.9 \text{ yd/yd concrete})(1 \text{ load}/4 \text{ yd})$

$VMT/hr = 0.68 \text{ mi/hr}$

Then with 75% effective control by watering:

$Emissions = (2.24 \text{ lb PE/VMT})(0.68 \text{ mi/hr})(1 - 0.75) = 0.38 \text{ lb PM}_{10}/hr$

i. Emission Limitation:

The emissions of fugitive dust shall not exceed 0.09 ton of PM₁₀ per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum annual throughput rate (75,000 cuyd) and the hourly emission factor calculated above:

$Emissions = 0.38 \text{ lb/hr} (75000 \text{ yd/yr})(1 \text{ hr}/160 \text{ yd})(1 \text{ t}/2000 \text{ lb}) = 0.09 \text{ t PM}_{10}/yr$

j. Emission Limitation:

The emissions of fugitive dust shall not exceed 1.73 tons of PE per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing a storage area of 0.25 acre each of sand and gravel, a throughput rate 75,000 cubic yards of concrete per rolling, 12-month period, 75% control efficiency for adequate moisture and the emissions factor calculated by USEPA RACM Guide, Section 2.2.1, dated 9/80, as follows:

$E = 0.05 (S/1.5)(D/90)(d/235)(f/15)$

where:

E = PE emission factor (lb /ton)

S = silt content = 2% aggregate & 10% sand (Table 2.1.2-2)

D = duration of storage

d = dry days per year = 229 days (Figure 2.1.2-2)

f = percentage of time wind speed exceeds 12 mph = 20%

the storage piles are estimated at an individual maximum 0.25 acre x 9 feet in height = 90,000 cuft. At a density of 100 lb /cuft for sand and 90 lb /cuft for limestone, and a formula weight for 75,000 yd/yr of concrete of 1865 lb aggregate and 1428 lb sand per yard:

usage = 75,000 yd concrete/yr (1865 lb aggregate/yd concrete)(1 cuft/90 lb aggregate) = 1,550,000 cuft aggregate/yr

$D_{\text{aggregate}} = 365 \text{ days} \div (1,550,000 \text{ cuft})(1 \text{ turnover}/90000 \text{ cuft}) = 21 \text{ days for aggregate}$

usage = 75,000 yd concrete/yr (1428 lb sand/yd concrete)(1 cuft/100 lb sand) = 1,070,000 cuft sand/yr

$D_{\text{sand}} = 365 \text{ days} \div (1,070,000 \text{ cuft})(1 \text{ turnover}/90000 \text{ cuft}) = 30 \text{ days for sand}$

then:

$E_{\text{aggregate}} = 0.05 (10/1.5)(21/90)(229/235)(20/15) = 0.101 \text{ lb /t}$

$E_{\text{sand}} = 0.05 (2/1.5)(30/90)(229/235)(20/15) = 0.029 \text{ lb /t}$

and for a control efficiency of 75%:

Emissions = $1 - 0.75$ [(0.101 lb /t)(75,000 yd concrete/yr)(1865 lb aggregate/yd concrete) +

(0.029 lb /t)(75,000 yd concrete/yr)(1428 lb sand/yd concrete)] (1/2000 lb)²

Emissions = 1.07 tPE/yr

k. Emission Limitation:

The emissions of fugitive dust shall not exceed 0.43 ton of PM10 per rolling, 12-month period.

Applicable Compliance Method:

Kuhln

PTI A

Emissions Unit ID: **F002**

Issued: To be entered upon final issuance

Compliance shall be demonstrated by a one time emissions calculation utilizing the allowable PE emission factor calculated above, adjusted to PM10 as 40% of the mass of PE (RACM guide, Table 2.1.2-6):

$$\text{Emissions} = 1.07 \text{ tPE/yr} (0.40 \text{ tPM10/tPE}) = 0.43 \text{ tPM10/yr}$$

F. Miscellaneous Requirements

1. All requirements of Sections A. through E. of this permit to install are federally enforceable.

Kuhln

PTI A

Emissions Unit ID: **F003**

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>
F003 - portable plant seven, 160 cuyd/hr portable trans-mix concrete plant: transfer of sand and aggregate to bins	OAC rule 3745-31-05(A)(3)
pneumatic conveying of cement to the storage silo with a fabric filter	OAC rule 3745-31-05(C)
	OAC rule 3745-17-07(B)(1)

Kuhln

PTI A

Emissions Unit ID: **F003**

Issued: To be entered upon final issuance

OAC rule 3745-17-08(B), (B)(3)

OAC rule 3745-31-05(A)(3)

Applicable Emissions
Limitations/Control Measures

The emissions of fugitive dust shall not exceed 1.26 pounds of particulate emissions (PE) per hour .

The emissions of fugitive dust equal to or less than 10 microns in diameter (PM10) shall not exceed 0.61 pound per hour.

Visible emissions of fugitive dust shall not exceed 10% opacity as a three-minute average.

See sections A.2.a and c through e.

The emissions of fugitive dust shall not exceed 0.30 ton of PE per rolling, 12-month period.

The emissions of fugitive PM10 shall not exceed 0.15 ton per rolling, 12-month period.

See section A.2.f.

See section A.2.g.

See section A.2.g.

OAC rule 3745-31-05(C)

OAC rule 3745-17-07(B)(1)

OAC rule 3745-17-08(B), (B)(3)

The particulate emissions (PE) from the baghouse stack shall not exceed 0.03 pounds per hour .

The emissions of particulate from the baghouse stack equal to or less than 10 microns in diameter (PM10) shall not exceed 0.02 pound per hour

Visible emissions of fugitive dust shall not exceed 10% opacity as a three-minute average.

Visible emissions of particulate from the baghouse filter stack shall not exceed 10% opacity as a six-minute average.

See sections A.2.b through e.

The particulate emissions (PE) from the baghouse stack shall not exceed 0.01 ton per rolling, 12-month period.

The emissions of particulate from the baghouse stack equal to or less than 10 microns in diameter (PM10) shall not exceed 0.01 ton per rolling, 12-month period.

See section A.2.f.

See section A.2.g.

See section A.2.g.

Kuhlman Corporation
PTI A
Issued

Facility ID: 0448970001

Emissions Unit ID: **F003**

2. Additional Terms and Conditions

- 2.a** The permittee shall employ the following best available control measures for the transfer process of sand and aggregate to the elevated storage bins for the purpose of ensuring compliance with the associated applicable requirements:

Issued: To be entered upon final issuance

The permittee shall install and employ water spray systems to maintain adequate moisture in the materials being handled. These control systems shall be operated at all times that the transfer process is in operation and these controls shall be sufficient to minimize or eliminate visible emissions of fugitive dust from the transfer of sand and aggregate to the elevated storage bins. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

- 2.b** The permittee shall employ the following best available control measures for the pneumatic conveying process for the purpose of ensuring compliance with the above-mentioned applicable requirements:

The permittee shall install and employ a dust collection system equipped with a fabric filter. This control system shall be operated at all times that the associated process is in operation and this control shall be sufficient to minimize or eliminate visible emissions of fugitive dust from the pneumatic conveying of cement to the storage silo. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

- 2.c** Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the requirements of OAC rules 3745-17-08 and 3745-31-05.
- 2.d** The hourly particulate emission limitations specified above are based upon the emissions unit's potential to emit. Therefore, no hourly records are required to be maintained to demonstrate compliance with these limitations.
- 2.e** The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(C).
- 2.f** The rolling, 12-month particulate emission limitations specified above are based upon the emissions unit's potential to emit at a rolling, 12-month production restriction of 75,000 cubic yards of concrete made enforceable in the associated emissions unit, F001. Therefore, no emission records are required to be maintained for this emissions unit to demonstrate compliance with these limitations.
- 2.g** The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

Kuhln

PTI A

Issued: To be entered upon final issuance

None

Emissions Unit ID: **F003**

Issued: To be entered upon final issuance

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall perform daily checks, when the associated process is in operation and when the weather conditions allow, for any visible particulate emissions from the baghouse stack and for any visible fugitive particulate emissions from the pneumatic conveying of cement or the transfer of sand and aggregate to the elevated bins. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. the location and color of the emissions;
 - b. whether the emissions are representative of normal operations;
 - c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. the total duration of any visible emission incident; and
 - e. any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item (d) above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

D. Reporting Requirements

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the baghouse stack serving this emissions unit, (b) identify all days during which any visible fugitive particulate emissions were observed from the pneumatic conveying of cement or the transfer of sand and aggregate to the elevated bins, and (c) describe any corrective actions taken to minimize or eliminate the visible particulate and/or visible fugitive particulate emissions. These reports shall be submitted to the City of Toledo, Division of Environmental Services and the appropriate field office (having jurisdiction over the new site) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. Pursuant to OAC rule 3745-31-03(A)(1)(p), the permittee of a portable emissions unit may relocate within the State of Ohio without first obtaining a permit to install (PTI) providing certain criteria are met. The portable emissions unit shall meet one of the two following scenarios in

order to qualify for this PTI exemption for the new location:

- a. The following determinations have been documented, pursuant to OAC rule 3745-31-03(A)(1)(p)(i):
 - i. the portable emissions unit is equipped with the best available technology for such portable emissions unit;
 - ii. the portable emissions unit is operating pursuant to a currently effective permit to operate (PTO) or registration status;
 - iii. the applicant has provided proper notice of intent to relocate the portable emissions unit to the City of Toledo, Division of Environmental Services and the appropriate field office having jurisdiction over the new site within a minimum of 30 days prior to the scheduled relocation; and
 - iv. in the City of Toledo, Division of Environmental Services and the appropriate field office's (having jurisdiction over the new site) judgement, the proposed site is acceptable under OAC rule 3745-15-07.

- b. In the alternative, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), the permittee of a portable emissions unit may relocate within the State of Ohio without first obtaining a PTI, providing the following criteria of OAC rule 3745-31-05(E) are met:
 - i. the portable emissions unit permittee possesses an Ohio EPA PTI, PTO or registration status;
 - ii. the portable emissions unit is equipped with best available technology;
 - iii. the portable emissions unit owner has identified the proposed site to Ohio EPA;
 - iv. Ohio EPA has determined that the portable emissions unit, at the proposed site, will have an acceptable environmental impact;
 - v. a public notice, consistent with OAC Chapter 3745-47, is published in the county where the proposed site is located;
 - vi. the owner of the proposed site has provided the portable emissions unit owner with approval or equivalent declaration that it is acceptable to the site owner to move the portable emissions unit to this proposed site; and

- vii. the portable emissions unit owner has provided Ohio EPA with 15 days written notice of the relocation.

Any site approvals issued by the Ohio EPA, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), shall be valid for no longer than 3 years and are subject to renewal.

In order for the City of Toledo, Division of Environmental Services and the appropriate field office having jurisdiction over the new site to determine compliance with all of the above criteria, the permittee of the portable emissions unit must file a " Notice of Intent to Relocate", within the specified time frame (30 or 15 days) prior to the relocation of the emissions unit with the City of Toledo, Division of Environmental Services and the appropriate field office having jurisdiction over the new site. Upon receipt of the notice, the City of Toledo, Division of Environmental Services, and/or appropriate field office having jurisdiction over the new site, will evaluate the request in accordance with the above criteria.

Failure to submit said notification and to receive Ohio EPA approval prior to relocation of the emissions unit may result in fines and civil penalties.

Pursuant to OAC rule 3745-31-05(F), the Director may modify the site approval to add or delete certain portable sources or add or delete certain terms and conditions as appropriate.

E. Testing Requirements

1. Compliance with the emission limitations in section A.1. of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emission Limitation:

Visible emissions of fugitive dust shall not exceed 10% opacity as a three-minute average.

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with Method 9 of 40 CFR Part 60, Appendix A using the methods and procedures specified in OAC rule 3745-17-03(B)(3).
 - b. Emission Limitation:

Visible emissions of particulate from the baghouse filter stack shall not exceed 10% opacity as a six-minute average.

Kuhln

PTI A

Emissions Unit ID: **F003**

Issued: To be entered upon final issuance

Applicable Compliance Method:

Compliance shall be determined through visible emission observations performed in accordance with Method 9 of 40 CFR Part 60, Appendix A using the methods and procedures specified in OAC rule 3745-17-03(B)(1).

c. Emission Limitation:

The emissions of fugitive dust shall not exceed 1.26 pounds of particulate emissions (PE) per hour.

Kuhln

PTI A

Emissions Unit ID: **F003**

Issued: To be entered upon final issuance

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum hourly throughput rate (160 cuyd) and the controlled emissions factor listed in AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 11.12, Table 11.12-3, dated 10/01/98, (0.0064 lb PE/cuyd for aggregate and 0.0015 lb PE/cuyd for sand) as follows:

$$(160 \text{ cuyd/hr})(0.0064 + 0.0015 \text{ lb PE/cuyd}) = 1.26 \text{ lb PE/hr}$$

c. Emission Limitation:

The emissions of fugitive dust shall not exceed 0.30 ton of PE per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum annual throughput rate (75,000 cuyd) and the controlled emissions factor listed in AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 11.12, Table 11.12-3, dated 10/01/98, (0.0064 lb PE/cuyd for aggregate and 0.0015 lb PE/cuyd for sand) as follows:

$$(75,000 \text{ cuyd/yr})(0.0064 + 0.0015 \text{ lb PE/cuyd}) \div (2000 \text{ lb /t}) = 0.30 \text{ tPE/yr}$$

d. Emission Limitation:

The emissions of fugitive dust shall not exceed 0.61 pound of PM10 per hour.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum hourly throughput rate (160 cuyd) and the controlled emissions factor listed in AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 11.12, Table 11.12-3, dated 10/01/98, (0.0031 lb PM10/cuyd for aggregate and 0.0007 lb PM10/cuyd for sand) as follows:

$$(160 \text{ cuyd/hr})(0.0031 + 0.0007 \text{ lb PM10/cuyd}) = 0.61 \text{ lb PM10/hr}$$

e. Emission Limitation:

Kuhln

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: **F003**

The emissions of fugitive dust shall not exceed 0.15 ton of PM10 per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum annual throughput rate (75,000 cuyd) and the controlled emissions factor listed in AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 11.12, Table 11.12-3, dated 10/01/98, (0.0031 lb PM10/cuyd for aggregate and 0.0007 lb PM10/cuyd for sand) as follows:

$$(75,000 \text{ cuyd/yr})(0.0031 + 0.0007 \text{ lb PM10/cuyd}) \div (2000 \text{ lb /t}) = 0.15 \text{ tPM10/yr}$$

f. Emission Limitation:

The particulate emissions (PE) from the baghouse stack shall not exceed 0.03 pounds per hour.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum hourly throughput rate (160 cuyd) and the controlled emissions factor listed in AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 11.12, Table 11.12-3, dated 10/01/98, (0.0002 lb PE/cuyd) as follows:

$$(160 \text{ cuyd/hr})(0.0002 \text{ lb PE/cuyd}) = 0.03 \text{ lb PE/hr}$$

c. Emission Limitation:

The particulate emissions (PE) from the baghouse stack shall not exceed 0.01 ton per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum annual throughput rate (75,000 cuyd) and the controlled emissions factor listed in AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 11.12, Table 11.12-3, dated 10/01/98, (0.0002 lb PE/cuyd) as follows:

$$(75,000 \text{ cuyd/yr})(0.0002 \text{ lb PE/cuyd}) \div (2000 \text{ lb/t}) = 0.01 \text{ tPE/yr}$$

d. Emission Limitation:

The emissions of PM10 from the baghouse stack shall not exceed 0.02 pound per hour.

Kuhln

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: **F003**

Applicable Compliance Method:

Kuhln

PTI A

Emissions Unit ID: **F003**

Issued: To be entered upon final issuance

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum hourly throughput rate (160 cuyd) and the controlled emissions factor listed in AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 11.12, Table 11.12-3, dated 10/01/98, (0.0001 lb PM10/cuyd) as follows:

$$(160 \text{ cuyd/hr})(0.0001 \text{ PM10/cuyd}) = 0.02 \text{ lb PM10/hr}$$

e. Emission Limitation:

The emissions of PM10 from the baghouse stack shall not exceed 0.01 ton per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum annual throughput rate (75,000 cuyd) and the controlled emissions factor listed in AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 11.12, Table 11.12-3, dated 10/01/98, (0.0001 lb PM10/cuyd) as follows:

$$(75,000 \text{ cuyd/yr})(0.0001 \text{ lb PM10/cuyd}) \div (2000 \text{ lb/t}) = 0.01 \text{ tPM10/yr}$$

F. Miscellaneous Requirements

1. All requirements of Sections A. through E. of this permit to install are federally enforceable.

Kuhln

PTI A

Emissions Unit ID: **F004**

Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	OAC rule 3745-17-07(B)(1), (B)(5)
F004 - portable plant seven, 160 cuyd/hr portable trans-mix concrete plant: unpaved roadways and parking lots	OAC rule 3745-31-05(A)(3)	OAC rule 3745-17-08(B), (B)(2), (B)(7), (B)(8), (B)(9)
	OAC rule 3745-31-05(C)	

Kuhln

PTI A

Emissions Unit ID: **F004**

Issued: To be entered upon final issuance

Applicable Emissions
Limitations/Control Measures

The emissions of fugitive dust shall not exceed 6.00 pounds of particulate emissions (PE) per hour

The emissions of fugitive dust equal to or less than 10 microns in diameter (PM10) shall not exceed 1.53 pounds per hour.

There shall be no visible emissions of fugitive dust except for a period of time not to exceed 3 minute in any 60-minute observation period.

See section A.2.a thru h.

The emissions of fugitive dust shall not exceed 1.41 tons of PE per rolling, 12-month period.

The emissions of fugitive dust equal to or less than 10 microns in diameter (PM10) shall not exceed 0.36 ton per rolling, 12-month period.

See section A.2.i.

See section A.2.j.

See section A.2.j.

2. Additional Terms and Conditions

2.a The permittee shall employ best available control measures on all unpaved roadways and

Emissions Unit ID: **F004**

parking areas for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to treat the unpaved roadways and parking areas with water at sufficient treatment frequencies to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

- 2.b** The needed frequencies of implementation of the control measures shall be determined by the permittee's inspections pursuant to the monitoring section of this permit. Implementation of the control measures shall not be necessary for an unpaved roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Implementation of any control measure may be suspended if unsafe or hazardous driving conditions would be created by its use.
- 2.c** Any unpaved roadway or parking area, which during the term of this permit is paved or takes the characteristics of a paved surface due to the application of certain types of dust suppressants, may be controlled using sweeping or watering. Any unpaved roadway or parking area that takes the characteristics of a paved roadway or parking area due to the application of certain types of dust suppressants shall remain subject to the visible emission limitation for unpaved roadways and parking areas. Any unpaved roadway or parking area that is paved shall be subject to a visible emission limitation of no visible particulate emissions except for one minute during any 60-minute period.
- 2.d** The permittee shall promptly remove, in such a manner as to minimize or prevent resuspension, earth and/or other material from paved streets onto which such material has been deposited by trucking or earth moving equipment or erosion by water or other means.
- 2.e** Open-bodied vehicles transporting materials likely to become airborne shall have such materials covered at all times if the control measure is necessary for the materials being transported.
- 2.f** Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the best available technology requirements of OAC rule 3745-31-05.
- 2.g** The hourly particulate emission limitations specified above are based upon the emissions unit's potential to emit. Therefore, no hourly records are required to be maintained to demonstrate compliance with these limitations.
- 2.h** The requirements of this rule also include compliance with the requirements of OAC rule

Kuhln

PTI A

Emissions Unit ID: **F004**

Issued: To be entered upon final issuance

3745-31-05(C).

- 2.i** The rolling, 12-month particulate emission limitations specified above are based upon the emissions unit's potential to emit at a rolling, 12-month production restriction of 75,000 cubic yards of concrete made enforceable in the associated emissions unit, F001. Therefore, no emission records are required to be maintained for this emissions unit to demonstrate compliance with these limitations.
- 2.j** The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

- 1. Except as otherwise provided in this section, the permittee shall perform daily inspections of all unpaved roadways and parking areas comprising this emissions unit.
- 2. The purpose of the inspections is to determine the need for implementing the above-mentioned control measures. The inspections shall be performed during representative, normal traffic conditions. No inspection shall be necessary for a roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements.
- 3. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.
- 4. The permittee shall maintain records of the following information:
 - a. the date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;
 - b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;
 - c. the dates the control measures were implemented; and

Emissions Unit ID: **F004**

- d. on a calendar quarter basis, the total number of days the control measures were implemented and the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measures.

The information required in 4.d. shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

Kuhln

PTI A

Emissions Unit ID: **F004**

Issued: To be entered upon final issuance

D. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:
 - a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and
 - b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.

These reports shall be submitted to the City of Toledo, Division of Environmental Services and the appropriate field office (having jurisdiction over the new site) by January 31 and July 31 of each year and shall cover the previous 6-month period.

2. Pursuant to OAC rule 3745-31-03(A)(1)(p), the permittee of a portable emissions unit may relocate within the State of Ohio without first obtaining a permit to install (PTI) providing certain criteria are met. The portable emissions unit shall meet one of the two following scenarios in order to qualify for this PTI exemption for the new location:
 - a. The following determinations have been documented, pursuant to OAC rule 3745-31-03(A)(1)(p)(i):
 - i. the portable emissions unit is equipped with the best available technology for such portable emissions unit;
 - ii. the portable emissions unit is operating pursuant to a currently effective permit to operate (PTO) or registration status;
 - iii. the applicant has provided proper notice of intent to relocate the portable emissions unit to the City of Toledo, Division of Environmental Services and the appropriate field office having jurisdiction over the new site within a minimum of 30 days prior to the scheduled relocation; and
 - iv. in the City of Toledo, Division of Environmental Services and the appropriate field office's (having jurisdiction over the new site) judgement, the proposed site is acceptable under OAC rule 3745-15-07.
 - b. In the alternative, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), the permittee of a portable emissions unit may relocate within the State of Ohio without first obtaining a PTI, providing the following criteria of OAC rule 3745-31-05(E) are met:

Kuhn

PTI A

Emissions Unit ID: **F004**

Issued: To be entered upon final issuance

- i. the portable emissions unit permittee possesses an Ohio EPA PTI, PTO or registration status;
- ii. the portable emissions unit is equipped with best available technology;
- iii. the portable emissions unit owner has identified the proposed site to Ohio EPA;
- iv. Ohio EPA has determined that the portable emissions unit, at the proposed site, will have an acceptable environmental impact;
- v. a public notice, consistent with OAC Chapter 3745-47, is published in the county where the proposed site is located;
- vi. the owner of the proposed site has provided the portable emissions unit owner with approval or equivalent declaration that it is acceptable to the site owner to move the portable emissions unit to this proposed site; and
- vii. the portable emissions unit owner has provided Ohio EPA with 15 days written notice of the relocation.

Any site approvals issued by the Ohio EPA, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), shall be valid for no longer than 3 years and are subject to renewal.

In order for the City of Toledo, Division of Environmental Services and the appropriate field office having jurisdiction over the new site to determine compliance with all of the above criteria, the permittee of the portable emissions unit must file a " Notice of Intent to Relocate", within the specified time frame (30 or 15 days) prior to the relocation of the emissions unit with the City of Toledo, Division of Environmental Services and the appropriate field office having jurisdiction over the new site. Upon receipt of the notice, the City of Toledo, Division of Environmental Services, and/or appropriate field office having jurisdiction over the new site, will evaluate the request in accordance with the above criteria.

Failure to submit said notification and to receive Ohio EPA approval prior to relocation of the emissions unit may result in fines and civil penalties.

Pursuant to OAC rule 3745-31-05(F), the Director may modify the site approval to add or delete certain portable sources or add or delete certain terms and conditions as appropriate.

E. Testing Requirements

1. Compliance with the emission limitations in section A.1. of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation:

There shall be no visible emissions of fugitive dust except for a period of time not to exceed 3 minute in any 60-minute observation period.

Kuhln

PTI A

Emissions Unit ID: **F004**

Issued: To be entered upon final issuance

Applicable Compliance Method:

Compliance with the visible emission limitations for the storage piles identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

- b. The emissions of fugitive dust shall not exceed 6.00 pounds of particulate emissions (PE) per hour.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum annual throughput rate (75,000 cuyd), 75% control efficiency for adequate moisture and the emissions factor calculated by AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 13.2.2, Equation 1a, dated 12/03 as follows:

$$E = [k(s/12)^a (W/3)^b] = 6.82 \text{ lb PE/VMT}$$

Where:

E = emission factor, pounds per vehicle mile traveled (lb/VMT)

k = 4.9 for PE

a = 0.7 for PE

b = 0.45

s = surface material silt content = 7.1 (Table 13.2.2-2)

W = average vehicle weight (26 tons)

Given 160 yard per hour of concrete production, a 10 yard load, 500 feet round trip and doubling the estimated mileage to account for the delivery of raw materials:

$$\text{VMT/hr} = 500 \text{ ft/load} (1 \text{ mi}/5280 \text{ ft})(160 \text{ yd concrete/hr})(1 \text{ load}/10 \text{ yd})(2)$$

$$\text{VMT/hr} = 3.52 \text{ mi/hr}$$

Then with 75% effective control by watering:

$$\text{Emissions} = (6.82 \text{ lb PE/VMT})(3.52 \text{ mi/hr})(1 - 0.75) = 6.00 \text{ lb PE/hr}$$

- c. Emission Limitation:

Kuhln

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: **F004**

The emissions of fugitive dust shall not exceed 1.41 tons of PE per rolling, 12-month period.

Kuhln

PTI A

Emissions Unit ID: **F004**

Issued: To be entered upon final issuance

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum annual throughput rate (75,000 cuyd) and the hourly emission factor calculated above:

$$\text{Emissions} = 6.00 \text{ lb/hr} (75000 \text{ yd/yr})(1 \text{ hr}/160 \text{ yd})(1 \text{ t}/2000 \text{ lb}) = 1.41 \text{ t PE/yr}$$

d. Emission Limitation:

The emissions of fugitive dust shall not exceed 1.53 pounds of PM10 per hour.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum annual throughput rate (75,000 cuyd), 75% control efficiency for adequate moisture and the emissions factor calculated by AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 13.2.2, Equation 1a, dated 12/03 as follows:

$$E = k(s/12)^a (W/3)^b = 1.74 \text{ lb PM10/VMT}$$

Where:

E = emission factor, pounds per vehicle mile traveled (lb/VMT)

k = 1.5 for PM10

a = 0.9 for PM10

b = 0.45

s = surface material silt content = 4.8 (Table 13.2.2-2)

W = average vehicle weight (26 tons)

Given 160 yard per hour of concrete production, a 10 yard load, 500 feet round trip and doubling the estimated mileage to account for the delivery of raw materials:

$$\text{VMT/hr} = 500 \text{ ft/load} (1 \text{ mi}/5280 \text{ ft})(160 \text{ yd concrete/hr})(1 \text{ load}/10 \text{ yd})(2)$$

$$\text{VMT/hr} = 3.52 \text{ mi/hr}$$

Then with 75% effective control by watering:

$$\text{Emissions} = (1.74 \text{ lb PM10/VMT})(3.52 \text{ mi/hr})(1 - 0.75) = 1.53 \text{ lb PM10/hr}$$

i. Emission Limitation:

The emissions of fugitive dust shall not exceed 0.36 ton of PM10 per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be demonstrated by a one time emissions calculation utilizing the maximum annual throughput rate (75,000 cuyd) and the hourly emission factor calculated above:

$$\text{Emissions} = 1.53 \text{ lb/hr} (75000 \text{ yd/yr})(1 \text{ hr}/160 \text{ yd})(1 \text{ t}/2000 \text{ lb}) = 0.36 \text{ t PM10/yr}$$

F. Miscellaneous Requirements

1. All requirements of Sections A. through E. of this permit to install are federally enforceable.