



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL
SHELBY COUNTY**

CERTIFIED MAIL

Street Address:

50 West Town Street, Suite 700

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049

Application No: 05-14435

Fac ID: 0575000174

DATE: 1/24/2008

Honda of America Mfg Inc
Paul Huwer
12500 MERANDA RD
ANNA, OH 45302-9699

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action of the Director is final and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. The appeal must be filed with the Commission within thirty (30) days after notice of the Director's action. The appeal must be accompanied by a filing fee of \$70.00 which the Commission, in its discretion, may reduce if by affidavit you demonstrate that payment of the full amount of the fee would cause extreme hardship. Notice of the filing of the appeal shall be filed with the Director within three (3) days of filing with the Commission. Ohio EPA requests that a copy of the appeal be served upon the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, OH 43215

Sincerely,

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: USEPA

SWDO



**Permit To Install
Terms and Conditions**

**Issue Date: 1/24/2008
Effective Date: 1/24/2008**

FINAL PERMIT TO INSTALL 05-14435

Application Number: 05-14435
Facility ID: 0575000174
Permit Fee: **\$3750**
Name of Facility: Honda of America Mfg Inc
Person to Contact: Paul Huwer
Address: 12500 MERANDA RD
ANNA, OH 45302-9699

Location of proposed air contaminant source(s) [emissions unit(s)]:

**12500 Meranda Rd
Anna, Ohio**

Description of proposed emissions unit(s):

Installation of Spin Cast Line 2 consisting of emissions units P098-Autopour, P099-Spincast Machine 3, P100-Shotblast Machine, P101-Tube Cutting Machinr 5, and P102-Tube Cutting Machine 6.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Chris Korleski
Director

Part I - GENERAL TERMS AND CONDITIONS

A. State and Federally Enforceable Permit-To-Install General Terms and Conditions

1. Monitoring and Related Recordkeeping and Reporting Requirements

- a. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:
 - i. The date, place (as defined in the permit), and time of sampling or measurements.
 - ii. The date(s) analyses were performed.
 - iii. The company or entity that performed the analyses.
 - iv. The analytical techniques or methods used.
 - v. The results of such analyses.
 - vi. The operating conditions existing at the time of sampling or measurement.
- b. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.
- c. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall submit required reports in the following manner:
 - i. Reports of any required monitoring and/or recordkeeping of federally enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
 - ii. Quarterly written reports of (i) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, excluding deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06, that have been detected by the testing, monitoring and recordkeeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures taken, shall be made to the appropriate Ohio EPA District Office or local air agency. The written

Honda of America Mfg. Inc.
PTI Application: 05-14435
Issued: 1/24/2008

Facility ID: 0575000174

reports shall be submitted (i.e., postmarked) quarterly, by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. See B.9 below if no deviations occurred during the quarter.

- iii. Written reports, which identify any deviations from the federally enforceable monitoring, recordkeeping, and reporting requirements contained in this permit shall be submitted (i.e., postmarked) to the appropriate Ohio EPA District Office or local air agency every six months, by January 31 and July 31 of each year for the previous six calendar months. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report, which states that no deviations occurred during that period.
 - iv. If this permit is for an emissions unit located at a Title V facility, then each written report shall be signed by a responsible official certifying that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.
- d. The permittee shall report actual emissions pursuant to OAC Chapter 3745-78 for the purpose of collecting Air Pollution Control Fees.

2. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction, i.e., upset, of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. (The definition of an upset condition shall be the same as that used in OAC rule 3745-15-06(B)(1) for a malfunction.) The verbal and written reports shall be submitted pursuant to OAC rule 3745-15-06.

Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emission unit(s) that is (are) served by such control system(s).

3. Risk Management Plans

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. 7401 et seq. ("Act"), the permittee shall comply with the requirement to register such a plan.

Honda of America Mfg. Inc.
PTI Application: 05-14435
Issued: 1/24/2008

Facility ID: 0575000174

4. Title IV Provisions

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

5. Severability Clause

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition declared invalid.

6. General Requirements

- a. The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and re-issuance, or modification
- b. It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.
- c. This permit may be modified, revoked, or revoked and reissued, for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.
- d. This permit does not convey any property rights of any sort, or any exclusive privilege.
- e. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

Honda of America Mfg. Inc.
PTI Application: 05-14435
Issued: 1/24/2008

Facility ID: 0575000174

7. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable permit-to-install fees within 30 days after the issuance of any permit-to-install. The permittee shall pay all applicable permit-to-operate fees within thirty days of the issuance of the invoice.

8. Federal and State Enforceability

Only those terms and conditions designated in this permit as federally enforceable, that are required under the Act, or any its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA and the State and by citizens (to the extent allowed by section 304 of the Act) under the Act. All other terms and conditions of this permit shall not be federally enforceable and shall be enforceable under State law only.

9. Compliance Requirements

- a. Any document (including reports) required to be submitted and required by a federally applicable requirement in this permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.
- b. Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:
 - i. At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.
 - ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with ORC section 3704.08.
 - iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.

Honda of America Mfg. Inc.
PTI Application: 05-14435
Issued: 1/24/2008

Facility ID: 0575000174

- iv. As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.
- c. The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually, or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:
 - i. Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
 - ii. An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

10. Permit-To-Operate Application

- a. If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).
- b. If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35, the source(s) identified in this permit is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the source(s) covered by this permit.

11. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

12. Air Pollution Nuisance

Honda of America Mfg. Inc.
PTI Application: 05-14435
Issued: 1/24/2008

Facility ID: 0575000174

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

Honda of America Mfg. Inc.
PTI Application: 05-14435
Issued: 1/24/2008

Facility ID: 0575000174

13. Permit-To-Install

A permit-to-install must be obtained pursuant to OAC Chapter 3745-31 prior to "installation" of "any air contaminant source" as defined in OAC rule 3745-31-01, or "modification", as defined in OAC rule 3745-31-01, of any emissions unit included in this permit.

B. State Only Enforceable Permit-To-Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping of state-only enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from state-only required emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted (i.e., postmarked) quarterly, by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing

Honda of America Mfg. Inc.
PTI Application: 05-14435
Issued: 1/24/2008

Facility ID: 0575000174

of any transfer of this permit.

Honda of America Mfg. Inc.
PTI Application: 05-14435
Issued: 1/24/2008

Facility ID: 0575000174

4. Authorization To Install or Modify

If applicable, authorization to install or modify any new or existing emissions unit included in this permit shall terminate within eighteen months of the effective date of the permit if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

5. Construction of New Sources(s)

This permit does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. This permit does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the application and terms and conditions of this permit. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of this permit does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Issuance of this permit is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

6. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

7. Applicability

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

8. Construction Compliance Certification

Honda of America Mfg. Inc.
PTI Application: 05-14435
Issued: 1/24/2008

Facility ID: 0575000174

If applicable, the applicant shall provide Ohio EPA with a written certification (see enclosed form if applicable) that the facility has been constructed in accordance with the permit-to-install application and the terms and conditions of the permit-to-install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

9. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations (See Section A of This Permit)

If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly (i.e., postmarked), by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.

C. Permit-To-Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
PE	15.5

Honda of America Mfg. Inc.
PTI Application: 05-14435
Issued: 1/24/2008

Facility ID: 0575000174

Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

A. State and Federally Enforceable Permit To Install Facility Specific Terms and Conditions

1. This facility is not located in an Appendix A area as described in OAC rule 3745-17-08; therefore, OAC rules 3745-17-07(B) and 3745-17-08(B) do not apply to the fugitive emissions from the affected emissions units at this facility.
2. The particulate emissions (PE) from baghouse BH-1 serving emissions units P098, P099, P100, P101 and P102 shall not exceed 0.005 grain/dry standard cubic foot (dscf) of the total exhaust gases.

B. State Only Enforceable Permit To Install Facility Specific Terms and Conditions

None

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment -(P098) - Spin Line 2 Autopour

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(C)	PE emissions shall not exceed 13.14 tons per 12 month rolling period for emissions units P098, P099, P100, P101, and P102 combined. The fugitive emissions from P098 shall not exceed 1.53 tons of PE per rolling 12-month period.
OAC rule 3745-17-11(B)(1)	The PE emissions shall not exceed 9.3 lbs per hour.
OAC rule 3745-17-07(A)(1)	Visible PE emissions from any baghouse vent that this emission unit is controlled by shall not exceed 20% opacity, as a 6-minute average.
OAC rule 3745-31-05(A)(3)(b)	See Section I.2.b.

2. Additional Terms and Conditions

- 2.a The annual emissions limitations specified above represent the emissions unit's potential to emit. Therefore, no additional monitoring, record keeping or reporting is required to demonstrate compliance with these emission limitations.
- 2.b The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the particulate emissions (PE) emissions from this emissions unit since the potential emissions are less than ten tons per year.

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

1. The pressure drop across the baghouse shall be maintained within the range of 1 to 15 inches of water while any emission unit controlled by the baghouse is in operation. The exception is for the first 45 days following a change of at least 50% of the fabric bags. During that time, the pressure drop shall be maintained below 15 inches of water while any emission unit controlled by the baghouse is in operation.

The permittee shall properly operate, and maintain equipment to monitor the pressure drop across the baghouse(s) while the emissions unit is in operation. The monitoring equipment shall be calibrated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse once each operating day.

2. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible PE from the stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operational log. If visible emissions are observed, the permittee shall also note the following in the operational log;
 - a. the color of the emissions;
 - b. the total duration of any visible emission incident; and
 - c. any corrective actions taken to eliminate the visible emissions.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation reports that identify the following:
 - a. all exceedances of the combined rolling, 12-month period PE limitation of 13.14 tons from baghouse # 1, (emissions from emissions units P098, P099, P100, P101, and P102);
 - b. all exceedances of the rolling 12-month period fugitive PE limitation of 1.53 tons per rolling 12-month period from emissions unit P098;

These quarterly deviation reports are due by the dates specified in Part I - General Terms and Conditions A.1.

2. The permittee shall submit quarterly deviation (excursion) reports that identify the all periods of time in which this emissions unit was in operation and the pressure drop across the baghouse(s) did not comply with the allowable range.

These quarterly deviation reports are due by the dates specified in Part I - General Terms and Conditions A.1.

Honda of America Mfg. Inc.
DTI Application: 05 11125

Facility ID: 0575000174

Emissions Unit ID: P098

Issued: 1/24/2008

3. The permittee shall submit semiannual written reports that:
 - a. identify all days during which any visible PE were observed from any stack serving this emissions unit;
 - b. describe the corrective actions taken to eliminate the visible PE.

These reports shall be submitted to the Ohio EPA, Southwest District Office by January 31 and July 31 of each year and shall cover the previous 6-month period.

V. Testing Requirements

1. Compliance with the emission limitations specified in Part III - A.I.1 shall be determined in accordance with the following methods:

- a. Emission Limitation:

9.3 lbs of PE/hr

The hourly emission limitation was established by the following methodology:

$$AMR = 4.10 \times (P \text{ to the power of } 0.67)$$

where:

AMR = Allowable Mass Emission Rate, in lbs/hr;

P = Process weight at maximum capacity (3.4 TPH maximum metal rate).

Emission calculation is based on the requirements of OAC rule 3745-17-11(B)(1) Table I.

Applicable Compliance Method:

Compliance with the above limitations is based on the 3.4 tons of metal being the maximum potential metal usage in this emissions unit and emission testing demonstrating 0.005 grains/ dscf requirement.

- b. Emission Limitation:

The particulate emissions (PE) from baghouse # 1, which controls emissions from emissions units, P098, P099, P100, P101, and P102 shall not exceed

Issued: 1/24/2008

13.14 tons (PE)combined/rolling 12-month period.

The combined rolling 12-month emission limitation is the total sum of the following equation for all of the above listed emissions units:

$$\text{AER} = [(\text{Af} \times \text{Ef} \times 60 \text{ mins/hr} \times \text{Cf}) \times \text{Ho}] / 2000$$

where:

AER = Particulate emissions, in tons per rolling 12 month period;

Af = Maximum Air Flow from Baghouse # 1, in acfm, (70,000, specific acfm rates are from the data provide by Honda);

Ef = Emission factor of the control device, grains of PE per dscf, (0.005 grains/dscf, data from Honda);

Cf = Conversion factor, (1 lbs/7,000 grains); and

Ho = Allowable rolling 12-month hours of operation limitation, (8,760 hrs).

Applicable Compliance Method:

The permittee shall demonstrate compliance with the above limits based upon the record keeping requirements of Sections III.1., of this permit.

c. Emission Limitation:

The fugitive particulate emissions (PE) from emissions unit P098, shall not exceed 1.53 tons (PE)/ rolling 12-month period.

The fugitive PE rolling 12-month emission limitation is the total sum of the following equation:

$$\text{FER} = [(\text{MMR} \times \text{Ef}) \times (1-\text{CAP})] / 2000\text{lbs/ton}$$

where:

FER = Fugitive Particulate emissions, in tons per rolling 12 month period;

MMR = Maximum metal usage rate, in tons, (3.4 tons/hr, from the data provide by Honda);

Ef = Emission factor, in lbs of PE/ton of metal, (2.06 lbs PE/ton of metal, from data provided by Honda); and

CAP = Assumed capture efficiency, in %, (95.0% (0.95), from data provided by Honda).

Issued: 1/24/2008

Applicable Compliance Method:

The permittee shall demonstrate compliance with the above limits based upon the record keeping requirements of Sections III.2, of this permit.

d. Emission Limitation:

Visible PE shall not exceed 20% opacity, as a 6-minute average, from the baghouse stack serving this emission unit.

Issued: 1/24/2008

Applicable Compliance Method:

If required, compliance shall be determined through visible emissions observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9.

2. The permittee shall conduct, or have conducted, emission testing for baghouse # 1 to demonstrate compliance with the allowable PE limitations.
 - a. The emission testing shall be conducted within 6 months of the installation certificate for this source (facility).
 - b. The emission testing shall be conducted to demonstrate compliance with the allowable PE limitations.
 - c. The following test methods shall be employed to demonstrate compliance with the allowable mass emission limitations.

PE: Methods 1-5 of 40 CFR Part 60, Appendix A

Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA.

- d. The test(s) shall be conducted while the emission units being controlled by the baghouse(s) are being operated at or near their maximum capacities, unless otherwise specified or approved by the Ohio EPA, Southwest District Office.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, Southwest District Office. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, Southwest District Office's refusal to accept the results of the emission test(s). Personnel from the Ohio EPA shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

VI. Miscellaneous Requirements

21

Honda of America Mfg. Inc.
DTI Application: 05 11125

Facility ID: 0575000174

Emissions Unit ID: P098

None

Issued: 1/24/2008

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P098) - Spin Line 2 Autopour

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05	Limit(s)

2. **Additional Terms and Conditions**

- 2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Issued: 1/24/2008

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment -(P099) - Spin Line 2 Spincast Machine 3

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(C)	PE emissions shall not exceed 13.14 tons per 12 month rolling period for emissions units P098, P099, P100, P101, and P102 combined. The fugitive emissions from P099 shall not exceed 0.04 tons of PE per rolling 12-month period.
OAC rule 3745-17-11(B)(1)	The PE emissions shall not exceed 9.3 lbs per hour.
OAC rule 3745-17-07(A)(1)	Visible PE emissions from any baghouse vent that this emission unit is controlled by shall not exceed 20% opacity, as a 6-minute average.
OAC rule 3745-31-05(A)(3)(b)	See Section I.2.b.

2. Additional Terms and Conditions

- 2.a The annual emissions limitations specified above represent the emissions unit's potential to emit. Therefore, no additional monitoring, record keeping or reporting is required to demonstrate compliance with these emission limitations.
- 2.b The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the particulate emissions (PE) emissions from this emissions unit since the potential emissions are less than ten tons per year.

II. Operational Restrictions

None

Honda of America Mfg. Inc.
DTI Application: 05 11125

Facility ID: 0575000174

Emissions Unit ID: P099

Issued: 1/24/2008

III. Monitoring and/or Recordkeeping Requirements

1. The pressure drop across the baghouse shall be maintained within the range of 1 to 15 inches of water while any emission unit controlled by the baghouse is in operation. The exception is for the first 45 days following a change of at least 50% of the fabric bags. During that time, the pressure drop shall be maintained below 15 inches of water while any emission unit controlled by the baghouse is in operation.

The permittee shall properly operate, and maintain equipment to monitor the pressure drop across the baghouse(s) while the emissions unit is in operation. The monitoring equipment shall be calibrated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse once each operating day.

2. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible PE from the stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operational log. If visible emissions are observed, the permittee shall also note the following in the operational log;
 - a. the color of the emissions;
 - b. the total duration of any visible emission incident; and
 - c. any corrective actions taken to eliminate the visible emissions.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation reports that identify the following:
 - a. all exceedances of the combined rolling, 12-month period PE limitation of 13.14 tons from baghouse # 1, (emissions from emissions units P098, P099, P100, P101, and P102);
 - b. all exceedances of the rolling 12-month period fugitive PE limitation of 0.04 tons per rolling 12-month period from emissions unit P099;

These quarterly deviation reports are due by the dates specified in Part I - General Terms and Conditions A.1.

2. The permittee shall submit quarterly deviation (excursion) reports that identify the all

Emissions Unit ID: P099

Issued: 1/24/2008

periods of time in which this emissions unit was in operation and the pressure drop across the baghouse(s) did not comply with the allowable range.

These quarterly deviation reports are due by the dates specified in Part I - General Terms and Conditions A.1.

Issued: 1/24/2008

3. The permittee shall submit semiannual written reports that:
 - a. identify all days during which any visible PE were observed from any stack serving this emissions unit;
 - b. describe the corrective actions taken to eliminate the visible PE.

These reports shall be submitted to the Ohio EPA, Southwest District Office by January 31 and July 31 of each year and shall cover the previous 6-month period.

V. Testing Requirements

1. Compliance with the emission limitations specified in Part III - A.I.1 shall be determined in accordance with the following methods:

- a. Emission Limitation:

9.3 lbs of PE/hr

The hourly emission limitation was established by the following methodology:

$$AMR = 4.10 \times (P \text{ to the power of } 0.67)$$

where:

AMR = Allowable Mass Emission Rate, in lbs/hr;

P = Process weight at maximum capacity (3.4 TPH maximum metal rate).

Emission calculation is based on the requirements of OAC rule 3745-17-11(B)(1) Table I.

Applicable Compliance Method:

Compliance with the above limitations is based on the 3.4 tons of metal being the maximum potential metal usage in this emissions unit and emission testing demonstrating 0.005 grains/ dscf requirement.

- b. Emission Limitation:

The particulate emissions (PE) from baghouse # 1, which controls emissions from emissions units, P098, P099, P100, P101, and P102 shall not exceed

Issued: 1/24/2008

13.14 tons (PE)combined/rolling 12-month period.

The combined rolling 12-month emission limitation is the total sum of the following equation for all of the above listed emissions units:

$$\text{AER} = [(\text{Af} \times \text{Ef} \times 60 \text{ mins/hr} \times \text{Cf}) \times \text{Ho}] / 2000$$

where:

AER = Particulate emissions, in tons per rolling 12 month period;

Af = Maximum Air Flow from Baghouse # 1, in acfm, (70,000, specific acfm rates are from the data provide by Honda);

Ef = Emission factor of the control device, grains of PE per dscf, (0.005 grains/dscf, data from Honda);

Cf = Conversion factor, (1 lbs/7,000 grains); and

Ho = Allowable rolling 12-month hours of operation limitation, (8,760 hrs).

Applicable Compliance Method:

The permittee shall demonstrate compliance with the above limits based upon the record keeping requirements of Sections III.1., of this permit.

c. Emission Limitation:

The fugitive particulate emissions (PE) from emissions unit P099, shall not exceed 0.04 tons (PE)/ rolling 12-month period.

The fugitive PE rolling 12-month emission limitation is the total sum of the following equation:

$$\text{FER} = [(\text{MMR} \times \text{Ef}) \times (1-\text{CAP})] / 2000\text{lbs/ton}$$

where:

FER = Fugitive Particulate emissions, in tons per rolling 12 month period;

MMR = Maximum metal usage rate, in tons, (3.4 tons/hr, from the data provide by Honda);

Ef = Emission factor, in lbs of PE/ton of metal, (0.33 lbs PE/ton of metal, from Air Emission from Permanent Mold Casting of Ductile Iron Pipe, prepared by Marvin D. McKinley, Professor of Chemical Engineering, Univ. of AL, 9/94); and

CAP = Assumed capture efficiency, in %, (99.0% (0.99), from data provided by

Honda of America Mfg. Inc.
DTI Application: 05 11125

Facility ID: 0575000174

Emissions Unit ID: P099

Honda).

Applicable Compliance Method:

The permittee shall demonstrate compliance with the above limits based upon the record keeping requirements of Sections III.2, of this permit.

d. Emission Limitation:

Visible PE shall not exceed 20% opacity, as a 6-minute average, from the baghouse stack serving this emission unit.

Issued: 1/24/2008

Applicable Compliance Method:

If required, compliance shall be determined through visible emissions observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9.

2. The permittee shall conduct, or have conducted, emission testing for baghouse # 1 to demonstrate compliance with the allowable PE limitations.
 - a. The emission testing shall be conducted within 6 months of the installation certificate for this source (facility).
 - b. The emission testing shall be conducted to demonstrate compliance with the allowable PE limitations.
 - c. The following test methods shall be employed to demonstrate compliance with the allowable mass emission limitations.

PE: Methods 1-5 of 40 CFR Part 60, Appendix A

Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA.

- d. The test(s) shall be conducted while the emission units being controlled by the baghouse(s) are being operated at or near their maximum capacities, unless otherwise specified or approved by the Ohio EPA, Southwest District Office.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, Southwest District Office. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, Southwest District Office's refusal to accept the results of the emission test(s). Personnel from the Ohio EPA shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

VI. Miscellaneous Requirements

Issued: 1/24/2008

None

Emissions Unit ID: P099

Issued: 1/24/2008

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment -(P099) - Spin Line 2 Spincast Machine 3

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05	Limit(s)

2. **Additional Terms and Conditions**

- 2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment -(P100) - Spin Line 2 Shotblast Machine

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(C)	PE emissions shall not exceed 13.14 tons per 12 month rolling period for emissions units P098, P099, P100, P101, and P102 combined. The fugitive emissions from P100 shall not exceed 0.22 tons of PE per rolling 12-month period.
OAC rule 3745-17-11(B)(1)	The PE emissions shall not exceed 7.5 lbs per hour.
OAC rule 3745-17-07(A)(1)	Visible PE emissions from any baghouse vent that this emission unit is controlled by shall not exceed 20% opacity, as a 6-minute average.
OAC rule 3745-31-05(A)(3)(b)	See Section I.2.b.

2. Additional Terms and Conditions

- 2.a The annual emissions limitations specified above represent the emissions unit's potential to emit. Therefore, no additional monitoring, record keeping or reporting is required to demonstrate compliance with these emission limitations.
- 2.b The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the particulate emissions (PE) emissions from this emissions unit since the potential emissions are less than ten tons per year.

II. Operational Restrictions

None

Issued: 1/24/2008

III. Monitoring and/or Recordkeeping Requirements

1. The pressure drop across the baghouse shall be maintained within the range of 1 to 15 inches of water while any emission unit controlled by the baghouse is in operation. The exception is for the first 45 days following a change of at least 50% of the fabric bags. During that time, the pressure drop shall be maintained below 15 inches of water while any emission unit controlled by the baghouse is in operation.

The permittee shall properly operate, and maintain equipment to monitor the pressure drop across the baghouse(s) while the emissions unit is in operation. The monitoring equipment shall be calibrated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse once each operating day.

2. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible PE from the stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operational log. If visible emissions are observed, the permittee shall also note the following in the operational log;
 - a. the color of the emissions;
 - b. the total duration of any visible emission incident; and
 - c. any corrective actions taken to eliminate the visible emissions.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation reports that identify the following:
 - a. all exceedances of the combined rolling, 12-month period PE limitation of 13.14 tons from baghouse # 1, (emissions from emissions units P098, P099, P100, P101, and P102);
 - b. all exceedances of the rolling 12-month period fugitive PE limitation of 0.22 tons per rolling 12-month period from emissions unit P100;

These quarterly deviation reports are due by the dates specified in Part I - General Terms and Conditions A.1.

2. The permittee shall submit quarterly deviation (excursion) reports that identify the all

Honda of America Mfg. Inc.

DTI Application: 05 44125

Facility ID: 0575000174

Emissions Unit ID: P100

periods of time in which this emissions unit was in operation and the pressure drop across the baghouse(s) did not comply with the allowable range.

These quarterly deviation reports are due by the dates specified in Part I - General Terms and Conditions A.1.

Issued: 1/24/2008

3. The permittee shall submit semiannual written reports that:
 - a. identify all days during which any visible PE were observed from any stack serving this emissions unit;
 - b. describe the corrective actions taken to eliminate the visible PE.

These reports shall be submitted to the Ohio EPA, Southwest District Office by January 31 and July 31 of each year and shall cover the previous 6-month period.

V. Testing Requirements

1. Compliance with the emission limitations specified in Part III - A.I.1 shall be determined in accordance with the following methods:

- a. Emission Limitation:

7.5 lbs of PE/hr

The hourly emission limitation was established by the following methodology:

$$\text{AMR} = 0.5782 \times (\text{U to the power of } 0.6456)$$

where:

AMR = Allowable Mass Emission Rate, in lbs/hr;

U = Uncontrolled particulate emissions, in lbs/hr (52.7 lb/hr based on an emission factor of 15.5 lb PE/ton and 3.4 TPH maximum metal rate).

Emission calculation is based on the requirements of OAC rule 3745-17-11(B)(1) Figure II, curve P-1.

Applicable Compliance Method:

Compliance with the above limitations is based on the 3.4 tons of metal being the maximum potential metal usage in this emissions unit and emission testing demonstrating 0.005 grains/ dscf requirement.

- b. Emission Limitation:

The particulate emissions (PE) from baghouse # 1, which controls emissions

Issued: 1/24/2008

from emissions units, P098, P099, P100, P101, and P102 shall not exceed 13.14 tons (PE) combined/rolling 12-month period.

The combined rolling 12-month emission limitation is the total sum of the following equation for all of the above listed emissions units:

$$\text{AER} = [(\text{Af} \times \text{Ef} \times 60 \text{ mins/hr} \times \text{Cf}) \times \text{Ho}] / 2000$$

where:

AER = Particulate emissions, in tons per rolling 12 month period;
 Af = Maximum Air Flow from Baghouse # 1, in acfm, (70,000, specific acfm rates are from the data provide by Honda);
 Ef = Emission factor of the control device, grains of PE per dscf, (0.005 grains/dscf, data from Honda);
 Cf = Conversion factor, (1 lbs/7,000 grains); and
 Ho = Allowable rolling 12-month hours of operation limitation, (8,760 hrs).

Applicable Compliance Method:

The permittee shall demonstrate compliance with the above limits based upon the record keeping requirements of Sections III.1., of this permit.

c. Emission Limitation:

The fugitive particulate emissions (PE) from emissions unit P100, shall not exceed 0.22 tons (PE)/ rolling 12-month period.

The fugitive PE rolling 12-month emission limitation is the total sum of the following equation:

$$\text{FER} = [(\text{MMR} \times \text{Ef}) \times (1-\text{CAP})] / 2000\text{lbs/ton}$$

where:

FER = Fugitive Particulate emissions, in tons per rolling 12 month period;
 MMR = Maximum metal usage rate, in tons, (3.4 tons/hr, from the data provide by Honda);
 Ef = Emission factor, in lbs of PE/ton of metal, (15.5 lbs PE/ton of metal, from Modern Casting, 1/72); and
 CAP = Assumed capture efficiency, in %, (99.9% (0.999), from data provided by

Issued: 1/24/2008

Honda).

Applicable Compliance Method:

The permittee shall demonstrate compliance with the above limits based upon the record keeping requirements of Sections III.2, of this permit.

d. Emission Limitation:

Visible PE shall not exceed 20% opacity, as a 6-minute average, from the baghouse stack serving this emission unit.

Issued: 1/24/2008

Applicable Compliance Method:

If required, compliance shall be determined through visible emissions observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9.

2. The permittee shall conduct, or have conducted, emission testing for baghouse # 1 to demonstrate compliance with the allowable PE limitations.
 - a. The emission testing shall be conducted within 6 months of the installation certificate for this source (facility).
 - b. The emission testing shall be conducted to demonstrate compliance with the allowable PE limitations.
 - c. The following test methods shall be employed to demonstrate compliance with the allowable mass emission limitations.

PE: Methods 1-5 of 40 CFR Part 60, Appendix A

Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA.

- d. The test(s) shall be conducted while the emission units being controlled by the baghouse(s) are being operated at or near their maximum capacities, unless otherwise specified or approved by the Ohio EPA, Southwest District Office.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, Southwest District Office. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, Southwest District Office's refusal to accept the results of the emission test(s). Personnel from the Ohio EPA shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

VI. Miscellaneous Requirements

40

Honda of America Mfg. Inc.
DTI Application: 05 11125

Facility ID: 0575000174

Emissions Unit ID: P100

None

Issued: 1/24/2008

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment -(P100) - Spin Line 2 Shotblast Machine

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05	Limit(s)

2. **Additional Terms and Conditions**

- 2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Issued: 1/24/2008

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment -(P101) - Spin Line 2 Tube Cutting Machine 5

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(C)	PE emissions shall not exceed 13.14 tons per 12 month rolling period for emissions units P098, P099, P100, P101, and P102 combined. The fugitive emissions from P101 shall not exceed 0.26 tons of PE per rolling 12-month period.
OAC rule 3745-17-11(B)(1)	The PE emissions shall not exceed 7.9 lbs per hour.
OAC rule 3745-17-07(A)(1)	Visible PE emissions from any baghouse vent that this emission unit is controlled by shall not exceed 20% opacity, as a 6-minute average.
OAC rule 3745-31-05(A)(3)(b)	See Section I.2.b.

2. Additional Terms and Conditions

- 2.a The annual emissions limitations specified above represent the emissions unit's potential to emit. Therefore, no additional monitoring, record keeping or reporting is required to demonstrate compliance with these emission limitations.
- 2.b The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the particulate emissions (PE) emissions from this emissions unit since the potential emissions are less than ten tons per year.

II. Operational Restrictions

None

Honda of America Mfg. Inc.
DTI Application: 05 11125

Facility ID: 0575000174

Emissions Unit ID: P101

Issued: 1/24/2008

III. Monitoring and/or Recordkeeping Requirements

1. The pressure drop across the baghouse shall be maintained within the range of 1 to 15 inches of water while any emission unit controlled by the baghouse is in operation. The exception is for the first 45 days following a change of at least 50% of the fabric bags. During that time, the pressure drop shall be maintained below 15 inches of water while any emission unit controlled by the baghouse is in operation.

The permittee shall properly operate, and maintain equipment to monitor the pressure drop across the baghouse(s) while the emissions unit is in operation. The monitoring equipment shall be calibrated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse once each operating day.

2. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible PE from the stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operational log. If visible emissions are observed, the permittee shall also note the following in the operational log;
 - a. the color of the emissions;
 - b. the total duration of any visible emission incident; and
 - c. any corrective actions taken to eliminate the visible emissions.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation reports that identify the following:
 - a. all exceedances of the combined rolling, 12-month period PE limitation of 13.14 tons from baghouse # 1, (emissions from emissions units P098, P099, P100, P101, and P102);
 - b. all exceedances of the rolling 12-month period fugitive PE limitation of 0.26 tons per rolling 12-month period from emissions unit P101;

These quarterly deviation reports are due by the dates specified in Part I - General Terms and Conditions A.1.

2. The permittee shall submit quarterly deviation (excursion) reports that identify the all

Emissions Unit ID: P101

Issued: 1/24/2008

periods of time in which this emissions unit was in operation and the pressure drop across the baghouse(s) did not comply with the allowable range.

These quarterly deviation reports are due by the dates specified in Part I - General Terms and Conditions A.1.

Issued: 1/24/2008

3. The permittee shall submit semiannual written reports that:
 - a. identify all days during which any visible PE were observed from any stack serving this emissions unit;
 - b. describe the corrective actions taken to eliminate the visible PE.

These reports shall be submitted to the Ohio EPA, Southwest District Office by January 31 and July 31 of each year and shall cover the previous 6-month period.

V. Testing Requirements

1. Compliance with the emission limitations specified in Part III - A.I.1 shall be determined in accordance with the following methods:

- a. Emission Limitation:

7.9 lbs of PE/hr

The hourly emission limitation was established by the following methodology:

$$\text{AMR} = 0.5782 \times (\text{U to the power of } 0.6456)$$

where:

AMR = Allowable Mass Emission Rate, in lbs/hr;

U = Uncontrolled particulate emissions, in lbs/hr (57.8 lb/hr based on an emission factor of 17.0 lb PE/ton and 3.4 TPH maximum metal rate).

Emission calculation is based on the requirements of OAC rule 3745-17-11(B)(1) Figure II, curve P-1.

Applicable Compliance Method:

Compliance with the above limitations is based on the 3.4 tons of metal being the maximum potential metal usage in this emissions unit and emission testing demonstrating 0.005 grains/ dscf requirement.

- b. Emission Limitation:

The particulate emissions (PE) from baghouse # 1, which controls emissions

Issued: 1/24/2008

from emissions units, P098, P099, P100, P101, and P102 shall not exceed 13.14 tons (PE) combined/rolling 12-month period.

The combined rolling 12-month emission limitation is the total sum of the following equation for all of the above listed emissions units:

$$\text{AER} = [(\text{Af} \times \text{Ef} \times 60 \text{ mins/hr} \times \text{Cf}) \times \text{Ho}] / 2000$$

where:

AER = Particulate emissions, in tons per rolling 12 month period;
 Af = Maximum Air Flow from Baghouse # 1, in acfm, (70,000, specific acfm rates are from the data provide by Honda);
 Ef = Emission factor of the control device, grains of PE per dscf, (0.005 grains/dscf, data from Honda);
 Cf = Conversion factor, (1 lbs/7,000 grains); and
 Ho = Allowable rolling 12-month hours of operation limitation, (8,760 hrs).

Applicable Compliance Method:

The permittee shall demonstrate compliance with the above limits based upon the record keeping requirements of Sections III.1., of this permit.

c. Emission Limitation:

The fugitive particulate emissions (PE) from emissions unit P101, shall not exceed 0.26 tons (PE)/ rolling 12-month period.

The fugitive PE rolling 12-month emission limitation is the total sum of the following equation:

$$\text{FER} = [(\text{MMR} \times \text{Ef}) \times (1-\text{CAP})] / 2000\text{lbs/ton}$$

where:

FER = Fugitive Particulate emissions, in tons per rolling 12 month period;
 MMR = Maximum metal usage rate, in tons, (3.4 tons/hr, from the data provide by Honda);
 Ef = Emission factor, in lbs of PE/ton of metal, (17.0 lbs PE/ton of metal, Fire SCC 304000340); and
 CAP = Assumed capture efficiency, in %, (99.9% (0.999), from data provided by

Honda of America Mfg. Inc.
DTI Application: 05 11125

Facility ID: 0575000174

Emissions Unit ID: P101

Honda).

Applicable Compliance Method:

The permittee shall demonstrate compliance with the above limits based upon the record keeping requirements of Sections III.2, of this permit.

d. Emission Limitation:

Visible PE shall not exceed 20% opacity, as a 6-minute average, from the baghouse stack serving this emission unit.

Issued: 1/24/2008

Applicable Compliance Method:

If required, compliance shall be determined through visible emissions observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9.

2. The permittee shall conduct, or have conducted, emission testing for baghouse # 1 to demonstrate compliance with the allowable PE limitations.
 - a. The emission testing shall be conducted within 6 months of the installation certificate for this source (facility).
 - b. The emission testing shall be conducted to demonstrate compliance with the allowable PE limitations.
 - c. The following test methods shall be employed to demonstrate compliance with the allowable mass emission limitations.

PE: Methods 1-5 of 40 CFR Part 60, Appendix A

Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA.

- d. The test(s) shall be conducted while the emission units being controlled by the baghouse(s) are being operated at or near their maximum capacities, unless otherwise specified or approved by the Ohio EPA, Southwest District Office.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, Southwest District Office. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, Southwest District Office's refusal to accept the results of the emission test(s). Personnel from the Ohio EPA shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

VI. Miscellaneous Requirements

Issued: 1/24/2008

None

Emissions Unit ID: P101

Issued: 1/24/2008

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (P101) - Spin Line 2 Tube Cutting Machine 5

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05	Limit(s)

2. **Additional Terms and Conditions**

- 2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment -(P102) - Spin Line 2 Tube Cutting Machine 6

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(C)	PE emissions shall not exceed 13.14 tons per 12 month rolling period for emissions units P098, P099, P100, P101, and P102 combined. The fugitive emissions from P102 shall not exceed 0.26 tons of PE per rolling 12-month period.
OAC rule 3745-17-11(B)(1)	The PE emissions shall not exceed 7.9 lbs per hour.
OAC rule 3745-17-07(A)(1)	Visible PE emissions from any baghouse vent that this emission unit is controlled by shall not exceed 20% opacity, as a 6-minute average.
OAC rule 3745-31-05(A)(3)(b)	See Section I.2.b.

2. Additional Terms and Conditions

- 2.a The annual emissions limitations specified above represent the emissions unit's potential to emit. Therefore, no additional monitoring, record keeping or reporting is required to demonstrate compliance with these emission limitations.
- 2.b The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the particulate emissions (PE) emissions from this emissions unit since the potential emissions are less than ten tons per year.

II. Operational Restrictions

None

Issued: 1/24/2008

III. Monitoring and/or Recordkeeping Requirements

1. The pressure drop across the baghouse shall be maintained within the range of 1 to 15 inches of water while any emission unit controlled by the baghouse is in operation. The exception is for the first 45 days following a change of at least 50% of the fabric bags. During that time, the pressure drop shall be maintained below 15 inches of water while any emission unit controlled by the baghouse is in operation.

The permittee shall properly operate, and maintain equipment to monitor the pressure drop across the baghouse(s) while the emissions unit is in operation. The monitoring equipment shall be calibrated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse once each operating day.

2. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible PE from the stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operational log. If visible emissions are observed, the permittee shall also note the following in the operational log;
 - a. the color of the emissions;
 - b. the total duration of any visible emission incident; and
 - c. any corrective actions taken to eliminate the visible emissions.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation reports that identify the following:
 - a. all exceedances of the combined rolling, 12-month period PE limitation of 13.14 tons from baghouse # 1, (emissions from emissions units P098, P099, P100, P101, and P102);
 - b. all exceedances of the rolling 12-month period fugitive PE limitation of 0.26 tons per rolling 12-month period from emissions unit P102;

These quarterly deviation reports are due by the dates specified in Part I - General Terms and Conditions A.1.

2. The permittee shall submit quarterly deviation (excursion) reports that identify the all

Honda of America Mfg. Inc.

DTI Application: 05 11125

Facility ID: 0575000174

Emissions Unit ID: P102

periods of time in which this emissions unit was in operation and the pressure drop across the baghouse(s) did not comply with the allowable range.

These quarterly deviation reports are due by the dates specified in Part I - General Terms and Conditions A.1.

Issued: 1/24/2008

3. The permittee shall submit semiannual written reports that:
 - a. identify all days during which any visible PE were observed from any stack serving this emissions unit;
 - b. describe the corrective actions taken to eliminate the visible PE.

These reports shall be submitted to the Ohio EPA, Southwest District Office by January 31 and July 31 of each year and shall cover the previous 6-month period.

V. Testing Requirements

1. Compliance with the emission limitations specified in Part III - A.I.1 shall be determined in accordance with the following methods:

- a. Emission Limitation:

7.9 lbs of PE/hr

The hourly emission limitation was established by the following methodology:

$$\text{AMR} = 0.5782 \times (\text{U to the power of } 0.6456)$$

where:

AMR = Allowable Mass Emission Rate, in lbs/hr;

U = Uncontrolled particulate emissions, in lbs/hr (57.8 lb/hr based on an emission factor of 17.0 lb PE/ton and 3.4 TPH maximum metal rate).

Emission calculation is based on the requirements of OAC rule 3745-17-11(B)(1) Figure II, curve P-1.

Applicable Compliance Method:

Compliance with the above limitations is based on the 3.4 tons of metal being the maximum potential metal usage in this emissions unit and emission testing demonstrating 0.005 grains/ dscf requirement.

- b. Emission Limitation:

The particulate emissions (PE) from baghouse # 1, which controls emissions

Issued: 1/24/2008

from emissions units, P098, P099, P100, P101, and P102 shall not exceed 13.14 tons (PE) combined/rolling 12-month period.

The combined rolling 12-month emission limitation is the total sum of the following equation for all of the above listed emissions units:

$$\text{AER} = [(\text{Af} \times \text{Ef} \times 60 \text{ mins/hr} \times \text{Cf}) \times \text{Ho}] / 2000$$

where:

AER = Particulate emissions, in tons per rolling 12 month period;

Af = Maximum Air Flow from Baghouse # 1, in acfm, (70,000, specific acfm rates are from the data provide by Honda);

Ef = Emission factor of the control device, grains of PE per dscf, (0.005 grains/dscf, data from Honda);

Cf = Conversion factor, (1 lbs/7,000 grains); and

Ho = Allowable rolling 12-month hours of operation limitation, (8,760 hrs).

Applicable Compliance Method:

The permittee shall demonstrate compliance with the above limits based upon the record keeping requirements of Sections III.1., of this permit.

c. Emission Limitation:

The fugitive particulate emissions (PE) from emissions unit P102, shall not exceed 0.26 tons (PE)/ rolling 12-month period.

The fugitive PE rolling 12-month emission limitation is the total sum of the following equation:

$$\text{FER} = [(\text{MMR} \times \text{Ef}) \times (1-\text{CAP})] / 2000\text{lbs/ton}$$

where:

FER = Fugitive Particulate emissions, in tons per rolling 12 month period;

MMR = Maximum metal usage rate, in tons, (3.4 tons/hr, from the data provide by Honda);

Ef = Emission factor, in lbs of PE/ton of metal, (17.0 lbs PE/ton of metal, Fire SCC 304000340); and

CAP = Assumed capture efficiency, in %, (99.9% (0.999), from data provided by

Issued: 1/24/2008

Honda).

Applicable Compliance Method:

The permittee shall demonstrate compliance with the above limits based upon the record keeping requirements of Sections III.2, of this permit.

d. Emission Limitation:

Visible PE shall not exceed 20% opacity, as a 6-minute average, from the baghouse stack serving this emission unit.

Issued: 1/24/2008

Applicable Compliance Method:

If required, compliance shall be determined through visible emissions observations performed in accordance with 40 CFR Part 60, Appendix A, Method 9.

2. The permittee shall conduct, or have conducted, emission testing for baghouse # 1 to demonstrate compliance with the allowable PE limitations.
 - a. The emission testing shall be conducted within 6 months of the installation certificate for this source (facility).
 - b. The emission testing shall be conducted to demonstrate compliance with the allowable PE limitations.
 - c. The following test methods shall be employed to demonstrate compliance with the allowable mass emission limitations.

PE: Methods 1-5 of 40 CFR Part 60, Appendix A

Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA.

- d. The test(s) shall be conducted while the emission units being controlled by the baghouse(s) are being operated at or near their maximum capacities, unless otherwise specified or approved by the Ohio EPA, Southwest District Office.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, Southwest District Office. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, Southwest District Office's refusal to accept the results of the emission test(s). Personnel from the Ohio EPA shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

VI. Miscellaneous Requirements

Honda of America Mfg. Inc.
DTI Application: 05 11125

Facility ID: 0575000174

Emissions Unit ID: P102

None

Issued: 1/24/2008

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment -(P102) - Spin Line 2 Tube Cutting Machine 6

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05	Limit(s)

2. **Additional Terms and Conditions**

- 2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None