



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL  
GUERNSEY COUNTY**

**CERTIFIED MAIL**

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center  
P.O. Box 1049

**Application No: 06-07130**

**DATE:** 4/22/2003

Detroit Diesel Remanufacturing East  
Bill Reed  
PO Box 940  
Cambridge, OH 43725

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission  
236 East Town Street, Room 300  
Columbus, Ohio 43215

Very truly yours,

Michael W. Ahern, Supervisor  
Field Operations and Permit Section  
Division of Air Pollution Control

cc: USEPA

SEDO



**Permit To Install  
Terms and Conditions**

**Issue Date: 4/22/2003  
Effective Date: 4/22/2003**

**FINAL PERMIT TO INSTALL 06-07130**

Application Number: 06-07130  
APS Premise Number: 0630010130  
Permit Fee: **\$5600**  
Name of Facility: Detroit Diesel Remanufacturing East  
Person to Contact: Bill Reed  
Address: PO Box 940  
Cambridge, OH 43725

Location of proposed air contaminant source(s) [emissions unit(s)]:  
**60703 Country Club Rd.  
Byesville, Ohio**

Description of proposed emissions unit(s):  
**Shot blast and flame spray units used for part reconditioning.**

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

## **Part I - GENERAL TERMS AND CONDITIONS**

### **A. Permit to Install General Terms and Conditions**

#### **1. Compliance Requirements**

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

#### **2. Reporting Requirements**

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or record keeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and record keeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

#### **3. Records Retention Requirements**

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

#### **4. Inspections and Information Requests**

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized

representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

#### **5. Scheduled Maintenance/Malfunction Reporting**

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

#### **6. Permit Transfers**

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

#### **7. Air Pollution Nuisance**

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

#### **8. Termination of Permit to Install**

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

#### **9. Construction of New Sources(s)**

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio

Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

#### **10. Public Disclosure**

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

#### **11. Applicability**

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

#### **12. Best Available Technology**

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

#### **13. Source Operation and Operating Permit Requirements After Completion of Construction**

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

**Detroit Diesel Remanufacturing East**  
**PTI Application: 06-07130**  
**Issued: 4/22/2003**

**Facility ID: 0630010130**

**14. Construction Compliance Certification**

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

**15. Fees**

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

**B. Permit to Install Summary of Allowable Emissions**

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)**  
**TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
PE	2.1

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P903 - Shot Blasting Unit (SB-1 Skirt Blasting) Controlled with a Baghouse	OAC rule 3745-31-05(A)(3)	Particulate emissions (PE) shall not exceed 0.02 lb/hr and 0.1 ton/yr.  There shall be no visible emissions from the baghouse exhaust stack.
	OAC rule 3745-17-07(A)(1) OAC rule 3745-17-11(B)(1)	The emission limitations specified by these rules are less stringent than those established pursuant to OAC rule 3745-31-05(A)(3).

**2. Additional Terms and Conditions**

- 2.a None

**B. Operational Restrictions**

- 1. The permittee shall employ a baghouse having a minimum design control efficiency for particulate emissions of 99% during any operation of this emissions unit.

**C. Monitoring and/or Record keeping Requirements**

- 1. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the baghouse exhaust stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:

- a. The color of the emissions;
  - b. The total duration of any visible emission incident; and
  - c. Any corrective actions taken to eliminate the visible emissions.
2. The permittee shall maintain daily records that document any time periods when the baghouse was not in service when the emissions unit was in operation.

#### **D. Reporting Requirements**

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the baghouse exhaust stack serving this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall submit deviation (excursion) reports that identify any daily record showing that the baghouse was not in service when the emissions unit was in operation. The deviation reports shall be submitted within 30 days after the deviation.

#### **E. Testing Requirements**

##### **1. Emission Limitations:**

PE shall not exceed 0.02 lb/hr and 0.1 ton/yr.

##### **Applicable Compliance Method:**

Compliance with the lb/hr emission limitation may be demonstrated through the following one-time calculation using the emission factor of 27 lb PE/1000 lb shot, the maximum shot use rate, a steel shot adjustment factor, and the baghouse design control efficiency. The emission factor is specified in the U.S. EPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 13.2.6, Table 13.2.6-1 (9/97).

$$\text{PE(lb/hr)} = 27 \text{ lb PE/1000 lb shot} \times 526 \text{ lbs shot/hr} \times 0.1 \text{ (emissions using steel shot are 10\% that of sand)} \times 0.01 \text{ (99\% min. baghouse efficiency)} = 0.014 \text{ lb/hr}$$

If required, the permittee shall demonstrate compliance with the lb/hr emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5.

**Detroit Diesel Remanufacturing East**

**PTI Application: 06-07130**

**Issued**

**Facility ID: 0630010130**

**Emissions Unit ID: P903**

Compliance with the ton/yr emission limitation may be demonstrated through the following one-time calculation using the maximum hourly emission rate.

$$PE(tpy) = 0.014 \text{ lb/hr} \times 8760 \text{ hrs/yr} \times 0.0005 \text{ ton/lb} = 0.061 \text{ tpy}$$

**2. Emission Limitation:**

There shall be no visible emissions from the baghouse exhaust stack.

**Applicable Compliance Method:**

If required, compliance shall be demonstrated based upon the visible particulate emission observations specified in Test Method 22.

**F. Miscellaneous Requirements**

None

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P904 - Shot Blasting Unit (SB-2 Bore Blaster) Controlled with a Baghouse	OAC rule 3745-31-05(A)(3)  OAC rule 3745-17-07(A)(1) OAC rule 3745-17-11(B)(1)	Particulate emissions (PE) shall not exceed 0.02 lb/hr and 0.1 ton/yr.  There shall be no visible emissions from the baghouse exhaust stack.  The emission limitations specified by these rules are less stringent than those established pursuant to OAC rule 3745-31-05(A)(3).

2. **Additional Terms and Conditions**

- 2.a None

**B. Operational Restrictions**

1. The permittee shall employ a baghouse having a minimum design control efficiency for particulate emissions of 99% during any operation of this emissions unit.

**C. Monitoring and/or Record keeping Requirements**

1. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the baghouse exhaust stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:

- a. The color of the emissions;
  - b. The total duration of any visible emission incident; and
  - c. Any corrective actions taken to eliminate the visible emissions.
2. The permittee shall maintain daily records that document any time periods when the baghouse was not in service when the emissions unit was in operation.

#### **D. Reporting Requirements**

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the baghouse exhaust stack serving this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall submit deviation (excursion) reports that identify any daily record showing that the baghouse was not in service when the emissions unit was in operation. The deviation reports shall be submitted within 30 days after the deviation.

#### **E. Testing Requirements**

##### **1. Emission Limitations:**

PE shall not exceed 0.02 lb/hr and 0.1 ton/yr.

##### **Applicable Compliance Method:**

Compliance with the lb/hr emission limitation may be demonstrated through the following one-time calculation using the emission factor of 27 lb PE/1000 lb shot, the maximum shot use rate, a steel shot adjustment factor, and the baghouse design control efficiency. The emission factor is specified in the U.S. EPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 13.2.6, Table 13.2.6-1 (9/97).

$$\text{PE(lb/hr)} = 27 \text{ lb PE/1000 lb shot} \times 526 \text{ lbs shot/hr} \times 0.1 \text{ (emissions using steel shot are 10\% that of sand)} \times 0.01 \text{ (99\% min. baghouse efficiency)} = 0.014 \text{ lb/hr}$$

If required, the permittee shall demonstrate compliance with the lb/hr emission limitation through

**Detroit Diesel Remanufacturing East**

PTI Application: 06-07130

**Issued****Facility ID: 0630010130**Emissions Unit ID: **P904**

emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5.

Compliance with the ton/yr emission limitation may be demonstrated through the following one-time calculation using the maximum hourly emission rate.

$$PE(tpy) = 0.014 \text{ lb/hr} \times 8760 \text{ hrs/yr} \times 0.0005 \text{ ton/lb} = 0.061 \text{ tpy}$$

**2. Emission Limitation:**

There shall be no visible emissions from the baghouse exhaust stack.

Applicable Compliance Method:

If required, compliance shall be demonstrated based upon the visible particulate emission observations specified in Test Method 22.

**F. Miscellaneous Requirements**

None

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P905 - Shot Blasting Unit (SB-3 Water Pumps Shot Blaster) Controlled with a Baghouse	OAC rule 3745-31-05(A)(3)  OAC rule 3745-17-07(A)(1) OAC rule 3745-17-11(B)(1)	Particulate emissions (PE) shall not exceed 0.02 lb/hr and 0.1 ton/yr.  There shall be no visible emissions from the baghouse exhaust stack.  The emission limitations specified by these rules are less stringent than those established pursuant to OAC rule 3745-31-05(A)(3).

2. **Additional Terms and Conditions**

- 2.a None

**B. Operational Restrictions**

1. The permittee shall employ a baghouse having a minimum design control efficiency for particulate emissions of 99% during any operation of this emissions unit.

**C. Monitoring and/or Record keeping Requirements**

1. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the baghouse exhaust stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the

operations log:

- a. The color of the emissions;
  - b. The total duration of any visible emission incident; and
  - c. Any corrective actions taken to eliminate the visible emissions.
2. The permittee shall maintain daily records that document any time periods when the baghouse was not in service when the emissions unit was in operation.

#### **D. Reporting Requirements**

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the baghouse exhaust stack serving this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall submit deviation (excursion) reports that identify any daily record showing that the baghouse was not in service when the emissions unit was in operation. The deviation reports shall be submitted within 30 days after the deviation.

#### **E. Testing Requirements**

1. Emission Limitations:

PE shall not exceed 0.02 lb/hr and 0.1 ton/yr.

Applicable Compliance Method:

Compliance with the lb/hr emission limitation may be demonstrated through the following one-time calculation using the emission factor of 27 lb PE/1000 lb shot, the maximum shot use rate, a steel shot adjustment factor, and the baghouse design control efficiency. The emission factor is specified in the U.S. EPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 13.2.6, Table 13.2.6-1 (9/97).

$$\text{PE(lb/hr)} = 27 \text{ lb PE/1000 lb shot} \times 526 \text{ lbs shot/hr} \times 0.1 \text{ (emissions using steel shot are 10\% that of sand)} \times 0.01 \text{ (99\% min. baghouse efficiency)} = 0.014 \text{ lb/hr}$$

**Detroit Diesel Remanufacturing East**

PTI Application: 06-07130

**Issued****Facility ID: 0630010130**Emissions Unit ID: **P905**

If required, the permittee shall demonstrate compliance with the lb/hr emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5.

Compliance with the ton/yr emission limitation may be demonstrated through the following one-time calculation using the maximum hourly emission rate.

$$PE(tpy) = 0.014 \text{ lb/hr} \times 8760 \text{ hrs/yr} \times 0.0005 \text{ ton/lb} = 0.061 \text{ tpy}$$

**2.** Emission Limitation:

There shall be no visible emissions from the baghouse exhaust stack.

Applicable Compliance Method:

If required, compliance shall be demonstrated based upon the visible particulate emission observations specified in Test Method 22.

**F. Miscellaneous Requirements**

None

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P906 - Shot Blasting Unit (SB-4 Rough Blast Shot Blaster) Controlled with a Baghouse	OAC rule 3745-31-05(A)(3)  OAC rule 3745-17-07(A)(1) OAC rule 3745-17-11(B)(1)	Particulate emissions (PE) shall not exceed 0.02 lb/hr and 0.1 ton/yr.  There shall be no visible emissions from the baghouse exhaust stack.  The emission limitations specified by these rules are less stringent than those established pursuant to OAC rule 3745-31-05(A)(3).

2. **Additional Terms and Conditions**

- 2.a None

**B. Operational Restrictions**

1. The permittee shall employ a baghouse having a minimum design control efficiency for particulate emissions of 99% during any operation of this emissions unit.

**C. Monitoring and/or Record keeping Requirements**

1. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the baghouse exhaust stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the

operations log:

- a. The color of the emissions;
  - b. The total duration of any visible emission incident; and
  - c. Any corrective actions taken to eliminate the visible emissions.
2. The permittee shall maintain daily records that document any time periods when the baghouse was not in service when the emissions unit was in operation.

#### **D. Reporting Requirements**

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the baghouse exhaust stack serving this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall submit deviation (excursion) reports that identify any daily record showing that the baghouse was not in service when the emissions unit was in operation. The deviation reports shall be submitted within 30 days after the deviation.

#### **E. Testing Requirements**

1. Emission Limitations:

PE shall not exceed 0.02 lb/hr and 0.1 ton/yr.

Applicable Compliance Method:

Compliance with the lb/hr emission limitation may be demonstrated through the following one-time calculation using the emission factor of 27 lb PE/1000 lb shot, the maximum shot use rate, a steel shot adjustment factor, and the baghouse design control efficiency. The emission factor is specified in the U.S. EPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 13.2.6, Table 13.2.6-1 (9/97).

$$\text{PE(lb/hr)} = 27 \text{ lb PE/1000 lb shot} \times 526 \text{ lbs shot/hr} \times 0.1 \text{ (emissions using steel shot are 10\% that of sand)} \times 0.01 \text{ (99\% min. baghouse efficiency)} = 0.014 \text{ lb/hr}$$

**Detroit Diesel Remanufacturing East**

PTI Application: 06-07130

**Issued****Facility ID: 0630010130**Emissions Unit ID: **P906**

If required, the permittee shall demonstrate compliance with the lb/hr emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5.

Compliance with the ton/yr emission limitation may be demonstrated through the following one-time calculation using the maximum hourly emission rate.

$$PE(tpy) = 0.014 \text{ lb/hr} \times 8760 \text{ hrs/yr} \times 0.0005 \text{ ton/lb} = 0.061 \text{ tpy}$$

**2. Emission Limitation:**

There shall be no visible emissions from the baghouse exhaust stack.

**Applicable Compliance Method:**

If required, compliance shall be demonstrated based upon the visible particulate emission observations specified in Test Method 22.

**F. Miscellaneous Requirements**

None

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P907 - Shot Blasting Unit (SB-5 Clean-up Shot Blaster) Controlled with a Baghouse	OAC rule 3745-31-05(A)(3)	Particulate emissions (PE) shall not exceed 0.02 lb/hr and 0.1 ton/yr.  There shall be no visible emissions from the baghouse exhaust stack.
	OAC rule 3745-17-07(A)(1) OAC rule 3745-17-11(B)(1)	The emission limitations specified by these rules are less stringent than those established pursuant to OAC rule 3745-31-05(A)(3).

2. **Additional Terms and Conditions**

- 2.a None

**B. Operational Restrictions**

1. The permittee shall employ a baghouse having a minimum design control efficiency for particulate emissions of 99% during any operation of this emissions unit.

**C. Monitoring and/or Record keeping Requirements**

1. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the baghouse exhaust stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the

operations log:

- a. The color of the emissions;
  - b. The total duration of any visible emission incident; and
  - c. Any corrective actions taken to eliminate the visible emissions.
2. The permittee shall maintain daily records that document any time periods when the baghouse was not in service when the emissions unit was in operation.

#### **D. Reporting Requirements**

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the baghouse exhaust stack serving this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall submit deviation (excursion) reports that identify any daily record showing that the baghouse was not in service when the emissions unit was in operation. The deviation reports shall be submitted within 30 days after the deviation.

#### **E. Testing Requirements**

1. Emission Limitations:

PE shall not exceed 0.02 lb/hr and 0.1 ton/yr.

Applicable Compliance Method:

Compliance with the lb/hr emission limitation may be demonstrated through the following one-time calculation using the emission factor of 27 lb PE/1000 lb shot, the maximum shot use rate, a steel shot adjustment factor, and the baghouse design control efficiency. The emission factor is specified in the U.S. EPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 13.2.6, Table 13.2.6-1 (9/97).

$$\text{PE(lb/hr)} = 27 \text{ lb PE/1000 lb shot} \times 526 \text{ lbs shot/hr} \times 0.1 \text{ (emissions using steel shot are 10\% that of sand)} \times 0.01 \text{ (99\% min. baghouse efficiency)} = 0.014 \text{ lb/hr}$$

**Detroit Diesel Remanufacturing East**

PTI Application: 06-07130

**Issued****Facility ID: 0630010130**Emissions Unit ID: **P907**

If required, the permittee shall demonstrate compliance with the lb/hr emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5.

Compliance with the ton/yr emission limitation may be demonstrated through the following one-time calculation using the maximum hourly emission rate.

$$PE(tpy) = 0.014 \text{ lb/hr} \times 8760 \text{ hrs/yr} \times 0.0005 \text{ ton/lb} = 0.061 \text{ tpy}$$

**2. Emission Limitation:**

There shall be no visible emissions from the baghouse exhaust stack.

**Applicable Compliance Method:**

If required, compliance shall be demonstrated based upon the visible particulate emission observations specified in Test Method 22.

**F. Miscellaneous Requirements**

None

## PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

### A. Applicable Emissions Limitations and/or Control Requirements

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P908 - Shot Blasting Unit (SB-6 4 Cycle Shot Blaster) Controlled with a Baghouse	OAC rule 3745-31-05(A)(3)  OAC rule 3745-17-07(A)(1) OAC rule 3745-17-11(B)(1)	Particulate emissions (PE) shall not exceed 0.02 lb/hr and 0.1 ton/yr.  There shall be no visible emissions from the baghouse exhaust stack.  The emission limitations specified by these rules are less stringent than those established pursuant to OAC rule 3745-31-05(A)(3).

### 2. Additional Terms and Conditions

- None

### B. Operational Restrictions

- The permittee shall employ a baghouse having a minimum design control efficiency for particulate emissions of 99% during any operation of this emissions unit.

### C. Monitoring and/or Record keeping Requirements

- The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the baghouse exhaust stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the

operations log:

- a. The color of the emissions;
  - b. The total duration of any visible emission incident; and
  - c. Any corrective actions taken to eliminate the visible emissions.
2. The permittee shall maintain daily records that document any time periods when the baghouse was not in service when the emissions unit was in operation.

#### **D. Reporting Requirements**

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the baghouse exhaust stack serving this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall submit deviation (excursion) reports that identify any daily record showing that the baghouse was not in service when the emissions unit was in operation. The deviation reports shall be submitted within 30 days after the deviation.

#### **E. Testing Requirements**

1. Emission Limitations:

PE shall not exceed 0.02 lb/hr and 0.1 ton/yr.

Applicable Compliance Method:

Compliance with the lb/hr emission limitation may be demonstrated through the following one-time calculation using the emission factor of 27 lb PE/1000 lb shot, the maximum shot use rate, a steel shot adjustment factor, and the baghouse design control efficiency. The emission factor is specified in the U.S. EPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 13.2.6, Table 13.2.6-1 (9/97).

$$\text{PE(lb/hr)} = 27 \text{ lb PE/1000 lb shot} \times 526 \text{ lbs shot/hr} \times 0.1 \text{ (emissions using steel shot are 10\% that of sand)} \times 0.01 \text{ (99\% min. baghouse efficiency)} = 0.014 \text{ lb/hr}$$

**Detroit Diesel Remanufacturing East**

PTI Application: 06-07130

**Issued****Facility ID: 0630010130**Emissions Unit ID: **P908**

If required, the permittee shall demonstrate compliance with the lb/hr emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5.

Compliance with the ton/yr emission limitation may be demonstrated through the following one-time calculation using the maximum hourly emission rate.

$$PE(tpy) = 0.014 \text{ lb/hr} \times 8760 \text{ hrs/yr} \times 0.0005 \text{ ton/lb} = 0.061 \text{ tpy}$$

**2. Emission Limitation:**

There shall be no visible emissions from the baghouse exhaust stack.

**Applicable Compliance Method:**

If required, compliance shall be demonstrated based upon the visible particulate emission observations specified in Test Method 22.

**F. Miscellaneous Requirements**

None

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P909 - Shot Blasting Unit (SB-7 2 Cycle Shot Blaster) Controlled with a Baghouse	OAC rule 3745-31-05(A)(3)  OAC rule 3745-17-07(A)(1) OAC rule 3745-17-11(B)(1)	Particulate emissions (PE) shall not exceed 0.02 lb/hr and 0.1 ton/yr.  There shall be no visible emissions from the baghouse exhaust stack.  The emission limitations specified by these rules are less stringent than those established pursuant to OAC rule 3745-31-05(A)(3).

2. **Additional Terms and Conditions**

- 2.a None

**B. Operational Restrictions**

1. The permittee shall employ a baghouse having a minimum design control efficiency for particulate emissions of 99% during any operation of this emissions unit.

**C. Monitoring and/or Record keeping Requirements**

1. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the baghouse exhaust stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the

operations log:

- a. The color of the emissions;
  - b. The total duration of any visible emission incident; and
  - c. Any corrective actions taken to eliminate the visible emissions.
2. The permittee shall maintain daily records that document any time periods when the baghouse was not in service when the emissions unit was in operation.

#### **D. Reporting Requirements**

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the baghouse exhaust stack serving this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall submit deviation (excursion) reports that identify any daily record showing that the baghouse was not in service when the emissions unit was in operation. The deviation reports shall be submitted within 30 days after the deviation.

#### **E. Testing Requirements**

1. Emission Limitations:

PE shall not exceed 0.02 lb/hr and 0.1 ton/yr.

Applicable Compliance Method:

Compliance with the lb/hr emission limitation may be demonstrated through the following one-time calculation using the emission factor of 27 lb PE/1000 lb shot, the maximum shot use rate, a steel shot adjustment factor, and the baghouse design control efficiency. The emission factor is specified in the U.S. EPA reference document AP-42, Fifth Edition, Compilation of Air Pollution Emission Factors, Section 13.2.6, Table 13.2.6-1 (9/97).

$$\text{PE(lb/hr)} = 27 \text{ lb PE/1000 lb shot} \times 526 \text{ lbs shot/hr} \times 0.1 \text{ (emissions using steel shot are 10\% that of sand)} \times 0.01 \text{ (99\% min. baghouse efficiency)} = 0.014 \text{ lb/hr}$$

**Detroit Diesel Remanufacturing East**

PTI Application: 06-07130

**Issued****Facility ID: 0630010130**Emissions Unit ID: **P909**

If required, the permittee shall demonstrate compliance with the lb/hr emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5.

Compliance with the ton/yr emission limitation may be demonstrated through the following one-time calculation using the maximum hourly emission rate.

$$PE(tpy) = 0.014 \text{ lb/hr} \times 8760 \text{ hrs/yr} \times 0.0005 \text{ ton/lb} = 0.061 \text{ tpy}$$

**2. Emission Limitation:**

There shall be no visible emissions from the baghouse exhaust stack.

**Applicable Compliance Method:**

If required, compliance shall be demonstrated based upon the visible particulate emission observations specified in Test Method 22.

**F. Miscellaneous Requirements**

None

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
R004 - Flame Spray (4 Cycle) Controlled with a Dust Collector	OAC rule 3745-31-05(A)(3)  OAC rule 3745-17-07(A)(1) OAC rule 3745-17-11(B)(1)	Particulate emissions (PE) shall not exceed 0.05 lb/hr and 0.2 ton/yr.  There shall be no visible emissions from the dust collector exhaust stack.  The emission limitations specified by these rules are less stringent than those established pursuant to OAC rule 3745-31-05(A)(3).

2. **Additional Terms and Conditions**

- 2.a None

**B. Operational Restrictions**

1. The permittee shall employ a dust collector having a minimum design control efficiency for particulate emissions of 99% during any operation of this emissions unit.

**C. Monitoring and/or Record keeping Requirements**

1. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the dust collector exhaust stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following

in the operations log:

- a. The color of the emissions;
  - b. The total duration of any visible emission incident; and
  - c. Any corrective actions taken to eliminate the visible emissions.
2. The permittee shall maintain daily records that document any time periods when the dust collector was not in service when the emissions unit was in operation.

#### **D. Reporting Requirements**

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the dust collector exhaust stack serving this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall submit deviation (excursion) reports that identify any daily record showing that the dust collector was not in service when the emissions unit was in operation. The deviation reports shall be submitted within 30 days after the deviation.

#### **E. Testing Requirements**

1. Emission Limitations:

PE shall not exceed 0.05 lb/hr and 0.2 ton/yr.

Applicable Compliance Method:

Compliance with the lb/hr emission limitation may be demonstrated through the following one-time calculation using the emission factor based on a mass balance provided by the permittee and the dust collector design control efficiency.

$$PE(\text{lb/hr}) = 4.27 \text{ lb/hr} \times 0.01 \text{ (99\% min. dust collector efficiency)} = 0.043 \text{ lb/hr}$$

If required, the permittee shall demonstrate compliance with the lb/hr emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5.

**Detroit Diesel Remanufacturing East**

PTI Application: 06-07130

**Issued****Facility ID: 0630010130**Emissions Unit ID: **R004**

Compliance with the ton/yr emission limitation may be demonstrated through the following one-time calculation using the maximum hourly emission rate.

$$PE(tpy) = 0.043 \text{ lb/hr} \times 8760 \text{ hrs/yr} \times 0.0005 \text{ ton/lb} = 0.19 \text{ tpy}$$

**2. Emission Limitation:**

There shall be no visible emissions from the dust collector exhaust stack.

**Applicable Compliance Method:**

If required, compliance shall be demonstrated based upon the visible particulate emission observations specified in Test Method 22.

**F. Miscellaneous Requirements**

None

## **PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

### **A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
R005 - Automatic Flame Spray (4 Cycle) Controlled with a Dust Collector	OAC rule 3745-31-05(A)(3)  OAC rule 3745-17-07(A)(1) OAC rule 3745-17-11(B)(1)	Particulate emissions (PE) shall not exceed 0.05 lb/hr and 0.2 ton/yr.  There shall be no visible emissions from the dust collector exhaust stack.  The emission limitations specified by these rules are less stringent than those established pursuant to OAC rule 3745-31-05(A)(3).

2. **Additional Terms and Conditions**

- 2.a None

### **B. Operational Restrictions**

1. The permittee shall employ a dust collector having a minimum design control efficiency for particulate emissions of 99% during any operation of this emissions unit.

### **C. Monitoring and/or Record keeping Requirements**

1. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the dust collector exhaust stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following

in the operations log:

- a. The color of the emissions;
  - b. The total duration of any visible emission incident; and
  - c. Any corrective actions taken to eliminate the visible emissions.
2. The permittee shall maintain daily records that document any time periods when the dust collector was not in service when the emissions unit was in operation.

#### **D. Reporting Requirements**

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the dust collector exhaust stack serving this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall submit deviation (excursion) reports that identify any daily record showing that the dust collector was not in service when the emissions unit was in operation. The deviation reports shall be submitted within 30 days after the deviation.

#### **E. Testing Requirements**

1. Emission Limitations:

PE shall not exceed 0.05 lb/hr and 0.2 ton/yr.

Applicable Compliance Method:

Compliance with the lb/hr emission limitation may be demonstrated through the following one-time calculation using the emission factor based on a mass balance provided by the permittee and the dust collector design control efficiency.

$$PE(\text{lb/hr}) = 4.27 \text{ lb/hr} \times 0.01 \text{ (99\% min. dust collector efficiency)} = 0.043 \text{ lb/hr}$$

If required, the permittee shall demonstrate compliance with the lb/hr emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5.

**Detroit Diesel Remanufacturing East**

PTI Application: 06-07130

**Issued****Facility ID: 0630010130**Emissions Unit ID: **R005**

Compliance with the ton/yr emission limitation may be demonstrated through the following one-time calculation using the maximum hourly emission rate.

$$PE(tpy) = 0.043 \text{ lb/hr} \times 8760 \text{ hrs/yr} \times 0.0005 \text{ ton/lb} = 0.19 \text{ tpy}$$

**2. Emission Limitation:**

There shall be no visible emissions from the dust collector exhaust stack.

**Applicable Compliance Method:**

If required, compliance shall be demonstrated based upon the visible particulate emission observations specified in Test Method 22.

**F. Miscellaneous Requirements**

None

## PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

### A. Applicable Emissions Limitations and/or Control Requirements

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
R006 - Flame Spray Booth (2 Cycle) Controlled with a Dust Collector	OAC rule 3745-31-05(A)(3)  OAC rule 3745-17-07(A)(1) OAC rule 3745-17-11(B)(1)	Particulate emissions (PE) shall not exceed 0.05 lb/hr and 0.2 ton/yr.  There shall be no visible emissions from the dust collector exhaust stack.  The emission limitations specified by these rules are less stringent than those established pursuant to OAC rule 3745-31-05(A)(3).

### 2. Additional Terms and Conditions

- None

### B. Operational Restrictions

- The permittee shall employ a dust collector having a minimum design control efficiency for particulate emissions of 99% during any operation of this emissions unit.

### C. Monitoring and/or Record keeping Requirements

- The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the dust collector exhaust stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following

in the operations log:

- a. The color of the emissions;
  - b. The total duration of any visible emission incident; and
  - c. Any corrective actions taken to eliminate the visible emissions.
2. The permittee shall maintain daily records that document any time periods when the dust collector was not in service when the emissions unit was in operation.

#### **D. Reporting Requirements**

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the dust collector exhaust stack serving this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall submit deviation (excursion) reports that identify any daily record showing that the dust collector was not in service when the emissions unit was in operation. The deviation reports shall be submitted within 30 days after the deviation.

#### **E. Testing Requirements**

1. Emission Limitations:

PE shall not exceed 0.05 lb/hr and 0.2 ton/yr.

Applicable Compliance Method:

Compliance with the lb/hr emission limitation may be demonstrated through the following one-time calculation using the emission factor based on a mass balance provided by the permittee and the dust collector design control efficiency.

$$PE(\text{lb/hr}) = 4.27 \text{ lb/hr} \times 0.01 \text{ (99\% min. dust collector efficiency)} = 0.043 \text{ lb/hr}$$

If required, the permittee shall demonstrate compliance with the lb/hr emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5.

**Detroit Diesel Remanufacturing East**

PTI Application: 06-07130

**Issued****Facility ID: 0630010130**Emissions Unit ID: **R006**

Compliance with the ton/yr emission limitation may be demonstrated through the following one-time calculation using the maximum hourly emission rate.

$$PE(tpy) = 0.043 \text{ lb/hr} \times 8760 \text{ hrs/yr} \times 0.0005 \text{ ton/lb} = 0.19 \text{ tpy}$$

**2. Emission Limitation:**

There shall be no visible emissions from the dust collector exhaust stack.

Applicable Compliance Method:

If required, compliance shall be demonstrated based upon the visible particulate emission observations specified in Test Method 22.

**F. Miscellaneous Requirements**

None

## PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

### A. Applicable Emissions Limitations and/or Control Requirements

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
R007 - Automatic Flame Spray (2 Cycle) Controlled with a Dust Collector	OAC rule 3745-31-05(A)(3)  OAC rule 3745-17-07(A)(1) OAC rule 3745-17-11(B)(1)	Particulate emissions (PE) shall not exceed 0.05 lb/hr and 0.2 ton/yr.  There shall be no visible emissions from the dust collector exhaust stack.  The emission limitations specified by these rules are less stringent than those established pursuant to OAC rule 3745-31-05(A)(3).

### 2. Additional Terms and Conditions

- None

### B. Operational Restrictions

- The permittee shall employ a dust collector having a minimum design control efficiency for particulate emissions of 99% during any operation of this emissions unit.

### C. Monitoring and/or Record keeping Requirements

- The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the dust collector exhaust stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following

in the operations log:

- a. The color of the emissions;
  - b. The total duration of any visible emission incident; and
  - c. Any corrective actions taken to eliminate the visible emissions.
2. The permittee shall maintain daily records that document any time periods when the dust collector was not in service when the emissions unit was in operation.

#### **D. Reporting Requirements**

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the dust collector exhaust stack serving this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall submit deviation (excursion) reports that identify any daily record showing that the dust collector was not in service when the emissions unit was in operation. The deviation reports shall be submitted within 30 days after the deviation.

#### **E. Testing Requirements**

1. Emission Limitations:

PE shall not exceed 0.05 lb/hr and 0.2 ton/yr.

Applicable Compliance Method:

Compliance with the lb/hr emission limitation may be demonstrated through the following one-time calculation using the emission factor based on a mass balance provided by the permittee and the dust collector design control efficiency.

$$PE(\text{lb/hr}) = 4.27 \text{ lb/hr} \times 0.01 \text{ (99\% min. dust collector efficiency)} = 0.043 \text{ lb/hr}$$

If required, the permittee shall demonstrate compliance with the lb/hr emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5.

**Detroit Diesel Remanufacturing East**

PTI Application: 06 07130

**Issued****Facility ID: 0630010130**Emissions Unit ID: **R007**

Compliance with the ton/yr emission limitation may be demonstrated through the following one-time calculation using the maximum hourly emission rate.

$$PE(tpy) = 0.043 \text{ lb/hr} \times 8760 \text{ hrs/yr} \times 0.0005 \text{ ton/lb} = 0.19 \text{ tpy}$$

**2. Emission Limitation:**

There shall be no visible emissions from the dust collector exhaust stack.

**Applicable Compliance Method:**

If required, compliance shall be demonstrated based upon the visible particulate emission observations specified in Test Method 22.

**F. Miscellaneous Requirements**

None

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
R008 - Flame Spray (Water Pumps) Controlled with a Dust Collector	OAC rule 3745-31-05(A)(3)  OAC rule 3745-17-07(A)(1) OAC rule 3745-17-11(B)(1)	Particulate emissions (PE) shall not exceed 0.05 lb/hr and 0.2 ton/yr.  There shall be no visible emissions from the dust collector exhaust stack.  The emission limitations specified by these rules are less stringent than those established pursuant to OAC rule 3745-31-05(A)(3).

2. **Additional Terms and Conditions**

- 2.a None

**B. Operational Restrictions**

1. The permittee shall employ a dust collector having a minimum design control efficiency for particulate emissions of 99% during any operation of this emissions unit.

**C. Monitoring and/or Record keeping Requirements**

1. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the dust collector exhaust stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following

in the operations log:

- a. The color of the emissions;
  - b. The total duration of any visible emission incident; and
  - c. Any corrective actions taken to eliminate the visible emissions.
2. The permittee shall maintain daily records that document any time periods when the dust collector was not in service when the emissions unit was in operation.

#### **D. Reporting Requirements**

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the dust collector exhaust stack serving this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall submit deviation (excursion) reports that identify any daily record showing that the dust collector was not in service when the emissions unit was in operation. The deviation reports shall be submitted within 30 days after the deviation.

#### **E. Testing Requirements**

1. Emission Limitations:

PE shall not exceed 0.05 lb/hr and 0.2 ton/yr.

Applicable Compliance Method:

Compliance with the lb/hr emission limitation may be demonstrated through the following one-time calculation using the emission factor based on a mass balance provided by the permittee and the dust collector design control efficiency.

$$PE(\text{lb/hr}) = 4.27 \text{ lb/hr} \times 0.01 \text{ (99\% min. dust collector efficiency)} = 0.043 \text{ lb/hr}$$

If required, the permittee shall demonstrate compliance with the lb/hr emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5.

**Detroit Diesel Remanufacturing East**

PTI Application: 06 07130

**Issued****Facility ID: 0630010130**Emissions Unit ID: **R008**

Compliance with the ton/yr emission limitation may be demonstrated through the following one-time calculation using the maximum hourly emission rate.

$$PE(tpy) = 0.043 \text{ lb/hr} \times 8760 \text{ hrs/yr} \times 0.0005 \text{ ton/lb} = 0.19 \text{ tpy}$$

**2. Emission Limitation:**

There shall be no visible emissions from the dust collector exhaust stack.

**Applicable Compliance Method:**

If required, compliance shall be demonstrated based upon the visible particulate emission observations specified in Test Method 22.

**F. Miscellaneous Requirements**

None

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
R009 - Flame Spray (Bottoms, Tops, Heads, and End Plates) Controlled with a Dust Collector	OAC rule 3745-31-05(A)(3)  OAC rule 3745-17-07(A)(1) OAC rule 3745-17-11(B)(1)	Particulate emissions (PE) shall not exceed 0.05 lb/hr and 0.2 ton/yr.  There shall be no visible emissions from the dust collector exhaust stack.  The emission limitations specified by these rules are less stringent than those established pursuant to OAC rule 3745-31-05(A)(3).

2. **Additional Terms and Conditions**

- 2.a None

**B. Operational Restrictions**

1. The permittee shall employ a dust collector having a minimum design control efficiency for particulate emissions of 99% during any operation of this emissions unit.

**C. Monitoring and/or Record keeping Requirements**

1. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the dust collector exhaust stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following

in the operations log:

- a. The color of the emissions;
  - b. The total duration of any visible emission incident; and
  - c. Any corrective actions taken to eliminate the visible emissions.
2. The permittee shall maintain daily records that document any time periods when the dust collector was not in service when the emissions unit was in operation.

#### **D. Reporting Requirements**

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the dust collector exhaust stack serving this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall submit deviation (excursion) reports that identify any daily record showing that the dust collector was not in service when the emissions unit was in operation. The deviation reports shall be submitted within 30 days after the deviation.

#### **E. Testing Requirements**

1. Emission Limitations:

PE shall not exceed 0.05 lb/hr and 0.2 ton/yr.

Applicable Compliance Method:

Compliance with the lb/hr emission limitation may be demonstrated through the following one-time calculation using the emission factor based on a mass balance provided by the permittee and the dust collector design control efficiency.

$$PE(\text{lb/hr}) = 4.27 \text{ lb/hr} \times 0.01 \text{ (99\% min. dust collector efficiency)} = 0.043 \text{ lb/hr}$$

If required, the permittee shall demonstrate compliance with the lb/hr emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5.

**Detroit Diesel Remanufacturing East**

PTI Application: 06 07130

**Issued****Facility ID: 0630010130**Emissions Unit ID: **R009**

Compliance with the ton/yr emission limitation may be demonstrated through the following one-time calculation using the maximum hourly emission rate.

$$PE(tpy) = 0.043 \text{ lb/hr} \times 8760 \text{ hrs/yr} \times 0.0005 \text{ ton/lb} = 0.19 \text{ tpy}$$

**2. Emission Limitation:**

There shall be no visible emissions from the dust collector exhaust stack.

**Applicable Compliance Method:**

If required, compliance shall be demonstrated based upon the visible particulate emission observations specified in Test Method 22.

**F. Miscellaneous Requirements**

None

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
R010 - Flame Spray (Bores) Controlled with a Dust Collector	OAC rule 3745-31-05(A)(3)  OAC rule 3745-17-07(A)(1) OAC rule 3745-17-11(B)(1)	Particulate emissions (PE) shall not exceed 0.05 lb/hr and 0.2 ton/yr.  There shall be no visible emissions from the dust collector exhaust stack.  The emission limitations specified by these rules are less stringent than those established pursuant to OAC rule 3745-31-05(A)(3).

2. **Additional Terms and Conditions**

- 2.a None

**B. Operational Restrictions**

1. The permittee shall employ a dust collector having a minimum design control efficiency for particulate emissions of 99% during any operation of this emissions unit.

**C. Monitoring and/or Record keeping Requirements**

1. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the dust collector exhaust stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following

in the operations log:

- a. The color of the emissions;
  - b. The total duration of any visible emission incident; and
  - c. Any corrective actions taken to eliminate the visible emissions.
2. The permittee shall maintain daily records that document any time periods when the dust collector was not in service when the emissions unit was in operation.

#### **D. Reporting Requirements**

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the dust collector exhaust stack serving this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall submit deviation (excursion) reports that identify any daily record showing that the dust collector was not in service when the emissions unit was in operation. The deviation reports shall be submitted within 30 days after the deviation.

#### **E. Testing Requirements**

1. Emission Limitations:

PE shall not exceed 0.05 lb/hr and 0.2 ton/yr.

Applicable Compliance Method:

Compliance with the lb/hr emission limitation may be demonstrated through the following one-time calculation using the emission factor based on a mass balance provided by the permittee and the dust collector design control efficiency.

$$PE(\text{lb/hr}) = 4.27 \text{ lb/hr} \times 0.01 \text{ (99\% min. dust collector efficiency)} = 0.043 \text{ lb/hr}$$

If required, the permittee shall demonstrate compliance with the lb/hr emission limitation through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5.

**Detroit Diesel Remanufacturing East**

PTI Application: 06 07130

**Issued****Facility ID: 0630010130**Emissions Unit ID: **R010**

Compliance with the ton/yr emission limitation may be demonstrated through the following one-time calculation using the maximum hourly emission rate.

$$PE(tpy) = 0.043 \text{ lb/hr} \times 8760 \text{ hrs/yr} \times 0.0005 \text{ ton/lb} = 0.19 \text{ tpy}$$

**2. Emission Limitation:**

There shall be no visible emissions from the dust collector exhaust stack.

**Applicable Compliance Method:**

If required, compliance shall be demonstrated based upon the visible particulate emission observations specified in Test Method 22.

**F. Miscellaneous Requirements**

None

**NEW SOURCE REVIEW FORM B**

PTI Number: 06-07130 Facility ID: 0630010130

FACILITY NAME Detroit Diesel Remanufacturing East

FACILITY DESCRIPTION Engine Reconditioning CITY/TWP Bvesville

Emissions Unit ID: **R010**

SIC CODE 3519 SCC CODE 30900207 EMISSIONS UNIT ID P903

EMISSIONS UNIT DESCRIPTION Shot Blasting Unit (SB-1 Skirt Blasting) Controlled with a Baghouse

DATE INSTALLED 1/92

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter		0.02 lb/hr	0.1	0.02 lb/hr	0.1
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination Baghouse, VE Checks

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? N

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to containinants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

**NEW SOURCE REVIEW FORM B**

PTI Number: 06-07130 Facility ID: 0630010130

FACILITY NAME Detroit Diesel Remanufacturing East

FACILITY DESCRIPTION Engine Reconditioning CITY/TWP Bvesville

Emissions Unit ID: **R010**

SIC CODE 3519 SCC CODE 30900207 EMISSIONS UNIT ID P904

EMISSIONS UNIT DESCRIPTION Shot Blasting Unit (SB-2 Bore Blaster) Controlled with a Baghouse

DATE INSTALLED 1/96

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter		0.02 lb/hr	0.1	0.02 lb/hr	0.1
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? PSD? OFFSET POLICY?

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

Enter Determination Baghouse, VE Checks

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? N  
OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

**NEW SOURCE REVIEW FORM B**

PTI Number: 06-07130 Facility ID: 0630010130

FACILITY NAME Detroit Diesel Remanufacturing East

FACILITY DESCRIPTION Engine Reconditioning CITY/TWP Bvesville

Emissions Unit ID: **R010**

SIC CODE 3519 SCC CODE 30900207 EMISSIONS UNIT ID P905

EMISSIONS UNIT DESCRIPTION Shot Blasting Unit (SB-3 Water Pumps Shot Blaster) Controlled with a Baghouse

DATE INSTALLED 1/92

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter		0.02 lb/hr	0.1	0.02 lb/hr	0.1
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? PSD? OFFSET POLICY?

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

Enter Determination Baghouse, VE Checks

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? N  
OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to containinants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

**NEW SOURCE REVIEW FORM B**

PTI Number: 06-07130 Facility ID: 0630010130

FACILITY NAME Detroit Diesel Remanufacturing East

FACILITY DESCRIPTION Engine Reconditioning CITY/TWP Bvesville

Emissions Unit ID: **R010**

SIC CODE 3519 SCC CODE 30900207 EMISSIONS UNIT ID P906

EMISSIONS UNIT DESCRIPTION Shot Blasting Unit (SB-4 Rough Blast Shot Blaster) Controlled with a Baghouse

DATE INSTALLED 1/96

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter		0.02 lb/hr	0.1	0.02 lb/hr	0.1
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? PSD? OFFSET POLICY?

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

Enter Determination Baghouse, VE Checks

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? N  
OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to containinants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

**NEW SC**

PTI Num

FACILITY

Emissions Unit ID: **R010** \_\_\_\_\_

FACILITY DESCRIPTION Engine Reconditioning CITY/TWP Byesville

SIC CODE 3519 SCC CODE 30900207 EMISSIONS UNIT ID P907

EMISSIONS UNIT DESCRIPTION Shot Blasting Unit (SB-5 Clean-up Shot Blaster) Controlled with a Baghouse

DATE INSTALLED 1/96

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter		0.02 lb/hr	0.1	0.02 lb/hr	0.1
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? \_\_\_\_\_ NESHAP? \_\_\_\_\_ PSD? \_\_\_\_\_ OFFSET POLICY? \_\_\_\_\_

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

**Enter Determination** Baghouse, VE Checks

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? N

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ \_\_\_\_\_

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? \_\_\_\_\_ YES \_\_\_\_\_ NO

IDENTIFY THE AIR CONTAMINANTS: \_\_\_\_\_

**NEW SOURCE REVIEW FORM B**

PTI Number: 06-07130 Facility ID: 0630010130

FACILITY NAME Detroit Diesel Remanufacturing East

FACILITY DESCRIPTION Engine Reconditioning CITY/TWP Bvesville

Emissions Unit ID: **R010**

SIC CODE 3519 SCC CODE 30900207 EMISSIONS UNIT ID P908

EMISSIONS UNIT DESCRIPTION Shot Blasting Unit (SB-6 4 Cycle Shot Blaster) Controlled with a Baghouse

DATE INSTALLED 1/01

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter		0.02 lb/hr	0.1	0.02 lb/hr	0.1
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? PSD? OFFSET POLICY?

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

Enter Determination Baghouse, VE Checks

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? N

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to containinants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

**NEW SOURCE REVIEW FORM B**

PTI Number: 06-07130 Facility ID: 0630010130

FACILITY NAME Detroit Diesel Remanufacturing East

FACILITY DESCRIPTION Engine Reconditioning CITY/TWP Bvesville

Emissions Unit ID: **R010**

SIC CODE 3519 SCC CODE 30900207 EMISSIONS UNIT ID P909

EMISSIONS UNIT DESCRIPTION Shot Blasting Unit (SB-7 2 Cycle Shot Blaster) Controlled with a Baghouse

DATE INSTALLED 1/96

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter		0.02 lb/hr	0.1	0.02 lb/hr	0.1
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? PSD? OFFSET POLICY?

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

Enter Determination Baghouse, VE Checks

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? N

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

**NEW SC**

PTI Num

FACILITY

Emissions Unit ID: **R010** \_\_\_\_\_

FACILITY DESCRIPTION Engine Reconditioning CITY/TWP Byesville

SIC CODE 3519 SCC CODE 30904010 EMISSIONS UNIT ID R004

EMISSIONS UNIT DESCRIPTION Flame Spray (4 Cycle) Controlled with a Dust Collector

DATE INSTALLED 1/01

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter		0.05 lb/hr	0.2	0.05	0.2
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? \_\_\_\_\_ NESHAP? \_\_\_\_\_ PSD? \_\_\_\_\_ OFFSET POLICY? \_\_\_\_\_

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

**Enter Determination** Dust Collector, VE Checks

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? N

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ \_\_\_\_\_

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? \_\_\_\_\_ YES \_\_\_\_\_ NO

IDENTIFY THE AIR CONTAMINANTS: \_\_\_\_\_

**NEW SOURCE REVIEW FORM B**

PTI Number: 06-07130 Facility ID: 0630010130

FACILITY NAME Detroit Diesel Remanufacturing East

FACILITY DESCRIPTION Engine Reconditioning CITY/TWP Bvesville

Emissions Unit ID: **R010**

SIC CODE 3519 SCC CODE 30904010 EMISSIONS UNIT ID R005

EMISSIONS UNIT DESCRIPTION Automatic Flame Spray (4 Cycle) Controlled with a Dust Collector

DATE INSTALLED 1/01

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter		0.05 lb/hr	0.2	0.05 lb/hr	0.2
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? PSD? OFFSET POLICY?

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

**Enter Determination** Dust Collector, VE Checks

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? N

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to containinants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

**NEW SOURCE REVIEW FORM B**

PTI Number: 06-07130 Facility ID: 0630010130

FACILITY NAME Detroit Diesel Remanufacturing East

FACILITY DESCRIPTION Engine Reconditioning CITY/TWP Bvesville

Emissions Unit ID: **R010**

SIC CODE 3519 SCC CODE 30904010 EMISSIONS UNIT ID R006

EMISSIONS UNIT DESCRIPTION Flame Spray Booth (2 Cycle) Controlled with a Dust Collector

DATE INSTALLED 1/96

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter		0.05 lb/hr	0.2	0.05 lb/hr	0.2
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? PSD? OFFSET POLICY?

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

**Enter Determination** Dust Collector, VE Checks

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? N  
OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to containinants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

**NEW SC**

PTI Num

FACILITY

Emissions Unit ID: **R010**

FACILITY DESCRIPTION Engine Reconditioning CITY/TWP Byesville

SIC CODE 3519 SCC CODE 30904010 EMISSIONS UNIT ID R007

EMISSIONS UNIT DESCRIPTION Automatic Flame Spray (2 Cycle) Controlled with a Dust Collector

DATE INSTALLED 1/99

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter		0.05 lb/hr	0.2	0.05 lb/hr	0.2
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? \_\_\_\_\_ NESHAP? \_\_\_\_\_ PSD? \_\_\_\_\_ OFFSET POLICY? \_\_\_\_\_

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

**Enter Determination** Dust Collector, VE Checks

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? N

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ \_\_\_\_\_

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? \_\_\_\_\_ YES \_\_\_\_\_ NO

IDENTIFY THE AIR CONTAMINANTS: \_\_\_\_\_

**NEW SOURCE REVIEW FORM B**

PTI Number: 06-07130 Facility ID: 0630010130

FACILITY NAME Detroit Diesel Remanufacturing East

FACILITY DESCRIPTION Engine Reconditioning CITY/TWP Bvesville

Emissions Unit ID: **R010**

SIC CODE 3519 SCC CODE 30904010 EMISSIONS UNIT ID R008

EMISSIONS UNIT DESCRIPTION Flame Spray (Water Pumps) Controlled with a Dust Collector

DATE INSTALLED 1/92

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter		0.05 lb/hr	0.2	0.05 lb/hr	0.2
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? PSD? OFFSET POLICY?

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

**Enter Determination** Dust Collector, VE Checks

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? N

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to containinants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

**NEW SOURCE REVIEW FORM B**

PTI Number: 06-07130 Facility ID: 0630010130

FACILITY NAME Detroit Diesel Remanufacturing East

FACILITY DESCRIPTION Engine Reconditioning CITY/TWP Bvesville

Emissions Unit ID: **R010**

SIC CODE 3519 SCC CODE 30904010 EMISSIONS UNIT ID R009

EMISSIONS UNIT DESCRIPTION Flame Spray (Bottoms, Tops, Heads, and End Plates) Controlled with a Dust Collector

DATE INSTALLED 1/96

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter		0.05 lb/hr	0.2	0.05 lb/hr	0.2
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? PSD? OFFSET POLICY?

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

Enter Determination Dust Collector, VE Checks

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? N

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to containinants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? YES NO

IDENTIFY THE AIR CONTAMINANTS:

62 **NEW SC**

PTI Num

FACILITY

Emissions Unit ID: **R010**

FACILITY DESCRIPTION Engine Reconditioning CITY/TWP Byesville

SIC CODE 3519 SCC CODE 30904010 EMISSIONS UNIT ID R010

EMISSIONS UNIT DESCRIPTION Flame Spray (Bores) Controlled with a Dust Collector

DATE INSTALLED 1/96

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter		0.05 lb/hr	0.2	0.05 lb/hr	0.2
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? \_\_\_\_\_ NESHAP? \_\_\_\_\_ PSD? \_\_\_\_\_ OFFSET POLICY? \_\_\_\_\_

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

**Enter Determination** Dust Collector, VE Checks

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? N

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ \_\_\_\_\_

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? \_\_\_\_\_ YES \_\_\_\_\_ NO

IDENTIFY THE AIR CONTAMINANTS: \_\_\_\_\_