

Tool & Die Systems, Inc.
PN 0247090953
PTI No. 02-12746

Additional Terms and Conditions

A. Additional Terms and Conditions

None

B. Operational Restrictions

1. This emissions unit shall not employ more than ten (10) gallons of coatings per day.
2. A dry filtration system for the paint spray booth (K001) shall be used while the booth is in operation.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each day for the coating line:
 - a. The name and identification number of each coating employed.
 - b. The volume, in gallons, of each coating employed.
 - c. The total volume, in gallons, of all of the coatings employed.
2. The permittee shall collect and record the following information for the purpose of determining annual VOC emissions:
 - a. The name and identification of each cleanup material employed.
 - b. The number of gallons of each cleanup material employed.
 - c. The VOC content of each cleanup material, in pounds per gallon.
 - d. The VOC content of each coating, as applied, in pounds per gallon.
 - e. The total VOC emissions from all coatings and cleanup materials employed, in pounds or tons.

3. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings, if a strip-chart recorder is employed, for continuous monitoring instrumentation, and copies of all reports required by the permit. Such records may be maintained in computerized form.

D. Reporting Requirements

1. The permittee shall notify the Northeast District Office of the Ohio EPA in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit. The notification shall include a copy of such record and shall be sent to the Northeast District Office of the Ohio EPA within forty five days after the exceedance occurs.

2. The permittee shall collect and record the following information for each change where the air toxic modeling was required pursuant to the Air Toxic Policy:

a. background data that describes the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.); and

b. a copy of the resulting computer model runs that show the results of the application of the Air Toxic Policy for the change.

3. The permittee shall submit required reports in the following manner:

a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.

b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the

probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

E. Testing Requirements

1. Compliance with the terms and conditions of this permit shall be determined in accordance with the following method:

Emission Limitation

10 gallons of coating per day.

Applicable Compliance Method

Compliance shall be determined based upon the recordkeeping performed in term and condition C.1.

2. **Emission Limitation**

10.6 tons per year of volatile organic compounds.

Applicable Compliance Method

Compliance shall be determined based upon the recordkeeping performed in term and condition C.2.

F. Miscellaneous Requirements

1. This permit allows the use of materials (typically coatings and cleanup materials) specified by the permittee in the permit to install application for this emissions unit. To fulfill the best available technology requirements of (OAC) rule 3745-31-05 and to ensure compliance with OAC rule 3745-15-07 (Air Pollution Nuisances Prohibited), the emission limitation(s) specified in this permit was (were) established using the Ohio EPA's "Air Toxic Policy" and is (are) based on both the materials used and the design parameters of the

emissions unit's exhaust system, as specified in the application. The Ohio EPA's "Air Toxic Policy" was applied for each pollutant using the SCREEN 3.0 model and comparing the predicted 1-hour maximum ground-level concentration to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for each pollutant:

Pollutant: cyclohexanone

TLV (ug/m3): 100000

Maximum Hourly Emission Rate (lbs/hr): 0.54

Predicted 1-Hour Maximum Ground-Level
Concentration (ug/m3): 46.8

MAGLC (ug/m3): 2380

Pollutant: n-Butyl Acetate

TLV (ug/m3): 713000

Maximum Hourly Emission Rate (lbs/hr): 0.59

Predicted 1-Hour Maximum Ground-Level
Concentration (ug/m3): 50.93

MAGLC (ug/m3): 16980

OAC Chapter 3745-31 requires permittees to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by the OAC rule 3745-31-01. The permittee is hereby advised that the following changes to the process may be determined to be a "modification":

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value specified in the above table;
- b. changes to the emissions unit or its exhaust parameters (e.g., increased emission rate [not including an increase in an

"allowable" emission conditions of this permit], decreased stack height);

limitation specified in the terms and reduced exhaust gas flow rate, and

c. changes in the composition of the materials used, or use of new materials, that would result in the emission of an air contaminant not previously permitted; and

d. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant that has a listed TLV.

The Ohio EPA will not consider any of the above-mentioned as a "modification" requiring a permit to install, if the following conditions are met:

a. the change is not otherwise considered a "modification" under OAC Chapter 3745-31;

b. the permittee can continue to comply with the allowable emission limitations specified in its permit to install; and

c. prior to the change, the applicant conducts an evaluation pursuant to the Air Toxic Policy, determines that the changed emissions unit still satisfies the Air Toxic Policy, and the permittee maintains documentation that identifies the change and the results of the application of the Air Toxic Policy for the change.

For any change to the emissions unit or its method of operation that either would require an increase in the emission limitation(s) established by this permit or would otherwise be considered a "modification" as defined in OAC rule 3745-31-01, the permittee shall obtain a final permit to install prior to the change.