Facility ID: 0448011513 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0448011513 Emissions Unit ID: D001 Issuance type: Final State Permit To Operate

Go to the top of this document

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

   (a) None.

2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

   (a) None.

A. **Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
Dry to Dry perchloroethylene (PCE) dry cleaning with a refrigerated condenser	OAC rule 3745-31-05 (A)(3) PTI 04-1075 issued Aug. 13, 1997	Perchloroethylene usage at this facility shall not exceed 139 gallons per rolling, 12-month period. Emissions of perchloroethylene from this facility shall not exceed 0.94 tons per rolling, 12-month period. The requirements of this rule also include compliance with OAC rule 3745-21-09(AA) and 40 CFR Part 63, Subparts A & M.
	OAC rule 3745-21-09(AA)	See terms A.2.b and B. 1-4.
	40 CFR Part 63, Subparts A & M	See terms A.2.a, A.2.c and B. 5-7.

2. **Additional Terms and Conditions**

   (a) The exhaust from each dry cleaning machine shall be vented through a refrigerated condenser.
   The dryer is equipped with or vented to a refrigerated vapor condenser whereby there is no exhaust of perchloroethylene vapors to the ambient air throughout the drying cycle, except for when the dryer's door is momentarily opened during loading or unloading.
   The permittee must comply with all of the requirements listed for an area source per 40 CFR Part 63, Subpart M.

B. **Operational Restrictions**

1. The waste from any diatomaceous earth filter which has been used to filter perchloroethylene shall contain no more than twenty-five percent (25%) by weight perchloroethylene, as determined under paragraph (J) of OAC rule 3745-21-10.

2. The waste from any distillation operation (solvent still) which has been used to distill perchloroethylene shall contain no more than sixty per cent (60%) by weight perchloroethylene, as determined under paragraph (J) of OAC rule 3745-21-10.

3. Any disposable filter cartridge which has been used to filter perchloroethylene shall be drained in the filter housing for at least twenty-four (24) hours before being discarded.

4. All equipment must be maintained so as to prevent the leaking of perchloroethylene liquid and prevent perceptible vapor leaks from gaskets, seals, ducts, and related equipment. Any equipment which is leaking perchloroethylene liquid or has a perceptible vapor leak shall not be operated until the leak is repaired.

5. The permittee shall store all perchloroethylene and wastes that contain perchloroethylene in solvent tanks or solvent containers with no perceptible leaks. The exception to this requirement is that containers for separator water may be uncovered, as necessary, for proper operation of the machine and still.

6. The door of each dry cleaning machine shall be closed at all times except to transfer articles to and from the machine.

7. The dry cleaning machine shall be operated and maintained according to manufacturer's specifications and recommendations.

C. **Monitoring and/or Record Keeping Requirements**

1. The following components shall be visually inspected biweekly for perceptible leaks while the dry cleaning system is operating:

   a. hose and pipe connections, fittings, coupling and valves;

   b. machine door gaskets and seatings;

   c. filter gaskets and seatings;

   d. pumps;

   e. solvent tanks and containers;

   f. water separators;

   g. filter sludge recovery or muck cookers;

   h. distillation unit;

   i. diverter valves;

   j. saturated lint from the lint basket;

   k. cartridge filters and housings;

   l. stills; and

   m. exhaust dampers.

   Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills this requirement.

   Leaks are to be repaired within 24 hours after being detected. If repair parts are to be ordered, the order shall be initiated within two (2) working days after detecting the leak. The repair parts shall be installed within five (5) working days after they are received.

2. Beginning no later than July 28, 2008, the components listed in Section C.1 shall be inspected monthly for vapor leaks using a halogenated hydrocarbon detector or PCE gas analyzer. The inspections shall be done while the components are in operation. The analyzer shall be operated according to the manufacturer's instructions. Specifically, the operator shall place the probe inlet at the surface of each component interface where leakage could occur and move it slowly along the interface of the periphery. The monthly inspection performed using a halogenated hydrocarbon detector or PCE gas analyzer shall satisfy the requirements for the biweekly visual inspection for perceptible leaks as required in Section C.1.

3. The following records shall be kept on site in a log for a period of not less than five (5) years, and shall be made available upon request:

   a. Receipts of all perchloroethylene purchases.

   b. The volume of perchloroethylene purchased each month as recorded from perchloroethylene purchase receipts. If no perchloroethylene is purchased during a given month, then the records shall state zero gallons.

   c. The calculation and result of the yearly perchloroethylene consumption (12-month rolling summation) determined on the first day of each month.

   d. The dates of all biweekly visual inspections and monthly vapor leak inspections conducted with the use of a halogenated hydrocarbon detector or PCE gas analyzer, and the name or location of dry cleaning system components where leaks are detected.

   e. The dates of repair and records of written or verbal orders for repair parts.

4. The following records shall be kept for a period of not less than three years:

   a. control equipment maintenance; and

   b. the amount of fabric dry cleaned with perchloroethylene, from January 1 to December 31 of each year, in pounds.

5. A copy of the design specifications and the operating manuals for each dry-cleaning system and each emission control device located at the dry cleaning facility shall be retained on site and shall be made available upon request.

D. **Reporting Requirements**

1. The permittee shall notify the Toledo Division of Environmental Services in writing of any record from Section C.3 showing that the perchloroethylene usage limitation of 139 gallons per rolling, 12-month period specified in Section A.1 was exceeded. The notification shall include a copy of such record and shall be sent to the Toledo Division of Environmental Services within 45 days after the exceedance occurs.

E. **Testing Requirements**

1. Compliance with the mass emission limit listed in Section A.1 of 0.94 tons of perchloroethylene per rolling, 12-month period is demonstrated by multiplying the rolling, 12-month consumption of perchloroethylene in gallons (required in Section C.3.c) by 0.66 (the percentage of perchloroethylene assumed to be emitted to the atmosphere including vent and fugitive emissions) and by 0.00675 ton/gallon (the specific density of perchloroethylene).

2. Compliance with the annual perchloroethylene consumption limitation shall be determined using the records maintained in accordance with Section C.3.

F. **Miscellaneous Requirements**

1. If the total yearly consumption of perchloroethylene exceeds 140 gallons per year, this dry cleaning facility must comply with 40 CFR 63.322, 63.323, and 63.324 by 180 calendar days from the date that the facility determines it has exceeded the amounts specified.

2. The yearly perchloroethylene solvent consumption limit based on the yearly solvent consumption calculated according to 40 CFR 63.323(d) is 139 gallons.