



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL MODIFICATION
MUSKINGUM COUNTY**

CERTIFIED MAIL

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:
Lazarus Gov. Center
P.O. Box 1049

Application No: 06-07250

Fac ID: 0660010023

DATE: 8/1/2006

Mar-Zane Plant No 3
Anthony Ruggiero III
PO Box 1585
Zanesville, OH 43701

Enclosed Please find a modification to the Ohio EPA Permit To Install referenced above which will modify the terms and conditions.

You are hereby notified that this action of the Director is final and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. The appeal must be filed with the Commission within thirty (30) days after notice of the Director's action. The appeal must be accompanied by a filing fee of \$70.00 which the Commission, in its discretion, may reduce if by affidavit you demonstrate that payment of the full amount of the fee would cause extreme hardship. Notice of the filing of the appeal shall be filed with the Director within three (3) days of filing with the Commission. Ohio EPA requests that a copy of the appeal be served upon the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, OH 43215

Sincerely,

Michael W. Ahern

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: USEPA

SEDO



Permit To Install
Terms and Conditions

Issue Date: 8/1/2006
Effective Date: 8/1/2006

FINAL ADMINISTRATIVE MODIFICATION OF PERMIT TO INSTALL 06-07250

Application Number: 06-07250
Facility ID: 0660010023
Permit Fee: **\$625**
Name of Facility: Mar-Zane Plant No 3
Person to Contact: Anthony Ruggiero III
Address: PO Box 1585
Zanesville, OH 43701

Location of proposed air contaminant source(s) [emissions unit(s)]:
7574 State Route 36
Gnadenhutten, Ohio

Description of proposed emissions unit(s):
Administrative modification of PTI 06-07250, issued November 13, 2003, to correct allowable emissions based on source specific test data.

The above named entity is hereby granted a modification to the permit to install described above pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this modification does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described source(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans included in the application, the above described source(s) of pollutants will be granted the necessary operating permits.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Mar-Zane Plant No 3
PTI Application: 06-07250
Modification Issued: 8/1/2006

Facility ID: 066001002

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon

Mar-Zane Plant No 3
PTI Application: 06-07250
Modification Issued: 8/1/2006

Facility ID: 066001002

the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

Mar-Zane Plant No 3
PTI Application: 06-07250
Modification Issued: 8/1/2006

Facility ID: 066001002

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

Mar-Zane Plant No 3
 PTI Application: 06-07250
 Modification Issued: 8/1/2006

Facility ID: 066001002

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)
 TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
VOC	18.8
CO	16.3
SO ₂	9.6
NO _x	9.03
PE(stack)	4.1

Mar-Zane Plant No 3
PTI Application: 06-07250
Modification Issued: 8/1/2006

Facility ID: 066001002

PE(fugitive)

10.6

Mar-Z

PTI A

Modification Issued: 8/1/2006

Emissions Unit ID: F001

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>
F001 - Plant paved roadways and parking areas (Portable with Mar-Zane Plant 3)	OAC rule 3745-31-05(A)(3)
	OAC rule 3745-17-07 (B)(5)
	OAC rule 3745-17-07 (B)(4)
	OAC rule 3745-17-08 (B), (B)(2)
	OAC rule 3745-17-08 (B), (B)(8), (B)(9)
Plant unpaved roadways and parking areas	OAC rule 3745-31-05(A)(3)

Mar-Z

PTI A

Modification Issued: 8/1/2006

Emissions Unit ID: **F001**

Applicable Emissions
Limitations/Control Measures

Particulate emissions (PE) shall not exceed 0.7 ton per year (TPY).

No visible PE except for one minute during any 60-minute period

Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see Sections A.2.a, A.2.c, and A.2.e through A.2.i)

The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

PE shall not exceed 6.5 TPY.

No visible PE except for three minutes during any 60-minute period

Best available control measures that are sufficient to minimize or eliminate visible

emissions of fugitive dust (see Sections A.2.b and A.2.d through A.2.i)

The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** The paved roadways and parking areas that are covered by this permit and subject to the above-mentioned requirements are listed below:

paved roadways:

all

paved parking areas:

all

- 2.b** The unpaved roadways and parking areas that are covered by this permit and subject to the above-mentioned requirements are listed below:

unpaved roadways:

all

unpaved parking areas:

all

- 2.c** The permittee shall employ best available control measures on all paved roadways and parking areas for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to the following methods to ensure compliance: the application of water at sufficient treatment frequencies to control fugitive dust; and a vehicle speed reduction to 5 mph on paved surfaces. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

- 2.d** The permittee shall employ best available control measures on all unpaved roadways and parking areas for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to the following methods to ensure compliance: the application of water and/or emulsified asphalt at sufficient treatment frequencies to control fugitive dust; and a vehicle speed reduction to 5 mph on unpaved surfaces. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

- 2.e** The needed frequencies of implementation of the control measures shall be

Emissions Unit ID: F001

determined by the permittee's inspections pursuant to the monitoring section of this permit. Implementation of the control measures shall not be necessary for a paved or unpaved roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Implementation of any control measure may be suspended if unsafe or hazardous driving conditions would be created by its use.

- 2.f** Any unpaved roadway or parking area, which during the term of this permit is paved or takes the characteristics of a paved surface due to the application of certain types of dust suppressants, may be controlled with the control measure(s) specified above for paved surfaces. Any unpaved roadway or parking area that takes the characteristics of a paved roadway or parking area due to the application of certain types of dust suppressants shall remain subject to the visible emission limitation for unpaved roadways and parking areas. Any unpaved roadway or parking area that is paved shall be subject to the visible emission limitation for paved roadways and parking areas.
- 2.g** The permittee shall promptly remove, in such a manner as to minimize or prevent resuspension, earth and/or other material from paved streets onto which such material has been deposited by trucking or earth moving equipment or erosion by water or other means.
- 2.h** Open-bodied vehicles transporting materials likely to become airborne shall have such materials covered at all times if the control measure is necessary for the materials being transported.
- 2.i** Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the best available technology requirements of OAC rule 3745-31-05.

Mar-Z**PTI A****Modification Issued: 8/1/2006**Emissions Unit ID: **F001****B. Operational Restrictions**

None

C. Monitoring and/or Recordkeeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform inspections of the roadways and parking areas in accordance with the following frequencies:

<u>paved roadways and parking areas</u>	<u>minimum inspection frequency</u>
all	daily

<u>unpaved roadways and parking areas</u>	<u>minimum inspection frequency</u>
all	daily

2. The purpose of the inspections is to determine the need for implementing the above-mentioned control measures. The inspections shall be performed during representative, normal traffic conditions. No inspection shall be necessary for a roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above-identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.
3. The permittee shall maintain records of the following information:
 - a. The date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;
 - b. The date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;
 - c. The dates the control measures were implemented; and
 - d. On a calendar quarter basis, the total number of days the control measures were implemented and the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measures.

The information required in 3.d. shall be kept separately for (i) the paved roadways and

Mar-Z

PTI A

Modification Issued: 8/1/2006

Emissions Unit ID: **F001**

parking areas and (ii) the unpaved roadways and parking areas, and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

Mar-Z**PTI A****Modification Issued: 8/1/2006**Emissions Unit ID: **F001****D. Reporting Requirements**

1. The permittee shall submit deviation reports that identify any of the following occurrences:
 - a. Each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and
 - b. Each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.

These reports shall be submitted in accordance with Section A.2 of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the emissions limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emission Limitation:
Particulate emissions shall not exceed 0.7 TPY from paved roadways and parking areas.

Applicable Compliance Method:

Compliance shall be determined based on the emissions factor calculation for unpaved roadways and parking areas in AP-42 section 13.2.1 (10/02). Initial compliance has been determined using inputs representing current conditions as follows:

$$E = [k(sL/2)^{0.65}(W/3)^{1.5} (1 - (P/4N))]$$

where:

E = size-specific emission factor (lb/VMT)

k = particle size multiplier (dimensionless) = 0.082

sL = road surface silt loading (g/m²) = 0.4

W = mean vehicle weight (tons) = 25

P = number of rain days per year >0.01 in = 130

N = number of days in the averaging period = 365

Therefore, $E = 0.63 \text{ lb PE/VMT}$

Maximum travel = 11,600 VMT/year

$(11,600 \text{ VMT/yr})(0.63 \text{ lbs/VMT})(1 \text{ ton}/2000 \text{ lbs}) = 3.7 \text{ TPY uncontrolled PE}$

Assume 80% control for roadway watering (RACM, Table 2.1.1-3)
 $(3.7 \text{ TPY})(.20) = 0.7 \text{ TPY controlled PE}$

- b. Emission Limitation:
 No visible PE except for one minute during any 60-minute period from paved roadways and parking areas.

Applicable Compliance Method:

If required, compliance shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources," as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(d) of OAC rule 3745-17-03.

- c. Emission Limitation:
 Particulate emissions shall not exceed 6.5 TPY from unpaved roadways and parking areas.

Applicable Compliance Method:

Compliance shall be determined based on the emissions factor calculation for unpaved roadways and parking areas in AP-42 section 13.2.2 (Draft, 2001). Initial compliance has been determined using inputs representing current conditions as follows:

$$E = [k(s/12)^a(W/3)^b][(365-p)/365]$$

Where:

E = size-specific emission factor (lb/VMT)
 s = silt content of road surface material (%) = 10 %
 W = mean vehicle weight (tons) = 25
 a = constant (dimensionless) = 0.7
 b = constant (dimensionless) = 0.45
 k = particle size multiplier (dimensionless) = 4.9

Mar-Z**PTI A****Modification Issued: 8/1/2006**Emissions Unit ID: **F001**

$p = \text{number of rain days per year } >0.01 \text{ in} = 130$

Therefore, $E = 7.21 \text{ lbs particulate/VMT}$

Maximum travel = 18,000 VMT/year

$(18,000 \text{ VMT/yr})(7.21 \text{ lbs/VMT})(1 \text{ ton}/2000 \text{ lbs}) = 64.9 \text{ TPY uncontrolled PE}$

Assume 90% control for roadway watering and emulsified asphalt application (RACM, Table 2.1.1-3)

$(64.9 \text{ tons/year})(.10) = 6.5 \text{ TPY controlled PE}$

- d. Emission Limitation:
No visible PE except for three minutes during any 60-minute period from unpaved roadways and parking areas.

Applicable Compliance Method:

If required, compliance shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources," as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(d) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

1. Pursuant to Ohio Administrative Code (OAC) rule 3745-31-03(A)(1)(p)(i), the permittee of a portable or mobile emissions unit may relocate within the State of Ohio without first obtaining a PTI providing the following criteria are met:
 - a. The portable emissions unit is equipped with the best available control technology for such portable emissions unit;
 - b. The portable emissions unit is operating pursuant to a currently effective permit to install, permit to operate or registration;
 - c. The applicant has provided proper notice of intent to relocate the portable emissions unit to the Southeast District Office (SEDO) and the appropriate field office having jurisdiction over the new site within a minimum of thirty days prior to the scheduled relocation; and

- d. In the SEDO's and the appropriate field office's judgement, the proposed site is acceptable under the rule 3745-15-07 of the Administrative Code.
2. In the alternative, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), the permittee of a portable or mobile emissions unit may relocate within the State of Ohio without first obtaining a PTI providing the following criteria of OAC rule 3745-31-05(F) are met:
 - a. The portable emissions unit permittee possesses an Ohio EPA PTI, PTO or registration status;
 - b. The portable emissions unit is equipped with best available technology;
 - c. The portable emission unit owner has identified the proposed site to Ohio EPA;
 - d. Ohio EPA has determined that the portable emissions unit, at the proposed site, will have an acceptable environmental impact;
 - e. A public notice, consistent with Chapter 3745-47 of the Administrative Code, is published in the county where the proposed site is located;
 - f. The owner of the proposed site has provided the portable emissions unit owner with approval or equivalent declaration that it is acceptable to the site owner to move the portable emissions unit to the proposed site; and
 - g. The portable emissions unit owner has provided the Ohio EPA with fifteen days written notice of the relocation.

Any site approvals issued by the Ohio EPA, pursuant to this section, shall be valid for no longer than three years and are subject to renewal.

3. In order for the SEDO and the appropriate field office having jurisdiction over the new site to determine compliance with all of the above criteria, the owner or operator of the portable or mobile emissions unit must file a "Notice of Intent to Relocate", within the specified time frame (30 or 15 days) prior to the relocation of the emissions unit with the SEDO (2195 Front Street, Logan, Ohio 43138) and the appropriate office having jurisdiction over the new site. Upon receipt of the notice, the SEDO and/or the appropriate field office having jurisdiction over the new site, will evaluate the request in accordance with the above criteria.
4. The permittee should be advised that when portable emission units are located at a stationary source or at a source comprised of portable emission units, potential

Mar-Z

PTI A

Modification Issued: 8/1/2006

Emissions Unit ID: **F001**

emissions from the portable emission units are included in the facility potential to emit calculations for Title V and PSD applicability.

The permittee shall include a potential to emit analysis of facility-wide emissions (including the portable sources) for the proposed relocation in the "Notice of Intent to Relocate".

Mar-Z

PTI A

Modification Issued: 8/1/2006

Emissions Unit ID: **F002**

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
F002 - Plant load-in and load-out of storage piles (Portable with Mar-Zane Plant 3)	OAC rule 3745-31-05 (A)(3)	OAC rule 3745-31-05 (A)(3)
	OAC rule 3745-17-07 (B)(6)	OAC rule 3745-17-07 (B)(6)
	OAC rule 3745-17-08 (B)	OAC rule 3745-17-08 (B)
wind erosion from storage piles		

Mar-Z

PTI A

Modification Issued: 8/1/2006

Emissions Unit ID: **F002**

Applicable Emissions
Limitations/Control Measures

Particulate emissions (PE) shall not exceed 0.2 ton per year (TPY).

No visible PE except for one minute during any 60-minute period.

Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see Section A.2.b, A.2.c and A.2.f).

The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

Particulate emissions (PE) shall not exceed 2.6 TPY.

No visible PE except for one minute during any 60-minute period.

Best available control measures that are sufficient to

minimize or eliminate visible emissions of fugitive dust (see Sections A.2.d through A.2.f).

The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a The storage piles that are covered by this permit and subject to the above-mentioned requirements are listed below:

storage pile identification
all

- 2.b The permittee shall employ best available control measures on all load-in and load-out operations associated with the storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to minimizing the drop height of the front end loader bucket to the extent possible, in order to minimize or eliminate visible emissions of fugitive dust from the loading area. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.
- 2.c The above-mentioned control measure(s) shall be employed for each load-in and load-out operation of each storage pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) are necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measure(s) shall continue during any such operation until further observation confirms that use of the measure(s) is unnecessary.
- 2.d The permittee shall employ best available control measures for wind erosion from the surfaces of all storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to maintenance of low storage pile heights to minimize or eliminate visible emissions of fugitive dust from storage pile wind erosion. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.
- 2.e The above-mentioned control measure(s) shall be employed for wind erosion from each pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) are necessary to ensure compliance with the above-mentioned applicable requirements. Implementation of the control measure(s) shall not be necessary for a storage pile that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements.

2.f Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the requirements of OAC rules 3745-17-08 and 3745-31-05.

B. Operational Restrictions

None.

C. Monitoring and/or Recordkeeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform inspections of each load-in operation at each storage pile in accordance with the following frequencies:

<u>storage pile identification</u>	<u>minimum load-in inspection frequency</u>
all	daily

2. Except as otherwise provided in this section, the permittee shall perform inspections of each load-out operation at each storage pile in accordance with the following frequencies:

<u>storage pile identification</u>	<u>minimum load-out inspection frequency</u>
all	daily

3. Except as otherwise provided in this section, the permittee shall perform inspections of the wind erosion from pile surfaces associated with each storage pile in accordance with the following frequencies:

<u>storage pile identification</u>	<u>minimum wind erosion inspection frequency</u>
all	daily

Emissions Unit ID: F002

4. No inspection shall be necessary for wind erosion from the surface of a storage pile when the pile is covered with snow and/or ice and for any storage pile activity if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements.

Any required inspection that is not performed due to any of the above identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.

5. The purpose of the inspections is to determine the need for implementing BAT control measures for load-in and load-out of a storage pile, and wind erosion from the surface of a storage pile. The inspections shall be performed during representative, normal storage pile operating conditions.
6. The permittee shall maintain records of the following information:
 - a. The date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;
 - b. The date of each inspection where it was determined by the permittee that it was necessary to implement control measures;
 - c. The dates the control measures were implemented; and
 - d. On a calendar quarter basis, the total number of days control measures were implemented and, for wind erosion from pile surfaces, the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measure(s).

The information required in 6.d. shall be kept separately for (i) the load-in operations, (ii) the load-out operations, and (iii) the pile surfaces (wind erosion), and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation reports that identify any of the following occurrences:
 - a. Each day during which an inspection was not performed by the required

Mar-Z**PTI A****Modification Issued: 8/1/2006**Emissions Unit ID: **F002**

frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and

- b. Each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.

These reports shall be submitted in accordance with Section A.2 of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the emissions limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emission Limitation:
Particulate emissions shall not exceed 0.2 TPY from plant load-in and load-out of storage piles.

Applicable Compliance Method:

Compliance shall be determined based on the emission factor calculation for drop operations associated with storage piles in AP-42 section 13.2.4 (01/95). Initial compliance has been determined using inputs representing current conditions as follows:

$$E = k (0.0032)[(U/5)^{1.3}/(M/2)^{1.4}]$$

Where:

E = emission factor expressed in pounds (lbs) / ton

k = particle size multiplier for TSP (dimensionless) = 0.74

U = mean wind speed expressed in miles per hour (MPH) = 9

M = material moisture content (%) = 7

Therefore, $E = 8.8 \times 10^{-4}$ lb PE/ton

maximum annual load-in throughput = 250,000 tons/year

maximum annual load-out throughput= 250,000 tons/year

$$[(250,000 \text{ tons/yr})(8.8 \times 10^{-4} \text{ lb PE/ton}) + (250,000 \text{ tons/yr})(8.8 \times 10^{-4} \text{ lb PE/ton})]/2000 \text{ lb/ton}$$

Mar-Z**PTI A****Modification Issued: 8/1/2006**Emissions Unit ID: **F002**

= 0.2 TPY

- b. Emission Limitation:
Particulate emissions shall not exceed 2.6 TPY from wind erosion of storage piles.

Applicable Compliance Method:

Compliance shall be determined based on the emission factor calculation for wind erosion from storage piles in BACM, Equation 2-12 (September, 1992). Initial compliance has been determined using inputs representing current conditions as follows:

$$E = 1.7(s/1.5)((365-p)/235)(f/15)$$

Where:

E = emission factor expressed in pounds (lbs) /day/acre

s = silt content of road surface material (%) = 9 %

p = number of rain days per year > 0.01 in = 130

f = percentage of time wind speed exceeds 12 mph (%) = 10

A = total surface area of storage piles (acres) = 3

Therefore, E = 6.8 lbs/day/acre

$$(6.8 \text{ lbs/day/acre})(365 \text{ days/yr})(3 \text{ acres})/2000 \text{ lbs/ton} = 3.7 \text{ TPY uncontrolled PE}$$

Assume 30% control for precautionary operating practices (RACM, Table 2.1.1-8)

$$(3.7 \text{ tons/year})(.70) = 2.6 \text{ TPY controlled PE}$$

- c. Emission Limitation:
No visible particulate emissions except for one minute during any 60-minute period.

Applicable Compliance Method:

If required, compliance shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

1. Pursuant to Ohio Administrative Code (OAC) rule 3745-31-03(A)(1)(p)(i), the permittee of a portable or mobile emissions unit may relocate within the State of Ohio without first obtaining a PTI providing the following criteria are met:
 - a. The portable emissions unit is equipped with the best available control technology for such portable emissions unit;
 - b. The portable emissions unit is operating pursuant to a currently effective permit to install, permit to operate or registration;
 - c. The applicant has provided proper notice of intent to relocate the portable emissions unit to the Southeast District Office (SEDO) and the appropriate field office having jurisdiction over the new site within a minimum of thirty days prior to the scheduled relocation; and
 - d. In the SEDO's and the appropriate field office's judgement, the proposed site is acceptable under the rule 3745-15-07 of the Administrative Code.

2. In the alternative, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), the permittee of a portable or mobile emissions unit may relocate within the State of Ohio without first obtaining a PTI providing the following criteria of OAC rule 3745-31-05(F) are met:
 - a. The portable emissions unit permittee possesses an Ohio EPA PTI, PTO or registration status;
 - b. The portable emissions unit is equipped with best available technology;
 - c. The portable emission unit owner has identified the proposed site to Ohio EPA;
 - d. Ohio EPA has determined that the portable emissions unit, at the proposed site, will have an acceptable environmental impact;
 - e. A public notice, consistent with Chapter 3745-47 of the Administrative Code, is published in the county where the proposed site is located;
 - f. The owner of the proposed site has provided the portable emissions unit owner with approval or equivalent declaration that it is acceptable to the site owner to move the portable emissions unit to the proposed site; and

Mar-Z**PTI A****Modification Issued: 8/1/2006**Emissions Unit ID: **F002**

- g. The portable emissions unit owner has provided the Ohio EPA with fifteen days written notice of the relocation.

Any site approvals issued by the Ohio EPA, pursuant to this section, shall be valid for no longer than three years and are subject to renewal.

3. In order for the SEDO and the appropriate field office having jurisdiction over the new site to determine compliance with all of the above criteria, the owner or operator of the portable or mobile emissions unit must file a "Notice of Intent to Relocate", within the specified time frame (30 or 15 days) prior to the relocation of the emissions unit with the SEDO (2195 Front Street, Logan, Ohio 43138) and the appropriate office having jurisdiction over the new site. Upon receipt of the notice, the SEDO and/or the appropriate field office having jurisdiction over the new site, will evaluate the request in accordance with the above criteria.
4. The permittee should be advised that when portable emission units are located at a stationary source or at a source comprised of portable emission units, potential emissions from the portable emission units are included in the facility potential to emit calculations for Title V and PSD applicability.

The permittee shall include a potential to emit analysis of facility-wide emissions (including the portable sources) for the proposed relocation in the "Notice of Intent to Relocate".

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, <u>and/or Equipment</u>	aggregate storage bins, cold aggregate elevator
P901 - 180 TPH portable parallel flow drum mix asphalt plant	
Administrative modification of PTI 06-07250, issued on 11/26/2003, to change emission factors.	

Mar-Z**PTI A****Modification Issued: 8/1/2006**Emissions Unit ID: **P901**Applicable Rules/RequirementsApplicable Emissions
Limitations/Control Measures

OAC rule 3745-31-05(A)(3)

Emissions shall not exceed:

OAC rule 3745-23-06(B)

13.9pounds per hour (lbs/hr)
sulfur dioxide (SO₂);

OAC rule 3745-17-07(A)

13.0 lbs/hr nitrogen oxides (NO_x);27.0 lbs/hr volatile organic
compounds (VOC); and

OAC rule 3745-17-11(B)

23.4 lbs/hr carbon monoxide
(CO).See Section A.2.a for emission
control measures.

OAC rule 3745-18-06(E)

The requirements of this rule also
include compliance with the
requirements of 40 CFR Part 60
Subpart I, OAC rule
3745-23-06(B) and OAC rule
3745-35-07(B).

OAC rule 3745-35-07(B)

OAC rule 3745-31-05(A)(3)

Emissions shall not exceed, as a
12 month rolling summation:4.1 tons particulate emissions
(PE) from the stack
0.6 ton fugitive PE
16.3 tons CO
9.6 tons SO₂
9.03 tons NO_x
18.8 tons VOCPE from the stack shall not
exceed 0.04 grain/dscf.

40 CFR Part 60, Subpart I

Mar-Z**PTI A****Modification Issued: 8/1/2006**Emissions Unit ID: **P901**

The emissions unit shall not discharge into the atmosphere any stack gases which exhibit 20 percent opacity or greater.

See Section A.2.b.

The emissions limitation specified by this rule is less stringent than the emission limitation established pursuant to 40 CFR Part 60 Subpart I.

The emissions limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

The emissions limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

Visible emissions of fugitive dust shall be less than or equal to 10% opacity, as a 3-minute average.

Fugitive PE shall not exceed 0.9 lbs/hr.

The drop height of the front end loader bucket shall be minimized to the extent possible in order to minimize or eliminate visible emissions of fugitive dust from the elevator

loading area.

The aggregate loaded into the storage bins shall have a moisture content sufficient to eliminate the visible emissions of fugitive dust from the elevator and the transfer point to the dryer.

Mar-Z**PTI A****Modification Issued: 8/1/2006**Emissions Unit ID: **P901****2. Additional Terms and Conditions**

- 2.a** The fabric filter shall be used at all times when the emissions unit is in operation.
- 2.b** The permittee has satisfied the "latest available control techniques and operating practices" required pursuant to OAC rule 3745-23-06, by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05(A)(3).
- 2.c** The application and enforcement of the provisions of the New Source Performance Standards (NSPS), as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60, are delegated to the Ohio Environmental Protection Agency. The requirements of 40 CFR Part 60 are also federally enforceable.

B. Operational Restrictions

1. To ensure the baghouse is operated according to the manufacturer's specifications and to maintain compliance with the allowable particulate emission rate, the pressure drop across the baghouse shall be maintained within the range of 2.0 to 8.0 inches of water while the emissions unit is in operation.
2. The maximum asphalt production rate for emissions unit P901 shall not exceed 250,000 tons as a rolling 12-month summation of the production rates. To ensure enforceability during the first 12 calendar months of operation following the startup of the modified emissions unit P901, the permittee shall not exceed the production levels specified in the following table:

<u>Month(s)</u>	<u>Maximum Allowable Cumulative Production (Tons)</u>
1	134,000
1-2	250,000
1-3	250,000
1-4	250,000
1-5	250,000
1-6	250,000
1-7	250,000
1-8	250,000
1-9	250,000

Mar-Zane Plant No 3
PTI Application: 06 07250
Modif

Facility ID: 066001002

Emissions Unit ID: P901

1-10	250,000
1-11	250,000
1-12	250,000

After the first 12 calendar months of operation following the startup of the modified emissions unit P901, compliance with the production rate limitation shall be based upon a rolling 12-month summation of the production rates.

3. All recycled, used oil burned in emissions unit P901 shall meet the following specifications:

<u>Contaminant/Property</u>	<u>Allowable Specifications</u>
arsenic	5 ppm, maximum
cadmium	2 ppm, maximum
chromium	10 ppm, maximum
lead	100 ppm, maximum
PCB's	50 ppm, maximum*
total halogens	4000 ppm maximum**
mercury	1 ppm, maximum
flash point	100°F, minimum
heat content	135,000 Btu/gallon, minimum

* If the permittee is burning used oil with any quantifiable level ≥ 2 ppm < 50 ppm of PCB's, then the permittee is subject to any applicable requirements found under 40 CFR part 279, subparts G and H and 40 CFR 761.20 (e).

** Used oil containing more than 1000 ppm total halogens is presumed to be a hazardous waste under the rebuttable presumption provided under 40 CFR 279.10 (b)(1)(ii) and OAC rule 3745-279-10 (B)(1)(b). Therefore, the permittee may receive and burn used oil exceeding 1000 ppm of total halogens (but less than 4000 ppm, maximum) only if the used oil burner can demonstrate the used oil does not contain any hazardous waste pursuant to OAC rule 3745-279-63.

4. The burning of hazardous waste is prohibited without first complying with all applicable state and federal hazardous waste and air regulations and permits.
5. Each fuel burned in emissions unit P901 shall have a sulfur content equal to or less than the following:

<u>Type of fuel</u>	<u>Allowable Sulfur Content (by weight)</u>
natural gas	0.5 %

33

Mar-Z

PTI A

Modification Issued: 8/1/2006

Emissions Unit ID: **P901**

No. 2

0.5 %

Mar-Z**PTI A****Modification Issued: 8/1/2006**Emissions Unit ID: **P901**

No. 4	0.8 %
No. 6	1.0 %
used oil	0.5 %

6. The permittee may substitute recycled asphalt pavement (RAP) aggregates in the raw material feed mix in amounts not to exceed 50% of all aggregate materials introduced, based on a monthly average of all aggregate material.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a once per day basis.
2. The permittee shall maintain monthly records of the following information for emissions unit P901:
 - a. The asphalt production, in tons.
 - b. For the first 12 calendar months following the startup of the modified emissions unit P901, the cumulative asphalt production calculated by adding the current month's asphalt production to the asphalt production for each calendar month since the startup of the modified emissions unit P901.
 - c. Beginning after the first 12 calendar months following the startup of the modified emissions unit P901, the rolling 12-month summation of asphalt production calculated by adding the current month's asphalt production to the asphalt production for the preceding eleven calendar months.
 - d. The total amount of aggregate used in the raw material feed mix.
 - e. The amount of RAP used in the raw material feed mix.
 - f. The average percentage of RAP used (e. divided by d. multiplied by 100).
3. For each shipment of oil received for burning in this emissions unit, the permittee shall maintain records of the total quantity of oil received and the permittee's or oil supplier's

Mar-Z**PTI A****Modification Issued: 8/1/2006**Emissions Unit ID: **P901**

analyses for the following:

- a. The date(s) of shipment or delivery.
- b. The quantity of oil received.
- c. The heat content, in BTU/gallon.
- d. The flash point, in degrees F (required only for used oil).
- e. The arsenic content, in ppm (required only for used oil).
- f. The cadmium content, in ppm (required only for used oil).
- g. The chromium content, in ppm (required only for used oil).
- h. The lead content, in ppm (required only for used oil).
- i. The PCB content, in ppm (required only for used oil).
- j. The total halogen content, in ppm (required only for used oil).
- k. The mercury content, in ppm (required only for used oil).
- l. The sulfur content, in percent (%) by weight.

A shipment may be comprised of multiple tank truck loads from the same supplier's batch, or may be represented by single or multiple pipeline deliveries from the same supplier's batch, and the quality of the oil for those loads or pipeline deliveries may be represented by a single batch analysis from the supplier.

The permittee shall perform or require the supplier to perform the analyses for sulfur content and heat content in accordance with 40 CFR Part 60, Appendix A, Method 19, or the appropriate ASTM methods (such as, ASTM methods D240 and D4294), or equivalent methods as approved by the Director.

The permittee shall maintain records of the oil burned in this emissions unit in accordance with either Alternative 1 or Alternative 2 described below.

- a. Alternative 1:

For each shipment of oil received for burning in this emissions unit, the permittee shall collect or require the oil supplier to collect a representative grab sample of oil and maintain records of the permittee's or oil supplier's analyses for items a - l above. A shipment may be comprised of multiple tank truck loads from the same supplier's batch, and the quality of the oil for those loads may be represented by a single batch analysis from the supplier.

- b. Alternative 2:

The permittee shall collect a representative grab sample of oil that is burned in this

Mar-Zane Plant No 3
PTI Application: 06 07250
Modif

Facility ID: 066001002

Emissions Unit ID: P901

emissions unit for each day when the emissions unit is in operation. If additional fuel oil is added to the tank serving this emissions unit on a day when the emissions unit is in operation, the permittee shall collect a sufficient number of grab samples to develop a composite sample representative of the oil burned in this emissions unit. A representative grab sample of oil does not need to be collected on days when this emissions unit is only operated for the purpose of "test-firing." The permittee shall maintain records of the total quantity of oil burned each day, except for the purpose of test-firing, and the permittee's analyses for items a - l above.

4. The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible PE from the stack and any visible fugitive PE from the aggregate storage bins and cold aggregate elevator associated with this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. The color of the emissions;
 - b. Whether the emissions are representative of normal operations;
 - c. If the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. The total duration of any visible emission incident; and
 - e. Any corrective actions taken to eliminate the visible emissions.

5. The permit to install for this emissions unit (P901) was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Heptane

TLV (mg/m3): 1639.26

Maximum Hourly Emission Rate (lbs/hr): 1.692

Predicted 1-Hour Maximum Ground-Level
Concentration (ug/m3): 563

Mar-Zane Plant No 3
PTI Application: 06 07250
Modif

Facility ID: 066001002

Emissions Unit ID: P901

MAGLC (ug/m3): 39030

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. Changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. Physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. A description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. Documentation of its evaluation and determination that the changed emissions

Mar-Zane Plant No 3
PTI Application: 06 07250
Modif

Facility ID: 066001002

Emissions Unit ID: P901

unit still satisfies the "Air Toxic Policy"; and

- c. Where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify the following:
 - a. All periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified in Section B.1.
 - b. All exceedances of the rolling 12-month asphalt production limitation and, for the first 12 calendar months of operation following the issuance of this permit, all exceedances of the maximum allowable cumulative production levels.
 - c. All exceedances of sulfur content fuel restrictions specified in Section B.5.

These reports shall due by the dates specified in Part I - General Terms and Conditions of this permit under Section A.2.

Mar-Z**PTI A****Modification Issued: 8/1/2006**Emissions Unit ID: **P901**

2. The permittee shall notify the USEPA and the Ohio EPA if any of the used oil exceeds the used oil specifications found in OAC rule 3745-279-11 and the applicable portions of 40 CFR part 761, and shall also notify Ohio EPA if any used oil exceeds the mercury limitation and falls below the heat content limitation listed in Section B.3 within thirty days after the exceedance occurs. If the permittee is burning used oil which exceeds the specifications found in OAC rule 3745-279-11 and the applicable portions 40 CFR part 761, the permittee is subject to that rule and must comply with all applicable provisions of that rule(s).
3. The permittee shall submit deviation (excursion) reports which identify any exceedance of the 50 percent RAP content limitation specified in Section B.6. The notification shall be sent to the Ohio EPA, Southeast District Office within 30 days after the exceedance occurs.
4. The permittee shall submit semiannual written reports that include the following:
 - a. An identification of all days during which any visible PE or fugitive PE were observed from the stack and the aggregate storage bins and cold aggregate elevator associated with this emissions unit.
 - b. A description of any corrective actions taken to eliminate the visible particulate emissions.

These reports shall be submitted to the Ohio EPA, Southeast District Office by January 31 and July 31 of each year and shall cover the previous 6-month period.

5. Pursuant to the NSPS, the source owner/operator is hereby advised of the requirement to report the following at the appropriate times:
 - a. Construction date (no later than 30 days after such date);
 - b. Anticipated start-up date (not more than 60 days or less than 30 days prior to such date);
 - c. Actual start-up date (within 15 days after such date); and
 - d. Date of performance testing (if required, at least 30 days prior to testing).

Reports are to be sent to:

Mar-Zane Plant No 3
PTI Application: 06 07250
Modif

Facility ID: 066001002

Emissions Unit ID: P901

Ohio Environmental Protection Agency
 DAPC - Permit Management Unit
 P. O. Box 163669
 Columbus, Ohio 43216-3669

and

Southeast District Office of the Ohio EPA
 Division of Air Pollution Control
 2195 Front Street
 Logan, Ohio 43138

E. Testing Requirements

1. Compliance with the particulate emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation:
 PE from the stack shall not exceed 0.04 grain/dscf

Applicable Emission Limitation

Compliance shall be determined in accordance with Test Methods 1-5 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources").

- b. Emission Limitation:
 Emissions shall not exceed 4.1 tons PE from the stack as a rolling 12-month summation.

Applicable Compliance Method:

Compliance shall be determined based upon the following equation:

$$E = EF * AAPR * 0.0005 \text{ ton/lb} = \text{TPY of PE}$$

Where

EF is the PE emission factor in lb/ton, and is based on the most recent stack test as required in Section E. 7, and

AAPR is the actual asphalt production rate, in tons, for each 12-month period as monitored and recorded in Section C. 2. Note: The emissions factor used to

calculate the PE mass emission limitation (0.033 lb PE/ton asphalt produced) is from AP-42, Table 11.1-3 (12/00).

c. Emission Limitation:

The emissions unit shall not discharge into the atmosphere any stack gases which exhibit 20 percent opacity or greater.

Applicable Compliance Method:

If required, compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources").

d. Emission Limitation:

Visible emissions of fugitive dust shall be less than or equal to 10% opacity, as a 3-minute average.

Applicable Compliance Method:

If required, compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources").

e. Emissions Limitation:

Emissions shall not exceed 0.6 ton fugitive PE as a rolling 12-month summation.

Applicable Compliance Method:

Compliance with the annual emissions limitation shall be determined using the following worst case calculation, where total fugitive emissions equal the summation of the fugitives from the aggregate storage bins, cold aggregate elevator, and associated operations:

$$((137,500 \text{ tons of aggregate/year} \times 0.0069 \text{ lb PE/ton of aggregate}) + (112,500 \text{ tons of sand/year} \times 0.0021 \text{ lb PE/ton of sand})) \times (0.0005 \text{ ton/lb}) = 0.6 \text{ ton}$$

The emissions factors in the above equation are derived from AP-42, Table 11.12-2 (10/01).

f. Emission Limitation:

Fugitive PE shall not exceed 0.9 lb/hr.

Applicable Compliance Method:

Mar-Z**PTI A****Modification Issued: 8/1/2006**Emissions Unit ID: **P901**

Compliance with the hourly emissions limitation shall be determined using the following worst case calculation, where total fugitive emissions equal the summation of the fugitives from the aggregate storage bins, cold aggregate elevator, and associated operations:

$$((99 \text{ tons of aggregate/hour} \times 0.0069 \text{ lb PE/ton of aggregate}) + (81 \text{ tons of sand/hour} \times 0.0021 \text{ lb PE/ton of sand})) = 0.9 \text{ lb PE/hr}$$

The emissions factors in the above equation are derived from AP-42, Table 11.12-2 (10/01).

2. Compliance with the CO emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation:
Emissions shall not exceed 23.4 lbs/hr CO.

Mar-Zane Plant No 3
PTI Application: 06 07250
Modif

Facility ID: 066001002

Emissions Unit ID: P901

Applicable Compliance Method:

Compliance shall be determined in accordance with Test Methods 1-4 and 10 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"). Note: The CO mass emission limitation was calculated by multiplying the maximum rated capacity of P901 (180 TPH) by the AP-42 emission factor of 0.13 lb CO/ton asphalt produced (Table 11.1-7, 12/00).

- b. **Emission Limitation:**
 Emissions shall not exceed 16.3 tons CO as a rolling 12-month summation.

Applicable Compliance Method:

Compliance shall be determined based upon the following equation:

$$E = EF * AAPR * 0.0005 \text{ ton/lb} = \text{TPY of CO}$$

Where

EF is the CO emission factor in lb/ton, and is based on the most recent stack test as required in Section E. 7, and

AAPR is the actual asphalt production rate, in tons, for each 12-month period as monitored and recorded in Section C. 2.

3. Compliance with the SO₂ emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

- a. **Emission Limitation:**
 Emissions shall not exceed 13.9 lbs/hr SO₂.

Applicable Compliance Method:

Compliance shall be determined in accordance with Test Methods 1-4 and 6 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"). Note: The SO₂ mass emission limitation was calculated by multiplying the maximum rated capacity of P901 (180 TPH) by the emission factor (0.077 lbs SO₂/ton) calculated from stack test data gathered on July 26, 2005. The emission factor was calculated by dividing the tested emission rate of 11.0 lb SO₂/hr by the source operating rate at the time of the stack test (164 TPH).

Compliance shall be determined based upon the following equations:

Mar-Z**PTI A****Modification Issued: 8/1/2006**Emissions Unit ID: **P901**

$$\begin{aligned} \text{EF} &= \text{Emission Rate (lbs SO}_2\text{/hr)} / \text{Operating Capacity (TPH)} \\ &= 11.0 \text{ lbSO}_2\text{/hr} / 164 \text{ TPH} \\ &= 0.077 \text{ lbs SO}_2\text{/ton} \end{aligned}$$

$$\begin{aligned} \text{Allowable emission rate} &= \text{EF} * \text{Maximum rated capacity} \\ &= 0.077 \text{ lbs SO}_2\text{/ton} * 180 \text{ Tons/hour} \\ &= 13.9 \text{ lbs SO}_2\text{/hour} \end{aligned}$$

- b. Emission Limitation:
Emissions shall not exceed 9.6 tons SO₂ as a rolling 12-month summation.

Applicable Compliance Method:
Compliance shall be determined based upon the following equation:

$$E = \text{EF} * \text{AAPR} * 0.0005 \text{ ton/lb} = \text{TPY of SO}_2$$

Where

EF is the SO₂ emission factor in lb/ton, and is based on the most recent stack test as required in Section E. 7, and
AAPR is the actual asphalt production rate, in tons, for each 12-month period as monitored and recorded in Section C. 2.

4. Compliance with the NO_x emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation:
Emissions shall not exceed 13.0 lbs/hr NO_x.

Applicable Compliance Method:
Compliance shall be determined in accordance with Test Methods 1-4 and 7 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"). Note: The NO_x mass emission limitation was calculated by multiplying the maximum rated capacity of P901 (180 TPH) by the emission factor (0.0722 lbs NO_x/ton) calculated from stack test data gathered on July 26, 2005. The emission factor was calculated by multiplying the tested emission rate of 10.3 lb NO_x/hr by the source operating rate at the time of the stack test (164 TPH).

Mar-Z**PTI A****Modification Issued: 8/1/2006**Emissions Unit ID: **P901**

Compliance shall be determined based upon the following equation:

$$\begin{aligned} \text{EF} &= \text{Emission Rate (lbs NOx/hr)} / \text{Operating Capacity (TPH)} \\ &= 10.3 \text{ lb NOx/hr} / 164 \text{ TPH} \\ &= 0.0722 \text{ lbs NOx/ton} \end{aligned}$$

$$\begin{aligned} \text{Allowable emission rate} &= \text{EF} * \text{Maximum rated capacity} \\ &= 0.0722 \text{ lbs NOx/ton} * 180 \text{ Tons/hour} \\ &= 13.0 \text{ lbs SO}_2\text{/hour} \end{aligned}$$

Mar-Zane Plant No 3
PTI Application: 06 07250
Modif

Facility ID: 066001002

Emissions Unit ID: P901

- b. **Emission Limitation:**
 Emissions shall not exceed 9.03 tons NO_x as a 12-month rolling summation.

Applicable Compliance Method:
 Compliance shall be determined based upon the following equation:

$$E = EF * AAPR * 0.0005 \text{ ton/lb} = \text{TPY of NO}_x$$

Where

EF is the NO_x emission factor in lb/ton, and is based on the most recent stack test as required in Section E. 7, and
 AAPR is the actual asphalt production rate, in tons, for each 12-month period as monitored and recorded in Section C. 2.

5. Compliance with the VOC emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

- a. **Emission Limitation:**
 Emissions shall not exceed 27.0 lbs/hr VOC.

Applicable Compliance Method:
 Compliance shall be determined in accordance with Test Methods 1 - 4 and 25 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"). Note: The emissions factor used to calculate the VOC mass emission limitation is 0.15 lb VOC/ton asphalt produced. This emissions factor is based on best engineering judgement and was developed using emissions testing data from a similar source.

- b. **Emission Limitation:**
 Emissions shall not exceed 18.8 tons VOC as a rolling 12-month summation.

Applicable Compliance Method:
 Compliance shall be determined based upon the following equation:

$$E = EF * AAPR * 0.0005 \text{ ton/lb} = \text{TPY of VOC's}$$

Where

EF is the VOC emission factor in lb/ton, and is based on the most recent stack test as required in Section E. 7, and

Mar-Z**PTI A****Modification Issued: 8/1/2006**Emissions Unit ID: **P901**

AAPR is the actual asphalt production rate, in tons, for each 12-month period as monitored and recorded in Section C. 2.

6. Compliance with the Operational Restriction(s) in Section B. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Operational Limitation:
Pressure drop across the baghouse shall be maintained within the range of 2.0 to 8.0 inches of water while the emissions unit is in operation

Applicable Compliance Method:
Compliance shall be demonstrated by the record keeping requirements in Section C.1.
 - b. Operational Limitation:
The maximum asphalt production rate for emissions unit P901 shall not exceed 250,000 tons as a rolling 12-month summation of the production rates.

Applicable Compliance Method:
Compliance shall be demonstrated by the record keeping requirements in Section C.2.
 - c. Operational Limitation:
Used oil specifications as specified in Section B.3.

Applicable Compliance Method:
Compliance shall be demonstrated by the record keeping requirements in Section C.3.
 - d. Operational Limitation:
Fuel sulfur content restrictions as specified in Section B.5.

Applicable Compliance Method:
Compliance shall be demonstrated by the record keeping requirements in Section C.3.
 - e. Operational Limitation:
Use of recycled asphalt pavement (RAP) aggregates in the raw material feed mix in amounts not to exceed 50% of all aggregate materials introduced, based on a monthly average of all aggregate material.

Mar-Z

PTI A

Modification Issued: 8/1/2006

Emissions Unit ID: **P901**

Applicable Compliance Method:

Compliance shall be demonstrated by the record keeping requirements in Section C.2.

7. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. The emission testing shall be conducted within 60 days after startup of the modified emissions unit.

Mar-Z**PTI A****Modification Issued: 8/1/2006**Emissions Unit ID: **P901**

- b. The emission testing shall be conducted to demonstrate compliance with the allowable mass emission rate(s) for PE ,CO, NO_x, SO₂, and VOC.
- c. The following test method(s) shall be employed to demonstrate compliance with the allowable mass emission rate(s): Methods 1-5 for PE, Method 25 for VOC, Method 1-4 and 10 for CO, Method 1-4 and 6 for SO₂, and Method 1-4 and 7 for NO_x.
- d. The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity using worst case fuel and per cent of RAP listed in this permit, unless otherwise specified or approved by the Ohio EPA Southeast District Office.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA Southeast District Office. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA Southeast District Office's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA Southeast District Office shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA Southeast District Office within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA Southeast District Office.

F. Miscellaneous Requirements

1. Pursuant to Ohio Administrative Code (OAC) rule 3745-31-03(A)(1)(p)(i), the permittee of a portable or mobile emissions unit may relocate within the State of Ohio without first obtaining a PTI providing the following criteria are met:
 - a. The portable emissions unit is equipped with the best available control

Mar-Zane Plant No 3
PTI Application: 06 07250
Modif

Facility ID: 066001002

Emissions Unit ID: P901

- technology for such portable emissions unit;
- b. The portable emissions unit is operating pursuant to a currently effective permit to install, permit to operate or registration;
 - c. The applicant has provided proper notice of intent to relocate the portable emissions unit to the Southeast District Office (SEDO) and the appropriate field office having jurisdiction over the new site within a minimum of thirty days prior to the scheduled relocation; and
 - d. The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity using worst case fuel and per cent of RAP listed in air permit, unless otherwise specified or approved by the Ohio EPA Southeast District Office.
2. In the alternative, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), the permittee of a portable or mobile emissions unit may relocate within the State of Ohio without first obtaining a PTI providing the following criteria of OAC rule 3745-31-05(F) are met:
- a. The portable emissions unit permittee possesses an Ohio EPA PTI, PTO or registration status;
 - b. The portable emissions unit is equipped with best available technology;
 - c. The portable emission unit owner has identified the proposed site to Ohio EPA;
 - d. Ohio EPA has determined that the portable emissions unit, at the proposed site, will have an acceptable environmental impact;
 - e. A public notice, consistent with Chapter 3745-47 of the Administrative Code, is published in the county where the proposed site is located;
 - f. The owner of the proposed site has provided the portable emissions unit owner with approval or equivalent declaration that it is acceptable to the site owner to move the portable emissions unit to the proposed site; and
 - g. The portable emissions unit owner has provided the Ohio EPA with fifteen days written notice of the relocation.

Any site approvals issued by the Ohio EPA, pursuant to this section, shall be valid for

no longer than three years and are subject to renewal.

3. In order for the SEDO and the appropriate field office having jurisdiction over the new site to determine compliance with all of the above criteria, the owner or operator of the portable or mobile emissions unit must file a "Notice of Intent to Relocate", within the specified time frame (30 or 15 days) prior to the relocation of the emissions unit with the SEDO (2195 Front Street, Logan, Ohio 43138) and the appropriate office having jurisdiction over the new site. Upon receipt of the notice, the SEDO and/or the appropriate field office having jurisdiction over the new site, will evaluate the request in accordance with the above criteria.
4. The permittee should be advised that when portable emission units are located at a stationary source or at a source comprised of portable emission units, potential emissions from the portable emission units are included in the facility potential to emit calculations for Title V and PSD applicability.

The permittee shall include a potential to emit analysis of facility-wide emissions (including the portable sources) for the proposed relocation in the "Notice of Intent to Relocate".

52

Mar-Zane Plant No 3

PTI Application: 06 07250

Modif

Facility ID: 066001002

Emissions Unit ID: P901