☒ **Synthetic Minor Determination and/or** ☐ **Netting Determination**

Permit To Install **06-07059**

A. Source Description

This source, Shelly Materials Plant 15, is proposing to use natural gas, #2 oil and waste 'on-spec' oil as alternative fuels for the 327 TPH portable hot mix asphalt drum plant.

B. Facility Emissions and Attainment Status

The company is headquartered in Perry County in which this plant will be permitted due to its portable status. Perry County is attainment for particulate, sulfur dioxide, carbon monoxide, ozone, lead and oxides of nitrogen. The maximum potential to emit at 8760 hours per year for this emissions unit (P901) is 214.8 tons per year (tpy) for carbon monoxide (CO) and 329.4 tpy for VOCs. This would trigger PSD and Title V.

C. Source Emissions

Shelly Materials Plant 15, will limit the plant's annual production to 400,000 tons per rolling 12-month period. With the proposed production restriction, the total annual CO emissions will be limited to 30.0 tons per year and total annual VOC emissions will be limited to 46.0 tons per year. The PTI requires record keeping to ensure compliance with the production restriction.

D. Conclusion

The production restriction required in this permit is sufficient to provide federally enforceable limitations for ensuring that the applicable Title V thresholds will not be exceeded.

State of Ohio Environmental Protection Agency
Street Address: Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329
Mailing Address: Lazarus Gov. Center

RE: DRAFT PERMIT TO INSTALL **CERTIFIED MAIL**
PERRY COUNTY
Application No: 06-07059
DATE: 6/5/2003

Shelly Materials Plant 15
Larry Shively
8775 Blackbird Lane
Thornville, OH 43076

You are hereby notified that the Ohio Environmental Protection Agency has made a draft action recommending that the Director issue a Permit to Install for the air contaminant source(s) [emissions unit(s)] shown on the enclosed draft permit. This draft action is not an authorization to begin construction or modification of your emissions unit(s). The purpose of this draft is to solicit public comments on the proposed installation. A public notice concerning the draft permit will appear in the Ohio EPA Weekly Review and the newspaper in the county where the facility will be located. Public comments will be accepted by the field office within 30 days of the date of publication in the newspaper. Any comments you have on the draft permit should be directed to the appropriate field office within the comment period. A copy of your comments should also be mailed to Robert Hodanbosi, Division of Air Pollution Control, Ohio EPA, P.O. Box 1049, Columbus, OH, 43266-0149.

A Permit to Install may be issued in proposed of final form based on the draft action, any written public comments received within 30 days of the public notice, or record of a public meeting if one is held. You will be notified in writing of a scheduled public meeting. Upon issuance of a final Permit to Install a fee of **$1500** will be due. Please do not submit any payment now.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469. If you have any questions about this draft permit, please contact the field office where you submitted your application, or Mike Ahern, Field Operations & Permit Section at (614) 644-3631.

Very truly yours,
Michael W. Ahern
Michael W. Ahern, Supervisor
Field Operations and Permit Section
Division of Air Pollution Control

CC: USEPA **SEDO** **WV**

PERRY COUNTY

PUBLIC NOTICE
ISSUANCE OF DRAFT PERMIT TO INSTALL **06-07059** FOR AN AIR CONTAMINANT SOURCE FOR
SHELLY MATERIALS PLANT 15

On 6/5/2003 the Director of the Ohio Environmental Protection Agency issued a draft action of a Permit To Install an air contaminant source for **Shelly Materials Plant 15**, located at **1177 Hopetown Rd., Chillicothe**, Ohio.

Installation of the air contaminant source identified below may proceed upon final issuance of Permit To Install 06-07059:

Portable 200 TPH hot mix asphalt drum.

Comments concerning this draft action, or a request for a public meeting, must be sent in writing to the address identified below no later than thirty (30) days from the date this notice is published. All inquiries concerning this draft action may be directed to the contact identified below.

Kay Gilmer, Ohio EPA, Southeast District Office, 2195 Front Street, Logan, OH 43138 [(740)385-8501]

DRAFT PERMIT TO INSTALL 06-07059

Application Number:	06-07059
APS Premise Number:	0664000040
Permit Fee:	**To be entered upon final issuance**
Name of Facility:	Shelly Materials Plant 15
Person to Contact:	Larry Shively
Address:	8775 Blackbird Lane Thornville, OH 43076

Location of proposed air contaminant source(s) [emissions unit(s)]:
1177 Hopetown Rd.
Chillicothe, **Ohio**

Description of proposed emissions unit(s):
Portable 200 TPH hot mix asphalt drum.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

_____
Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.

b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any

information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions

and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

a. If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete

Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).

b. If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35, the source(s) identified in this Permit To Install is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the source(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

Pollutant	Tons Per Year
NOx	10.0
CO	30.0
SO2	8.0
PE	12.8
PM-10	10.0
fugitive PE	0.9
fugitive PM-10	0.9
VOC	46.0

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
F001 - Plant Unpaved Roadways and Parking Areas. (Portable with Shelly Plant #15)	OAC rule 3745-31-05 (A)(3)	Particulate emissions shall not exceed 2.7 ton per year (tpy). No visible particulate emissions (PE) except for 3 minutes during any 60-minute period. Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust.(see Sections A.2.b through A.2.g).
	OAC rule 3745-17-08 (B), (B)(2)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

2.a The unpaved roadways and parking areas that are covered by this permit and subject to the above-mentioned requirements are listed below:

unpaved roadways:	unpaved parking areas:
all	all

2.b The permittee shall employ best available control measures on all unpaved roadways and parking areas for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to the following methods to ensure compliance: the application of water at sufficient treatment frequencies to control fugitive dust; the addition of gravel to the unpaved surface as needed for surface improvement; and a vehicle speed reduction of 10 to 15 mph on unpaved surfaces. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

2.c The needed frequencies of implementation of the control measures shall be determined by the permittee's inspections pursuant to the monitoring section of this permit. Implementation of the control measures shall not be necessary for an unpaved roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Implementation of any control measure may be suspended if unsafe or hazardous driving conditions would be created by its use.

2.d Any unpaved roadway or parking area, which during the term of this permit is paved or takes the characteristics of a paved surface due to the application of certain types of dust suppressants, may be controlled using any combination of flushing, sweeping, and/or watering. Any unpaved roadway or parking area that takes the characteristics of a paved roadway or parking area due to the application of certain types of dust suppressants shall remain subject to the visible emission limitation for unpaved roadways and parking areas.

2.e The permittee shall promptly remove, in such a manner as to minimize or prevent resuspension, earth and/or other material from paved streets onto which such material has been deposited by trucking or earth moving equipment or erosion by water or other means.

2.f Open-bodied vehicles transporting materials likely to become airborne shall have such materials covered at all times if the control measure is necessary for the materials being transported.

2.g Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the requirements of OAC rule 3745-31-05.

B. Operational Restrictions

None

C. Monitoring and/or Record keeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform inspections of the unpaved roadways and parking areas in accordance with the following frequencies:

unpaved roadways	minimum inspection frequency
all	daily

unpaved parking areas	minimum inspection frequency
all	daily

2. The purpose of the inspections is to determine the need for implementing the above-mentioned control measures. The inspections shall be performed during representative, normal traffic conditions. No inspection shall be necessary for a roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above-identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.

3. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.

4. The permittee shall maintain records of the following information:

   a. The date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;

   b. The date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;

   c. The dates the control measures were implemented; and

   d. On a calendar quarter basis, the total number of days the control measures were implemented and the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measures.

The information required in 4.d. shall be updated on a calendar quarterly basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:

   a. Each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and

   b. Each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.

2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Emission Limitation:

   No visible particulate emissions except for 3 minutes during any 60-minute period

   Compliance Method:

   Compliance with the emission limitation for the unpaved roadways and parking areas identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources," as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(d) of OAC rule 3745-17-03.

2. Emission Limitation:

   Particulate emissions shall not exceed 2.68 tons per year.

   Compliance Method:

   The emission factor calculation for unpaved roadways and parking areas in AP-42 section 13.2.2 (Draft, 2001) shall be utilized to determine compliance. Initial compliance has been determined using inputs representing current conditions as follows:

   $E = [k(s/12)^a(W/3)^b[(365-p)/365)]$

   Where:

   E = size-specific emission factor (lb/VMT)
   s = silt content of road surface material (%) = 8.3 %
   W = mean vehicle weight (tons) = 40
   M = surface material moisture content (%) = 6.7%
   a = 0.8 (dimension less constant)
   b = 0.5 (dimension less constant)
   c = 0.4 (dimension less constant)
   k = 1.5 (dimension less constant) particle size multiplier

p = 140 no. of rain days per year

Therefore, E = 2.14 lbs particulate/VMT

Maximum travel = 50,000 VMT/year

(50,000 VMT/yr)(2.14 lbs/VMT)(1ton/2000 lbs) = 53.61 tons of particulate unconrolled/year

Assume 95% control for roadway watering
(53.61 tons/year) (.05) = 2.68 tons of particulate controlled/year

F. Miscellaneous Requirements

1. Pursuant to Ohio Administrative Code (OAC) rule 3745-31-03(A)(1)(p)(i), the permittee of a portable or mobile emissions unit may relocate within the State of Ohio without first obtaining a PTI providing the following criteria are met:

   a. the portable emissions unit is equipped with the best available control technology for such portable emissions unit;

   b. the portable emissions unit is operating pursuant to a currently effective permit to install, permit to operate or registration;

   c. the applicant has provided proper notice of intent to relocate the portable emissions unit to the Southeast District Office (SEDO) and the appropriate field office having jurisdiction over the new site within a minimum of thirty days prior to the scheduled relocation; and,

   d. in the SEDO's and the appropriate field office's judgement, the proposed site is acceptable under the rule 3745-15-07 of the Administrative Code.

2. In the alternative, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), the permittee of a portable or mobile emissions unit may relocate within the State of Ohio without first obtaining a PTI providing the following criteria of OAC rule 3745-31-05(F) are met:

   a. the portable emissions unit permittee possesses an Ohio EPA PTI, PTO or registration status;

   b. the portable emissions unit is equipped with best available technology;

   c. the portable emission unit owner has identified the proposed site to Ohio EPA;

d. Ohio EPA has determined that the portable emissions unit, at the proposed site, will have an acceptable environmental impact;

e. a public notice, consistent with Chapter 3745-47 of the Administrative Code, is published in the county where the proposed site is located;

f. the owner of the proposed site has provided the portable emissions unit owner with approval or equivalent declaration that it is acceptable to the site owner to move the portable emissions unit to the proposed site; and,

g. the portable emissions unit owner has provided the Ohio EPA with fifteen days written notice of the relocation.

Any site approvals issued by the Ohio EPA, pursuant to this section, shall be valid for no longer than three years and are subject to renewal.

3. In order for the SEDO and the appropriate field office having jurisdiction over the new site to determine compliance with all of the above criteria, the owner or operator of the portable or mobile emissions unit must file a "Notice of Intent to Relocate", within the specified time frame (30 or 15 days) prior to the relocation of the emissions unit with the SEDO (2195 Front Street, Logan, Ohio 43138) and the appropriate office having jurisdiction over the new site. Upon receipt of the notice, the SEDO and/or the appropriate field office having jurisdiction over the new site, will evaluate the request in accordance with the above criteria.

4. The permittee should be advised that when portable emission units are located at a stationary source or at a source comprised of portable emission units, potential emissions from the portable emission units are included in the facility potential to emit calculations for Title V and PSD applicability.

   The permittee shall include a potential to emit analysis of facility-wide emissions (including the portable sources) for the proposed relocation in the "Notice of Intent to Relocate".

5. If this portable facility is relocated to an area listed in OAC rule 3745-17-08 then the facility must meet the requirements of OAC rules 3745-17-08 and 3745-17-07(B).

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/Requirements	
F002 - Plant load-in and load-out of storage piles (Portable with Shelly Plant #15)	OAC rule 3745-31-05 (A)(3)	OAC rule 3745-17-08 (B)
	OAC rule 3745-17-08 (B)	
wind erosion from storage piles	OAC rule 3745-31-05 (A)(3)	

Applicable Emissions Limitations/Control Measures	
Particulate emissions (PE) shall not exceed 0.1 ton per year.	
No visible PE except for 1 minute during any 60-minute period.	
Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see Section A.2.b, A.2.c and A.2.f).	
The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).	
No visible PE except for 1 minute during any 60-minute period.	
Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see Sections A.2.d through A.2.f).	
The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).	

2. Additional Terms and Conditions

2.a The storage piles that are covered by this permit and subject to the above-mentioned requirements are listed below:

storage pile identification
all

2.b The permittee shall employ best available control measures on all load-in and load-out operations associated with the storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to minimizing the drop height of the front end loader bucket to the extent possible, in order to minimize or eliminate visible emissions of fugitive dust from the loading area. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

2.c The above-mentioned control measure(s) shall be employed for each load-in and load-out operation of each storage pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) are necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measure(s) shall continue during any such operation until further observation confirms that use of the measure(s) is unnecessary.

2.d The permittee shall employ best available control measures for wind erosion from the surfaces of all storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements.

2.e Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the requirements of OAC rules 3745-17-08 and 3745-31-05.

B. Operational Restrictions

None.

C. Monitoring and/or Recordkeeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform inspections of each load-in operation at each storage pile in accordance with the following frequencies:

storage pile identification	minimum load-in inspection frequency
all	daily

2. Except as otherwise provided in this section, the permittee shall perform inspections of each load-out operation at each storage pile in accordance with the following frequencies:

storage pile identification	minimum load-out inspection frequency
all	daily

3. Except as otherwise provided in this section, the permittee shall perform inspections of the wind erosion from pile surfaces associated with each storage pile in accordance with the following frequencies:

storage pile identification	minimum wind erosion inspection frequency
all	daily

4. No inspection shall be necessary for wind erosion from the surface of a storage pile when the pile is covered with snow and/or ice and for any storage pile activity if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.

5. The purpose of the inspections is to determine the need for implementing BAT control measures for load-in and load-out of a storage pile, and wind erosion from the surface of a storage pile. The inspections shall be performed during representative, normal storage pile operating conditions.

6. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.

7. The permittee shall maintain records of the following information:

   a. The date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;

   b. The date of each inspection where it was determined by the permittee that it was necessary

to implement control measures;

c. The dates the control measures were implemented; and

d. On a calendar quarter basis, the total number of days control measures were implemented and, for wind erosion from pile surfaces, the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measure(s).

The information required in 7.d. shall be kept separately for (i) the load-in operations, (ii) the load-out operations, and (iii) the pile surfaces (wind erosion), and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:

   a. Each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and

   b. Each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.

2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Emission Limitation:

   No visible particulate emissions except for 1 minute during any 60-minute period.

   Compliance Method:

   Compliance with the visible emission limitations for the storage piles identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

2. Emission Limitation:

   Particulate emissions shall not exceed 0.05 ton per year.

   Compliance Method:

   The emission factor calculation for storage piles in AP-42 section 13.2.4 (January, 1995) shall be utilized to determine compliance. Initial compliance has been determined using inputs representing current conditions as follows:

   $E = k\ (0.0032)[(U/5)^{1.3}/(M/2)^{1.4}$

E = emission factor expressed in pounds (lbs) / ton
k (PM) = particle size multiplier (dimension less) = 0.74
k (PM 10) = particle size multiplier (dimension less) = 0.35

U = mean wind speed expressed in miles per hour (MPH) = 9.9
M = material moisture content (%) = 4
A Material ton per year value of 400,000

F. Miscellaneous Requirements

1. Pursuant to Ohio Administrative Code (OAC) rule 3745-31-03(A)(1)(p)(i), the permittee of a portable or mobile emissions unit may relocate within the State of Ohio without first obtaining a PTI providing the following criteria are met:

   a. the portable emissions unit is equipped with the best available control technology for such portable emissions unit;

   b. the portable emissions unit is operating pursuant to a currently effective permit to install, permit to operate or registration;

   c. the applicant has provided proper notice of intent to relocate the portable emissions unit to the Southeast District Office (SEDO) and the appropriate field office having jurisdiction over the new site within a minimum of thirty days prior to the scheduled relocation; and,

   d. in the SEDO's and the appropriate field office's judgement, the proposed site is acceptable under the rule 3745-15-07 of the Administrative Code.

2. In the alternative, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), the permittee of a portable or mobile emissions unit may relocate within the State of Ohio without first obtaining a PTI providing the following criteria of OAC rule 3745-31-05(F) are met:

   a. the portable emissions unit permittee possesses an Ohio EPA PTI, PTO or registration status;

   b. the portable emissions unit is equipped with best available technology;

   c. the portable emission unit owner has identified the proposed site to Ohio EPA;

   d. Ohio EPA has determined that the portable emissions unit, at the proposed site, will have an acceptable environmental impact;

   e. a public notice, consistent with Chapter 3745-47 of the Administrative Code, is published in the county where the proposed site is located;

f. the owner of the proposed site has provided the portable emissions unit owner with approval or equivalent declaration that it is acceptable to the site owner to move the portable emissions unit to the proposed site; and,

g. the portable emissions unit owner has provided the Ohio EPA with fifteen days written notice of the relocation.

Any site approvals issued by the Ohio EPA, pursuant to this section, shall be valid for no longer than three years and are subject to renewal.

3. In order for the SEDO and the appropriate field office having jurisdiction over the new site to determine compliance with all of the above criteria, the owner or operator of the portable or mobile emissions unit must file a "Notice of Intent to Relocate", within the specified time frame (30 or 15 days) prior to the relocation of the emissions unit with the SEDO (2195 Front Street, Logan, Ohio 43138) and the appropriate office having jurisdiction over the new site. Upon receipt of the notice, the SEDO and/or the appropriate field office having jurisdiction over the new site, will evaluate the request in accordance with the above criteria.

4. The permittee should be advised that when portable emission units are located at a stationary source or at a source comprised of portable emission units, potential emissions from the portable emission units are included in the facility potential to emit calculations for Title V and PSD applicability.

   The permittee shall include a potential to emit analysis of facility-wide emissions (including the portable sources) for the proposed relocation in the "Notice of Intent to Relocate".

5. If this portable facility is relocated to an area listed in OAC rule 3745-17-08 then the facility must meet the requirements of OAC rules 3745-17-08 and 3745-17-07(B).

Shelly
PTI A Emissions Unit ID: **P901**
Issued: To be entered upon final issuance

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment		
P901 - 327 TPH Drum Mix Asphalt Plant Terms in this permit supersede those identified in PTI # 06- 06022 issued 12/22/1999.		
		aggregate storage bins, cold aggregate elevator

Applicable Rules/Requirements		Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(A)(3)	40 CFR Part 60, Subpart I	Hourly emissions of Carbon Monoxide (CO) from the stack shall not exceed 49.1 pounds. Hourly emissions of Nitrogen Oxides (NOx) from the stack shall not exceed 16.4 pounds.
	OAC rule 3745-23-06(B) OAC rule 3745-17-07(A)	Hourly emissions of Sulfur Dioxide (SO_2) from the stack shall not exceed 13.1 pounds. Hourly emissions of Volatile Organic Compounds (VOC) from the stack shall not exceed 75.2 pounds.
	OAC rule 3745-17-11(B)	See Section A.2.a for emission control measures.
	OAC rule 3745-18-06(E)	The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart I, OAC rule 3745-23-06(B) and OAC rule 3745-31-05(D).
OAC rule 3745-31-05(D)	OAC rule 3745-31-05(A)(3)	Annual emissions shall not exceed the following based on a rolling 12-month summation: 10.0 TPY Particulate emissions (PE) from the stack 10.0 TPY PM-10 from the stack 0.9 TPY fugitive PE 0.9 TPY fugitive PM-10 30.0 TPY CO 8.0 TPY SO_2

10.0 TPY NOx
46.0 TPY VOC

PE from the stack shall not exceed 0.04 grain/dscf.

The emissions unit shall not discharge into the atmosphere any stack gases which exhibit 20 percent opacity or greater.

See Section A.2.b.

The emissions limitation specified by this rule is less stringent than the emission limitation established pursuant to 40 CFR Part 60 Subpart I.

The emissions limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

The emissions limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

Visible PE of fugitive dust shall be less than or equal to 10% opacity, as a 3-minute average.

Emissions of fugitive PE shall not exceed 0.9 pounds per hour.

Emissions of fugitive PM-10 shall not exceed 0.9 pounds per hour.

The drop height of the front end loader bucket shall be minimized to the extent possible in order to minimize or eliminate visible emissions of fugitive dust from the elevator loading area.

The aggregate loaded into the storage bins shall have a moisture content sufficient to eliminate the visible emissions of fugitive dust from the elevator and the transfer point to the dryer.

2. Additional Terms and Conditions

2.a. The fabric filter shall be used at all times when the emissions unit is in operation.

2.b. The permittee has satisfied the "latest available control techniques and operating practices" required pursuant to OAC rule 3745-23-06, by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05(A)(3).

2.c. The application and enforcement of the provisions of the New Source Performance Standards (NSPS), as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60, are delegated to the Ohio Environmental Protection Agency. The requirements of 40 CFR Part 60 are also federally enforceable.

B. Operational Restrictions

1. To ensure the baghouse is operated according to the manufacturer's specifications and to maintain compliance with the allowable particulate emission rate, the pressure drop across the baghouse shall be maintained within the range of 2.0 to 8.0 inches of water while the emissions unit is in operation.

2. The maximum annual asphalt production rate for emissions unit P901 shall not exceed 400,000 tons based upon a rolling, 12-month summation of the production rates. To ensure enforce ability during the first 12 calendar months of operation following the startup of the modified emissions unit P901, the permittee shall not exceed the production levels specified in the following table:

Month(s)	Maximum Allowable Cumulative Production (Tons)
1	200,000
1-2	300,000
1-3	400,000
1-4	400,000
1-5	400,000
1-6	400,000
1-7	400,000
1-8	400,000
1-9	400,000
1-10	400,000
1-11	400,000

1-12	400,000

After the first 12 calendar months of operation following the startup of the modified emissions unit P901, compliance with the annual production rate limitation shall be based upon a rolling, 12-month summation of the production rates.

3. All recycled, used oil burned in emissions unit P901 shall meet the following specifications:

Contaminant/Property	Allowable Specifications
arsenic	5 ppm, maximum
cadmium	2 ppm, maximum
chromium	10 ppm, maximum
lead	100 ppm, maximum
PCB's	50 ppm, maximum*
total halogens	4000 ppm maximum**
mercury	1 ppm, maximum
flash point	100°F, minimum
heat content	135,000 Btu/gallon, minimum

* If the permittee is burning used oil with any quantifiable level ≥2 ppm < 50 ppm of PCB's, then the permittee is subject to any applicable requirements found under 40 CFR part 279, subparts G and H and 40 CFR 761.20 (e).

** Used oil containing more than 1000 ppm total halogens is presumed to be a hazardous waste under the rebuttable presumption provided under 40 CFR 279.10 (b)(1)*(ii)* and OAC rule 3745-279-10 (B)(1)(b). Therefore, the permittee may receive and burn used oil exceeding 1000 ppm of total halogens (but less than 4000 ppm, maximum) only if the used oil burner can demonstrate the used oil does not contain any hazardous waste pursuant to OAC rule 3745-279-63**.**

4. The burning of hazardous waste is prohibited without first complying with all applicable state and federal hazardous waste and air regulations and permits.

5. The permittee shall only burn low sulfur fuels, containing less than 0.5% sulfur by weight, in this emissions unit.

6. The permittee may substitute recycled asphalt pavement (RAP) aggregates in the raw material feed mix in amounts not to exceed 50% of all aggregate materials introduced, based on a monthly average of all aggregate material.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a once per shift basis.

2. The permittee shall maintain monthly records of the following information for emissions unit P901:

   a. The asphalt production, in tons.

   b. For the first 12 calendar months following the startup of the modified emissions unit P901, the cumulative asphalt production calculated by adding the current month's asphalt production to the asphalt production for each calendar month since the startup of the modified emissions unit P901.

   c. Beginning after the first 12 calendar months following the startup of the modified emissions unit P901, the rolling, 12-month summation of asphalt production calculated by adding the current month's asphalt production to the asphalt production for the preceding eleven calendar months.

   d. The total amount of aggregate used in the raw material feed mix.

   e. The amount of RAP used in the raw material feed mix.

   f. The average percentage of RAP used (e. divided by d. multiplied by 100).

3. For each shipment of oil received for burning in this emissions unit, the permittee shall maintain records of the total quantity of oil received and the permittee's or oil supplier's analyses for the following:

   a. The date of shipment or delivery.
   b. The quantity of oil received.
   c. The heat content of the used oil, in BTU/gallon.
   d. The flash point of the used oil in degrees F.
   e. The arsenic content, in ppm.
   f. The cadmium content, in ppm.
   g. The chromium content, in ppm.

h. The lead content, in ppm.
i. The PCB content, in ppm.
j. The total halogen content, in ppm.
k. The mercury content, in ppm.
l. The sulfur content, in ppm

A shipment may be comprised of multiple tank truck loads from the same supplier's batch, or may be represented by single or multiple pipeline deliveries from the same supplier's batch, and the quality of the oil for those loads or pipeline deliveries may be represented by a single batch analysis from the supplier.

The permittee shall perform or require the supplier to perform the analyses for sulfur content and heat content in accordance with 40 CFR Part 60, Appendix A, Method 19, or the appropriate ASTM methods (such as, ASTM methods D240 and D4294), or equivalent methods as approved by the Director.

The permittee shall maintain records of the oil burned in this emissions unit in accordance with either Alternative 1 or Alternative 2 described below.

a. Alternative 1:

For each shipment of oil received for burning in this emissions unit, the permittee shall collect or require the oil supplier to collect a representative grab sample of oil and maintain records of the total quantity of oil received, the permittee's or oil supplier's analyses for items a - l above. A shipment may be comprised of multiple tank truck loads from the same supplier's batch, and the quality of the oil for those loads may be represented by a single batch analysis from the supplier.

b. Alternative 2:

The permittee shall collect a representative grab sample of oil that is burned in this emissions unit for each day when the emissions unit is in operation. If additional fuel oil is added to the tank serving this emissions unit on a day when the emissions unit is in operation, the permittee shall collect a sufficient number of grab samples to develop a composite sample representative of the fuel oil burned in this emissions unit. A representative grab sample of oil does not need to be collected on days when this emissions unit is only operated for the purpose of "test-firing." The permittee shall maintain records of the total quantity of oil burned each day, except for the purpose of test-firing, the permittee's analyses for sulfur content and heat content, and the calculated sulfur dioxide emission rate (in lbs/mmBtu). (The sulfur dioxide emission rate shall be calculated in accordance with the formula specified in OAC rule 3745-18-04(F).)

4. The permittee shall maintain documentation on the sulfur content of all fuels received.

5. The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible PE from the stack and any visible fugitive PE from the aggregate storage bins and cold aggregate elevator associated with this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:

   a. The color of the emissions;
   b. Whether the emissions are representative of normal operations;
   c. If the emissions are not representative of normal operations, the cause of the abnormal emissions;
   d. The total duration of any visible emission incident; and
   e. Any corrective actions taken to eliminate the visible emissions.

6. The permit to install for this emissions unit (P901) was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

   Pollutant: Heptane

   TLV (mg/m3): 1639.26

   Maximum Hourly Emission Rate (lbs/hr): 3.07

   Predicted 1-Hour Maximum Ground-Level
   Concentration (ug/m3): 932

   MAGLC (ug/m3): 39030

   Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will

not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. Changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

b. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. Physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

a. A description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. Documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. Where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify the following:

a. All periods of time during which the pressure drop across the baghouse did not comply

with the allowable range specified in Section B.1.

b. All exceedances of the rolling, 12-month production rate limitation and, for the first 12 calendar months of operation following the issuance of this permit, all exceedances of the maximum allowable cumulative production levels.

c. All exceedances of sulfur content fuel restriction specified in Section B.5.

These quarterly deviation (excursion) reports shall due by the dates specified in Part I - General Terms and Conditions of this permit under section (A)(2).

2. The permittee shall notify the USEPA and the Ohio EPA if any of the used oil exceeds the used oil specifications found in OAC rule 3745-279-11 and the applicable portions of 40 CFR part 761, and shall also notify Ohio EPA if any used oil exceeds the mercury limitation and falls below the heat content limitation listed in Section B.3 within thirty days after the exceedance occurs. If the permittee is burning used oil which exceeds the specifications found in OAC rule 3745-279-11 and the applicable portions 40 CFR part 761, the permittee is subject to that rule and must comply with all applicable provisions of that rule(s).

3. The permittee shall submit deviation (excursion) reports which identify any exceedance of the 50 percent RAP content limitation specified in Section B.6. The notification shall be sent to the Ohio EPA, Southeast District Office within 30 days after the exceedance occurs.

4. The permittee shall submit semiannual written reports that include the following:

a. An identification of all days during which any visible PE or fugitive PE were observed from the stack and the aggregate storage bins and cold aggregate elevator associated with this emissions unit.

b. A description of any corrective actions taken to eliminate the visible particulate emissions.

These reports shall be submitted to the Ohio EPA, Southeast District Office by January 31 and July 31 of each year and shall cover the previous 6-month period.

5. Pursuant to the NSPS, the source owner/operator is hereby advised of the requirement to report the following at the appropriate times:

a. Construction date (no later than 30 days after such date);

b. Anticipated start-up date (not more than 60 days or less than 30 days prior to such date);

c. Actual start-up date (within 15 days after such date); and

d. Date of performance testing (if required, at least 30 days prior to testing).

Reports are to be sent to:

Ohio Environmental Protection Agency
DAPC - Permit Management Unit
P. O. Box 163669
Columbus, Ohio 43216-3669

and

Southeast District Office of the Ohio EPA
Division of Air Pollution Control
2195 Front Street
Logan, Ohio 43138

E. Testing Requirements

1. Compliance with the particulate emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

a. Emission Limitation:

PE from the stack shall not exceed 0.04 grain/dscf

Applicable Emission Limitation

Compliance shall be determined in accordance with Test Methods 1-5 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources").

b. Emission Limitation:

Annual emissions shall not exceed 10.0 TPY of PE from the stack as a rolling 12-month summation.

Applicable Compliance Method:

Compliance shall be determined based upon the following equation:

E = EF * AAPR * 0.0005 ton/lb = TPY of particulates

Where

EF is the PE emission factor in lb/ton, and is based on the most recent stack test as required in Section E. 7, and
AAPR, is the actual asphalt production rate, in tons for each 12-month period as monitored and recorded in Section C. 2. *The emissions factor used to calculate the PE mass emission limitation is 0.05 lb PE/ton asphalt produced. This emissions factor is based on best engineering judgement and was developed using emissions testing data from similar sources.

c. Emission Limitation:

Annual emissions shall not exceed 10.0 TPY of PM-10 from the stack as a rolling 12-month summation.

Applicable Compliance Method:

Compliance with the annual emissions limitation shall be assumed as long as compliance is maintained with the rolling 12-month emissions limitation for PE.

d. Emission Limitation:

The emissions unit shall not discharge into the atmosphere any stack gases which exhibit 20 percent opacity or greater.

Applicable Compliance Method:

Compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources").

e. Emission Limitation:

Visible PE of fugitive dust shall be less than or equal to 10% opacity, as a 3-minute average.

Applicable Compliance Method:

Compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources").

f. Emissions Limitation:

Fugitive particulate emissions (PE) shall not exceed 0.9 ton per rolling 12-month period.

Applicable Compliance Method:

Compliance with the annual emissions limitation shall be assumed based upon the following worst case calculation, where total fugitive emissions equal the summation of the fugitives from the aggregate storage bins, cold aggregate elevator, and associated operations:

((200,000 tons of aggregate/year X 0.0069 lb PE/ton of aggregate) + (200,000 tons of sand/year X 0.0021 lb PE/ton of sand)) X (0.0005 ton/lb) = 0.9 ton

The emissions factors in the above equation are derived from AP-42, Fifth Edition, Table 11.12-2(10/01).

g. Emissions Limitation:

Fugitive PM-10 shall not exceed 0.9 ton per rolling 12-month period.

Applicable Compliance Method:

Compliance with the annual emissions limitation shall be assumed as long as compliance is maintained with the rolling 12-month emissions limitation for fugitive PE.

h. Emission Limitation:

Emissions of fugitive PE shall not exceed 0.9 pounds per hour.

Applicable Compliance Method:

Compliance with the hourly fugitive PE emissions limitation shall be assumed as long as compliance is maintained with the rolling 12-month asphalt production operational restriction. Calculation of this emissions limitation is based on the annual fugitive PE emission limitation and an operating schedule of 2000 hours per year.

i. Emission Limitation:

Emissions of fugitive PM-10 shall not exceed 0.9 pounds per hour.

Applicable Compliance Method:

Compliance with this emissions limitation shall be assumed as long as compliance is maintained with the hourly fugitive PE emission limitation.

2. Compliance with the CO emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

a. Emission Limitation:

Hourly emissions of CO from the stack shall not exceed 49.1 pounds.

Applicable Compliance Method:

Compliance shall be determined in accordance with Test Methods 1-4 and 10 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"). *The emissions factor used to calculate the CO mass emission limitation is 0.15 lb CO/ton asphalt produced. This emissions factor is based on best engineering judgement and was developed using emissions testing data from similar sources.

b. Emission Limitation:

Annual emissions shall not exceed 30.0 TPY for CO from the stack as a rolling 12-month

average

Applicable Compliance Method:

Compliance shall be determined based upon the following equation:

E = EF * AAPR * 0.0005 ton/lb = TPY of CO

Where

EF is the CO emission factor in lb/ton, and is based on the most recent stack test as required in Section E. 7, and
AAPR, is the actual asphalt production rate, in tons for each 12-month period as monitored and recorded in Section C. 2.

3. Compliance with the SO_2 emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

a. Emission Limitation:

Hourly emissions of SO_2 from the stack shall not exceed 13.1 pounds

Applicable Compliance Method:

Compliance shall be determined in accordance with Test Methods 1-4 and 6 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"). *The emissions factor used to calculate the SO_2 mass emission limitation is 0.04 lb SO_2/ton asphalt produced. This emissions factor is based on best engineering judgement and was developed using emissions testing data from similar sources.

b. Emission Limitation:

Annual emissions shall not exceed 8.0 TPY of SO_2 from the stack as a rolling 12-month average.

Applicable Compliance Method:

Compliance shall be determined based upon the following equation:

E = EF * AAPR * 0.0005 ton/lb = TPY of SO_2

Where

EF is the SO_2 emission factor in lb/ton, and is based on the most recent stack test as required in Section E. 7, and
AAPR, is the actual asphalt production rate, in tons for each 12-month period as monitored and recorded in Section C. 2.

4. Compliance with the NOx emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

   a. Emission Limitation:

   Hourly emissions of NOx from the stack shall not exceed 16.4 pounds.

   Applicable Compliance Method:

   Compliance shall be determined in accordance with Test Methods 1-4 and 7 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"). *The emissions factor used to calculate the NOx mass emission limitation is 0.05 lb NOx/ton asphalt produced. This emissions factor is based on best engineering judgement and was developed using emissions testing data from similar sources.

   b. Emission Limitation:

   Annual emissions shall not exceed 10.0 TPY of NOx from the stack as a rolling 12-month average.

   Applicable Compliance Method:

   Compliance shall be determined based upon the following equation:

   E = EF * AAPR * 0.0005 ton/lb = TPY of NOx

   Where

   EF is the NOx emission factor in lb/ton, and is based on the most recent stack test as required in Section E. 7, and
   AAPR, is the actual asphalt production rate, in tons for each 12-month period as monitored and recorded in Section C. 2.

5. Compliance with the VOC emission limitation(s) in Section A.I. of these terms and conditions

shall be determined in accordance with the following method(s):

a. Emission Limitation:

Hourly emissions of VOC from the stack shall not exceed 75.2 pounds.

Applicable Compliance Method:

Compliance shall be determined in accordance with Test Methods 1 - 4 and 25 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"). *The emissions factor used to calculate the VOC mass emission limitation is 0.23 lb VOC/ton asphalt produced. This emissions factor is based on best engineering judgement and was developed using emissions testing data from similar sources.

b. Emission Limitation:

Annual emissions shall not exceed 46.0 TPY of VOC from the stack as a rolling 12-month average.

Applicable Compliance Method:

Compliance shall be determined based upon the following equation:

E = EF * AAPR * 0.0005 ton/lb = TPY of VOC's

Where

EF is the VOC emission factor in lb/ton, and is based on the most recent stack test as required in Section E. 7, and
AAPR, is the actual asphalt production rate, in tons for each 12-month period as monitored and recorded in Section C. 2.

6. Compliance with the Operational Restriction(s) in Section B. of these terms and conditions shall be determined in accordance with the following method(s):

a. Operational Limitation:

Pressure drop across the baghouse shall be maintained within the range of 2.0 to 8.0 inches of water while the emissions unit is in operation

Applicable Compliance Method:

Compliance shall be demonstrated by the record keeping requirements in Section C.1.

b. Operational Limitation:

The maximum annual asphalt production rate for emissions unit P901 shall not exceed 400,000 tons per year based upon a rolling, 12-month summation of the production rates.

Applicable Compliance Method:

Compliance shall be demonstrated by the record keeping requirements in Section C.2.

c. Operational Limitation:

Used oil specifications as specified in Section B.3.

Applicable Compliance Method:

Compliance shall be demonstrated by the record keeping requirements in Section C.3.

d. Operational Limitation:

Sulfur content of fuel restricted to less than 0.5%, by weight

Applicable Compliance Method:

Compliance shall be demonstrated by the record keeping requirements in Section C.4.

e. Operational Limitation:

Use of recycled asphalt pavement (RAP) aggregates in the raw material feed mix in amounts not to exceed 50% of all aggregate materials introduced, based on a monthly average of all aggregate material.

Applicable Compliance Method:

Compliance shall be demonstrated by the record keeping requirements in Section C.2.

7. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:

   a. The emission testing shall be conducted within 60 days after startup of the modified emissions unit.

   b. The emission testing shall be conducted to demonstrate compliance with the allowable mass emission rate(s) for PE ,CO, NO_X, SO_2, and VOC.

   c. The following test method(s) shall be employed to demonstrate compliance with the allowable mass emission rate(s): Methods 1-5 for PE, Method 25 for VOC, Method 1-4 and 10 for CO, Method 1-4 and 6 for SO2, and Method 1-4 and 7 for NOX.

   d. The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity using worst case fuel and per cent of RAP listed in air permit, unless otherwise specified or approved by the Ohio EPA Southeast District Office.

   Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA Southeast District Office. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA Southeast District Office's refusal to accept the results of the emission test(s).

   Personnel from the Ohio EPA Southeast District Office shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

   A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA Southeast District Office within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA Southeast District Office.

F. Miscellaneous Requirements

1. Pursuant to Ohio Administrative Code (OAC) rule 3745-31-03(A)(1)(p)(i), the permittee of a portable or mobile emissions unit may relocate within the State of Ohio without first obtaining a PTI providing the following criteria are met:

a. The portable emissions unit is equipped with the best available control technology for such portable emissions unit;

b. The portable emissions unit is operating pursuant to a currently effective permit to install, permit to operate or registration;

c. The applicant has provided proper notice of intent to relocate the portable emissions unit to the Southeast District Office (SEDO) and the appropriate field office having jurisdiction over the new site within a minimum of thirty days prior to the scheduled relocation; and,

d. In the SEDO's and the appropriate field office's judgement, the proposed site is acceptable under the rule 3745-15-07 of the Administrative Code.

2. In the alternative, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), the permittee of a portable or mobile emissions unit may relocate within the State of Ohio without first obtaining a PTI providing the following criteria of OAC rule 3745-31-05(F) are met:

a. The portable emissions unit permittee possesses an Ohio EPA PTI, PTO or registration status;

b. The portable emissions unit is equipped with best available technology;

c. The portable emission unit owner has identified the proposed site to Ohio EPA;

d. Ohio EPA has determined that the portable emissions unit, at the proposed site, will have an acceptable environmental impact;

e. A public notice, consistent with Chapter 3745-47 of the Administrative Code, is published in the county where the proposed site is located;

f. The owner of the proposed site has provided the portable emissions unit owner with approval or equivalent declaration that it is acceptable to the site owner to move the portable emissions unit to the proposed site; and,

g. The portable emissions unit owner has provided the Ohio EPA with fifteen days written notice of the relocation.

Any site approvals issued by the Ohio EPA, pursuant to this section, shall be valid for no longer than three years and are subject to renewal.

3. In order for the SEDO and the appropriate field office having jurisdiction over the new site to determine compliance with all of the above criteria, the owner or operator of the portable or mobile emissions unit must file a "Notice of Intent to Relocate", within the specified time frame (30 or 15 days) prior to the relocation of the emissions unit with the SEDO (2195 Front Street, Logan, Ohio 43138) and the appropriate office having jurisdiction over the new site. Upon receipt of the notice, the SEDO and/or the appropriate field office having jurisdiction over the new site, will evaluate the request in accordance with the above criteria.

4. The permittee should be advised that when portable emission units are located at a stationary source or at a source comprised of portable emission units, potential emissions from the portable emission units are included in the facility potential to emit calculations for Title V and PSD applicability.

   The permittee shall include a potential to emit analysis of facility-wide emissions (including the portable sources) for the proposed relocation in the "Notice of Intent to Relocate".

5. If this portable facility is relocated to an area listed in OAC rule 3745-17-08 then the facility must meet the requirements of OAC rules 3745-17-08 and 3745-17-07(B).

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
T003 - 20,000 gallon used oil storage tank	OAC rule 3745-31-05(A)(3)	Volatile Organic Compound (VOC) emissions shall not exceed 0.008 ton per year. See Part II.A.2.b below. The requirements of this rule also include compliance with the requirements of 40 CFR 60 Subpart Kb.
	40 CFR Part 60 Subpart Kb	See Part II.C.1 and II.D.1 below.
	OAC rule 3745-21-09(L)	Exempt see section A.2.a below.

2. Additional Terms and Conditions

2.a In accordance with OAC rule 3745-21-09(L)(2), this storage tank is exempt from the requirements of OAC rule 3745-21-09(L)(1) because the tank has a capacity of less than 40,000 gallons.

2.b This emissions unit shall employ submerged fill.

B. Operational Restrictions

1. The permittee shall not place, store, or hold in this fixed roof tank any petroleum liquid which, as stored, has a true vapor pressure greater than 1.52 pounds per square inch absolute, unless such tank is designed or equipped in accordance with the requirements of paragraph(L)(1) of OAC rule 3745-21-09.

C. Monitoring and/or Recordkeeping Requirements

1. In accordance with 40 CFR Part 60.116b(a) and 40 CFR Part 60.116b(b), the permittee shall keep readily accessible records for the life of the tank that document the dimensions and capacity of the tank.

2. The permittee shall maintain readily accessible records of the following information:

   a. the types of petroleum liquids stored in the tank; and

   b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.

D. Reporting Requirements

1. If the permittee places, stores, or holds in the fixed roof tank any petroleum liquid with a true vapor pressure which is greater than 1.52 pounds per square inch absolute, and such tank does not comply with the requirements of paragraph (L)(1) of OAC rule 3745-21-09, the permittee shall notify the Ohio EPA, Southeast District Office within 30 days of becoming aware of the occurrence.

E. Testing Requirements

1. Compliance with the emission limitations in section A.1 of these terms and conditions shall be determined in accordance with the following methods:

   Emission Limitation:

   VOC emissions shall not exceed 0.008 ton per year.

   Applicable Compliance Method:

   VOC emissions due to standing and withdrawal losses from the storage tanks shall be determined using the most recent version of USEPA's "Tanks" program.

F. Miscellaneous Requirements

1. The following source is subject to the applicable provision of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60.

Source Number	Source Description	NSPS Regulation (Subpart)
T003	20,000 gallon fixed roof tank	Subpart Kb

The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

Pursuant to NSPS, the source owner/operator is hereby advised of the requirement to report the following at the appropriate times:

a. construction date (no later than 30 days after such date);
b. anticipated start-up date (not more than 60 days or less than 30 days prior to such date);
c. actual start-up date (within 15 days after such date); and
d. date of performance testing (if required, at least 30 days prior to testing).

Reports are to be sent to:

Ohio Environmental Protection Agency
DAPC- Air Quality Modeling and Planning
P.O. Box 1049
Columbus, OH 43216-1049

and

Southeast District Office
Division of Air Pollution Control
2195 Front Street
Logan, Ohio 43138